Rancho Seco

Final Status Survey Summary Report

September 8, 2008

Turbine Building Exterior Walls, (+) 0' El. to (+) 40' El.

Survey Unit F8260302

Prepared By:	CB. PRODUCEDOR	Date:_	91812000	
	FSS Engineer			
Reviewed By:	24 Deelen	Date:_	11/20/08	
	Lead FSS Enginee	er	` '	
Approved By:	5.718	Date:_	2-27-0	9
Dism	antlement Superintenden	t. Radiolo	ogical	

FINAL STATUS SURVEY SUMMARY REPORT

Survey Unit:

F8260302, Turbine Building Exterior Walls, (+) 0' El. to (+) 40' El.

Survey Unit Description:

Operating History: The reinforced concrete and steel structure contained the turbinegenerator and supporting systems. The building contained five main elevations. Residual radioactive material was known to be present on all levels of the interior of the building. Operating records and the HSA document several events with the potential for a release of radioactivity inside this structure.

Site Characterization: Direct measurements were made of each of the interior elevation surfaces as well as the exterior surfaces of the structure. These measurements confirmed the presence of plant-derived radionuclides. Direct measurements in the condenser pit elevation showed a mean gross activity level of 3,077 dpm/100 cm² and a maximum value of 24,900 dpm/100 cm². Direct measurements on the grade elevation showed a mean gross activity level of 2,035 dpm/100 cm² and a maximum value of 6,980 dpm/100 cm². Direct measurements on the mezzanine elevation showed a mean gross activity level of 1,566 dpm/100 cm² and a maximum value of 2,626 dpm/100 cm². Direct measurements on the +40° elevation showed a mean gross activity level of 2,843 dpm/100 cm² and a maximum value of 3,615 dpm/100 cm². Direct measurements on the building exterior showed a mean gross activity level of 1,984 dpm/100 cm² and a maximum value of 10,312 dpm/100 cm². Based on the classification procedure (DSIP-0020) and levels of gross activity reported, the interior of the turbine building was determined to be Class 1, 2, & 3 areas and the exterior was a Class 3.

HSA Events: HSA Report pg. 63.

Survey Unit Design Information:

The Survey Unit Design Parameters are presented in Table 1 below. The survey unit and measurement locations are depicted on the maps in Attachment 1. Direct measurement locations were randomly determined and 903 m² were scanned for approximately 57% coverage. Samples of removable contamination were collected at each direct measurement location. The instrumentation used for the survey along with the MDC values are listed in Tables 2-1 and 2-2 in Attachment 2.

Table 1. Survey Unit Design Parameters

Survey Design	Value	Comment
Parameter		
Survey Area:	F826	Turbine Building Exterior
		Walls, (+) 0' El. to (+) 40'
		El.
Survey Unit:	0302	Structure Surface
Class:	3	LTP Table 5-4
SU Area (m²):	1,596	
Evaluator:	D. Anderson	
DCGL (dpm/100 cm ²):	43,000	Gross Activity DCGL
Area Factor:	N/A	Class 3
Design DCGLemc	N/A	Class 3
(dpm/100 cm ²):		
LBGR (dpm/100 cm ²):	37,831	Adjusted
Design Sigma (dpm/100 cm ²):	1,723	
Type I Error:	0.05	•
Type II Error:	0.05	
Predominant Nuclide:	Cs-137	
Sample Area (m ²):	N/A	Class 3
Scan Area (m ²):	903	
Scan Coverage (%):	57%	Class 3
$Z_{1-\alpha}$:	1.645	
\mathbf{Z}_{1-eta} :	1.645	
Sign P:	0.99865	_
Calculated Relative Shift:	3	
Relative Shift Used:	3	Uses 3.0 if Relative Shift is
		>3
N-Value:	11	\#\#\#\
Design N-Value + 20%:	14	NUREG-1575 Table 5-5
Design Min Samples N:	14	Class 3
Grid Spacing L:	N/A	Class 3

Survey Results:

A total of 14 direct measurements were made in F8260302. The results including mean, median, standard deviation and range are shown in Table 2. All direct measurements were less than the DCGL. None of the scan measurements indicated areas of elevated activity. The gamma activity ranged from < 974 dpm/100 cm² Co-60 and < 953 dpm/100 cm² to 971 dpm/100 cm² Cs-137. Samples for removable surface activity were all less than 10% of the DCGL as shown in Table 3. Removable surface activity samples were counted for alpha activity and none was detected at the MDC shown in Table 2-1 of Attachment 2.

Table 2. Direct Measurement Results

Measurement ID	Gross Activity (dpm/100 cm²)
F8260302-M0001BD	1,015
F8260302-M0002BD	640
F8260302-M0003BD	655
F8260302-M0004BD	809
F8260302-M0005BD	621
F8260302-M0006BD	671
F8260302-M0007BD	. 769
F8260302-M0008BD	1,138
F8260302-M0009BD	1,504
F8260302-M0010BD	1,129
F8260302-M0011BD	1,477
F8260302-M0012BD	1,972
F8260302-M0013BD	1,935
F8260302-M0014BD	1,830
Mean:	1,155
Median:	1,072
Standard Deviation:	502
Range:	621 – 1,972

Table 3. Removable Surface Activity Results

Measurement ID	Surface Beta Activity (dpm/100 cm ²)
F8260302M0001SM	-0.95
F8260302M0002SM	-3.53
F8260302M0003SM	0.34
F8260302M0004SM	-0.95
F8260302M0005SM	2.93
F8260302M0006SM	-3.53
F8260302M0007SM	-3.53
F8260302M0008SM	-0.95
F8260302M0009SM	-2.24
F8260302M0010SM	-2.24
F8260302M0011SM	-3.53
F8260302M0012SM	-6.11
F8260302M0013SM	-2.24
F8260302M0014SM	-0.95
Mean:	-1.96
Median:	-2.24
Standard Deviation:	2.16
Range:	-6.11 to 2.93

Survey Unit Data Assessment:

The survey design required 14 direct measurements for the Sign Test. The critical value and the results of the Sign Test are presented in Table 4. The sample mean and median values were less than the DCGL. The sample standard deviation was less than the design standard deviation so no additional samples were required.

Table 4. Data Assessment Results

Survey Results Parameter	Value	Comment
Material Background Used (dpm/100 cm²):	N/A	
Ambient Background Used (dpm/100 cm²):	N/A	Average Ambient BKG = 0
Actual Direct Measurements (N):	14	·
Median (dpm/100 cm ²):	1,072	
Mean (dpm/100 cm ²):	1,155	
Direct Measurement Standard Deviation	502	
(dpm/100 cm ²):		
Total Standard Deviation (dpm/100 cm ²):	502	Based on samples and backgrounds.
Maximum (dpm/100 cm ²):	1,972	•
Material Type:	N/A	Background Subtract Not
		Applied
Sign Test Final N Value:	. 14	
S+ Value:	14	
Critical Value:	10	
Sufficient Samples Collected:	Yes	
Maximum Value < DCGL:	Yes	
Median Value < DCGL:	Yes	
Mean Value < DCGL:	Yes	
Maximum Value < DCGLemc:	N/A	Class 3
Total Standard Deviation <= Sigma:	Yes	
Pass the Sign Test?	Yes	
Reject the Null Hypothesis?	Yes	
Does the Survey Unit Pass All Criteria?	Yes	

Survey Unit Investigations and Results:

No investigations were required for either direct or scan measurements and no investigation results are reported.

ALARA Statement:

As stated in Chapter 4 of the LTP, as long as the residual activity within the survey unit is less than the DCGL (i.e. the survey unit average activity is less than the DCGL and the EMC criterion has been met), the ALARA criterion has been met.

Changes in Initial Survey Unit Assumptions:

The survey unit was designed as a Class 3 structure survey and the sample results are consistent with that classification. The variability of the survey results was less than the characterization data used for survey design. No potential areas of elevated activity were detected.

Conclusion:

The FSS of this survey unit was properly designed as a Class 3 survey based on Table 5-4 of the LTP. The required number of direct measurements was made and the scan coverage met the requirement of Table 5-6 of the LTP. No direct measurements exceeded the DCGL of 43,000 dpm/100 cm² and none of the removable surface activity measurements exceeded 10% of the DCGL. No investigations were required.

The direct measurement data support rejection of the null hypothesis, providing high confidence that the survey unit satisfied the release criteria and that the data quality objectives were met.


It is concluded that survey unit F8260302 meets the release criteria of 10CFR20.1402.

Attachment 1


Maps


September 8, 2008

Survey Unit F8260302




Turbine Building East Exterior Wall Area Estimate: 154 sq. meters






Turbine Building South Exterior Wall Area Estimate: 398 sq. meters

Map F8260302-1, Turbine Building Exterior East and South Exterior Walls Area Estimate: 552 square meters




Turbine Building North Exterior Wall Area Estimate: 454 sq. meters





Turbine Building West Exterior Wall Area Estimate: 590 sq. meters




Map F8260302-2, Turbine Building Exterior North and West Exterior Walls Area Estimate: 1,044 square meters










•

Map F8260302-5, Turbine Building East and South Exterior Walls Beta Direct Measurements F8260302M0005BD to F8260302M0010BD





Distance in meters from Turbine Building (+) 40' El.




Map F8260302-6, Turbine Building
East Exterior Wall
ISOCS Gamma Scan Measurements
F8260302M0001GS to F8260302M0007GS
12.57 sq. meter field of view
Total Scan Area: 79 sq. meters











Map F8260302-8, Turbine Building
West Exterior Wall
ISOCS Gamma Scan Measurements
F8260302M0026GS to F8260302M0029GS,
F8260302M0033GS, and
F8260302M0039GS to F8260302M0045GS
12.57 sq. meter field of view
F8260302M0030GS to F8260302M0032GS
F8260302M0034GS to F8260302M0038GS, and
F8260302M0046GS to F8260302M0050GS

19.6 sq. meter field of view Total Scan Area: 377 sq. meters





Attachment 2 Instrumentation September 8, 2008

Survey Unit F8260302

Table 2-1. Survey Unit Instrumentation

Instrument Model; Serial No.	Detector Model; Serial No.	MDC Static (dpm/100 cm²)	MDC Scan (dpm/100 cm²)
M2350; 203486	43-68B; 161400	257	612
Tennelec; 0401171	N/A	5.88 dpm α, 11.71 dpm β	N/A

Instrument	Detector Model No.	Detector Serial No.	MDC
ISOCS	N/A	2983947	Concrete – 974 dpm/100 cm ² Cs-137, Concrete – 953 dpm/100 cm ² Co-60

Table 2-2. Investigation Criteria and DCGL

Parameter	Value (dpm/100 cm²)
Investigation Criteria - Direct	21,500
Investigation Criteria – Scan (ISOCS average Cs-137 activity for 12.5 m ² field of view)	2,300
DCGL _W	43,000
DCGL _{EMC}	N/A

Attachment 3
Investigation
September 8, 2008
Survey Unit F8260302

(none required)

Attachment 4

Data Assessment

September 8, 2008

Survey Unit F8260302

