

Initial Condition for US-APWR's SBLOCA Analysis
using M-RELAP5
(Non-Proprietary)

Table Initial Condition (Main Parameters)

No.	Parameters	Target value		M-RELAP5 calculated value		Error	Criteria	corresponding parameter in M-RELAP5
1	Core power							
2	Pressurizer pressure							
3	Secondary pressure	A-loop						
		B-loop						
4	RCS average Temperature (Tave)	A-loop						
		B-loop						
5	RV outlet Temperature (Thot) at Nominal power	A-loop						
		B-loop						
6	RV inlet Temperature (Tcold) at Nominal power	A-loop						
		B-loop						
7	ΔT at Nominal power	A-loop						
		B-loop						
8	RV upper head temperature							
9	Loop flow rate	A-loop						
		B-loop						
10	Pressurizer water mass							

Table2 Initial Condition (Coolant Flows in RV)

No.	Parameters	Target value		M-RELAP5 calculated value		Error		Criteria	corresponding parameter in M-RELAP5
1	Core flow rate								
2	Upper head bypass flow rate								
3	Neutron-Reflector's cooling holes flow rate								
4	Flow rate in Control rod guide thimbles and Neutron-Reflector gap between Neutron-Reflector's outer surface and core-barrel inner surface								

Table3 Initial Condition (Pressure drop) (1/2)

No.	Locations / Components	Target value	M-RELAP5 calculated value	Error	Criteria	corresponding parameter in M-RELAP5
1	RV inlet nozzle	5.56 psi				
2	Downcomer	0.47 psi				
3	Lower plenum	7.22 psi				
4	Lower core support plate	8.94 psi				
5	Core inlet	1.46 psi				
6	Core	20.14 psi				
7	Core outlet	0.54 psi				
8	Total core, inlet to outlet	22.14 psi				
9	Upper core plate	4.98 psi				
10	Upper plenum	0.66 psi				
11	RV outlet nozzle	2.09 psi				
12	Total RV, inlet to outlet	52.06 psi				
13	Hot leg	1.64 psi				
14	SG inlet plenum nozzle	6.68 psi				
15	SG U-tube inlet	0.47 psi				

* A-loop = broken loop

B-loop = intact loop

Table3 Initial Condition (Pressure drop) (2/2)

No.	Locations / Components		Target value		M-RELAP5 calculated value		Error		Criteria	corresponding parameter in M-RELAP5
16	SG U-tube	A-loop	29.87	psi						
		B-loop								
17	SG U-tube outlet	A-loop	0.82	psi						
		B-loop								
18	SG outlet plenum nozzle	A-loop	3.40	psi						
		B-loop								
19	Crossover leg	A-loop	3.44	psi						
		B-loop								
20	Cold leg	A-loop	1.42	psi						
		B-loop								
21	Total, entire loops	A-loop	47.74	psi						
		B-loop								
22	RCP head	A-loop	99.79	psi						
		B-loop								
23	Upper head spray nozzle		34.96	psi						
24	Control rod guide tube		8.79	psi						

* A-loop = broken loop

B-loop = intact loop

Table4 Initial Condition (Fuel Pellet Temperature)

No.	Parameters	Target value		M-RELAP5 calculated value		Error		Criteria	corresponding parameter in M-RELAP5
1	Pellet average temperature (average-power core)								
2	Pellet average temperature (hot assembly)								
3	Pellet average temperature (hot rod)								

Table5 Initial Condition (SG Secondary Side)

No.	Parameters		Target value		M-RELAP5 calculated value		Error	Criteria	corresponding parameter in M-RELAP5
1	Recirculation ratio	A-loop							
		B-loop							
2	SG secondary mass	A-loop							
		B-loop							
3	Heat transfer rate from primary to secondary (one-loop)	A-loop							
		B-loop							
4	Main steam flow rate at Nominal power	A-loop							
		B-loop							
5	Main feed water flow rate at Nominal power	A-loop							
		B-loop							