

Facility: Palisades		Date of Exam: July 2008				Operating Test No.: 1									
A P P L I C A N T	E V E N T T Y P E	Scenarios													
		1			2			SPARE (#)			T O T A L	M I N I M U M (*)			
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N							
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P		R	I	U	
SRO-U	RX	-							-			0			0
	NOR	1							1			1			1
	I/C	23458							234			5			2
	MAJ	7							7			1			1
	TS	248							246			3			2
SRO-U	RX					-			-			0			0
	NOR					1			1			2			1
	I/C					2345			234			4			2
	MAJ					7			7			1			1
	TS					245			246			3			2
RO	RX		1						1		-	1	1		
	NOR		-						-		1	1	1		
	I/C		2568						246		345	7	4		
	MAJ		7						7		7	2	2		
	TS		-						-		-	0	0		
	Note:	Each SRO-U will perform as SRO in one scenario. A surrogate will act as BOP or ATC operator as necessary # Spare scenario not included in totals													
Instructions: <ol style="list-style-type: none"> Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls (ATC)" and "balance-of-plant (BOP)" positions; Instant SROs must do one scenario, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. Reactivity manipulations may be conducted under normal or <i>controlled</i> abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis. Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns. 															