ENCLOSURE

ATTACHMENT 13.9

SIA calculation NMP-26Q-302 (Non-proprietary version)

Nine Mile Point Unit 2 Main Steam Line Strain Gage Data Reduction

V	iuciurai mi	egrity Associat	es, Inc.	File No.: NMP-26Q-3	302
C	ALCULATI	ON PACKAG	E	Project No.: NMP-26	5Q
PROJECT	NAME:				
EPU Vibrati	on Monitoring				
CONTRAC	T NO.:				
7705420 Re	v. 0 and Rev. 1				
CLIENT:			PLANT:		
Constellation	Structural Integrity Associal CALCULATION PACKAG COJECT NAME: "U Vibration Monitoring ONTRACT NO.: 05420 Rev. 0 and Rev. 1 LIENT: onstellation Energy ALCULATION TITLE: ne Mile Point Unit 2 Main Steam Line Strain reument Affected Pages Revision Description 0 1-34 Original Iss Appendices A1-A21, B1-B21, C1-C21, D1-D21, E1-E21, F1-F21, G1-G21, H1-H21, I1-I21, J1-J21, K1-K21, L1-L5	Nine Mile	Point Unit 2		
CALCULA	TION TITLE:				
Nine Mile P	oint Unit 2 Main	Steam Line Strain G	iage Data R	eduction	
Document Revision	Affected Pages	Revision Descrip	vrity Associates, Inc. N PACKAGE PLANT: Nine Mile I eam Line Strain Gage Data Re Revision Description Original Issue	Project Manager Approval Signature & Date	Preparer(s) & Checker(s) Signatures & Date
U	1-34 Appendices A1-A21, B1-B21, C1-C21, D1-D21, E1-E21, F1-F21, C1 C21	Original Issu	e	Jad. Mg- Miroslav Trubelja 3/29/09	Month Adur Roland Horvath 3/26/09 Inf. Mon



Table of Contents

1.0 INTRODUCTION	5
2.0 TECHNICAL APPROACH	5
2.1 Data Acquisition Parameters and Filename Convention	5
2.2 Channels with Invalid Signals	8
2.3 Data Reduction Methodology	8
2.4 Strain Gage Data and Dynamic Pressure Estimates	.10
3.0 STRAIN GAGE INSTRUMENT LOCATIONS	.11
4.0 VIBRATION DATA	.11
4.1 Noise floor comparison	.12
5.0 SUMMARY	. 13
6.0 REFERENCES	. 14
APPENDIX A 0% POWER	A1
APPENDIX B 25% POWER	B 1
APPENDIX C 45% POWER	C 1
APPENDIX D 53.5% POWER (ONE FW PUMP)	D1
APPENDIX E 53.5% POWER (TWO FW PUMP)	.E1
APPENDIX F 69% POWER	.F1
APPENDIX G 88% POWER	G1
APPENDIX H 90% POWER	H1
APPENDIX I 94% POWER	I1
APPENDIX J 97% POWER	. J1
APPENDIX K 100% POWER	K1
APPENDIX L WATERFALL DIAGRAMS	.L1

Document Does Not Contain Vendor Proprietary Information



List of Tables

Table 1: Strain Gage Channels and Locations	6
Table 2: File Names vs. Power Levels	7
Table 3: Virtual Channels	7
Table 4: Applied Notch Filters	9
Table 5: Pressure Conversion Factor	10
Table 6: 0% Power – Strain RMS and Max-Min	15
Table 7: 25% Power – Strain RMS and Max-Min	16
Table 8: 45% Power – Strain RMS and Max-Min	17
Table 9: 53.5% Power (One FW Pump) – Strain RMS and Max-Min	18
Table 10: 53.5% Power (Two FW Pump) – Strain RMS and Max-Min	19
Table 11: 69% Power – Strain RMS and Max-Min	20
Table 12: 88 % Power – Strain RMS and Max-Min	21
Table 13: 90% Power – Strain RMS and Max-Min	
Table 14: 94% Power – Strain RMS and Max-Min	23
Table 15: 97% Power – Strain RMS and Max-Min	24
Table 16: 100% Power – Strain RMS and Max-Min	

·

Document Does Not Contain Vendor Proprietary Information



List of Figures

 \sim

۰.

	Figure 1: MSL-A-Upper RMS u-STR	26
	Figure 2: MSL-A-Lower RMS u-STR	26
	Figure 3: MSL-B-Upper RMS u-STR	27
	Figure 4: MSL-B-Lower RMS u-STR	27
	Figure 5: MSL-C-Upper RMS u-STR	28
	Figure 6: MSL-C-Lower RMS u-STR	28
	Figure 7: MSL-D-Upper RMS u-STR	29
	Figure 8: MSL-D-Lower RMS u-STR	29
	Figure 9: MSL A and B, RMS u-STR	30
	Figure 10: MSL C and D, RMS u-STR	.30
	Figure 11: Coherence plot MSL-A-Upper vs. MSL-A-Lower	.31
	Figure 12: Coherence plot MSL-B-Upper vs. MSL-B-Lower	31
	Figure 13: Coherence plot MSL-B-Upper vs. MSL-B-Lower	32
	Figure 14: Coherence plot MSL-B-Upper vs. MSL-B-Lower	32
	Figure 15: Main Steam Line A-Upper vs. B-Upper	.33
•	Figure 16: Lab test EIC compared to NMP EIC at power level 25% and 100%	.33
	Figure 17: Lab test EIC compared to NMP DATA at power level 25% and 100%	

Page 4 of 34

Document Does Not Contain Vendor Proprietary Information

1.0 INTRODUCTION

During the fall 2007 Nine Mile Point Unit 2 maintenance outage, strain gages were installed on the main steam piping inside the drywell to indirectly measure the dynamic pressure pulsations that occur during plant operation. Main Steam (MS) line strain measurements were recorded during the April 2008 power ascension. The purpose of this calculation is to determine magnitude of pressure pulsation and convert the time history strain gage data into frequency spectra in order to characterize its frequency content. Conversion factors between strain and pressure are also provided for each data location [2].

2.0 TECHNICAL APPROACH

2.1 Data Acquisition Parameters and Filename Convention

The strain gage data [3] was recorded on Structural Integrity's VersaDASTM Version 4.4 strain gage data acquisition system with each strain gage configuration in a ½ bridge. Each data set was recorded using a sample rate of 2500 samples per second (sps) for 120 seconds.

Each data set contains 32 columns of data in binary format where each column represents 1 channel of ½ bridge MS strain gage data. The channel number versus MS strain gage location is summarized in Table 1. In addition, signals from the individual channels are also grouped into 8 virtual channels based on their location. The purpose of the virtual channels is to calculate the dynamic pressure at a certain pipe location by averaging all working strain gages at that location. Table 3 describes how the recorder channels are combined into virtual channels for each MS gage locations.

Data was obtained during the April 2008 power ascension at 0%, 25%, 45%, 53.5%, 69%, 88%, 90%, 94%, 97% and 100% power levels. The 0% power data set represents reactor conditions low core and no steam flow: Normal Operating Pressure and Normal Operating Temperature (NOP/NOT). Additionally, at every power level above NOP/NOT a measurement was repeated without Wheatstone bridge excitation voltage. In this configuration the cables of the strain gages serve as antennae capturing only the electric noise normally present in the signal. The purpose of this measurement is to identify the noise characteristic of the system. This technique is called Electric Interference Check (EIC). Table 2 summarizes the filenames for each dataset.

Once acquired, these signals were downloaded from the VersaDASTM data acquisition computer by Structural Integrity Associates (SIA) for analysis. The analysis of the data was done using MATLAB [1].

File No.: NMP-26Q-302 Revision: 0

Page 5 of 34

Document Does Not Contain Vendor Proprietary Information

	Channel No.	MSL	Elevation	Gage	Orientation (Deg)	Comment
	1			01A - C	6 · · · · ·	
	1.1			*• 05A***	180	
		1	1	02A	45 :	
	2	· ·	Upper	.06A	225	
	Sec. 1. 5	as for the	· 315'9-7/8"	03A	· 90	CALLER AND A CALLER
	5			07A	· · · 270 · · ·	
		1		04A	135	Inoperational Strain Gage Staring at 0% Power
	4		1	08A	315	Inoperational Strain Gage Staring at 0% Power
•	1-1-5 March	A		094		Inoperational Strain Gage Starting at 0% Power
	5	· ·	· ·	134	180.	
		1		104	45	<u>Britan di sendera di la composi de la composi La composi de la composi de</u>
	6		Lower	144		
	د ه	4	303' 2.7/16"	14A	225 5-5-26-200	and a start of the second s
	7.		505 2-110	TIA 24	1706 2 19	
	1	ł		10A	30 1 12/0 PERS	The second
	8			12A	135	inoperational Strain Gage Starting at 0% Power
	1. S. 1. S. 1. S. 1. S.			10A	313	THE WORKS IN A STRUCTURE STRUCTURE AND A STRUCTURE STRUCTURES IN THE STRUCTURES IN
	9	j	J	NOTB A	1	
	"A state of any i			USB TA	2	an and an
	10		The second	028	43	
	986 3 M / 1	1	Upper -	U0B		Market and the second
	5 11 5 1		514 10-5/10	5. 13 (USB)	901	moperational Strain Gage Starting at 0% Power
•	and the second of the	· ·		07B	a 179 270 Same	CALIFORNIA CONTRACTOR DE PROVINCIÓN DE CONTRACTOR DE CONTRACTOR DE CONTRACTOR DE CONTRACTOR DE CONTRACTOR DE C
1 M + 1	12	· ,	1. 1. 1. 1. 1.	0418	135	Inoperational Strain Gage Starting at 0% Power
	-	B ·		08B	¹ . 315	The A COMMAN AND THE DESCRIPTION AND A AND AND ADDRESS AND ADDRESS AND ADDRESS AND ADDRESS AND ADDRESS AND ADDR
	13	J	j	09Bt #42	0. st. fill	and the second
	A STATE OF STATE		1	13B	as 180 - 11	and the first of the second
·	. 14	,		<u>10B</u>	45	
			Lower	14B	225	Inoperational Strain Gage Starting at 0% Power
	2 . 15		309'.6"	72.711B	90	a been and the state of the sta
1	1. S.			15B	270	
,	16			12B	. 135	
		. م .		<u>16B</u>	315	
	17			5 01C	• · · · · · · · · · · · · · · · · · · ·	See State State State State State State State State State
• * ·	1. S.	· .		05C	180	Inoperational Strain Gage Starting at 0% Power.
	18	14 A		<u>, 02C</u>	45	Inoperational Strain Gage Starting at 0% Power
			Upper	06C	225	
	. 19	1	307' 3-5/16"	1 03C	- 90 · · · · ·	and the second
			1	. 07C	270	
	·ì 20			. 04C	135	Inoperational Strain Gage Starting at 0% Power
tant so the second		c `		08C	315	
	21		· · ·	* 09C	() () () () () () () () () () () () () (A SALE FRANCIA CARAGE STRATE
	> <u>- 78 - 1</u>			*13C	180	
	22			10C	45	
Buch Barry		• . ~	Lower	14C	225,	· · · · ·
,	* 73		301'11"	11C	90,	and the second second second second
			•	15C	270	
	74		• · · · ·	12C	135	
			·	16C	315	
•	25			1. No 01D	'	
	<u> 1. 70 k o</u>		1.1.	, 05D	180	1 Inoperational Strain Gage Starting at 0% Power
	26			02D	45	
			Upper	06D	225	
	27	1. A.	`309'	> • • • 03D	90)	这次自己已经已经有1000年,这日2.65万元的公司的工作在内
	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	•	i de la	07D	270 📚 🛵	
	2.8	1 T	l	04D	135 ``	Inoperational Strain Gage Starting at 0% Power
	, u u	n		08D	315	Inoperational Strain Gage Starting at 0% Power
	20			/ 09D		MARKAR STATEMAR STATISTICS
	A. A. C.			编译出3D2参照	A 180 C	1.3133.1123、如果2013年月月月月日,中国10月13日,中国
	30 .			10D	45	
	96		Lower	14D	225	
	Tent 1 Search		303' 7-11/16"	7. 11D	90, 1978	Inoperational Strain Gage Starting at 0% Power
				4 15D	× 5, 270 × 5	
	32			12D	135	
			L	16D	315	

Table 1: Strain Gage Channels and Locations

File No.: NMP-26Q-302 Revision: 0

Document Does Not Contain Vendor Proprietary Information

1.5.1g 1

F0306-01R0

Page 6 of 34

		Ľ	Data Files	· · · · · · · · · · · · · · · · · · ·	i
Powe	er %	File Name	Date	Time	Comment
NOPMOT	DATA	20080416224519.dta	4/16/2008	22:45	No EIC
NOP/NOT	EIC		•	· · -	NOEIC
25	DATA	20080417082119.dta	4/17/2008	8:21:00 AM	
23	' EIC ·	20080417082921.dta	4/17/2008	8:29:00 AM	
45	DATA	20080418064142.dta	4/18/2008	6:41	
43	EIC	20080418063619.dta	4/18/2008	6:36	
52.5	DATA	20080418102812.dta	4/18/2008	10:28:00 AM	
55.5	EIC	20080418103314.dta	4/18/2008	10:33:00 AM	- One FW Pump
52.5	DATA	20080418114515.dta	4/18/2008	11:45:00 AM .	
55.5	EIC	20080418115050.dta	4/18/2008	11:50:00 AM	Two FW Pumps
60	DATA	20080418133533.dta	4/18/2008	1:35:00 PM	
	EIC	20080418134134.dta	4/18/2008	1:41:00 PM	
00	DATA	20080419042237.dta	4/19/2008	4:22:00 AM	
00	EIC	20080419042836.dta	4/19/2008	4:28:00 AM	
00	DATA	20080419052320.dta	4/19/2008	5:23:00 AM	
90	EIC	20080419051618.dta	4/19/2008	5:16:00 AM	
04	DATA	20080419070235.dta	4/19/2008	7:02:00 AM	;
94	EIC	20080419065611.dta	4/19/2008	6:56:00 AM	
07	DATA	20080419082350.dta	4/19/2008	8:23:00 AM	
9/	EIC	20080419081737.dta	4/19/2008	8:17:00 AM	
100	DATA	20080419094734.dta	4/19/2008	9:47:00 AM	
100	EIC	20080419094134.dta	4/19/2008	9:41:00 AM	c.

 Table 2: File Names vs. Power Levels.

 Table 3: Virtual Channels

Location	Channels
MSL-A-Upper	1 2 3
MSL-A-Lower	5 6 7 8
MSL-B-Upper	9 10 11 12
MSL-B-Lower	13 14 15 16
MSL-C-Upper	17 18 19 20
MSL-C-Lower	21 22 23 24
MSL-D-Upper	25 26 27
MSL-D-Lower	29 30 31 32

File No.: NMP-26Q-302 Revision: 0 Page 7 of 34

Document Does Not Contain Vendor Proprietary Information

2.2 Channels with Invalid Signals

Initial review of the main steam line strain gage data was performed to determine if the data was valid and to determine how to combine the strain gage data at each MS line location. Based on this review certain channels have failed and these signals were not used in any of the subsequent analyses. On channels 4 and 28, both strain gages, had bad resistance reading starting at 0% power level. The Wheatstone bridge on these channels could not be balanced and had to be excluded from the entire data processing. A couple of strain gages failed prior the power ascension (Table 1) and their functioning condition did not change during the entire power ascension. Table 3 summarizes the created virtual channels for the power ascension as well as the channel exclusions.



File No.: NMP-26Q-302 Revision: 0

Document Does Not Contain Vendor Proprietary Information

Page 8 of 34



File No.: NMP-26Q-302 Revision: 0

Page 9 of 34

Document Does Not Contain Vendor Proprietary Information

2.4 Strain Gage Data and Dynamic Pressure Estimates

The strain gages to Pressure Conversion Factors (PCF) were determined using formulas for a thick wall cylinder acted upon by internal pressure only Reference [2]. Table 5 summarizes the pressure conversion factors for each main steam line location.

Channei No.	MSL	Elevation	Mean Conversion Factor for each location (psi/µɛ)		
1		-			
2		Upper	0.00		
3		315 9-7/8"	3.62		
4					
5	A				
6		Lower	2.94		
7		303' 2-7/16"	3.04		
8					
9					
10	-	Upper	2 04		
11		314' 10-5/16"	3.04		
12	_				
13	В		-		
14		Lower	2.04		
15	В	309' 6"	3.81		
16					
17					
18		Upper	2.95		
19	A B C	307' 3-5/16"	3.65		
20	~				
21			· · ·		
22		Lower	2.01		
23		301' 11"	5.01		
24					
25					
26		Upper	3.02		
27		309'	3.52		
28	р				
29	MSL A B C				
30		Lower	2.04		
31		303' 7-11/16"	3.94		
32					

Table 5: Pressure Conversion Factor

File No.: NMP-26Q-302 Revision: 0

Page 10 of 34

Document Does Not Contain Vendor Proprietary Information

3.0 STRAIN GAGE INSTRUMENT LOCATIONS

Eight sets of strain gages were installed at eight elevations on the main steam piping inside the drywell with 2 locations per line. The opposite strain gages are connected in a ½ bridge in order to reduce the effect of the bending modes. These eight groups of strain gages were combined into eight virtual channels. Table 3 shows the detailed description of these 8 virtual channels. In order to increase the quality of the signal an External Power Source (EPS) was used to provide more robust voltage excitation to the Wheatstone bridges. The application of the EPS made the EIC measurement relatively easy. That is the reason why all the data sets above NOP/NOT level are coupled with an EIC data set.

At 100% power level a coherence check was done to verify the improved signal quality. For every main steam line, the upper and the lower virtual channels were coupled to check the coherence level. These plots are shown in Figure 11 thought Figure 14. The upper and lower virtual channels are mechanically coupled. The excitation induced by the acoustic pressure pulsation, in the common space, results that the coherence is reaching higher values in lower frequency domain. Figure 15 shows the coherence plot of two virtual channels where the source (acoustic pressure pulsation) and the mechanical path have highly indirect relationship and coupling. The coherence check, between MSL-A-Upper and MSL-B-Upper, results in generally low coherence.

It is important to notice that on the coherence plots there are a couple of peaks reaching near 1 value. These peaks are the result of electrical interference of 60Hz and its upper harmonics (common excitation of changing external magnetic and electrostatic filed). Also we can observe high coherence at 149Hz. At this frequency the coherence is high because all the strain gages have a response due to the uniform mechanical vane pass excitation.

4.0 VIBRATION DATA

Appendices A through K contain the frequency spectra for the strain gage vibration data collected during the April 2008 power ascension. Vibration data for all ten (10) power levels were recorded and the corresponding frequency spectra were generated using MATLAB [1].

Appendix	Α	—	0%	Power
Appendix	В		25%	Power
Appendix	С	—	45%	Power
Appendix	D	-	53.5%	Power
Appendix	Ε		53.5%	Power
Appendix	F		69%	Power
Appendix	G	—	88%	Power
Appendix	Η		90%	Power
Appendix	I		94%	Power
Appendix	J		97%	Power
Appendix	Κ	_	100%	Power
Appendix	L	—	Waterfal	l Plots

Page 11 of 34

Table 8 through Table 16 contain summaries of the strain RMS and Max-Min values ($\mu\epsilon$) and corresponding pressure values (psi) for each power level.

Figure 1 through Figure 10 show the RMS micro strain values as a function of power level for each MS lines and elevations. In addition, waterfall plots are provided in Appendix L of the frequency spectra versus power level for each of the combined main steam line strain gage data sets.

4.1 Noise floor comparison

Additional tests were performed in order to compare the NMP noise floor to the laboratory noise floor test. The NMP noise floor was captured generating EICs at different power levels. These EIC noise floors combine the noise originated from the signal path such as cabling and penetration plus the noise of the data acquisition hardware itself.

The laboratory noise floor was generated using 300ft cables with two real strain gages with identical data acquisition hardware. For the lab test the two strain gages connected in similar fashion to a half bridge like the strain gages on the NMP main steam lines.

The EICs recorded at 25% and 100% power level and the EIC generated in laboratory environment are nearly identical showing that the NMP has excellent installation of strain gage data acquisition system. However, when laboratory generated noise floor is compared to that of real data at 25% and 100% of power, it is apparent that the lab noise floor is lower at all frequencies and it never obscures any strain signals. Therefore, it is safe to filter any electrical and mechanical interference frequencies present in the EIC recordings out of the actual strain data. The results of these comparisons can be seen on Figure 16 and Figure 17.

Page 12 of 34

Document Does Not Contain Vendor Proprietary Information



5.0 SUMMARY

Main steam strain gage data was collected following the April 2008 Nine Mile Point Unit 2 maintenance outage. Initially the gages were connected in ½ Wheatstone bridge with two strain gages at the opposite side of the main steam pipe. When one of the strain gages failed it was replaced by a completion resistor and the ½ bridge was configure to a ¼ bridge. The data was collected at ten (10) power levels during the power ascension. At every power level above NOP/NOT an extra set of data was recorded without bridge excitation in order to identify the characteristic of the electric noise in the signal. During the data acquisition an analog filter was used to prevent signal aliasing. When the data was post processed different types of digital filter were applied to remove undesired frequency content originated from 60Hz AC electrical network and the Reactor Recirculation System pumps.

Observations:

- 1) In general the maximum time history RMS micro-strain of the virtual channels is less than 0.17. The highest RMS micro-strain of 0.16274 is measured on MSL-C-Upper at 100% power level.
- 2) In the frequency spectra the dominant frequencies are lower than 50Hz.
- 3) 60Hz electrical noise and its upper harmonics in the signal were expected based on industrial experience. The presence of this electrical noise and the correct application of notch filters, to remove these frequencies, were verified by the Electrical Interference Check at different power level.
- 4) Coherence check at 100% has satisfying results.
- 5) In general the noise floor is between 1 and 2 nano-strain.

6.0 REFERENCES

1. MATLAB, Version 7.1.0.246, Release 14, Service Pack 3, Mathworks, August 02, 2005.

2. Structural Integrity Associates Calculation, "Nine Mile Point Unit 2 Strain Gage Uncertainty Evaluation and Pressure Conversion Factors", Revision 0, SI File No. NMP-26Q-301. .

. .

· .•

. ·

3. Nine Mile Point Unit 2 April 2008 Strain Gage Data, SI File NMP-26Q-209.

· . :

-	
\leq	
200	

ŝ 1 į ı

File No.: NMP-26Q-302 Revision: 0

Page 15 of 34

.,

Document Does Not Contain Vendor Proprietary Information

F0306-01R0

1.1

File No.: NMP-26Q-302 Revision: 0

Page 16 of 34

.

•

;

Document Does Not Contain Vendor Proprietary Information



	·····	·		1 5. 5 .				
1		~	 որդեր պահեր է հեր			· · ·		· . "
•								•
+								
								,
1								2
· -								
+								
;								
:								
:								3
								5
								•
1								9
								1
			• •				•	,
					•			•
·		·			,			
·								1
с 1	•							
4				4				
								r
						,		
	,		۰ ,					
								ł
								,
	,							
:			, ×					;
						. *		
:								

File No.: NMP-26Q-302 Revision: 0

1

Document Does Not Contain Vendor Proprietary Information

F0306-01R0

Page 17 of 34

51

	· · · · · · · · · · · · · · · · · · ·				•	
						í
						,
						ę
						2
				· .		
		r				
						,
						•
			•			
						•
		•				۱ •
						÷
						÷
						*
	ι.			•		ť
					1 A.	
				,		•
						:
						;
						•
		x				

and the second second

 Ω

File No.: NMP-26Q-302 Revision: 0

1.1

Page 18 of 34

Document Does Not Contain Vendor Proprietary Information







Page 19 of 34

Document Does Not Contain Vendor Proprietary Information



Page 20 of 34

Document Does Not Contain Vendor Proprietary Information





File No.: NMP-26Q-302 Revision: 0

Page 21 of 34

Document Does Not Contain Vendor Proprietary Information



Document Does Not Contain Vendor Proprietary Information





File No.: NMP-26Q-302 Revision: 0

Page 23 of 34

Document Does Not Contain Vendor Proprietary Information



File No.: NMP-26Q-302 Revision: 0 Page 24 of 34

Document Does Not Contain Vendor Proprietary Information



Γ

Structural Integrity Associates, Inc.

.....

				,
				,
				. •
		45		1
		. •		
				:
				-
• •				
				1
· .				•
	~			•

-- ;

.

File No.: NMP-26Q-302 Revision: 0 Page 25 of 34

Document Does Not Contain Vendor Proprietary Information

F0306-01R0

••

File No.: NMP-26Q-302 Revision: 0

, •

Page 26 of 34

Document Does Not Contain Vendor Proprietary Information



•



File No.: NMP-26Q-302 Revision: 0

Page 27 of 34

Document Does Not Contain Vendor Proprietary Information

File No.: NMP-26Q-302 Revision: 0

Page 28 of 34

Document Does Not Contain Vendor Proprietary Information





Page 29 of 34

Document Does Not Contain Vendor Proprietary Information

1. 16 25

File No.: NMP-26Q-302 Revision: 0

 $(x,y) \in \mathcal{A}_{1}^{(n)}$

Document Does Not Contain Vendor Proprietary Information

F0306-01R0

Page 30 of 34

•••



File No.: NMP-26Q-302 Revision: 0

Page 31 of 34

· •

Document Does Not Contain Vendor Proprietary Information

File No.: NMP-26Q-302 Revision: 0

Page 32 of 34

Document Does Not Contain Vendor Proprietary Information

File No.: NMP-26Q-302 Revision: 0

Page 33 of 34

Document Does Not Contain Vendor Proprietary Information

File No.: NMP-26Q-302 Revision: 0

Page 34 of 34

Document Does Not Contain Vendor Proprietary Information

All content in Appendices A through L are proprietary and are excluded from this version of the document.



Page A1 of A21

Document Does Not Contain Vendor Proprietary Information