R R R R	SOUTHWEST RESEA 6220 Culebra Road, P Institute Quali Institute Calibrati Phone: 210-522-5215 Certificate of	P.O. Drawer 28510 ty Systems on Laboratory Fax 210-522-4834	ACCREDITED Calibration Laboratory Certificate #0972-01
Cost Center:	DIV20	Work Order: 30	3088983
Mail Stop:	B51	Date Issued: 17-	-Jul-2009
Customer:	DON BANNON	Date Calibrated: 16	-Jul-2009
Manufacturer/Model:	DURO-SENSE / TYPE K	* Date Due : 16-	-Jul-2010
Description:	THERMOCOUPLE	** Results: FC	UND-LEFT
Serial Number:		Temperature: 75	°F
Asset Number:	012397	Humidity: 50	
	TEMPERATURE PROBES - 5 JUN 06		
This certificate documents trac	eability to the National Institute of Standards and Te	echnology (NIST) and the International System of Ur	nits (SI). The Laboratory

This certificate documents traceability to the National Institute of Standards and Technology (NIST) and the International System of Units (SI). The Laboratory quality system conforms to ISO/IEC 17025, 2005, ANSI/NCSL Z540-1-1994 and relevant requirements of the ISO 9000-2000 standard. This certificate shall not be reproduced, except in full, without the written approval of the Southwest Research Institute Calibration Laboratory. This certificate shall not be used to claim product endorsement by Southwest Research Institute, American Association for Laboratory Accreditation (A2LA) or any agency of the U.S. Government. Results of this calibration relate only to the instrument described above at the time of calibration and does not imply any long term stability of the instrument.

*Determined by the customer, does not imply the instrument will remain within tolerance as any number of factors may cause an out-of-tolerance condition before this date. **Data type found in this certificate or attached measurement report must be interpreted as: Found-left - adjustment and/or repair was not performed, As-found - data is before unit is adjusted and/or repaired, As-left - data is after adjusted and/or repaired was performed. The customer has sole responsibility for determination of in-/out-of-tolerance or compliance/noncompliance.

Measurement uncertainty calculated in accordance with the method described in the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM), for a confidence level of approximately 95 percent using a coverage factor of k=2.

Remarks: 3 POINT CAL (25 °, 100 °, 200 °C)

Standards Used

<u>Asset #</u>	Manufacturer	Model	Description	Cal Date	Due Date
009137	HART SCIENTIFIC	1575	SUPER THERMOMETER	15-May-2009	15-Nov-2009
013908	HART SCIENTIFIC	5628	SPRT	20-Feb-2008	20-Feb-2010
015240	HART SCIENTIFIC	2566	TC SCANNER, 12-CHANNEL MODULE	10-Dec-2008	10-Dec-2009

Mr Nat Walt Hill

Laboratory Manager m:VA2LA OCT_08.rpt Metrology Technician

Southwest Research Institute Calibration Laboratory Measurement Report

. . 4

Work Order: Asset No.	303088983 012397	Mfr. Model	Duro-Sense Type K		Technician: Type Data:	Mark R Found-	
Serial No.	12397	Туре.	Thermocouple		Cal Date:	16-Jul-09	
Remarks: Limits taken	from ASTM E230)-02 and are bas	ed on brand new	unused therm	locouples.		
Function/Range	Test Point	TI Reading	Difference	+/- Limit	+/- Uncertainty	Result	% Limi
Function/Range	Test Point °C	TI Reading ℃	Difference °C	+/- Limit °C	+/- Uncertainty °C	Result	% Limi

199.919 -0.234 END OF REPORT

0.192

100.351

2.2

2.2

0.5

0.5

100.159

200.153

9%

11%

Pass

Pass