# Seabrook Station 2009 NRC Exam JPM - RO

Facility: <u>Seabrook</u>		Date of Examination: 6/15/09
Examination Level: RO 🗵	SRO 🗌	Operating Test Number:
Administrative Topic (see Note)	Type Code*	Describe activity to be performed
Conduct of Operations	R, M	2.1.7 Ability to evaluate plant performance and make operational judgments based on operating characteristics, reactor behavior, and instrument interpretation.      Activity – Manual QPTR calculation      (L0027J AP - modified) (RO ADMIN#1)
Conduct of Operations	R, M	2.1.37 Knowledge of procedures, guidelines, or limitations associated with reactivity management.  Activity – Perform Estimated Critical Position Calculation  (L0033J) (RO-ADMIN#4)
Equipment Control	R, M	2.2.12 Knowledge of Surveillance procedures  Activity – Manual RCS Steady State Leak Rate Calculation  (L0082J - Modified) (RO- ADMIN#2)
Radiation Control	R, M	2.3.6 Ability to Approve Release Permits Activity - Initiate a Liquid Effluent Waste Sample Request (RO-ADMIN#3)
Emergency Procedures/Plan		
		Os. RO applicants require only 4 items unless they are s, when all 5 are required.
* Type Codes & Criteria:	(D)irect from (N)ew or (M)	om, (S)imulator, or Class(R)oom n bank (≤ 3 for ROs; ≤ 4 for SROs & RO retakes) odified from bank (≥ 1) exams (≤ 1; randomly selected)

# Seabrook Station 2009 NRC Exam JPM – SRO -I

Facility: <u>Seabrook</u> Examination Level: RO	SRO ⊠	Date of Examination: <u>6/15/09</u> Operating Test Number:
Administrative Topic (see Note)	Type Code*	Describe activity to be performed
Conduct of Operations	R, N	2.1.25 Ability to interpret reference materials, such as graphs, tables, etc.  Activity – Verify Blended Makeup 2000 gallon flush of Reactor Coolant Mixed Bed  (New) (SRO-ADMIN#1)
Conduct of Operations	R, M	2.1.37 Knowledge of procedures, guidelines, or limitations associated with reactivity management.  Activity – Approve an Estimated Critical Position Calculation (L0033J) (SRO-ADMIN#2)
Equipment Control	R, M	2.2.12 Knowledge of Surveillance procedures  Activity – Verify RCS Steady State Leak Rate Determination  (L0082J – Modified - AP)(SRO-ADMIN#3)
Radiation Control	R, N	2.3.4 Knowledge of radiation exposure limits under normal or emergency conditions     Activity - Authorize an Emergency Dose Limit Extension     (New) (SRO-ADMIN#4)
Emergency Procedures/Plan	R, N	2.4.40 Knowledge of the SRO's responsibilities in emergency plan implementation  Activity – Determine Emergency Action Level - PARS  (New) (SRO-ADMIN#5)
		ROs. RO applicants require only 4 items unless they are cs, when all 5 are required.
* Type Codes & Criteria:	(D)irect fron (N)ew or (M	om, (S)imulator, or Class(R)oom n bank (≤ 3 for ROs; ≤ 4 for SROs & RO retakes) l)odified from bank (≥ 1) exams (≤ 1; randomly selected)

# Seabrook Station 2009 NRC Exam JPM - SRO-U

Facility: Seabrook Examination Level: RO	SRO ⊠	Date of Examination: 6/15/09 Operating Test Number:
Administrative Topic (see Note)	Type Code*	Describe activity to be performed
Conduct of Operations	R, N	2.1.25 Ability to interpret reference materials, such as graphs, tables, etc.  Activity – Verify Blended Makeup 2000 gallon flush of Reactor Coolant Mixed Bed  (New) (SRO-ADMIN#1)
Conduct of Operations	R, M	2.1.37 Knowledge of procedures, guidelines, or limitations associated with reactivity management.  Activity – Approve an Estimated Critical Position Calculation (L0033J) (SRO-ADMIN#2)
Equipment Control	R, M	2.2.12 Knowledge of Surveillance procedures  Activity – Verify RCS Steady State Leak Rate Determination  (L0082J – Modified -AP)(SRO-ADMIN#3)
Radiation Control	R, N	2.3.4 Knowledge of radiation exposure limits under normal or emergency conditions  Activity - Authorize an Emergency Dose Limit Extension  (New) (SRO-ADMIN#4)
Emergency Procedures/Plan	R, N	2.4.40 Knowledge of the SRO's responsibilities in emergency plan implementation  Activity – Determine Emergency Action Level - PARS  (New) (SRO-ADMIN#5)
		ROs. RO applicants require only 4 items unless they are cs, when all 5 are required.
* Type Codes & Criteria:	(D)irect from (N)ew or (M	om, (S)imulator, or Class(R)oom n bank (≤ 3 for ROs; ≤ 4 for SROs & RO retakes) l)odified from bank (≥ 1) 2 exams (≤ 1; randomly selected)

Facility: Seabrook Date of Exam Level: RO SRO-I SRO-U	kamination: <u>6/15/09</u> Oper	9 rating Test No.:	
Control Room Systems <sup>®</sup> (8 for RO); (7 for SRO-I); (2 or 3 fo	r SRO-U, including 1	ESF)	
System / JPM Title		Type Code*	Safety Function
a. (Pair A1) Isolate Open PORV – E-0 , L0069JAP (all)		A, L, M, S	3
b. (Pair A2) Transfer SW to the Cooling Tower using manua	l TA Signal, (all)	A, EN, N, S	8
c. (Pair B1) Trip all RCPs, L0083JAP (all)		A, D, L, S	2
d. (Pair B2) Start Hydrogen Recombiners, L0084J (all)		EN, L, M, S	5
e. (Pair C1) Off-site Power Restoration, (all)		L, N, S	6
f. (Pair C2) Pressurizer Pressure Channel Failure (all)		N, S	7
g. (Pair D1) Blended Makeup performance, L0035J (all)		A, M, S	1
h. (Pair E2) Establish SG Feed Flow from SUFP, L0085J (a	I)	A, D, L, S	4
In-Plant Systems <sup>®</sup> (3 for RO); (3 for SRO-I); (3 or 2 for SRC	-U)		
j. (In-plant #1) Reset Steam Driven EFW Pump Trip Valve, I	_0016J (all)	D, E, L,	4
k. (In-plant #2) Locally Close a stuck open ASDV, (all)		E, N, R	5
I. (In-plant #3) Deenergize Bus 5 due to Fire during RSS, L0	1162J (all)	E, L, N	6
All RO and SRO-I control room (and in-plant) systems in systems must serve different safety functions; in-plant s			
* Type Codes	Criteria	for RO / SRO-I / SRO-U	
(A)Iternate path (C)ontrol room (D)irect from bank (E)mergency or abnormal in-plant (EN)gineered safety feature (L)ow-Power / Shutdown (N)ew or (M)odified from bank including 1(A) (P)revious 2 exams (R)CA (S)imulator		4-6/4-6/2-3 ≤ 9 / ≤ 8 / ≤ 4 ≥ 1 / ≥ 1 / ≥ 1 - / - / ≥ 1 (control room system) ≥ 1 / ≥ 1 / ≥ 1 ≥ 2 / ≥ 2 / ≥ 1 ≤ 3 / ≤ 3 / ≤ 2 (randomly selected) ≥ 1 / ≥ 1 / ≥ 1	

Seabrook Station 2009 NRC	Exam JPM – <b>SR</b>	O-I	
Facility: <u>Seabrook</u> Exam Level: RO □ SRO-I ⊠ SRO-U □		of Examination: <u>6/15</u> tting Test No.:	
Control Room Systems <sup>®</sup> (8 for RO); (7 for SRO-I); (2 or 3 for	SRO-U, including 1	ESF)	
System / JPM Title		Type Code*	Safety Function
a. (Pair A1) Isolate Open PORV – E-0, L0069JAP (all)		A, L,, M, S	3
b. (Pair A2) Transfer SW to the Cooling Tower using manual	TA Signal, all)	A, EN, N, S	8
c. (Pair B1) Trip all RCPs, L0083JAP (all)		A, D, L, S	2
d. (Pair B2) Start Hydrogen Recombiners, L0084J (all)		EN, L, M, S	5
e. (Pair C1) Off-site Power Restoration, (all)		L, N, S	6
f. (Pair C2) Pressurizer Pressure Channel Failure (all)		N, S	7
g. (Pair E1) Transfer to Cold Leg Recirculation (CBS-V-2), London NRC) (SROI 1,2,3,4)	0139JAP (used on	A, D, L, P, S	4
h. (Pair E2) Establish SG Feed Flow from SUFP, L0085J (SI	ROI 6, 7, 8)	A, D, L, S	4
In-Plant Systems <sup>®</sup> (3 for RO); (3 for SRO-I); (3 or 2 for SRO	-U)		
j. (In-plant #1) Reset Steam Driven EFW Pump Trip Valve, L	0016J (all)	D, E, L,	4
k. (In-plant #2) Locally Close a stuck open ASDV, (all)		E, N, R	5
I. (In-plant #3) Deenergize Bus 5 due to Fire during RSS, L0	162J (All)	E, L, N	6
All RO and SRO-I control room (and in-plant) systems m systems must serve different safety functions; in-plant systems.			
* Type Codes	Criteria fo	or RO / SRO-I / SRO-U	
(A)Iternate path (C)ontrol room (D)irect from bank (E)mergency or abnormal in-plant (EN)gineered safety feature (L)ow-Power / Shutdown (N)ew or (M)odified from bank including 1(A) (P)revious 2 exams (R)CA (S)imulator		4-6/4-6/2-3 ≤ $9/≤8/≤4$ ≥ $1/≥1/≥1$ - $/-//>≥1$ (control roll 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2	

Seabrook Station 2009 NR0	C Exam JPM – :	SRO-U	
Facility: Seabrook Exam Level: RO SRO-I SRO-U		of Examination: _ ating Test No.:	
Control Room Systems <sup>®</sup> (8 for RO); (7 for SRO-I);	(2 or 3 for SRO-U,	including 1 ESF)	
System / JPM Title		Type Code*	Safety Function
a. (Pair A1) Isolate Open PORV, L0069JAP (all)		A, L, M, S	3
b.(Pair A2) Transfer SW to the Cooling Tower using Signal (all)	Pair A2) Transfer SW to the Cooling Tower using manual TA		8
In-Plant Systems <sup>@</sup> (3 for RO); (3 for SRO-I); (3 or 2	? for SRO-U)		
j. (In-plant #1) Reset Steam Driven EFW Pump Trip (all)	o Valve, L0016J	D, E, L.	4
k. (In-plant #2) Locally Close a stuck open ASDV (a	all)	E, N, R	5
k. (In-plant #3) Deenergize Bus 5 due to Fire during (all)	g RSS, L0162J	E, L, N	6
All RO and SRO-I control room (and in-plant) s functions; all 5 SRO-U systems must serve dif overlap those tested in the control room.			
*Type Codes	Criteria	for RO / SRO-I / SR	<b>D-U</b>
(A)Iternate path (C)ontrol room (D)irect from bank (E)mergency or abnormal in-plant (EN)gineered safety feature (L)ow-Power / Shutdown (N)ew or (M)odified from bank including 1(A) (P)revious 2 exams (R)CA (S)imulator		4-6/4-6/2-3 $\leq 9/\leq 8/\leq 4$ $\geq 1/\geq 1/\geq 1$ $-/-/\geq 1$ (contributed to 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2 1/2	

### Seabrook Station 2009 NRC Exam-Simulator Scenarios

Facility: <u>Seabrook</u>	Scenario No.: <u>B</u> Op-Test No.:
Examiners: Peter Presby	Operators:

Initial Conditions: Mode 1, 8% power.

**Turnover:** The plant is at 8% power. Increase plant power to 18% to warm up Main Turbine. No fuel preconditioning guidelines in effect. SEPS diesels are out of service. Main Steam Atmospheric Steam Dump ("A"ASDV) valve, MS-PV-3001 is Danger Tagged due to excessive seat leakage. MS-V-5 is closed and tagged. "A" MFP is in service. OS1000.02, "Plant Startup from Hot Standby to Minimum Load", step 4.2.7 in progress. RCS temperature is being verified greater than minimum temp for criticality per T.S. 3.1.1.4.

Event No.	Malf. No.	Event Type*	Event Description	
1		BOP N PSO R	Increase plant power to 18%.	
2	ptRCPT455	PSO I	PZR Pressure Controlling channel fails LOW	
		SRO TS	TS 3.3.1, Rx Trip System Instrumentation; Table 3.3-1, Items 7,9 & 10	
			TS 3.3.2, ESFAS Instrumentation; Table 3.3-3, Items 1.d. and 10.a.	
3	ltFWLT549	BOP I	Controlling level transmitter on SG D Feed Regulating Bypass Valve, fails LOW.	
		SRO TS	Enter T.S. 3.3.1, table 3.3-1, Item 13 and T.S 3.3-3, items 5.b, 6.a, 7.c, and 10C.	
4	mfRC019 mfRC050A	PSO C	45 gpm Rx Vessel Flange Leak with a 2 minute ramp inside containment. After isolation of flange leak, followed by initiation of 20 gpm RCS leak w/ 2 minute ramp inside containment.	
		SRO TS	TS 3.4.6.2, RCS Unidentified leakage > 1 GPM.	
5	ptMSPT507	ворт	MS header Pressure instrument, MS-PT-507, fails HIGH.	
6	mfCP011	М	Initiation of 2 simultaneous dropped rods requiring Manual Reactor trip.	
	mfRC050A		Upon the manual reactor trip the RCS leakage will increase to 50,000 gpm.	
7	mfRPS007	PSO C	Upon the manual reactor trip the following will occur:	
	mfRPS008		o "B" Centrifugal Charging pump trips.	
	mfCBS004		o SI will fail to auto actuate.	
	mfCBS005		CBS pumps fail to Auto Start.	
	mfCS017			

<sup>(</sup>N)ormal, (R)eactivity, (I)nstrument, (C)omponent, (M)ajor

Seabrook Station 2009 NRC Exam-Simulator Scenarios

Facility: <u>Seabrook</u>	Scenario No.: <u>C</u> Op-Test No.:
Examiners: Peter Presby	_ Operators:

Initial Conditions: Mode 1, 75% power.

**Turnover:** The plant is at 75% power due to grid load restrictions. Current power level was achieved 12 hrs ago. The Motor driven EFW pump has been tagged out for motor inspection. T.S. Action Statement 3.7.1.2 was entered at 0600. Plant is being held at 75% power, waiting ISO direction to return plant power to 100%. The "A" ASDV is isolated and tagged closed.

Eve nt No.	Malf. No.	Event Type*	Event Description
1	ttRCTT431, mfRC049A	PSO I	Tcold Temperature instrument, RC-TI-431, fails LOW. Causes a 30 gpm RCS leak with a 5 minute ramp. (leak not counted towards I/C requirements.)
		SRO TS	T.S. 3.3.1, Rx Trip Instruments, Table 3.3-1, Items 7 & *, TR-19, FWI on Low Tavg. TS T.S. 3.4.6.2, RCS Unidentified Leakage > 1gpm
2		SRO N BOP/PSO R	Plant shutdown due to RCS leakage exceeding TS value TS 3.4.6.2 Reactor Coolant System Leakage
3	ftFWFT512	BOPI	Controlling Steam Flow transmitter, FW-FT-512, fails low.
	SRO TS		TS 3.3.1, Rx Trip System Instrumentation; Table 3.3-1, Item 13
		T.S. 3.3.2, Engineered Safety Features Actuation System Instrumentation; Table 3.3-3, Items 5.b, 6.a, 7.c, 10.c	
4	ctFWFK509B	BOP C	FW-P-32A Slave Controller Auto Output fails to zero
5	mfFW038	PSO C	MFP-32A trip on low lube oil pressure, rods fail to insert in Auto
6	avMSVSV2 mfFW054 mfRPS001 mfRPS002 mfRPS003	M	Loss of All Feedwater Main Turbine Stop Valve #2 FAILS OPEN. An AUTO Reactor Trip will not occur, PSO performs a MANUAL Trip.
7	rmvMSV129		After the crew has passed step 3 of FR-S.1 AND Wide Range level on all SGs >/= 35% and increasing then TRIP MS-V-129, Steam Supply to Turbine Driven EFW pump.
8	mfFW041		SUFP trips (faulty 86 device)
9	rmvMSV129	BOP C	Recovery of Turbine Driven EFW Pump

### Seabrook Station 2009 NRC Exam-Simulator Scenarios

Facility: Seabroo	<u>k</u> Sc	enario No.: <u>D</u>	Op-Test N	o.:		
Examiners: Petel	r Presby	Operators:				
Initial Canditia	me: Mode 1 520	)/ nowor				

**Turnover:** The plant is at 52% power preparing to do a power increase of 10%/hr to 100% following repairs to FW-P-32B. Stable at current power level for 12 hrs. The "A" ASDV is isolated and tagged closed. The Supplemental Emergency Diesel Generators are unavailable due to a tag out for maintenance. The Crew is in OS1000.05, Power Increase at step 4.3.15.

Event No.	Malf. No.	Event Type*	Event Description
1		BOP N PSO R	Power increase at 10%/hr from 50% to 100%
2	mfAR006C	C BOP	Failure of the seal water pump to one of the running Condenser Air Removal Pumps results in lowering condenser Vacuum.
3	ItRCLT459	I PSO TS US (SRO)	Failure of Pressurizer level Transmitter, RC-LT-459, LOW. Causes an isolation of letdown flow.  T.S. 3.3.1, table 3.3-1, item 11, 3.3.3.6, table 3.3.10, item 5, 3.3.3.5, table 3.3-9, item 5.
4	mfSG002B	PSO C TS US	"B" Steam Generator Tube leak at 75 gpm. TS 3.4.6.2, action c
5	mfSG002B	M	Leak in "B" Steam Generator Tube increases to 300 gpm. Crew should manually trip the Reactor and Actuate SI.
6	Trigger, mfCC014	C PSO	On the Manual Reactor trip the "A" PCCW pump will trip, and the "C" PCCW pump will fail to auto start.
7	svMSV3002	C BOP	On the Manual Reactor trip the SG "B" Atmospheric Steam Dump valve (ASDV) will fail partially open, causing a release to atmosphere.
8	rfMS012	С	After a time delay a Safety Valve on the "B" SG will lift below setpoint re-initiating the release.

Facility: SEAB	ROOK						Date	e of l	Exan	1:	6/15	5/9						
						ко к	VA C	ateg	ory I	oint	S				SR	<u> </u>	ly Poin	its
Tier	Group	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G *	Total	A2	2	(	3*	Total
1.	1	4	1	2				3	4			4	18					6
Emergency & Abnormal	2	2	3	1		N/A		1	1	N	/A	1	9					4
Abnormal Plant Evolutions	Tier Totals	6	4	3				4	5			5	27					10
	1	3	2	2	4	1	2	2	3	3	3	3	28					5
2. Plant	2	2	0	0	2	1	1	2	1	0	0	1	10					3
Systems	Tier Totals	5	2	2	6	2	3	4	4	3	3	4	38					8
	Generic Knowledge and Abilities     Categories							2		3		4	10	1	2	3	4	7
								3		2		2						

Note:

- Ensure that at least two topics from every applicable K/A category are sampled within each tier of the RO
  and SRO-only outlines (i.e., except for one category in Tier 3 of the SRO-only outline, the "Tier Totals"
  in each K/A category shall not be less than two).
- 2. The point total for each group and tier in the proposed outline must match that specified in the table. The final point total for each group and tier may deviate by ±1 from that specified in the table based on NRC revisions. The final RO exam must total 75 points and the SRO-only exam must total 25 points.
- 3. Systems/evolutions within each group are identified on the associated outline; systems or evolutions that do not apply at the facility should be deleted and justified; operationally important, site-specific systems/evolutions that are not included on the outline should be added. Refer to Section D.1.b of ES-401 for guidance regarding the elimination of inappropriate K/A statements.
- 4. Select topics from as many systems and evolutions as possible; sample every system or evolution in the group before selecting a second topic for any system or evolution.
- Absent a plant-specific priority, only those K/As having an importance rating (IR) of 2.5 or higher shall be selected.
   Use the RO and SRO ratings for the RO and SRO-only portions, respectively.
- 6. Select SRO topics for Tiers 1 and 2 from the shaded systems and K/A categories.
- 7.\* The generic (G) K/As in Tiers 1 and 2 shall be selected from Section 2 of the K/A Catalog, but the topics must be relevant to the applicable evolution or system. Refer to Section D.1.b of ES-401 for the applicable K/As.
- 8. On the following pages, enter the K/A numbers, a brief description of each topic, the topics' importance ratings (IRs) for the applicable license level, and the point totals (#) for each system and category. Enter the group and tier totals for each category in the table above; if fuel handling equipment is sampled in other than Category A2 or G\* on the SRO-only exam, enter it on the left side of Column A2 for Tier 2, Group 2 (Note #1 does not apply). Use duplicate pages for RO and SRO-only exams.
- For Tier 3, select topics from Section 2 of the K/A catalog, and enter the K/A numbers, descriptions, IRs, and point totals (#) on Form ES-401-3. Limit SRO selections to K/As that are linked to 10 CFR 55.43.

Emergen	cy ar	d A	bno	rma	I Pla	nt Eve	olutions - Tier 1/Group 1 (RO / SRO)	l e	T
E/APE # / Name / Safety Function	K 1	K 2	K 3	A 1	A 2	G	K/A Topic(s)	IR	#
000007 (BW/E02&E10 CE/E02) Reactor Trip - Stabilization - Recovery / 1							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000008 Pressurizer Vapor Space Accident / 3		V					AK2. Knowledge of the interrelations between the Pressurizer Vapor Space Accident and the following: (CFR 41.7 / 45.7)  AK2.02 Sensors and detectors	2.7	1
000009 Small Break LOCA / 3							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000011 Large Break LOCA / 3	1						EK1 Knowledge of the operational implications of the following concepts as they apply to the Large Break LOCA: (CFR 41.8 / 41.10 / 45.3)	4.1	1
							EK1.01 Natural circulation and cooling, including reflux boiling		
000015/17 RCP Malfunctions / 4						7	2.2 Equipment Control 2.2.39 Knowledge of less than or equal to one hour Technical Specification action statements for systems.	3.9	1
							(CFR: 41.7 / 41.10 / 43.2 / 45.13)		
000022 Loss of Rx Coolant Makeup / 2	1						AK1. Knowledge of the operational implications of the following concepts as they apply to Loss of Reactor Coolant Makeup:	3.0	1
							(CFR 41.8 / 41.10 / 45.3)		
							AK1.03 Relationship between charging flow and PZR level		
000025 Loss of RHR System / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000026 Loss of Component Cooling Water / 8			٧				AK3. Knowledge of the reasons for the following responses as they apply to the Loss of Component Cooling Water:	3.6	1
							(CFR 41.5,41.10 / 45.6 / 45.13)		
							AK3.02 The automatic actions (alignments) within the CCWS resulting from the actuation of the ESFAS		
000027 Pressurizer Pressure Control System Malfunction / 3					1		AA2. Ability to determine and interpret the following as they apply to the Pressurizer Pressure Control Malfunctions:	3.7	1
							(CFR: 43.5 / 45.13)		
							AA2.15 Actions to be taken if PZR pressure instrument fails high		

ES-401 Emerge	ncy an	d Al	ono				ation Outline olutions - Tier 1/Group 1 (RO / SRO)	orm ES-	401-2
E/APE # / Name / Safety Function	K 1	K 2	K 3	A 1	A 2	G	K/A Topic(s)	IR	#
000029 ATWS / 1			0			٧	2.1 Conduct of Operations 2.1.20 Ability to interpret and execute procedure steps.	4.6	1
							(CFR: 41.10 / 43.5 / 45.12)		
000038 Steam Gen. Tube Rupture / 3				٧			EA1 Ability to operate and monitor the following as they apply to a SGTR:	4.3	1
							(CFR 41.7 / 45.5 / 45.6)		
					- E		EA1.04 PZR spray, to reduce coolant system pressure		
000040 (BW/E05; CE/E05; W/E12) Steam Line Rupture - Excessive Heat Transfer / 4	1						040AK1. Knowledge of the operational implications of the following concepts as they apply to Steam Line Rupture:	3.4	1
							(CFR 41.8 / 41.10 / 45.3)		
							AK1.07 Effects of feedwater introduction on dry S/G		
000054 (CE/E06) Loss of Main Feedwater / 4						١	2.2 Equipment Control 2.2.44 Ability to interpret control room indications to verify the status and operation of a system, and understand how operator actions and directives affect plant and system conditions. (CFR: 41.5 / 43.5 / 45.12)	4.2	1
000055 Station Blackout / 6					<b>√</b>		EA2 Ability to determine or interpret the following as they apply to a Station Blackout:  (CFR 43.5 / 45.13)	4.4	
							EA2.02 RCS core cooling through natural circulation cooling to S/G cooling		
000056 Loss of Off-site Power / 6				7			AA1. Ability to operate and / or monitor the following as they apply to the Loss of Offsite Power:  (CFR 41.7 / 45.5 / 45.6)	3.3	1
							AA1.31 PZR heater group control switches		
000057 Loss of Vital AC Inst. Bus / 6							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000058 Loss of DC Power / 6	1						AK1. Knowledge of the operational implications of the following concepts as they apply to Loss of DC Power:	2.8	1
							(CFR 41.8 / 41.10 / 45.3)		
							AK1.01 Battery charger equipment and instrumentation		

ES-401 Emergence	cy an	d A	bno				nation Outline Polutions - Tier 1/Group 1 (RO / SRO)	orm ES-	401-2
E/APE # / Name / Safety Function	K 1	K 2	K 3	A 1	A 2	G	K/A Topic(s)	IR	#
000062 Loss of Nuclear Svc Water / 4					I .	1	2.4 Emergency Procedures / Plan 2.4.11 Knowledge of abnormal condition procedures. (CFR: 41.10 / 43.5 / 45.13)	4.0	1
000065 Loss of Instrument Air / 8			7				AK3. Knowledge of the reasons for the following responses as they apply to the Loss of Instrument Air:  (CFR 41.5,41.10 / 45.6 / 45.13)  AK3.04 Cross-over to backup air supplies	3.0	1
W/E04 LOCA Outside Containment / 3					7		EA2. Ability to determine and interpret the following as they apply to the (LOCA Outside Containment) (CFR: 43.5 / 45.13)	3.4	1
							EA2.1 Facility conditions and selection of appropriate procedures during abnormal and emergency operations		
W/E11 Loss of Emergency Coolant Recirc. / 4					7		EA2. Ability to determine and interpret the following as they apply to the (Loss of Emergency Coolant Recirculation) (CFR: 43.5 / 45.13)	3.4	1
							EA2.1 Facility conditions and selection of appropriate procedures during abnormal and emergency operations		
BW/E04; W/E05 Inadequate Heat Transfer - Loss of Secondary Heat Sink / 4				1			EA1. Ability to operate and / or monitor the following as they apply to the (Loss of Secondary Heat Sink)  (CFR: 41.7 / 45.5 / 45.6)	3.7	1
							EA1.2 Operating behavior characteristics of the facility.		
000077 Generator Voltage and Electric Grid Disturbances / 6							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
						<u> </u>			18
K/A Category Totals:	4	1	2	3	4	4	Group Point Total:		18/ 6

ES-401 Emergency and					ation Iution		ne ier 1/Group 2 (RO / SRO)	orm ES-	401-2
E/APE # / Name / Safety Function	K	K 2	K 3	A 1	A 2	G	K/A Topic(s)	IR	#
000001 Continuous Rod Withdrawal / 1		\[ \frac{2}{}	7	1	74		AK2. Knowledge of the interrelations between the Continuous Rod Withdrawal and the following:  (CFR 41.7 / 45.7)	2.9	1
					ļ		AK2.01 Rod bank step counters		
000003 Dropped Control Rod / 1							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000005 Inoperable/Stuck Control Rod / 1			V		•		AK 3 Knowledge of the reasons for the following responses as they apply to the Inoperable/Stuck Control Rod. AK3.04 Tech-Spec Limits for inoperable rods.	3.4	1
000024 Emergency Boration / 1							(CFR: 41.5, 41.10/ 45.6 / 45.13)  Randomly selected and removed as described in ES-401 Attachment 1, item		
							2.c		
000028 Pressurizer Level Malfunction / 2							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000032 Loss of Source Range NI / 7							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000033 Loss of Intermediate Range NI / 7							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000036 (BW/A08) Fuel Handling Accident / 8							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000037 Steam Generator Tube Leak / 3							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000051 Loss of Condenser Vacuum / 4					1		AA2. Ability to determine and interpret the following as they apply to the Loss of Condenser Vacuum:	3.9	1
							(CFR: 43.5 / 45.13)		
							AA2.02 Conditions requiring reactor and/or turbine trip		
000059 Accidental Liquid RadWaste Rel. / 9							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		

ES-401 Emergency and A						Outlir is - Ti	ne er 1/Group 2 (RO / SRO)	orm ES-	401-2
E/APE # / Name / Safety Function	K 1	K 2	K 3	A 1	A 2	G	K/A Topic(s)	IR	#
000060 Accidental Gaseous Radwaste Rel. / 9		V					AK2. Knowledge of the interrelationships between Accidental Gaseous Radwaste Release and the following:  (CFR 41.5,41.10 / 45.6 / 45.13)  AK2.02 Auxiliary building ventilation system	2.7	1
000061 ARM System Alarms / 7							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000067 Plant Fire On-site / 8							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000068 (BW/A06) Control Room Evac. / 8							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000069 (W/E14) Loss of CTMT Integrity / 5		1					EK2. Knowledge of the interrelations between the (High Containment Pressure) and the following:  (CFR: 41.7 / 45.7)	3.4	1
							EK2.1 Components, and functions of control and safety systems, including instrumentation, signals, interlocks, failure modes, and automatic and manual features.		
000074 (W/E06&E07) Inad. Core Cooling / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000076 High Reactor Coolant Activity / 9						1	2.2 Equipment Control 2.2.25 Knowledge of the bases in Technical Specifications for limiting conditions for operations and safety limits.	3.2	1
							(CFR: 41.5 / 41.7 / 43.2)		
W/EO1 & E02 Rediagnosis & SI Termination / 3	V						EK1. Knowledge of the operational implications of the following concepts as they apply to the (SI Termination)	3.4	1
							(CFR: 41.8 / 41.10, 45.3) EK1.2 Normal, abnormal and emergency operating procedures associated with (SI Termination).		

ES-401 Emergency and A				and the face of the	the state of the	Outlins - Ti	ne Fo ier 1/Group 2 (RO / SRO)	rm ES-	401-2
E/APE # / Name / Safety Function	K	K 2	K 3	A	A 2	G	K/A Topic(s)	IR	#
W/E13 Steam Generator Over-pressure / 4	•			1	4		EA1. Ability to operate and/or monitor the following as they apply to the (Steam Generator Overpressure) (CFR: 41.7, 45.5, 45.6)	3.1	1
							EA1.1 Components, and functions of control and safety systems, including instrumentation, signals, interlocks, failure modes, and automatic and manual features.		
W/E15 Containment Flooding / 5							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
W/E16 High Containment Radiation / 9							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/A01 Plant Runback / 1									
BW/A02&A03 Loss of NNI-X/Y / 7									
BW/A04 Turbine Trip / 4									
BW/A05 Emergency Diesel Actuation / 6									
BW/A07 Flooding / 8									
BW/E03 Inadequate Subcooling Margin / 4									
BW/E08; W/E03 LOCA Cooldown - Depress. / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/E09; CE/A13; W/E09&E10 Natural Circ. / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/E13&E14 EOP Rules and Enclosures							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
CE/A11; W/E08 RCS Overcooling - PTS / 4	1						EK1. Knowledge of the operational implications of the following concepts as they apply to the (Pressurized Thermal Shock)	3.5	1
							(CFR: 41.8 / 41.10, 45.3) EK1.3 Annunciators and conditions indicating signals, and remedial actions associated with the (Pressurized Thermal Shock).		
CE/A16 Excess RCS Leakage / 2									
CE/E09 Functional Recovery									
K/A Category Point Totals:	2	3	1	1	1	1	Group Point Total:		9/4

ES-401				Plar	nt Sy			xamii Tier	0.7071.7		1000	Fc O / SRO)	rm ES-4	401-2
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
003 Reactor Coolant Pump	1				V							K1 Knowledge of the physical connections and/or cause-effect relationships between the RCPS and the following systems:  (CFR: 41.2 to 41.9 / 45.7 to 45.8)  K1.04 CVCS	2.6	2
				Siegove	ente e		100 m					K5 Knowledge of the operational implications of the following concepts as they apply to the RCPS:  (CFR: 41.5 / 45.7)  K5.04 Effects of RCP shutdown on secondary parameters, such as steam pressure, steam flow, and feed flow	3.2	
004 Chemical and Volume Control									1			A3 Ability to monitor automatic operation of the CVCS, including:  (CFR: 41.7 / 45.5)  A3.02 Letdown isolation.	3.6	1
005 Residual Heat Removal				V								K4 Knowledge of RHRS design feature(s) and/or interlock(s) which provide for the following:  (CFR: 41.7)  K4.11 Lineup for low head recirculation mode (external and internal)	3.5	1

ES-401				Plar				camir Tier				6 O / SRO)	rm ES-	401-2
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
006 Emergency Core Cooling			7							1		K3 Knowledge of the effect that a loss or malfunction of the ECCS will have on the following:  (CFR: 41.7 / 45.6)  K3.03 Containment	4.2	2
												A4 Ability to manually operate and/or monitor in the control room:  (CFR: 41.7 / 45.5 to 45.8)		
			301									A4.11 Overpressure protection system		
007 Pressurizer Relief/Quench Tank											<b>√</b>	2.4 Emergency Procedures / Plan 2.4.20 Knowledge of the operational implications of EOP warnings, cautions, and notes.	3.8	1
												(CFR: 41.10 / 43.5 / 45.13)		
008 Component Cooling Water	1											K1 Knowledge of the physical connections and/or cause-effect relationships between the CCWS and the following systems:  (CFR: 41.2 to 41.9 / 45.7 to 45.9)  K1.02 Loads cooled by CCWS	3.3	2
												A2 Ability to (a) predict the impacts of the following malfunctions or operations on the CCWS, and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of	3.2	
												those malfunctions or operations:  (CFR: 41.5 / 43.5 / 45.3 / 45.13)		
												A2.02 High/low surge tank level		

ES-401				Plar	nt Sy			xamir Tier				9 F0 O / SRO)	rm ES-	401-2
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
010 Pressurizer Pressure Control								1				A2 Ability to (a) predict the impacts of the following malfunctions or operations on the PZR PCS; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those malfunctions or operations:  (CFR: 41.5 / 43.5 / 45.3 / 45.13)	3.3	1
012 Reactor Protection						V						A2.01 Heater failures K6 Knowledge of the effect of a loss or malfunction of the following will have on the RPS: (CFR: 41.7 / 45/7)	2.9	1
013 Engineered Safety Features Actuation						V						K6.02 Redundant channels K6 Knowledge of the effect of a loss or malfunction on the following will have on the ESFAS:	2.7	1
												(CFR: 41.7 / 45.5 to 45.8) K6.01 Sensors and detectors		
022 Containment Cooling									√			A3 Ability to monitor automatic operation of the CCS, including:  (CFR: 41.7 / 45.5)  A3.01 Initiation of safeguards mode of operation	4.1	
025 Ice Condenser														
026 Containment Spray											<b>V</b>	2.4 Emergency Procedures / Plan 2.4.4 Ability to recognize abnormal indications for system operating parameters that are entry level conditions for emergency and abnormal operating procedures.	4.5	
												(CFR: 41.10 / 43.2 / 45.6)		

ES-401				Plar	nt Sy			xamii Tier				O / SRO)	rm ES-	401-2
System # / Name	K	K 2	K 3	K 4	K 5	K 6	A	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
039 Main and Reheat Steam							7					A1 Ability to predict and/or monitor changes in parameters (to prevent exceeding design limits) associated with operating the MRSS controls including:  (CFR: 41.5 / 45.5)  A1.06 Main steam pressure	3.0	1
059 Main Feedwater			<b>V</b>									K3 Knowledge of the effect that a loss or malfunction of the MFW will have on the following: (CFR: 41.7 / 45.6) K3.03 S/GS	3.5	1
061 Auxiliary/Emergency Feedwater							<b>V</b>	1				A1 Ability to predict and/or monitor changes in parameters (to prevent exceeding design limits) associated with operating the AFW controls including:  (CFR: 41.5 / 45.5)  A1.04 AFW source tank level	3.9	2
												A2 Ability to (a) predict the impacts of the following malfunctions or operations on the AFW; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those malfunctions or operations:	3.1	
												(CFR: 41.5 / 43.5 / 45.3 / 45.13) A2.05 Automatic control malfunction		

ES-401				Plar	nt Sy			xamiı Tier				Fc O / SRO)	orm ES-	401-2
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
062 AC Electrical Distribution	V								7			K1 Knowledge of the physical connections and/or cause effect relationships between the AC distribution system and the following systems:  (CFR: 41.2 to 41.9)  K1.02 ED/G	4.1	2
												A3 Ability to monitor automatic operation of the ac distribution system, including:  (CFR: 41.7 / 45.5)	2.7	
												A3.04 Operation of inverter (e.g., precharging synchronizing light, static transfer)		
063 DC Electrical Distribution		√										K2 Knowledge of bus power supplies to the following:  (CFR: 41.7)  K2.01 Major DC loads	2.9	1
064 Emergency Diesel Generator				V						7		K3 Knowledge of the effect that a loss or malfunction of the ED/G system will have on the following:  (CFR: 41.7 / 45.6)  K3.02 ESFAS controlled or actuated systems	4.2	2
												A4 Ability to manually operate and/or monitor in the control room:  (CFR: 41.7 / 45.5 to 45.8)  A4.09 Establishing power from the ring bus (to relieve ED/G)	3.2	

.

ES-401				Plar	ıt Sy						utline 1 (R	Form O / SRO)	n ES-4	401-2
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A l	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
073 Process Radiation Monitoring				7								interlock(s) which provide for the following:	4.0	1
												(CFR: 41.7) K4.01 Release termination when radiation exceeds setpoint		
076 Service Water											1	2.1 Conduct of Operations 2.1.30 Ability to locate and operate components, including local controls.	4.4	1
												(CFR: 41.7 / 45.7) K2 Knowledge of bus power		
078 Instrument Air		٧		V								supplies to the following:	3.3	2
												(CFR: 41.7)		
												K2.02 Emergency air compressor		
												K4 Knowledge of IAS design feature(s) and/or interlock(s) which provide for the following:	3.2	
												(CFR: 41.7) K4.02 Cross-over to other air systems		
103 Containment								100		V		A4 Ability to manually operate	3.5	1
												(CFR: 41.7 / 45.5 to 45.8)		
												A4 04 Phase A and phase B resets		
K/A Category Point Totals:	3	2	2	4	1	2	2	3	3	3	3	Group Point Total:		28 <i>i</i> 5

ES-401				Pla	ınt S			Exar S - Ti				ine Fo (RO / SRO)	orm ES-	401-2
System # / Name	K	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
001 Control Rod Drive					>							K5 Knowledge of the following operational implications as they apply to the CRDS:  (CFR: 41.5/45.7)  K5.65 CRDS circuity, including effects of primary/secondary power mismatch on rod control	3.2	1
002 Reactor Coolant						1						K6 Knowledge of the effect or a loss or malfunction on the following RCS components:  (CFR: 41.7 / 45.7)  K6.12 Code Safety valves	3.0	1
011 Pressurizer Level Control												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
014 Rod Position Indication							V					A1 Ability to predict and/or monitor changes in parameters (to prevent exceeding design limits) associated with operating the RPIS controls, including:  (CFR: 41.5 / 45.5)  A1.02 Control rod position indication on control room panels	3.2	1
015 Nuclear Instrumentation	1											K1 Knowledge of the physical connections and/or cause effect relationships between the NIS and the following systems:  (CFR: 41.2 to 41.9 / 45.7 to 45.8)  K1.04 ESF	3.5	1
016 Non-nuclear Instrumentation												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
017 In-core Temperature Monitor				V								K4 Knowledge of In-Core Temperature Monitoring System design feature(s) and/or interlock(s) which provide for the following: (CFR: 41.5 / 45.7) K4.01 Input to subcooling Monitors	3.4	1

ES-401				Pla	int S			Exan - Tie					ne Fo RO / SRO)	orm ES-	401-2
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	(	3	K/A Topic(s)	IR	#
027 Containment Iodine Removal													Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
028 Hydrogen Recombiner and Purge Control													Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
029 Containment Purge													Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
033 Spent Fuel Pool Cooling													A2 Ability to (a) predict the impacts of the following malfunctions or operations on the Spent Fuel Pool Cooling System; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those malfunctions or operations:  CFR: 41.5 / 43.5 / 45.3 / 45.13)  A2.03 Abnormal spent fuel pool water level or loss of water level	3.1	1
034 Fuel Handling Equipment								18					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
035 Steam Generator							<b>V</b>						A1 Ability to predict and/or monitor changes in parameters (to prevent exceeding design limits) associated with operating the S/GS controls including: (CFR: 41.5 / 45.5)	3.6	1
													A1.01 S/G wide and narrow range level during startup, shutdown, and normal operation		
041 Steam Dump/Turbine Bypass Control													Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
045 Main Turbine Generator	7												K1 Knowledge of the physical connections and/or cause effect relationships between the MT/G system and the following systems:	3.4	1
													(CFR: 41.2 to 41.9 / 45.7 to 45.8) K1.20 Protection system		
055 Condenser Air Removal													Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		

ES-401				Pla	ınt S						Outli Jp 2 (	ne Fo (RO / SRO)	rm ES-	401-2
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
056 Condensate											1	2.1 Conduct of Operations 2.1.7 Ability to evaluate plant performance and make operational judgments based on operating characteristics, reactor behavior, and instrument interpretation.  (CFR: 41.5 / 43.5 / 45.12 / 45.13)	4.4	1
068 Liquid Radwaste												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
071 Waste Gas Disposal												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
072 Area Radiation Monitoring				7								K4 Knowledge of ARM system design feature(s) and/or interlock(s) which provide for the following:  (CFR: 41.7)  K4.01 Containment ventilation isolation	3.3	1
075 Circulating Water												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
079 Station Air												De-selected and removed as described in ES-401 section D.1.d. See ES-4-1-4		
086 Fire Protection												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
K/A Category Point Totals:	2	0	0	2	1	1	2	1	0	0	1	Group Point Total:		10/

Facility: SEAE		Date of Exam: 6/15/09		30	eno.	0.4.
Category	K/A#	Topic	IR	₹O   #	SRO-	·Only #
1. Conduct of Operations	2.1.	2.1.4 Knowledge of individual licensed operator responsibilities related to shift staffing, such as medical requirements, "no-solo" operation, maintenance of active license status, 10CFR55, etc. (CFR: 41.10 / 43.2)	3.3	1		
	2.1.	2.1.15 Knowledge of administrative requirements for temporary management directives, such as standing operating orders, night orders, Operations Memos, etc.	2.7	1		
	21.	(CFR: 41.10 / 45.2)  2.1.23 Ability to perform specific system and integrated plant procedures during all modes of plant operation.	4.3	1		
		(CFR: 41.10 / 43.5 / 45.2 / 45.6)				
	2.1.					
	2.1.					
	2.1.					
	Subtotal			3		
2	2.2.	2.2.1 Ability to perform pre-startup procedures for the facility, including operating those controls associated with plant equipment that could affect reactivity.	4.5	1		
Equipment Control		(CFR: 41.5 / 41.10 / 43.5 / 43.6 / 45.1)				
	2.2.	2.2.20 Knowledge of the process for managing troubleshooting activities.	2.6	1		
		(CFR: 41.10 / 43.5 / 45.13)				
	2.2.	2.2.40 Ability to apply Technical Specifications for a system.	3.4	1		
		(CFR: 41.10 / 43.2 / 43.5 / 45.3)				
	2.2.					
	2.2.					
	2.2.					
	Subtotal			3		
	2.3.	2.3.4 Knowledge of radiation exposure limits under normal or emergency conditions.  (CFR: 41.12 / 43.4 / 45.10)	3.2	1		

Category	K/A#	Topic		२०	SRO	-Only
			IR	#	IR	#
3. Radiation Control	2.3.	2.3.13 Knowledge of radiological safety procedures pertaining to licensed operator duties, such as response to radiation monitor alarms, containment entry requirements, fuel handling responsibilities, access to locked high-radiation areas, aligning filters, etc.	3.4	1		
		(CFR: 41.12 / 43.4 / 45.9 / 45.10)				
	2.3.					
	2.3.					
	2.3.					
	2.3.					
	Subtotal			2		
4	2.4.	2.4.28 Knowledge of procedures relating to a security event (non-safeguards information). (CFR: 41.10 / 43.5 / 45.13)	3.2	1		
Emergency Procedures / Plan	2.4.	2.4.41 Knowledge of the emergency action level thresholds and classifications.	2.9	1		
		(CFR: 41.10 / 43.5 / 45.11)				
	2.4.					
	2.4.					
	2.4.					
	2.4.					
	Subtotal			2		
Tier 3 Point Tota	al			10		7

					I	о к	(/A C	ateg	ory I	Point	S				SF	(O-On	ly Poin	ts
Tier	Group	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G *	Total	,	\2	(	}* 	Total
1.	1	4	1	2				3	4			4	18		3		3	6
Emergency & Abnormal	2	2	3	1		N/A		1	1	N	/A	1	9		1		3	4
Plant Evolutions	Tier Totals	6	4	3				4	5			5	27		4		6	10
	1	3	2	2	4	1	2	2	3	3	3	3	28		3		2	5
2. Plant	2	2	0	0	2	1	1	2	1	0	0	1	10	K4:	1 1		1	3
Systems	Tier Totals	5	2	2	6	2	3	4	4	3	3	4	38		5		3	8
	Generic Knowledge and Abilities     Categories	Abil	ities			1		2		3		4	10	1	2	3	4	7-
				3		3		2		2		2	2	1	2			

Note:

- Ensure that at least two topics from every applicable K/A category are sampled within each tier of the RO
  and SRO-only outlines (i.e., except for one category in Tier 3 of the SRO-only outline, the "Tier Totals"
  in each K/A category shall not be less than two).
- 2. The point total for each group and tier in the proposed outline must match that specified in the table. The final point total for each group and tier may deviate by ±1 from that specified in the table based on NRC revisions. The final RO exam must total 75 points and the SRO-only exam must total 25 points.
- 3. Systems/evolutions within each group are identified on the associated outline; systems or evolutions that do not apply at the facility should be deleted and justified; operationally important, site-specific systems/evolutions that are not included on the outline should be added. Refer to Section D.1.b of ES-401 for guidance regarding the elimination of inappropriate K/A statements.
- 4. Select topics from as many systems and evolutions as possible; sample every system or evolution in the group before selecting a second topic for any system or evolution.
- 5. Absent a plant-specific priority, only those K/As having an importance rating (IR) of 2.5 or higher shall be selected. Use the RO and SRO ratings for the RO and SRO-only portions, respectively.
- 6. Select SRO topics for Tiers 1 and 2 from the shaded systems and K/A categories.
- 7.\* The generic (G) K/As in Tiers 1 and 2 shall be selected from Section 2 of the K/A Catalog, but the topics must be relevant to the applicable evolution or system. Refer to Section D.1.b of ES-401 for the applicable K/As.
- 8. On the following pages, enter the K/A numbers, a brief description of each topic, the topics' importance ratings (IRs) for the applicable license level, and the point totals (#) for each system and category. Enter the group and tier totals for each category in the table above; if fuel handling equipment is sampled in other than Category A2 or G\* on the SRO-only exam, enter it on the left side of Column A2 for Tier 2, Group 2 (Note #1 does not apply). Use duplicate pages for RO and SRO-only exams.
- 9. For Tier 3, select topics from Section 2 of the K/A catalog, and enter the K/A numbers, descriptions, IRs, and point totals (#) on Form ES-401-3. Limit SRO selections to K/As that are linked to 10 CFR 55.43.

ES-401 Emergenc	y an	d Al	ono	PV rma	/R Ex I Plai	camir nt Eve	nation Outline Solutions - Tier 1/Group 1 (RO / SRO)	orm ES-	401-2 
E/APE # / Name / Safety Function	K 1	K 2	K 3		A 2	G	K/A Topic(s)	IR	#
000007 (BW/E02&E10 CE/E02) Reactor Trip - Stabilization - Recovery / 1							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000008 Pressurizer Vapor Space Accident / 3							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000009 Small Break LOCA / 3							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000011 Large Break LOCA / 3							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000015/17 RCP Malfunctions / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000022 Loss of Rx Coolant Makeup / 2						1	2.4 Emergency Procedures / Plan 2.4.45 Ability to prioritize and interpret the significance of each annunciator or alarm.  (CFR: 41.10 / 43.5 / 45.3 / 45.12)	4.3	1
000025 Loss of RHR System / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000026 Loss of Component Cooling Water / 8						1	2.4 Emergency Procedures / Plan 2.4.4. Ability to recognize abnormal indications for system operating parameters that are entry level conditions for emergency and abnormal operating procedures.  (CFR: 41.10 / 43.2 / 45.6)	4.1	
000027 Pressurizer Pressure Control System Malfunction / 3							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000029 ATWS / 1							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000038 Steam Gen. Tube Rupture / 3					1		EA2 Ability to determine or interpret the following as they apply to a SGTR:  (CFR 43.5 / 45.13)  EA2.12 Status of MSIV activating system	4.2	1
000040 (BW/E05; CE/E05; W/E12) Steam Line Rupture - Excessive Heat Transfer / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000054 (CE/E06) Loss of Main Feedwater / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000055 Station Blackout / 6							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000056 Loss of Off-site Power / 6							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000057 Loss of Vital AC Inst. Bus / 6							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		

ES-401 Emergen	cy an	d A	bno				ration Outline For Solutions - Tier 1/Group 1 (RO / SRO)	rm ES-	401-2
E/APE # / Name / Safety Function	K 1	K 2		A 1	A 2	G	K/A Topic(s)	IR	#
000058 Loss of DC Power / 6							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000062 Loss of Nuclear Svc Water / 4						1	2.2 Equipment Control 2.2.25 Knowledge of the bases in Technical Specifications for limiting conditions for operations and safety limits. (CFR: 41.5 / 41.7 / 43.2)	4.2	1
000065 Loss of Instrument Air / 8							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
W/E04 LOCA Outside Containment / 3							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
W/E11 Loss of Emergency Coolant Recirc. / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/E04; W/E05 Inadequate Heat Transfer - Loss of Secondary Heat Sink / 4					<b>V</b>		EA2. Ability to determine and interpret the following as they apply to the (Loss of Secondary Heat Sink)  (CFR: 43.5 / 45.13)  EA2.1 Facility conditions and selection of appropriate procedures during abnormal and emergency operations	4.4	1
000077 Generator Voltage and Electric Grid Disturbances / 6					7		AA2. Ability to determine and interpret the following as they apply to Generator Voltage and Electric Grid Disturbances:  (CFR: 41.5 and 43.5 / 45.5, 45.7, and 45.8)  AA2.07 Operational status of engineered safety features	4.0	1
K/A Category Totals:					3	3	Group Point Total:		18/ 6

ES-401 Emergency and a		towns to	10000	500		on Out ions -	tline Fo Tier 1/Group 2 (RO / SRO)	orm ES-	401-2
E/APE # / Name / Safety Function	K		100	A 1	A 2	G	K/A Topic(s)	IR	#
000001 Continuous Rod Withdrawal / 1							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000003 Dropped Control Rod / 1						7	2.2 Equipment Control 2.2.38 Knowledge of conditions and limitations in the facility license. (CFR: 41.7 / 41.10 / 43.1 / 45.13)	4.5	1
000005 Inoperable/Stuck Control Rod / 1							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000024 Emergency Boration / 1						7	2.4 Emergency Procedures / Plan 2.4.34 Knowledge of RO tasks performed outside the main control room during an emergency and the resultant operational effects.  (CFR: 41.10 / 43.5 / 45.13)	4.1	1
000028 Pressurizer Level Malfunction / 2							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000032 Loss of Source Range NI / 7							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000033 Loss of Intermediate Range NI / 7							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000036 (BW/A08) Fuel Handling Accident / 8							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000037 Steam Generator Tube Leak / 3							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000051 Loss of Condenser Vacuum / 4							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000059 Accidental Liquid RadWaste Rel. / 9							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000060 Accidental Gaseous Radwaste Rel. / 9							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000061 ARM System Alarms / 7							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000067 Plant Fire On-site / 8							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000068 (BW/A06) Control Room Evac. / 8					\ \ \		AA2. Ability to determine and interpret the following as they apply to the Control Room Evacuation:	4.3	1
							(CFR: 43.5 / 45.13) AA2.05 Availability of heat sink		
000069 (W/E14) Loss of CTMT Integrity / 5							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		

ES-401 Emergency and A				n Ou ons -	tline Tier 1/Group 2 (RO / SRO)	rm ES-	401-2
E/APE # / Name / Safety Function	K 1	K		G	K/A Topic(s)	IR	#
000074 (W/E06&E07) Inad. Core Cooling / 4					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
000076 High Reactor Coolant Activity / 9					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
W/EO1 & E02 Rediagnosis & SI Termination / 3					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
W/E13 Steam Generator Over-pressure / 4					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
W/E15 Containment Flooding / 5					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
W/E16 High Containment Radiation / 9					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/A01 Plant Runback / 1					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/A02&A03 Loss of NNI-X/Y / 7					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/A04 Turbine Trip / 4					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/A05 Emergency Diesel Actuation / 6					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/A07 Flooding / 8					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/E03 Inadequate Subcooling Margin / 4					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/E08; W/E03 LOCA Cooldown - Depress. / 4					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
BW/E09; CE/A13; W/E09&E10 Natural Circ. / 4				1	2.1 Conduct of Operations 2.1.25 Ability to interpret reference materials, such as graphs, curves, tables, etc.	4.2	1
BW/E13&E14 EOP Rules and Enclosures					(CFR: 41.10 / 43.5 / 45.12)  Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
CE/A11; W/E08 RCS Overcooling - PTS / 4					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
CE/A16 Excess RCS Leakage / 2					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
CE/E09 Functional Recovery					Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
K/A Category Point Totals:			1	3	Group Point Total:		9/4

ES-401				Pla	nt S				otline 1 (F	e Fo RO / SRO)	orm ES-	401-2
System # / Name	K 1	K 2	K 3	K 4			A 3	A 4	G	K/A Topic(s)	IR	#
003 Reactor Coolant Pump										A2 Ability to (a) predict the impacts of the following malfunctions or operations on the RCPS; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those malfunctions or operations:  (CFR: 41.5 / 43.5 / 45.3 / 45/13)  A2.05 Effects of VCT pressure on RCP seal leakoff flows	2.8	1
004 Chemical and Volume Control										Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
005 Residual Heat Removal										Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
006 Emergency Core Cooling										Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
007 Pressurizer Relief/Quench Tank										Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
008 Component Cooling Water										Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
010 Pressurizer Pressure Control										Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
012 Reactor Protection									1	2.4 Emergency Procedures / Plan 2.4.4 Ability to recognize abnormal indications for system operating parameters that are entry-level conditions for emergency and abnormal operating procedures.  (CFR: 41.10 / 43.2 / 45.6)	4.7	1
013 Engineered Safety Features Actuation										Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		

ES-401 PWR Examination Outline Form ES-401-2 Plant Systems - Tier 2/Group 1 (RO / SRO)														
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
022 Containment Cooling							J	7	3			A2 Ability to (a) predict the impacts of the following malfunctions or operations on the CCS; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those malfunctions or operations:  (CFR: 41.5 / 43.5 / 45.3 / 45.13)  A2.05 Major leak in CCS	3.5	1
025 Ice Condenser												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
026 Containment Spray								1				A2 Ability to (a) predict the impacts of the following malfunctions or operations on the CSS; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those malfunctions or operations:  (CFR: 41.5 / 43.5 / 45.3 / 45.13)  A2.04 Failure of spray pump	4.2	1
039 Main and Reheat Steam												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
059 Main Feedwater												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
061 Auxiliary/Emergency Feedwater												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
062 AC Electrical Distribution												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
063 DC Electrical Distribution												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
064 Emergency Diesel Generator												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
073 Process Radiation Monitoring												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		

ES-401				Pla	nt S						Outline o 1 (R	e Fo RO / SRO)	ırm ES-	401-2
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
076 Service Water												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
078 Instrument Air												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
103 Containment											٨	2.2 Equipment Control 2.2.42 Ability to recognize system parameters that are entry-level conditions for Technical Specifications.  (CFR: 41.7 / 41.10 / 43.2 / 43.3 / 45.3)	4.6	1
K/A Category Point Totals:								3			2	Group Point Total:		28/

a.

ES-401		PWR Examination Outline Form ES-40 Plant Systems - Tier 2/Group 2 (RO / SRO)											101-2	
System # / Name	K 1	K 2		K 4	K 5	K 6	A 1	A 2	A 3	A 4	G	K/A Topic(s)	IR	#
001 Control Rod Drive												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
002 Reactor Coolant												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
011 Pressurizer Level Control												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
014 Rod Position Indication												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
015 Nuclear Instrumentation												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
016 Non-nuclear Instrumentation												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
017 In-core Temperature Monitor												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
027 Containment lodine Removal												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
028 Hydrogen Recombiner and Purge Control												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
029 Containment Purge												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
033 Spent Fuel Pool Cooling												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
034 Fuel Handling Equipment				1								K4 Knowledge of design feature(s) and/or interlock(s) which provide for the following:  (CFR: 41.7)	3.3	1
												K4.03 Overload protection		
035 Steam Generator												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		

ES-401	ES-401 PWR Examination Outline Form ES-401-; Plant Systems - Tier 2/Group 2 (RO / SRO)									401-2				
System # / Name	K 1	K 2	K 3	K 4	K 5	K 6	A 1		A 3	A 4		K/A Topic(s)	IR	#
041 Steam Dump/Turbine Bypass Control											<b>V</b>	2.4 Emergency Procedures / Plan 2.4.9 Knowledge of low power/shutdown implications in accident (e.g., loss of coolant laccident or loss of residual heat removal) mitigation strategies.	4.2	1
045 Main Turbine Generator								100				Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
055 Condenser Air Removal												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
056 Condensate					livite.							Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
068 Liquid Radwaste												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
071 Waste Gas Disposal												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
072 Area Radiation Monitoring												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
075 Circulating Water								1				A2 Ability to (a) predict the impacts of the following malfunctions or operations on the circulating water system; and (b) based on those predictions, use procedures to correct, control, or mitigate the consequences of those malfunctions or operations:  (CFR: 41.5 / 43.5 / 45.3 / 45.13)  A2.02 Loss of circulating water pumps	2.7	1
079 Station Air												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		
086 Fire Protection												Randomly selected and removed as described in ES-401 Attachment 1, item 2.c		

ES-401				Pla	nt S					Outlii Jp 2 (	ne Form RO / SRO)	1 ES-4	<del>1</del> 01-2
System # / Name	K 1	K 2	K 3	K 4			A 2	A 3	A 4	G		IR	#
K/A Category Point Totals:				1			1			1	Group Point Total:		10/ 3

di

Facility: SEAB		Date of Exam: 6/15/09				
Category	K/A#	Topic	R	75 C. F. F. F. F. F.	H State State	Only
1. Conduct	2.1.	2.1.5 Ability to use procedures related to shift staffing, such as minimum crew complement, overtime limitations, etc.	IR	#	3.9	1
of Operations	2.1.	(CFR: 41.10 / 43.5 / 45.12)  2.1.45 Ability to identify and interpret diverse indications to validate the response of another indication.  (CFR: 41.7 / 43.5 / 45.4)			4.3	1
	2.1.					
	2.1.					
	2.1.					
	2.1.					
	Subtotal					2
2. Equipment Control	2.2.	2.2.21 Knowledge of pre- and post-maintenance operability requirements.			4.1	1
	2.2.	(CFR: 41.10 / 43.2)  2.2.37 Ability to determine operability and/or availability of safety related equipment.  (CFR: 41.7 / 43.5 / 45.12)			4.6	1
	2.2.					
	2.2.					
	2.2.					
	2.2.					
	Subtotal		745,165			2
3. Radiation Control	2.3	2.3.13 Knowledge of radiological safety procedures pertaining to licensed operator duties, such as response to radiation monitor alarms, containment entry requirements, fuel handling responsibilities, access to locked high-radiation areas, aligning filters, etc.  (CFR: 41.12 / 43.4 / 45.9 / 45.10)			3.8	
	2.3.					
	2.3.					
	2.3.					
	2.3.					
	2.3.					
	Subtotal					1

Facility: SEAE	BROOK	Date of Exam: 6/15/09					
Category	K/A#	Topic	R	0	SRO-Only		
			IR	#	IR	#	
4. Emergency Procedures / Plan	2.4.	2.4.4 Ability to recognize abnormal indications for system operating parameters that are entry-level conditions for emergency and abnormal operating procedures.			4.7	1	
		(CFR: 41.10 / 43.2 / 45.6)					
ria);	2.4.	2.4.29 Knowledge of the emergency plan.			4.4	1	
		(CFR: 41.10 / 43.5 / 45.11)					
	2.4.						
	2.4.						
	2.4.						
	2.4.						
	Subtotal					2	
Tier 3 Point Tot	al			10		7	

Tier / Group	Randomly Selected K/A	Reason for Rejection
Tier 1/ Group 1	000055 Station Blackout	The first KA drawn was "EA2 Ability to determine or interpret the following as they apply to a Station Blackout", EA2.05 "When battery is approaching fully discharged".
		No additional plant change or change in strategy is anticipated when the station batteries are discharged.
		Reselected K/A category to EA2.02, RCS core cooling through natural circulation cooling to S/G cooling.
Tier 1/ Group 1	000058 Loss of DC Power	Randomly drawn K2 was rejected because it contains no K/A statement with a RO importance greater than 2.5.
		Reselected K/A category to K1
Tier 1/ Group 2	000051 Loss of Condenser Vacuum	Randomly drawn AA1 was rejected because it only contains one K/A statement with an RO importance greater than 2.5, "Ability to operate and / or monitor 'rod position' as it applies to the loss of condenser vacuum." No suitable question could be generated from that constraint.
		Reselected K/A category to AA2.
Tier 1/ Group 2	000076 High Reactor Coolant Activity	The first K/A drawn was Generic KA "2.4.34, Knowledge of RO tasks performed outside the main control room during an emergency and the resultant operational effects".
		This was rejected because the topic does not have any clear actions that an RO would conceivably be required to perform outside the control room under theses circumstances.
		Reselected K/A category to generic K/A 2.2.25, Knowledge of the bases in Technical Specifications for limiting conditions for operations and safety limits.
Tier 2/ Group 1	025 Ice Condenser	During exam outline generation the K/A associated with Ice Condenser (025) were suppressed. This system is N/A to Seabrook.
Tier 2/ Group 1	059 Main Feedwater	Randomly drawn K6 was rejected because it contains no K/A statement with a RO importance greater than 2.5.
		Reselected K/A category K3
Tier 2/ Group 1	064 Emergency Diesel Generator	Randomly drawn K5 was rejected because it contains no K/A statement with a RO importance greater than 2.5.
		Reselected K/A category K4

Tier / Group	Randomly Selected K/A	Reason for Rejection
Tier 2/ Group 1	073 Process Radiation Monitor	Randomly drawn K2 was rejected because it contains no K/A statement with a RO importance greater than 2.5.
		Reselected K/A category K4
Tier 2/ Group 1	078 Instrument Air	Category 5 was randomly drawn for the 2 <sup>nd</sup> item in this KA. (7 KA categories in Tier2/Group1 had to be sampled twice in order to generate 28 total questions. This was done in accordance with the ES 401, attachment 1 sampling methodology).
		Category K5 was then rejected because it contains no K/A statement with a RO importance greater than 2.5.
		Reselected K/A category K2. Randomly drawn A2 was also rejected because it contains no K/A statement with an RO importance greater than 2.5.
		Reselected K/A category K4.
Tier 2/ Group 2	016 Non-nuclear Instrumentation	During exam outline generation the K/A associated with Non-Nuclear Instrumentation (016) were suppressed.
		This system is N/A to Seabrook
Tier 2/ Group 2	027 Containment Iodine Removal	During exam outline generation the K/A associated with Containment Iodine Removal (027) were suppressed.
		This system is included as part of the Containment Building Spray System at Seabrook
Tier 2/ Group 2	033 Spent Fuel Pool Cooling	Randomly drawn A4 was rejected because it contains no K/A statement with a RO importance greater than 2.5.
		Reselected K/A category A2
Tier 2/ Group 2	072 Area Radiation	Randomly drawn K2 was rejected because it contains no K/A statement with a RO importance greater than 2.5.
	Monitoring	Reselected K/A category K4
Tier 2/ Group 2	079 Station Air	Randomly drawn K5 was rejected because it contains no K/A statement with a RO importance greater than 2.5.
		Reselected K/A category A4
Tier 2/ Group 2	079 Station Air	Plant system de-selected after review of aggregate balance of outline plan as described in ES-401, section D.1.d.
		Two Station air supply questions had already been selected. Reselected Plant System 002, Reactor Coolant as a replacement.

Tier / Group	Randomly Selected K/A	Reason for Rejection
Tier 1/ Group 1	062 Loss of Nuclear Service Water	Original K/A selected was G 2.4.30, Emergency Procedures, Knowledge of events related to system operation/status that must be reported to internal organizations or external agencies, such as the States, the NRC, or the Transmission system operator.
		No discriminating question could be generated within this narrow scope for the SW system.
		Randomly reselected within the generic category of 2.4 Emergency procedures for 062 Loss of Service Water and chose G 2.4.11, knowledge of abnormal condition procedures.
Tier 1/ Group 2	005 Inoperable/ Stuck Control Rod	Original K/A selected was G 2.4.35, Emergency Procedures, Knowledge of local auxiliary operator task during an emergency and the resultant operational effects.
		No local Auxiliary Operator tasks are performed with a stuck control rod for Seabrook.
		Randomly reselected within the APE 005, Inoperable/Stuck Control Rod, to choose AK3.04, Tech Spec limits for inoperable rods.
Tier 1/ Group 2	W/E13 Steam Generator Overpressure	Original K/A selected was EK3/EK3.3, Knowledge of the reasons for the following responses as they apply to the (Steam Generator Overpressure): EK3.3 Manipulation of controls required to obtain desired operating results during abnormal, and emergency situations.
		SG overpressure conditions are addressed by the H-2 yellow path procedure which are optional entry procedures. No discriminating operationally valid question could be generated that did not also have a more overriding safety concern to address.
		Reselected within W/E13 Steam Generator Overpressure and selected EA1: Ability to operate and/or monitor the following as they apply to the (Steam Generator Overpressure): EA1.1 Components, and functions of control and safety systems, including instrumentation, signals, interlocks, failure modes, and automatic and manual features.

Tier / Group	Randomly Selected K/A	Reason for Rejection
Tier 1/ Group 2	060 Accidental Gaseous Radwaste Release	Original K/A selected was K3/AK3.02, Knowledge of the reasons for the following responses as they apply to the Accidental Gaseous Radwaste: AK3.02 Isolation of the auxiliary building ventilation.
		No automatic or manual actions are performed to isolate auxiliary building ventilation for Seabrook.
		Reselected within the APE 060 Accidental Gaseous Radwaste Release and selected AK2.02: Knowledge of the interrelationship between the Accidental Gaseous Radwaste Release and the following: AK2.02: Auxiliary Building Ventilation.
Tier 2/ Group 1	026 Containment Spray System	Original K/A selected was G 2.4.47, Ability to diagnose and recognize trends in an accurate and timely manner utilizing the appropriate control room reference material.
		Re-chose K/A to minimize open reference material questions on the test.
		Randomly reselected within 026 Containment Spray and within generic category 2.4, Emergency Procedures/Plan, to choose G 2.4.4 Ability to recognize abnormal indications for system operating parameters that are entry level conditions for emergency and abnormal operating procedures.
Tier 2/ Group 2	001 Control Rod Drive System	Original K/A selected was K5/AK5.13, Knowledge of the following operational implication as they apply to the CRDS, K 5.13 Effects of past power history on xenon concentration and samarium concentration.
		Question topic is tied to GFES subject material vs. initial license operator test material.
		Reselected within K5 of the 001 Control Rod Drive system and selected K5.65: Knowledge of the following operational implication as they apply to the CRDS K5.65, CRDS circuitry, including effects of primary/secondary power mismatch on rod control

Tier / Group	Randomly Selected K/A	Reason for Rejection
Tier 2/ Group 2	017 In-Core Temperature Monitoring	Original K/A selected was K3/K3.01, Knowledge of the effect that a loss or malfunction of the ITM system will have on the following: K3.01 Natural Circulation indications.
	System	The core exit thermocouples are one of 4 diverse and widely redundant subsystems used to verify natural circulation at Seabrook. A suitable operationally valid and discriminating question could not be generated for this topic. Additionally, only limited K/A statements are contained within this plant system.
		Reselected within the 017 In-Core Temperature Monitoring system and selected K4: Knowledge of the ITM system design feature(s) and/or interlock(s) which provide for the following: K4.01, Input to Subcooling Monitors.
Tier 3/ Category 1	Conduct of Operations	Original K/A selected was G 2.4.38, Knowledge of the station's requirements for verbal communications when implementing procedures.
		Generic KA is too simplistic to write a valid discriminating question.
		Randomly reselected within the Conduct of Operations generic category to choose G 2.1.15. Knowledge of administrative requirements for temporary management directives, such as standing operating orders, night orders, Operations Memos, etc
		SRO SCREENING BELOW
Tier 1/ Group 1	062 Loss of Nuclear Service	Generic Knowledge and Abilities 2.1.28 selected during SRO random sampling.
	Water	KA statement is tied to 10CFR55.41, but not tied to 10CFR55.43 (as identified in NUREG -1122, rev.2, supp 1).
		Reselected KA Statement 2.2.25.
Tier 1/ Group 2	003 Dropped Control Rod	Generic Knowledge and Abilities 2.1.31 selected during SRO random sampling.
		KA statement is tied to 10CFR55.41 and 55.45, but not tied to 10CFR55.43 (as identified in NUREG -1122, rev.2, supp1).
		Reselected KA Statement 2.2.38.

Tier / Group	Randomly Selected K/A	Reason for Rejection
Tier 2/ Group 2	041 Steam Dump/Turbine Bypass Controls	Generic Knowledge and Abilities 2.2.39 selected during SRO random sampling.
		Equipment Category does not have any associated Technical Specifications with 1 hour or less action statements.
		Reselected KA Statement 2.4.9.
Tier 2/ Group 2	034 Fuel Handling	Selected during SRO random sampling.
		Randomly drawn K2 was rejected because it contains no K/A statement with a SRO importance greater than 2.5.
		Reselected K/A category K4
Tier 3/ Category 2	2. Equipment Control	Selected generic KA 2.2.13 during SRO random sampling.
		KA statement is not identified as being tied to 10 CFR 55.43.
		Reselected KA Statement 2.2.21
Tier 1/ Group 1	026 Loss of Component Cooling Water	Original K/A selected was G 2.4.30, Knowledge of events related to system operation/status that must be reported to internal organizations or external agencies such as the State, the NRC or the Transmission system operator.
		No discerning, operationally valid SRO level question that also meets the 10CFR55.43 criteria and still relates to this KA topic could be generated.
		Reselected within Generic K/A category 2.4 Emergency Procedures/Plan and selected G 2.4.4, Ability to recognize abnormal indications for system operating parameters that are entry level conditions for emergency and abnormal operating procedures.
Tier3/ Group 2	2. Equipment Control	Originally selected generic category KA 2.2.20, Knowledge of the process for managing troubleshooting activities. During NRC review of initial exam submittal no suitable discriminating RO level question could be generated. Reselected within Generic K/A category 2, Equipment Control and selected: G 2.2.22; Knowledge of limiting conditions for operations and safety limits.
Tier 3/ Group 4	4. Emergency Procedures / Plan	Originally selected generic category KA 2.4.41, Knowledge of the emergency action level thresholds and classifications. During NRC review of initial exam submittal no suitable RO level question using closed reference material could be generated. Reselected within Generic K/A category 4, Emergency Procedures / Plan and selected 2.4.35; Knowledge of local auxiliary operator tasks during an emergency and the resultant operational effects.