


70-925


*George France*

**CIMARRON CORPORATION**

P.O. BOX 25861 • OKLAHOMA CITY, OKLAHOMA 73125



October 18, 1989



**CERTIFIED MAIL  
RETURN RECEIPT REQUESTED**

Mr. Davis Hurt  
U.S. Nuclear Regulatory Commission  
Uranium Fuel Licensing Branch  
Division of Fuel Cycle & Material Safety  
Office of Nuclear Material Safety & Safeguards (NMSS)  
Washington, D.C. 20555

RE: License SNM-928; Docket 70-925  
Amendment Request: On-site Disposition of  
Uranium Containing Soils Meeting NRC  
Branch Technical Position Option 2 Criteria

Dear Mr. Hurt:

Attached are four (4) additional copies of Cimarron Corporation's October 9, 1989, submittal relating to the above referenced amendment request.

Sincerely,

*J. C. Munson*  
for John C. Stauter, Director  
Environmental Affairs

JCS:gw

Enclosures

JAN 16 1990

Docket No. 70-925

Cimarron Corporation  
ATTN: J. C. Stauter, Director  
Nuclear Licensing and Regulation  
P. O. Box 25861  
Kerr-McGee Center  
Oklahoma City, OK 73125

Dear Dr. Stauter:

Enclosed for your information is a staff memorandum describing our meeting of December 1, 1989, concerning the Cimarron and Cushing sites.

Sincerely,

Original Signed by

Glen L. Sjoblom, Deputy Director  
Division of Industrial and  
Medical Nuclear Safety  
Office of Nuclear Material Safety  
and Safeguards

Enclosure: Memorandum of December 28, 1989  
from R. D. Hurt to G. L. Sjoblom

cc: Dale McHard  
Oklahoma State  
Department of Health

Distribution: w/o enclosure

NRC File Center : Docket No. 70-925  
NMSS R/F : IMSB R/F  
RDHurt : JSwift  
Beveridge/Cornell 1-23 : GFrance, RIII  
GLSjoblom

PDR  
IMAF R/F  
FBrown  
GComfort

(DH/CIMARRON CORPORATION)

OFC : IMAF <i>RDH</i>	: IMI <i>FB</i>	: IMAF <i>RDH</i>	: IMSB
NAME : RDHurt: jc	: FBrown	: JSwift <i>for</i>	: GLSjoblom
DATE : 01/12/90	: 01/12/90	: 01/12/90	: 01/12/90

# CIMARRON CORPORATION

P.O. BOX 25861 • OKLAHOMA CITY, OKLAHOMA 73125

October 9, 1989

FEDERAL EXPRESS

Mr. A. Bert Davis  
U.S. Nuclear Regulatory Commission  
Region III  
799 Roosevelt Road  
Glen Ellyn, IL 60137

Re: License SNM-928; Docket 70-925  
Amendment Request: Onsite Disposition of Uranium Containing  
Soils Meeting NRC Branch Technical Position Option 2 Criteria

Dear Mr. Davis:

Cimarron Corporation submitted on June 29, 1988, a request for the onsite disposition of uranium contaminated soils at the Cimarron Facility. A letter dated February 3, 1989, from Jerry J. Swift of the NMSS office, requested additional information based on NRC's and State of Oklahoma's review of our request. Cimarron Corporation responds to each of the NRC and State comments in Attachments A and B to this letter. Questions related to regional and site geology/hydrology are answered in the detailed "Site Investigation Report" by James L. Grant and Associates (Attachment C) and demonstrates that the soils to be left on site as proposed under NRC's Branch Technical Position do not pose any environmental concerns.

Cimarron requests your prompt review and authorization of the proposed site program. Please contact me at your convenience should you have any questions related to these materials.

Sincerely,



J.C. Stauter, Director  
Environmental Affairs

JCS:wpc

Attachment

cc: Mr. Leland C. Rouse, NRC-NMSS  
Mr. Dale McHard, OSDH

0008s

ATTACHMENT A

CIMARRON CORPORATION

RESPONSE TO NRC COMMENTS  
PROVIDED BY LETTER DATED FEBRUARY 3, 1989

NRC Comment 1.a.: Please provide a map showing existing pipelines and routes of old pipelines.

Cimarron Corp.  
Response: Exhibits I and II respectively are maps showing the Underground Piping Systems and Facilities as they existed during operations and after decommissioning. During excavation of piping, soils were analyzed and any contaminated materials removed.

NRC Comment 1.b.: Please identify, preferably on a map similar to Exhibit 1A (the borehole map) of the March 21, 1988 Request for Amendment, the areas and depths of possible soil contamination. It is not clear to us at present how the 400,000 and 3,000,000 ft<sup>3</sup> estimates of Table 1 in your submittal were derived.

Cimarron Corp.  
Response: Material volume estimates were derived from gamma logging of boreholes drilled in potentially contaminated areas at the Cimarron Facility. The borehole gamma logging results were compared to data derived from logging test drums of known concentration. Cimarron Corporation stresses that this estimation technique was used to identify those areas where contamination existed and is believed to be conservative. We are confident, however, that the borehole logging method delineated suspect areas which require evaluation and excavation.

The borehole program was undertaken to provide the bounds of volume and activity information required by NRC for evaluation of Cimarron Corporation's request for onsite disposal of uranium and thorium contaminated soils in accordance with the Branch Technical Position. The borehole program encompassed the area surrounding the uranium facility and the potentially impacted buried pipeline routes to obtain the best information to make these impacted area estimates. Approximately 300 boreholes were drilled on gridded 50 foot centers and gamma logged with reference to known standards. Approximately 7,500 gamma logging measurements were obtained by measuring at one foot intervals in each borehole.

Based upon computer interpolation of the gamma data between boreholes, the greater than Option #1 and less than Option #2 concentration soil volume was estimated at 400,000 and 3,000,000 ft<sup>3</sup> for material located within four feet of the surface and deeper than four feet, respectively. No material was identified as being above Option 2 concentration criteria deeper than four feet.

Probes used for gamma logging were calibrated daily using a series of specially prepared 55 gallon drums containing known uniform concentrations of uranium and/or thorium. A three inch diameter PVC access pipe was installed down the center of each drum to provide a portal for the probe. The sodium iodide (Na I) probe was placed in the center of each drum standard and the count rate recorded. In addition, soil samples were collected from randomly selected depths of several boreholes and analyzed for U-238, U-235, U-234, Th-232 and Th-228 to provide additional reference data.

The soil sample isotopic results were compared with the counting results to enhance the accuracy of the estimated in-situ concentrations. Although a strong linear statistical correlation was not demonstrated over a large count rate versus concentration range, the logging data and soil isotopic analyses support the gamma logging technique as adequate for use as a screening tool in identifying Option 1 and 2 concentration materials. Additional information concerning the logging data evaluation is included in the attached Site Investigation Report performed by James L. Grant and Associates.

The approximately 7,500 gamma logging count rate measurements were entered into a computer database<sup>1/</sup>, analyzed and an estimate of the location and volume of soil requiring removal generated. Cimarron Corporation believes the 3,000,000 ft<sup>3</sup> volume estimate for material proposed to be left in-situ below at least 4 feet of soil in accordance with Option No. 2 of the Branch Technical Position is conservative. The actual volume is believed to be less because of the computer model bounds used to generate the volume estimate and the distribution of the contaminated soil. The computer model calculates volumes using the assumption that concentrations are uniform and increase/decrease uniformly in all directions between the logging point grid and the next nearest grid location.

---

\* <sup>1/</sup> CPS-3 by Radian Corporation, 8501 MoPac Blvd., Austin, Texas, 78720-1088  
(Volumetric Algorithm in CPS-3 software)

The count rate which represents the cut-off between Option No. 1 and Option No. 2 concentrations is also conservative. The range of values obtained from the drum source calibration program and the count rate reflecting a known sample concentration equivalent to the Option 1 cutoff criterion was identified, this value was near 26,000 cpm.

In summary, the borehole gamma logging program properly identifies suspect areas, but is not intended to provide an accurate or detailed isotopic concentration to individual borehole depth and areal locations. The volume estimates derived for soil which exceed Option No. 1 concentrations but are less than Option No. 2 levels are, therefore, conservative upper bound type estimates.

NRC Comment 1.c.:

Please translate the borehole logging data of Exhibit 2A of your March 21 submittal into microcuries of uranium or thorium per gram of soil, at least for the potentially contaminated areas.

Cimarron Corp.  
Response:

Borehole gamma logging was used to identify areas which could contain materials greater than Branch Technical Position Option No. 1 uranium equivalent concentration criteria of 30 pCi/g. The technique provides a screening method for identification of areas suspected to exceed the criteria only and is not intended to provide detailed radionuclide concentration data. The borehole program identified areas which meet the applicable concentration criteria, i.e. at or below the established concentration.

Areas which have been identified to contain Option 2 concentrations of uranium by gamma borehole logging will be evaluated as required when an area is being excavated to demonstrate that the appropriate release criteria have been met. Both gamma logging and sample collection for gamma pulse height analysis will be used as methods to evaluate soil concentrations at that time.

Gamma logging will continue to be used as a screening tool to define the extent of impacted soil. In addition, samples will be collected from each area and analyzed by gamma pulse height analysis to determine the uranium activity. Soil samples collected will be placed into 500 ml bottles and analyzed. The analytical accuracy for samples analyzed using the Cimarron Facility NaI detector based gamma pulse height system has been verified by ORAU. Discussion of analysis comparison results with Mr. Davis Hurt of NRC-NMSS indicates that Cimarron Corporation's analysis system is acceptable.

Each excavated area, when decontamination is believed to be complete, will be gridded and probed at 2 meter intervals and a representative number of the grid intervals sampled for gamma spec. analysis. In unexcavated areas, the 10 meter grid and sampling program will be maintained. The analysis results for each sample will be compared to the Option 1 or Option 2 criteria. If the concentration exceeds the applicable action criterion the area will be re-excavated and resampled at locations specified by the Cimarron Facility Manager. Cimarron Corporation will maintain these sample results to demonstrate that all required contaminated soil removal is complete.

Gamma logging will also be used to probe at depths below the surface as material is excavated to identify contaminated soil below the surface which may exceed the Option 1 or Option 2 criteria, as appropriate. Excavated material will be sorted by inserting a NaI gamma logging probe into each bucket of soil at three locations and obtaining a count rate at each location. The count rate results will be used to determine into which pile the material should be placed (e.g. material stored for future placement into the designated area). Newly stockpiled material will be sampled by obtaining representative samples of the material placed in each pile and using these samples to prepare a composite sample for that pile. Composite samples will be analyzed using the Cimarron Facility gamma pulse height system.

All sample and gamma logging locations will be identified using a standard coordinate system so that locations can be easily referenced. As a quality assurance measure, randomly selected samples will be sent to the Kerr-McGee Technical Center for independent alpha pulse height analysis.

NRC Comment 2.:

On page 3 of your June 29, 1988 submittal, you state that the uranium in the soil can be assumed to be 3 percent soluble. In the attachment to the June 29 submittal that addresses previous NRC questions you refer (p.2) to Exhibit 2 for solubility data on the uranium found in soil samples. The only solubility data we can find is in Exhibit 3 of your March 21 submittal. The Exhibit 3 data show solubilities ranging from 6 percent to 42 percent. Please clarify this inconsistency.

Cimarron Corp.  
Response:

The statement on page 3 of the Cimarron Corporation June 29, 1988 submittal refers to 3 percent enrichment in U-235, not 3 percent solubility. The solubility data are provided in Exhibit 3 of that submittal.

NRC Comment 3.:

Ground Water Issue

Cimarron Corp.  
Response:

The ground water issues related to this comment have been comprehensively addressed by James L. Grant and Associates in their report titled "Site Investigation Report for the Cimarron Corporation Facility, Logan County, Oklahoma." A copy of this report is attached as part of this submittal. Briefly:

Consideration of the site geological and hydrological features, the characteristics of the source, the climatology and other pertinent factors shows both the material to be removed to the designated burial area and that to be left in-situ beneath at least four feet of clean soil will not represent a real or potential threat to groundwater or surface-water use in the surrounding area. Model simulations, based on site-specific data, show the potential for uranium to leach and reach the water table is very low and that if such occurs, the period required would be many tens to hundreds of thousands of years.

The old burial trenches, which have been excavated and are awaiting back filling, were located at the base of the bluff overlooking the Cimarron River flood plain and water depth in that location is strongly influenced by the river's flood plain. The designated burial area and the in-situ areas are at much higher elevations and are not influenced by the flood plain status. The wells installed clearly show the depth to water in these latter areas is greater than 20 feet.



Based on the existing ground water quality, the ready availability of supplied water and the area developmental potentials, Cimarron is not aware of any likely potential ground water uses within a mile of the site that would be hydrologically influenced by the site. The surface water potential use is similarly unlikely for the same reasons.

ATTACHMENT A

EXHIBIT I

---

(OCT 1989)

A-7 0008s  
License SNM-928; Docket 70-925

**THIS PAGE IS AN  
OVERSIZED DRAWING OR  
FIGURE,  
THAT CAN BE VIEWED  
AT THE RECORD TITLED:  
“BOREHOLE & UNDERGROUND  
PIPING MAP  
EXHIBIT I”  
DRAWING NO. ATP-C-11**

**WITHIN THIS PACKAGE... OR  
BY SEARCHING USING THE  
DOCUMENT/REPORT NO.**

**D-01**

ATTACHMENT A

EXHIBIT II

---

(OCT 1989)

A-8 0008s  
License SNM-928; Docket 70-925

**THIS PAGE IS AN  
OVERSIZED DRAWING OR  
FIGURE,  
THAT CAN BE VIEWED AT THE  
RECORD TITLED:  
“FACILITIES AFTER  
DECOMMISSIONING  
EXHIBIT II”  
DRAWING NO. ATO-C-11  
WITHIN THIS PACKAGE... OR  
BY SEARCHING USING THE  
DOCUMENT/REPORT NO.**

**D-02**

ATTACHMENT B

CIMARRON CORPORATION

RESPONSE TO STATE OF OKLAHOMA COMMENTS  
ATTACHED TO LETTER DATED FEBRUARY 3, 1989

State Comment 1.(a): In regard to burial of the relocated wastes, SFC should specify the dust suppression methods to be used. Water spraying, if contemplated for dust suppression, could exacerbate the groundwater contamination issue by speeding leaching of contaminants from the wastes.

Cimarron Corp.  
Response: Water spraying will be used to control dust emissions. The amount of water used for dust control will not be sufficient to generate leachate or result in the leaching of contaminants from the soil. Water seepage into the soil from a typical rain event will exceed the amount of water used for dust control by many orders of magnitude. Operations would be conducted in a quagmire if anything close to generation of leachate occurred from application of water spray for dust suppression. Further, the detailed site investigation demonstrates the negligible leaching potential.

State Comment 1.(b): SFC should specify the final grade slopes proposed for the relocation burial area, preferably supported with a detailed final grade topographic map of the burial site. The Permian sediments (and the soils derived from them) in the area of the Facility are subject to severe erosion. Oklahoma requires that municipal waste landfills, for example, be graded so that final cover slopes are no steeper than 25 to 1 (horizontal or vertical).

Cimarron Corp.  
Response: The final grade of the material relocation area will match the natural grade of the area existing prior to excavation. The final slope of the cover will be no greater than 25H to 1V after backfilling and site closure is complete. A vegetative cover will be established to control erosion. Surrounding areas of the property are gently rolling and routinely farmed without any evidence of gullying. Cimarron, as part of the final decommissioning closeout, will provide survey information as to location and elevation of the relocation burial area.

State Comment 1.(c):

SFC should provide complete details on the methodology used to measure activity of the radioisotopes placed in the calibration drums, and how the calibration drums can be related to the measurement of isotopes in place in the soil. The correlation between calibration drums and natural soil measurement is not fully demonstrated. The relationship of known isotope mixes in the drums to gross gamma count detected by the probes does not appear to be dependably quantifiable.

Cimarron Corp.  
Response:

The instrumentation used for the gamma logging was calibrated using a series of specially prepared 55 gallon drums containing known uniform concentrations of uranium and/or thorium. A three inch diameter PVC access pipe was installed down through the center of each drum to provide a portal for the probe. Calibration of the system was accomplished by inserting the center of the probe into the PVC pipe so the probe was also located at the center of each drum. The count rate obtained at this position was recorded for each drum standard.

In addition, soil samples were randomly collected for isotopic analysis (U-238, U-235, U-234, Th-232 and Th-228) at selected depths from several boreholes. These data were used along with the calibration drum data to develop a screening level for gamma logging to categorize material as less than Option 1, greater than Option 1 but less than Option 2, etc.

Please see Cimarron Corporation's responses to NRC Comment 1.b. in Attachment A of this submittal and State Comment 1.(d) of this Attachment for additional information relating to this issue.

State Comment 1.(d):

It does not appear that SFC can reliably measure the relative quantities of isotopes in the soil by means of gross gamma scintillation probes. The soil probe data in the application shows little correlation between probe response and what is assumed (but not demonstrated by SFC) to be gamma spectrometric measurements of soil samples.

Cimarron Corp.  
Response:

Material volume estimates were obtained from gamma logging of boreholes drilled in potentially contaminated areas at the Cimarron Facility. Cimarron Corporation emphasizes that this technique is a screening tool only and not intended to provide an isotopic analysis. We are confident the method appropriately identifies suspect areas requiring additional evaluation. Please see Cimarron's response to NRC comment 1.b. in Attachment A.

State Comment 1.(e):

SFC should provide complete and detailed data on the chemical species in which the radioactive isotopes were bound when they entered the soil or water, and on the probable geochemical fate of those species in the shallow soil/bedrock environment at the Facility. The relationship between the various isotopes and other elements or compounds with which they were associated must be established to be able to characterize the non-radioactive aspects of any groundwater contamination at the Facility. Uranium is especially mobile in highly oxidizing environments, which could result in highly variable relationships between gamma count and actual isotope content of the soils and groundwater at the Facility. The time in which the contaminants have been in the subsurface is also of interest, as that will affect the observed gamma count rates, which are strongly dependent on the parent-daughter isotope relationships.

Cimarron Corp.  
Response:

These points are comprehensively addressed in the James L. Grant and Associates report of the site investigation study for the Cimarron Facility. The monitor well analyses show there has been no impact to ground water associated with the uranium in soil; any impacts are confined downgradient of the previously closed lagoons and are steadily decreasing. The isotopic analyses address the isotope relationships.

State Comment 1.(f):

SFC has not demonstrated that the wastes proposed for burial are insoluble. We also note that SFC appears to refer to 3% uranium enrichment on Page 3 of the revised application, in a context where it could be mistaken for a reference to 3% uranium solubility.

Cimarron Corp.  
Response:

The statement on Page 3 of the Cimarron Corporation June 29, 1988 submittal refers to 3 percent enrichment in U-235, not 3 percent solubility. The solubility issue is fully evaluated and is presented in Exhibit 3 of that submittal.

State Comment 1.(g):

It is not clear from the application, but it appears possible that soils meeting Option 1 Standards could be left in place as "cover" for Option 2 materials and remain within the plan proposed by SFC. Is this intended, and if so, is it within NRC's guidelines?



Cimarron Corp.  
Response:

Cimarron Corporation's interpretation of the Branch Technical Position is that soils with concentrations less than the Option 1 levels can be left in place without any cover requirements. Soil with concentrations greater than Option 1 levels but less than Option 2 levels may be left in place if a four foot soil cover is provided. Should soils meeting Option 1 concentration levels exist as part of the "cover" over Option 2 materials, Cimarron Corporation plans to leave this soil in place. We believe that this is permitted and appropriate under the guidance provided in the Branch Technical Position.

State Comment 1.(h):

The soils to be left in place should be delineated on a map, with distinct representation of which soils are to be treated as described on pages 4 through 6 of the revised application.

Cimarron Corp.  
Response:

The utility for such a "map" prior to beginning the soil reclamation program is not apparent. Cimarron's characterization program has identified the general areas meeting the option 1 and 2 criteria, but as has been stressed, additional evaluation will be done during removal to assure appropriate criteria are satisfied. Isopleth diagrams are attached (Annex I to Attachment B) which show the general areas and depths identified by the borehole gamma logging and that will be treated as described on pages 4 through 6 of the revised application dated June 29, 1988.

State Comment 1.(i):

Were soil and water samples taken in the areas downgradient from the backfilled waste ponds? It is not clear from the application how extensively these areas were sampled, but they should be sampled in assessing the groundwater and soil contamination issues. It appears that more sampling points may have been located upgradient from some of the ponds than downgradient.

Cimarron Corp.  
Response:

Soil and water samples were taken in areas downgradient from the previously cleaned, backfilled and released waste ponds. Additional wells were recently installed as part of the site characterization program conducted by James L. Grant and Associates. As is evident from the report, extensive sampling has been done and the status of the site has been assessed adequately.

State Comment 1.(j):

Where are wells 3011 and 3012 (see page 15, revised application)?

Cimarron Corp.  
Response:

The reference to well numbers 3011 and 3012 on page 15 of the June 29, 1988 revised application should be changed to well numbers 1311 and 1312. A page with these corrections is attached (Annex II to Attachment B) for insertion into that submittal.

State Comment 1.(k): SFC should clarify locations and names of features at the Facility, as the information in the application is unclear and apparently inconsistent in references to the ponds, lagoons, burial pit, and "land fill". All features should be clearly identified on the maps in the application.

Cimarron Corp.  
Response: Exhibits I and II to Attachment A of this submittal are maps which show the borehole, underground piping systems and the facilities to be left in place after decommissioning. These maps include the identification of the pertinent site features.

State Comment 2.(a): Monitoring data appended to the revised application show elevated concentrations of radioactive constituents, nitrates, and fluorides in several of the wells, particularly around the "landfill", which may correspond to the backfilled Waste Pond #1. Some of the concentrations reported exceed both Oklahoma's Water Quality Standards and the U.S. Environmental Protection Agency's Primary and Secondary Drinking Water Standards.

Cimarron Corp.  
Response: The elevated constituents are a result of previous use of the waste pond. The pond has since been cleaned, closed and released. The mechanism resulting in the appearance of uranium in the near downgradient shallow water in this area is addressed fully in the James L. Grant and Associates site investigation report. The presence of these localized concentrations is not germane to the soil disposal application. Further, as demonstrated in the site investigation report, there are not, and will not be, any discernible impacts to either groundwater or surface water potential use.

State Comment 2.(b): Additional data from Oak Ridge Associated Universities shows radioactivity in groundwater downgradient from the old burial area in the northeast part of the site.

Cimarron Corp.  
Response: There are four (4) groundwater monitoring wells located in and near the old burial area in the northeastern part of the Cimarron property. One of the wells is located upgradient, one well is between two of the waste trenches near the downgradient end of the old burial area and two wells are located downgradient. Elevated radioactivity levels have been detected in the well between the two trenches and in the other two downgradient monitoring wells. However, the concentrations drop significantly in the two wells located outside and downgradient of the old burial area. Radioactivity in the upgradient well is at natural background levels.

The wastes in those trenches have been excavated and shipped to a licensed facility. We believe the groundwater quality will steadily improve as any sources have been removed. Cimarron Corporation will continue to monitor, evaluate the results and report the findings to NRC and the State with the facility annual environmental monitoring report.

State Comment 2.(c): Groundwater levels in rainy seasons may be high enough to leach contaminants from the soils in the proposed soil burial and in site areas, which may violate the conditions expressed in NRC's Branch Technical Position. The application does not provide sufficient support for statements that "there are no concerns regarding contact [of the wastes] with groundwater".

Cimarron Corp.  
Response: The Site Investigation Report (Attachment C) submitted with this material clearly corroborates the referenced statement. In addition, a "Hydrologic Water Balance" for the Cimarron Facility was also done (Annex III to Attachment B of this submittal) and includes an evaluation of groundwater recharge at the facility. This water balance report was used by James L. Grant and Associates in evaluating the potential for local impacts. The evaluation shows there is no basis for the stated concern.

State Comment 3.(a): SFC should provide a complete assessment of the groundwater system at the site, including potentiometric maps and analyses of the groundwater sufficient to show extent and degree of radioactive and chemical contamination. Sample analyses should test for any chemical constituents found in the materials responsible for contaminating the soil that is the subject of SFC's application, as well as any constituents of other processes carried out at the plant that may have contributed to contamination of the groundwater.

SFC should include in the assessment an evaluation of the degree to which the material proposed for burial has contributed to the groundwater contamination, and a projection of continuing effects on groundwater (chemical as well as radiological) if the soils are left in place. The assessment should also contain an evaluation of the population that is or could be affected by the groundwater contamination.

Cimarron Corp.  
Response: The James L. Grant and Associate's Site Investigation Report is fully responsive to the matters stated above. There is no reasonably identifiable population that is or could be impacted by conditions at the site.

State Comment 3.(b):

The application states that wells 1306, 1309, and 1310 are for monitoring the unsaturated zone, but that they have water in them during the rainy season. This implies that the seasonal high water table may be notably above that measured in the other wells, and that additional work is needed to assure proper determination of the seasonal water table.

Cimarron Corp.

These wells were constructed near the wastewater treatment pond in the mid 60's to a predetermined depth of 20 feet. A groundwater hydrologist was not involved with these monitor wells and well construction information is not available. Periodically, these shallow wells have been noted to have a small amount of standing water. Although some amount of perched water develops on the shale layers in the unsaturated zone after periods of heavy rainfall and recharge, it is uncertain if these wells monitor a single perched zone or provide a temporary collection point for several shale layers penetrated by the well. Information derived from these wells is not considered to be reliable. The wells do not represent bonafide monitoring of the unsaturated zone.

More recently constructed monitor wells in the area, namely Wells 1320, 1325, 1335 and 1336, provide a more reliable record of seasonal water table fluctuations.

ATTACHMENT B

ANNEX I

Branch Technical Position  
Option 2 Areas

Designated Impacted Areas  
From Gamma Logging Results

**THE FOLLOWING PAGES  
ARE OVERSIZED  
DRAWINGS OR FIGURES,  
THAT CAN BE VIEWED AT THE  
RECORDS TITLED:  
GAMMA PROBE READINGS IN  
COUNTS / MINUTE (C/M)**

**WITHIN THIS PACKAGE...**

**D-03 THROUGH D-31**

ATTACHMENT B

ANNEX II

Replacement Page 15

for Submittal of June 29, 1988

---

(OCT 1989)

B-9

0008s

License 5MM-928; Docket 70-925

permeabilities determined from the tests of wells 1311 and 1312 are reasonable values. For the relocation site, permeabilities ranging from 0.35 to 1.7 feet per day are representative of the upper part of Garber Sandstone.

Direction and Rate of Groundwater Movement - Groundwater movement is to the north-northwest towards the Cimarron River. The difference in potentiometric surface elevation between monitor wells 1311 and 1312 along the direction of groundwater movement is 3.3 feet across a horizontal distance of 230 feet, which is equivalent to a hydraulic gradient of approximately 76 feet per mile. This relatively steep gradient is believed due to entrenchment of the prairie surface by the Cimarron River and its tributaries in the immediate vicinity. Calculations presented in Appendix C show the average velocity of groundwater movement through the upper part of the Garber Sandstone to be between 0.03 and 0.12 foot per day. Assuming the maximum velocity of 0.12 foot per day, groundwater would traverse the 230 feet along the hydraulic gradient between monitor wells 3011 and 3012 in approximately 1,917 days (5.3 years).

#### Meteorology:

The area climate is characterized by hot summers and moderate winters. July, the hottest month, has an average temperature of 82.9°F and January, the coldest month, averages 38.3°F. The average annual rainfall is 31 inches, received predominantly in the early spring and late fall months. The annual net evaporation rate is approximately 30 inches.



ATTACHMENT B

ANNEX III

Hydrologic Water Balance  
Option Two Burial Site and Vicinity  
Cimarron Corporation Facility  
Crescent, Oklahoma

**HYDROLOGIC WATER BALANCE  
OPTION TWO BURIAL SITE AND VICINITY  
CIMARRON CORPORATION FACILITY  
CRESCENT, OKLAHOMA**

**Prepared by:**

**S.R. Lower  
Area Hydrologist  
Hydrology Department  
Engineering Services Division  
Kerr-McGee Corporation  
May 18, 1989**

## TABLE OF CONTENTS

EXECUTIVE SUMMARY	1
INTRODUCTION	2
CLIMATE	2
Air Flow	3
Precipitation	3
Temperature	7
Evapotranspiration	10
SURFACE CONDITIONS	13
Soils	14
Runoff	17
WATER BALANCE CALCULATIONS	18
CONCLUSIONS	22
REFERENCES	25
APPENDICES	
A. Cimarron Corporation Facility Water Balance Calculations Case 1: Mean Annual Precipitation with Runoff	
B. Cimarron Corporation Facility Water Balance Calculations Case 2: Mean Annual Precipitation with no Runoff	
C. Cimarron Corporation Facility Water Balance Calculations Case 3: Maximum Recorded Annual Water-Year Precipitation with Runoff	

## ILLUSTRATIONS

### FIGURE

1	Water-Year Precipitation at Oklahoma City, Oklahoma 1905-1987	6
2	Cumulative Departure from Mean Water-Year Precipitation/Oklahoma City, Oklahoma 1905-1987	8
3	Map Showing Distribution of Major Soil Types Cimarron Corporation Facility	15

### TABLES

### TABLE

1	Oklahoma City Water-Year (Oct-Sep) Precipitation 1905-1987	4
2	Oklahoma City Water-Year (Oct-Sep) Temperatures 1905-1987	9
3	Mean Monthly Potential Evapotranspiration Cimarron Corporation Facility Crescent, Oklahoma	12
4	Ground Condition Classification and Runoff Coefficients Cimarron Corporation Facility	19
5	Summary of Water Balance Calculations	24

HYDROLOGIC WATER BALANCE  
OPTION TWO BURIAL SITE AND VICINITY  
CIMARRON CORPORATION FACILITY  
CRESCENT, OKLAHOMA  
May 1989

EXECUTIVE SUMMARY

A water balance has been developed for the Cimarron Corporation Facility located near Crescent, Oklahoma, following the procedures outlined in EPA publication EPA/530/SW-168 (Fenn, et al., 1975). Three soils reportedly underlie the study area, all of which are relatively thin (Mickles, et al., 1960). The compositions of the soils typically generate high runoff while precluding rapid infiltration. Based upon this analysis, it is concluded that no percolation (groundwater recharge) can be expected on the Cimarron Corporation Facility during years of average precipitation. Maximizing infiltration by artificially disregarding runoff, some groundwater recharge will occur on some areas of the site during years of average precipitation. Assuming the worst case, some groundwater recharge will occur on all parts of the site during years of maximum recorded annual precipitation.

## INTRODUCTION

The water balance equates the water available to, and lost from, the site specific hydrologic regime. The purpose of this report is to estimate the water balance at the Option Two Burial Site and vicinity at the Cimarron Corporation Facility near Crescent, Oklahoma. Water availability at this site is represented by total precipitation. Water loss is by evapotranspiration, surface runoff, and soil moisture storage.

## CLIMATE

Climatic data for central Oklahoma is collected at Oklahoma City by the National Oceanic and Atmospheric Administration's National Weather Service station located at Will Rogers World Airport. The climate of central Oklahoma is controlled predominantly by the continental effects of the Great Plains Region. The climate is characterized by the National Weather Service as having long and usually hot summers and comparatively mild and short winters. The continental effects of the Great Plains produce pronounced daily and seasonal temperature changes and considerable variations in seasonal and annual precipitation.

## Air Flow

The climate of the Oklahoma City area and vicinity is dominated by continental air masses which assume the temperature and moisture characteristics of the land. Prevailing winds are out of the south except in January and February when northerly breezes predominate.

## Precipitation

The mean annual water-year precipitation for central Oklahoma, based upon the 83-year Oklahoma City record extending from October 1905 through September 1988, is 32.25 inches. Annual water-year (October through September) precipitation during this period ranged from a minimum of 15.48 inches (1910-11) to a maximum of 51.79 inches (1984-85).

Approximately 64% of annual precipitation normally comes in the form of spring and summer thunderstorms. Snowfall averages less than 10 inches per year. The Oklahoma City precipitation record is presented in Table 1 and shown on Figure 1.

A cumulative departure histogram of the Oklahoma City precipitation data is shown on Figure 2. The cumulative

TABLE 1 (continued)

Oklahoma City Water-Year (Oct-Sep) Precipitation 1905 - 1987

Mean Annual Water-Year Precipitation (83 years) = 32.25 inches

Year	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Totals
1951	1.54	1.42	0.05	1.07	1.89	2.95	1.92	5.87	0.76	3.09	2.72	0.25	23.53
1952	0.00	1.97	0.80	0.79	1.01	4.30	4.31	1.63	1.33	4.56	3.98	1.39	26.07
1953	6.17	0.74	1.20	0.43	0.69	0.67	3.04	6.21	0.93	0.79	1.24	0.63	22.74
1954	1.77	0.10	1.34	1.03	1.35	1.50	0.78	9.40	6.68	0.36	3.18	4.73	32.22
1955	8.34	0.04	0.03	0.26	1.31	0.56	2.43	5.07	2.46	2.19	0.86	0.20	23.75
1956	3.76	1.49	1.97	1.49	0.86	2.19	7.32	8.67	8.60	0.63	1.08	5.58	43.64
1957	2.65	2.25	0.72	1.29	0.83	3.39	2.22	3.10	7.17	2.02	3.56	3.87	33.07
1958	0.00	0.60	1.11	0.31	0.69	1.40	2.81	7.60	2.93	8.44	4.10	7.90	37.89
1959	6.08	0.94	3.26	1.47	2.12	0.85	3.01	6.79	5.68	7.69	2.89	1.62	42.40
1960	4.66	0.24	2.48	0.15	1.98	3.35	0.73	1.92	3.86	4.82	2.91	7.37	34.47
1961	2.86	3.81	1.04	1.45	1.02	0.80	2.16	2.64	7.84	1.71	2.26	3.08	30.67
1962	2.43	1.34	0.76	0.21	0.22	3.21	2.77	1.91	2.35	6.19	1.61	1.91	24.91
1963	2.05	2.45	0.89	0.83	2.17	1.30	2.06	5.21	0.77	2.01	4.91	2.96	27.61
1964	0.84	5.46	0.62	0.98	0.85	0.86	3.24	2.14	3.65	1.57	3.37	3.94	27.52
1965	1.00	0.06	2.51	1.05	2.39	1.30	3.68	0.88	2.63	2.38	6.77	2.82	27.47
1966	0.37	0.84	0.45	0.77	0.20	2.49	5.71	4.25	2.27	1.21	1.40	3.15	23.11
1967	2.92	0.40	1.04	2.19	1.02	2.84	3.03	8.40	2.39	1.41	3.75	2.64	32.03
1968	2.40	4.11	1.33	0.20	1.93	3.01	1.66	3.99	4.92	1.42	2.38	6.51	33.86
1969	1.58	0.06	1.44	0.32	0.29	2.09	5.33	6.53	2.45	1.30	0.80	9.64	31.83
1970	3.29	1.03	0.26	0.75	1.95	0.07	0.62	2.68	5.15	4.13	2.13	4.25	26.31
1971	2.62	0.29	2.79	0.21	0.43	1.13	3.10	4.03	1.36	3.22	1.82	2.04	23.04
1972	7.17	2.28	0.84	3.39	0.31	6.76	2.32	3.61	6.31	3.38	1.36	8.00	45.73
1973	3.05	2.81	0.47	0.10	2.68	3.12	4.66	5.01	3.36	0.48	4.42	6.24	36.40
1974	5.57	2.34	1.47	1.99	1.90	1.72	1.92	8.76	4.82	7.71	0.60	1.92	40.72
1975	0.84	1.77	1.30	0.00	0.33	3.09	2.94	4.36	0.88	1.38	1.46	1.53	19.88
1976	1.78	0.12	0.19	0.32	1.40	1.30	2.88	7.97	2.00	4.10	3.08	1.20	26.34
1977	2.41	1.59	0.34	1.26	3.23	1.32	1.65	10.12	4.04	3.75	0.25	0.96	30.92
1978	1.02	2.88	0.70	1.55	0.63	2.73	2.78	7.29	9.94	5.62	3.78	0.72	39.64
1979	1.58	1.93	2.57	1.69	1.29	1.38	2.16	9.00	2.52	0.42	0.60	2.21	27.35
1980	0.99	0.51	1.98	0.19	1.15	2.87	2.97	2.73	7.49	6.45	3.61	1.48	32.02
1981	7.70	2.11	0.20	3.68	0.98	1.63	1.92	12.07	4.06	2.11	1.13	2.86	40.45
1982	1.03	2.78	1.94	2.62	1.71	2.51	2.34	6.88	3.18	0.00	3.18	0.90	29.07
1983	13.18	1.90	0.70	0.35	1.16	4.70	1.79	1.62	3.48	0.30	2.35	1.01	32.54
1984	6.64	2.05	8.14	0.92	3.71	6.60	5.35	1.49	8.34	1.33	2.63	4.59	51.79
1985	5.23	3.73	0.26	0.00	0.68	1.75	4.42	8.21	3.11	0.38	3.29	9.54	40.60
1986	8.00	4.63	1.16	2.45	4.05	2.33	0.41	11.86	6.50	2.99	1.83	4.58	50.79
1987	1.82	1.92	3.75	1.24	0.41	7.85	3.19	1.07	3.59	1.92	1.60	5.19	33.55
Means	3.17	1.87	1.43	1.24	1.32	2.24	3.28	5.02	4.16	2.59	2.60	3.33	32.25
Minimum	0.00	0.00	0.03	0.00	0.02	0.02	0.03	0.43	0.02	0.00	0.17	0.06	15.48
Maximum	13.18	9.63	8.14	5.64	4.05	7.85	11.91	12.07	14.12	9.35	8.34	10.28	51.79



TABLE 1

Oklahoma City Water-Year (Oct-Sep) Precipitation 1905 - 1987  
 Mean Annual Water-Year Precipitation (83 years) = 32.25 inches

Year	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Totals
1905	1.29	1.42	0.70	0.89	0.56	2.28	4.77	1.43	1.54	7.30	8.34	3.93	34.45
1906	1.58	1.25	0.79	1.42	0.53	0.75	4.06	5.60	6.74	1.20	0.80	1.34	26.06
1907	3.42	0.91	2.02	1.25	3.14	0.82	6.73	9.17	12.12	1.27	1.59	4.37	46.81
1908	8.41	3.13	0.03	0.12	0.57	2.13	2.44	7.40	2.44	1.35	1.42	0.53	29.97
1909	1.73	5.29	0.34	0.89	0.53	0.65	4.31	2.72	1.09	0.94	3.08	1.72	23.29
1910	1.31	0.00	0.03	0.17	2.05	0.02	2.93	2.65	0.26	3.74	0.94	1.38	15.48
1911	1.29	0.54	3.86	0.10	1.37	4.11	2.81	2.91	4.75	2.32	3.61	2.64	30.31
1912	1.38	0.39	0.62	0.56	2.72	3.11	1.88	3.88	3.82	5.06	0.57	4.80	28.79
1913	2.52	3.71	3.38	0.05	0.86	1.68	2.41	5.07	0.02	0.62	2.76	1.70	24.78
1914	1.50	0.70	2.74	0.78	3.10	2.08	7.50	3.69	7.23	1.19	5.26	3.62	39.39
1915	2.84	1.01	0.33	4.28	0.39	1.66	3.15	0.59	6.16	2.87	0.68	2.38	26.34
1916	1.73	2.38	1.05	0.37	0.84	1.20	2.11	2.14	1.83	2.98	4.50	1.55	22.68
1917	0.02	0.80	0.04	0.95	0.07	1.55	2.45	8.31	3.09	0.13	1.91	4.28	23.60
1918	5.31	3.53	3.04	0.29	1.52	1.88	5.04	5.66	4.87	0.53	2.28	1.03	34.98
1919	8.12	2.84	0.12	2.09	0.19	4.20	2.11	8.66	2.08	4.02	4.86	3.60	42.89
1920	7.38	2.04	1.37	2.29	1.23	1.93	2.39	1.85	3.80	4.43	0.85	3.79	33.35
1921	0.18	0.33	0.18	1.15	0.64	4.37	7.67	6.83	0.30	2.31	0.19	0.90	25.05
1922	4.30	2.37	0.53	2.74	0.20	2.58	4.27	7.01	3.62	0.15	3.57	10.28	41.62
1923	9.64	2.13	2.06	0.18	0.54	3.83	3.67	2.58	3.15	3.55	3.10	2.65	37.08
1924	0.38	3.04	2.41	0.42	0.69	0.28	4.02	2.63	1.94	2.35	1.83	7.73	27.72
1925	3.12	2.42	0.31	2.13	0.04	1.81	2.66	2.09	3.77	6.69	1.23	9.58	35.85
1926	3.23	0.83	3.79	1.61	1.07	2.23	4.59	1.94	4.95	3.31	4.65	3.63	35.83
1927	7.81	0.63	1.23	0.31	1.33	1.75	3.68	1.92	4.21	2.86	1.98	0.61	28.52
1928	2.74	3.88	2.01	1.61	0.93	5.05	2.08	6.67	1.60	3.37	0.93	2.69	33.56
1929	4.49	1.74	0.57	2.69	1.29	0.25	2.30	7.53	8.76	0.60	3.12	0.16	33.50
1930	6.10	2.11	3.52	0.70	1.48	3.06	4.45	1.18	1.34	0.55	2.17	0.43	27.09
1931	1.83	9.63	1.08	4.92	1.33	0.39	0.93	5.50	14.12	2.40	2.74	1.20	46.07
1932	1.89	0.10	4.86	0.33	1.42	2.88	3.05	3.98	0.15	1.73	5.38	3.37	29.14
1933	3.34	1.88	1.61	2.06	1.15	0.95	1.46	3.61	1.98	0.13	7.44	6.45	32.06
1934	2.03	3.23	0.62	0.60	0.86	3.77	1.81	5.29	4.11	1.11	2.82	1.91	28.16
1935	2.84	2.00	1.81	0.09	0.76	0.21	0.03	5.56	0.23	0.06	0.17	8.49	22.25
1936	1.93	0.06	1.31	1.21	0.12	1.15	2.66	1.82	4.65	0.74	2.44	2.90	20.99
1937	2.25	2.47	1.12	0.92	3.66	5.51	3.06	5.92	5.45	2.75	0.84	1.23	35.18
1938	0.21	1.94	0.38	3.76	0.43	1.16	1.08	2.88	7.83	0.62	5.52	0.06	25.87
1939	2.39	0.84	0.93	0.70	3.35	0.02	4.46	3.89	3.05	5.21	3.14	2.71	30.69
1940	1.72	4.66	1.89	1.12	1.83	0.58	5.90	5.22	5.99	1.08	3.08	4.57	37.64
1941	10.35	1.49	1.07	0.37	1.40	0.53	8.58	0.43	6.97	0.60	4.87	6.73	43.39
1942	2.50	0.73	2.07	0.03	0.89	1.45	2.79	9.76	2.07	0.31	0.77	2.87	26.24
1943	1.28	0.37	2.92	2.30	2.03	3.82	4.87	2.72	6.14	1.79	1.97	2.20	32.41
1944	3.19	2.39	2.30	1.21	2.91	4.16	7.00	2.59	10.05	4.42	3.43	7.42	51.07
1945	0.37	0.27	0.08	3.31	1.92	2.64	2.07	6.92	3.80	0.18	2.39	1.70	25.65
1946	1.22	4.30	1.71	0.53	0.02	0.48	11.91	7.92	2.07	5.13	1.19	2.43	38.91
1947	0.79	1.68	2.35	0.56	3.11	6.18	2.06	4.97	9.42	3.54	1.63	0.17	36.46
1948	0.54	1.78	0.30	5.64	0.56	1.43	1.65	6.91	4.35	1.36	1.70	3.35	29.57
1949	2.97	0.00	1.07	1.76	1.32	0.12	0.85	10.34	2.60	9.35	2.92	1.55	34.85
1950	1.99	0.65	0.07	1.88	2.15	1.26	3.85	7.16	4.94	2.97	2.14	4.46	33.52




Figure 1: Water-Year Precipitation at Oklahoma City, Oklahoma 1905-1987

departure statistical analysis of precipitation typically shows the beginning, end, and duration of relative wet and dry periods.

Review of Figure 2 indicates that precipitation in central Oklahoma is not uniform. Annual precipitation is cyclic in nature, with relative wet and dry periods of several years duration alternating over the long term. Thus, soil moisture infiltration, percolation, and runoff will not be uniform. However, years of unusually high precipitation can and do occur during relatively dry periods. Likewise, years of unusually low precipitation can and do occur during otherwise relatively wet periods.

### Temperature

Annual temperatures in central Oklahoma are relatively uniform. The mean annual temperature, based upon 32 years of temperature data extending from (water-year) 1956-57 through 1987-88, is 59.8 degrees (F). Annual temperatures during this period ranged from a minimum of 58.3 degrees (1979-80) to a maximum of 61.7 degrees (1965-66). Record highest and lowest temperatures are -4 degrees (January 1959) and 110 degrees (August 1980), respectively. A 32-year temperature record for Oklahoma City is presented in Table 2.




Figure 2: Cumulative Departure from Mean Water-Year Precipitation  
Oklahoma City, Oklahoma 1905-1987

TABLE 2

Oklahoma City Water-Year (Oct-Sep) Temperatures 1956-1987

Mean Annual Water-Year Temperature (32 years) = 59.8 degrees

Year	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Mean Water-Year Temp
1956	66.3	47.1	41.7	36.1	40.6	50.5	57.9	72.6	78.1	83.0	84.4	76.6	60.9
1957	57.3	45.6	44.3	33.2	45.4	46.7	55.9	65.7	74.2	83.5	80.7	69.3	58.7
1958	61.9	51.4	36.5	39.4	35.5	41.0	56.1	69.4	76.8	80.1	79.9	73.2	58.6
1959	58.3	43.5	44.2	33.0	40.0	49.6	58.5	70.4	75.7	77.4	80.1	72.6	58.8
1960	64.4	51.4	37.4	36.3	34.5	39.7	61.7	66.5	77.3	78.2	79.3	74.5	58.6
1961	63.0	46.5	36.7	36.3	42.7	52.2	59.2	67.7	74.1	79.1	78.4	70.6	59.0
1962	64.7	49.4	40.6	32.3	45.1	48.1	58.3	74.3	75.3	82.2	82.5	71.4	60.4
1963	71.1	52.3	33.0	28.3	40.0	53.8	64.8	70.3	78.7	83.1	82.0	75.1	61.0
1964	60.3	49.9	37.9	40.1	38.5	47.1	64.1	70.0	77.4	85.3	80.8	72.3	60.4
1965	62.8	56.3	48.8	38.8	39.5	40.7	65.5	71.3	78.0	84.6	80.6	73.9	61.7
1966	60.9	54.3	37.8	33.8	38.6	52.8	57.8	68.7	77.9	86.4	78.8	70.5	59.9
1967	62.6	49.4	39.8	41.8	41.7	56.4	65.4	66.9	77.4	79.7	79.3	70.9	60.9
1968	62.1	46.2	38.1	36.6	36.4	50.7	58.1	64.7	74.8	79.8	80.0	70.5	58.4
1969	57.6	48.7	40.4	38.8	42.3	42.0	60.4	67.7	75.0	83.9	80.2	73.3	59.3
1970	57.9	46.0	43.9	31.8	42.7	45.0	60.2	69.2	76.3	82.1	83.6	75.1	59.6
1971	63.4	49.0	42.2	36.9	39.1	49.1	60.4	67.3	78.6	80.7	77.2	73.3	59.9
1972	61.1	43.4	34.4	34.9	42.1	53.4	63.2	67.6	79.0	79.8	80.4	75.8	59.7
1973	64.3	53.1	39.3	33.3	39.8	52.5	56.0	66.8	75.2	79.8	79.7	70.6	59.3
1974	63.5	49.3	39.6	35.0	44.4	54.8	60.0	71.5	74.1	82.7	78.5	65.5	60.0
1975	63.4	50.7	41.8	40.3	36.5	46.1	58.7	67.4	75.1	78.0	80.1	68.3	59.0
1976	56.5	43.9	48.8	39.0	52.2	52.4	61.6	63.6	74.8	79.8	81.3	72.6	60.6
1977	62.7	50.9	40.0	29.2	45.9	54.1	62.5	70.0	79.6	83.0	80.7	78.0	61.3
1978	64.7	50.4	36.9	26.3	29.4	49.1	64.5	68.1	77.3	87.0	82.6	79.7	59.8
1979	65.7	46.5	43.3	25.4	31.5	51.2	58.1	65.8	75.2	81.0	80.0	73.1	58.3
1980	61.1	50.3	41.9	38.2	38.2	46.3	56.7	69.0	81.4	88.3	88.0	76.3	61.3
1981	60.1	50.3	39.1	37.7	43.9	51.9	65.6	65.7	78.4	84.2	78.8	74.1	60.8
1982	62.7	48.6	43.2	35.3	37.7	52.7	57.5	68.2	72.2	81.0	84.1	74.5	59.9
1983	62.7	50.4	25.8	38.6	42.6	48.8	54.0	64.6	73.4	81.6	84.0	74.9	58.6
1984	61.6	49.7	43.0	34.0	45.4	46.4	56.5	68.4	78.6	81.6	82.6	71.5	60.0
1985	61.2	46.1	35.1	30.6	37.2	53.0	62.7	70.0	76.0	80.9	81.3	73.1	59.1
1986	61.6	44.8	40.8	35.1	45.9	50.3	61.8	72.6	77.1	80.1	82.2	72.4	60.4
1987	60.0	50.5	40.6	34.2	40.3	49.5	58.9	70.3	78.4	81.6	82.8	73.5	60.1
Mean	62.1	48.9	39.9	35.0	40.5	49.3	60.1	68.5	76.6	81.9	81.1	73.0	59.8
Minimum	56.5	43.4	25.8	25.4	29.4	39.7	54.0	63.6	72.2	77.4	77.2	65.5	58.3
Maximum	71.1	56.3	48.8	41.8	52.2	56.4	65.6	74.3	81.4	88.3	88.0	79.7	61.7

## Evapotranspiration

Evapotranspiration is the process by which water is returned to the atmosphere as vapor. It consists of the combined action of three factors:

- **Evaporation:** the vaporization of liquid phase water. Dunne and Leopold (1978) report a mean annual Class A pan evaporation rate of approximately 80 inches for central Oklahoma. This value is approximately equivalent to 58 inches of annual lake evaporation. This standing water evaporation rate is 180 percent of mean annual precipitation.
  
- **Sublimation:** the vaporization of solid phase water - ice and snow. Sublimation is not considered a major factor in central Oklahoma.
  
- **Transpiration:** the loss of water by plants to the atmosphere. During the biologic process, plants remove moisture from the soil and transpire part of it to the atmosphere through their leaves. Cottonwood trees, for instance, which grow along drainages with shallow water tables, can annually transpire up to 4.5 acre-feet of water per acre of fully developed trees.

The evapotranspiration for a given area is a function of the temperature and solar radiation received at the earth's surface. Evapotranspiration can be considered in two ways - potential and actual. Potential evapotranspiration (pE-T) is that which can theoretically occur for given site temperature and solar radiation data. It is the total amount of moisture (usually expressed in inches) which can dissipate into the atmosphere assuming the continuous presence of water in the soil.

As recommended by U.S. EPA publication EPA/530/SW-168 (Fenn, et al., 1975), potential evapotranspiration for the central Oklahoma Cimarron Corporation Facility was calculated by a procedure developed by Thornthwaite and Mather (1944, 1957). The product of this analysis is estimated potential evapotranspiration in inches per month. Mean monthly pE-T values for the Cimarron Corporation Facility are given in Table 3.

Actual evapotranspiration (aE-T) is the water loss that will, in fact, occur under given conditions of temperature, solar radiation, precipitation, runoff, and soil moisture. Monthly actual evapotranspiration is therefore dependent upon monthly precipitation and soil moisture conditions. Annual actual evapotranspiration is generally less than potential evapotranspiration since water (soil moisture) is not always available for evapotranspiration. For those months when soil

TABLE 3  
 Mean Monthly Potential Evapotranspiration Values  
 Cimarron Corporation Facility  
 Crescent, Oklahoma

Month	Mean Monthly Temperature Degrees F	Temperature Degree C	Potential Evapotranspiration (inches)
October	62.1	16.7	2.27
November	48.9	9.4	0.78
December	39.9	4.4	0.21
January	35.0	1.7	0.04
February	40.5	4.7	0.26
March	49.3	9.6	0.94
April	60.1	15.6	2.34
May	68.5	20.3	3.91
June	76.6	24.8	5.67
July	81.9	27.7	6.74
August	81.1	27.3	6.19
September	73.0	22.8	4.19
Total Evapotranspiration -----			33.54 inches



moisture recharge (infiltration) exceeds potential evapotranspiration, the rate of evapotranspiration is not limited by soil moisture and actual evapotranspiration is equal to potential evapotranspiration. During those months when potential evapotranspiration exceeds soil moisture recharge (typically the summer months), actual evapotranspiration is limited by declining soil moisture and is equal to potential evapotranspiration plus the difference between soil moisture recharge and potential evapotranspiration and the change in soil moisture. Actual evapotranspiration values for the Cimarron Corporation Facility are included in Table 5 later in this report, and in the water balance calculations presented in the Appendices.

#### SURFACE CONDITIONS

Surface runoff and soil moisture storage are functions of the soil types underlying the Cimarron Corporation Facility and vicinity and the extent to which these soils have been made impervious by development. The EPA water budget methodology results in maximum runoff and infiltration since the interception of precipitation by vegetative cover is not a factor.

The Cimarron Corporation Facility study area consists of approximately 150 acres. Of this area, about 17 acres or 11% of the total are developed with building complexes, parking

lots, storage areas, and associated facilities and sanitary lagoons. The remaining land is primarily pasture. The actual water balance analysis will be limited to the 133 acres of undeveloped lands of the Cimarron Corporation Facility.


### Soils

Three major soil series have been identified on the Cimarron Corporation Facility study area (Mickles, et al., 1960): 1) Renfrow silt loam, 2) Vernon clay loam, and 3) Zaneis silty loam. The distribution of these soils on the Cimarron Corporation Facility study area is shown on Figure 3.

The section that follows discusses the soils of the Cimarron Corporation Facility and the characteristics of these soils that affect the water balance. Field capacity, the maximum moisture content which a soil can retain against gravity without percolation, has been estimated based upon information provided by EPA publication EPA/530/SW-168 (Fenn, et al., 1975) and Thornthwaite and Mather (1957).

1. Renfrow silt loam: covers approximately 42 acres or 28% of the 150-acre Cimarron Corporation Facility study area. The soil is a silt loam developed from red clay beds on gentle to moderate slopes. It is very slowly permeable. Runoff is high. While the

**FIGURE 3: Map Showing Distribution of Major Soil Types  
Cimarron Corporation Facility**



SCALE  
0 500 1000 Feet  
Contour Interval - 10 feet



- R Renfrow Silt Loam Soil
- V Undifferentiated Vernon and Luclen Soils
- Z Zane's Loam Soil
- Boundary of Hydrologic Balance Study Area

profile is recognized to a depth of 40 inches and greater, it is generally thin, with the soil consisting mostly of clay below a depth of about 13 inches. Available water capacity is moderate, with an estimated field capacity of 4.0 inches.

2. Vernon clay loam: covers approximately 67 acres or 44% of the 150-acre Cimarron Corporation Facility study area. Since the Vernon clay loam reportedly underlies the 17 developed acres of the Facility, the actual acreage that will be analyzed will be limited to 50 acres.

Comprised of undifferentiated Vernon and Lucien soils, this is a clay loam developed from soft, unconsolidated clay banded with sandstone on steep slopes. It is slowly permeable. Runoff is typically high. While the profile is recognized to a depth of 20 inches, it is generally thin, with the organic soil typically not extending below 11 inches. Available water capacity is moderate, with an estimated field capacity of 4.2 inches.

3. Zaneis loam: covers approximately 42 acres or 28% of the 150-acre Cimarron Corporation Facility study area. The Zaneis soil underlies the Material Relocation Site.

The soil is a loam developed from red sandy and silty clay banded with sandstone on moderate slopes. It is permeable. Runoff is typically high. The profile is relatively thick, with the soil typically recognized to a depth of 54 inches and greater, although at depths deeper than 33 inches it typically consists of shale. Available water capacity is good, with an estimated field capacity of 10.2 inches.

### Runoff

A portion of the precipitation that falls at the Cimarron Corporation Facility is lost to surface runoff before it can infiltrate the soil. The primary factors that determine the amount of surface runoff that will occur during any particular precipitation event are the intensity and duration of the precipitation, antecedent soil moisture conditions, the permeability and infiltration capacities of the soils, and the amount of soil that is made impermeable by development.

There is no surface runoff monitoring system at the Cimarron Corporation Facility. In lieu of actual runoff data, runoff has been calculated by the application of published empirical runoff coefficients as recommended by U.S. EPA publication EPA/530/SW-168 (Fenn, et al., 1975). The runoff coefficients of Chow (1964) and Dunne and Leopold (1978) were applied to

precipitation data to develop estimates of mean monthly surface runoff for the site specific ground conditions at the Facility. Runoff coefficients for the various site specific conditions are listed in Table 4.

EPA publication EPA/530/SW-168 reports that the rational runoff calculation method will, in most cases, underestimate surface runoff. Therefore, the runoff estimates used in this water balance analysis, shown in Table 5 later in this report, yield probable maximum infiltration and percolation values.

#### WATER BALANCE CALCULATIONS

The method used here to calculate the water balance is that published as U.S. EPA publication EPA/530/SW-168 (Fenn, et al., 1975). The goal of this method is to estimate the amount of percolation (groundwater recharge) that may occur at a given site. Water balance calculations are made in the following manner:

1. The selected runoff coefficient is applied to the mean monthly precipitation to obtain mean monthly surface runoff.

TABLE 4

Ground Condition Classification and Coefficients  
Cimarron Corporation Facility

Land Use	Acres	Percent of Total Area	Runoff Coefficient
Pasture	143	89%	0.45 <sup>1</sup>
Building Complex and Associated Facilities	17	11%	0.50 <sup>2</sup>

Sources: <sup>1</sup>Water in Environmental Planning, 1975 (Dunne  
and Leopold)  
<sup>2</sup>Handbook of Applied Hydrology, 1964 (Chow)

2. Mean monthly surface runoff is subtracted from mean monthly precipitation. The result is the mean monthly infiltration of remaining precipitation into the soil, which constitutes soil moisture recharge.
  
3. Mean monthly potential evapotranspiration is subtracted from mean monthly infiltration; the difference is used to identify periods of soil moisture excess or deficiency. A negative value indicates a net loss of moisture from the soil, a positive value a net gain through excess infiltration.
  
4. The net gain or loss of available water, represented by the difference between infiltration and potential evapotranspiration, is added to or subtracted from the previous month's soil moisture storage. The mean monthly soil moisture storage represents moisture retained in the soil. During periods of monthly gains in soil moisture (generally the cooler months), the soil moisture increases until field capacity is reached or warmer weather and attendant increased evapotranspiration losses result in soil moisture deficiencies. Once field capacity is reached, additional net gains in excess infiltration become percolation.



In all cases of the current analysis, soil moisture is depleted by mid summer. Thus, the initial soil moisture storage value for the beginning of the water year (October through September) is set to zero.

5. The change in soil moisture storage represents the change in soil moisture on a month to month basis.
6. Percolation represents groundwater recharge. Significant percolation only occurs during those months when excess infiltration above field capacity is available.
7. Actual evapotranspiration is equal to potential evapotranspiration during months when the difference between infiltration and potential evapotranspiration is positive. During those months when this value is negative, actual evapotranspiration is equal to the sum of potential evapotranspiration and the difference between infiltration and potential evapotranspiration and the change in soil moisture.

The EPA water balance methodology does not provide for the interception of precipitation by vegetation. The estimates of infiltration and percolation developed by this methodology for the Cimarron Corporation Facility are thus maximum probable values.

A summary of water balance values for the undeveloped portion of the primary Cimarron Corporation Facility is presented in Table 5. Actual water balance tabulations are presented in Appendices A through C.

## CONCLUSIONS

A water balance has been calculated for the Cimarron Corporation Facility located near Crescent, Oklahoma, following the procedures outlined in EPA publication EPA/530/SW-168 (Fenn, et al., 1975). Three soils reportedly underlie the study area, all of which are relatively thin. The compositions of the soils typically generate high runoff while precluding rapid infiltration.

The summary of water balance data listed in Table 5 and the tabulations presented in Appendix A show that no percolation (groundwater recharge) can be expected on the Cimarron Corporation Facility during years of average precipitation. As summarized in Table 5 and shown in Appendix B, if infiltration is maximized by disregarding runoff, a total of approximately 9.44 inches or 35.72 acres feet of percolation would occur in areas underlain by the Renfrow and Vernon soils during years of average precipitation. No percolation would occur through the thicker Zaneis soils.

Also included in this study of the Cimarron Corporation Facility water budget is an analysis of percolation for the maximum recorded annual water-year precipitation. During water-year 1984 (October 1984 through September 1985) a record 51.79 inches of precipitation were recorded in central Oklahoma. As summarized in Table 5 and shown in Appendix C, a total of approximately 14.88 inches or 56.34 acre-feet of percolation would have occurred in areas underlain by the Renfrow and Vernon soils. Approximately 1.33 inches or 4.66 acre-feet of percolation would have occurred through the thicker Zaneis soils.

TABLE 5  
 Summary of Water Balance Calculations  
 Cimarron Facility Water Balance Analysis

Case	Soil	Area (acres)	Field Capacity (inches)	Mean Annual Precipitation (inches)	Mean Annual Precipitation (ac/ft)	Mean Annual Runoff (inches)	Mean Annual Runoff (ac/ft)	Mean Annual Actual Evapotranspiration (inches)	Mean Annual Actual Evapotranspiration (ac/ft)	Mean Annual Percolation (inches)	Mean Annual Percolation (ac/ft)
Mean Annual Precipitation with Runoff	Renfrow silt loam	41	4.0	32.25	110.19	14.52	49.61	17.73	60.58	0.00	0.00
	Vernon clay loam	50	4.2	32.25	134.38	14.52	60.50	17.73	73.88	0.00	0.00
	Zaneis loam	42	10.2	32.25	112.88	14.52	50.82	17.73	62.06	0.00	0.00
Mean Annual Precipitation with no Runoff	Renfrow silt loam	41	4.0	32.25	110.19	0.00	0.00	27.43	93.72	4.82	16.47
	Vernon clay loam	50	4.2	32.25	134.38	0.00	0.00	27.63	115.13	4.62	19.25
	Zaneis loam	42	10.2	32.25	112.88	0.00	0.00	32.25	112.88	0.00	0.00
Maximum Recorded Annual Precipitation with Runoff	Renfrow silt loam	41	4.0	51.79	176.95	23.30	79.61	20.95	71.58	7.54	25.76
	Vernon clay loam	50	4.2	51.79	215.79	23.30	97.08	21.42	89.25	7.34	30.58
	Zaneis loam	42	10.2	51.79	181.27	23.30	81.55	27.15	95.03	1.33	4.66

## REFERENCES CITED

- Chow, V.T., 1964, *Runoff: Handbook of applied hydrology*, V.T. Chow, Editor: New York, McGraw-Hill.
- Dunne, T., and L.B. Leopold, 1978, *Water in environmental planning*: San Francisco, W.H. Freeman and Company.
- Fenn, D.G., Hanley, K.J., and T.V. DeGeare, 1975, *Use of the water balance method for predicting leachate generation from solid waste disposal sites*: U.S. EPA Publication EPA/530/SW-168.
- Mickles, H.P., L.H. Marshall, A.G. Fielder, F.W. Clarke, and M.L. Markley, 1960, *Soil survey of Logan County, Oklahoma*: U.S. Department of Agriculture, Soil Conservation Service.
- National Oceanic and Atmospheric Administration, 1988, *Local Climatological Data, Annual Summary with Comparative Data for Oklahoma City, Oklahoma*.
- Thornthwaite, C.W., and H.G. Wilm, 1944, *Report to the commission on evaporation and transpiration, 1943-44*: Transactions of the Geophysical Union, Volume 25, Part V., pp. 683-693.
- Thornthwaite, C.W., and J.R. Mather, 1955, *The water balance*: Drexel Institute of Technology, Laboratory of Climatology; Publications in Climatology, Volume 8, Number 1.
- Thornthwaite, C.W., and J.R. Mather, 1957, *Instructions and tables for computing potential evapotranspiration and the water balance*: Drexel Institute of Technology, Laboratory of Climatology; Publications in Climatology, Volume 10, Number 3.

**APPENDIX A**

**Cimarron Corporation Facility Water Balance Calculations**

**Case 1: Mean Annual Precipitation with Runoff**









**APPENDIX B**

**Cimarron Corporation Facility Water Balance Calculations**

**Case 2: Mean Annual Precipitation with no Runoff**

TABLE B-1

## Cimarron Facility Water Balance Calculations

Case: Mean Annual Precipitation with no Runoff

Land Use: Pasture

Soil Classification: Renfrow Silt Loam

Field Capacity: 4.0 inches

Runoff Coefficient: 0

Total Area: 41 acres

Percent of Total Facility Area: 27%

NOTE: All data in inches unless otherwise noted.

Water Balance Factor	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Totals
‡Precipitation	3.17	1.87	1.43	1.24	1.32	2.24	3.28	5.02	4.16	2.59	2.60	3.33	32.25
‡Surface Runoff	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	.00
‡Infiltration	3.17	1.87	1.43	1.24	1.32	2.24	3.28	5.02	4.16	2.59	2.60	3.33	32.25
‡Potential	2.27	.78	.21	.04	.26	.94	2.34	3.91	5.67	6.74	6.19	4.19	33.54
Evapotranspiration													
‡Infiltration Minus Potential	.90	1.09	1.22	1.20	1.06	1.30	.94	1.11	-1.51	-4.15	-3.59	-.86	-----
Evapotranspiration													
‡Actual	2.27	.78	.21	.04	.26	.94	2.34	3.91	5.67	5.08	2.60	3.33	27.43
Evapotranspiration													
‡Soil Moisture Storage	.90	1.99	3.21	4.00	4.00	4.00	4.00	4.00	2.49	0.00	0.00	0.00	-----
‡Change in Soil Moisture Storage	.90	1.09	1.22	.79	0.00	0.00	0.00	0.00	-1.51	-2.49	0.00	0.00	-----
‡Percolation	0.00	0.00	0.00	.41	1.06	1.30	.94	1.11	0.00	0.00	0.00	0.00	4.82

TABLE B-2

## Cimarron Facility Water Balance Calculations

Case: Mean Annual Precipitation with no Runoff

Land Use: Pasture

Soil Classification: Vernon Clay Loam

Field Capacity: 4.2 inches

Runoff Coefficient: 0

Total Area: 50 acres

Percent of Total Facility Area: 33%

NOTE: All data in inches unless otherwise noted.

Water Balance Factor	Oct	Nov	Dec	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Totals
‡Precipitation	3.17	1.87	1.43	1.24	1.32	2.24	3.28	5.02	4.16	2.59	2.60	3.33	32.25
‡Surface Runoff	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
‡Infiltration	3.17	1.87	1.43	1.24	1.32	2.24	3.28	5.02	4.16	2.59	2.60	3.33	32.25
‡Potential	2.27	.78	.21	.04	.26	.94	2.34	3.91	5.67	6.74	6.19	4.19	33.54
Evapotranspiration													
‡Infiltration Minus Potential	.90	1.09	1.22	1.20	1.06	1.30	.94	1.11	-1.51	-4.15	-3.59	-.86	-----
Evapotranspiration													
‡Actual	2.27	.78	.21	.04	.26	.94	2.34	3.91	5.67	5.28	2.60	3.33	27.63
Evapotranspiration													
‡Soil Moisture Storage	.90	1.99	3.21	4.20	4.20	4.20	4.20	4.20	2.69	0.00	0.00	0.00	-----
‡Change in Soil Moisture Storage	.90	1.09	1.22	.99	0.00	0.00	0.00	0.00	-1.51	-2.69	0.00	0.00	-----
‡Percolation	0.00	0.00	0.00	.21	1.06	1.30	.94	1.11	0.00	0.00	0.00	0.00	4.62



**APPENDIX C**

**Cimarron Corporation Facility Water Balance Calculations**

**Case 3: Maximum Recorded Annual Water-Year  
Precipitation with Runoff**









ATTACHMENT C

Site Investigation Report  
for the  
Cimarron Corporation Facility  
Logan County, Oklahoma

September 12, 1989

---

(OCT 1989)

C-1 0008s  
License SNM-928; Docket 70-925

**SITE INVESTIGATION REPORT**

**FOR THE**

**CIMARRON CORPORATION FACILITY**  
**LOGAN COUNTY, OKLAHOMA**

Prepared for

**KERR-MCGEE CORPORATION**  
**AND**  
**CIMARRON CORPORATION**  
**OKLAHOMA CITY, OKLAHOMA**

Prepared By

**James L. Grant and Associates, Inc.**  
**Denver, Colorado**  
**September 12, 1989**

TABLE OF CONTENTS

1. EXECUTIVE SUMMARY ..... 1-1

2. INTRODUCTION ..... 2-1

    2.1 Report Purpose and Scope ..... 2-1

    2.2 Description of the Facility ..... 2-2

3. SITE INVESTIGATIONS ..... 3-1

    3.1 Previous Cimarron Investigations ..... 3-1

    3.2 JLGA Investigation ..... 3-2

        3.2.1 Drilling and Sampling ..... 3-2

        3.2.2 Well Installation ..... 3-3

        3.2.3 Borehole Abandonment ..... 3-3

        3.2.4 Well Development ..... 3-3

        3.2.5 Field Tests ..... 3-4

            3.2.5.1 Well Surveying ..... 3-4

            3.2.5.2 Water-Level Measurements ..... 3-4

        3.2.6 Slug Tests ..... 3-5

        3.2.7 Ground-Water Sampling ..... 3-6

        3.2.8 Laboratory Tests ..... 3-7

            3.2.8.1 Ground-Water Analyses ..... 3-7

            3.2.8.2 Soil and Rock Analyses ..... 3-7

            3.2.8.3 Physical Property Analyses ..... 3-8

            3.2.8.4 Soil and Rock Mineralogical Analyses ..... 3-8

            3.2.8.5 Distribution Coefficient Analyses ..... 3-8

4. REGIONAL HYDROGEOLOGY ..... 4-1

    4.1 Regional Structure and Stratigraphy ..... 4-1

    4.2 Regional Ground-Water Occurrence ..... 4-2

    4.3 Ground-Water Use ..... 4-3

    4.4 Regional Ground-Water Quality ..... 4-4

        4.4.1 Background Nitrate and Fluoride Concentrations ..... 4-5

        4.4.2 Background TOC and TOX Concentrations ..... 4-5

        4.4.3 Background Radionuclide Concentrations ..... 4-6

5. SITE HYDROGEOLOGY ..... 5-1

    5.1 Site Physiography ..... 5-1

    5.2 Site Geology ..... 5-1

        5.2.1 Site Stratigraphy ..... 5-1

            5.2.1.1 Shallow Stratigraphic Units ..... 5-2

            5.2.1.2 Description of Sandstones: ..... 5-3

            5.2.1.3 Description of Mudstone: ..... 5-4

        5.2.2 Structure ..... 5-5

        5.2.3 Mineralogy and Rock Chemistry ..... 5-5

            5.2.3.1 Mineralogy ..... 5-5

                5.2.3.1.1 Testing ..... 5-5

                5.2.3.1.2 Discussion ..... 5-5

            5.2.3.2 Soil and Rock Chemistry ..... 5-6

                5.2.3.2.1 Testing ..... 5-6

                5.2.3.2.2 Discussion ..... 5-6

- 5.2.3.3 Chemical Interactions ..... 5-6
  - 5.2.3.3.1 Chemical Environments ..... 5-7
  - 5.2.3.3.2 Site-Related Elements ..... 5-7
- 5.3 Surface-Water Hydrology ..... 5-7
  - 5.3.1 Local Surface-Water Bodies ..... 5-7
  - 5.3.2 Influence on Ground-Water System ..... 5-8
- 5.4 Site Ground-Water Hydrology ..... 5-8
  - 5.4.1 Ground-Water Occurrence ..... 5-8
  - 5.4.2 Ground-Water Flow System ..... 5-9
  - 5.4.3 Hydraulic Properties of Water-Bearing Strata ... 5-9
- 5.5 Ground-Water Quality ..... 5-10
  - 5.5.1 pH and Conductivity ..... 5-10
- 6. SITE-SPECIFIC PARAMETER ANALYSIS ..... 6-1
  - 6.1 Site Ground-Water Analyses ..... 6-1
    - 6.1.1 Fluoride and Nitrate ..... 6-1
    - 6.1.2 TOC and TOX ..... 6-2
    - 6.1.3 Radionuclides ..... 6-3
      - 6.1.3.1 Gross Alpha Activity ..... 6-3
      - 6.1.3.2 Gross Beta Activity ..... 6-4
      - 6.1.3.3 Uranium ..... 6-5
      - 6.1.3.4 Radium ..... 6-6
    - 6.1.4 Facility Impacted Areas ..... 6-8
  - 6.2 Site Soil and Rock Analyses ..... 6-8
    - 6.2.1 Fluoride and Nitrate ..... 6-8
    - 6.2.2 Total Organic Carbon ..... 6-9
    - 6.2.3 Radionuclides ..... 6-9
      - 6.2.3.1 Alpha and Beta Activity ..... 6-9
      - 6.2.3.2 Plutonium ..... 6-9
      - 6.2.3.3 Uranium ..... 6-10
      - 6.2.3.4 Radium ..... 6-10
      - 6.2.3.5 Thorium ..... 6-10
    - 6.2.4 Correlation with Field-Measured Gamma Activity . 6-10
  - 6.3 Uranium Mobility ..... 6-11
- 7. MOBILITY AND MATRIX RETENTION OF RADIONUCLIDES ..... 7-1
  - 7.1 Infiltration ..... 7-1
    - 7.1.1 Methods of Analysis ..... 7-1
      - 7.1.1.1 Data ..... 7-2
      - 7.1.1.2 Calculations ..... 7-2
  - 7.2 Leachability ..... 7-3
  - 7.3 Potential for Migration ..... 7-5
  - 7.4 Computer Simulation of Leaching and Migration ..... 7-6
    - 7.4.1 Kd limited release simulation - Vadose zone .... 7-6
    - 7.4.2 Kd limited release simulation - Saturated zone . 7-7
    - 7.4.3 Discussion of Results ..... 7-7
  - 7.5 Migration of Uranium Left In-Situ ..... 7-7
- 8. REFERENCES ..... 8-1

Appendix A	WORK PLAN FOR SITE INVESTIGATION PROGRAM
Appendix B	MONITORING WELL RECORDS
Appendix C	SLUG TEST DATA
Appendix D	GROUND-WATER ANALYSES
Appendix E	SOIL AND ROCK SITE-SPECIFIC PARAMETER ANALYSES
Appendix F	PHYSICAL PROPERTY ANALYSES
Appendix G	SOIL AND ROCK MINERALOGICAL ANALYSES
Appendix H	DISTRIBUTION COEFFICIENT ANALYSES
Appendix I	HELP MODEL SIMULATIONS
Appendix J	TRANSS MODEL SIMULATIONS

## LIST OF TABLES

Table 3.1	Well Completion Details .....	3-11
Table 3.2	Well Development Summary .....	3-12
Table 3.3	Aquifer Test Results .....	3-13
Table 3.4	Ground Water Analyses .....	3-14
Table 3.5	Rock and Soil Parameter Analyses .....	3-15
Table 3.6	Physical Property Analyses .....	3-16
Table 3.7	Rock and Soil Mineralogical Analyses .....	3-17
Table 3.8	Distribution Coefficient Analyses .....	3-18
Table 4.1	Regional Ground-Water Quality .....	4-7
Table 4.2	Garber/Wellington Ground-Water Quality .....	4-8
Table 5.1	Average Monthly Precipitation .....	5-11
Table 6.1	Annual Ground-Water Sampling Results .....	6-12
Table 6.2	Radium Concentrations in Ground Water .....	6-13
Table 7.1	Assumed Soil Properties .....	7-9
Table 7.2	Cover Profiles Analyzed .....	7-10
Table 7.3	Summary of Percolation Calculations .....	7-11
Table 7.4	Average Monthly Water Balances .....	7-12
Table 7.5	Hydrologic Parameters used in TRANSS Model .....	7-14

## LIST OF FIGURES

Figure 2.1	Location of the Cimarron Facility .....	2-5
Figure 2.2	Cimarron Facility Site Map .....	2-6
Figure 3.1	Monitoring Well Design .....	3-19
Figure 4.1	Geologic Map .....	4-9
Figure 4.2	Tectonic Province Map of Oklahoma .....	4-10
Figure 4.3	Garber/Wellington Potentiometric Surface ....	4-11
Figure 4.4	Garber/Wellington Aquifer Recharge Area ....	4-12
Figure 5.1	Geologic Cross-Section A-A' .....	5-12
Figure 5.2	Geologic Cross-Section B-B' .....	5-13
Figure 5.3	Cross-Section Location Map .....	5-14
Figure 5.4	Shallow Well Potentiometric Surface .....	5-15
Figure 5.5	Deep Well Potentiometric Surface .....	5-16
Figure 6.1	Fluoride Concentrations in Ground Water .....	6-14
Figure 6.2	Nitrate Concentrations in Ground Water .....	6-15
Figure 6.3	Alpha Activity in Ground Water .....	6-16
Figure 6.4	Beta Activity in Ground Water .....	6-17
Figure 6.5	Total Uranium Activity in Ground Water .....	6-18
Figure 6.6	Total Radium Activity in Ground Water .....	6-19
Figure 6.7	Histogram of Radium Concentrations .....	6-20
Figure 6.8	Log-Transformed Probability Plot of Radium ..	6-21
Figure 6.9	Fluoride vs. U-238 in Soil and Rock .....	6-22
Figure 6.10	Field Probe Gamma Activity vs. U-238 .....	6-23
Figure 7.1	Annual Uranium Concentrations: 1985-1989 ....	7-15
Figure 7.2	Uranium Concentrations with Distance .....	7-16
Figure 7.3	Leachate Concentration with Time .....	7-17
Figure 7.4	Leachate Concentration with Time .....	7-18
Figure 7.5	Pathline for Saturated Zone Simulations .....	7-19
Figure 7.6	Leachate Concentration with Time .....	7-21
Figure 7.7	Leachate Concentration with Time .....	7-22



## 1. EXECUTIVE SUMMARY

Cimarron Corporation (Cimarron), a wholly-owned subsidiary of Kerr-McGee Corporation (Kerr-McGee), operated a facility near Crescent, Oklahoma for the fabrication of mixed oxide (plutonium and uranium) and enriched uranium fuel elements. The facility was closed in 1975 and decommissioning, which commenced in 1979, is continuing at present. These activities are conducted under NRC Special Nuclear Materials Licenses SNM-928 and SNM-1174.

Decommissioning activities consist of dismantling the former production facilities and management of any waste materials related to production and decommissioning activities. Management of waste materials includes off-site disposal of equipment and soils and on-site stabilization of soils which contain either or both uranium and thorium at concentrations meeting Options 1 and 2 of the Nuclear Regulatory Commission Branch Technical Position (46 Federal Register 52061, October 23, 1981). Approximately 370 cubic yards of greater than Option 2 limit soil materials will be disposed at a licensed commercial radioactive waste disposal facility.

Approximately 14,800 cubic yards of Option 2 limit materials will be buried on-site at least four feet below the ground surface in a designated landfill. In addition, approximately 96,300 cubic yards of soil that meets Option 2 limits and which is already four or more feet deep will be left in place under the uranium plant yard. These volume estimates are based on results of a facility area soil boring program, logging of boreholes with a counter and comparison of count rates to reference standards of known radiological content. These data were then processed using a computer program. The volumes are believed to be conservative and samples will be taken during excavation to provide final volume definition.

As part of planning for the disposition of Option 2 limit materials, Cimarron has conducted site studies to characterize the local hydrogeologic system, establish a system for ground-water monitoring, evaluate current ground-water quality, and estimate the long-term effect on ground-water quality which on-site burial of Option 2 limit soil might have. This report summarizes the field investigation, laboratory analyses, and data evaluation conducted for the site characterization.

The facility is located south of the Cimarron River in an area of low, rolling hills and incised drainages. Local elevations range between about 940 along the river to 1010 feet at the plant. Subsurface materials at the site include one to eight feet of soil covering the Garber Sandstone. The rock strata in the upper 140 feet of the Garber include alternating sandstones and mudstones. The sandstone layers, which are between 30 and 55 feet thick, have been designated Sandstones A, B, and C. The three sandstones are separated by mudstone layers. The mudstones are designated Mudstones A and B and are between 6 and 20 feet thick.

Shallow ground water occurs in Sandstone A under water table conditions. Most of the site monitoring wells are completed in this zone. The depth to water is between 10 and 30 feet below ground surface. Ground-water flow is to the north-northwest where discharge to the surface or to Cimarron River alluvium is likely. The hydraulic conductivity of Sandstone A is  $1.03 \times 10^{-3}$  cm/sec. Ground water also occurs in Sandstones B and C. Four of the site wells are completed in Sandstone C. The hydraulic conductivity in the deeper unit is about  $1.27 \times 10^{-4}$  cm/sec. Flow in this stratum is toward the northwest where discharge to the Cimarron river alluvium is likely.

Current ground-water quality in Sandstone A indicates that past operations might have affected the water in the immediate vicinity of certain facility units. The units where down-gradient ground-water impacts may have occurred include: wastewater ponds #1 and 2, the former burial area, and the area between the plutonium and uranium buildings. Since closure, ground-water sampling around these units shows water quality has improved. No definite effects are apparent in the deeper Sandstone C stratum.

Soil and rock samples from the unsaturated and saturated zones were chemically analyzed. Radionuclides were not detected in significant concentrations and facility operations do not appear to have affected soil and rock in the subsurface.

The results of soil, rock, and water analyses have been analyzed to estimate effects which could result from infiltration of water through Option 2 limit materials buried on-site. The solubility and mobility of radionuclides in the subsurface have been estimated using infiltration models and measurements of aquifer properties, water chemistry, and elemental partition coefficients.

The calculations demonstrate that the Option 2 limit materials which will remain at the site after decommissioning will not present a real or potential threat to ground-water or surface-water use.

## 2. INTRODUCTION

### 2.1 Report Purpose and Scope

This report presents the results of a site investigation program conducted by James L. Grant and Associates (JLGA) during early 1989. The purpose of the investigation was to determine the possible impacts that facility production and decommissioning operations may have had on the hydrogeologic system underlying the site. The geotechnical characteristics of selected site materials that may be used in construction of the permanent repository for site soils that contain low levels of uranium and thorium were evaluated.

A "Work Plan for Site Investigation Program" (Work Plan) was submitted January 4, 1989 to Kerr-McGee Corporation and Cimarron Corporation. The Work Plan specified procedures for drilling, sampling soil and rock, well installation, ground-water sampling, conducting aquifer tests and cleaning drilling and sampling equipment. Procedures specified in the Work Plan were adhered to during the site investigation. The Work Plan is included in this report as Appendix A.

The report emphasis is on the local ground-water system and assesses the impacts facility operations may have had on this system. The anticipated behavior of radionuclides in the shallow subsurface of the site is addressed, as are the engineering properties of materials to be used in the permanent soil repository planned at the site. Data have been obtained that permit the following:

- o Characterization of stratigraphy and lithology of the soils and bedrock strata at the site;
- o Characterization of aquifer properties including hydraulic conductivity, ground-water flow direction, and gradient;
- o Characterization of ground-water quality and determination of the effects that facility operations may have had on ground-water quality;
- o Determination of the mobility of radionuclides, particularly uranium, in the subsurface and the ability of subsurface materials to retard migration;
- o The suitability of selected site soil and rock for cover materials of the planned landfill.

## 2.2 Description of the Facility

Cimarron Corporation (Cimarron), a wholly-owned subsidiary of Kerr-McGee Corporation (Kerr-McGee), manages the decommissioning activities at the Cimarron Facility in Logan County, Oklahoma. Figure 2.1 shows the location of the facility. The facility was operational from 1965 to 1975. The principal operations at the facility involved the fabrication of fuel elements from plutonium and enriched uranium. Production ceased in 1975; decommissioning commenced in 1979 and is continuing at present. Figure 2.2 is a detailed map of the facility.

Enriched uranium fuel was produced from 1965 to 1975. In general, the process is described by the following steps:

- o Uranium hexafluoride gas was passed through an ammonia solution, producing solid ammonium diuranate.
- o Ammonium diuranate was calcined to produce uranium oxide powder ( $UO_3$ ).
- o Uranium oxide powder was pressed into pellets.
- o The pellets were converted into ceramic-grade uranium dioxide ( $UO_2$ ) in reduction furnaces.

Mixed-oxide fuel also was produced from 1970 to 1975 in the plutonium plant. Additional operations at the facility included a solvent extraction process to recover uranium from the processing of scrap and from material that did not meet contract specifications.

Liquid wastes from uranium processing were passed through an ion-exchange system for the recovery of uranium. The treated effluent was discharged to the Cimarron River under permit from 1965 to 1971. From 1971 to 1975, the treated effluent was pumped to wastewater evaporation ponds. Contaminated sludges that accumulated in the ponds were excavated in 1976 and 1977 and shipped to a licensed commercial low-level radioactive waste disposal facility. The ponds were subsequently reclaimed, inspected, and released for unrestricted use.

Sanitary water and laundry water from the uranium and plutonium operations was sent to the sewage lagoons. Contaminated sediments that accumulated were removed from the lagoons. The sediments contained up to 1300 pCi/g uranium and 11 pCi/g plutonium. These sediments were shipped off-site to a commercial disposal facility. Sediments that have accumulated since those shipments are from decommissioning activities and will be analyzed, excavated and disposed off-site if activity levels warrant.

Contaminated solid wastes generated from uranium plant activities were buried at a designated location on-site from 1966 to 1970. These solid wastes have since been excavated and shipped to a commercial disposal facility. Since 1970, all contaminated solid wastes were shipped off-site to a commercial disposal facility.

Thorium was present at the former burial site as drummed waste materials from the decommissioning of the Kerr McGee Corporation Cushing facility. Equipment from the Cushing facility also was stored at the uranium plant yard. The equipment and excavated drummed waste was shipped to a commercial disposal facility. Thorium has not been detected in soils or ground water at the Cimarron facility above background levels indicating there has been no impact from these materials. No plutonium waste was disposed on-site.

Only purified uranium and plutonium were used in the production processes. The concentrations of daughter products were negligible. Radium and thorium detected in ground-water and soil samples represent natural background levels and not the effects of facility activities.

Facility operations ceased in 1975 and Cimarron staff are presently decommissioning the facilities. Certain soil materials associated with the decommissioning activities will be left on-site, either in a designated, engineered site or in-situ, in accordance with the Nuclear Regulatory Commission's (NRC) Branch Technical Position (46 Federal Register 52061, October 23, 1981). The soils to be left on-site contain enriched uranium and thorium that meet the Branch Technical Position Options 1 and 2 concentration limits and conditions for disposal.

o NRC Branch Technical Position Option 1:

This Option places no restrictions on the method of disposal or on-site storage of soils that contain up to 30 pCi/g enriched uranium, 35 pCi/g depleted uranium, and 10 pCi/g natural thorium (Th-232 plus Th-228).


o NRC Branch Technical Position Option 2:

This Option permits the burial of soils containing low levels of uranium with no subsequent restrictions on land use or continued NRC licensing of the material. To meet this disposal criterion, soils must not contain more than 100 pCi/g soluble enriched uranium, 250 pCi/g insoluble enriched uranium, 100 pCi/g soluble depleted uranium, 300 pCi/g insoluble depleted uranium, or 50 pCi/g natural thorium. A minimum burial depth of four

feet is required, and the proposed burial site must have acceptable hydrogeologic, meteorologic and topographic characteristics to mitigate against transport.

Cimarron plans to leave in place soils that contain Option 2 levels of uranium that are deeper than four feet below the ground surface. Soils that are shallower than four feet and meet the Option 2 disposal criterion will be excavated and transported to a designated on-site landfill.

The hydrologic, meteorologic and topographic characteristics of the Cimarron facility and the engineered on-site landfill are addressed in this report.




808211



**JAMES L GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 2.1**  
**CIMARRON FACILITY LOCATION**





### 3. SITE INVESTIGATIONS

#### 3.1 Previous Cimarron Investigations

The Cimarron facility has an extensive and continuous environmental monitoring program to determine the impacts of facility activities on the environment. This program consists of routinely collecting and analyzing air, surface water, ground water, soil and vegetation samples from the site and adjacent areas.

The environmental program includes many monitoring wells installed throughout the facility area for collection of ground-water samples from the shallow, unconfined aquifer which occurs at depths less than 50 feet below ground surface. Wells no. 1311 through 1317 shown on Figure 2.2 were installed during previous site investigations. Boring logs and well completion information were available for these wells; hydrologic and geologic data, and analyses of ground water collected from these wells have been incorporated into the JLGA investigation.

Cimarron also has conducted a detailed soil boring survey and sampling program to provide semi-quantitative information on the extent of facility-related radionuclide contamination in the shallow subsurface. The survey consisted of lowering a sodium iodide (NaI) probe into borings and measuring gamma radiation at one-foot intervals. The probe was calibrated against standards of known concentrations of uranium and thorium. Measurements of total gamma activity were recorded and concentrations of radionuclides were estimated by comparing counts in the boreholes with the standards.

The quantities of soils meeting the Option 1 and 2 disposal criteria have been conservatively estimated from the borehole gamma survey. Cimarron estimates that 14,800 cubic yards of soil at depths less than four feet meet the Option 2 on-site disposal criteria. This soil will be excavated and placed in the designated on-site landfill. An estimated 96,300 cubic yards of soil and rock that meets the Option 2 limits occurs at depths greater than four feet. Cimarron plans to leave this material in place.

### 3.2 JLGA Investigation

James L. Grant and Associates (JLGA) was retained by Cimarron to conduct a supplemental site characterization investigation. The field investigation was conducted between January 16 and April 1, 1989.

#### 3.2.1 Drilling and Sampling.

A total of eighteen wells were installed during the field investigation. The wells were drilled using air rotary, water rotary and coring techniques. Drilling was conducted by Kerr-McGee and Jim Winnek, Inc. of Tulsa, Oklahoma. The equipment decontamination procedures presented in the Work Plan (Appendix A) were used to minimize the potential for introduction of contaminants into intervals penetrated by drilling. All drilling and sampling activities were observed by a JLGA geologist and descriptive sample logs were maintained.

The majority of wells were sampled by continuous coring. Both diamond and Criss bits were used. The cores are NX size and are stored in waxed cardboard boxes. The diamond bits cut a 1-7/8 inch diameter core and the Criss bits cut a 2-1/8 inch diameter core. Upon completion of coring to the designated depth, the bore holes were reamed to a 6 inch diameter using water rotary techniques.

Rock was sampled by continuous coring or rotary techniques. For the intervals drilled by air or water rotary, cuttings were collected and composited over 24-inch intervals. The cuttings were logged and stored in plastic bags. Descriptions are recorded on the monitoring well records in Appendix B.

Soil was sampled with split-spoon samplers following the procedures specified in ASTM 1586. Each sample represented a 24-inch interval except at the top of bedrock where refusal of the sampling tool resulted in a smaller sample collected. Samples were stored in plastic bags. Descriptions of the samples and the interval sampled are indicated on the monitoring well records included in Appendix B.

### 3.2.2 Well Installation.

Monitoring well installation procedures are described in the Work Plan (Appendix A). A 2.5 feet long sump was installed below the well screen to provide a repository for fines that accumulate during well development and evacuation prior to sampling. Figure 3.1 shows the relative placement of well screen, sand pack, and sealed sections of the well. Table 3.1 lists the pertinent completion details for the monitoring wells. Well completion information also is shown on the monitoring well records presented in Appendix B. The locations of the monitoring wells are indicated on Figure 2.2 and in Table 3.1.

At borings where wells were completed, the well casing was installed after completion of drilling to the desired depth. Two-inch diameter, flush-joint, threaded, schedule 80 PVC well casing and screen was used for all the monitoring wells (1320 through 1336).

### 3.2.3 Borehole Abandonment.

Sample recoveries were inadequate at two borings. These borings were abandoned and redrilled using drilling and sampling techniques suitable for the materials encountered. Wells 1323 and 1330 were constructed in the redrilled borings. The abandoned borings were backfilled to ground surface with a portland cement/sodium bentonite grout. A shallow concrete cap was placed on top of the hardened grout.

Two additional 10 feet deep borings were advanced adjacent to Well 1325 at the request of Cimarron personnel. These borings were drilled to obtain a continuous core sample from 5 to 10 feet. These additional borings were also backfilled with a portland cement/sodium bentonite grout.

### 3.2.4 Well Development.

The ground-water monitoring wells were developed soon after they were completed. Each of the wells was developed to remove fines and drill cuttings from the screened interval. Well development was accomplished by the air-lift method or by bailing with a cleaned PVC bailer. The wells developed by bailing were Nos. 1320 and 1322. The remainder were developed via air-lift. The air-lift method is described in the Work Plan (Appendix A). Development was terminated when the turbidity of the discharge water stabilized and a minimum of ten well volumes had been removed.

Water removed from each well during development was discharged to the ground surface. The volume of water removed was estimated by periodically measuring the quantity discharged into a bucket per unit of time. For the wells developed by bailing, water was discharged into buckets and the quantities recorded. The volume, color, odor, and clarity of water evacuated from each of the wells during development was established by visually noting these characteristics. Table 3.2 provides a summary of well-development data.

### 3.2.5 Field Tests.

#### 3.2.5.1 Well Surveying.

Locations, datum and ground-surface elevations for wells and surface water elevations of the three reservoirs at the site were determined by R. E. Heinz and Associates of Guthrie, Oklahoma. The wells were surveyed between March 20 and March 27, 1989

All elevations and horizontal locations are based on the Cimarron Facility plant datum located due west of the the uranium building. The elevation of the datum was determined from facility construction plans. It is believed that the elevation of the plant datum is tied to the U. S. Geological Survey mean sea level datum since it corresponds to elevations noted on the U.S. Geological Survey topographic quadrangle of the area; however, no established benchmarks were located within several miles of the facility for verification. Horizontal coordinates for the wells are based upon a north-aligned grid system established at the plant datum. The elevations and coordinates for each well are noted on the monitoring well records in Appendix B and in Table 3.1.

#### 3.2.5.2 Water-Level Measurements.

Water levels were measured at the site monitoring wells after installation and development. The levels were measured over a relatively short time interval so that the data are comparable. Measurements were made on March 21, 1989, and again on March 31, 1989. Additional measurements were made periodically during the drilling program to anticipate the depth ground water would be encountered at subsequent wells.

The depth to water below the measurement datum was recorded to the nearest 1/8 inch (0.01 feet). The ground-water levels measured during the investigation are included in Table 3.1.

### 3.2.6 Slug Tests.

In-situ field tests using the slug insertion and withdrawal procedure to obtain measures of hydraulic conductivity were conducted at all wells installed during this investigation. These tests were conducted by quickly inserting a weighted slug of known volume into the well and recording changes in head as a function of time as the water in the aquifer adjusts to the presence of the slug. After the water level in the well has stabilized, the slug is quickly withdrawn, and the resulting drawdown and recovery are recorded.

The water level in the wells recovered too quickly for head fluctuations to be measured manually. Head fluctuations were measured using an In-Situ Model SE-1000B Hermit Environmental Data Logger and a 10.13 psi down-hole pressure transducer. This unit allowed accurate measurement of rapid water level changes over very short time intervals. Recovery and drawdown data were recorded using a pre-programmed logarithmic sampling rate with very frequent measurements during the first 20 seconds and less frequent measurements during the remaining portion of the test.

The test data were interpreted using techniques described in Bouwer and Rice (1976), Cooper, Bredehoeft and Papadopoulos (1967) and Hvorslev (1951). The results of these aquifer tests are presented in Table 3.3. The test data are presented in Appendix C. The three different analytical techniques were employed for comparison and to ensure that reliable estimates of hydraulic conductivity were obtained.

Hydraulic conductivities and transmissivities were calculated for both the slug insertion (falling head) and slug withdrawal (rising head) portions of the tests. From past experience the calculations based on rising head data are believed more representative of the aquifer since it partially removes the effects of the greater permeability of the sand packs around the well screens. Since the sand pack around the well screen has a greater permeability than the adjacent aquifer, it is believed that upon insertion of the slug, the water level will initially rise more rapidly and to a higher level in the sand pack than in the aquifer. The initial stages of the subsequent water-level recovery therefor reflect ground water reentering the well from the sand pack rather than the aquifer.

The rising head portion of the slug test serves to remove the effects of the sand pack. When the slug is withdrawn, the water level in the well drops an amount equivalent to the volume displaced by the slug. The subsequent recovery to the initial water level is due to ground water entering the well from the aquifer. The amount of water stored in the sand pack and available to enter the well after the slug is withdrawn is negligible. The calculations for both the falling and rising head portions of

the test showed slightly higher values for hydraulic conductivity and transmissivity for the falling head tests.

According to Bouwer & Rice (1976), their method is applicable for partially or fully penetrating wells in unconfined aquifers, or for wells in leaky confined aquifers. Cooper, Bredehoeft & Papadopulus (1967) state their method is applicable to wells fully or partially screened in confined aquifers. The Hvorslev method (1951) is applicable to wells installed in unconfined aquifers. A comparison of the three methods is presented in Table 3.3 and shows reasonable agreement among the three methods.

The hydraulic conductivity of the shallow aquifer is best approximated by the Bouwer & Rice and Hvorslev methods since it is under water table conditions. The results of these two methods were averaged geometrically to arrive at an approximation for the hydraulic conductivity and transmissivity. Geometric averages are more appropriate than arithmetic averages for data that differs by orders of magnitude. The hydraulic conductivity of the shallow aquifer ranges from  $2.41 \times 10^{-4}$  cm/sec to  $5.7 \times 10^{-3}$  cm/sec. The geometric mean of the measured values is  $1.03 \times 10^{-3}$  cm/sec. The transmissivity of this aquifer ranges from 10.3 ft sq/day to 108 ft sq/day, with a geometric mean of 33.4 ft sq/day.

The hydraulic conductivity and transmissivity of the confined aquifer screened in the deep wells is best approximated by the Cooper et. al. method. The results from those analyses were averaged geometrically. The hydraulic conductivity of the deep aquifer ranges from  $1.39 \times 10^{-5}$  cm/sec to  $7.06 \times 10^{-4}$  cm/sec, with a geometric mean of  $1.27 \times 10^{-4}$  cm/sec. The transmissivity ranges from .67 ft sq/day to 50 ft sq/day, with a geometric mean of 7.96 ft sq/day.

### 3.2.7 Ground-Water Sampling.

Monitoring wells installed during this program were sampled during the week of March 19, 1989. Cimarron sampled existing wells at the same time to provide a full-facility range of comparable data for the evaluation of ground-water quality. All samples were analyzed for the same constituents.

The ground-water samples were collected using the procedures described in the Work Plan (Appendix A). Specific conductance and pH were measured in the field for each sample collected. The ground-water samples were placed in containers provided by the laboratory and by Cimarron Corporation. Both one-gallon and one-quart plastic cubitainers were filled at each well. An additional one quart glass jar was filled for the samples requiring TOC and TOX analyses.

A label was placed on each sample container. This label contained the well number, date, type of sample, name of collector, and any special instructions. The ground-water samples were kept chilled and delivered to the laboratory within hours of collection. Chain of custody documentation was maintained for all the samples and is included in Appendix D. The analyses conducted are described in the following section.

### 3.2.8 Laboratory Tests.

#### 3.2.8.1 Ground-Water Analyses.

Ground-water analyses were conducted by the Kerr-McGee Technical Center Laboratory. The samples were analyzed for nitrate, fluoride, gross alpha and beta activity, Pu-239, Ra-228, Ra-226, Th-232, Th-228, U-238, U-235, and U-234 in accordance with standard EPA methods. Four samples were also selected for Total Organic Carbon (TOC) and Total Organic Halide (TOX) analyses in accordance with standard EPA methods. Standard ground-water quality analyses for major cations and anions were performed in conjunction with the distribution coefficient (Kd) tests. Table 3.4 provides a summary of the ground-water analyses. Documentation of the analyses and the chain of custody documentation are included as Appendix D to this report.

#### 3.2.8.2 Soil and Rock Analyses.

Selected soil and rock samples were submitted to the Kerr-McGee Technical Center laboratory for analysis. The samples were analyzed for parameters related to facility activities. The parameters analyzed for include nitrate, fluoride, gross alpha and beta activity, Pu-239, Ra-228, Ra-226, Th-232, Th-228, U-238, and U-234 in accordance with standard EPA methods. Table 3.5 provides a summary of the results. Documentation of these analyses and the chain of custody documentation are included as Appendix E.

The samples selected for site-specific parameter analyses are representative of the different strata encountered and different locations around the site. Sample selection was not random, but emphasized stratigraphic intervals where migration of contaminants may be restricted, such as at the top of less permeable, confining strata, or adsorbed in strata of favorable chemistry. The well number, interval sampled and lithologic description of the rock or soil also are indicated in Table 3.5.

Prior to submission to the laboratory, Cimarron measured the uranium activity in the samples by gamma spectrometry. The Cimarron gamma spectrometry analysis utilizes the EG&G Ortec ADCAM computer analysis program. The samples were analyzed inside a lead-shielded box to minimize background interference. These results also are presented in Table 3.5.

#### 3.2.8.3 Physical Property Analyses.

Samples were submitted to Standard Testing, Inc. of Oklahoma City for physical property analyses. These analyses included characterization tests (grain size and Atterberg Limits), standard Proctor tests and compacted permeabilities. The Proctor and compacted permeability tests were performed on samples of borrow material from the designated landfill site which are representative of materials that may be used to construct the landfill cover. The results of these tests are presented in Table 3.6 and documentation is included in Appendix F.

#### 3.2.8.4 Soil and Rock Mineralogical Analyses.

Samples were submitted to the Department of Agronomy and Soils at Auburn University for analysis of selected properties. The tests performed included cation exchange capacity (CEC), exchangeable cation (EXC), mineralogy, grain size and matric potential. The well number, interval sampled, lithologic description and analytical results are presented in Table 3.7. Documentation of the results are presented in Appendix G. The samples submitted are representative of the different strata encountered during this investigation.

#### 3.2.8.5 Distribution Coefficient Analyses.

Five samples of site soils, rock and ground water were analyzed by the Kerr-McGee Technical Center to determine equilibrium distribution coefficients (Kd) for uranium and thorium. This test provides a measure of the affinity of the selected elements for soil and rock and the solubility of the material in the rock/ground-water system. The tests were conducted according to the batch test procedures included in Appendix H. Kd test results are summarized in Table 3.8 and documentation of the results is included in Appendix H.

The samples for Kd determinations were selected after the soil and rock mineralogical and chemical analyses were completed. The aquifer matrix materials can be broadly classified into one of four major groups: low clay (<18%), low calcite (<3%) content; high clay (>30%), low calcite content; low clay, high calcite (>3%) content; and high clay, high calcite content. For the aquifer matrix materials underlying the Cimarron facility, clay and calcite content were the important constituents affecting the distribution coefficients. The matrix samples submitted for Kd



determinations are representative of the four groups identified, including "reduced" and "non-reduced" samples. The reduced samples are representative of iron-deficient intervals where ferric oxides have been reduced to ferrous oxides and removed by ground water.

Two distribution coefficient tests were conducted for each sample submitted for both uranium and thorium. The first test used 20 milliliters (ml) of site ground water spiked to a uranium concentration of 850 pCi/l and a thorium concentration of 850 pCi/l. This solution was applied to 5 gram samples of site aquifer matrix materials for a total concentration of 3.40 pCi/g uranium and 3.40 pCi/g thorium. After reaching equilibrium with the matrix materials, final concentrations of uranium in solution ranged from 1.2 pCi/l to 9.3 pCi/l. Final concentrations of thorium ranged from 0.6 to 1.2 pCi/l.

The second test used 100 ml of site ground water spiked to a uranium concentration of 850 pCi/l and a thorium concentration of 850 pCi/l. This solution was applied to 5 gram samples of matrix materials for a total concentration of 17 pCi/g uranium and 17 pCi/g thorium. After reaching equilibrium, final concentrations of uranium in solution ranged from 1.5 to 9.9 pCi/l. Final concentrations of thorium ranged from 0.6 to 1.3 pCi/l.

The experimentally derived Kd values for uranium range from 339 ml/g to 2829 ml/g. Experimental Kd values for thorium range from 2262 ml/g to 5662 ml/g. The experimentally derived values for both elements are within published value ranges. Isherwood (1981) reports Kd values for uranium in soil at near neutral pH that range from 4,400 ml/g to 62,000 ml/g. Kd values for thorium at near neutral pH are reported to range from 40 ml/g to 400,000 ml/g. The experimental Kd values did not exhibit a direct correlation with either the clay mineral or calcite content of the site soils.

Approximations of distribution coefficients can also be made by comparing the amount of uranium detected on the aquifer material with the amount detected in ground water from that interval. Six of the aquifer material samples submitted to the laboratory for uranium analyses represent screened intervals in monitoring wells. Comparing the uranium values found in the rock samples with the ground-water samples yield approximate Kd values ranging from 10 ml/g to 192 ml/g.

The difference between the approximated Kd values and those from the laboratory tests may be attributable to precipitation of uranium in the batch test. The laboratory Kd tests are conducted under controlled conditions using ground water spiked to a concentration greater than that typically found at the site. Precipitation of uranium during the test will result in higher Kd values than if adsorption were the sole mechanism removing

uranium from ground water.

The distribution coefficient ( $K_d$ ) tests demonstrate that uranium will have limited solubility in the subsurface ground water. Final concentrations of uranium in the test solutions ranged from 1.2 to 9.9 pCi/l. These concentrations are consistent with naturally occurring uranium concentrations in ground-water samples from most of the monitoring wells. The combined effects of uranium precipitation and adsorption on the aquifer matrix materials appear to produce equilibrium concentrations of uranium in ground water less than 10 pCi/l.

Water from certain wells sampled had uranium concentrations greater than the above equilibrium concentration. These wells are located adjacent to and immediately down-gradient from the closed wastewater ponds and the former solid-waste burial area, where the chemistry of the ground water probably was changed by the materials stored in these areas. The higher uranium concentrations probably result from the differences in water chemistry, especially the presence of nitrate and fluoride ions. As discussed in Section 7.3, uranium concentrations in the ground water decrease rapidly with distance from such a source as the concentrations of ions is reduced through dilution and sorption.

TABLE 3.1  
Well Completion Details

WELL NO.	INSTALLED BY	DATUM ELEVATION (feet msl)	GROUND ELEVATION (feet msl)	COORDINATES		WELL DEPTH	DEPTH TO SCREEN		GROUND WATER LEVELS			
									3/31/89		3/21/89	
									DEPTH	ELEVATION	DEPTH	ELEVATION
1311	Cimarron	995.69	993.9	11087.15	10949.24	80.00	25.00	40.00	28.28	967.41	28.07	967.62
1312	Cimarron	992.17	989.6	10917.11	11133.08	36.00	21.00	35.00	26.50	965.67	25.50	966.67
1313	Cimarron	994.70	992.4	10955.19	11278.42	38.00	23.00	38.00	28.95	965.75	28.70	966.00
1314	Cimarron	983.02	980.0	14093.26	12266.33	80.00	30.00	45.00	27.82	955.20	27.40	955.62
1315	Cimarron	955.98	953.0	14126.89	12610.52	27.00	12.00	27.00	13.64	942.34	13.92	942.06
1316	Cimarron	951.31	949.9	14066.96	12637.28	32.00	17.00	32.00	10.60	940.71	10.65	940.66
1317	Cimarron	946.62	943.9	14026.01	12798.60	18.00	3.00	18.00	10.30	936.32	10.95	935.67
1320	JLGA	998.14	995.6	11755.70	11266.69	41.30	28.50	38.50	27.66	970.48	27.01	971.13
1321	JLGA	998.38	996.0	11743.26	11261.76	124.40	111.60	121.60	59.85	938.53	60.25	938.13
1322	JLGA	1001.48	998.6	10238.93	10386.13	37.90	25.00	35.00	32.12	969.36	31.76	969.72
1323	JLGA	1001.85	998.9	10224.06	10387.37	129.60	116.80	126.80	57.20	944.65	57.48	944.37
1324	JLGA	997.58	995.2	12075.48	10972.36	35.00	25.00	35.00	25.58	972.00	25.03	972.55
1325	JLGA	1008.32	1005.9	11951.47	10494.65	48.30	35.50	45.50	33.08	975.24	32.49	975.83
1326	JLGA	1009.33	1006.5	10719.85	10112.93	45.10	32.30	42.30	37.62	971.71	37.11	972.22
1327	JLGA	1009.17	1006.2	10100.10	10103.73	41.80	29.00	39.00	dry		dry	
1327-B	JLGA	1008.42	1006.2	10100.10	10090.43	51.80	39.00	49.00	41.03	968.14	40.93	967.49
1328	JLGA	1008.44	1006.0	10411.70	9830.36	137.80	125.00	135.00	55.35	953.09	55.54	952.90
1329	JLGA	1008.55	1005.9	10405.36	9835.39	47.80	35.00	45.00	38.79	969.76	38.86	969.69
1330	JLGA	997.70	995.3	10231.32	9657.06	41.50	28.70	38.70	26.60	971.10	26.17	971.53
1331	JLGA	978.00	975.3	10202.71	10751.13	25.00	12.20	22.20	10.51	967.49	9.81	968.19
1332	JLGA	989.54	987.1	10457.35	10686.36	118.80	106.00	116.00	46.97	942.57	47.05	942.49
1333	JLGA	989.77	986.8	10442.73	10662.97	34.80	22.00	32.00	20.75	969.02	20.62	969.15
1334	JLGA	980.26	977.6	10776.31	10688.14	22.80	10.00	20.00	12.33	967.93	12.60	967.66
1335	JLGA	1002.50	1000.2	11758.09	10944.05	42.80	30.00	40.00	28.91	973.59	28.20	974.30
1336	JLGA	986.02	984.0	11722.31	11738.39	30.80	18.00	28.00	25.34	960.68	25.14	960.88

NOTE: DATUM IS TOP OF CASING FOR ALL WELLS.  
 ELEVATION OF WATER IN RESERVOIR 1: 959.3' 3/26/89  
 ELEVATION OF WATER IN RESERVOIR 2: 966.3' 3/26/89  
 ELEVATION OF WATER IN RESERVOIR 3: 971.0' 3/26/89

**TABLE 3.2**  
**Well Development Summary**

WELL NO.	DATE	DEPTH TO WATER			GALLONS REMOVED	CLARITY AFTER DEVELOPMENT	COMMENTS
		WELL TD (BTOC)	BEFORE (BTOC)	AFTER (BTOC)			
1320	3/14/89	41.2	26.88	34.65	30	Clear, with orange tint	Develop. by bailing
1321	3/16/89	128.4	60.2	74.91	130	Clear and colorless	
1322	2/16,22/89	40.8	29.9	30.56	20	Clear and colorless	Develop. by bailing & air-lift
1323	2/22-24/89	129.2	54.58	85.9	130	Clear, v. faint orange tint	
1324	3/15/89	34.95	24.17	27.9	30	Clear, pale orange tint	
1325	3/15/89	50.5	32.78	33.97	75	Clear, v. pale orange tint	
1326	3/16/89	47.9	N/M	N/M	>40	Colorless	Develop. by Kerr-McGee
1327	NOT DEVELOPED						
1327-B	3/20/89	N/M	N/M	N/M	40	Clear, pale orange tint	
1328	3/16/89	139.15	55.34	64.02	250	Clear, v. pale orange tint	Well made >4 gpm during devel.
1329	3/13/89	49.5	38.7	41.3	35	Clear, v. pale orange tint	
1330	3/16/89	43.7	26.21	27.1	80	Clear, pale orange tint	
1331	3/15/89	27.9	10.1	13.35	80	Clear, colorless	
1332	3/16/89	121.1	46.8	59.25	240	Clear, colorless	Well made about 4 gpm
1333	3/14/89	37.6	20.7	N/M	30	Clear, colorless	Well made about 1 qt/m
1334	3/16/89	25.1	9.85	N/M	30	Clear, pale orange tint	
1335	3/15/89	45.1	28.65	31.25	50	Clear, v. pale orange tint	
1336	3/15/89	32.7	25.18	N/M	20	Clear, colorless	Very slow flow rate

NOTE: N/M means not measured

TABLE 3.3  
Aquifer Test Results

WELL NO.	BOUWER AND RICE METHOD		COOPER ET.AL. METHOD		HVORSLEV METHOD	
	Conductivity cm/sec	Transmissivity ft sq/day	Conductivity cm/sec	Transmissivity ft sq/day	Conductivity cm/sec	Transmissivity ft sq/day
-----						
SHALLOW WELLS						
=====						
1320	2.34E-04	1.03E+01	2.30E-04	6.50E+00	2.57E-04	7.44E+00
1322	1.29E-03	2.10E+01			1.88E-03	3.09E+01
1324	5.19E-04	1.74E+01				
1325	9.66E-04	4.19E+01			2.72E-03	1.04E+02
1326	5.01E-04	1.06E+01			7.45E-04	1.70E+01
1327-B	8.98E-04	2.85E+01			2.41E-03	7.53E+01
1329	3.03E-03	1.02E+02			5.70E-03	1.94E+02
1330	8.60E-04	6.36E+01	7.40E-04	5.46E+01	1.41E-03	1.03E+02
1331	1.08E-03	4.34E+01	1.13E-03	4.00E+01		
1333	2.46E-04	9.92E+00				
1334	8.52E-04	2.50E+01			5.96E-04	5.76E+00
1335	4.11E-04	2.72E+01				
1336	2.28E-03	1.08E+02			4.61E-03	1.05E+02
-----						
DEEP WELLS						
=====						
1321	2.25E-04	4.76E+01	4.41E-05	5.00E+00	1.09E-04	1.55E+01
1323	2.00E-05	4.58E+00	1.39E-05	6.70E-01	1.59E-05	5.90E-01
1328	1.03E-03	2.54E+02	7.06E-04	5.00E+01	1.06E-03	4.49E+01
1332	4.66E-04	1.03E+02	6.05E-04	2.40E+01		

TABLE 3.4  
Ground Water Analyses

Well No.	pH	Conductivity umho	Fluoride mg/l	Nitrate mg/l	Gross Alpha pCi/l	Gross Beta pCi/l	U-238 pCi/l	U-235 pCi/l	U-234 pCi/l	TOTAL URANIUM pCi/l	Ra-228 pCi/l	Ra-226 pCi/l	TOTAL RADIUM pCi/l	Th-232 pCi/l	Th-228 pCi/l	Pu-239 pCi/l	TOC mg/l	TOX ug/l
1311			<0.20	66.00	<10.00	23.00	0.77 +-0.11	0.018 +-0.18	0.99 +-0.13	1.78	0.082 +-0.19	0.180 +-0.21	0.26	0.004 +-0.004	0.004 +-0.004	0.002 +-0.002		
1312			50.00	1020.00	59.00	2370.00	15.30 +-1.90	1.230 +-0.55	41.60 +-3.20	58.13	1.380 +-0.54	0.450 +-0.34	1.83	0.004 +-0.004	0.007 +-0.005	0.003 +-0.002		
1313			140.00	720.00	260.00	2200.00	30.00 +-2.00	2.700 +-0.70	84.00 +-4.00	116.70	2.340 +-0.91	0.490 +-0.49	2.83	0.004 +-0.004	0.004 +-0.004	0.003 +-0.002		
1314			<0.20	0.36	<10.00	<20.00	0.31 +-0.08	0.039 +-0.027	0.77 +-0.12	1.12	0.000 +-0.27	0.110 +-0.23	0.11	0.004 +-0.004	0.004 +-0.004	0.003 +-0.002		
1315			0.22	13.00	6440.00	660.00	1550.00 +-190.0	110.000 +-51.0	3570.00 +-285.0	5230.00	1.610 +-0.77	0.000 +-0.22	1.61	0.004 +-0.004	0.013 +-0.007	0.003 +-0.002		
1316			<0.20	16.00	331.00	100.00	67.00 +-10.0	10.000 +-3.8	210.00 +-17.0	287.00	0.470 +-0.58	0.000 +-0.30	0.47	0.004 +-0.004	0.004 +-0.004	0.003 +-0.002		
1317			<0.20	0.38	66.00	26.00	8.10 +-0.34	0.580 +-0.29	15.00 +-1.5	23.68	0.100 +-0.39	0.000 +-0.24	0.10	0.004 +-0.004	0.004 +-0.004	0.003 +-0.002		
1320	7.39	520	0.42	20.00	<10.00	<20.00	3.10 +-0.28	0.170 +-0.10	5.58 +-0.57	8.85	0.250 +-0.30	0.150 +-0.22	0.40	0.004 +-0.004	0.004 +-0.004	0.005 +-0.003		
1321	6.91	1910	<.20	9.10	18.00	26.00	2.75 +-0.40	0.120 +-0.08	8.10 +-0.70	10.97	0.021 +-0.14	0.000 +-0.14	0.02	0.004 +-0.004	0.004 +-0.004	0.004 +-0.003		
1322	7.32	560	<.20	9.20	15.00	<20.00	3.90 +-0.65	0.130 +-0.011	8.20 +-0.09	12.23	0.038 +-0.30	0.220 +-0.29	0.26	0.004 +-0.004	0.004 +-0.004	0.002 +-0.002	<10.00	77.00
1323	7.27	2510	<.20	1.70	51.00	<20.00	9.80 +-1.00	0.420 +-0.21	17.00 +-1.30	27.22	0.012 +-0.24	0.046 +-0.20	0.06	0.004 +-0.004	0.004 +-0.004	0.004 +-0.003		
1324	7.55	440	0.26	18.00	<10.00	<20.00	0.20 +-0.07	0.022 +-0.022	0.44 +-0.10	0.66	0.059 +-0.27	0.000 +-0.27	0.06	0.004 +-0.004	0.004 +-0.004	0.002 +-0.002		
1325	7.32	460	0.35	13.00	<10.00	<20.00	1.00 +-0.12	0.046 +-0.026	1.49 +-0.015	2.54	0.260 +-0.26	0.086 +-0.26	0.35	0.004 +-0.004	0.004 +-0.004	0.006 +-0.003	12.00	130.00
1326	7.37	610	<0.20	14.00	14.00	25.00	1.48 +-0.15	0.058 +-0.029	4.43 +-0.25	5.97	0.150 +-0.20	0.000 +-0.16	0.15	0.004 +-0.004	0.008 +-0.005	0.002 +-0.001	<10.00	98.00
1327-B	7.71	450	0.20	8.20	<10.00	<20.00	1.52 +-0.20	0.140 +-0.06	2.80 +-0.28	4.46	0.009 +-0.10	0.052 +-0.082	0.06	0.004 +-0.004	0.004 +-0.004	0.006 +-0.003		
1328	7.39	2310	<0.20	2.20	29.00	<20.00	9.00 +-0.90	0.660 +-0.25	18.00 +-1.30	27.66	0.000 +-0.19	0.054 +-0.13	0.05	0.004 +-0.004	0.011 +-0.007	0.002 +-0.002		
1329	7.49	400	<0.20	0.40	12.00	<20.00	2.04 +-0.18	0.093 +-0.037	5.30 +-0.29	7.43	0.000 +-0.17	0.030 +-0.13	0.03	0.004 +-0.004	0.008 +-0.006	0.006 +-0.003	<10.00	62.00
1330	6.99	1590	<0.20	172.00	16.00	62.00	2.40 +-0.22	0.100 +-0.05	5.17 +-0.33	7.67	0.000 +-0.31	0.088 +-0.22	0.09	0.008 +-0.008	0.008 +-0.008	0.006 +-0.003		
1331	7.10	710	<0.20	5.70	190.00	23.00	35.00 +-6.10	3.700 +-1.80	126.00 +-12.0	164.70	0.000 +-0.23	0.000 +-0.23	0.00	0.004 +-0.004	0.008 +-0.005	0.002 +-0.002		
1332	7.21	3190	1.30	3.40	23.00	<20.00	6.40 +-0.60	0.12 +-0.08	13.900 +-0.90	20.42	1.000 +-0.46	0.180 +-0.36	1.18	0.004 +-0.004	0.004 +-0.004	0.002 +-0.002		
1333	7.05	800	<0.20	6.30	47.00	<20.00	6.20 +-0.50	0.710 +-0.12	18.00 +-0.60	24.91	0.120 +-0.32	0.120 +-0.39	0.24	0.004 +-0.004	0.004 +-0.004	0.002 +-0.002		
1334	7.10	730	0.26	6.10	30.00	<20.00	5.00 +-0.33	0.230 +-0.07	13.20 +-0.50	18.43	0.200 +-0.14	0.029 +-0.13	0.23	0.004 +-0.004	0.004 +-0.004	0.002 +-0.002		
1335	7.01	470	0.24	22.00	<10.00	<20.00	1.25 +-0.15	1.640 +-0.17	1.640 +-0.17	4.53	0.000 +-0.32	0.000 +-0.32	0.00	0.004 +-0.004	0.004 +-0.004	0.006 +-0.004		
1336	7.30	664	17.00	1260.00	140.00	4970.00	23.00 +-2.40	2.400 +-0.80	76.000 +-4.0	101.40	7.830 +-1.63	1.950 +-1.02	9.78	0.004 +-0.004	0.085 +-0.018	0.002 +-0.002		
1337*	7.05	800	<0.20	5.70	33.00	<20.00	5.10 +-0.54	0.170 +-0.10	18.700 +-1.04	23.97	1.200 +-0.41	0.200 +-0.21	1.40	0.004 +-0.004	0.004 +-0.004	0.002 +-0.002		
1338**			0.32	<0.23	<10.00	<20.00	0.04 +-0.025	0.017 +-0.017	0.071 +-0.036	0.12	0.028 +-0.089	0.000 +-0.061	0.03	0.004 +-0.004	0.004 +-0.004	0.002 +-0.002		

MAJOR ION ANALYSIS  
WELL 1324  
(Sampled 6/12/89)

Ca	71.5 mg/l	Cl	3.8 mg/l
Mg	37.2 mg/l	HCO3	394 mg/l
F	0.6 mg/l	NO3(N)	20 mg/l
K	0.36 mg/l	SO4	72 mg/l
Na	40.1 mg/l		

NOTE: \* 1337 is a duplicate of 1333.  
\*\* 1338 is an equipment blank  
Blank spaces mean parameter not measured

TABLE 3.5  
Rock and Soil Parameter Analyses

SAMPLE NO.	BORING NO.	SAMPLE INTERVAL	SAMPLE DESCRIPTION	FIELD GAMMA LOG counts/min	GAMMA SPECTROMETRY URANIUM ACTIVITY pCi/g	F (ppm)	NO3 (ppm)	TOC (ppm)	GROSS ALPHA pCi/g	GROSS BETA pCi/g	Pu-239 pCi/g	Ra-228 pCi/g	Ra-226 pCi/g	Th-232 pCi/g	Th-228 pCi/g	U-238 pCi/g	U-234 pCi/g
CS-100	1325	6.0-7.0'	Sandy mudstone	26930	5.76	170.00	14.00	45.00	16.00	<20.00	0.003 +-0.001	0.07 +-0.18	0.55 +-0.36	0.70 +-0.03	0.70 +-0.03	0.34 +-0.05	0.51 +-0.05
CS-101	1321	42.0-42.5'	Sandy mudstone	31845	7.92	560.00	3.00	<10.00	34.00	<20.00	0.002 +-0.001	1.84 +-0.39	0.51 +-0.28	1.37 +-0.07	1.37 +-0.07	0.66 +-0.07	0.57 +-0.07
CS-102	1323	8.7-9.7'	Sandy mudstone	30119	6.91	640.00	2.00	190.00	30.00	<20.00	0.001 +-0.001	0.29 +-0.20	0.21 +-0.21	1.39 +-0.06	1.42 +-0.06	0.67 +-0.08	0.63 +-0.08
CS-103	1323	35.0-36.0'	Sandy mudstone	30754	3.91	440.00	3.00	23.00	30.00	<20.00	0.001 +-0.001	0.27 +-0.85	0.28 +-0.95	1.17 +-0.10	1.28 +-0.10	0.51 +-0.06	0.60 +-0.06
CS-104	1326	16.0-17.0'	Sandy mudstone	30829	6.44	600.00	4.00	<10.00	35.00	<20.00	0.001 +-0.001	1.17 +-0.24	0.77 +-0.21	1.15 +-0.06	1.15 +-0.06	0.69 +-0.07	0.77 +-0.07
CS-105	1327	21.0-22.0'	Sandy mudstone	32050	4.11	470.00	3.00	<10.00	31.00	<20.00	0.001 +-0.001	0.77 +-0.35	0.65 +-0.34	1.00 +-0.08	1.20 +-0.08	0.68 +-0.04	0.68 +-0.04
CS-106	1328	19.0-20.0'	Sandy mudstone	30502	8.13	600.00	15.00	<10.00	38.00	<20.00	0.001 +-0.001	0.99 +-0.42	0.66 +-0.39	1.14 +-0.07	1.18 +-0.07	0.71 +-0.07	0.72 +-0.07
CS-107	1330	11.5-12.5'	Sandy mudstone	30944	6.36	560.00	16.00	420.00	19.00	<20.00	0.001 +-0.001	0.62 +-0.21	0.29 +-0.22	0.69 +-0.05	0.87 +-0.05	0.84 +-0.08	0.73 +-0.08
CS-108	1336	14.0-15.0'	Sandstone, fine-grained		8.87	140.00	9.00	1180.00	<10.00	<20.00	0.002 +-0.001	0.04 +-0.17	0.19 +-0.34	0.53 +-0.07	0.52 +-0.07	0.23 +-0.04	0.21 +-0.04
CS-109	1336	25.0-25.5'	Sandstone, fine-grained		10.79	190.00	27.00	<10.00	<10.00	<20.00	0.002 +-0.001	0.37 +-0.31	0.26 +-0.25	0.52 +-0.05	0.52 +-0.05	0.38 +-0.05	0.42 +-0.05
CS-110	1335	25.0-25.6'	Sandstone, fine-grained		8.34	40.00	3.00	840.00	<10.00	<20.00	0.001 +-0.001	0.10 +-0.14	0.08 +-0.11	0.27 +-0.03	0.27 +-0.03	0.24 +-0.04	0.24 +-0.04
CS-111	1324	16.0-18.0'	Very sandy mudstone	6271 *	13.25	39.00	4.00	27.00	<10.00	<20.00	0.006 +-0.001	0.00 +-0.16	0.11 +-0.26	0.45 +-0.02	0.41 +-0.02	0.19 +-0.05	0.19 +-0.05
CS-112	1321	69.5-70.0'	Sandstone, fine-grained		16.18	55.00	2.00	160.00	<10.00	<20.00	0.002 +-0.001	0.07 +-0.27	0.10 +-0.30	0.34 +-0.03	0.41 +-0.03	0.29 +-0.03	0.33 +-0.03
CS-113	1321	13.4-14.0'	Sandstone, fine-grained	7703	9.58	65.00	130.00	170.00	<10.00	<20.00	0.001 +-0.001	0.08 +-0.10	0.12 +-0.20	0.32 +-0.03	0.33 +-0.03	0.23 +-0.03	0.18 +-0.03
CS-114	1334	11.2-11.8'	Sandstone, fine-grained		9.08	51.00	4.00	18.00	11.00	<20.00	0.001 +-0.001	0.00 +-0.09	0.33 +-0.17	0.27 +-0.03	0.28 +-0.03	0.38 +-0.05	0.61 +-0.05
CS-115	1332	7.0-7.5'	Sandstone, fine-grained		10.29	150.00	5.00	440.00	<10.00	<20.00	0.002 +-0.001	0.02 +-0.16	0.26 +-0.26	0.61 +-0.05	0.65 +-0.05	0.38 +-0.04	0.36 +-0.04
CS-116	1332	68.0-68.5'	Conglomeratic sandstone		10.40	65.00	3.00	110.00	<10.00	<20.00	0.001 +-0.001	0.00 +-0.44	0.30 +-0.22	0.56 +-0.04	0.56 +-0.04	0.38 +-0.04	0.45 +-0.04
CS-117	1332	41.5-42.0'	Sandy mudstone		7.45	450.00	3.00	<10.00	25.00	<20.00	0.001 +-0.001	0.54 +-0.36	0.32 +-0.36	0.89 +-0.04	0.96 +-0.04	0.70 +-0.05	0.63 +-0.05
CS-118	1331	9.5-10.0'	Sandstone, fine-grained		5.99	210.00	3.00	250.00	12.00	<20.00	0.001 +-0.001	0.02 +-0.04	0.40 +-0.57	0.56 +-0.04	0.63 +-0.05	0.34 +-0.04	0.30 +-0.04
CS-119	1323	34.3-37.9'	Sandy mudstone	29253 *	17.6	330.00	3.00	130.00	18.00	<20.00	0.001 +-0.001	0.30 +-0.27	0.38 +-0.33	0.96 +-0.06	0.93 +-0.03	0.63 +-0.05	0.59 +-0.05
CS-120	1323	112-112.5'	Sandstone, fine-grained		7.05	59.00	3.00	140.00	<10.00	<20.00	0.001 +-0.001	0.00 +-0.14	0.03 +-0.20	0.42 +-0.05	0.42 +-0.05	0.27 +-0.04	0.27 +-0.04
CS-121	1326	2.0-4.0'	Sand, slightly silty	17255 *	12.1	170.00	5.00	3110.00	<10.00	<20.00	0.001 +-0.001	0.00 +-0.25	0.42 +-0.32	0.49 +-0.04	0.59 +-0.05	0.44 +-0.05	0.68 +-0.05
CS-122	1328	11.0-11.6'	Sandstone, fine-grained		13.87	72.00	5.00	47.00	<10.00	<20.00	0.002 +-0.001	0.01 +-0.19	0.12 +-0.25	0.33 +-0.03	0.33 +-0.03	0.26 +-0.03	0.36 +-0.03
CS-123	1328	37.8-38.3'	Conglomeratic sandstone	8128	10.92	180.00	2.00	320.00	11.00	<20.00	0.003 +-0.001	0.30 +-0.21	0.37 +-0.22	0.50 +-0.06	0.68 +-0.06	0.45 +-0.04	0.45 +-0.04
CS-124	1328	83.5-84.0'	Sandstone, fine-grained		10.41	23.00	6.00	1180.00	<10.00	<20.00	0.002 +-0.001	1.90 +-0.54	0.00 +-0.06	0.27 +-0.04	0.47 +-0.04	0.19 +-0.03	0.19 +-0.03
CS-125	1330	20.5-21.0'	Sandstone, fine-grained	19269	10.86	88.00	12.00	240.00	NR	NR	0.001 +-0.001	0.00 +-0.25	0.11 +-0.32	0.26 +-0.03	0.22 +-0.03	0.22 +-0.03	0.23 +-0.03
CS-126	1321	131.5-132'	Sandy mudstone		5.98	18.00	4.00	130.00	<10.0	<20.0	0.002 +-0.001	0.00 +-0.09	0.01 +-0.13	0.41 +-0.04	0.41 +-0.04	0.16 +-0.02	0.21 +-0.03

NOTE: \* Indicates value averaged over interval sample composited.  
Gamma spectrometry performed by Cimarron personnel using the EG&G Ortec ADCAM computer analysis program.  
NR means value not reported.

TABLE 3.6

Physical Property Analyses

SAMPLE NO.	PP-1	PP-2	PP-3	PP-4	PP-5	PP-6	PP-7	PP-8	PP-9	PP-10
WELL NO.	Landfill Borrow	Landfill Borrow	Landfill Borrow	1328	1328	1323	1332	1332	1334	1327
SAMPLE INTERVAL				6-8'	15-15.5'	2-4'	20-20.4'	10.5-11'	13.5-14	16.5-17'
<b>ATTERBERG LIMITS</b>										
LIQUID LIMIT	24.0	23.0	23.0	26.0	34.0	NP	NP	25.0	36.0	NP
PLASTIC LIMIT	10.0	9.0	8.0	8.0	9.0	NP	NP	8.0	13.0	NP
<b>PERCENT PASSING SIEVE</b>										
#10	93.8	98.3	97.3	100.0	100.0	100.0	100.0	100.0	100.0	95.9
#40	90.0	95.4	93.5	94.8	95.6	99.9	99.2	99.9	98.5	71.8
#200	70.5	73.3	72.9	62.8	87.7	39.2	89.2	94.6	94.1	44.7
<b>STANDARD PROCTOR TEST</b>										
ASTM D698										
% MOISTURE	13.1	13.0	14.0							
DRY DENSITY	119.7	120.5	117.8							
<b>PERMEABILITY TEST</b>										
ASTM STP-479										
% MOISTURE	13.4	15.3	16.9							
% COMPACTION	80.8	77.9	77.1							
PERMEABILITY cm/sec	1.02E-04	1.98E-05	1.38E-04							
% MOISTURE	12.8	14.7	15.5							
% COMPACTION	89.6	88.2	87.7							
PERMEABILITY cm/sec	1.18E-05	2.99E-06	1.60E-05							
% MOISTURE	14.3	14.6	16.0							
% COMPACTION	96.1	97.4	97.1							
PERMEABILITY cm/sec	3.00E-07	3.08E-08	2.48E-08							



TABLE 3.7


Rock and Soil Mineralogical Analyses

SAMPLE NO.	BORING NO.	SAMPLED INTERVAL	ABBREVIATED FIELD DESCRIPTION	GRAIN SIZE DISTRIBUTION			pH	CEC meq/100g	EXCHANGEABLE CATIONS (meq/100g)				MINERALOGICAL COMPOSITION (wt. percent)						
				% FRACTION < 2mm					Ca	Mg	K	Na	Kaolinite	Fe Oxides/ Hydroxides	Expanding Silicates	Feldspar + mica	Calcite	Quartz	Adsorbed Water
				Sand	Silt	Clay													
CH-1	1323	37.9-38.4'	VFG sandy mudstone	0.70	78.74	20.56	8.43	10.83	6.96	3.29	0.32	0.30	15	4	12	17	<1	48	1.63
CH-2	1323	34.3-37.9'	Comp. of red. zones	15.50	64.94	19.56	8.72	7.96	17.25	2.78	0.23	0.28	12	2	8	17	<1	56	2.25
CH-3	1326	2-4'	Silty sand	57.70	27.82	14.48	6.87	7.71	5.01	1.61	0.16	0.11							
CH-4	1328	20-20.4	Slightly sandy mudstone	18.70	47.22	34.08	8.53	18.56	27.37	6.62	0.47	0.30							
CH-5	1328	37.2-38'	Sandstone conglomerate	82.40	10.48	7.12	9.18	2.55	18.84	1.14	0.08	0.21	1	3	3	5	29	58	0.5
CH-6	1336	15.3-15.7	VFG sandy mudstone	2.50	58.18	39.32	8.18	22.75	26.26	5.97	0.48	0.35	27	8	23	27	<1	12	3.63
CH-7	1321	25.5-26	VFG sandy mudstone	39.60	45.56	14.84	7.91	4.59	8.35	1.62	0.11	0.33							
CH-8	1321	25-25.3	FG-VFG sandstone	80.00	13.08	6.92	8.30	3.37	10.93	1.43	0.07	0.33	1	<1	3	3	1	90	0.38
CH-9	Landfill borrow		silt, sand, rock frags.	37.50	39.66	22.84	8.76	9.93	21.14	2.94	0.25	0.21	8	3	10	14	3	59	1.63
CH-10	1324	20-22'	Sandy mudstone	74.20	16.12	9.68	5.99	2.96	10.50	1.36	0.10	0.17							
CH-11	1325	24-26'	Sandy mudstone	56.40	25.56	18.04	8.86	6.00	17.82	5.71	0.22	0.29							
CH-12	Landfill		Grab - gray red. zone	47.00	43.44	9.56	8.69	6.20	9.29	4.03	0.50	0.27	7	1	6	9	3	72	1
CH-13	1332	4-5.5'	Silty sand	25.50	55.34	19.16	8.89	8.02	20.24	4.95	0.34	0.47							
CH-14	1334	16.4-16.7'	Gray, silty red. zone	59.20	24.16	16.64	8.95	6.87	17.71	4.2	0.50	0.21	1	1	7	11	12	59	1.25
CH-15	1334	15.6-15.9'	Sandy mudstone	21.90	51.94	26.16	8.62	11.32	12.35	5.18	0.58	0.15	10	4	11	17	3	52	1.88

TABLE 3.8

## Distribution Coefficient Analyses

Sample No.	Initial Water Conc. (pCi/ml)	Total Spike (pCi)	Initial pH	Final pH	Equilibrium Water Conc. (pCi/ml)	Soil Conc. (pCi/g)	Distribution Coefficient (ml soln/g soil)
-----							
TEST 1 - Uranium-232							
CH-1R	0.85	17.00	7.45	7.90	1.20E-03	3.40	2829.333
CH-5R	0.85	17.00	7.45	7.76	2.70E-03	3.39	1255.259
CH-6R	0.85	17.00	7.50	7.82	9.30E-03	3.36	361.591
CH-8R	0.85	17.00	7.49	7.75	1.20E-03	3.40	2829.333
CH-14R	0.85	17.00	7.50	7.82	3.00E-03	3.39	1129.333
- Thorium-228							
CH-1R	0.85	17.00	7.45	7.90	6.00E-04	3.40	5662.667
CH-5R	0.85	17.00	7.45	7.76	9.00E-04	3.40	3773.778
CH-6R	0.85	17.00	7.50	7.82	6.00E-04	3.40	5662.667
CH-8R	0.85	17.00	7.49	7.75	1.20E-03	3.40	2829.333
CH-14R	0.85	17.00	7.50	7.82	1.20E-03	3.40	2829.333
TEST 2 - Uranium-232							
CH-1R	0.85	85.00	7.11	7.38	7.50E-03	3.37	449.333
CH-5R	0.85	85.00	7.22	7.46	3.60E-03	3.39	940.444
CH-6R	0.85	85.00	7.19	7.40	9.90E-03	3.36	339.434
CH-8R	0.85	85.00	7.20	7.42	1.50E-03	3.39	2262.667
CH-14R	0.85	85.00	7.23	7.46	2.10E-03	3.39	1615.048
- Thorium-228							
CH-1R	0.85	85.00	7.11	7.38	1.50E-03	3.39	2262.667
CH-5R	0.85	85.00	7.22	7.46	9.00E-04	3.40	3773.778
CH-6R	0.85	85.00	7.19	7.40	9.00E-04	3.40	3773.778
CH-8R	0.85	85.00	7.20	7.42	9.00E-04	3.40	3773.778
CH-14R	0.85	85.00	7.23	7.46	6.00E-04	3.40	5662.667



808211



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 3.1**  
**MONITORING WELL DESIGN**

#### 4. REGIONAL HYDROGEOLOGY

##### 4.1 Regional Structure and Stratigraphy

Subsurface rock units in the central Oklahoma region range in age from Precambrian through Permian. Outcropping bedrock in the area consists of Permian and Pennsylvanian strata. Near drainages and flood plains the rocks are capped with unconsolidated Quaternary alluvium and terrace deposits. Figure 4.1 is a geologic map of the region.

The principal structural feature in the central Oklahoma region is the Nemaha ridge or uplift, a north-northwest trending subsurface uplift formed during the Mississippian. Figure 4.2 is a map of Oklahoma showing the tectonic provinces.

The Phanerozoic (Cambrian and younger) geologic history of central Oklahoma is characterized by periods of marine and non-marine sedimentation punctuated by periods of extensive erosion. Four widespread unconformities have been identified marking periods of uplift, erosion, and subsequent deposition. These unconformities occur at the top of the Ordovician Arbuckle formation, at the base of the Mississippian system, at the base of the Pennsylvanian system, and during the Tertiary Period.

Of particular importance to the central Oklahoma region is a period of uplift and erosion that occurred between the Mississippian and Pennsylvanian systems. This period of activity produced the north-northwest trending normal faults and anticlinal structures that comprise the Nemaha ridge. Early Pennsylvanian strata onlap and thin over the structures signifying continued uplift into the Pennsylvanian. Reactivation of the faults is not documented after early to middle Pennsylvanian time.

The Nemaha ridge controlled sedimentation during part of the Pennsylvanian by partially subdividing the existing basin. Sediments east of the ridge are generally representative of shallow marine and non-marine deposition, while strata west of the ridge were deposited from essentially shallow and deeper marine environments. The axis of the Nemaha ridge or uplift lies west of the site.

By Permian time, the central Oklahoma region lay along the eastern shelf of a shallow sea. The Permian strata underlying the Cimarron facility area are the Garber and Wellington formations. These formations consist of interbedded sandstones, siltstones and shales primarily and were deposited from a west-flowing deltaic system. These clastic units are characteristically interbedded and of limited areal extent with rapid facies changes.

A widespread unconformity has truncated all pre-Quaternary formations in the region. This has produced the characteristic north-trending outcrop pattern indicated in Figure 4.1.

Along rivers and streams, Quaternary terrace and alluvial deposits have formed. These deposits consist of unconsolidated gravels, sands, silts and clays. The deposits generally range in thickness from 10 to 50 feet. Locally, they may be as much as 100 feet thick. In the vicinity of the Cimarron facility, the Cimarron terrace is Pleistocene in age and is the result of glacial outwash.

#### 4.2 Regional Ground-Water Occurrence

Ground water in the central Oklahoma region occurs principally in the Permian-aged Garber/Wellington aquifer. The Oklahoma Geological Survey groups the Garber and Wellington formations together as a single hydrologic unit on the basis of similar lithologies and water-bearing characteristics (Bingham and Moore, 1975).

The water-bearing sandstones are fine grained and friable, with numerous interbedded siltstones and shales. The matrix of the sandstones is frequently a fine red mud. Sandstones are generally thin and the percentage of sandstone versus shale increases from north to south in the central Oklahoma region. The combined thickness of the Garber and Wellington formations is approximately 600 to 800 feet.

Carr and Marcher (1977) have identified differences in ground-water flow patterns within the Garber/Wellington aquifer. The shallow ground water generally flows laterally towards streams and springs where it discharges to the surface. A minor component of flow is vertical and leakage partially recharges deeper confined aquifers. The authors also note that shallow ground water occasionally flows upward where rivers or streams have deeply entrenched the bedrock and the potentiometric surface is higher than the surface-water elevation.

Ground water in the deeper portion of the Garber/Wellington aquifer flows primarily to the southwest along the regional dip. The points of discharge of the deeper ground water are outside the central Oklahoma region. Figure 4.3 shows the potentiometric surface of the Garber/Wellington aquifer in southern Logan and northern Oklahoma counties.

Recharge of the Garber/Wellington aquifer is accomplished through precipitation and infiltration in areas of outcrop. Infiltration through overlying porous and permeable strata also provides considerable recharge. Johnson (1983) identified the principal recharge area for the Garber/Wellington aquifer as an area lying generally north of the Canadian River, south of Guthrie, east of the Canadian County line, and west of Shawnee. Figure 4.4 shows the recharge area.

Bingham and Moore (1975) estimated the amount of water available for recharge of ground water in the central Oklahoma region. Average annual precipitation ranges from 28 inches per year near Kingfisher to about 41 inches per year near Holdenville. Approximately 24 to 30 inches per year is returned to the atmosphere through evaporation and transpiration. Runoff ranges from 2.5 to 8 inches per year. The authors estimate that 1.5 to 3.5 inches per year is subsequently available for recharge.

In addition to the Garber/Wellington aquifer, Quaternary-aged terrace and alluvial deposits are locally important sources of ground water. These deposits consist of lenticular unconsolidated gravels, sands, silts, and clays. Alluvium refers to sediments deposited along modern stream channels and flood plains. Terrace deposits are older alluvial deposits that remain after rivers shift position, or may represent previous flood plains. Figure 4.1 shows the extent of the surficial alluvium and terrace deposits in the area near the Cimarron facility.

According to Bingham and Moore (1975), well yields of 200 to 250 gallons per minute (gpm) are common and that up to 500 gpm have been reported locally from these deposits. Engineering Enterprises (1973) reports that ground water in the terrace deposits near the town of Crescent flows southward towards the Cimarron River and contributes to its base flow. Recharge of the terrace and alluvial aquifers also occurs through precipitation and infiltration; however, water levels in the alluvial aquifers are commonly maintained by streams and rivers.

#### 4.3 Ground-Water Use

The principal source of ground water in the area near the Cimarron facility is the Garber/Wellington formation. Well fields supply water to the towns of Edmond, Cashion, and others from this aquifer. North of the Cimarron River, domestic and agricultural users frequently obtain ground water from the Cimarron terrace deposits. Engineering Enterprises (1973) reports that well density in the terrace is approximately three wells per square mile. The river alluvium in the vicinity of the Cimarron facility is not used for ground water or drinking water supplies because of the salinity of the Cimarron River.

#### 4.4 Regional Ground-Water Quality

Bingham and Moore (1975) discuss ground-water quality in the region encompassed by the Oklahoma City quadrangle. Previously published water quality data were combined with samples collected by the authors to characterize ground-water quality in the region. A summary of their results is presented in Table 4.1. Table 4.2 is a summary of ground-water quality analyses compiled by the U.S. Geological Survey for wells in the Garber/Wellington aquifer in Logan County.

In general, the water from bedrock aquifers is of good quality although the water usually is hard to very hard. Ground water from terrace deposits is also of good quality. Water from the alluvium along the Cimarron, North Canadian and Canadian Rivers is generally fair to poor because of the poor quality of the river water (Bingham and Moore, 1975). Engineering Enterprises (1973) reports that the Cimarron River has elevated naturally occurring chlorides derived from the Big Salt plains area approximately 100 miles upstream from the Cimarron facility.

The Garber/Wellington aquifer generally has good water. Bingham and Moore (1975) report that in the central Oklahoma region, hardness ranges from 4 ppm to 538 ppm, with a median value of 156 ppm; sulfate ranges from 3 ppm to 1450 ppm with a median of 17 ppm; chlorides range from 0.2 ppm to 458 ppm, with a median of 14 ppm; and nitrate ranges from 0 ppm to 100 ppm with a median of 1 ppm. Generally, hardness and dissolved solids tend to increase with depth. These data are presented in Table 4.1.

Table 4.2 presents data compiled by the U.S. Geological Survey for wells screened in the Garber/Wellington aquifer at depths less than 200 feet below ground surface in the area near the Cimarron facility. The data represents wells located in an area defined by Township 15 North, Range 2 West on the southeast to Township 16 North, Range 4 West on the northwest. In this area, hardness ranges from 130 ppm to 1300 ppm, with an average of 381 ppm; sulfate ranges from 7 ppm to 1900 ppm, with an average of 245 ppm; chlorides range from about 5 ppm to 110 ppm, with an average of about 32 ppm; and nitrates plus nitrite ranges from 0.3 to 63 ppm, with an average of about 15 ppm.

Near the town of Crescent, ground water from the terrace deposits above the Cimarron River is generally of good quality. Engineering Enterprises (1973) reports that wells screened in the terrace deposits near Crescent have a hardness ranging from 100 ppm to 200 ppm; total dissolved solids range from 400 ppm to 1000 ppm; and chlorides average about 50 ppm. They also report, however, that the terrace aquifer is locally impacted by brines that were disposed in unlined pits in the Crescent oilfield. Chlorides have been measured up to 17,000 ppm in this area.

According to Engineering Enterprises (1973), the water quality in the alluvial aquifers is similar to the terrace aquifers where the alluvium is recharged by the terrace ground water. In general, however, the alluvial aquifers are of poor quality because they are recharged by the Cimarron River which contains high chlorides that result from water from the natural salt springs about 100 miles upstream.

#### 4.4.1 Background Nitrate and Fluoride Concentrations.

In the Garber/Wellington aquifer in the central Oklahoma region, Bingham and Moore (1975) report nitrate concentrations of 0 ppm to 100 ppm. Carr and Havens (1976) report nitrate concentrations of 1 ppm to 32 ppm from six wells in the Garber/Wellington aquifer near the Cimarron facility. The average nitrate concentration for the six wells is 12 ppm.

Carr and Havens (1976) also sampled one well in section 29, Township 15 North, Range 4 West for fluoride. The fluoride concentration was 0.9 ppm. At the Cimarron facility, twenty of the twenty four wells sampled had fluoride levels less than 0.5 mg/l. Regional fluoride concentrations in the Garber/Wellington aquifer are believed similar to these values.

#### 4.4.2 Background TOC and TOX Concentrations.

Total organic carbon (TOC) and total organic halides (TOX) are general indicators of ground-water impacts from organic origins. At the Cimarron facility, three of the four wells sampled had TOC concentrations less than the laboratory detection limit of 10 mg/l. A fourth sample had a TOC content of 12 mg/l. These are equivalent to regional background concentrations in the Garber/Wellington aquifer.

Regional TOX concentrations in the Garber/Wellington aquifer probably are similar to values in the shallow ground water at the facility. These values range from 62 ug/l to 130 ug/l.



#### 4.4.3 Background Radionuclide Concentrations.

Cimarron personnel installed monitoring wells approximately one-half mile south of the facility near the intersection of State Highways 33 and 74 to provide background data. These wells are up-gradient from the facility. Samples have been collected and analyzed for radionuclides since 1971. The data indicates that background values of U-238 are generally less than 0.7 pCi/l; Pu-239 is generally less than 0.010 pCi/l; gross alpha activity is less than 10 pCi/l; and gross beta activity is less than 20 pCi/l.

TABLE 4.1

## Regional Ground-Water Quality


(from Bingham and Moore, 1975)

AQUIFERS	HARDNESS (ppm)			SULFATE (ppm)			CHLORIDE (ppm)			NITRATE (ppm)			TDS (ppm)		
	minimum	maximum	median	minimum	maximum	median	minimum	maximum	median	minimum	maximum	median	minimum	maximum	median
Alluvium and Terrace deposits	14	1320	297	3.3	1320	64	2.0	1450	40	0.0	189	5.8	82	3060	520
Garber/Wellington	4.0	538	156	3.0	1450	17	0.2	458	14	0.0	100	1.0	101	2110	320
Other Permian Formations	40	1670	310	12	5350	73	9.0	945	40	0.0	175	14	246	5900	577
Vamoosa Formation	36	600	200	3.5	796	28	4.0	320	13	0.0	214	0.8	113	1540	357
Other Pennsylvanian Formations	9.0	2760	164	4.8	4850	35	3.0	2100	38	0.0	160	2.0	77	9580	416



TABLE 4.2

GARBER/WELLINGTON AQUIFER GROUND-WATER QUALITY  
 LOGAN COUNTY WELLS  
 Townships 15N-R2W to 16N-R4W  
 (From Carr & Havens, 1976)







PARAMETER	HIGH (ppm)	LOW (ppm)	AVERAGE (ppm)	STD. DEVIATION
Calcium	370	29	108.7	100.9
Chloride	110	4.8	31.7	32.6
Dissolved Solids - residue on evaporation	3260	215	758.2	907.5
Hardness	1300	130	381.2	316.2
Bicarbonate	420	136	293.2	74.8
Magnesium	89	15	35.2	22.6
Sodium	690	22	104.2	187.7
Nitrate	32	1	12	11.4
Nitrate + Nitrite	63	0.3	14.9	21.9
pH	8.1	7.2	7.8	0.3
Sulfate	1900	7	245.4	562.6
Depth (feet)	200'	41'	121.7'	



QUATERNARY



PERMIAN



**ALLUVIUM**

Sand, silt, clay, and lenticular beds of gravel. Thickness ranges from about 30 to 100 feet and probably averages about 50 feet along major streams. Along minor streams, thickness ranges from a few feet to about 50 feet and probably averages about 25 feet. Alluvium is a major aquifer in parts of quadrangle.

**TERRACE DEPOSITS**

Lenticular beds of sand, silt, clay, and gravel. Thickness ranges from a few feet to about 100 feet and probably averages about 50 feet along major streams. These deposits are major aquifers along Cimarron, Canadian, and North Canadian Rivers.

**DUNCAN SANDSTONE**

Mainly red-brown to orange-brown fine-grained sandstone, with some mudstone conglomerate and shale; grades northward into Cedar Hills Sandstone and Chickasha Formation. Thickness, 450 feet near Chickasha, 300 feet near Oklahoma City, and 100 feet or more near Okarche.

**BISON FORMATION**

Mostly red-brown shale; grades northward into many thin greenish-gray calcitic siltstones and some orange-brown fine-grained sandstones and siltstones. *Reeding Sandstone Bed* at base. Thickness ranges from 95 feet in south to 120 feet in north.

**SALT PLAINS FORMATION**

Red-brown blocky shale and orange-brown siltstone, grades southward into Purcell Sandstone in Norman area. Thickness, 200 feet.

**FAIRMONT SHALE**


Red-brown blocky shale; grades into Garber Sandstone at base. Thickness, 30 feet at Oklahoma City, 110 feet near Purcell, and 120 feet near Kingfisher.

**GARBER SANDSTONE**

Mostly orange-brown to red-brown fine-grained sandstone, irregularly bedded with red-brown shale and some chert and mudstone conglomerate. Thickness ranges from 150 feet in south to 400 feet or more in north. The Garber and underlying Wellington are major aquifers in Cleveland and Oklahoma Counties.

**WELLINGTON FORMATION**

Red-brown shale and orange-brown fine-grained sandstone, containing much maroon mudstone conglomerate and chert conglomerate to south. Thickness ranges from about 150 feet in south to 500 feet in north.




CONTOUR INTERVAL 100 FEET  
WITH SUPPLEMENTARY CONTOURS AT 50-FOOT INTERVALS  
DATUM: MEAN SEA LEVEL



**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
ENGLEWOOD, COLORADO

**FIGURE 4.1**  
**GEOLOGIC MAP**



808211



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

(from Landes, 1970)

**FIGURE 4.2**  
**TECTONIC PROVINCE MAP**  
**OF OKLAHOMA**


EXPLANATION

- 1100 — POTENTIOMETRIC CONTOUR DETERMINED FROM WELLS IN THE UPPER PART OF THE AQUIFER
- - 900 - - POTENTIOMETRIC CONTOUR DETERMINED FROM WELLS IN THE LOWER PART OF THE AQUIFER

Shows altitude at which the water level would have stood in tightly cased wells (1973-74). Contour interval 50 ft. Datum is mean sea level

- ⊙ Control point in the upper part of the aquifer
- Control point in the lower part of the aquifer

CIMARRON FACILITY



Base from U. S. Geological Survey  
1:24,000 and 1:62,500 quadrangles

(from Carr & Marcher, 1977)

808211



**JAMES L. GRANT & ASSOCIATES**


geotechnical engineering • management •  
computer science

ENGLEWOOD, COLORADO

FIGURE 4.3

GARBER/WELLINGTON AQUIFER

PIEZOMETRIC SURFACE




## EXPLANATION

### RECHARGE AREAS

Patterns of red lines on the map show known or potential recharge areas for the various bedrock aquifers.




**Recharge Areas.** This pattern shows areas that are known to be part of the recharge area for a bedrock aquifer: includes outcrops of the aquifer and of overlying porous and permeable rocks hydraulically connected with the aquifer.




**Potential Recharge Areas.** This pattern shows areas that may be part of the recharge area for a bedrock aquifer: includes areas where confining strata may contain pathways for downward movement of water to the aquifer, and safety zones (generally extending 4 miles beyond the known limits of the aquifer) that may overlie unknown extensions of the aquifer or rocks hydraulically connected with the aquifer.

### BEDROCK AQUIFERS



**GW**

**Garber Sandstone and Wellington Formation** (Permian in age). Fine-grained sandstone irregularly interbedded with shale and siltstone in central Oklahoma; grades into shale to north and south. Thickness of aquifer ranges from about 300 ft. in the south to about 800 ft. in the north. Wells commonly yield 25 to 400 gpm of water that is of good quality (generally 200 to 1,000 mg/L dissolved solids). Recharge areas consist of outcrops of the aquifer and extend eastward to the approximate top of shales that make up much of the lower one-third of the Wellington Formation. Potential recharge areas include areas in the west where aquifer underlies younger Permian strata; also areas that extend 4 miles south, west, and north of aquifer limits. References: HA-4; also Other Reports 4, 5, 29, 33, 61, 67, 68.




**Os-a**

**Oscar Group** (Early Permian or Late Pennsylvanian in age). Area designated a consists of fine-grained sandstone interbedded with shale and siltstone in central Oklahoma; contains some conglomerate in the south. Main part of aquifer is in lower half of Oscar Group; upper half of Oscar is predominantly shale. Thickness of aquifer ranges from about 150 ft. in south to 300 ft. in north. Wells commonly yield 25 to 50 gpm of water that is of good quality (generally 300 to 1,000 mg/L dissolved solids). Recharge areas include outcrops of Oscar Group; also included are outcrops of shales and sandstones in lower part of overlying Wellington Formation that appear to be hydraulically connected with either the Oscar or the Garber-Wellington aquifer. Potential recharge areas extend 4 miles north, east, and south of aquifer limits. References: HA-4.

Scale: 1:500,000

1 inch equals approximately 8 miles



Base map modified from U.S. Geological Survey, 1:500,000 series, dated 1972

## 5. SITE HYDROGEOLOGY

### 5.1 Site Physiography

The Cimarron facility lies in the Central Lowlands portion of the Great Plains physiographic province. The topography is characterized by low, rolling hills and incised drainages and floodplains. The elevation of the site above sea level ranges from about 940 to 1010 feet. The principal geomorphic feature at the site is the Cimarron River floodplain which is approximately one-half mile in width and trends east-west.

Vegetation in the site area is mainly native grasses with well developed tree stands in the drainages and along the bluff overlooking the Cimarron River.

Precipitation averages about 39 inches per year. Table 5.1 shows average monthly precipitation at the Cimarron facility. The majority of the precipitation occurs during the spring and fall months.

### 5.2 Site Geology

#### 5.2.1 Site Stratigraphy.

A veneer of soil, one to eight feet thick, covers most of the site. The shallow rock at the site consists of sandstones and siltstones of the Garber formation (Garber Sandstone). The Garber Sandstone is relatively thick in the facility area and no other formations were penetrated by drilling conducted during this investigation to depths of up to 140 feet. Figures 5.1 and 5.2 are geologic cross-sections showing the shallow subsurface stratigraphy underlying the site.

The deeper stratigraphic units in the area were penetrated by a proposed deep disposal well that was completed in 1969. This well is the deepest borehole known to have been drilled in the immediate vicinity of the site. The deep well is on Cimarron facility property near the uranium plant. The depth of the well is 2078 feet. The top of the unit immediately underlying the Garber, the Wellington formation, was identified at 200 feet below the ground surface. The Wellington consists of 960 feet of red shale with several thin siltstone beds. The top of the Wolfcampian age Stratford formation was found at 1160 feet. It is 870 feet thick and consists of red and gray shale with thin anhydrite beds in the upper part. The lower part of the Stratford



is predominately red and gray sandy shale with three porous sandstone members.

Process wastes were planned to be injected into one of the sandstone members of the Stratford; however, no injection into the well ever was conducted. The injection well will be plugged and abandoned in accordance with State regulations as part of the site decommissioning activities.

#### 5.2.1.1 Shallow Stratigraphic Units.

##### SOIL LAYER:

The soil layer ranges from one to eight feet thick and is chiefly a reddish-brown silty sand. This soil type predominates and is present where the underlying rock type is sandstone. A very fine sandy silt/clay also occurs at the site where the underlying bedrock is a sandy siltstone or mudstone. The silt/clay type soils are less abundant than the silty sand soils.

##### ROCK LAYERS:

The upper portion of the Garber Sandstone at the site consists primarily of sandstone layers separated by relatively continuous siltstone and mudstone layers. For the purposes of this report, the lithologically similar sandstones are designated, from shallowest to deepest, Sandstones A, B, and C. Similarly, the intervening siltstones and mudstones are designated Mudstones A and B. The discussion of the stratigraphy and lithology of these strata, and later references to hydrogeologic and chemical properties, are keyed to this arbitrary nomenclature.

- o SANDSTONE A: The first or uppermost sandstone is up to 35 feet thick. The bottom of this sandstone occurs at an elevation of about 970 feet (msl).
- o MUDSTONE A: The mudstone stratum separating Sandstones A and B ranges from about 6 to nearly 20 feet thick.
- o SANDSTONE B: The second or intermediate sandstone is up to about 30 feet thick and lies roughly between the 925 and 955 feet elevations (msl).
- o MUDSTONE B: The mudstone stratum separating Sandstones B and C ranges from about 6 to 14 feet thick.

- o SANDSTONE C: The third significant sandstone may not have been fully penetrated during this investigation. The presence of a basal siltstone or mudstone layer was not verified at the depth penetrated by the site wells; but, Sandstone C appears to be at least 55 feet thick and contains interbedded siltstones.

These strata are inferred to have been deposited in a fluvial/upper deltaic system. Lateral facies changes are frequent and correlations over long distances are difficult, perhaps as a result of shifting channel locations. Each of the major strata identified above has interbedded, thin and discontinuous sandstones and siltstones. Patterson (1933) interprets the Garber as originating from a deltaic system that entered the Permian sea from the east.

#### 5.2.1.2 Description of Sandstones:

All three sandstones encountered during this investigation can be described as generally fine to very fine grained with well sorted subangular to rounded grains. Variable silt content was observed in the sandstones. The estimated silt content ranges from less than 10 to up 50 percent. Where the silt content is high, distinction between sandstone and siltstone is difficult. The sand grains are virtually all quartz, with minor amounts of potassium feldspar and occasional mafic grains such as magnetite. Micas are minor constituents. Intergranular porosity is generally good, though obviously varies with silt content.

The sandstones typically are weakly cemented and friable. The cementing agents appear to be calcite and hematite; however, silt and clay-sized fractions in the matrix may also contribute to cementation. Thin intervals are present occasionally that are well cemented and hard. These intervals are frequently conglomeratic with gypsum and possibly barite providing additional intergranular cement.

The sandstones often are cross-stratified with thin, silty laminae. The cross-stratification is planar and might be indicative of bar deposition in fluvial systems. Cross stratification was usually found near the middle of the sandstone intervals.

Conglomeratic intervals were encountered in most of the borings. These intervals are associated with the sandstone strata although, in some instances, the matrix materials are mudstones. The conglomeratic intervals are 2.5 feet or less in thickness. The matrix is either sandstone or mudstone and the clasts are predominately mudstone. Patches of sandstone clasts also are present. These conglomeratic intervals commonly possess a vuggy porosity. The vugs probably formed through dissolution of lithic clasts. The presence of vugs is not attributed to drilling fluids

because the vugs often are lined with euhedral calcite, gypsum and barite crystals.

The origin of the conglomeratic sandstones and mudstones might be related to an influx of more rapidly moving water, such as a flood. The influx could have caused the pre-existing rocks and sediments to be torn up and re-transported. Transport distance probably was minimal as the weakly-cemented clasts would have disintegrated if they were agitated for prolonged periods. In all cases, a fining upward sequence in grain size accompanies the conglomeratic intervals, as is typical in fluvial and deltaic systems.

#### 5.2.1.3 Description of Mudstone:.

Separating the sandstones are fine-grained, silty and shaley beds. These beds were identified in the field as mudstones, a genetic description inferring their origin. Dessication cracks in the mudstones were observed in several borings and these beds might represent flood plain deposits. Stratification within the mudstones is largely absent and they lack the fissile nature characteristic of shales.

The mudstone units typically are poorly consolidated as indicated by the tendency for core samples to deteriorate rapidly. The mudstone cores have a consistency more like a very stiff to hard sandy silt or clay than rock, even at depths greater than 100 feet below ground.

Encapsulating the mudstone layers were thin, bluish-gray zones or layers that ranged from less than 0.1 inches to over 4 inches in thickness. These layers tentatively were identified in the field as "reduction zones." Reduction spots were also observed. This phenomenon is common in red bed formations and is not unique to the site. In the subsurface at the facility, the thickness of the bluish-gray layers is directly proportional to the thickness of the silt and clay-rich layers they bound.

The reduction zones might represent intervals where ferric oxides have been reduced to ferrous compounds. Ferrous iron is soluble and is removed by ground water. Al-Shaieb et.al. (1977) attribute the reduction of ferric iron to a reaction with hydrogen sulfide produced either by the contact of sulfate with hydrocarbons, or hydrogen sulfide released directly from naturally occurring hydrocarbons.

### 5.2.2 Structure.

The strata underlying the Cimarron facility are largely undeformed. Dip is westerly to southwesterly and has been described by various authors as ranging from 20 to 40 feet per mile. Measurements at outcrops at the facility indicate the sandstones strike to the northwest and dip very slightly to the southwest. The site lies to the east of the Nemaha ridge, a narrow, subsurface north-northwest trending uplift formed during the Mississippian.

The Nemaha ridge or uplift is characterized by a series of en-echelon, parallel normal faults which are down-thrown on the west side, with anticlinal folding across the top. Some reactivation of the faults occurred during the early Pennsylvanian; however, movement has not been described since that time. Regional dip is to the southwest into the Anadarko basin and is the result of post-Paleozoic uplift and erosion.

### 5.2.3 Mineralogy and Rock Chemistry.

Analysis of selected samples for mineralogy and chemical parameters including cation exchange capacity and exchangeable cation were performed by Auburn University. These tests were performed to verify the field classification of soils and rocks, and to provide information useful for determining the capacity of selected rock units to adsorb radionuclides and inhibit their migration. Table 3.7 summarizes the results of these analyses.

#### 5.2.3.1 Mineralogy.

##### 5.2.3.1.1 Testing

Site representative samples were analyzed via X-ray diffraction at Auburn University for major mineral constituents. X-ray diffraction is one of the more effective analytical methods for identifying clay minerals in rock material. The mineral constituents of the samples analyzed are listed in Table 3.7.

##### 5.2.3.1.2 Discussion

The mineralogical analyses indicate that quartz and feldspar are the predominant minerals of the larger sized fractions. Kaolinite and 2:1 expanding layer clay minerals (montmorillonites) dominate the fine fraction in nearly equal proportions. Minor amounts of calcite, iron oxides and iron hydroxides are identified and are probably the cementing agents.

The particle size distributions reflect the field descriptions listed in Table 3.7. The rock units identified as mudstones and sandy mudstones are composed predominantly of silt-size particles. The sandstones are dominated by particle sizes in the 0.25 to 0.05 mm range, which corresponds to the fine and very-fine grained descriptions assigned in the field.

Samples from the "reduction zones", Nos. CH-2, CH-12, and CH-14, are of particular interest. The distinction between these samples and the "non-reduced" samples is subtle. Samples CH-1 and CH-2 are from essentially the same interval and are nearly identical in gross mineralogy. The principal difference between the two samples is that the iron content of sample CH-2 is about one-half that of CH-1. Samples CH-12 and CH-14 had low iron values compared to non-reduced samples as well.

#### 5.2.3.2 Soil and Rock Chemistry.

##### 5.2.3.2.1 Testing

In addition to mineralogy, the samples submitted to Auburn University were analyzed for cation exchange capacity (CEC) and exchangeable cation (EXC). These results are presented in Table 3.7.

##### 5.2.3.2.2 Discussion

Cation exchange capacity ranges from 2.96 to 22.75 meq/l. The majority of samples had CEC's less than 10 meq/l. The clay minerals responsible for the cation exchange capacity of the samples are identified as montmorillonites.

The most prevalent exchangeable cations are divalent. Calcium and magnesium are the significant exchangeable cations. Potassium and sodium are also present but their concentrations are about an order of magnitude less than calcium and magnesium.

#### 5.2.3.3 Chemical Interactions.

The hydrogeologic environment underlying the site is composed of physical and chemical systems. The physical system is characterized by lithologies, structures, hydraulic conductivities, and flow gradient and directions. The chemical system is characterized by the interaction between ground-water chemistry and the enclosing strata.

#### 5.2.3.3.1 Chemical Environments

The chemical environment underlying the site is characterized by the chemistry of the unsaturated and saturated zones. The unsaturated zone environment will be dominated by the chemistry of the soils and rock strata. The saturated zone will be dominated by the chemistry of the ground water.

Ground water at the site is oxygenated and slightly alkaline. The strata appear oxidized and have a relatively low cation exchange capacity. The organic content of the strata is negligible.

#### 5.2.3.3.2 Site-Related Elements

Elements targeted in this investigation that may interact with the subsurface environment include fluoride, nitrate, plutonium, uranium, thorium and radium. Thorium and radium were not used in the facility processes; however analyses were conducted to determine background concentrations. The availability of plutonium for interaction with the environment is considered negligible. Plutonium was only present within the plutonium plant and in very small concentrations in the sewage lagoon sediments.

Thorium was present as drummed waste in the former burial location. The drums containing thorium were removed and disposed in a commercial disposal facility. Some thorium processing equipment from the Cushing facility was stored at the uranium facility yard; however thorium has not been detected above natural background levels. Radium was not used in the facility production processes and there is no source for radium to enter the environment. Consequently, thorium and radium encountered in this investigation are considered to be representative of background sources, and not derived from materials processed by the Cimarron facility.

### 5.3 Surface-Water Hydrology

#### 5.3.1 Local Surface-Water Bodies.

The principal surface-water bodies at the site are the three reservoirs indicated on the site map and the Cimarron River.

The water elevation of the three reservoirs was determined at the time the monitoring wells were surveyed. The water elevations for reservoirs 1, 2 and 3 are 959.3, 966.3, and 959.7 feet above mean sea level, respectively. The average stage for the Cimarron River near the facility is approximately 940 feet above mean sea level.

### 5.3.2 Influence on Ground-Water System.

The three reservoirs appear to influence shallow ground-water flow at the site. Reservoirs 1 and 3 have water levels significantly below the water table in the nearest wells indicating that shallow ground water maintains the water level of these reservoirs and hence provides the base flow for the streams that exit the reservoirs.

## 5.4 Site Ground-Water Hydrology

### 5.4.1 Ground-Water Occurrence.

Shallow ground water occurs under water table and partially confined conditions at the site. The depth to water in the shallow wells ranges from about 10 to 30 feet below ground level. The shallow wells constructed during this investigation are all screened at about the same stratigraphic interval. This interval is approximately the base of the first major sandstone (sandstone A). Figure 5.4 is a map of the potentiometric surface of the shallow ground water.

The water table shows a strong influence exerted by topography and the surface-water bodies. Seepage faces were observed along the slope above the Cimarron River floodplain. In the vicinity of Well 1334, seepage occurs at an elevation of about 964 feet with standing water occurring in a marshy area at an elevation of about 960 feet.

All the rocks below the water table are saturated. The deep wells were screened in a confined sandstone that occurs approximately 80 to 100 feet below the ground surface. This interval was subsequently identified as the third major sandstone (sandstone C) underlying the site. Figure 5.5 is a map of the potentiometric surface defined by the deep wells.

#### 5.4.2 Ground-Water Flow System.

Shallow ground water is strongly influenced by topography and the surface-water bodies. Flow direction is primarily north-northwest toward the Cimarron River. The incised drainages and bluff overlooking the river's floodplain exert local influences. The gradient averages approximately 0.025 except where it steepens as a result of proximity to discharge areas.

Ground water from the confined aquifer screened in the deep wells also flows to the north-northwest. The gradient is approximately 0.014. This deeper ground-water interval probably recharges the Cimarron alluvium and contributes to the base flow of the Cimarron River.

#### 5.4.3 Hydraulic Properties of Water-Bearing Strata.

Hydraulic conductivities of the Garber Formation sandstones generally are moderate. The primary hydraulic conductivity control is the good intergranular porosity observed in the core samples. The sandstones are poorly cemented and show few diagenetic effects, thus the primary porosity restrictions are the variable amounts of fines present in the sandstones. Inspection of outcrops at the site and core samples revealed minimal jointing indicating that the effect of fractures on hydraulic conductivities is expected to be low.

The hydraulic conductivities of the sandstones that are screened in both the deep and shallow wells have been measured by slug test methods. Descriptions of the test methods and analytical techniques was presented in Section 2.2.6.

The hydraulic conductivity of the shallow aquifer ranges from  $2.41 \times 10^{-4}$  cm/sec to  $5.7 \times 10^{-3}$  cm/sec. The geometric mean of the measured values is  $1.03 \times 10^{-3}$  cm/sec. The transmissivity of this aquifer ranges from 10.3 ft sq/day to 108 ft sq/day, with a geometric mean of 33.4 ft sq/day.

The hydraulic conductivity of the deep aquifer ranges from  $1.39 \times 10^{-5}$  cm/sec to  $7.06 \times 10^{-4}$  cm/sec, with a geometric mean of  $1.27 \times 10^{-4}$  cm/sec. The transmissivity ranges from .67 ft sq/day to 50 ft sq/day, with a geometric mean of 7.96 ft sq/day. Slug test results are included in Table 3.3.



## 5.5 Ground-Water Quality

A standard water quality analysis was performed on a sample of ground water from Well 1324. This well is up-gradient from all facility components and is representative of background presence of major cations and anions in the shallow ground water. Shallow ground-water quality at the site is consistent with the regional average concentrations of major ions reported by Bingham and Moore (1975) and Carr and Havens (1976). The results are presented in Table 3.4.

### 5.5.1 pH and Conductivity.


At the time of sampling, pH and specific conductance were measured for all ground-water samples collected. In general, the ground water at the site is near neutral to slightly alkaline. Ground water from the deep wells is similar in pH to the shallow, but has significantly higher specific conductance.

Ground water from the shallow wells has a pH ranging from 6.99 to 7.71. Specific conductance ranges from 400 to 1590 micromhos per centimeter (umho/cm) and averages 646 umho/cm. The highest value indicated for the shallow wells, 1590 umho/cm, is from Well 1330. Ground water from the deep wells has a pH ranging from 6.91 to 7.39. Specific conductance ranges from 1910 to 3190 umho/cm, and averages 2480 umho/cm.

Specific conductance values are higher in the deeper ground water as a result of limited infiltration and mixing of precipitation, according to Bingham and Moore (1975).

TABLE 5.1  
Average Monthly Precipitation

MONTH	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	AVERAGE
January	0.5	1.3	0.9	0.0	0.0	1.2	1.0	2.9	0.0	2.2	1.3	1.0
February	4.0	0.5	0.8	1.2	1.1	4.0	1.0	8.8	0.8	2.7	0.2	2.3
March	1.3	4.1	2.0	3.1	1.7	3.6	4.2	8.5	0.4	5.0	3.8	3.4
April	2.1	4.1	5.8	0.3	2.4	2.9	2.7	5.9	3.6	0.9	5.0	3.2
May	11.4	6.5	9.8	4.4	13.4	6.5	2.4	2.9	5.9	7.5	0.8	6.5
June	7.2	3.9	3.6	7.6	6.2	5.5	4.7	6.0	4.0	4.6	3.2	5.1
July	2.3	1.9	0.0	5.6	0.8	1.4	0.2	4.8	2.3	5.6	1.7	2.4
August	2.5	4.8	0.3	5.5	1.5	2.6	2.5	2.6	3.5	2.5	2.5	2.8
September	3.9	8.4	1.6	2.7	0.7	1.1	1.4	6.5	9.9	5.1	7.5	4.4
October	0.6	0.9	1.7	3.6	0.5	8.1	4.0	6.4	12.8	0.1	2.4	3.7
November	5.0	3.2	0.3	1.9	2.7	2.0	2.9	2.7	2.6	2.8	4.2	2.7
December	0.0	1.6	2.0	0.6	1.2	0.4	4.8	0.2	3.2	2.6	0.5	1.5
Totals	40.7	41.1	28.6	36.2	32.0	39.1	31.7	58.1	48.9	41.5	32.9	39.2




- LEGEND**
- CONCRETE
  - PORTLAND CEMENT/  
SODIUM BENTONITE GROUT
  - GROUND-WATER LEVEL
  - SODIUM BENTONITE  
PELLET SEAL
  - SAND
  - SCREENED INTERVAL
  - SAND
  - SODIUM BENTONITE  
PELLET BACKFILL
  - B.T. @ 44.0' **BORING TERMINATION DEPTH**

**NOTE:**  
Refer to Figure 5.3 for Cross-section location.




**JAMES L GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 5.1**  
**GEOLOGIC CROSS-SECTION A-A'**



**NOTE:**  
 Refer to Figure 5.1 for legend.  
 Refer to Figure 5.3 for Cross-section location.




808211




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 5.2**  
**GEOLOGIC CROSS-SECTION B-B'**




**James L Grant & Associates**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 5.3**  
**CROSS-SECTION LOCATION MAP**



**jlgr**  
JAMES L. GRANT & ASSOCIATES  
geotechnical engineering • management •  
computer science  
ENGLEWOOD, COLORADO

FIGURE 5.4  
SHALLOW WELL  
POTENTIOMETRIC SURFACE



**alg**  
**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 5.5**  
**DEEP WELL POTENTIOMETRIC SURFACE**

## 6. SITE-SPECIFIC PARAMETER ANALYSIS

### 6.1 Site Ground-Water Analyses

Ground-water samples were collected and analyzed for specific parameters which potentially are related to facility production and decommissioning activities. The parameters include fluoride, nitrate, TOC and TOX, gross alpha and beta activity, Pu-239, Ra-228, Ra-226, Th-232, Th-228, U-238, U-235, and U-234. Each of these parameters are discussed in the following sections.

#### 6.1.1 Fluoride and Nitrate.

Fluoride and nitrate were present in the wastewater stream discharged from production operations. The presence of these ions at concentrations above background could be an indication of facility effects. Figure 6.1 shows the concentrations of fluoride in ground-water samples from around the site. Figure 6.2 shows the concentrations of nitrate in ground water.

#### Fluoride

The background concentration of fluoride is interpreted to be approximately 1 milligram per liter (mg/l) or less. Twenty of the twenty-four wells had concentrations less than 1 mg/l. Well 1332 had a fluoride concentration of 1.30 mg/l.

In the March, 1989 data, three wells had fluoride concentrations significantly higher than the background value. These wells and the fluoride concentrations were: Well 1312 - 50 mg/l; Well 1313 - 140 mg/l; and Well 1336 - 17 mg/l. These wells all are completed in Sandstone A, the shallowest water-bearing stratum.

These three wells contain levels of fluoride in excess of the EPA Maximum Contaminant Level (MCL) of 4.0 mg/L. These wells are down-gradient from the two closed wastewater ponds. The ground-water monitoring results from the annual sampling of these wells indicates that the concentration of fluoride is decreasing. The results of the annual sampling are tabulated in Table 6.1.

The proximity of Wells 1312, 1313, and 1336 to the two wastewater retention ponds indicates that the ponds had been sources of fluoride. The ponds have since been closed, back-filled, and reclaimed, and the detections at the monitoring wells reflects residual amounts of fluoride remaining in the un-saturated zone or in the water-bearing stratum.



### Nitrate

The average nitrate concentration reported by Carr and Havens (1976) for wells completed in the Garber/Wellington aquifer is 12 mg/l, which is probably representative of regional background in the Cimarron facility area. Wells at the site which are located in areas up-gradient of plant facilities, including Wells 1324, 1325, and 1335, show nitrate concentrations between 13 and 22 mg/l. The nitrate concentrations depicted in Figure 6.2 indicate that twelve of the twenty-four wells show nitrate concentrations above the MCL of 10 mg/l. Local nitrate background is higher than the MCL.

Only five monitoring wells have concentrations greater than 22 mg/l; four of these wells have concentrations greater than 100 mg/l. All five of these higher concentration wells are completed in the shallowest water-bearing stratum, Sandstone A. Wells 1311, 1312, 1313, and 1336 show concentrations of 66 mg/l, 1020 mg/l, 720 mg/l, and 1260 mg/l, respectively. Well 1311 is up-gradient, but near, closed wastewater pond #1. The three remaining wells are down-gradient from closed wastewater ponds #1 or #2.

The nitrate concentration at Well 1330 was 172 mg/l. This well is located near the edge of a cultivated wheat field. The location is also adjacent to a small drainage that begins in the uranium plant areas. Surface runoff from part of the plant area drains toward the well location. A significant portion of the runoff comes from cultivated fields and is believed reflect the application of nitrogen-based fertilizers.

#### 6.1.2 TOC and TOX.

Total organic carbon (TOC) and total organic halide (TOX) analyses were performed on four ground-water samples. These organic species parameters are general indicators of ground-water quality. Three wells near the facility production operations and one well near the designated landfill area were tested. These all are Sandstone A wells and include Well 1322 between the uranium and plutonium plants, Well 1326 east of the uranium plant, Well 1329 south of the uranium plant and near the former solvent extraction area, and Well 1325 south of the designated landfill area. Well 1325 was chosen to provide background data.

Only the background well, Well 1325, showed a TOC concentration above the laboratory detection limit of 10 mg/L. The source or type of organic compounds responsible for the 12 mg/l concentration at the background well is not known but probably is related to natural causes.

The total organic halide concentrations ranged from 62 ug/l in Well 1329 to 130 ug/l in Well 1325. 130 ug/l is probably representative of local background. The TOX results do not indicate that organic constituents used during facility production operations have impacted the shallow ground-water quality.

### 6.1.3 Radionuclides.

The ground-water samples also were analyzed for gross alpha and beta activity, Pu-239, Ra-226, Ra-228, Th-232, Th-228, U-238, U-235, and U-234. These results are presented in Table 3.4. Figure 6.3 shows alpha activity in ground water; Figure 6.4 shows beta activity; Figure 6.5 shows total uranium activity; and Figure 6.6 shows total radium activity. Plutonium and thorium activities are not indicated on separate figures because the ground-water analyses indicate they are not present in quantities above background.

#### 6.1.3.1 Gross Alpha Activity.

Figure 6.3 shows four areas where ground water shows gross alpha activity greater than 50 picoCuries per liter (pCi/l). These are the two closed wastewater ponds, the former burial ground, and an area down-gradient from the uranium plant.

- o Down-gradient from waste water ponds #1 and 2: Well 1312, 59 pCi/l, and Well 1313, 260 pCi/l, are down-gradient from pond 1. Well 1336, 140 pCi/l is down-gradient from pond #2. These wells are completed in Sandstone A.
- o Down-gradient from former burial area: Wells 1315, 1316, and 1317 had gross alpha levels of 6440 pCi/l, 331 pCi/l, and 66 pCi/l, respectively. These wells are completed in Sandstone A.
- o Down-gradient from the uranium plant: Well 1331, 190 pCi/l, and Well 1323, 51 pCi/l. Well 1331 is completed in Sandstone A and Well 1323 is completed in Sandstone C.

At four locations, wells completed in Sandstone A are paired with wells completed in the deeper Sandstone C. At three of these locations, the deep well has higher gross alpha activity levels than the shallow well. These data are summarized below:

Well	Completion	Gross Alpha Concentration
1320	A	<10 pCi/l
1321	C	18 pCi/l
1322	A	15 pCi/l
1323	C	51 pCi/l
1329	A	12 pCi/l
1328	C	29 pCi/l
1333	A	47 pCi/l
1332	C	23 pCi/l

The generally higher activity levels in the deeper, Sandstone C wells reflect higher natural background level in the confined sandstone. The Sandstone C data are not interpreted to reflect effects of the plant since several significant confining layers separate Sandstone C from the most shallow stratum.

The MCL for gross alpha excluding uranium and radon is 15 pCi/l. Fourteen of the twenty-four wells sampled had values greater than 15 pCi/l. These wells generally are located in one of the areas previously identified as locally impacted.

#### 6.1.3.2 Gross Beta Activity.

Thirteen of the twenty-four wells sampled had gross beta activity levels less than the detection limit of 20 pCi/l, and five more wells had values between 20 and 26 pCi/l. These data suggest that background levels are generally comparable to these values. The EPA has not published guidelines or standards for beta activity in ground water.

Figure 6.4 depicts gross beta activity in ground water. The map shows that the highest gross beta concentrations occur down-gradient from the two closed wastewater ponds and the former burial ground, and in the surface-water drainage feature north and down-gradient from the uranium building.

The six wells with gross beta values of 50 pCi/l or more are summarized below.

- o Down-gradient from waste water pond #1: Wells 1312, 2370 pCi/l and 1313, 2200 pCi/l. These wells are completed in Sandstone A.
- o Down-gradient from waste water pond #2: Well 1336, 4970 pCi/l. This well is completed in Sandstone A.

- o Down-gradient from former burial area: Wells 1315, 660 pCi/l and 1316, 100 pCi/l. These wells are completed in Sandstone A.
- o Southwest and down-stream (surface water) from the uranium building: Well 1330, 62 pCi/l. This well is completed in Sandstone A.

Gross beta values do not exceed background in shallow or deep wells at any of the locations of paired Sandstone A and C wells.

#### 6.1.3.3 Uranium.

The EPA has not yet established specific guidelines or limits on uranium activity in drinking water; however the proposed rules governing uranium in drinking water supplies will be announced in the summer of 1990. It is anticipated that the MCL for uranium will be in the 20 to 40 pCi/l range (Mr. Bob Clement, U.S. EPA Drinking Water Section, Denver, personal communication).

Figure 6.5 shows total uranium (U-238 + U-235 + U-234) activity at the facility. The distribution of uranium activity levels is comparable to the gross alpha activity levels shown in Figure 6.3. Figure 6.5 also suggests that four site-activity related sources for uranium are present. Locations and wells where uranium levels exceed 30 pCi/l are summarized below.

- o Down-gradient from waste water ponds #1 and 2: Well 1312, 58 pCi/l, and Well 1313, 117 pCi/l, are down-gradient from closed wastewater pond #1. Well 1336, 101 pCi/l is down-gradient from closed wastewater pond #2. These wells are completed in Sandstone A.
- o Down-gradient from former burial area: Wells 1315, 5230 pCi/l, and 1316, 287 pCi/l. These wells are completed in Sandstone A.
- o Down-gradient from the uranium plant: Well 1331, 165 pCi/l. This well is completed in Sandstone A.

At three of the four locations where paired Sandstone A and C wells were completed, the deep well has higher uranium levels than the shallow well. These data are summarized below:

Well	Completion	Total Uranium Concentration
1320	A	8.85 pCi/l
1321	C	10.97 pCi/l
1322	A	12.23 pCi/l
1323	C	27.22 pCi/l
1329	A	7.43 pCi/l
1328	C	27.66 pCi/l
1333	A	24.91 pCi/l
1332	C	20.42 pCi/l

These wells show the same pattern as described for gross alpha activity levels. The slightly higher uranium activity levels in the deep wells is representative of regional background values.

#### 6.1.3.4 Radium.

Figure 6.6 shows areal variations in total radium activity (Ra-228 + Ra-226) in the ground-water samples. The analyses are tabulated in Table 3.4. Radium sources were not used at the facility, and concentrations detected in the ground-water samples represent naturally-occurring levels. Table 6.2 presents the radium analyses in order of increasing concentration. Statistical analyses of the radium data were performed to determine background levels and the statistical significance of any variations.

A visual inspection of Table 6.2 indicates that two populations of radium values may exist. Nineteen of the twenty-four wells have values less than 0.5 pCi/l, four of the twenty-four lie between 1.1 and 2.9 pCi/l, and Well 1336 showed a concentration of 9.78 pCi/l. A histogram and probability distribution were constructed to determine how the data are distributed.

Figure 6.7 is a histogram of the natural logarithm of radium concentrations in ground water, which shows a log-normal distribution skewed to the right. A second population may be indicated by the increased number of observations in the last three classes.

Figure 6.8 is a probability plot of the log-transformed radium values. The majority of values in Figure 6.8 generally lie along a straight line, confirming the data are log-normally distributed (EPA, 1989). Two populations and an outlier are suggested in Figure 6.8.

A t-test was performed to determine the statistical significance of the radium values greater than 1 pCi/l. The calculations were performed in accordance with the procedures presented in 40 CFR Part 264, Appendix IV. The outlier, 9.78 pCi/l, was not included in the calculations.

The t-test assumed the data represents one population (all background) and the statistical significance of the values lying above 1 pCi/l compared to the population mean was calculated. The test conducted in this manner is more likely to fail to recognize a statistical difference in the larger values. Statistical significance was determined by calculating a t-statistic at the 0.05 level of significance and comparing it to a comparison t-statistic (40 CFR, Part 264, Appendix IV).

The t-statistic,  $t^*$ , is calculated to be 3.72. The comparison t-statistic,  $t_c$ , is calculated to be 2.26. Since  $t^*$  is greater than  $t_c$ , the group of values lying between 1.1 and 2.9 pCi/l represent a significant increase compared to background (40 CFR, Part 264, Appendix IV).

Since nineteen of the twenty-four wells had total radium concentrations less than 0.5 pCi/l and the log-transformed probability plot of radium concentrations suggests two populations are present, background is believed to be represented by the group of values below 0.5 pCi/l. The background mean is 0.155 pCi/l with a standard deviation of 0.141 and a variance of 0.020. Values above 1 pCi/l lie greater than six standard deviations from the background mean. The locations and wells where radium values elevated above background were reported are summarized below.

- o Down-gradient from waste water ponds #1 and 2: Well 1312, 1.83 pCi/l, and Well 1313, 2.83 pCi/l, are down-gradient from pond 1. Well 1336, 9.78 pCi/l is down-gradient from pond #2. These wells are completed in Sandstone A.
- o Down-gradient from former burial area: Well 1315, 1.61 pCi/l. This well is completed in Sandstone A.
- o Well 1332: Well 1332 with a level of 1.18 pCi/l is a deep Sandstone C well northwest of the sewage lagoons. The shallower Sandstone A wells in the area do not exhibit radium levels above background.

Since no sources of radium were managed at the facility, the elevated radium cannot result from leaching of waste materials. Changes in ground-water chemistry from natural background near the wastewater ponds and the former burial location could be responsible for the slightly elevated values. The wastewater disposed in the now-closed ponds may have altered the ground-water chemistry sufficiently to elute naturally occurring radium from the aquifer matrix.

The maximum contaminant level (MCL) for combined Ra-228 and Ra-226 in community water supplies is 5 pCi/l. Only Well 1336, down-gradient from wastewater pond #2, exceeds this standard.

#### 6.1.4 Facility Impacted Areas.

The ground-water analyses indicate that there are four likely sources of site-related activity impacts. These include the closed wastewater ponds #1 and #2, the former burial ground, and the uranium plant areas. Elevated fluoride, nitrate, uranium, and gross alpha and beta activities were detected near the wastewater ponds. Elevated uranium, and alpha and beta activity were detected near the former burial location. Elevated nitrate and uranium concentrations, and alpha activity were detected near the uranium plant.

### 6.2 Site Soil and Rock Analyses

Selected soil and rock samples were submitted to the Kerr-McGee Technical Center laboratory for fluoride, nitrate, TOC, gross alpha and beta activity, Pu-239, Ra-228, Ra-226, Th-232, Th-228, U-238, and U-234 analyses. The samples selected were representative of the various strata encountered in the shallow subsurface, and emphasize those intervals that may be the host for the contaminants and retarding medium for the vertical and horizontal movement of contaminants. Before the samples were shipped to the laboratory, the uranium activity in each sample was measured by Cimarron personnel by gamma spectrometry. The results of the analyses are summarized below.

#### 6.2.1 Fluoride and Nitrate.

Fluoride and nitrate were detected in all selected soil and rock samples submitted to the laboratory. Fluoride concentrations ranged from 18 ppm to 640 ppm and are comparable to the average naturally-occurring crustal abundance of fluoride in sedimentary rocks reported by Levinson (1980) and Mason (1966), which ranges up to 740 ppm. Although Figure 6.9 shows a positive correlation between fluoride and uranium, neither set of values are above

natural background levels and may not be directly related to past activities at the facility.

Nitrate concentrations ranged from 2 ppm to 130 ppm and show no apparent correlation with the other parameters analyzed.

#### 6.2.2 Total Organic Carbon.

Total organic carbon (TOC) was analyzed to determine if organic materials in the subsurface adsorbed uranium. TOC in the soil and rock samples ranged from less than the detection limit of 10 ppm to 3110 ppm. The highest value occurred at Well 1326 in soil from the two to four feet deep interval. Organic carbon does not appear to have adsorbed uranium as no correlation between TOC and uranium concentrations was determined.

#### 6.2.3 Radionuclides.

Site soil and rock samples were analyzed for gross alpha and beta activity, Pu-239, Ra-228, Ra-226, U-238, U-234, Th-232, and Th-228. The laboratory analyses are tabulated in Table 3.5.

##### 6.2.3.1 Alpha and Beta Activity.

Gross alpha activity values ranged from less than the detection limit of 10 pCi/g to 38 pCi/g. The higher values were all associated with mudstone samples. No sandstone samples had gross alpha values higher than 12 pCi/g. Alpha activity is probably related to naturally-occurring isotopes and the higher concentrations detected in the mudstones samples reflects adsorption on the clay-rich mudstone matrix.

None of the samples submitted had values for gross beta activity greater than the detection limit of 20 pCi/g.

##### 6.2.3.2 Plutonium.

No plutonium above background was detected in any samples submitted. Reported values range from 0.001 to 0.006 pCi/g, which are representative of background values. The precision of these analyses is 0.001 pCi/g.



#### 6.2.3.3 Uranium.

Uranium-238 ranged from 0.16 to 0.84 pCi/g. Uranium-234 ranged from 0.21 to 0.73 pCi/g. The higher concentrations for both isotopes were associated with mudstone samples. There is no apparent correlation with proximity to facility components and is therefore attributed to be representative of naturally-occurring uranium rather than an impact from plant activities. A greater concentration in the higher surface area mudstone matrix is to be expected as it provides an active adsorption environment.

#### 6.2.3.4 Radium.

Radium-228 ranged from 0 to 1.9 pCi/g. Radium-226 ranged from 0 to 0.77 pCi/g. As was reflected in the uranium values, the higher radium values are associated with mudstone samples. These values represent naturally-occurring radium and do not indicate an impact from plant activities. Radium was not used in the production processes. The facility processed high purity enriched uranium isotopes.

#### 6.2.3.5 Thorium.

Thorium was present at the site either as drummed waste buried at the former burial location or as contamination on equipment from the Cushing facility which was stored at the uranium plant yard. The drums and equipment were removed and disposed in an off-site licensed commercial disposal facility. No thorium was processed at the facility and its presence in the subsurface is attributed to naturally-occurring isotopes.

#### 6.2.4 Correlation with Field-Measured Gamma Activity.

A comparison of laboratory measured values for uranium-238 and the borehole gamma probe measurements was made and is presented in Figure 6.10. Although the data does not show a strong correlation the method does provide a gross evaluation tool to distinguish between naturally occurring background gamma activity and that resulting from plant activities.

A threshold count is apparent (see Figure 6.10) at approximately 27,000 to 30,000 counts/minute. Below that threshold, uranium activities are typically less than 1 pCi/g. Above the threshold, uranium activities significantly greater than 1 pCi/g are apparent. This threshold is believed to represent the division between natural background gamma activities and facility related impacts.

### 6.3 Uranium Mobility

The mobility of uranium at the site depends upon the chemistry of the ground water and the soil and rock chemistry. The stability and mobility of particular species in the subsurface depends primarily on active matrix adsorption sites, ligands available for complexation, pH, and Eh of the ground water. Uranium has limited solubility in the slightly alkaline and oxidizing ground water typical of the site. The solubility is higher near the ponds because of the altered ground-water chemistry in these areas and the presence of complexing agents, e.g. fluoride and nitrate.

The dominant uranium species in the natural environment are uranyl complexes. Uranium exists in the hexavalent state as the uranyl ion  $UO_2^{+2}$  in this environment (Levinson, 1980). The solubility of uranium is limited by precipitation and adsorption on the aquifer matrix. Uranyl hydroxide and uranium trioxide will precipitate from slightly alkaline and oxidizing ground water. These compounds are relatively insoluble. Uranyl ions in solution also will be sorbed onto the aquifer matrix.

The distribution coefficient analyses described in Section 3.2.8.5 indicate that the equilibrium concentration of uranium in ground water should be less than 10 pCi/l. The tests performed on five representative samples of aquifer material yielded final concentrations of uranium in test solutions less than 10 pCi/l and relatively large equilibrium distribution coefficients. The ground-water analyses from most of the monitoring wells showed similar values.

Concentrations of uranium above the typical equilibrium level were detected in some monitoring wells. These wells generally were located down-gradient from the closed wastewater ponds and former burial area. Materials stored in these areas could cause changes in the chemistry of the ground water near the facilities. The process wastewater discharged to the ponds contained dissolved uranium and was significantly different chemically from the natural ground water (Wayne Norwood, personal communication, 1989). The difference is responsible for the higher uranium concentrations near the ponds. Likewise, leaching of materials stored at the former burial location would alter the ground-water chemistry in that area.

Uranium concentrations decreased rapidly to background levels with distance from the sources, as is discussed in Section 7.3.

TABLE 6.1

Annual Ground-Water Sampling Results


Date	Alpha pCi/L	Beta pCi/L	NO3 mg/L	F mg/L	U-238 pCi/L	Pu-239 pCi/L	Ra-224 pCi/L	Ra-226 pCi/L
WELL No. 1311								
06/21/85	10.0	31.0	57.0	< 0.2	< 0.7	0.015	NR	NR
06/26/86	<10.0	< 20.0	87.0	0.4	1.0	< 0.100	NR	NR
06/16/87	<10.0	< 20.0	34.0	0.4	1.7	0.010	0.081	0.3
06/28/88	<10.0	< 20.0	38.0	< 1.0	1.7	0.008	0.040	0.2
03/21/89	<10.0	23.0	66.0	< 0.2	0.8	0.002	NR	0.2
WELL NO. 1312								
06/21/85	2200.0	8275.0	< 20.0	83.0	86.0	0.020	NR	NR
06/28/86	94.0	7300.0	1310.0	59.0	5.6	< 0.100	NR	NR
06/16/87	41.0	65.0	620.0	18.0	15.0	0.002	0.290	0.6
06/30/88	90.0	231.0	480.0	22.0	48.0	0.012	0.410	1.1
03/21/89	59.0	2370.0	1020.0	50.0	15.3	0.003	NR	0.5
WELL NO. 1313								
06/21/85	453.0	1512.0	< 5.0	120.0	23.0	0.003	NR	NR
06/28/86	230.0	3000.0	690.0	157.0	25.4	< 0.100	NR	NR
06/16/87	84.0	25.0	450.0	120.0	26.0	0.004	0.350	0.2
06/28/88	61.0	24.0	570.0	3.1	42.0	0.006	0.120	0.3
03/21/89	260.0	2200.0	720.0	140.0	30.0	0.003	NR	0.5
WELL NO. 1314								
07/02/85	< 10.0	< 20.0	2.0	0.4	< 0.7	0.007	NR	NR
06/26/86	< 10.0	< 20.0	9.0	1.5	0.7	< 0.100	NR	NR
06/15/87	< 10.0	< 20.0	4.8	1.3	1.7	0.027	0.057	0.2
06/29/88	< 10.0	< 20.0	12.0	1.8	2.3	0.002	0.070	0.2
03/21/89	< 10.0	< 20.0	0.4	< 0.2	0.3	0.003	NR	0.1
WELL NO. 1315								
07/02/85	3125.0	189.0	11.0	< 0.2	1800.0	0.019	NR	NR
06/26/86	5400.0	740.0	5.0	0.5	2310.0	< 0.100	NR	NR
06/16/87	3850.0	2450.0	6.7	0.6	1600.0	0.005	0.036	0.1
06/27/88	3800.0	989.0	< 2.0	< 1.0	1590.0	0.002	0.210	0.2
09/13/88	3560.0	240.0	< 10.0	< 1.0	1340.0	NR	0.000	1.9
03/21/89	6440.0	660.0	13.0	0.2	1550.0	0.003	NR	0.0
WELL NO. 1316								
07/02/85	200.0	< 20.0	11.0	< 0.2	63.0	0.020	NR	NR
06/26/86	608.0	140.0	4.0	0.8	530.0	< 0.100	NR	NR
06/15/87	420.0	300.0	4.6	0.6	180.0	0.002	0.100	0.1
06/29/88	378.0	116.0	12.0	< 1.0	99.0	0.012	0.060	0.1
03/21/89	331.0	100.0	16.0	< 0.2	67.0	0.003	NR	0.0
WELL NO. 1317								
07/02/85	20.0	27.0	25.0	< 0.2	< 0.7	0.003	NR	NR
06/26/86	< 10.0	21.0	8.0	0.4	7.0	< 0.100	NR	NR
06/15/87	13.0	< 20.0	2.2	0.3	3.3	0.002	0.100	0.2
06/29/88	105.0	< 20.0	< 1.0	< 1.0	42.0	0.002	0.030	0.1
03/21/89	66.0	26.0	0.4	< 0.2	8.1	0.003	NR	0.0

NOTE: NR means result not reported

TABLE 6.2

## Radium Concentrations in Ground Water

Well No.	TOTAL RADIUM pCi/l	ln(Ra)	Frequency	i	Cumulative Frequency
1331	0.000		2	2	8.00
1335	0.000				
1321	0.021	-3.86	1	3	12.00
1329	0.030	-3.51	1	4	16.00
1328	0.054	-2.92	1	5	20.00
1323	0.058	-2.85	1	6	24.00
1324	0.059	-2.83	1	7	28.00
1327-B	0.061	-2.80	1	8	32.00
1330	0.088	-2.43	1	9	36.00
1317	0.100	-2.30	1	10	40.00
1314	0.110	-2.21	1	11	44.00
1326	0.150	-1.90	1	12	48.00
1334	0.229	-1.47	1	13	52.00
1333	0.240	-1.43	1	14	56.00
1322	0.258	-1.35	1	15	60.00
1311	0.262	-1.34	1	16	64.00
1325	0.346	-1.06	1	17	68.00
1320	0.400	-0.92	1	18	72.00
1316	0.470	-0.76	1	19	76.00
1332	1.180	0.17	1	20	80.00
1315	1.610	0.48	1	21	84.00
1312	1.830	0.60	1	22	88.00
1313	2.830	1.04	1	23	92.00
1336	9.780	2.28	1	24	96.00



- LEGEND**
- < 0.20 mg/l
  - 0.20-2.00
  - 2.00-4.00
  - ▲ > 4.00

**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 6.1**  
**FLUORIDE CONCENTRATIONS**  
**IN GROUND WATER**





FIGURE 6.2  
 NITRATE CONCENTRATION  
 IN GROUND WATER




LEGEND

- < 10.0 pCi/l
- 10-20
- 20-50
- 50-100
- ▲ > 100

**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 6.3**  
**ALPHA ACTIVITY IN GROUND WATER**




**LEGEND**

- < 20 pCi/l
- 20-50
- 50-100
- ▲ > 100

**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 6.4**  
**BETA ACTIVITY IN GROUND WATER**





MEANDER LINE SOUTH BANK

CLOSED WASTEWATER POND #1

CLOSED WASTEWATER POND #2

FORMER BURIAL LOCATION

PLUTONIUM PLANT

SEWAGE LAGOONS

DESIGNATED LANDFILL

URANIUM PLANT

CIMARRON PROPERTY BOUNDARY

CIMARRON PROPERTY BOUNDARY

SCALE IN FEET  
0 400 800



LEGEND

- 0-10 pCi/l
- 10-50
- 50-100
- ▲ > 100



JAMES L. GRANT & ASSOCIATES  
geotechnical engineering • management •  
computer science  
ENGLEWOOD, COLORADO

FIGURE 6.5  
TOTAL URANIUM ACTIVITY  
IN GROUND WATER




**LEGEND**

- < 0.1 pCi/l
- 0.1-1.0
- 1.0-5.0
- ▲ > 5.0


**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 6.6**  
**TOTAL RADIUM ACTIVITY**  
**IN GROUND WATER**




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 6.7**  
**HISTOGRAM OF RADIUM CONCENTRATIONS**  
**IN GROUND WATER**




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 6.8**  
**LOG-TRANSFORMED PROBABILITY PLOT**  
**OF RADIUM IN GROUND WATER**



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 6.9**  
**FLUORIDE VERSUS U-238**  
**IN SOIL AND ROCK**



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 6.10**  
**FIELD PROBE GAMMA ACTIVITY**  
**VERSUS U-238**

## 7. MOBILITY AND MATRIX RETENTION OF RADIONUCLIDES

This section describes the solubility and mobility of radionuclides in the subsurface at the Cimarron site. The discussion presents estimates of natural rainfall infiltration and percolation through the proposed landfill. Elemental partition coefficients are used to describe the solubility of the radionuclides in the undisturbed soil and in the proposed landfill. The percolation estimates are used to assess the rate and quantity of radionuclides that might leach from the soils.

The potential impacts of these radionuclides on ground-water and surface-water quality are discussed. The calculations in this section demonstrate that the materials which will remain at the site after decommissioning will not represent a real or potential threat to ground-water or surface-water use in the surrounding area.

### 7.1 Infiltration

#### 7.1.1 Methods of Analysis.

The HELP model (Schroeder et.al., 1984; Schroeder, 1988) was used to develop estimates of potential infiltration through a natural soil profile and through the cover of the proposed landfill. The HELP model is a water balance model developed by the U.S. EPA to calculate infiltration and percolation into and through solid waste disposal facilities. The program is a quasi-two-dimensional, deterministic model adapted from an earlier EPA model, HSSWDS, and the U.S. Department of Agriculture CREAMS model.

The HELP model uses the Soil Conservation Service runoff curve number method to calculate storm-water runoff. Evapotranspiration is calculated using a modified Penman method. Percolation is calculated using a modification of Darcy's law. The program provides default and synthetically-derived climatic data, and default soil properties. Default or site-specific properties can be used in the analysis.

The program allows layered profiles comprising vertical percolation layers, lateral drainage layers, and hydraulic barriers. The program uses daily climatic data to calculate daily, monthly, and annual water budgets at critical points in the soil profile. The simulations performed are included in Appendix I.

#### 7.1.1.1 Data.

The HELP model requires climatic data, soil properties, and the soil profile to be specified for each water budget simulation. Synthetically-generated 20-year records were used for Cimarron analyses. The records were generated using climatic data for Oklahoma City contained within the HELP model. Soil properties were developed from laboratory measurements of density, porosity, saturated hydraulic conductivity, and matric potential described in Section 2 of this report. Values appropriate for site soils were tabulated and matched with similar default values provided within the HELP database. The soil properties used in the analyses are summarized in Table 7.1. Hydraulic conductivity and porosity values are shown for "loose" and "dense" soil conditions. Surficial soil layers were assumed to be loose, and compacted layers were assumed to be dense.

Soil texture descriptions were used to estimate soil hydraulic classifications and to determine curve numbers for the surficial soils. An hydraulic group C was determined appropriate for the surficial site soils. Assuming a "fair" grass cover, a curve number of 65 for antecedent moisture condition II was obtained from standard references. This curve number was used for all soil analyses. The curve number is at the lower range of appropriate values for the site soils and is therefore conservative. Larger curve numbers would increase surface runoff and decrease infiltration estimates, although this effect would be relatively small within the range of realistic curve numbers.

#### 7.1.1.2 Calculations.

Calculations were made for a range of profiles described in Table 7.2. These profiles consist of differing arrangements of the two basic soil types identified in the laboratory testing program on site generated samples. The different arrangements were analyzed to determine the sensitivity of the percolation estimates to variations in the soil profile. The results of the calculations are summarized in Table 7.3. Table 7.4 presents average monthly water balances for the cases analyzed.

Estimates of natural percolation range from 5.3 inches per year for the more-permeable surface soil to 3.8 inches per year for the less-permeable soil. These differences reflect the differences in water-holding capacity of the two soils. These numbers are comparable to the infiltration estimates that range up to 3.5 inches per year presented by Bingham and Moore (1975).



Estimates of percolation through the landfill cover ranged from 0.14 inches to 4.9 inches per year. The percolation estimates for cases LF1, LF3, and LF4 are nearly equal to the saturated hydraulic conductivity of the barrier layer, indicating that percolation is limited by the capacity of the barrier to transmit water in these cases. The percolation estimate for case LF2 is significantly less than the saturated hydraulic conductivity of the barrier, indicating that percolation through this cover is limited by evapotranspiration demands in the vegetative layer. The latter value essentially is equal to the estimates of percolation through the natural profile.

The sensitivity analyses can be summarized by noting that for barrier layer hydraulic conductivities larger than about  $5 \times 10^{-7}$  cm/sec, percolation will be limited by evapotranspiration at a constant value of about 5 inches per year. For smaller barrier layer hydraulic conductivities, percolation will be limited by the barrier layer, and will be essentially equal to the hydraulic conductivity of the barrier layer.

## 7.2 Leachability

The radionuclide analyses and distribution coefficient (Kd) analyses indicate that uranium has limited solubility and mobility in the ground water beneath the Cimarron facility. The Kd analyses show equilibrium concentrations of uranium of about 10 pCi/l or less. Kd values obtained from the tests are high. The measured Kd values range from about 300 to 3000 ml/g.

Concentrations of dissolved uranium in the test solutions after soil contact were less than 10 pCi/l. These concentrations are typical of uranium concentrations in the site monitoring wells, where corresponding uranium concentrations on the soil are smaller than those in the laboratory tests. The larger distribution coefficients in the laboratory tests are believed reflective of the influence of solubility upon the calculated value of Kd. In other words, a larger source of uranium does not create higher concentrations of uranium in solution, but, because of the insolubility of the uranium, results in a larger apparent Kd. As described in Section 3.2.8.5, the amount of uranium used in the Kd laboratory tests was equivalent to 3 pCi/g and 17 pCi/g of soil for the two test conditions.

The uranium concentrations in the test fluids are consistent with the concentrations of uranium measured in the natural site ground water. Samples of ground water from twenty-four wells were tested to determine the concentration of U-238. Eighteen of the samples had concentrations less than 10 pCi/l. The six wells where U-238 concentrations were higher are located near the wastewater ponds and the former burial area, facility components

where the natural chemistry of the ground water has been altered due to seepage. Samples from wells down-gradient from these facilities show that the U-238 concentrations decrease to background levels away from these facilities where natural background conditions are again prevalent.

Soils which will be buried in the proposed landfill will contain soluble and insoluble uranium compounds in concentrations less than those prescribed in the NRC Branch Technical Position Option 2. The Option 2 concentration limit for soluble uranium is 100 pCi/g. Materials with soluble concentrations between 30 and 100 pCi/g will be placed in the landfill. Some materials placed in the landfill may have concentrations of soluble uranium less than 30 pCi/g. This point is important since the concentrations of uranium in the landfill soils is of the same order of magnitude as the concentration used in the laboratory Kd tests.

The materials to be placed in the proposed landfill are soils identical to the soils encountered during the site investigation. Leaching of these materials will not alter the chemistry of the leachate appreciably. Leachate chemistry will therefore reflect the chemistry of the unaltered ground water beneath the site. Under these conditions, leaching of the uranium from the landfill will be controlled by equilibrium established between the leachate and the soil matrix. The concentration of uranium in the leachate will be related to the concentration of uranium on the soil by the relation (Isherwood, 1981)

$$C_w = C_s * n / (\rho * K_d)$$

Where

$C_w$  is the concentration of uranium  
in the leachate (pCi/ml)  
 $C_s$  is the concentration of uranium  
on the soil (pCi/g)  
 $n$  is the porosity of the soil in the landfill  
 $\rho$  is the bulk density of the soil  
in the landfill, and  
 $K_d$  is the equilibrium distribution coefficient  
of uranium in the soil/leachate system.

For typical values of porosity and bulk density of the soil in the landfill of about 0.4 and 1.6 respectively, the concentration of uranium in the leachate will range from about 0.00008 to 0.00083 times the concentration of uranium in the soil. In units of pCi/l, the concentration of uranium in the leachate will range from about 0.08 to 0.83 times the concentration of uranium in the soil in units of pCi/g.

### 7.3 Potential for Migration

The mobility of dissolved uranium in the ground water is limited by solubility constraints and the affinity of uranium for site soils. The results of the  $K_d$  tests indicate that distribution coefficients of uranium in the natural ground-water system at the Cimarron facility range between 300 and 3000 ml/g. Estimates of  $K_d$  values from site well data indicate that the  $K_d$  of uranium may be on the order of 10 to 200 ml/g at low uranium concentrations. Even these smaller values are representative of immobile materials. With a  $K_d$  of ten, dissolved uranium will move about 40 times slower than water in the ground-water system. With a  $K_d$  of 200, the uranium will move about 800 times slower than ground water.

Site water-quality data reflect the immobility of uranium in the subsurface. Figure 7.1 is a plot of U-238 concentrations in water from wells near the former burial ground. Wastes were buried in this facility and later exhumed and disposed off-site. The concentration of uranium in well 1315, located within the burial ground, and well 1316, located near well 1315, increase during the year 1986. This temporary increase may be related to abnormally high rainfall during 1985. The peak concentration of uranium in well 1315 is about 2300 pCi/l, and the peak concentration in well 1316 is about 530 pCi/l. An increase in concentration is observed in well 1317 in 1988, two years after the increase in the wells nearer the former burial ground. The peak concentration in well 1317 is 42 pCi/l, or about 12 times less than well 1316.

The changes in U-238 concentrations with distance from the former burial ground are illustrated in Figure 7.2. Up-gradient well 1314 shows background U-238 concentrations of about one to two pCi/l. Concentrations are increased to as much as about 2300 pCi/l across the former burial area, and decrease rapidly with distance down-gradient of the area. Migration around this area reflects the influence of the leachate chemistry upon uranium  $K_d$ 's. Within the former burial area,  $K_d$ 's probably are much smaller than in the natural system. The  $K_d$ 's increase with distance from the facility as the ground-water chemistry approaches that of the native ground water.

Migration from the proposed landfill will be much less pronounced than from the former burial ground because the landfill will not influence ground-water chemistry, and because only soils with low levels of uranium will be buried in the landfill. Leaching of the uranium will be limited by solubility and by sorptive processes in the landfill. Migration of uranium that does leach will be limited by the sorption of the material in the subsurface.

#### 7.4 Computer Simulation of Leaching and Migration

Leaching and subsurface migration of uranium from the Option 2 limit soils disposed at the proposed landfill was simulated using the TRANSS model (Simmons et.al., 1986). The TRANSS model is a one-dimensional, convective, dispersive transport program based on Van Genuchten analytical solutions, modified to include the simultaneous decay of the source and released radionuclides. The program can model concentration or solubility limited releases, adsorption (Kd) limited releases, or diffusion beneath a barrier to the water table.

Simulations of distribution coefficient-limited releases were performed to predict uranium migration through the unsaturated zone to the water table, and through the saturated zone to the Cimarron River alluvium.

##### 7.4.1 Kd limited release simulation - Vadose zone.

Two simulations of uranium leaching and migration to the water table directly below the proposed landfill were performed using Kd values representative of the range of aquifer matrix materials. Kd values of 2000 ml/g and 300 ml/g were used. Kd is entered into the model through the retardation factor, R, which is related to Kd by the relation:

$$R = 1 + \rho / (\theta * Kd)$$

where  $\rho$  = dry bulk density of material (1.6 g/cc)  
 $\theta$  = moisture content (0.3)  
Kd = distribution coefficient

The source term used in the simulations is calculated to be 1.81 Curies, based upon a total of 14,800 cubic yards soil disposed at the Option 2 Limit of 100 pCi/g soluble uranium. The leachate velocity through the unsaturated zone is low, and dispersion will be negligible. Leachate velocity is calculated from the infiltration rate and soil field capacity calculated for the HELP model described in Section 7.1. The parameters used in the simulations are listed in Table 7.5, and the output generated is included in Appendix J.

Both simulations show that very little uranium will leach and enter the water table. For a distribution coefficient of 2000 ml/g, a maximum leachate concentration of about 10 pCi/l is estimated to arrive at the water table in approximately 170,000 years. Figure 7.3 shows leachate concentration with time at the water table directly under the landfill for Kd=2000 ml/g simulation.

A distribution coefficient of 300 ml/g results in a maximum leachate concentration of about 67 pCi/l arriving at the water table in approximately 27,000 years. Figure 7.4 shows leachate concentration with time for the  $K_d=300$  simulation.

#### 7.4.2 $K_d$ limited release simulation - Saturated zone.

Two simulations of leaching and migration of uranium from the landfill to the Cimarron River alluvium were performed using  $K_d$  values of 2000 and 300 ml/g. The pathline selected for the simulation is indicated on Figure 7.5. A length of 1000 feet, width of 360 feet, and thickness of 10 feet was estimated for the flowtube. Transport was modeled in the first saturated sandstone, which is approximately 10 feet thick, for a flowtube cross-sectional area of 3600 square feet. The same initial source concentration of uranium was modeled. The input parameters are listed in Table 7.5. The simulation output is included in Appendix J.

With a  $K_d$  of 2000 ml/g, a maximum leachate concentration of about 4 pCi/l is seen at the end of the flowtube in approximately 237,000 years. Figure 7.6 shows leachate concentration with time for the  $K_d=2000$  ml/g simulation.

A  $K_d$  of 300 ml/g produces a maximum leachate concentration of about 27 pCi/l at the end of the flowtube in approximately 36,000 years. Figure 7.7 shows leachate concentration with time for this simulation.

#### 7.4.3 Discussion of Results.

The results of the TRANSS model simulations support interpretations that leaching and migration of uranium in the subsurface of the Cimarron facility will be limited. The simulations show that the combined effects of precipitation, adsorption and dilution of uranyl complexes will prevent significant migration of uranium from the proposed landfill site.

#### 7.5 Migration of Uranium Left In-Situ

The TRANSS model simulations also indicate that migration of radionuclides from soils left in place at the facility will be negligible. The simulations of leaching through the proposed landfill represent a case where soils containing the maximum permissible concentration of soluble uranium under the NRC Branch Technical Position Option 2 criterion are confined in a small area. Since the uranium concentration in soils left in place will be less than those disposed in the proposed landfill and are

present over a greater area, the concentration of uranium in ground water that leached from the in-situ soils will be considerably less than that predicted for the landfill.

Subsurface conditions are essentially identical to those under the landfill and  $K_d$  values up to 2000 ml/g are expected. The concentration of uranium in ground water resulting from leaching of soils left in place is not anticipated to exceed the estimated equilibrium concentration of 10 pCi/l described in Section 3.2.8.5.

TABLE 7.1

Assumed Soil Properties  
for HELP model simulations

	Sand	Clay
Porosity (loose)	0.42	0.42
(dense)	0.33	0.33
Field Capacity	0.24	0.29
Wilting Point	0.104	0.187
K (cm/sec) (loose)	$1 \times 10^{-4}$	$5 \times 10^{-5}$
(dense)	$1 \times 10^{-6}$	$1 \times 10^{-7}$

TABLE 7.2

Cover Profiles Analyzed  
for HELP model simulations

Profile	Upper Layer		Barrier Layer	
	Material	Thickness (inches)	Material	Thickness (inches)
LF1	Sa	24	Cl	12
LF2	Sa	24	Sa	12
LF3	Cl	24	Cl	12
LF4	Sa	24	Cl*	12
NA1	Sa	36	--**	12
NA2	Cl	36	--**	12

Notes: Soil types correspond to those in Table 7.1

\* Hydraulic conductivity =  $1 \times 10^{-8}$  cm/sec.

\*\* Hydraulic conductivity =  $1 \times 10^{-6}$  cm/sec.



TABLE 7.3

Summary of Percolation Calculations  
for HELP model simulations

CASE	AVERAGE PERCOLATION (inches/yr)	STD.DEV.	SOIL PROFILE
LF1	1.32	0.55	Sa/Cl
LF2	4.87	2.62	Sa/Sa
LF3	1.24	0.51	Cl/Cl
LF4	0.14	0.06	Sa/Cl*
NA1	5.27	2.92	Sa**
NA2	3.77	2.17	Cl**

\* Hydraulic conductivity of Clay =  $1 \times 10^{-8}$  cm/sec.

\*\* Hydraulic conductivity of underlying soil =  $1 \times 10^{-6}$  cm/sec.

TABLE 7.4

Average Monthly Water Balances  
for HELP model simulations  
(inches)

LF1						
	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
PRECIPITATION	0.87	1.25	2.09	3.04	4.85	3.03
	2.88	2.27	4.40	3.27	1.77	1.13
RUNOFF	0.011	0.012	0.045	0.357	0.883	0.039
	0.010	0.000	0.013	0.120	0.159	0.039
EVAPOTRANSPIRATION	0.790	0.882	1.456	1.789	3.284	6.254
	4.491	2.456	2.689	1.727	1.044	0.857
PERCOLATION	0.1267	0.1199	0.1494	0.1771	0.2237	0.1723
	0.0440	0.0000	0.0049	0.0652	0.1075	0.1332
LF2						
	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
PRECIPITATION	0.87	1.25	2.09	3.04	4.85	3.03
	2.88	2.27	4.40	3.27	1.77	1.13
RUNOFF	0.000	0.000	0.000	0.051	0.234	0.000
	0.010	0.000	0.012	0.121	0.057	0.000
EVAPOTRANSPIRATION	0.781	0.885	1.459	1.803	3.306	5.454
	3.007	2.449	2.691	1.745	1.037	0.858
PERCOLATION	0.2337	0.2089	0.3218	0.6076	1.0633	0.5912
	0.0348	0.0000	0.0447	0.5105	0.6927	0.5559
LF3						
	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
PRECIPITATION	0.87	1.25	2.09	3.04	4.85	3.03
	2.88	2.27	4.40	3.27	1.77	1.13
RUNOFF	0.009	0.000	0.063	0.467	1.109	0.085
	0.124	0.034	0.305	0.407	0.188	0.030
EVAPOTRANSPIRATION	0.836	0.947	1.532	1.900	3.498	5.878
	3.092	2.388	2.741	1.844	1.094	0.925
PERCOLATION	0.1247	0.1184	0.1476	0.1765	0.2169	0.1328
	0.0093	0.0000	0.0050	0.0621	0.1110	0.1387

## Average Monthly Water Balances (continued)

## LF4

	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
PRECIPITATION	0.87 2.88	1.25 2.27	2.09 4.40	3.04 3.27	4.85 1.77	3.03 1.13
RUNOFF	0.032 0.010	0.076 0.000	0.224 0.013	0.543 0.127	1.168 0.176	0.075 0.063
EVAPOTRANSPIRATION	0.789 4.833	0.887 2.458	1.461 2.690	1.788 1.722	3.221 1.043	6.315 0.859
PERCOLATION	0.0137 0.0057	0.0132 0.0000	0.0164 0.0005	0.0189 0.0066	0.0235 0.0111	0.0185 0.0140

## NA1

	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
PRECIPITATION	0.87 2.88	1.25 2.27	2.09 4.40	3.04 3.27	4.85 1.77	3.03 1.13
RUNOFF	0.000 0.010	0.000 0.000	0.000 0.012	0.051 0.121	0.152 0.012	0.000 0.000
EVAPOTRANSPIRATION	0.780 2.914	0.885 2.449	1.459 2.698	1.803 1.741	3.306 1.039	5.253 0.866
PERCOLATION	0.2733 0.2592	0.2087 0.0077	0.3131 0.0369	0.5762 0.4647	1.0641 0.6638	0.7856 0.6193

## NA2


	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
PRECIPITATION	0.87 2.88	1.25 2.27	2.09 4.40	3.04 3.27	4.85 1.77	3.03 1.13
RUNOFF	0.000 0.125	0.000 0.034	0.014 0.306	0.189 0.397	0.577 0.082	0.035 0.000
EVAPOTRANSPIRATION	0.834 2.697	0.948 2.387	1.540 2.735	1.906 1.834	3.542 1.102	4.823 0.923
PERCOLATION	0.1773 0.0295	0.1476 0.0000	0.2632 0.0339	0.4975 0.3759	0.8370 0.5397	0.4777 0.3885

Note: All values in inches

TABLE 7.5

Hydrologic Parameters used in TRANSS Model


Parameter	Kd Limited Vadose Zone Simulation	Kd Limited Saturated Zone Simulation
Dispersion Coefficient	1.0 sq ft/yr	1.0 sq ft/yr
Retardation Factor: Kd=2000	10600	10600
Kd=300	1600	1600
Radionuclide Inventory	1.81 Ci	1.81 Ci
Pathline Length	20 ft	1000 ft
Travel Time in Unsat. Zone	14.5 years	14.5 years
Effective Porosity	0.30	0.30
Flowtube Area	80,000 sq ft	3,600 sq ft
Depth of Source Distribution	10 ft	10 ft
Infiltration Flux	0.3 ft/yr	0.3 ft/yr



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO


**FIGURE 7.1**

**ANNUAL URANIUM CONCENTRATIONS: 1985-1989**  
**AT THE FORMER BURIAL LOCATION**



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO


**FIGURE 7.2**  
**URANIUM CONCENTRATIONS IN GROUND WATER**  
**AT THE FORMER BURIAL LOCATION**



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 7.3**

**LEACHATE CONCENTRATION WITH TIME**  
**VADOSE ZONE:  $K_d=2000$**



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 7.4**

**LEACHATE CONCENTRATION WITH TIME**

**VADOSE ZONE:  $K_d = 300$**







FIGURE 7.5

PATHLINE

FOR SATURATED ZONE SIMULATIONS



JAMES L. GRANT & ASSOCIATES  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO



**JAMES L. GRANT & ASSOCIATES**


geotechnical engineering • management •  
computer science

ENGLEWOOD, COLORADO

**FIGURE 7.6**

**LEACHATE CONCENTRATION WITH TIME**

**SATURATED ZONE:  $K_d = 2000$**



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 7.7**

**LEACHATE CONCENTRATION WITH TIME**  
**SATURATED ZONE:  $K_d = 300$**

## 8. REFERENCES

- Al-Shaieb, Z., Olmsted, R.W., Shelton, J.W., May, R.T., Owens, R.T., Hanson, R.E., 1977, Uranium potential of Permian and Pennsylvanian sandstones in Oklahoma: American Association of Petroleum Geologists Bulletin, Vol.61, pp.360-71.
- Bingham, R.H., Moore, R.L., 1975, Reconnaissance of the Water Resources of the Oklahoma City quadrangle: Oklahoma Geological Survey Hydrologic Atlas 4, 1:250000, 4 sheets.
- Bouwer, H., Rice, R.C., 1976, A slug test for determining hydraulic conductivity of unconfined aquifers with completely or partially wells: Water Resources Research, Vol. 12, No. 3, pp. 423-428.
- Carr, J.E., Havens, J.S., 1976, Records of wells and water quality for the Garber-Wellington aquifer, northern Oklahoma and southern Logan Counties, Oklahoma: U.S. Geological Survey Open File Report 76-619, 32 p.
- Carr, J.E., Marcher, M.V., 1977, A preliminary appraisal of the Garber-Wellington Aquifer, southern Logan and northern Oklahoma Counties, Oklahoma: U.S. Geological Survey Open File Report 77-278,
- Code of Federal Regulations (CFR), 1988, Cochran's approximation to the Behrens-Fisher Students' T-test: 40 CFR Part 264, Appendix IV.
- Cooper, H.H.Jr., Bredehoeft, J.D., Papadopulos, I.S., 1967, Response of a finite-diameter well to an instantaneous charge of water: Water Resources Research, Vol.3, No.1, pp. 263-269.
- Drever, J.I., 1982, The geochemistry of natural waters: Prentice-Hall, Inc., Englewood Cliffs, N.J., 388 p.
- Engineering Enterprises, 1973, Hydrological information in the vicinity of the Kerr-McGee facility, Logan County, Oklahoma: Prepared for Kerr-McGee Corporation, 12 p.
- Environmental Protection Agency, 1989, Statistical analysis of ground-water monitoring data at RCRA facilities, interim final guidance: EPA/530-SW-89-026.
- Ford, W.J., 1954, The subsurface geology of southwest Logan County, Oklahoma: Oklahoma Geological Society Shale Shaker Digest, Vol. I, pp. 327-343.
- Hvorslev, M.J., 1951, Time lag and soil permeability in ground water observations: U.S. Army Corps of Engineers Waterways Experimentation Station, Bulletin 36, 50 p.

- Isherwood, D., 1981, Geoscience database handbook for modeling a nuclear waste repository, volume 1: NUREG/CR-0912, Vol. 1, 315 p.
- Johnson, K.S., 1983, Map showing principal ground-water resources and recharge areas in Oklahoma: Oklahoma State Department of Health, 1:500000, 2 sheets.
- Landes, K.K., 1970, Petroleum Geology of the United States: Wiley-Interscience, N.Y., N.Y., 571 p.
- Levinson, A.A., 1980, Exploration Geochemistry, 2nd. Ed.: Applied Publishing, Wilmette, Illinois, 924 p.
- Lohman, S.W., 1979, Ground-water hydraulics: U.S. Geological Survey Professional Paper 708, 70 p.
- Mason, B., 1966, Principles of geochemistry: John Wiley and Sons, N.Y., N.Y.
- Mosier, E.L., Bullock, J.H., Jr., 1988, Review of the general geology and solid-phase geochemical studies in the vicinity of the central Oklahoma aquifer: U.S. Geological Survey Circular 1019, 18 p.
- Patterson, J.M., 1933, Permian of Logan and Lincoln Counties, Oklahoma American Association of Petroleum Geologists Bulletin Vol. 17, No. 3, pp. 241-253.
- Schroeder, P.R., Gibson, A.C., Smolen, M.D., 1984, The Hydrologic Evaluation of Performance (HELP) model, Volume II documentation for Version I: U.S. Army Corps of Engineers Waterways Experiment Station, Vicksburg, MS.
- Schroeder, P.R., 1988, User's guide for HELP Version 2 for experienced users: U.S. EPA, Office of Solid Waste, Washington, D.C.
- Simmons, C.S., Kincaid, C.T., Reisenauer, A.E., 1986, A simplified model for radioactive contaminant transport; the TRANSS code: Battelle Pacific Northwest Laboratory PNL-6029, prepared under U.S. Department of Energy Contract DE-AC06-76RLO 1830.

**APPENDIX A**

**WORK PLAN FOR SITE INVESTIGATION PROGRAM**

808211: 9-12-89

WORK PLAN  
FOR  
SITE INVESTIGATION PROGRAM  
CIMARRON CORPORATION FACILITY  
LOGAN COUNTY, OKLAHOMA

Submitted to  
Kerr-McGee Corporation  
and  
Cimarron Corporation  
Oklahoma City, Oklahoma

Prepared By  
James L. Grant and Associates, Inc.  
Denver, Colorado  
January 4, 1989

TABLE OF CONTENTS

1. INTRODUCTION .....	1-1
1.1 Project Information .....	1-1
1.1.1 Facility Information .....	1-1
1.1.2 Investigations .....	1-1
1.2 Site Hydrogeology .....	1-2
1.2.1 Geology .....	1-2
1.3 Proposed Work Plan .....	1-3
1.3.1 Proposed Scope of Work .....	1-3
1.3.2 Areas of Investigation .....	1-4
1.3.3 Investigation Team .....	1-4
1.3.4 Health and Safety .....	1-4
2. WORK PLAN .....	2-1
2.1 Drilling and Well Installation .....	2-1
2.1.1 Well Locations .....	2-1
2.1.2 Drilling and Soil Sampling .....	2-2
2.1.3 Monitoring Well Installation .....	2-3
2.2 Field Testing .....	2-4
2.2.1 Water-Level Measurement .....	2-4
2.2.2 Slug Tests .....	2-5
2.3 Ground-Water Sampling .....	2-5
2.4 Laboratory Analyses .....	2-5
2.4.1 Ground-Water Analyses .....	2-5
2.4.2 Laboratory Soil Analyses .....	2-6
2.4.2.1 Physical Analyses .....	2-6
2.4.2.2 Soil Chemical Analyses .....	2-7
2.4.2.3 Soil Contamination Analyses .....	2-7
2.5 Data Evaluation and Reports .....	2-7
2.5.1 Data Evaluation .....	2-8
2.5.2 Report .....	2-9
2.5.2.1 Progress Reports .....	2-9
2.5.2.2 Project Report .....	2-9
3. SCHEDULE FOR IMPLEMENTATION .....	3-1
Appendix A	DRILLING AND SAMPLING PROCEDURES
Appendix B	WELL INSTALLATION PROCEDURES
Appendix C	FIELD TESTING PROCEDURES
Appendix D	GROUND-WATER SAMPLING PROCEDURES
Appendix E	LABORATORY ANALYSIS PROCEDURES



## LIST OF TABLES

Table 2.1	Summary of Ground-Water Analyses .....	2-10
Table 2.2	Summary of Physical Properties Analyses .....	2-11
Table 2.3	Summary of Soil Chemical Analyses .....	2-12
Table 2.4	Summary of Soil Contamination Analyses .....	2-13

LIST OF FIGURES

Figure 1.1 Facility and Monitoring Well Locations ..... 1-6  
Figure 3.1 Project Schedule ..... 3-2

WORK PLAN  
FOR  
SITE INVESTIGATION PROGRAM

Cimarron Facility  
Logan County, Oklahoma

1. INTRODUCTION

1.1 Project Information

1.1.1 Facility Information.

Cimarron Corporation (Cimarron), a wholly-owned subsidiary of Kerr-McGee Corporation (Kerr-McGee), operates the Cimarron Facility in Logan County, Oklahoma. The principal operation at the plant involved the fabrication of fuel elements from plutonium and enriched uranium. Cimarron is decommissioning the facilities. Certain materials associated with the decommissioning activities will be left on-site, either in a designated area or in-situ, in accordance with the Nuclear Regulatory Commission's (NRC) Branch Technical Position (46 Federal Register 52061, October 23, 1981). The soils contain uranium and thorium that meet the Branch Technical Position Options 1 and 2 concentration limits and conditions for disposal.

1.1.2 Investigations.

Cimarron has been conducting an extensive and continuous environmental monitoring program at the facility to determine the impacts of facility activities on the environment. This program consists of routinely collecting and analyzing air, surface water, ground water, soil and vegetation samples from the site and adjacent areas.

A number of monitoring wells have been installed throughout the facility area for collection of ground water samples from the unconfined aquifer which occurs at depths less than 50 feet below ground surface. Significant areas of radiological contamination of the ground water are not present; however, elevated levels of uranium and gross alpha and beta have been detected in soils near the uranium plant yard. Elevated concentrations of nitrate (NO<sub>3</sub>) and fluoride (F) have been detected in ground water near the closed wastewater disposal ponds. Figure 1.1 shows the location of these facility components.

Cimarron has conducted a detailed soil sampling program to quantify the extent and concentration of uranium in the shallow subsurface. The survey consisted of lowering a calibrated sodium iodide (NaI) probe into borings and measuring gamma radiation at one-foot intervals. The quantities of soils meeting the Option 1 and 2 disposal criteria have been estimated from the survey. A large quantity of soil has been identified as containing levels of uranium that pose no threat to human health and will be left in place.

## 1.2 Site Hydrogeology

### 1.2.1 Geology.

The Cimarron Facility is located in the Central Lowlands region of the Great Plains physiographic province. Bedrock in the region are Permian-aged clastic formations, which dip gently to the west-southwest at about 30 feet per mile into the Anadarko Basin. The formations of principal interest are the Hennessey Shale and the Garber Sandstone. Overlying the Hennessey is an unconformity upon which Quaternary terrace deposits and alluvium have been deposited in the vicinity of the Cimarron River.

The Garber group is mostly composed of orange to red brown fine-grained sandstones, interbedded with siltstones, shales and local chert and mudstone conglomerate. The Pleistocene terrace deposits are lenticular sands, silts, clays and gravels and represent glacial outwash. They lie predominantly north of the Cimarron River. Recent alluvium is restricted to the Cimarron River flood plain, with minor development in the intermittent drainages.

Ground water at the facility occurs in a shallow, unconfined aquifer and in a deeper, confined aquifer within the Garber Sandstone. The unconfined aquifer water table occurs at depths ranging from 15 to 40 feet below land surface. Ground water in the unconfined aquifer at the site is estimated to flow to the north-northwest under a gradient of 90 to 120 feet per mile, and contribute to the base flow of the Cimarron River. Local flow direction is influenced by topography. The hydraulic conductivity has been measured and ranges from  $1 \times 10^{-4}$  to  $6 \times 10^{-4}$  centimeters per second.

The deeper, confined aquifer in the Garber sandstone is found at depths greater than 100 feet below ground surface. The piezometric surface is substantially below the water table found in the unconfined aquifer. A fresh water/salt water transition is found in the confined aquifer at a depth of approximately 200'. Flow direction in the confined aquifer is likely to be more

influenced by regional dip than the unconfined aquifer. It is anticipated that the flow direction will be toward the west. Hydraulic conductivities of the deeper Garber aquifer in the region have been estimated at  $9 \times 10^{-4}$  to  $2 \times 10^{-3}$  centimeters per second.

### 1.3 Proposed Work Plan

#### 1.3.1 Proposed Scope of Work.

To more fully understand and determine the impact of facility activities on the environment, additional data will be collected to characterize the hydrogeologic regime and complement the on-going environmental monitoring program conducted by Cimarron. Data also will be collected to determine the geotechnical properties of site soils, particularly in the vicinity of the planned NRC Branch Technical Position Option 2 landfill.

This work plan describes the procedures which will be used to:

- o obtain lithologic and hydrologic data for the soils and the Garber Sandstone aquifers,
- o install ground-water monitoring wells in the Garber aquifers,
- o determine ground-water flow direction, gradient and other hydraulic properties of the aquifers,
- o sample and analyze site soils for engineering behavior, mineralogy, uranium, plutonium, NO<sub>3</sub> and F,
- o sample and analyze ground water from the aquifers for uranium, plutonium, gross alpha and beta activity, NO<sub>3</sub> and F, and
- o prepare a report summarizing these data.

### 1.3.2 Areas of Investigation.

The areas at the Cimarron Facility to be investigated include the uranium plant yard, the closed wastewater disposal ponds, the sanitary lagoons, and the NRC Branch Technical Position Option 2 landfill site. The possibility of off-site sources of  $\text{NO}_3^-$  will be investigated by sampling ground water from background wells. The facility components to be investigated are identified on Figure 1.1.

### 1.3.3 Investigation Team.

The team which will perform the investigation and analyses described in this program will consist of personnel from James L. Grant and Associates (JLGA), Cimarron Corporation and Kerr-McGee. The investigation team will be competent in the disciplines and skills required to complete their respective project assignments. Training will be required only in the program-specific aspects of the investigation.


The field data acquisition team, including professional and support personnel, will be trained in the specific project activities to which they are assigned. Professional personnel will be trained in program-specific activities required for drilling and well installation, soil and ground-water sampling. Drilling support personnel will be trained in program-specific requirements for equipment operation and drilling, soil sampling, and well installation. All on-site personnel will have completed safety training required for their specific work assignments.


The personnel performing the laboratory analyses will be trained for the program-specific aspects of the analyses to be performed. Proper quality assurance/quality control procedures will be followed to ensure the integrity of results.

### 1.3.4 Health and Safety.

The investigative activities described in this Work Plan will be conducted under the Cimarron facility Health and Safety Plan. This program includes provisions for training, site access control, personnel monitoring, and other measures necessary or prudent to protect the health and safety of site personnel. It is anticipated that this work will be conducted with modified-level D protective measures. These measures include standard safety equipment such as hard hat, safety glasses, hard toe/shank boots, and coveralls for splash protection.

No individual will be allowed on-site unless he is familiar with the provisions of the Health and Safety Plan. The Cimarron Health and Safety Officer will be responsible for instructing individuals in the requirements and contents of the Health and Safety Plan prior to the commencement of program activities. The Health and Safety Officer also will be responsible for verifying and maintaining records that site personnel have received the proper Health and Safety training.




**JAMES L GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

**FIGURE 1.1**  
 Facility Components  
 and Monitoring Well Locations



## 2. WORK PLAN

This investigation includes the installation of monitoring wells in the unconfined and confined aquifers underlying the Cimarron facility, sampling and categorizing site soils and bedrock, and collecting and analyzing ground-water samples. The major components of the investigation are summarized in the succeeding sections and include:

- o Drilling and well installations
- o Field testing
- o Ground-water sampling
- o Laboratory analyses
- o Data evaluation and reporting

### 2.1 Drilling and Well Installation

Procedures to be followed for drilling borings and obtaining soil and rock samples are specified in Appendix A. The completion procedures to be used for the monitoring wells are specified in Appendix B.

#### 2.1.1 Well Locations.

The installation of monitoring wells at locations down-gradient from the uranium plant yard, closed wastewater disposal ponds, landfill site, and the sanitary lagoons is one of the principal objectives of the investigation plan. The locations of the planned monitoring wells are shown on Figure 1.1. The locations of wells located down-gradient of the possible contamination sources may be adjusted as additional data allows better definition of the hydrologic flow of the site. Well locations may also be moved to minimize disturbance of plant activities and to adjust for cultural and topographic features. Well locations may be adjusted with approval of the Project Manager.

### 2.1.2 Drilling and Soil Sampling.

Four deep borings will be drilled into the confined Garber Sandstone aquifer. The estimated total depth for each deep boring is 135 feet. The actual termination depth of each boring will be determined by the field geologist and will be sufficient for penetrating a significant portion of the confined, saturated zone.

One additional boring at each of the deep boring locations will be drilled to complete a monitoring well nest of two wells. The monitoring well nest will consist of a shallow well screened in the unconfined aquifer and a deep well screened in the deep, confined aquifer. The shallow well will be drilled approximately thirty feet deep; however, the actual termination depth will be determined by the field geologist. Total depth of the well will be sufficient to penetrate approximately 10 feet into the shallow, unconfined aquifer. Based on sample examination and the appearance of water during drilling, the field geologist will set a ten foot well screen across the water-bearing zone in the borings. Longer lengths of well screen may be permitted with approval of the Project Manager.

Eleven additional borings will be drilled at locations indicated on Figure 1.1. Of the eleven additional borings, four will be drilled in the vicinity of the uranium plant yard, one near the closed wastewater disposal ponds, three adjacent to the new landfill site, and three in the vicinity of the sanitary lagoons. The borings will be approximately 30 feet in depth and will penetrate the shallow, unconfined aquifer. The field geologist will determine the total well depth and the screen interval of these borings based on sample examination and appearance of water during drilling. The borings should extend approximately 10 feet below the water table.

Samples of soil and rock materials will be obtained at each of the four deep borings and eleven additional shallow borings using standard sampling methods appropriate for the type of material present. Continuous sampling of soils is planned; however, this plan might be modified in the field if the nature of the soils indicates that continuous sampling is not possible or is unnecessary. The four shallow borings constructed for the monitoring well nests will not be sampled. Changes to the sampling program will be approved by JLGA.

Rock penetrated in the four deep borings will be sampled by continuous coring. Rock penetrated in the additional eleven shallow borings will be sampled by collection of rock cuttings or by continuous coring. One of the additional shallow borings drilled at each of the four specific areas of investigation will be sampled by continuous coring for correlation purposes. When rock cuttings are collected, they will be composited over each 2 feet interval of rock drilled.

If subsurface conditions are such that the planned drilling or sampling technique does not produce acceptable results, e.g. unstable borehole walls or poor sample recovery, another drilling or sampling technique deemed more appropriate to the type of material present will be used. Changes to the drilling or sampling techniques will be approved by the Project Manager.

A field geologist or geotechnical engineer will monitor all drilling and well installation activities and maintain a log of these activities. The field representative also will keep a detailed, descriptive log of materials penetrated by the boring. An example of the format to be followed for the descriptive log is shown in Appendix A.

Representative soil samples will be selected for physical and chemical properties analyses. Physical tests will be conducted to verify field classification of soil and rock types, and to provide quantitative measures of hydraulic and engineering properties of the subsurface materials. Chemical analyses will be conducted to determine the chemical properties of the subsurface materials. Samples will be selected for testing that are representative of the major strata found within the zone of investigation, including both the unsaturated and saturated zones. Approximately one sample will be selected from each boring in the uranium plant yard and landfill site. Additional samples will be collected from the wastewater treatment pond and sewage lagoon areas. Soil analysis procedures are discussed in Section 2.4.2 and Appendix E.

Representative samples will also be analyzed for the presence of uranium, plutonium, NO<sub>3</sub> and F.

### 2.1.3 Monitoring Well Installation.

Ground-water monitoring wells will be installed in each of the nineteen borings using the procedures outlined in Appendix B. The wells will be screened in either the unconfined or the confined aquifers which underlie the surface deposits. The purpose of the shallow wells is to determine the hydraulic properties of the unconfined aquifer and to determine if any contaminants have migrated through the soils and impacted the shallow ground water. The purpose of the deep wells is to determine the hydraulic

properties of the confined aquifer and to determine if contaminants have impacted the deep ground water.

The Garber is composed of interbedded sandstones, siltstones and shales. It is anticipated that both aquifers will be composed of several relatively thin, water-bearing zones separated by fine-grained, less permeable beds. The wells should be screened to include the upper ten feet of the water-bearing strata.

Before the wells are used for monitoring water levels, testing, or taking water samples, they will be thoroughly developed. Development removes sediment from inside the well casing and flushes fines, cuttings, and drilling fluids from the sand pack and the portion of the formation adjacent to the well screen. Well development will not be performed until at least 24 hours after well grouting is completed. Well development will be performed after all wells have been installed.

The procedure to be used for well development is included in Appendix B.

The horizontal position and elevation of the measurement datum at the monitoring wells will be surveyed soon after well completion. Surveying will be conducted by a qualified surveyor.

## 2.2 Field Testing

Procedures to be followed in conducting field tests are included in Appendix C. The following field tests or measurements will be made at the monitoring wells constructed during this investigation and at selected previously existing monitoring wells.

### 2.2.1 Water-Level Measurement.

Water levels at all monitoring wells constructed during this investigation will be measured within a short time interval so that the water-level data are comparable. Water levels in the monitoring wells will not be measured until the wells are developed. Water levels will also be measured at the following existing monitoring wells: 1307, 1311, 1312, 1313, 1314, 1315, 1316, 1317 and 1318. See Figure 1.1 for approximate locations of these monitoring wells. The depth to water below the measurement datum will be made to the nearest 1/8 inch (0.01 feet).

### 2.2.2 Slug Tests.

To measure the hydraulic conductivity of the aquifers, "slug tests" will be performed. A slug test will be performed in each of the nineteen monitoring wells installed during this investigation. The procedure involves lowering a slug, or sealed tube, into the water in the well and allowing the raised water level to recover to the pre-insertion level. The slug then is removed quickly and the recovery of the lowered water level to static level monitored, timed, and recorded.

### 2.3 Ground-Water Sampling

In order to characterize current water quality in the aquifers at the site, the monitoring wells installed during this investigation will be sampled. Ground water samples will also be collected from the existing monitoring wells shown in Figure 1.1. Sampling will be conducted no sooner than 24 hours after the wells have been completed in order for aquifer conditions to stabilize after the disturbance caused by drilling, well installation, and well development. Samples will be collected from all the designated wells on the same day within a relatively short time frame to produce results that are comparable. Ground-water sampling, sample handling, and chain of custody procedures are presented in Appendix D.

### 2.4 Laboratory Analyses

Laboratory analyses will be performed by Kerr-McGee Technical Center personnel. If the services of an outside laboratory are required, Kerr-McGee laboratory personnel will be responsible for ensuring that the proper analyses are performed and that acceptable QA/QC procedures are maintained.

#### 2.4.1 Ground-Water Analyses.

Ground-water samples will be analyzed for the presence of uranium, plutonium, gross alpha and beta, NO<sub>3</sub> and F. The number of ground-water samples to be collected at each area of investigation are identified in Table 2.1. Additional samples may be collected with the approval of the Project Manager. Analyses will be conducted under procedures specified by the EPA or NRC for the particular constituents. Specific procedures are identified in Appendix E.

## 2.4.2 Laboratory Soil Analyses.

### 2.4.2.1 Physical Analyses.

Physical analyses will be performed on samples of soils and rocks taken from the borings. The results of the tests will verify field descriptions and classifications, and will provide quantitative measures of hydraulic and engineering properties of the subsurface materials. Physical analyses to be performed include particle size distribution, Atterberg limits, Proctor tests, density, moisture content, matric potential, and permeability. Physical tests will be conducted in accordance with the current edition of ASTM Standards, American Laboratory Soils Testing and Materials, Part 19. The recommended testing procedures are identified in Appendix E.

The proposed numbers of these tests are presented in Table 2.2. The numbers of tests in this table represent the current estimate of the number of physical analyses necessary to support the characterization of the subsurface. The number of physical analyses may be increased by the field representative with the approval of the Project Manager if additional tests are necessary to characterize the subsurface strata.

The samples to be tested will be selected by the field representative and the Project Manager. Approximately one sample will be selected from each boring in the uranium plant yard and the landfill site. These samples will be selected to represent the major strata found within the zone of investigation, including both saturated and unsaturated zones. The samples selected to measure matric potential will be selected after the other characterization tests have been completed, and the lithologies in the subsurface has been tentatively delineated. It is expected that the matric potential samples will be selected from the unsaturated zone. At least one matric potential sample will be fabricated from a blend of shallow soils to represent compacted fills constructed during the decommissioning of the facility.

Different samples may be selected for the various analyses at the discretion of the Project Manager.

Additional samples will be selected from the borings in the wastewater pond and sanitary lagoon areas. These samples will be selected to represent any strata not found in the uranium plant yard and landfill site borings and to duplicate tested samples from these locations. The duplication will allow lithologic changes in the major strata to be quantified.

#### 2.4.2.2 Soil Chemical Analyses.

Chemical analyses of soil and rock samples will be completed to quantify the chemical properties of the soils and rocks within the zone of investigation. The tests to be performed to characterize the chemical properties of the soils and rocks include total organic carbon, cation exchange capacity, exchangeable cations, and equilibrium distribution coefficients for uranium and thorium.

The numbers and approximate distribution of tests to be performed are summarized in Table 2.3. The numbers of tests shown in this table are approximate, and may be changed by the Project Manager should additional or fewer tests be found necessary to characterize the subsurface. The samples to be tested will be selected according to the same rationale used to select the soil samples for physical analyses. In most instances, the samples selected for physical analyses will be used for the chemical characterization, although other samples may be selected for testing by the Project Manager. The distribution coefficient samples will be selected after the chemical and physical tests have been completed. These samples will be composites selected to represent the range of chemical and mineral soil conditions within the zones of potential contaminant movement.

#### 2.4.2.3 Soil Contamination Analyses.

Chemical analyses of selected soils will be performed to determine the presence and concentration of potential contaminants on the soil. The contaminants to be tested include uranium, plutonium, nitrate and fluoride. Cimarron has completed an extensive program to detect and characterize radioactivity in the soils in the uranium plant yard. The current program will complement that effort. Table 2.4 lists the numbers of samples for the contamination analyses by area. The actual samples to be tested will be selected by the field representative and the Project Manager from samples at and within the most shallow saturated zone in the uranium plant yard, and from the unsaturated zone and the most shallow saturated zone in the other areas.

### 2.5 Data Evaluation and Reports

Data analyses, evaluations, and reports to be prepared during the project are described in the following section. The scheduling of these investigation components are discussed in Section 3 and are shown in Figure 3.1.

### 2.5.1 Data Evaluation.

Upon completion of the field program, all of the pertinent subsurface and hydraulic properties data will be used to prepare a characterization of the site hydrogeologic system and to quantify the impact, if any, which the facility has had on the hydrogeologic system. These data evaluations will be used to prepare a written description of the hydrogeologic system and to prepare graphic depictions (cross-sections, maps, and graphs) necessary to support the description.



## 2.5.2 Report.

### 2.5.2.1 Progress Reports.

Brief progress summary reports will be prepared during the course of the investigation to describe activities completed and revisions to the program during the prior 30-day period. Data acquired during the month prior to the report will be included in progress reports, as appropriate. The progress report will identify problems encountered, solutions applied, and possible schedule revisions. The progress report also will list activities planned and products expected to be completed during the following 30-day period.

### 2.5.2.2 Project Report.

The Project Report will be prepared upon the conclusion of the project. The report will contain a description of the field and laboratory data collection program, including procedures used, and will include all data obtained. The report also will describe analytical activities conducted for this program and present the characterization of the hydrogeologic system.

The report will be submitted first in draft form and later in final form which incorporates any necessary revisions or corrections. Submittal of the draft report is planned for approximately four weeks after receipt of the laboratory test results. The completion of the final report is planned for three weeks later.

TABLE 2.1  
Summary of Ground-Water Analyses

Location	Uranium	Plutonium	Gross Alpha, Beta Activity	NO3	F
URANIUM PLANT YARD	8	8	8	8	8
CLOSED WASTEWATER TREATMENT PONDS	6	6	6	6	6
LANDFILL SITE	8	8	8	8	8
SEWAGE LAGOONS	4	4	4	4	4
Total	26	26	26	26	26

TABLE 2.2  
 Summary of Physical Properties Analyses

Location	Particle Size	Atterberg Limits	Proctor Tests	Density	Moisture Content	Permeabil.	Matric Potential
URANIUM PLANT YARD	6	6	6	6	6	6	1
CLOSED WASTEWATER TREATMENT PONDS	1	1	1	1	1	1	1
LANDFILL SITE	6	6	6	6	6	6	1
SEWAGE LAGOONS	4	4	4	4	4	4	1
Total	17	17	17	17	17	17	4

TABLE 2.3  
 Summary of Soil Chemical Analyses

Location	Total Organic Carbon	Cation Exchange Capacity, Exchangable Cation	Mineralogy	Equilibrium Distribution Coefficient
URANIUM PLANT YARD	6	6	3	On Three Composite:
CLOSED WASTEWATER TREATMENT PONDS	1	1	1	
LANDFILL SITE	6	6	3	U Th
SEWAGE LAGOONS	4	4	2	
Total	17	17	9	3

TABLE 2.4

Summary of Soil Contamination Analyses

Location	Uranium	Plutonium	NO3, F
URANIUM PLANT YARD	6	6	6
CLOSED WASTEWATER TREATMENT PONDS	1	1	1
LANDFILL SITE	6	6	6
SEWAGE LAGOONS	4	4	4
Total	17	17	17

### 3. SCHEDULE FOR IMPLEMENTATION

Figure 3.1 shows the anticipated project schedule. This schedule presents the order that the investigation described in the preceding sections will be completed. The investigation is anticipated to commence January 16, 1989. The project as structured will require approximately three months to complete.

The drilling, soil and rock sampling, and well installation is estimated to take approximately three weeks. Well development, slug tests, and ground water sampling will take approximately ten days. The laboratory analyses will take approximately one month to complete. Data reduction and evaluation, and the presentation of a draft report should be completed three weeks after receipt of all analyses.

Project management is shown as a continuous task over the duration of the project. This represents the commitment of the project team to the project. The project management staff are available throughout the project to assure that the project is completed in a timely, orderly, and successful manner.

FIGURE 3.1

PROJECT SCHEDULE

WEEKS AFTER PROJECT COMMENCEMENT

1 2 3 4 5 6 7 8 9 10 11 12

Field Program:

Well drilling, installation \*\*\*\*\*  
Soil sampling \*\*\*\*\*  
Ground water sampling \*\*\*\*\*  
Slug tests \*\*\*\*\*

Laboratory Testing \*\*\*\*\*

Data Reduction, Analysis \*\*\*\*\*

Reporting

Progress Reports \*\*\*\*\*  
Project Report (draft) \*\*\*\*\*  
Project Report (final) \*\*\*\*\*

APPENDIX A  
DRILLING AND SAMPLING PROCEDURES



TABLE OF CONTENTS

Appendix A Drilling and Sampling Procedures

1. EQUIPMENT DECONTAMINATION PROCEDURES ..... A-4

2. DRILLING AND SAMPLING PROCEDURES ..... A-5

    2.1 General ..... A-5

    2.2 Water Supply ..... A-5

    2.3 Soil Drilling and Sampling ..... A-6

    2.4 Rock Drilling and Sampling ..... A-7

    2.5 Site Cleanup ..... A-9

LIST OF FIGURES

Figure A-1	Soil Boring Record (Field Form) .....	A-10
Figure A-2	Core Boring Record (Field Form) .....	A-11

APPENDIX A  
DRILLING AND SAMPLING PROCEDURES

1. EQUIPMENT DECONTAMINATION PROCEDURES

When drilling through or sampling in potentially contaminated materials, the following procedures will be followed to minimize the potential for introduction of contaminants from the surface or shallow strata into the deeper strata penetrated by drilling activities and to minimize the potential of cross-contamination during sampling:

- o Equipment to be used for the project will be steam-cleaned prior to arrival at the site. This includes drilling rigs, water tanks (flushed inside), augers (if used), bits, casings, rods, samplers, tools, etc.
- o All sampling tools will be cleaned on-site, prior to use and between each sampling event with clean water and a phosphate-free detergent. A source of potable water, approved by the Field Hydrogeologist, must be used. Other cleaning procedures may be required, but are task specific. These procedures will be described in the task specific sampling protocols.
- o The down-hole portion of drilling equipment will be cleaned on-site prior to use and between each boring with a high-pressure, hot-water cleaner using approved water.
- o Well completion materials will be cleaned with a high-pressure, hot-water cleaner using approved water prior to use. Materials which cannot be cleaned to the satisfaction of the responsible Field Hydrogeologist will not be used.
- o If contaminated soils are encountered during drilling, and the potential for significant cross-contamination is anticipated, modified drilling procedures will be used to prevent the transfer of contaminants to a deeper zone by the drilling method.
- o Cleaning and decontamination procedures will be performed in an area that is remote from any site to be sampled, to the extent feasible. All downhole tools and equipment will be checked with a geiger counter or scintillometer after cleaning.

## 2. DRILLING AND SAMPLING PROCEDURES

### 2.1 General

A final borehole diameter of between 6.5 and 8 inches will be required for the installation of wells with a two inch inside diameter (i.d.) casing.

Fuel, lubricants, and other similar substances will be handled in a manner consistent with accepted safety procedures and standard operating practices. Well completion materials will not be stored near or in areas which could be effected by these substances.

Surface runoff such as miscellaneous spills and leaks, precipitation, and spilled drilling fluid shall not be allowed to enter any boring or well either during or after drilling/well construction. To prevent this from happening, the use of starter casing, recirculation tanks, berms around the borehole, and surficial bentonite packs, as appropriate, are suggested.

Cuttings and cores will be checked with a geiger counter or scintillometer for radiological contamination. Where contaminants exist in shallow strata, a double-casing procedure will be required to minimize the potential for transferring contaminants to deeper strata. For these installations, a five-inch or larger PVC casing will be grouted through the contaminated strata before the boring is continued to its termination depth.

The Field Hydrogeologist will be present to observe all drilling and well installation activities and maintain a log of these activities. The Field Hydrogeologist also will keep a detailed descriptive log of materials penetrated by the boring. An example descriptive log is shown on Figure A-1.

### 2.2 Water Supply

Water used in drilling, equipment cleaning, or grouting will be taken from the the local potable water supply. Identification of the water source will be verified by contacting the appropriate plant personnel. If sources of non-potable water are present which might be confused with the proper water source, both the acceptable and unacceptable sources will be clearly marked to avoid possible confusion.

### 2.3 Soil Drilling and Sampling

Drilling in soil will be performed with equipment and procedures complying with the latest revision of ASTM specifications D 1586 and D 1587. Drilling in soil is planned to be accomplished using a hollow-stem auger drilling technique. If subsurface conditions are such that the planned technique does not produce acceptable results, e.g. unstable borehole walls or poor soil sample recovery, another technique deemed more appropriate to the type of soils present will be used. The procedure used must be appropriate for the subsurface lithologies present and also must be compatible with the efficient soil sampling in accordance with ASTM specifications D 1586 and D 1587 or an alternate soil sampling methods approved in advance by JLGA. If hollow-stem augering is used with the intent of installing the well casing through the augers, the inside diameter of the augers must not be less than four inches.

If borehole caving is experienced, bentonitic drilling fluid can be used only after approval of the Field Hydrogeologist. No organic additives will be used.

Soil sampling will be performed in accordance with ASTM specifications D 1586 or D 1587 or another similar method judged acceptable by the field geologist. Samples will be taken continuously over the full thickness of the soil deposits unless an alternative sampling frequency is requested by the Field Hydrogeologist. Good sample recovery is most important, and procedures will be modified, as necessary, to improve sample recovery.

Samples will be stored in clear glass containers, or waxed cardboard containers, labeled with the project number, boring number and sample number and depth. Exceptions will be thin-wall tube samples which are designated for undisturbed tests. These samples will be described on the basis of materials exposed at the top and bottom of the sample tube and will be sealed in the tube, labeled, and handled in a manner consistent with this work plan and the testing requirements.

The Field Hydrogeologist will be responsible for maintaining a descriptive log of materials recovered, photographing representative samples, and properly labeling and storing samples. A copy of the proposed field soil boring record form is presented in Figure A-1. The descriptive log will contain:

1. sample interval (top and bottom depth);
2. sample recovery;

3. blow count (ASTM D1586) or hydraulic pressure (ASTM D1587);
4. presence or absence of contamination;
5. material description, including: relative density, color, major textural constituents, minor constituents, relative moisture content, plasticity of fines, grain size, structure or stratification, and any other significant observations.
6. lithologic contacts: the depth of contacts between differing lithologic units will be measured and recorded to the nearest 0.05 feet.

#### 2.4 Rock Drilling and Sampling

Drilling in rock will be by diamond core drilling techniques or by a rotary drilling technique. Diamond coring will be conducted in accordance with the latest revision of ASTM D 2113. Rotary drilling, wherein only cuttings samples are returned to the surface, will be used only in conjunction with diamond core drilling. The Field Hydrogeologist will determine the appropriate drilling technique.

For core drilling, the acceptable core diameter will be approximately two inches. The drilling contractor will modify drilling procedures, as necessary, to maximize the recovery of cored rock. The Field Hydrogeologist will monitor drilling production and core recovery and notify the drilling contractor of unacceptable performance.

For rock intervals not cored, cuttings brought to the surface in the drilling fluid will be sampled. Cuttings samples will be composited to represent each 2.0 feet long interval of rock penetrated by the drill bit. Cuttings samples will be placed in properly labeled, clear glass containers.

The Field Hydrogeologist will handle all recovered core or cuttings samples. He will prepare a descriptive log, take photographs, and properly label and store the samples. Recovered rock core will be placed in properly labeled waxed cardboard, plastic, or wood core boxes. Each box will be marked in accordance with ASTM D 2113 with the project name, boring number, depth interval represented, and the box number. Cuttings samples will be placed in properly labeled glass container. Container labels will show the project name, boring and sample number, and sample depth.

The descriptive log of recovered core will include:

1. cored interval and recovery;
2. Rock Quality Designation (RQD): RQD = cumulative length of recovered core pieces greater than or equal to four inches in length divided by the total length of the core run;
3. discontinuity description: depth, character, and orientation of joints, fractures, and other non-depositional breaks in the rock;
4. partings description: depth, character, and orientation of depositional (bedding) features;
5. rock weathering: description of weathering or weathered zones;
6. geohydrologic description: qualitative description of permeability;
7. penetration rate: where applicable, a record of the speed of drill bit penetration in minutes per foot;
8. rock lithology: description of rock lithology and depths of significant features or contacts. Description to include rock name, relative hardness, color, texture or grain size, cementation, structure or stratification, and other pertinent information such as accessory minerals or fossils.
9. lithologic contacts: the depth of contacts between differing lithologic units will be measured and recorded to the nearest 0.05 feet.
10. presence or absence of odors or visible evidence of contamination;
11. presence of radionuclides determined by use of a hand-held scintillometer.

Figure A-2 is an example of the form to be used for recording core boring information.

## 2.5 Site Cleanup

After completion of drilling, any cuttings brought to the surface which might be contaminated will be placed in drums and stored on-site. These materials will be included with other site materials moved to a location identified for long-term stabilization. Temporary on-site storage of such cuttings will be at a controlled location.



JOB NO. \_\_\_\_\_

DRILLER \_\_\_\_\_

GROUND SURFACE ELEV. \_\_\_\_\_

JOB NAME \_\_\_\_\_

HOURS DRILLING \_\_\_\_\_

HOURS MOVING \_\_\_\_\_

DATE: \_\_\_\_\_ WEATHER \_\_\_\_\_

PAGE \_\_\_\_\_ OF \_\_\_\_\_

Depth	SAMPLING			SCALE	UD	REC	SOIL CLASSIFICATION AND REMARKS
	1ST 6"	2ND 6"	3RD 6"				
0				0			
5				5			
10				10			
15				15			
20				20			
25				25			
30				30			
35				35			
40				40			
45				45			
50				50			
55				55			
60				60			
65				65			
70				70			
75				75			
80				80			
85				85			
90				90			
95				95			
100				100			

+STANDARD PENETRATION RESISTANCE IS SUM OF BLOWS FOR 2ND 6" AND 3RD 6" TO DRIVE 1-3/8" I.D., 2" O.D. SPLIT BARREL SAMPLER WITH 140 POUND HAMMER FALLING 30 INCHES.

BORING TERMINATED: \_\_\_\_\_  
 BORING REFUSAL: \_\_\_\_\_  
 WATER TOB DEPTH \_\_\_\_\_  
 WATER 24 HR.: DEPTH \_\_\_\_\_  
 WATER LOSSES \_\_\_\_\_  
 CASING: SIZE \_\_\_\_\_ LENGTH \_\_\_\_\_

METHOD OF ADVANCING BORING	DEPTH
POWER AUGER	TO _____
HAND CHOP: W/MUD: W/WATER	TO _____
ROTARY DRILL: W/MUD: W/WATER	TO _____
DIAMOND CORE	TO _____

PROJECT NAME \_\_\_\_\_

PROJECT NO. \_\_\_\_\_

BORING LOCATION \_\_\_\_\_

DRILLED BY \_\_\_\_\_

LOGGED BY \_\_\_\_\_

CHECKED BY \_\_\_\_\_

DRILLING DATES - FROM \_\_\_\_\_ TO \_\_\_\_\_

DATUM \_\_\_\_\_

DATUM ELEVATION \_\_\_\_\_

DEPTH (FEET)	CORE INFO		ROD		DISCONTINUITIES JOINTS/FRACTURES			PARTINGS BEDDING/FOLIATION			ROCK WEATHERING	GEOHYDROLOGIC INFORMATION	PENETRATION RATE (MIN/FT)	DEPTH	LITHOLOGIC DESCRIPTION	DEPTH (FEET)
	CORE SZ RUN NO	REC. %	PIECE LN	ROD	NATURE	SPACING	DIP & DIRECTION	NATURE	SPACING	DIP & DIRECTION						

A-11

FIGURE A-2

APPENDIX B  
WELL INSTALLATION PROCEDURES

TABLE OF CONTENTS

Appendix B Monitoring Well Installation Procedures

- 1. MONITORING WELL INSTALLATION PROCEDURES ..... B-4
  - 1.1 Materials Decontamination ..... B-4
  - 1.2 Well Casing ..... B-4
  - 1.3 Well Screen ..... B-5
  - 1.4 Sand Filter ..... B-5
  - 1.5 Annular Sealant ..... B-5
  - 1.6 Protective Surface Casing ..... B-6
  - 1.7 Well Survey ..... B-6
  
- 2. WELL DEVELOPMENT ..... B-6
  - 2.1 Procedure for Air-Lift Well Development ..... B-7
  - 2.2 Alternate Well Development Procedures ..... B-8
  - 2.3 Development Records ..... B-9
  
- 3. WELL ABANDONMENT ..... B-9

LIST OF FIGURES

Figure B-1      Monitoring Well Design ..... B-11

APPENDIX B  
MONITORING WELL INSTALLATION PROCEDURES

1. MONITORING WELL INSTALLATION PROCEDURES

1.1 Materials Decontamination

Well completion materials will be inspected by the Field Hydrogeologist and determined to be clean and acceptable for use. Casing, screen and casing plugs and caps will be cleaned with a high-pressure, hot-water cleaner using approved water prior to use. Pre-packaged sand will be used in well construction and the bags will be inspected for possible external contamination before use. Pre-packaged bentonite and portland cement, inspected for possible external contamination, also will be used. Materials which cannot be cleaned to the satisfaction of the responsible Field Hydrogeologist will not be used.

1.2 Well Casing

Upon completion of drilling to the proper termination depth, a monitoring well casing will be installed in each boring. A schematic representation of a completed well is shown on Figure B-1.

Blank well casing and well screen will be constructed of Schedule 40 PVC with an inside diameter of two inches. All well casing sections will be flush-threaded. Glued joints are not acceptable. The casing at each well will be fitted with a bottom plug and a top cap constructed of the same type material as the well casing.

The Field Hydrogeologist will verify and record the boring depth, the lengths of all casing sections, and the depth to the top of all well completion materials placed in the annulus between the casing and borehole wall. All lengths and depths will be measured to the nearest 0.1 foot.

### 1.3 Well Screen

Well screens will be constructed of flush-threaded, Schedule 40 PVC with an inside diameter of two inches. Each well will be screened in the water-bearing stratum underlying the soil deposits. The screened intervals will be 10 feet in length. The position of the screen will be selected by the Field Hydrogeologist after consideration is given to the geometry and hydraulic characteristics of the stratum in which the well will be screened.

Each well screen will be isolated from the overlying deposits using an annular seal consisting of a combination of a two-foot thick bentonite pellet seal overlain by an interval of cement/bentonite grout. The grout interval will extend from the top of the pellet seal to the ground surface.

The slots in the screens will be factory cut. A slot size of 0.010 inches is estimated to be appropriate for use in the rock.

### 1.4 Sand Filter

A graded sand filter will be placed against the screened interval and extend one to two feet above the top of the screen. If the screen is set in sound rock, the filter gradation will be selected so that no more than about ten percent of the filter material is finer than the size of the well screen slots. If fine grained materials are present in the rock, such as joint filling material, the gradation of the sand filter will be intermediate of the mean diameter of the fine-grained material and the screen slot size. The procedure use to select filter grain size is described by Driscoll.<sup>1</sup>

### 1.5 Annular Sealant

An annular seal will be placed above the sand filter using sodium bentonite pellets. The pellet seal will be a minimum of two feet thick.

---

<sup>1</sup> Driscoll, Fletcher G. "Groundwater and Wells". Johnson Division St. Paul Minnesota. 1986.

A portland cement/sodium bentonite grout will be placed from the top of the pellet seal to the ground surface. The grout mixture used will consist of one 94-pound sack of cement and about five pounds bentonite for each seven gallons of water used. All grouting below the ground-water level or deeper than 10 feet below ground surface will be performed by pumping using a small-diameter tremie pipe positioned several feet above the top of the bentonite pellet seal.

### 1.6 Protective Surface Casing

Each monitoring well will be completed with a five-foot long, 6 inch diameter, steel protective casing with a hinged, lockable cover. The inside diameter of the protective casing will be at least four inches. A one-half inch diameter drain hole will be drilled in the steel casing just above the ground surface. Each protective casing will be painted with a rust-retardant primer and a bright paint. A 4 foot by 4 foot concrete pad (well apron) will be constructed around each of the wells. The concrete pad will have a minimum thickness of 4 inches, except where underlain by the borehole where a minimum thickness of three feet is required.

### 1.7 Well Survey

The location and elevation of the new well will be surveyed by a surveyor registered in the State of Oklahoma soon after well completion. The horizontal location will be measured relative to established facility coordinates. Horizontal coordinates will be measured to the nearest 1.0 foot. Vertical location of the ground surface adjacent to the well casing and the measurement datum (top of interior casing), will be measured relative to U.S.G.S. datum. The ground surface elevation will be measured to the nearest 0.1 foot and the measurement datum to the nearest 0.01 foot.

## 2. WELL DEVELOPMENT

Before a new well can be considered in proper condition for monitoring water levels, testing, or taking water samples, it will be developed. Development removes sediment from inside the well casing and flushes fines, cuttings, and drilling fluids from the sand pack and the portion of the formation adjacent to the well screen.



Well development will not be performed until at least 24 hours after well grouting is completed. Well development will be performed within one week of well installation. Development water will be put into barrels and disposed of in the Cimarron wastewater treatment facilities.

## 2.1 Procedure for Air-Lift Well Development

The following procedure describes an air-lift technique for well development. The hardware used for this technique is installed so that air used to lift water from the well does not contact the well casing and does not enter the well screen.

1. Clean all apparatus to be used down-hole by first steam-cleaning and then using a detergent and tap water wash, tap water rinse, distilled water rinse.
2. Measure and record the depth to ground water and total depth of the well, before development.
3. Assemble the small diameter development tubing (e.g. 1" or 1.5" o.d. for 2" i.d. well casing), with a one-way, check-valve at the bottom and a total length which can extend from the bottom of the well to the ground surface.
4. Place the first section of the development tubing inside the well and place the air line inside the tubing. Assemble and lower additional sections of the development tubing and air line until the tubing rests at, or just above, the bottom of the well.
5. Lift the tubing several inches above the bottom of the well and secure the lifting line to the well protector pipe.
6. Secure the air line to prevent air pressure from lifting the air line.
7. Attach an in-line hydrocarbon filter to the air line.
8. Using the shut-off valve, send a pulse of air down the air line. Shut off the air when a column of water comes out of the well.
9. Water produced during development will be discharged to the ground surface at a location away from the well. Ground water from the water from the rock stratum is not anticipated to have been contaminated by prior activities at the facility and special provisions for management of this water are not planned.

10. Allow the well several seconds (or minutes, if necessary) to recover, then send another "air pulse".
11. Repeat the pulsing process, occasionally moving and securing the tubing at different levels within the well screen.
12. Repeat this process until water from the well is clear (or nearly clear).
13. Record the development time, the number of pulses and the estimated volume of water produced during development, and the color of water at the beginning and end of development.
14. Disconnect and remove the development apparatus from the well for cleaning before use in another well.
15. Verify that the protector pipe drain is functional and development water is not held inside the protector pipe.
16. Measure and record the post-development depth to ground water and total depth of the well.

## 2.2 Alternate Well Development Procedures

Well development also can be accomplished using surge blocks, cleaned bailers or manual or automatic pumps. A loosely-fitting surge block can be used to agitate the water and sediment in the well before water is removed from the well using bailer or pump. The bailer or pump intake regularly must be lowered to the bottom of the well so that fines which have accumulated in the bottom are agitated and removed from the well in the development water. If a pump is used, the intake level should be moved to different positions within the well screen so as to draw water into the well from different levels.

Development should be continued until a minimum of ten casing volumes of water have been removed from the well and the water produced is clear. If the development water still is turbid after removal of ten casing volumes, development should be continued until the water become clear or the turbidity of the water produced has been stable for the removal of several casing volumes.

### 2.3 Development Records

Development records should include:

- o Well Number
- o Date and time of development
- o Development method
- o Pre-development water level and well depth
- o Volume of water produced
- o Description of water produced
- o Post-development water level and well depth


### 3. WELL ABANDONMENT

Any boring or well to be abandoned shall be sealed by grouting from the bottom of the boring/well to ground surface. This shall be done by placing a grout pipe to the bottom of the boring/well and pumping grout through the pipe until undiluted grout flows from the boring well at ground surface.

A portland cement/sodium bentonite grout will be used for grouting. The grout mixture used will consist of one 94-pound sack of cement and about five pounds bentonite for each seven gallons of water used. Additives or cuttings are not to be added to the grout mixture. The grout materials are to be combined in an above-ground rigid container or mixer and mechanically mixed to produce a thick, lump-free mixture. The mixed grout is to be recirculated through the grout pump prior to placement. These procedures may require some modification to meet state requirements regarding borehole abandonment.

An abandoned well may be grouted with the well screen and casing in place. However, if the integrity of the casing seal is questioned, the Field Hydrogeologist may require that the casing be removed prior to abandonment. In this instant, partial or total hole re-drilling will be necessary prior to sealing the well. Each boring/well that is abandoned must have a record of abandonment completed.

Twenty-four hours after abandonment, the Field Hydrogeologist, or his designate, shall check the abandoned site for grout settlement and specify the addition grout, as necessary. This process is to be repeated until firm grout remains at the surface.



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD, COLORADO

FIGURE B-1  
**MONITORING WELL DESIGN**

APPENDIX C  
FIELD TESTING PROCEDURES

TABLE OF CONTENTS

Appendix C Field Testing Procedures

1. WATER-LEVEL MEASUREMENT .....	C-4
2. SLUG TEST PROCEDURE .....	C-4
3. STEP-DRAWDOWN TEST PROCEDURE .....	C-5
4. CONSTANT-RATE PUMPING TEST PROCEDURE .....	C-7

## LIST OF FIGURES

Figure C-1	Water Level Data .....	C-9
Figure C-2	Variable Head Permeability Test .....	C-10
Figure C-3	Aquifer Test Pump Log .....	C-11
Figure C-4	Aquifer Test Recovery Log .....	C-12
Figure C-5	Observation Well Log .....	C-13



APPENDIX C  
FIELD TESTING PROCEDURES

1. WATER-LEVEL MEASUREMENT

To determine the ground-water level and flow direction, water levels will be measured at all wells within a short time interval so that the data are comparable. Water levels will not be measured until the water level in the new wells have equilibrated to static conditions. The depth to water below the measurement datum will be made to the nearest 1/8 inch (0.01 feet).

Water-level data will be recorded on an appropriate data form. An example form is presented in Figure C-1.

2. SLUG TEST PROCEDURE

To measure the hydraulic conductivity at new wells, "slug tests" will be performed. The procedure involves lowering a slug, or sealed tube, into the water in the well and allowing the raised water level to recover to the pre-insertion level. The slug then is removed quickly and the recovery of the lowered water level to static level monitored, timed, and recorded. Slug test results will be evaluated in accordance with the methods presented by Bouwer and Rice.<sup>1</sup>

To provide useful data, slug tests usually must be conducted using a recording pressure transducer to measure ground-water levels. In sandy or other permeable aquifers, the useful portion of the recovery curve can occur within the first five seconds of the test. A log-type measurement frequency is necessary to allow very frequent measurements (0.5 second or less) in the first several seconds and less frequent measurements after about 10 to 20 seconds.

Using manual measurement methods, it is unlikely that any measurements can be made in the first several seconds. Manual measurement of recovery probably is adequate in low permeability materials where recovery is very slow.

---

<sup>1</sup> Bouwer, H. and R. C. Rice, 1976, "A Slug Test for Determining Hydraulic Conductivity of Unconfined Aquifers With Completely or Partially Penetrating Wells", Water Resources Research, Vol. 12, No. 3.

Test data from a slug test will be recorded on a Variable Head Permeability Test form, such as the one shown on Figure C-2.

### 3. STEP-DRAWDOWN TEST PROCEDURE

The step drawdown test procedure involves monitoring drawdown as the well is pumped at several pumping rates. The test results can be used to predict well drawdown from pumping at various rates for extended periods and are useful for selecting the proper pumping rate for 8 hour, 24 hour, or longer pumping tests. The results also can be used to compute specific capacity, transmissivity, and head losses in the well.

During a step-drawdown test, the well is pumped at several rates for short periods. Usually the initial pumping rate is small, often less than five gpm, and the rate is stepped up by approximately doubling the rate on each step. Pumping at each step is continued for about the same length of time. Ideally, the well would be allowed to recover to the initial static level between tests, but it is acceptable to conduct a continuous test by just stepping up the pumping rate at the proper time.

Drawdown measurements at the beginning of the test, and at the beginning of each successive step are made on a frequent interval. As the measurements are made, drawdown and log time are plotted. Examination of the plot allows estimation of the drawdown expected over the pumping period for each pumping rate. The step drawdown test data are evaluated in accordance with procedures presented by Brereton.<sup>2</sup>

The test is continued for several pumping rates. If the results are to be used to determine the proper pumping rate for a longer, constant-rate pumping test, the stepped rates are selected to bracket the required drawdown for the constant-rate test. The proper rate for the constant-rate test is selected using the planned test duration and required drawdown and comparing these numbers to the drawdown curves (from the step test) to select the proper pumping rate.

Pumping rates are measured with an in-line, totalizing water meter, an orifice weir, or timed filling of a container of known volume. Discharge rates will be measured frequently during the test.

---

<sup>2</sup> Brereton, N. R., 1979, "Step-drawdown Pumping Tests for the Determination of Aquifer and Borehole Characteristics" Water Research Center Technical Report TR 103 (UK)

Test data are recorded on the following data forms or in the Field Log Book:

- o Aquifer Test Pump Log (Figure C-3) for recording pumping steps and drawdown at the pumping well
- o Aquifer Test Recovery Log (Figure C-4): for recording draw-down changes during recovery

Upon completion of the final pumping test (unless the step test goes directly into a constant-rate test) a recovery test is conducted. Recovery test procedures involve monitoring the rate of water-level rise following cessation of pumping. Recovery test data can be evaluated using the straight-line methods contained in Lohman on pages 23 to 27.<sup>3</sup>

Water produced during a step-drawdown test, if considered contaminated, will be discharged to the ground surface in an area of known surface contamination. Otherwise, the water will be discharged to the Cimarron wastewater treatment facilities.

The equipment used for step-drawdown and constant-rate pumping tests are identical. The following list summarizes these items.

1. Pump - when final drawdowns will not exceed about 12 to 14 feet below ground surface, it is possible to use a surface pump with a suction intake hose set within the well screen. When the final water level is expected to exceed 12 to 14 feet, a submersible pump usually is required. (Jet pumps set at the surface can lift water from depths greater than 12 to 14 feet) Pump size (for submersed operation) and intake or discharge hoses must be sized to allow measurement equipment, power cords, safety lines, etc. to fit in the well.
2. Power source for the pump - "plug-in" electricity is preferable, but a generator properly sized for the pump usually is required. For submersible pumps, a power cable to the pump is required. Surface suction-type pumps often have gasoline engines.
3. Intake hose, properly sized for the well.
4. Discharge hose, to discharge pumped water to a container or to an impoundment.

---

<sup>3</sup> Lohman, S. W., 1979, "Ground-Water Hydraulics", U. S. Geological Survey Professional Paper 708.

5. Safety line for submersible pump.
6. Water-level measurement device - electric probe or transducer. When a part of pump flow is recirculated to the well (for low pumping rates) a "stilling well" (0.5 to 1.0 inch i.d. hose) is advisable for measuring water levels in the pumped well. The stilling well is not necessary when a transducer is used in the pumped well.
7. Valves, "T" coupling, and hoses - necessary to recirculate water to the pumped well and control discharge rate. Partial flow recirculation during low pumping rate is advisable during longer tests to prevent pump damage.
8. Discharge measurement device - bucket and stop-watch, water meter, or weir.
9. Tools, electrical tape, measurement tape, etc.

The attached sketch illustrates a typical set-up of pump test equipment.

#### 4. CONSTANT-RATE PUMPING TEST PROCEDURE

A sustained pumping test involves pumping a well at a nearly-constant discharge for several hours to several days. This procedure usually requires monitoring water levels in one or more observation wells in addition to the pumped well. Data are evaluated to determine aquifer transmissivity, storativity, and hydraulic conductivity.

Procedures and set-up for the constant-rate test are essentially identical to those for the step-drawdown test except that pumping rate is controlled at a constant rate. After the initial hour of the test, the measurement of drawdown in the pumped well and observation well(s) and discharge rate is made each half hour to one hour until the test is completed. Upon test completion, a recovery test is conducted.

The drawdown during the constant-rate test must be monitored to make sure the drawdown does not exceed the planned maximum. Usually limitations on drawdown are: pump lift capacity (12-14 feet for suction pumps, variable for submersible pumps), height of water column in the well (usually do not want to draw water level down below the top of the well screen), or a pre-determined maximum drawdown. As drawdown increases, pump lift increases and pumping rate (with set valve openings) decreases. Thus, as drawdown increases, the valve on the discharge hose probably must be opened to maintain a constant discharge rate.

Test data are recorded on the following data forms:

- o Aquifer Test Pump Log (Figure C-3): for pumping and drawdown data at the pumping well.
- o Aquifer Test Recovery Log (Figure C-4): for recovery data a pumping and observation wells.
- o Observation Well Log (Figure C-5): for drawdown data at observation wells.

Constant-rate pump test data for the pumped well usually are evaluated using Lohman's straight-line method. Data for the observation well(s) are evaluated using curve-matching techniques which also are included in Lohman (1979).

Water produced during a step-drawdown test, if considered contaminated, will be discharged to the ground surface in an area of know surface contamination. Otherwise, the water will be discharged to the wastewater treatment system.

WELL INFORMATION							WATER LEVELS							
Well Number	Installation Date	Ground Surface Elevation (Ft. MSL)	Reference Point Elevation (Ft. MSL)	Total Depth from Ref. Pt. (Feet)	Stickup (Feet)	Depth from Ground Surface (Feet)	Date	Measured by	Depth from Reference Point (Feet)	Water Surface Elevation (Ft. MSL)	Date	Measured by	Depth from Reference Point (Feet)	Water Surface Elevation (Ft. MSL)
Job Name								WATER LEVEL AND WELL INFORMATION						
Job Number														

FIGURE C-1

JAMES L. GRANT & ASSOCIATES

Variable Head Permeability Test

Test Performed By \_\_\_\_\_ Date \_\_\_\_/\_\_\_\_/\_\_\_\_

Well or Boring No. \_\_\_\_\_ Total Well Depth \_\_\_\_ ft.

Length of Solid Casing \_\_\_\_\_ ft. Length of Solid Casing \_\_\_\_\_ ft.

Initial Depth from Datum \_\_\_\_\_ ft. Quantity of Water Bailed \_\_\_\_\_ gal.

Datum (check one): Ground Surface \_\_\_\_ Top of Casing \_\_\_\_

Type of Test (check one): Inflow \_\_\_\_ Outflow (Bailing) \_\_\_\_

Time Slug Inserted \_\_\_\_\_ hrs. \_\_\_\_\_ min \_\_\_\_\_ sec

Time Slug Removed \_\_\_\_\_ hrs. \_\_\_\_\_ min \_\_\_\_\_ sec

Time (min.)	Depth* (ft.)	Remarks

# AQUIFER TEST PUMP LOG

FILING NO.	COMPANY _____				
WATER MEASURED FROM	WELL NO. _____				
ELEV. OF MEASURING POINT	CITY _____		COUNTY _____		
STATIC WATER LEVEL FT.	STATE _____		JOB NO. _____		
AQUIFER SCREENED	LOCATION SEC. _____ TWP _____ RGE _____			DATE _____	
TIME PUMPING BEGAN (A.M.) HRS. (P.M.)	MIN.	SEC.	DATE		TYPE OF DISCHARGE DEVICE
TIME PUMPING ENDED (A.M.) HRS. (P.M.)	MIN.	SEC.	DATE		TYPE OF W/L MEASURING DEVICE
	DATA TAKEN BY _____				

TIME	ELAPSED TIME (MIN)	TAPE HELD/ NEAREST BAND (FT)	WETTED/ DIST TO NEAREST BAND (FT)	WATER LEVEL (FT)	DISCHARGE MEASUREMENT	DISCHARGE RATE (GPM)	REMARKS



# AQUIFER TEST RECOVERY LOG

WELL NO.	COMPANY _____				
WATER MEASURED FROM	WELL _____				
ELEV. OF MEASURING POINT	CITY _____		COUNTY _____		
STATIC WATER LEVEL _____ FT.	STATE _____			JOB NO. _____	
AQUIFER SCREENED	LOCATION: SEC. _____ TWP _____ RGE _____			DATE	
TIME PUMPING BEGAN (A.M.) _____ HRS. (P.M.) _____	MIN. _____	SEC. _____	DATE _____	TYPE OF W/L MEASURING DEVICE	
TIME PUMPING ENDED (A.M.) _____ HRS. (P.M.) _____	MIN. _____	SEC. _____	DATE _____	DATA TAKEN BY _____	

TIME	ELAPSED TIME (MIN)	TAPE HELD/NEAREST BAND (FT)	WETTED/DIST TO NEAREST BAND (FT)	WATER LEVEL (FT)	REMARKS	TIME	ELAPSED TIME (MIN)	TAPE HELD/NEAREST BAND (FT)	WETTED/DIST TO NEAREST BAND (FT)	WATER LEVEL (FT)	REMARKS

# OBSERVATION WELL LOG

FILING NO. \_\_\_\_\_  
WATER MEASURED FROM \_\_\_\_\_  
ELEV. OF MEASURING POINT \_\_\_\_\_

COMPANY \_\_\_\_\_  
WELL \_\_\_\_\_  
CITY \_\_\_\_\_ COUNTY \_\_\_\_\_  
STATE \_\_\_\_\_ JOB NO. \_\_\_\_\_

STATIC WATER LEVEL \_\_\_\_\_ FT.  
AQUIFER SCREENED \_\_\_\_\_

LOCATION: \_\_\_\_\_  
SEC. \_\_\_\_\_ TWP \_\_\_\_\_ RGE \_\_\_\_\_

DATE \_\_\_\_\_  
TYPE OF W/L MEASURING DEVICE \_\_\_\_\_

TEST PUMP WELL \_\_\_\_\_

TEST RECOVERY WELL \_\_\_\_\_

DATA TAKEN BY \_\_\_\_\_

TIME	ELAPSED TIME (MIN)	TAPE HELD/ NEAREST BAND (FT)	WETTED/ DIST. TO NEAREST BAND (FT)	WATER LEVEL (FT)	REMARKS	TIME	ELAPSED TIME (MIN)	TAPE HELD/ NEAREST BAND (FT)	WETTED/ DIST. TO NEAREST BAND (FT)	WATER LEVEL (FT)	REMARKS

APPENDIX D  
GROUND-WATER SAMPLING PROCEDURES

## TABLE OF CONTENTS

## Appendix D Ground Water Sampling and Analysis Procedures

1. GROUND-WATER SAMPLING PROCEDURES .....	D-4
1.1 Sampling and Analysis Personnel .....	D-4
1.2 Summary of Sampling Procedures .....	D-4
1.3 Arrangements with Analytical Laboratory .....	D-5
1.4 Preparation for Sampling .....	D-5
1.4.1 Equipment Check-Out .....	D-5
1.4.2 Equipment Calibration .....	D-5
1.4.3 Equipment Cleaning .....	D-6
1.5 Sampling Procedures .....	D-6
1.5.1 Preparation of Location .....	D-7
1.5.2 Water-Level Measurement .....	D-7
1.5.3 Total Depth Measurement .....	D-8
1.5.4 Visual Inspection of Well Water .....	D-8
1.5.5 Well Bore Evacuation .....	D-8
1.5.6 Sample Extraction .....	D-10
1.5.7 Quality Control Samples .....	D-10
1.5.8 On-Site Parameter Measurement .....	D-11
1.6 Sample Handling .....	D-11
1.6.1 Sample Preservation .....	D-11
1.6.2 Container and Labels .....	D-12
1.6.3 Sample Shipment .....	D-12
1.6.4 Chain of Custody Control .....	D-13
1.7 Sampling Records .....	D-14

LIST OF FIGURES

Figure D-1	Well Evacuation Chart .....	D-15
Figure D-2	Chain of Custody Form .....	D-16
Figure D-3	Water Sampling Record .....	D-17

APPENDIX D  
GROUND WATER SAMPLING AND ANALYSIS PROCEDURES

1. GROUND-WATER SAMPLING PROCEDURES

1.1 Sampling and Analysis Personnel

Sampling and analysis will be conducted by trained personnel. All sampling and analysis personnel will be trained in the performance of the specific task to which they are assigned. Training documentation will be available if requested.

Sampling personnel will have thoroughly reviewed this Sampling and Analysis Plan prior to conducting sampling and will have a copy of the plan available for reference.

1.2 Summary of Sampling Procedures

Activities which will occur during ground-water sampling are summarized as follows:

- o pre-arrangement with testing laboratory
- o assembly and preparation of equipment and supplies
- o ground-water sampling
  - water-level measurements
  - visual inspection of borehole water
  - well bore evacuation
  - sampling
- o sample preservation and shipment
  - sample preparation
  - on-site measurement of parameters
  - sample labeling
- o completion of sample records
- o completion of chain-of-custody records
- o sample shipment

Detailed sampling and analysis procedures are presented in following sections.

### 1.3 Arrangements with Analytical Laboratory

Prior to sampling, arrangements will be made with an analytical laboratory which will conduct the sample analyses. The requirements for the laboratory are included in Section 2 of this Sampling and Analysis Plan.

The laboratory will provide a sufficient number of sample containers for the wells to be sampled and the blanks to be included. The laboratory will determine the proper type and size for the containers based upon the analyses to be conducted. For samples requiring chemical preservation, preservatives will be added to containers by the laboratory prior to shipping containers to the facility. Shipping containers, ice chests with adequate container padding and cooling media, will be sent to the facility with the containers.

### 1.4 Preparation for Sampling

Prior to the sampling episode, all equipment to be used will be assembled and its operating condition verified, calibrated (if required), and properly cleaned (if required). In addition, all record-keeping materials will be prepared.

#### 1.4.1 Equipment Check-Out.

This activity includes the verification that all equipment is in proper operating condition. Also, arrangements for repair or replacement of any equipment which is inoperative are made.

#### 1.4.2 Equipment Calibration.

Where appropriate, equipment will be calibrated according to the manufacturer's specifications prior to field use. This applies to the equipment for making on-site chemical measurements of pH, eH, conductivity, and temperature of water.

### 1.4.3 Equipment Cleaning.

All portions of sampling and test equipment which will contact the sample will be thoroughly cleaned before use for sampling. This includes water-level tapes or probes, pumps, tubing, bailers, lifting line, test equipment for on-site use, and other equipment or portions thereof which are to be immersed.

The procedure for equipment cleaning will depend upon the type of analyses to be conducted with the sample. Changes to the procedure are noted.

- o Clean with potable water and phosphate-free laboratory detergent;
- o Rinse with potable water;
- o Rinse with dilute (0.1N) reagent-grade hydrochloric or nitric acid (for samples planned for inorganic constituent analyses)
- o Rinse with distilled or deionized water;
- o Rinse with reagent-grade acetone (for samples planned for organic constituent analyses)
- o Rinse with reagent-grade hexane (for samples planned for organic constituent analyses)
- o Air dry the equipment prior to use.

Any deviations from these procedures should be documented in the permanent record of the sampling event.

Laboratory-supplied sample containers will be cleaned and sealed by the laboratory before shipping. The type of container provided and the method of container should be in the laboratory's permanent record of the sampling event.

### 1.5 Sampling Procedures

Special care will be exercised to prevent contamination of the ground water and extracted samples during the sampling activities. The two primary ways in which such contamination can occur are:

- o contamination of a sample through contact with improperly cleaned equipment; or



- o cross-contamination of the ground water through insufficient cleaning of equipment between wells.

To prevent such contamination, sampling equipment and sample containers will be thoroughly cleaned before and after field use and between uses at different sampling locations according to the procedures in Section 1.4.3. In addition to the use of properly cleaned equipment, two further precautions will be followed:

- o a clean pair of new, disposable latex (or similar) gloves will be worn each time a different well is sampled; and
- o sample collection activities will progress from the least affected (up-gradient) area to the most affected (down-gradient) area. Wells described as "background" or "up-gradient" wells will be sampled first.

The following paragraphs present procedures for the several activities which comprise ground-water sample acquisition. These activities will be performed in the same order as presented below. Exceptions to this procedure will be noted in the permanent sampling record.

#### 1.5.1 Preparation of Location.

Prior to starting the sampling procedure, the area around the well should be cleared of foreign materials, such as brush, rocks, debris, etc. A clean (new), disposable, plastic sheet should be placed around the well casing so that the sheet is flat on the ground and the well projects through and above the center of the sheet. Flush-with-ground wells will not project through the sheet. For projecting protective well casings, a clean (new) plastic trash bag should be placed around the projecting casing or protector pipe and secured (with tape) to the casing so that only the interior well casing is visible.

This preparation will prevent sampling equipment from inadvertently contacting the ground or exterior parts of the well.

#### 1.5.2 Water-Level Measurement.

The first sampling operation is water-level measurement. An electrical probe will be used to measure the depth to ground water below the datum to the nearest 1/8 inch (0.01 foot). The datum, usually the top of the inner casing (inside and below the protective steel cover), will be described in monitor well records. A permanent mark or scribe will be visible on inspection

of the inner casing.

If the wells to be sampled are closely spaced, such as in well clusters, the water levels at all of the closely-spaced wells should be measured before any of the wells are evacuated. The water level probe should be cleaned with phosphate-free detergent in distilled water and with a distilled water rinse between usage at different wells.

#### 1.5.3 Total Depth Measurement.

Once the water level has been measured and recorded, the water-level probe should be slowly lowered to the bottom of the well. The depth to the bottom should be measured and recorded. The probe then should be slowly withdrawn from the well. The bottom of the probe should be examined after withdrawal to determine if evidence of any viscous, heavy contaminants is apparent. Observations, and measurements if possible, of such materials should be made from examination of the probe.

#### 1.5.4 Visual Inspection of Well Water.

Prior to well evacuation, a small quantity of water will be removed with a bailer, in a manner which will not totally immerse the bailer. The recovered sample is representative of the top of the water column in the well casing. If immiscible materials accumulate at the top of the water column, this technique can allow their detection. The water from the bailer will be decanted into a clean container. If a transparent bailer is used, decanting is unnecessary and the observation can be made through the bailer. The water will be inspected for the presence of any floating films or other indications of immiscible materials. Any sample odors will be noted. These observations regarding odor or visual evidence of immiscible materials will be recorded in the sampling record.

The sample taken in this manner will be discarded unless the site-specific protocol calls for retention of this sample. If the sample is to be discarded but is suspected to be contaminated, the water should be placed in a container for proper disposal.

#### 1.5.5 Well Bore Evacuation.

Water contained within, and adjacent to, the well casing potentially can reflect chemical interaction with the atmosphere (by diffusion of gases down the casing) or the well construction materials (through prolonged residence adjacent to the casing). This water will be removed and discarded.

The volume of water contained within the well bore at the time of sampling will be calculated, and three times the calculated volume will be removed from the well and discarded. The use of a bailer for well evacuation is planned. Calculation of the volume of water to be evacuated will be done as follows.

$$\text{Number of Bailers} = 3 \times \frac{\text{volume of water in well } (V_w)}{\text{volume of bailer } (V_b)}$$

Volume of water in well

$$V_w = \frac{3.142 \times d_w^2}{4} \times L_w$$

where:  $V_w$  = water volume in well (ft<sup>3</sup>)  
 $d_w$  = inside diameter of well (ft)  
 $L_w$  = length of water column in well (ft)

Volume of water in full bailer

$$V_b = \frac{3.142 \times d_b^2}{4} \times L_b$$

where:  $V_b$  = water volume in bailer (ft<sup>3</sup>)  
 $d_b$  = inside diameter of bailer (ft)  
 $L_b$  = length of bailer (ft)

Alternatively, the chart in Figure D-1 and be used to determine the evacuation volume.

For wells which can be evacuated to a dry state, the well will be evacuated completely, and the sample taken as soon as sufficient water for sampling is present in the well. Sample compositing, or sampling over a lengthy period by accumulating small volumes of water at different times to eventually obtain a sample of sufficient volume, will not be allowed.

Water produced during well evacuation should be contained in a suitable container and discharge to the ground surface in an area of known surface contamination. In some instances, discharge to the city sanitary sewer also might be acceptable.

### 1.5.6 Sample Extraction.

A bailer or pump will be used to extract water samples from the well. Care will be taken during insertion of sampling equipment to prevent undue disturbance of water in the well.

If a pump is used, it will be a down-hole, bladder-type pump designed for use in small diameter wells. Pumps which would subject the sample to a negative pressure or could introduce a gas into the sample will not be used for sampling. However, suction pumps might be used for well evacuation.

When a pump is used, the immersed portion of the pump or suction line will be inserted gently into the water and the sample directed into the appropriate containers, or composited in a larger container and then transferred by pumping, siphoning, or carefully pouring into the appropriate container. The discharge line will be placed within the container, such that its end is below the water level in the container, in order to prevent significant aeration of the sample.

When a bailer is used for sampling, the bailer will be constructed of stainless steel or teflon. The bailer will be lowered into the water gently to prevent splashing and extracted gently to prevent creation of an excessive vacuum in the well. The sample will be transferred directly into the appropriate container. While pouring water from a bailer, the water will be carefully poured down the inside of the sample bottle to prevent significant aeration of the sample. If a bottom-discharge bailer is used, the discharge line will be placed so that its end is below the water level in the container. Unless other instructions are given by the analytical laboratory, the sample containers should be completely filled so that no air space remains in the container.

Excess water taken during sampling is placed in a container for proper disposition at the facility wastewater treatment plant.

### 1.5.7 Quality Control Samples.

Ground-water samples will include one split sample for each sampling event. If more than 20 wells are sampled, one additional split sample will be added. The decision of which sample to split will be made by sampling personnel. The split sample will be given a designation which can not be confused with other samples to be tested.

For each sampling event, a trip blank sample (distilled water) will be shipped from the laboratory to the facility and will be returned to the laboratory for analysis. The blank will not be opened in the field.

One equipment blank sample (distilled water) will be prepared for each day of the sampling event by pouring distilled water into a cleaned, sampling bailer or by pumping distilled water through the cleaned sampling pump and then filling a sample container in the sample manner that would be used for a ground-water sample.

#### 1.5.8 On-Site Parameter Measurement.

Certain chemical and physical parameters in water can change significantly within a short time of sample acquisition. These parameters cannot be accurately measured in a laboratory located more than a few hours from the facility, and so will be measured on-site with portable equipment. These parameters are:

- o pH,
- o eH (if appropriate),
- o specific conductance, and
- o temperature.

These parameters will be measured in unfiltered, un-preserved, "fresh" water taken by the same technique as the samples taken for laboratory analyses. The measurements will be made in a clean glass container separate from those intended for laboratory analysis. The tested sample will be discarded after use. The measured values will be recorded in the sampling record.

#### 1.6 Sample Handling

##### 1.6.1 Sample Preservation.

Water samples will be properly prepared for transportation to the laboratory by refrigeration and chemical preservation (for water samples), if necessary. The laboratory providing sample containers will have added any necessary chemical preservatives to the sealed containers provided. The samples collected for uranium, plutonium and gross alpha and beta analyses will be preserved with 2% by volume concentrated HCl after being filtered.

As a general rule, and in accordance with EPA analytical procedures, water samples will not be filtered in the field, with the following exception. Samples planned for uranium, plutonium, and gross alpha and beta analyses either will be field-filtered before being acid-preserved, or, if the time between sampling and arrival at the laboratory are sufficiently short, the samples will be shipped with no chemical preservation. In the latter instance, the water samples will be filtered in the laboratory.

#### 1.6.2 Container and Labels.

Glass containers and appropriate container lids will be provided by the laboratory. The containers will be filled and container lids will be tightly closed. All sample container lids will be sealed so that it will be obvious if the seal has been tampered with or broken. The label will be firmly attached to the container side (not lid). The following information will be legibly and indelibly written on the label:

- o facility name,
- o sample identification,
- o sample type (ground water, surface water, etc.)
- o sampling date,
- o sampling time,
- o preservatives added
- o sample collector's initials.

#### 1.6.3 Sample Shipment.

In most instances, the concentration and type of compounds present in the ground-water are considered by the U.S. Department of Transportation to be non-hazardous. Thus, the following packaging and labeling requirements for the sample materials are appropriate for shipping the sample to the testing laboratory:

- o package sample so that it does not leak, spill, or vaporize from its packaging;
- o label package with
  - sample collector's name, address, and telephone number;
  - laboratory's name, address, and telephone number;
  - description of sample;

- quantity of sample; and
- date of shipment.

If the materials to be shipped are considered hazardous or if their nature is uncertain, the samples will be appropriately labelled and will be transported by sampling personnel directly to the analytical facility or will be shipped using a carrier licensed to transport hazardous materials.

To comply with packaging regulations and to take practical measures to prevent damage to expensive ground water samples, JLGA will follow packaging and shipping instructions supplied by the certified testing laboratory.

#### 1.6.4 Chain of Custody Control.

After samples have been obtained, chain of custody procedures will be followed to establish a written record concerning sample movement between the sampling site and the testing laboratory. Each shipping container will have a chain of custody form completed by the site sampling personnel packing the samples. The chain of custody form for each container will be completed in triplicate. One copy of this form will be maintained at the site, and the other two copies at the laboratory. One of the laboratory copies will become a part of the permanent record for the sample and will be returned with the sample analyses.

A copy of a sample chain of custody form is shown in Figure D-2. The record must contain the following minimum information:

- o Collector's sample number,
- o Signature of collector,
- o Date and time of collection,
- o Place and address of collection,
- o Material type,
- o Preservatives added,
- o Analyses requested,
- o Signatures involved in the chain of possession,
- o Inclusive dates of possession.

The shipping container will be sealed so that it will be obvious if the seal has been tampered with or broken. The Chain of Custody documentation will be placed inside the container so that will be immediately apparent to the laboratory personnel receiving the container but will not be damaged or lost during shipping.

### 1.7 Sampling Records


To provide complete documentation of sampling, detailed records will be maintained during sampling. These records will include the information listed below:

- o sample location (facility name);
- o sample identification (cleaning area name and sample number)
- o sample location map or detailed sketch
- o date and time of sampling;
- o sampling method;
- o field observations of
  - sample appearance,
  - sample odor
- o weather conditions;
- o sampler's identification; and
- o any other information which is significant.


Ground-water sampling information will be recorded on the Water Sampling Record as shown in Figure D-3.



### CASING VOLUME



### BAILER VOLUME



NUMBER OF FULL BAILERS  
TO EVACUATE ONE (1)  
CASING WATER COLUMN  
VOLUME

$$= \frac{WCV}{BV}$$



**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
ENGLEWOOD, COLORADO

CALCULATION OF WELL  
EVACUATION VOLUMES

Chain-of-Custody Form.

CHAIN OF CUSTODY RECORD-Environmental Samples

PROJECT				SAMPLING FIRM							SAMPLE		
Phone				Name							<input type="checkbox"/> Soil <input type="checkbox"/> Groundwater		
Address				Address							<input type="checkbox"/> Waste <input type="checkbox"/> Surface Water		
				Signature									
SAMPLE I.D.	DESCRIPTION	DATE	TIME	WEATHER		COMP	GRAB	OTHER	MAN	NO. OF CONTAINERS	ANALYSIS REQUIRED	REMARKS	
				TEMP	PREC								
RECEIVED BY (SIGNATURE)				RECEIVED TO					DATE	TIME	ADDITIONAL REMARKS		
RECEIVED BY (SIGNATURE)				RECEIVED TO					DATE	TIME			
RECEIVED BY (SIGNATURE)				RECEIVED TO					DATE	TIME			
DISPATCHED BY (SIGNATURE)		DATE	TIME	RECEIVED FOR LABORATORY (SIGNATURE)					DATE	TIME			
CARRIER				LABORATORY					LAB PO #				
ADDRESS				ADDRESS					PO # AND SAMPLE I.D. #'S MUST BE ON THE LAB INVOICE				
METHOD OF SHIPMENT									ALL ANALYSIS PERFORMED BY EPA APPROVED PROCEDURES				
									<input type="checkbox"/> Yes <input type="checkbox"/> No. explain above				

D-16

FIGURE D-2

III. SAMPLING RECORD - MONITOR WELL \_\_\_\_\_  
(number)

REASON FOR SAMPLING:  Regular Sampling;  Special Sampling

DATE AND TIME OF SAMPLING: \_\_\_\_\_, 19\_\_\_\_ a.m./p.m.

SAMPLE COLLECTED BY: \_\_\_\_\_ of \_\_\_\_\_

WEATHER: \_\_\_\_\_

DATUM FOR WATER DEPTH MEASUREMENT (Describe): \_\_\_\_\_

MONITOR WELL CONDITION:

LOCKED:  UNLOCKED

WELL NUMBER (IS - IS NOT) APPARENT

STEEL CASING CONDITION IS: \_\_\_\_\_

INNER PVC CASING CONDITION IS: \_\_\_\_\_

WATER DEPTH MEASUREMENT DATUM (IS - IS NOT) APPARENT

DEFICIENCIES CORRECTED BY SAMPLE COLLECTOR

MONITOR WELL REQUIRED REPAIR (Describe): \_\_\_\_\_

ck-Off

1  EQUIPMENT CLEANED BEFORE USE WITH \_\_\_\_\_

Items Cleaned (List): \_\_\_\_\_

2  WATER DEPTH \_\_\_\_\_ FT. BELOW DATUM

Measured with: \_\_\_\_\_

3  WATER CONDITION BEFORE WELL EVACUATION (Describe):

Appearance: \_\_\_\_\_

Odor: \_\_\_\_\_

Other Comments: \_\_\_\_\_

4  WELL EVACUATION:

Method: \_\_\_\_\_

Volume Removed: \_\_\_\_\_

Observations: Water (slightly - very) cloudy

Water level (rose - fell - no change)

Water odors: \_\_\_\_\_

Other comments: \_\_\_\_\_

III. Sampling Record - Monitor Well \_\_\_\_\_ (cont'd.)  
(number)

5  SAMPLE EXTRACTION METHOD:

- Bailer made of: \_\_\_\_\_
- Pump, type: \_\_\_\_\_
- Other, describe: \_\_\_\_\_

Sample obtained is  GRAB;  COMPOSITE SAMPLE

6  ON-SITE MEASUREMENTS:

Temp: \_\_\_\_\_ ° \_\_\_\_\_ Measured with: \_\_\_\_\_  
pH: \_\_\_\_\_ Measured with: \_\_\_\_\_  
Conductivity: \_\_\_\_\_ Measured with: \_\_\_\_\_  
Other: \_\_\_\_\_

7  SAMPLE CONTAINERS (material, number, size): \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

8  ON-SITE SAMPLE TREATMENT:

- Filtration: Method \_\_\_\_\_ Containers: \_\_\_\_\_  
Method \_\_\_\_\_ Containers: \_\_\_\_\_  
Method \_\_\_\_\_ Containers: \_\_\_\_\_
- Preservatives Added:  
Method \_\_\_\_\_ Containers: \_\_\_\_\_  
Method \_\_\_\_\_ Containers: \_\_\_\_\_  
Method \_\_\_\_\_ Containers: \_\_\_\_\_  
Method \_\_\_\_\_ Containers: \_\_\_\_\_

9  CONTAINER HANDLING:

- Container Sides Labeled
- Container Lids Taped
- Containers Placed in Ice Chest

10  OTHER COMMENTS: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

APPENDIX E  
LABORATORY ANALYSIS PROCEDURES

TABLE OF CONTENTS

Appendix E Laboratory Analysis Procedures

- 1. LABORATORY ANALYSIS PROCEDURES ..... E-3
  - 1.1 Chemical Analyses ..... E-3
    - 1.1.1 Ground Water Analyses ..... E-3
    - 1.1.2 Soil Analyses ..... E-3
  - 1.2 Physical Analyses ..... E-4
  - 1.3 Laboratory Quality Assurance ..... E-4
    - 1.3.1 QA/QC Program Components ..... E-4
    - 1.3.2 Chemical Laboratory Sample Custody Procedures .. E-5

APPENDIX E  
LABORATORY ANALYSIS PROCEDURES

1. LABORATORY ANALYSIS PROCEDURES

1.1 Chemical Analyses

1.1.1 Ground Water Analyses.

Ground-water samples will be analyzed for uranium, plutonium, gross alpha and beta, nitrate (NO<sub>3</sub>) and fluoride (F). The suggested procedures for determining gross alpha and beta, and nitrate are EPA methods 9310 and 9200, respectively, found in EPA publication SW-846, "Test Methods for Evaluating Solid Waste". Fluoride may be determined by ASTM method D-1179-72, Method A. Uranium and plutonium may be analyzed using procedures found in ASTM publication "1988 Annual Book of ASTM Standards, Section 11: Water and Environmental Technology", or by an appropriate test method provided in another accepted standard. The laboratory doing the analyses will have a QA/QC program which specifies procedures and references to be used.

1.1.2 Soil Analyses.

Soil samples will be analyzed for uranium, plutonium, nitrate, fluoride, total organic carbon (TOC), cation exchange capacity (CEC), exchangeable cation (EXC), mineralogy, matric potential, and distribution coefficient for uranium and thorium. The suggested procedures for analyzing for uranium, plutonium, nitrate and fluoride will be the same used for ground water after an appropriate extraction procedure has been applied. Total organic carbon may be analyzed by EPA procedure 9060. Cation ion exchange capacity will be analyzed by EPA procedure 9081. These procedures are found in EPA publication SW-846, "Test Methods for Evaluating Solid Waste". Exchangeable cation, mineralogy, matric potential, and distribution coefficient will be determined by an appropriate test method provided in an accepted standard.

## 1.2 Physical Analyses

Physical tests will be conducted in accordance with the current edition of ASTM Standards, American Laboratory Soils Testing and Materials, Part 19. Soil classification will be determined according to the Unified Soil Classification System (ASTM D 2487). Liquid limit will be determined by ASTM D 423, and plastic limit and plasticity index will be determined by ASTM D 424. Other tests include particle size analysis (ASTM D 422) and moisture content (ASTM D 2216). Proctor tests will be conducted according to ASTM D 698, and density will be determined by ASTM D 2049, unless the soil composition dictates use of a different method.

## 1.3 Laboratory Quality Assurance

### 1.3.1 QA/QC Program Components.

The laboratory doing the analyses will have a QA/QC program which specifies procedures and references to be used. As a minimum, the program will contain:

1. Laboratory instrument calibration procedures and schedules.
2. Specification of adherence to accepted test methods.
3. Equipment inspection and servicing schedules.
4. The regular use of duplicate or split sample analyses.
5. The regular use of standard or spiked sample analyses.
6. Operator or analyst training procedures and schedules.
7. A program of continuous review of results, procedures, and compliance with the QA/QC program.
8. Documentation of compliance with the program.

The QA/QC program will be available for review.



### 1.3.2 Chemical Laboratory Sample Custody Procedures.

A sample custodian in the chemical analysis laboratory will be assigned to receive the samples. Upon receipt of a sample, the custodian will inspect the condition of the sample and the sample seal, reconcile the information on the sample label against that on the chain of custody record, assign a laboratory number and mark this number on the sample, log in the sample in the laboratory log book, and store the sample in a secured sample storage room or cabinet until assigned to an analyst for analysis. Discrepancies between the information on the sample label and the chain of custody record and the sample analysis request sheet will be resolved before the sample is assigned for analysis.

The laboratory portion of the sample analysis request form will be completed by the laboratory personnel and include:




- o Name of person receiving the sample,
- o Laboratory sample number,
- o Date of sample receipt,
- o Sample allocation
- o Analyses to be performed.

**APPENDIX B**  
**MONITORING WELL RECORDS**

808211: 9-12-89

# SAMPLE INFORMATION

## SOIL SAMPLING

-  SPLIT-SPOON SAMPLE  
(PER ASTM D1586)
-  THIN-WALL TUBE SAMPLE  
(PER ASTM D1587)
-  CUTTINGS COLLECTED

## ROCK CORING INFORMATION










- |    |                  |  |
|----|------------------|--|
| 1  | $\frac{100}{78}$ | CORE RUN NO. AND LIMITS<br><u>RECOVERY</u><br><u>RQD</u> |
| NX |                  |  |
- CORE SIZE
- USC = UNIFIED SOIL CLASSIFICATION  
(ASTM D-2487)

\*N\* VALUE IS BLOWS PER 12 INCH PENETRATION UNLESS OTHERWISE SPECIFIED.






### SAMPLE ODORS, WHERE APPROPRIATE

- |              |                  |
|--------------|------------------|
| NO NO ODOR   | MO MODERATE ODOR |
| WO WEAK ODOR | SO STRONG ODOR   |

## GRAPHIC LOG

- |   |        |   |                  |
|---|--------|---|------------------|
|    | FILL   |   |                  |
|    | CLAY   |    | SHALE (*SH)      |
|    | SILT   |    | LIMESTONE (*LS)  |
|   | SAND   |   | SILTSTONE (*SIS) |
|  | GRAVEL |  | SANDSTONE (*SS)  |

## WELL COMPLETION DETAIL

- |   |   |
|---|---|
|  | PORTLAND CEMENT/<br>SODIUM BENTONITE<br>GROUT |
|  | SODIUM BENTONITE<br>SEAL                      |
|  | SAND OR<br>GRAVEL BACKFILL                    |
|  | SCREENED INTERVAL                             |
|  | CAP   |

### NOTE:


A BORING/WELL RECORD IS CONSIDERED REPRESENTATIVE OF SUBSURFACE CONDITIONS AT THE BORING/WELL LOCATION ON THE DATES SHOWN. IT IS NOT WARRANTED TO REPRESENT SUBSURFACE CONDITIONS AT OTHER LOCATIONS OR TIMES.

SUBSURFACE CONDITIONS SHOWN ON THESE RECORDS OR ON PROFILES DEVELOPED FROM THESE RECORDS ARE NOT WARRANTED. THEY ARE ESTIMATED BASED ON ACCEPTED SOIL ENGINEERING PRINCIPLES AND PRACTICES AND REASONABLE ENGINEERING JUDGEMENT.



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 ENGLEWOOD COLORADO

**LEGEND FOR  
 MONITORING WELL RECORDS**




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1320**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 11,266.69 N 11,755.70 E  
 Drilled By KERR-MCGEE Drilling Method AIR ROTARY  
 Logged By PFB Checked By SLW  
 Installation Date January 20, 1989 Page 1 of 2

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample	"N"	Graphic	Well Completion Detail	DEPTH (Feet)
				Interval	Value			
				Core	Rec.			
				Pin	RQD			
				Size				
	40							40
		MUDSTONE: very fine grained, sandy, occasionally conglomeratic with lithic clasts, slightly calcareous, sand content variable, 15% - 50%. Contacts are bluish gray reduction zones	MS					
	45							45
	45.5							45.5
		B.T. @ 45.5'						
	50	NOTE: description taken from well 1321 which offsets this location 12' E-NE						50
	55							55
	60							60
	65							65
	70							70
	75							75
	80							80

**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

Monitoring Well Record 1320  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 11,266.69 N 11,755.70 E  
Drilled By KERR-MCGEE Drilling Method AIR ROTARY  
Logged By PFB Checked By SLW  
Installation Date January 20, 1989 Page 2 of 2




JAMES L. GRANT & ASSOCIATES  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

Monitoring Well Record 1321  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 11,261.76 N 11,743.26 E  
 Drilled By KERR-MCGEE Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date January 25, 1989 Page 1 of 4

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Run size	N Value Rec RQD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	40	MUDSTONE: very fine grained, sandy, occasionally conglomeratic with lithic clasts, slightly calcareous, sand content variable, 15 - 50%. Contacts are bluish gray reduction zones	MS	Run 5 NX				40
	45				100% 100			45
	46.5	SANDSTONE: brownish red, very fine to fine grained, silty, grains sub-rounded, well sorted. Moderately cemented. Silt content variable, 5 - 30%						
	50	... very clean and porous 51' to 60'		Run 6 NX			Portland Cement/ Sodium Bentonite Grout	50
	55		SS		96% 95		2" I.D. SCH 40 PVC Flush-threaded	55
	60	... cross bedded 60' to 62.5'		Run 7 NX				60
	65	... becomes conglomeratic at 62.5' to 64.7' with mudstone clasts. Matrix 50% sand, 50% silt, irregular vuggy porosity with some vugs lined with calcite, gypsum. Patches of $M_n O_2$ (?)			100% 100			65
	70	... becomes interbedded with mudstone at 70.5' to 71.5'		Run 8 NX				70
	71.5	MUDSTONE: very fine grained, sandy. Sand up to 30%, conglomeratic at 71.5' to 72.0'. Occasional reduction spots, sharp bottom contact.	MS		100% 92			75
	75							
	76.8	SANDSTONE: very fine to fine grained, silty, well sorted, rounded.	SS					
	79.5							
	80	see pg. 3	MS					80

JAMES L. GRANT & ASSOCIATES  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO


Monitoring Well Record 1321  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 11,261.76 N 11,743.26 E  
Drilled By KERR-MCGEE Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date January 25, 1989 Page 2 of 4



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO


**Monitoring Well Record 1321**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 11,261.76 N 11,743.26 E  
 Drilled By KERR-MCGEE Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date January 25, 1989 Page 3 of 4





**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1321**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 11,261.76 N 11,743.26 E  
 Drilled By KERR-MCGEE Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date January 25, 1989 Page 4 of 4




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1322**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,386.13 N 10,238.93 E  
 Drilled By KERR-MCGEE Drilling Method AIR ROTARY  
 Logged By PFB Checked By SLW  
 Installation Date January 28, 1989

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Top Size	N Value Rec. RQD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	40	Same as 32.6' to 40.0'	MS					40
	42.1	SANDSTONE: brownish red, fine grained with 30% to 40% silt content, grains well sorted, sub-rounded to rounded  ... becomes clean below 46.5'  ... thin mudstone interbeds at 48.2' to boring termination depth	SS				Sodium Bentonite Pellet Backfill	45
	45							
	49.0	B.T. @ 49.0'						49.0'
	50							50
	55	NOTE: descriptions are taken from Well 1323, which is located 14' West						55
	60							60
	65							65
	70							70
	75							75
	80							80

**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

**Monitoring Well Record 1322**  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 10,386.13 N 10,238.93 E  
Drilled By KERR-MCGEE Drilling Method AIR ROTARY  
Logged By PFB Checked By SLW  
Installation Date January 26, 1989 Page 2 of 2



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1323**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,387.37 N 10,224.06 E  
 Drilled By KERR-MCGEE Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date February 14, 1989 Page 1 of 4

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Run size	N Value Rec. RQD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	40	Same as 32.6' to 40.0'						40
	42.1	SANDSTONE: brownish red, fine grained with 30% to 40% silt content, grains well sorted, sub-rounded to rounded  ... becomes clean below 46.5'  ... thin mudstone interbeds 48.2' to 50.0'	MS	Run 5 NX				
	45		SS		100% 100			
	50	MUDSTONE: sandy, very fine grained with occasional reduction spots and sand clasts						
	50.3		MS	Run 6 NX				
	55				100% 100		← Portland Cement/ Sodium Bentonite Grout	
	57.9	SANDSTONE: fine grained, silty, well sorted, subrounded to rounded, weakly to moderately cemented, conglomeric with sandstone, mudstone clasts and vug-like porosity 60.8' to 61.1' ... sandstone becomes mostly clean below 61.1'						
	60		SS	Run 7 NX				
	65	... becomes crossbedded below 70.0' with occasional thin, shaley laminations			100% 100		← 2" I.D. SCH 40 PVC Flush-threaded	
	70							
	75	... thin mudstone bed at 75.5' to 76.6' with gray laminae			97% 97			
	80							


JAMES L. GRANT & ASSOCIATES  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

Monitoring Well Record 1323  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 10,387.37 N 10,224.06 E  
Drilled By KERR-MCGEE Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date February 14, 1989 Page 2 of 4

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Run Size	N Value Rec. RQD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	80	SANDSTONE: fine to very fine grained, silty, well sorted, sub-rounded to rounded, moderately cemented. Occasional patches of yellow-green minerals and shaley laminae	SS	Run 9 NX				80
	83.8	MUDSTONE: sandy, very fine grained, reddish brown, occasional reduction spots ... conglomeratic at 83.8' to 84.3'			97% 95			85
	85		MS					
	90	... becomes very sandy below 90.0'		Run 10 NX			Portland Cement/ Sodium Bentonite Grout	90
	94.4	SANDSTONE: fine to very fine grained, silty, moderately cemented; ... becomes fairly clean below 96.0'			100% 100		2" I.D. SCH 40 PVC Flush-threaded	95
	95							
	100		SS	Run 11 NX				100
	105	... conglomeratic at 105.8' to 106.0'			100% 100			105
	110	... becomes crossbedded below 110.0'		Run 12 NX				110
	112.6	MUDSTONE: sandy, very fine grained, occasional gray reduction spots, occasionally conglomeratic	MS		99% 99		Sodium Bentonite Pellet Seal	115
	115						Sand	
	117.9	SANDSTONE: fine to very fine grained, silty with horizontal laminations, moderately cemented	SS				2" I.D. SCH 40 PVC 0.020" Slotted Screen	120
	120							


**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

**Monitoring Well Record 1323**  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 10,387.37 N 10,224.06 E  
Drilled By KERR-MCGEE Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date February 14, 1989 Page 3 of 4



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO


**Monitoring Well Record 1323**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,387.37 N 10,224.06 E  
 Drilled By KERR-MCGEE Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date February 14, 1989 Page 4 of 4



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO


**Monitoring Well Record 1324**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,972.36 N 12,075.48 E  
 Drilled By KERR-MCGEE Drilling Method AIR ROTARY  
 Logged By PFB Checked By SLW  
 Installation Date February 8, 1989 Page 1 of 1






**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1325**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,494.65 N 11,951.47 E  
 Drilled By KERR-MCGEE Drilling Method AIR ROTARY  
 Logged By PFB Checked By SLW  
 Installation Date February 9, 1989 Page 1 of 2



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1325**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,494.65 N 11,951.47 E  
 Drilled By KERR-MCGEE Drilling Method AIR ROTARY  
 Logged By PFB Checked By SLW  
 Installation Date February 9, 1989 Page 2 of 2




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1326**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,112.93 N 10,719.85 E  
 Drilled By KERR-MCGEE Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date February 16, 1989 Page 1 of 2

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Run Size	% Value Rec. RQD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	40	MUDSTONE: sandy, very fine grained, with thin reduction laminae and spots		Run 5 NX				40
	45		MS		100% 100			45
	46.5	SANDSTONE: fine to very fine grained, silty						45.1'
	50.0	B.T. @ 50.0'	SS				50.0'	50
	55							55
	60							60
	65							65
	70							70
	75							75
	80							80

**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

**Monitoring Well Record 1326**  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 10,112.93 N 10,719.85 E  
Drilled By KERR-MCGEE Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date February 16, 1989 Page 2 of 2




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1327 A**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,103.73 N 10,100.10 E  
 Drilled By KERR-MCGEE Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 1, 1989

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample	"N	Graphic	Well Completion Detail	DEPTH (Feet)
				Interval	Value			
				Core	Rec.			
				Size	RQD			
	40	SANDSTONE: brownish red, fine grained, well sorted, subrounded to rounded, clean. Patchy yellow-green minerals appearing below 41.2'. Conglomeratic at 42.1' to 43.2' and 44.8' to 46.9' with lithic clasts, vug-like porosity, calcite and gypsum cementing clasts lining vugs. Crossbedded at 43.2' to 44.8' with abundant gypsum ... becomes silty below 46.9'		Run 6 NX				40
	45		SS	100%	100			45
	50.0		B.T. @ 50.0'					50.0'
	55							55
	60							60
	65							65
	70							70
	75							75
	80							80

**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

**Monitoring Well Record 1327 A**  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 10,103.73 N 10,100.10 E  
Drilled By KERR-MCGEE Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date March 1, 1989 Page 2 of 2



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO


**Monitoring Well Record 1327 B**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,090.43 N 10,100.10 E  
 Drilled By KERR-MCGEE Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 20, 1989

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Log Size	N Value Rec. RQD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	40	<p>SANDSTONE: brownish red, fine grained, well sorted, subrounded to rounded, clean. Patchy yellow-green minerals appearing below 41.2'. Conglomeratic at 42.1' to 43.2' and 44.8' to 46.9' with lithic clasts, vug-like porosity, calcite and gypsum cementing clasts lining vugs. Crossbedded at 43.2' to 44.8' with abundant gypsum ... becomes silty below 46.9'</p>	SS					40
	45							45
	50							50
	53.0							53.0
	55	B.T. @ 53.0'						55
	60							60
	65							65
	70							70
	75							75
	80							80

**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1327 B**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,090.43 N 10,100.10 E  
 Drilled By KERR-MCGEE Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 20, 1989 Page 2 of 2





**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1328**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 9830.36 N 10,411.70 E  
 Drilled By WINNEK, INC. Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 9, 1989 Page 1 of 4

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Top Size	7" Value Rec. RQD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	40							40
	41.0	Same as 27.5' to 40.0'	MS	Run 3 NX				
	45	SANDSTONE: Brownish-red, fine grained, well sorted, subrounded- rounded, silty to 42.4, then clean. Weakly cemented. Cross bedded to 53' ... Thin mudstone layers 44.3' to 44.4' and 46.8' to 47'		Run 4 NX	97% 97			45
	50		SS				Portland Cement/ Sodium Bentonite Grout	50
	55	... becomes hard, medium grained, slightly conglomeratic 56.4' to 57.7' with calcite, gypsum cement		Run 5 NX	75% 75		2" I.D. SCH 40 PVC Flush-threaded	55
	57.7	MUDSTONE: sandy, very fine to fine grained with reduction spots	MS					60
	61.0	SANDSTONE: brownish-red, fine grained, well sorted, rounded, moderately cemented, clean to slightly silty		Run 6 NX				65
	65	... mudstone layer 65.1' to 67.0'			79% 79			70
	70		SS					75
	75			Run 7 NX	79% 79			80

**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

**Monitoring Well Record 1328**  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 9830.36 N 10,411.70 E  
Drilled By WNNEK, INC. Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date March 9, 1989 Page 2 of 4


ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Pin Size	"N" Value Rec. ROD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	80	SANDSTONE: fine grained, well sorted, rounded, slightly silty ... becomes fine to medium grained	SS	Run 8 NX				80
	85	81' to 84.1', well sorted, subangular to subrounded, moderate to well cemented with calcite and gypsum, vug-like porosity, salt and pepper with dark minerals and bitumen						85
	86.0	... becomes siltier, finer grained, more weakly cemented below 84.1'			95% 95			
	90	MUDSTONE: reddish-brown, slightly sandy	MS					90
	91.0	SANDSTONE: fine grained, silty, well sorted, rounded		Run 9 NX				
	95	... Hard, well cemented layer 94.5' to 95.4' ... Mudstone layer 95.4' to 96.0'	SS		49% 49			95
	100							100
	103.4			Run 10 NX				
	105	MUDSTONE: reddish-brown, slightly sandy	MS		76% 75			105
	107.7	SANDSTONE: brownish-red, fine grained, well sorted, rounded to subrounded, fairly clean.	SS					110
	110							110
	115			Run 11 NX				
	115.5	MUDSTONE: reddish-brown, slightly sandy	MS		90% 90			115
	117.8	SANDSTONE: brownish-red, fine grained, well sorted, rounded to subrounded, fairly clean.	SS					120
	120							120

2" I.D. SCH 40 PVC  
Flush-threaded

Portland Cement/  
Sodium Bentonite  
Grout


**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

**Monitoring Well Record 1328**  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 9830.36 N 10,411.70 E  
Drilled By WINNEK, INC. Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date March 9, 1989



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1328**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 9830.36 N 10,411.70 E  
 Drilled By WINNEK, INC. Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 9, 1989




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1329**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 9835.39 N 10,405.36 E  
 Drilled By WINNEK, INC. Drilling Method WET ROTARY  
 Logged By PFB Checked By SLW  
 Installation Date March 10, 1989

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Type Size	"N" Value Rec. ROD	Graphic Log	Well Completion Detail	DEPTH (Feet)	
	40							40	
	41.0	Same as 27.5' to 40.0'	MS				<p>2" I.D. SCH 40 PVC 0.020" Slotted Screen</p> <p>Sand</p> <p>Cap</p>		
	45	SANDSTONE: brownish-red, fine grained, well sorted, subrounded to rounded, silty to 42.4', then clean. Weakly cemented. Cross bedded to B.T. depth Thin mudstone layers 44.3' to 44.4' and 46.8' to 47'	SS					45.0'	45
	48.0							47.8'	48.0'
	50	B.T. @ 48.0'						50	
	55							55	
	60	NOTE: Descriptions taken from Well 1328 located 8' NW of this location.						60	
	65							65	
	70							70	
	75							75	
	80							80	

**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

**Monitoring Well Record 1329**  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 9835.39 N 10,405.36 E  
Drilled By WINNEK, INC. Drilling Method WET ROTARY  
Logged By PFB Checked By SLW  
Installation Date March 10, 1989 Page 2 of 2



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO


**Monitoring Well Record 1330**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 9657.06 N 10,231.32 E  
 Drilled By WINNEK, INC. Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 10, 1989 Page 1 of 2

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Core run size	Rec. ROD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	40	SANDSTONE: fine grained, well sorted, subrounded, weakly to moderately cemented. Thin mudstone layer 40.7' to 40.9'	SS	Run 6 NX	76% 76			40
	44.5							44.5'
	45	B.T. @ 44.5'						45
	50							50
	55							55
	60							60
	65							65
	70							70
	75							75
	80							80

**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO


**Monitoring Well Record 1330**  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 9657.06 N 10,231.32 E  
Drilled By WINNEK, INC. Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date March 10, 1989





**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1331**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,751.13 N 10,202.71 E  
 Drilled By WINNEK, INC. Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 11, 1988 Page 1 of 1




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1332**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,686.36 N 10,457.35 E  
 Drilled By WINNEK, INC. Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 13, 1989


ELEV. (Feet)	DEPTH (Feet)	Description	usc	Core run size	Rec. RQD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	40	MUDSTONE: reddish-brown, sandy, very fine grained, weakly cemented. Reduction zone 44.0' to 44.4'	MS	Run 7 NX				40
	44.4	SANDSTONE: brownish-red, fine grained, well sorted, subrounded to rounded, weak to moderate cement, slightly calcareous, silty, occasional cross bedded intervals		Run 8 NX	64%	[Graphic Log]	[Well Completion Detail]	45
	45				64			
	50				44%			
	50				44			
	55	... conglomeratic with sandstone, mudstone clasts, patchy yellow-green minerals and vug-like porosity 63.5' to 64.1', 65.8' to 66.8', 68.4' to 69.0'	SS	Run 9 NX	50%	[Graphic Log]	[Well Completion Detail]	55
	55				50			
	60				100%			
	60	... conglomeratic with sandstone, mudstone clasts, patchy yellow-green minerals and vug-like porosity 63.5' to 64.1', 65.8' to 66.8', 68.4' to 69.0'		Run 10 NX	100%	[Graphic Log]	[Well Completion Detail]	60
	60				100			
	65				100%			
	65	... conglomeratic with sandstone, mudstone clasts, patchy yellow-green minerals and vug-like porosity 63.5' to 64.1', 65.8' to 66.8', 68.4' to 69.0'		Run 11 NX	100%	[Graphic Log]	[Well Completion Detail]	65
	65				100			
	69.7				96%			
	70	MUDSTONE: reddish-brown, sandy, very fine grained, weakly cemented.		Run 12 NX	96	[Graphic Log]	[Well Completion Detail]	70
	75	..				[Graphic Log]	[Well Completion Detail]	75
	80	... mudstone conglomerate 77.8' to 78.6'		Run 13 NX		[Graphic Log]	[Well Completion Detail]	80

<p><b>JAMES L. GRANT &amp; ASSOCIATES</b>  geotechnical engineering • management •  computer science  DENVER, COLORADO</p>	<p><b>Monitoring Well Record 1332</b>  Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  Coordinates 10,686.36 N 10,457.35 E  Drilled By WINNEK, INC. Drilling Method CORE  Logged By PFB Checked By SLW  Installation Date March 13, 1989</p>
--	--




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO

**Monitoring Well Record 1332**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,686.36 N 10,457.35 E  
 Drilled By WINNEK, INC. Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 13, 1989 Page 3 of 4

ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample Interval Core Run Size	"N" Value Rec. RCD	Graphic Log	Well Completion Detail	DEPTH (Feet)
	120							120
	121.0	Same as 106.8' to 120.0'	SS	Run 17				120
	123.0	MUDSTONE: sandy, very fine grain- ed	MS		88% 88		123.0' 	120
		B.T. @ 123.0'						
	125							125
	130							130
	135							135
	140							140
	145							145
	150							150
	155							155
	160							160

**JAMES L. GRANT & ASSOCIATES**  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

Monitoring Well Record 1332  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 10,686.35 N 10,457.35 E  
Drilled By WINNEK, INC. Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date March 13, 1989 Page 4 of 4



JAMES L. GRANT & ASSOCIATES

geotechnical engineering • management •  
computer science

DENVER, COLORADO

Monitoring Well Record 1333

Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA


Coordinates 10,662.97 N 10,442.73 E

Drilled By WINNEK, INC. Drilling Method WET ROTARY

Logged By PFB Checked By SLW


Installation Date March 12 1989

Page 1 of 1



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO



**Monitoring Well Record 1334**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,688.14 N 10,776.31 E  
 Drilled By WINNEK, INC. Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 12, 1989 Page 1 of 1



**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO


**Monitoring Well Record 1335**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 10,944.05 N 11,758.09 E  
 Drilled By WINNEK, INC. Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 13, 1989 Page 1 of 2



ELEV. (Feet)	DEPTH (Feet)	Description	USC	Sample	"N"	Graphic	Well Completion Detail	DEPTH (Feet)
				Interval	Value			
				Core	Rec.	Log		
				Run	RQD			
				4	100%			
				NX	100			
	40	SANDSTONE: fine to medium grained, well sorted, subrounded to rounded, crossbedded, weakly cemented	SS					40
	43.0			42.8'	43.0'			
		B.T. @ 43.0'						
	45							45
	50							50
	55							55
	60							60
	65							65
	70							70
	75							75
	80							80

JAMES L. GRANT & ASSOCIATES  
geotechnical engineering • management •  
computer science  
DENVER, COLORADO

Monitoring Well Record 1335  
Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
Coordinates 10,944.05 N 11,758.09 E  
Drilled By WINNEK, INC. Drilling Method CORE  
Logged By PFB Checked By SLW  
Installation Date March 13, 1989 Page 2 of 2




**JAMES L. GRANT & ASSOCIATES**  
 geotechnical engineering • management •  
 computer science  
 DENVER, COLORADO


**Monitoring Well Record 1336**  
 Location CIMARRON FACILITY, LOGAN COUNTY, OKLAHOMA  
 Coordinates 11,738.39 N 11,722.31 E  
 Drilled By WINNEK, INC. Drilling Method CORE  
 Logged By PFB Checked By SLW  
 Installation Date March 14, 1989 Page 1 of 1

**APPENDIX C**  
**SLUG TEST DATA**


808211: 9-12-89

\*\*\*\*\* HVORSLEV METHOD  
WELL 1320  
RISING HEAD TEST







WELL 1321  
RISING HEAD TEST




\*\*\*\*\* HVORSLEV METHOD  
WELL 1321  
RISING HEAD TEST









WELL 1322  
RISING HEAD TEST







WELL 1323  
RISING HEAD TEST



\*\*\*\*\* HVORSLEV METHOD  
WELL 1323  
RISING HEAD TEST



Well # 1323  
 RISING HEAD TEST



$$T = \frac{1.0 \left(\frac{1}{12}\right)^2}{900 \text{ sec}} = 7.72 \times 10^{-6} \text{ ft}^2/\text{sec}$$


$$T = 0.67 \text{ ft}^2/\text{day}$$

$$\text{let } d = 17'$$


$$K = 1.39 \times 10^{-5} \text{ cm/sec}$$

$$t = 900 \text{ sec.}$$


WEL 324  
RISING HEAD TEST



\*\*\*\*\* HVORSLEV METHOD  
WELL 1324  
FALLING HEAD TEST




WELL 1325  
RISING HEAD TEST







\*\*\*\*\* HVORSLEV METHOD  
WELL 1325  
RISING HEAD TEST




WELL 1326  
RISING HEAD TEST  
24"x1" SLUG




WELL 1326  
58"x1.67" SLUG  
RISING HEAD TEST




\*\*\*\*\* HVORSLEV METHOD  
WELL 1326  
RISING HEAD TEST  
58" x 1.67" SLUG




\*\*\*\*\* HVORSLEV METHOD  
WELL 1326  
RISING HEAD TEST  
24" x 1" SMC




WELL 1327-B  
RISING HEAD TEST



WELL 1327-B  
FALLING HEAD TEST




\*\*\*\*\* HVORSLEV METHOD  
WELL 1327-B  
RISING HEAD TEST






WELL 1328  
RISING HEAD TEST





WELL 1328  
FALLING HEAD TEST




$t_1 = 0.39$      $y_1 = 1$   
 $t_2 = 2.22$      $y_2 = -1.55$

\*\*\*\*\* HVORSLEV METHOD  
WELL 1328  
RISING HEAD TEST







WELL 1329  
RISING HEAD TEST  
1st Attempt




WELL 1329  
RISING HEAD TEST  
2nd ATTEMPT



WELL 1329  
PUMPING HEAD TEST  
1st ATTEMPT




WELL 1329  
FALLING HEAD TEST  
2nd ATTEMPT







\*\*\*\*\* HVORSLEV METHOD  
WELL 1329  
RISING HEAD TEST




WELL 1330  
RISING HEAD TEST




WELL 1330  
FALLING HEAD TEST




\*\*\*\*\* HVORSLEV METHOD  
WELL 1330  
RISING HEAD TEST







\*\*\*\*\* BOUWER AND RICE METHOD  
WELL NO. 1331  
RISING HEAD TEST

$t_0 = 0.00$   $y_0 = 1.56'$   
 $t_1 = 1.44$   $y_1 = 0.00$




WELL 1331  
FALLING HEAD TEST







WELL 1332  
RISING HEAD TEST



WELL 1332  
FALLING HEAD TEST

Ln HEAD CHANGE (feet)


1.00  
0.50  
0.00  
-0.50  
-1.00  
-1.50  
-2.00


ELAPSED TIME (minutes)

0.00 0.50 1.00 1.50 2.00 2.50 3.00


$(t_1, y_1)$

$(t_2, y_2)$






WELL 1333  
RISING HEAD TEST




WELL 1333  
FALLING HEAD TEST




$t_1 = .01$      $y_1 = 1.45$   
 $t_2 = 2.14$      $y_2 = 0.55$


WELL 1334  
RISING HEAD TEST



WELL 1334  
FALLING HEAD TEST




\*\*\*\*\* HVORSLEV METHOD  
WELL 1334  
RISING HEAD TEST







\*\*\*\*\* HVORSLEY METHOD  
WELL 1334  
FALLING HEAD TEST



WELL 1335  
FALLING HEAD TEST




WELL 1335  
RISING HEAD TEST



Curve 1  $t_0 = 0.00$   $y_0 = 1.56$   
 $t_1 = 4.00$   $y_1 = 0.17$


Curve 2  $t_2 = 0.01$   $y_2 = 1.73$   
 $t_3 = 4.00$   $y_3 = 0.05$

Well 1335  
Falling Head Test




WELL 1336  
RISER HEAD TEST

75"x1" SLUG




WELL 1336  
RING HEAD TEST

50"x1" SLUG




WELL 1336  
PULLING HEAD TEST

50"x1" SLUG



\*\*\*\*\* HVORSLEV METHOD  
WELL 1336  
RISING HEAD TEST





**APPENDIX D**  
**GROUND-WATER ANALYSES**

808211: 9-12-89


APE/PROJECT NUMBER: 84007

DATE RECEIVED: 3-22-89

SAMPLE ID: 932941

COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine



SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1311

SAMPLE DESCRIPTION: Ground Water

NOTES: 1607-LRW-10P81,82

APR 24 1989

F	<0.20 mg/l	Ra-228	0.082+-0.19 pCi/l
NO3(N)	66.0 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	<10 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	23 pCi/l	U238	0.77+-0.11 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	0.99+-0.13 pCi/l
Ra-226	0.18+-0.21 pCi/l	U-235	0.018+-0.018 pCi/l

All constituents soluble unless otherwise specified:

i=insoluble constituent, t=total constituent

\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\* APPROVED: D. Keck 4/17/89 DRG Qash


\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_

\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932942  
COMPLETION DATE: 4-17-89



LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1312  
SAMPLE DESCRIPTION: Ground Water

APR 24 1989

NOTES: NBR same as 932941

F	50 mg/l	Ra-228	1.38+-0.54 pCi/l
NO3(N)	1020 mg/l	Th-228	0.007+-0.005 pCi/l
Alpha	59 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	2370 pCi/l	U238	15.3+-1.9 pCi/l
Pu-239	0.003+-0.002 pCi/l	U-234	41.6+-3.2 pCi/l
Ra-226	0.45+-0.34 pCi/l	U-235	1.23+-0.55 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 4/17/89 JRC [Signature] \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932943  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine



SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1313  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932941

APR 24 1989

F	140 mg/l	Ra-228	2.34+-0.91 pCi/l
NO3(N)	720 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	260 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	2200 pCi/l	U238	30+-2 pCi/l
Pu-239	0.003+-0.002 pCi/l	U-234	84+-4 pCi/l
Ra-226	0.49+-0.49 pCi/l	U-235	2.7+-0.7 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\* APPROVED: D. Keck 4/17/89 J.R.G. [Signature] \*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932944  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

RECEIVED

SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1314  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932941

APR 24 1989

F	<0.20 mg/l	Ra-228	0+-0.27 pCi/l
NO3(N)	0.36 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	<10 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	0.31+-0.08 pCi/l
Pu-239	0.003+-0.002 pCi/l	U-234	0.77+-0.12 pCi/l
Ra-226	0.11+-0.23 pCi/l	U-235	0.039+-0.027 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\* APPROVED: D. Keck 4/17/89 *[Signature]* \*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

17-Apr-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932945  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

RECEIVED  
JCA

SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1315  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932941

APR 24 1989

F	0.22 mg/l	Ra-228	1.61+-0.77 pCi/l
NO3(N)	13 mg/l	Th-228	0.013+-0.007 pCi/l
Alpha	6440 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	660 pCi/l	U238	1550+-190 pCi/l
Pu-239	0.003+-0.002 pCi/l	U-234	3570+-285 pCi/l
Ra-226	0+-0.22 pCi/l	U-235	110+-51 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\* APPROVED: D. Keck J.R.Q. Dask AW \*

\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*

\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932946  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine



SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1316  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932941

APR 24 1989

F	<0.20 mg/l	Ra-228	0.47+-0.58 pCi/l
NO3(N)	16 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	331 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	100 pCi/l	U238	67+-10 pCi/l
Pu-239	0.003+-0.002 pCi/l	U-234	210+-17 pCi/l
Ra-226	0+-0.30 pCi/l	U-235	10.0+-3.8 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\* APPROVED: D. Keck 4/17/89 *[Signature]* \*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932926  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1320  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	0.42 mg/l	Ra-228	0.25+-0.30 pCi/l
NO3(N)	20 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	<10 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	3.1+-0.28 pCi/l
Pu-239	0.005+-0.003 pCi/l	U-234	5.58+-0.57 pCi/l
Ra-226	0.15+-0.22 pCi/l	U-235	0.17+_0.10 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \* APPROVED:           JAN 5-8-89 JRC [Signature]           \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.



AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932928  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1321  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	<0.2 mg/l	Ra-228	0.021+-0.14 pCi/l
NO3(N)	9.1 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	18 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	26 pCi/l	U238	2.75+-0.4 pCi/l
Pu-239	0.004+-0.003 pCi/l	U-234	8.1+-0.7 pCi/l
Ra-226	0+-0.14 pCi/l	U-235	0.12+-0.08 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric  
analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED: John 5-8-89 [Signature] \*  
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

APE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932936  
COMPLETION DATE: 5-08-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1322  
SAMPLE DESCRIPTION: Ground Water

NOTES: 1688-JAH-22P33  
1607-LRW-10P81,82

F	<0.20 mg/l	Ra-226	0.22+-0.29 pCi/l
NO3(N)	9.2 mg/l	Ra-228	0.038+-0.30 pCi/l
TOC	<10 mg/l	Th-228	0.004+-0.004 pCi/l
TOX	77 ug/l	Th-232	0.004+-0.004 pCi/l
Alpha	15 pCi/l	U238	3.9+-0.65 pCi/l
Beta	<20 pCi/l	U-234	8.2+-0.09 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-235	0.13+-0.011 pCi/l

All constituents soluble unless otherwise specified:

i=insoluble constituent, t=total constituent

\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\* APPROVED: D. Keck et al / [Signature] \*

\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*

\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division

Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are scheduled for disposal after 30 days.

If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932938  
COMPLETION DATE: 0-00-00

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1323  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932936

F	<0.20 mg/l	Ra-228	0.012+-0.24 pCi/l
NO3(N)	1.7 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	51 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	9.8+-1.0 pCi/l
Pu-239	0.004+-0.003 pCi/l	U-234	17+-1.3 pCi/l
Ra-226	0.046+-0.20 pCi/l	U-235	0.42+-0.21 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \* APPROVED: JRF JCH 5-8-89 DSK \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932927  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1324  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	0.26 mg/l	Ra-228	0.059+-0.27 pCi/l
NO3(N)	18 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	<10 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	0.20+-0.07 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	0.44+-0.10 pCi/l
Ra-226	0+-0.27 pCi/l	U-235	0.022+-0.022 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \* APPROVED:           JCH 5-8-89 [Signature]           \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

10-Aug-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967473  
11:46 a.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ 1324A  
SAMPLE DESCRIPTION: Water

NOTES: Results needed by 6-21-89  
1665-ADP-1P173;1663-MTM-6P116  
1559-DAW-26P190

Ca	71.5 mg/l	Cl	3.8 mg/l
Mg	37.2 mg/l	HCO3	394 mg/l
F	0.6 mg/l	NO3(N)	20 mg/l
K	0.36 mg/l	SO4	72 mg/l
Na	40.1 mg/l		

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: D. Kerr 6/10/89 LSec. 10 Aug 89 \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

9-Aug-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932922  
COMPLETION DATE: 5-08-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1325  
SAMPLE DESCRIPTION: Ground Water

NOTES: 1688-JAH-22P33  
1607-LRW-10P81,82

F	0.35 mg/l	Ra-226	0.086+-0.26 pCi/l
NO3(N)	13 mg/l	Ra-228	0.26+-0.26 pCi/l
TOC	12/12 mg/l	Th-228	0.004+-0.004 pCi/l
TOX	130 ug/l	Th-232	0.004+-0.004 pCi/l
Alpha	<10 pCi/l	U238	1.00+-0.12 pCi/l
Beta	<20 pCi/l	U-234	1.49+-0.015 pCi/l
Pu-239	0.006+-0.003 pCi/l	U-235	0.046+-0.026 pCi/l

All constituents soluble unless otherwise specified:

i=insoluble constituent, t=total constituent

\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\* APPROVED: D. Keck 8/9/89 DKK

\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_

\* \_\_\_\_\_

\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932923  
COMPLETION DATE: 5-08-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1326  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	<0.20 mg/l	Ra-226	0+-0.16 pCi/l
NO3(N)	14 mg/l	Ra-228	0.15+-0.20 pCi/l
TOC	<10 mg/l	Th-228	0.008+-0.005 pCi/l
TOX	98 ug/l	Th-232	0.004+-0.004 pCi/l
Alpha	14 pCi/l	U238	1.48+-0.15 pCi/l
Beta	25 pCi/l	U-234	4.43+-0.25 pCi/l
Pu-239	0.002+-0.001 pCi/l	U-235	0.058+-0.029 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\*  
\* APPROVED: D. Keck 8/9/89 DSK \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

8-May-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932934  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1327  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	0.20 mg/l	Ra-228	0.009+-0.10 pCi/l
NO3(N)	8.2 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	<10 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	1.52+-0.20 pCi/l
Pu-239	0.006+-0.003 pCi/l	U-234	2.8+-0.28 pCi/l
Ra-226	0.052+-0.082 pCi/l	U-235	0.14+-0.06 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric  
analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: JCH 5-8-89 [Signature] \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.



8-May-198

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932939  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1328  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932936

F	<0.2 mg/l	Ra-228	0+-0.19 pCi/l
NO3(N)	2.2 mg/l	Th-228	0.011+-0.007 pCi/l
Alpha	29 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	9+-0.9 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	18+-1.3 pCi/l
Ra-226	0.054+-0.13 pCi/l	U-235	0.66+-0.25 pCi/l

All constituents soluble unless otherwise specified:  
 i=insoluble constituent, t=total constituent  
 \* Gross Alpha greater than 15 pCi/l. Radiometric  
 analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED: JRD JMH 5-8-89 [Signature] \*  
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
 \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
 Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
 This/these samples are scheduled for disposal after 30 days.  
 If you want the samples retained or returned, please advise.

9-Aug-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932937  
COMPLETION DATE: 5-08-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1329  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932936

F	<0.20 mg/l	Ra-226	0.030+-0.13 pCi/l
NO3(N)	0.40 mg/l	Ra-228	0+-0.17 pCi/l
TOC	<10 mg/l	Th-228	0.008+-0.006 pCi/l
TOX	62 ug/l	Th-232	0.004+-0.004 pCi/l
Alpha	12 pCi/l	U238	2.04+-0.18 pCi/l
Beta	<20 pCi/l	U-234	5.3+-0.29 pCi/l
Pu-239	0.006+-0.003 pCi/l	U-235	0.093+-0.037 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\*  
\* APPROVED: D. Keck / J. Stauter \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932935  
COMPLETION DATE: 4-17-89

17-Apr-1989

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1330  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	<0.2 mg/l	Ra-228	0+-0.31 pCi/l
NO3(N)	172 mg/l	Th-228	0.008+-0.008 pCi/l
Alpha	16 pCi/l	Th-232	0.008+-0.008 pCi/l
Beta	62 pCi/l	U238	2.4+-0.22 pCi/l
Pu-239	0.006+-0.003 pCi/l	U-234	5.17+-0.33 pCi/l
Ra-226	0.088+-0.22 pCi/l	U-235	0.10+-0.05 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric  
analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: \_\_\_\_\_ \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KOCK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

8-May-1987

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932929  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1331  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	<0.2 mg/l	Ra-228	0+-0.23 pCi/l
NO3(N)	5.7 mg/l	Th-228	0.008+-0.005 pCi/l
Alpha	190 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	23 pCi/l	U238	35+-6.1 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	126+-12 pCi/l
Ra-226	0+-0.23 pCi/l	U-235	3.7+-1.8 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED:           galt 5-8-89 JRG Dask                    \*  
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_\*  
 \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932932  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1332  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	1.3 mg/l	Ra-228	1.00+-0.46 pCi/l
NO3(N)	3.4 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	23 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	6.4+-0.6 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	13.9+-0.9 pCi/l
Ra-226	0.18+-0.36 pCi/l	U-235	0.12+-0.08 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric  
analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED: JOH 5-8-89 [Signature] \*  
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932930  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1333  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	<0.20 mg/l	Ra-228	0.12+-0.32 pCi/l
NO3(N)	6.3 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	47 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	6.2+-0.5 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	18+-0.6 pCi/l
Ra-226	0.12+-0.39 pCi/l	U-235	0.71+-0.12 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: JCF 5-8-89 JCF \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

8-May-198

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932933  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1334  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	0.26 mg/l	Ra-228	0.20+-0.14 pCi/l
NO3(N)	6.1 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	30 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	5.0+-0.33 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	13.2+-0.5 pCi/l
Ra-226	0.029+-0.13 pCi/l	U-235	0.23+-0.07 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: JCH 5-8-89 [Signature] \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\*  
\* \_\_\_\_\_ \*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932924  
COMPLETION DATE: 5-60-98

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1335  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	0.24/0.20 mg/l	Ra-228	0+-0.32 pCi/l
NO3(N)	22/22 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	<10 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	1.25+-0.15 pCi/l
Pu-239	0.006+-0.004 pCi/l	U-234	1.64+-0.17 pCi/l
Ra-226	0+-0.32 pCi/l	U-235	0.10+-0.042 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \* APPROVED: JRQ 5-8-89 JCH \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.



8-May-198

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932925  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1336  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	17 mg/l	Ra-228	7.83+-1.63 pCi/l
NO3(N)	1260 mg/l	Th-228	0.085+-0.018 pCi/l
Alpha	140 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	4970 pCi/l	U238	23+-2.4 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	76+-4 pCi/l
Ra-226	1.95+-1.02 pCi/l	U-235	2.4+-0.8 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric  
analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: gah 5-8-89 JRG [Signature] \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

8-May-198

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-21-89

SAMPLE ID: 932931  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\21-MAR-89\ \ \ \ \1337  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932922

F	<0.2 mg/l	Ra-228	1.2+-0.41 pCi/l
NO3(N)	5.7 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	33 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	5.1+-0.54 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	18.7+-1.04 pCi/l
Ra-226	0.20+-0.21 pCi/l	U-235	0.17+-0.10 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: JEH 5-8-89 [Signature] \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

8-May-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 3-22-89

SAMPLE ID: 932940  
COMPLETION DATE: 4-17-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\22-MAR-89\ \ \ \ \1338  
SAMPLE DESCRIPTION: Ground Water

NOTES: NBR same as 932936

F	0.32/0.33 mg/l	Ra-228	0.028+-0.089 pCi/l
NO3(N)	<0.23/<0.23 mg/l	Th-228	0.004+-0.004 pCi/l
Alpha	<10 pCi/l	Th-232	0.004+-0.004 pCi/l
Beta	<20 pCi/l	U238	0.036+-0.025 pCi/l
Pu-239	0.002+-0.002 pCi/l	U-234	0.071+-0.036 pCi/l
Ra-226	0+-0.061 pCi/l	U-235	0.017+-0.017 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric  
analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: JKD JCH 5-8-89 [Signature] \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

CHAIN OF CUSTODY RECORD - ENVIRONMENTAL SAMPLES

FACILITY NAME: <u>CIMARRON FACILITY</u> ADDRESS: <u>Highway 74</u> <u>Crescent, OK</u>	SAMPLING FIRM NAME: <u>JAMES L. GIBSON &amp; Assoc.</u> ADDRESS: <u>8301 E. DODD AVE #402, ENGLEWOOD, CO. 80111</u> SIGNATURE: <u>Patricia Brown</u>	SAMPLE <input type="checkbox"/> Effluent <input checked="" type="checkbox"/> Groundwater <input type="checkbox"/> Solid <input type="checkbox"/> Surface Water
---	---	--

NO.	LOCATION	DATE	TIME	WEATHER		SAMPLE TYPE AND METHOD					TIMES CASING CLEARED	NO. OF CONTAINERS	ANALYSIS REQUIRED	REMARKS
				TEMP	PREC.	COMP	GRAB	MECH	MAN					
1325	CIMARRON FACILITY	3/20/09	08:45	30°F	45% NOB. NONE		X					3	NO <sub>2</sub> , NH <sub>3</sub> , F <sub>2</sub> , CHLORINE, ALUMINUM, BETA, TH-232, TH-228, U-235, U-238, Ra-228, Ra-224, Ra-226, TOC, TOX	
1326	"	"	10:35	"	"		"					3	SAME	
1335	"	"	09:15	"	"		"					2	SAME WITHOUT TOC, TOX	
1336	"	"	10:10	"	"		"					2	"	
1320	"	"	07:55	"	"		"					2	"	
1324	"	"	08:20	"	"		"					2	"	
1321	"	"	07:25	"	"		"					2	"	

RELINQUISHED BY (SIGNATURE): <u>Patricia Brown</u>	RECEIVED BY (SIGNATURE):	DATE:	TIME:	ADDITIONAL REMARKS:	
RELINQUISHED BY (SIGNATURE):	RECEIVED BY (SIGNATURE):	DATE:	TIME:		
RELINQUISHED BY (SIGNATURE):	RECEIVED BY (SIGNATURE):	DATE:	TIME:		
DISPATCHED BY (SIGNATURE):	DATE:	TIME:	RECEIVED FOR LABORATORY (SIGNATURE): <u>DM Kuck</u>	DATE: <u>3/24/09</u>	TIME: <u>11:30a</u>
CARRIER: <u>DELIVERED PERSONALLY</u>	LABORATORY:	ADDRESS:	ADDRESS:	ALL ANALYSIS PERFORMED BY EPA APPROVED PROCEDURES <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No, explain above	
ADDRESS:	ADDRESS:	ADDRESS:	ADDRESS:		
METHOD OF SHIPMENT:					

APR-24-09 MON 13:34

405 541 8551 240

P. 21

CHAIN OF CUSTODY RECORD - ENVIRONMENTAL SAMPLES

<p>FACILITY</p> <p>NAME: <u>CIMARRON FACILITY</u></p> <p>ADDRESS: <u>Highway 74</u> <u>Crescent, OK 73028</u></p>	<p>SAMPLING FIRM</p> <p>NAME: <u>JAMES L. GRANT &amp; Assoc.</u></p> <p>ADDRESS: <u>8301 E. PRENTICE #402 Enclewood, CO 80111</u></p> <p>SIGNATURE: <u>Patricia Brown</u></p>	<p>SAMPLE</p> <p><input type="checkbox"/> Effluent <input checked="" type="checkbox"/> Groundwater</p> <p><input type="checkbox"/> Soils <input type="checkbox"/> Surface Water</p> <p><input type="checkbox"/></p>
---	---	---

NO.	LOCATION	DATE	TIME	WEATHER		SAMPLE TYPE AND METHOD				TIMES CASING CLEARED	NO. OF CONTAINERS	ANALYSIS REQUIRED	REMARKS
				TEMP	PREC	COMP	GRAB	MECH	MAN				
1331	CIMARRON FACILITY	3/21/89	16:25	50°	None		X				2	H <sub>2</sub> , as N, F, Gross Alpha, Beta, Tc-232, Th-230, U-238, U-235, Ra-228, Ra-226, Ra-229	
1333	" "	"	16:50	"	"		"				2	SAME	
1337	" "	"	17:00	"	"		"				2	SAME	
1332	" "	"	17:25	"	"		"				2	SAME	
1334	" "	"	17:50	"	"		"				2	SAME	
1327	" "	"	19:35	"	"		"				2	SAME	
<del>1330</del> 1340	" "	"	19:10	"	"		"				2	SAME	

<p>RELINQUISHED BY (SIGNATURE): <u>Patricia F. Brown</u></p>	<p>RECEIVED BY (SIGNATURE): <u>E. J. Endert</u></p>	<p>DATE: <u>3-21-89</u></p>	<p>TIME: <u>20:15</u></p>	<p>ADD - CORAL REMARKS</p>
RELINQUISHED BY (SIGNATURE):	RECEIVED BY (SIGNATURE):	DATE:	TIME:	
RELINQUISHED BY (SIGNATURE):	RECEIVED BY (SIGNATURE):	DATE:	TIME:	
DISPATCHED BY (SIGNATURE):	RECEIVED FOR LABORATORY (SIGNATURE): <u>E. J. Endert</u>	DATE: <u>3/22/89</u>	TIME: <u>7:00</u>	
CARRIER:	LABORATORY:			
ADDRESS:	ADDRESS:			
METHOD OF SHIPMENT:	<p>ALL ANALYSIS PERFORMED BY EPA APPROVED PROCEDURES</p> <p><input checked="" type="checkbox"/> Yes <input type="checkbox"/> No, explain above</p>			

OPD-24-89 MMN 12-25  
 405 241 8551 240  
 P.22

CHAIN OF CUSTODY RECORD - ENVIRONMENTAL SAMPLES KM 275

<p>FACILITY</p> <p>NAME: <b>CIMARRON FACILITY</b></p> <p>ADDRESS: <b>Highway 74</b> <b>Crescent OK 73028</b></p>	<p>SAMPLING FIRM</p> <p>NAME: <b>JAMES L. GRANT &amp; ASSOC.</b></p> <p>ADDRESS: <b>8301 E. PRENTICE #402 ENCLAWOOD CO. OK 73111</b></p> <p>SIGNATURE: <i>Patricia Brown (Brown)</i></p>	<p>SAMPLE</p> <p><input type="checkbox"/> Effluent      <input checked="" type="checkbox"/> Groundwater</p> <p><input type="checkbox"/> Solid            <input type="checkbox"/> Surface Water</p> <p><input type="checkbox"/></p>
--	--	---

NO.	LOCATION	DATE	TIME	WEATHER		SAMPLE TYPE AND METHOD				TIMES CASING CLEARED	NO OF CONTAINERS	ANALYSIS REQUIRED	REMARKS
				TEMP	HREC	COMP	GRAB	MECH	MAN				
1322	CIMARRON	3/22/89	12:00	60	φ			X			3	NO <sub>2</sub> as N, P, Gases As per U-238, U-235, Ra-226, Ra-228, Th-232, Th-230, TOC, TOX	BETA, TH-232, Th-230
1329	"	"	1:15	60	φ			"			3	SAME	
1323	"	"	11:35	50	φ			"			2	SAME WITHOUT TOC, TOX	
1328	"	"	12:40	60	φ			"			2	SAME " " "	
1338	"	"	1:35	60	φ			"			2	SAME " " "	

RELINQUISHED BY (SIGNATURE): <i>Patricia Brown</i>	RECEIVED BY (SIGNATURE):	DATE:	TIME:	ADDITIONAL REMARKS:	
RELINQUISHED BY (SIGNATURE):	RECEIVED BY (SIGNATURE):	DATE:	TIME:		
RELINQUISHED BY (SIGNATURE):	RECEIVED BY (SIGNATURE):	DATE:	TIME:		
DISPATCHED BY (SIGNATURE):	DATE:	TIME:	RECEIVED FOR LABORATORY (SIGNATURE): <i>A. Keck</i>	DATE:	TIME:
CARRIER:			LABORATORY:	<i>3/22/89</i>	<i>3:25p</i>
ADDRESS:			ADDRESS:		
METHOD OF SHIPMENT:			ALL ANALYSIS PERFORMED BY EPA APPROVED PROCEDURES		
			<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No, explain above		

APR-24-89 MON 13:56 405 341 8551 240 P. 23

**APPENDIX E**  
**SOIL AND ROCK SITE-SPECIFIC PARAMETER ANALYSES**

808211: 9-12-89

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943087  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\24-JAN-89\ \ \ \ \CS-101 WELL 1321  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	560 ppm	Ra-226	0.51+-0.28 pCi/g
NO3(N)	3 ppm	Ra-228	1.84+-0.39 pCi/g
TOC	<10 ppm	Th-228	1.37+-0.07 pCi/g
Alpha	34 pCi/g	Th-232	1.37+-0.07 pCi/g
Beta	<20 pCi/g	U-234	0.57+-0.07 pCi/g
Pu-239	0.002+-0.001 pCi/g	U-238	0.66+-0.07 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89 gRg  \_\_\_\_\_ \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.





21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943099  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\20-JAN-89\ \ \ \ \CS-113 WELL 1321  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	65 ppm	Ra-226	0.12+-0.20 pCi/g
NO3(N)	130 ppm	Ra-228	0.08+-0.18 pCi/g
TOC	170 ppm	Th-228	0.33+-0.03 pCi/g
Alpha	<10 pCi/g	Th-232	0.32+-0.03 pCi/g
Beta	<20 pCi/g	U-234	0.18+-0.03 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.23+-0.03 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED: D. Keck 7/21/89   
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
 \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943112  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\20-JAN-89\ \ \ \ \CS-126 WELL 1321  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	18 ppm	Ra-226	0.01+-0.13 pCi/g
NO3(N)	4 ppm	Ra-228	0+-0.09 pCi/g
TOC	130 ppm	Th-228	0.41+-0.04 pCi/g
Alpha	<10 pCi/g	Th-232	0.41+-0.04 pCi/g
Beta	<20 pCi/g	U-234	0.21+-0.03 pCi/g
Pu-239	0.002+-0.001 pCi/g	U-238	0.16+-0.02 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89   
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943088  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\13-FEB-89\ \ \ \ C\5-102 WELL 1323  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	640 ppm	Ra-226	0.21+-0.21 pCi/g
NO3(N)	2 ppm	Ra-228	0.29+-0.20 pCi/g
TOC	190 ppm	Th-228	1.42+-0.06 pCi/g
Alpha	30 pCi/g	Th-232	1.39+-0.06 pCi/g
Beta	<20 pCi/g	U-234	0.63+-0.08 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.67+-0.08 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89  \_\_\_\_\_  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943089  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\13-FEB-89\ \ \ \ \CS-103 WELL 1323  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	440 ppm	Ra-226	0.28+-0.95 pCi/g
NO3(N)	3 ppm	Ra-228	0.27+-0.85 pCi/g
TOC	23 ppm	Th-228	1.28+-0.10 pCi/g
Alpha	30 pCi/g	Th-232	1.17+-0.10 pCi/g
Beta	<20 pCi/g	U-234	0.60+-0.06 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.51+-0.06 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED: D. Keck 7/21/89 JJK [Signature] \*  
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
 \* \_\_\_\_\_ \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943105  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-FEB-89\ \ \ \ \CS-119 WELL 1323  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	330 ppm	Ra-226	0.38+-0.33 pCi/g
NO3(N)	3 ppm	Ra-228	0.30+-0.27 pCi/g
TOC	130 ppm	Th-228	0.93+-0.06 pCi/g
Alpha	18 pCi/g	Th-232	0.96+-0.06 pCi/g
Beta	<20 pCi/g	U-234	0.59+-0.05 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.63+-0.05 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \* APPROVED: A. Keck 7/21/89  \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943106  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-FEB-89\ \ \ \ \CS-120 WELL 1323  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	59 ppm	Ra-226	0.03+-0.20 pCi/g
NO3(N)	3 ppm	Ra-228	0+-0.14 pCi/g
TOC	140 ppm	Th-228	0.42+-0.05 pCi/g
Alpha	<10 pCi/g	Th-232	0.42+-0.05 pCi/g
Beta	<20 pCi/g	U-234	0.27+-0.04 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.27+-0.04 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89   
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943097  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\08-FEB-89\ \ \ \ \CS-111 WELL 1324  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086



F	39 ppm	Ra-226	0.11+-0.26 pCi/g
NO3(N)	4 ppm	Ra-228	0+-0.16 pCi/g
TOC	27 ppm	Th-228	0.41+-0.02 pCi/g
Alpha	<10 pCi/g	Th-232	0.45+-0.02 pCi/g
Beta	<20 pCi/g	U-234	0.19+-0.05 pCi/g
Pu-239	0.006+-0.001 pCi/g	U-238	0.19+-0.05 pCi/g

All constituents soluble unless otherwise specified:

i=insoluble constituent, t=total constituent

\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\*  
\* APPROVED: A. Keck 7/21/89    
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.



21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943086  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\09-FEB-89\ \ \ \ \CS-100 WELL 1325  
SAMPLE DESCRIPTION: Soils

NOTES: 1705-JAE-18P36-50;1660-JRJ-23P183-190  
1663-MTM-6P108,109;1717-JRJ-24P20-46  
1717-JRJ-24P1-10;1660-JRJ-23P182-192

F	170 ppm	Ra-226	0.55+-0.36 pCi/g
NO3(N)	14 ppm	Ra-228	0.07+-0.18 pCi/g
TOC	45 ppm	Th-228	0.70+-0.03 pCi/g
Alpha	16 pCi/g	Th-232	0.70+-0.03 pCi/g
Beta	<20 pCi/g	U-234	0.51+-0.05 pCi/g
Pu-239	0.003+-0.001 pCi/g	U-238	0.34+-0.05 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric  
analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89 JPK  \_\_\_\_\_ \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943090  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\16-FEB-89\ \ \ \ \CS-104 WELL 1326  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	600 ppm	Ra-226	0.77+-0.21 pCi/g
NO3(N)	4 ppm	Ra-228	1.17+-0.24 pCi/g
TOC	<10 ppm	Th-228	1.15+-0.06 pCi/g
Alpha	35 pCi/g	Th-232	1.15+-0.06 pCi/g
Beta	<20 pCi/g	U-234	0.77+-0.07 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.69+-0.07 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89 [Signature] \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943107  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\15-FEB-89\ \ \ \ \CS-121 WELL 1326  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	170 ppm	Ra-226	0.42+-0.32 pCi/g
NO3(N)	5 ppm	Ra-228	0+-0.25 pCi/g
TOC	3110 ppm	Th-228	0.59+-0.05 pCi/g
Alpha	<10 pCi/g	Th-232	0.49+-0.04 pCi/g
Beta	<20 pCi/g	U-234	0.68+-0.05 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.44+-0.05 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric  
analyses will be run and the results reported later.

\*\*\*\*\*

\*  
\* APPROVED: D. Keck 7/21/89 *JK* \_\_\_\_\_ \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943091  
COMPLETION DATE: 7-21-89



LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\28-FEB-89\ \ \ \ \CS-105 WELL 1327  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	470 ppm	Ra-226	0.65+-0.34 pCi/g
NO3(N)	3 ppm	Ra-228	0.77+-0.35 pCi/g
TOC	<10 ppm	Th-228	1.2+-0.08 pCi/g
Alpha	31 pCi/g	Th-232	1.0+-0.08 pCi/g
Beta	<20 pCi/g	U-234	0.68+-0.04 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.68+-0.04 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED: D. Keck 7/21/89    
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
 \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943092  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\09-MAR-89\ \ \ \ \CS-106 WELL 1328  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	600 ppm	Ra-226	0.66+-0.39 pCi/g
NO3(N)	15 ppm	Ra-228	0.99+-0.42 pCi/g
TOC	<10 ppm	Th-228	1.18+-0.07 pCi/g
Alpha	36 pCi/g	Th-232	1.14+-0.07 pCi/g
Beta	<20 pCi/g	U-234	0.72+-0.07 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.71+-0.07 pCi/l

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric  
analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89    
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
\*  
\* \_\_\_\_\_  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943108  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\08-MAR-89\ \ \ \ \CS-122 WELL 1328  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	72 ppm	Ra-226	0.12+-0.25 pCi/g
NO3(N)	5 ppm	Ra-228	0.01+-0.19 pCi/g
TOC	47 ppm	Th-228	0.33+-0.03 pCi/g
Alpha	<10 pCi/g	Th-232	0.33+_0.03 pCi/g
Beta	<20 pCi/g	U-234	0.36+-0.03 pCi/g
Pu-239	0.002+-0.001 pCi/g	U-238	0.26+-0.03 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89   
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943109  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\08-MAR-89\ \ \ \ \CS-123 WELL 1328  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	180 ppm	Ra-226	0.37+-0.22 pCi/g
NO3(N)	2 ppm	Ra-228	0.30+-0.21 pCi/g
TOC	320 ppm	Th-228	0.68+-0.06 pCi/g
Alpha	11 pCi/g	Th-232	0.50+-0.06 pCi/g
Beta	<20 pCi/g	U-234	0.45+-0.04 pCi/g
Pu-239	0.003+-0.001 pCi/g	U-238	0.45+-0.04 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: N. Keck 7/21/89  \_\_\_\_\_  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943110  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\08-MAR-89\ \ \ \ \CS-124 WELL 1328  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	23 ppm	Ra-226	0+-0.06 pCi/g
NO3(N)	6 ppm	Ra-228	1.90+-0.54 pCi/g
TOC	1180 ppm	Th-228	0.47+-0.04 pCi/g
Alpha	<10 pCi/g	Th-232	0.27+-0.04 pCi/g
Beta	<20 pCi/g	U-234	0.19+-0.03 pCi/g
Pu-239	0.002+-0.001 pCi/g	U-238	0.19+-0.03 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\* APPROVED: D. Keck 7/21/89  \_\_\_\_\_ \*

\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*

\* \_\_\_\_\_ \*

\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.



21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943093  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\10-MAR-89\ \ \ \ \CS-107 WELL 1330  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	560 ppm	Ra-226	0.29+-0.22 pCi/g
NO3(N)	16 ppm	Ra-228	0.62+-0.21 pCi/g
TOC	420 ppm	Th-228	0.87+-0.05 pCi/g
Alpha	19 pCi/g	Th-232	0.69+-0.05 pCi/g
Beta	<20 pCi/g	U-234	0.73+-0.08 pCi/g
Pu-239	0.002+-0.001 pCi/g	U-238	0.84+-0.08 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89 Jkg   
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943111  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\10-MAR-89\ \ \ \ \CS-125 WELL 1330  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	88 ppm	Ra-226	0.11+-0.32 pCi/g
NO3(N)	12 ppm	Ra-228	0+-0.25 pCi/g
TOC	240 ppm	Th-228	0.26+-0.03 pCi/g
Alpha	<10 pCi/g	Th-232	0.26+-0.03 pCi/g
Beta	<20 pCi/g	U-234	0.23+-0.03 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.22+-0.03 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: *D. Keck 7/21/89* *[Signature]* \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
 DATE RECEIVED: 4-11-89

SAMPLE ID: 943104  
 COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
 SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\10-MAR-89\ \ \ \ \CS-118 WELL 1331  
 SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	210 ppm	Ra-226	0.40+-0.57 pCi/g
NO3(N)	3 ppm	Ra-228	0.02+-0.24 pCi/g
TOC	250 ppm	Th-228	0.63+-0.05 pCi/g
Alpha	12 pCi/g	Th-232	0.56+-0.04 pCi/g
Beta	<20 pCi/g	U-234	0.30+-0.04 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.34+-0.04 pCi/g

All constituents soluble unless otherwise specified:  
 i=insoluble constituent, t=total constituent  
 \* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED: D. Keck 7/21/89   
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
 \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
 Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
 This/these samples are scheduled for disposal after 30 days.  
 If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943101  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\11-MAR-89\ \ \ \ \CS-115 WELL 1332  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	150 ppm	Ra-226	0.26+-0.26 pCi/g
NO3(N)	5 ppm	Ra-228	0.02+-0.16 pCi/g
TOC	440 ppm	Th-228	0.65+-0.05 pCi/g
Alpha	<10 pCi/g	Th-232	0.61+-0.05 pCi/g
Beta	<20 pCi/g	U-234	0.36+-0.04 pCi/g
Pu-239	0.002+-0.001 pCi/g	U-238	0.38+-0.04 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89 *JK* \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943102  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\11-MAR-89\ \ \ \ \CS-116 WELL 1332  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	65 ppm	Ra-226	0.30+-0.22 pCi/g
NO3(N)	3 ppm	Ra-228	0+-0.44 pCi/g
TOC	110 ppm	Th-228	0.56+-0.04 pCi/g
Alpha	<10 pCi/g	Th-232	0.56+-0.04 pCi/g
Beta	<20 pCi/g	U-234	0.45+-0.04 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.38+-0.04 pCi/g

All constituents soluble unless otherwise specified:

i=insoluble constituent, t=total constituent

\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\* \_\_\_\_\_ \*

\* APPROVED: D. Keck 7/21/89  \_\_\_\_\_ \*

\* \_\_\_\_\_ \*

\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*

\* \_\_\_\_\_ \*

\* \_\_\_\_\_ \*

\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division

Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are scheduled for disposal after 30 days.

If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943103  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\11-MAR-89\ \ \ \ \CS-117 WELL 1332  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	450 ppm	Ra-226	0.32+-0.36 pCi/g
NO3(N)	3 ppm	Ra-228	0.54+-0.36 pCi/g
TOC	<10 ppm	Th-228	0.96+-0.04 pCi/g
Alpha	25 pCi/g	Th-232	0.89+-0.04 pCi/g
Beta	<20 pCi/g	U-234	0.63+-0.05 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.70+-0.05 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89 DRG  \_\_\_\_\_ \*  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*  
\* \_\_\_\_\_ \*

\*\*\*\*\*  
KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943100  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\11-MAR-89\ \ \ \ \CS-114 WELL 1334  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	51 ppm	Ra-226	0.33+-0.17 pCi/g
NO3(N)	4 ppm	Ra-228	0+-0.09 pCi/g
TOC	18 ppm	Th-228	0.28+-0.03 pCi/g
Alpha	11 pCi/g	Th-232	0.27+-0.03 pCi/g
Beta	<20 pCi/g	U-234	0.61+-0.05 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.38+-0.05 pCi/g

All constituents soluble unless otherwise specified:

i=insoluble constituent, t=total constituent

\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*

\* APPROVED: J. Keck 7/2/89 *[Signature]* \_\_\_\_\_ \*

\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_ \*

\* \_\_\_\_\_ \*

\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division

Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are scheduled for disposal after 30 days.

If you want the samples retained or returned, please advise.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943096  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\13-MAR-89\ \ \ \ \CS-110 WELL 1335  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	40 ppm	Ra-226	0.08+-0.11 pCi/g
NO3(N)	3 ppm	Ra-228	0.10+-0.14 pCi/g
TOC	840 ppm	Th-228	0.27+-0.03 pCi/g
Alpha	<10 pCi/g	Th-232	0.27+-0.03 pCi/g
Beta	<20 pCi/g	U-234	0.24+-0.04 pCi/g
Pu-239	0.001+-0.001 pCi/g	U-238	0.24+-0.04 pCi/g

All constituents soluble unless otherwise specified:  
 i=insoluble constituent, t=total constituent  
 \* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED: D. Keck 7/21/89  \_\_\_\_\_  
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
 \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
 Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
 This/these samples are scheduled for disposal after 30 days.  
 If you want the samples retained or returned, please advise.



21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943094  
COMPLETION DATE: 7-21-89


LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\14-MAR-89\ \ \ \ \CS-108 WELL 1336  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	140 ppm	Ra-226	0.19+-0.34 pCi/g
NO3(N)	9 ppm	Ra-228	0.04+-0.17 pCi/g
TOC	1180 ppm	Th-228	0.52+-0.07 pCi/g
Alpha	<10 pCi/g	Th-232	0.53+-0.07 pCi/g
Beta	<20 pCi/g	U-234	0.21+-0.04 pCi/g
Pu-239	0.002+-0.001 pCi/g	U-238	0.23+-0.04 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
 \*  
 \* APPROVED: D. Keck 7/21/89   
 \*  
 \* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
 \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

21-Jul-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 4-11-89

SAMPLE ID: 943095  
COMPLETION DATE: 7-21-89

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\14-MAR-89\ \ \ \ \CS-109 WELL 1336  
SAMPLE DESCRIPTION: Soils

NOTES: NBR same as 943086

F	190 ppm	Ra-226	0.26+-0.25 pCi/g
NO3(N)	27 ppm	Ra-228	0.37+-0.31 pCi/g
TOC	<10 ppm	Th-228	0.52+-0.05 pCi/g
Alpha	<10 pCi/g	Th-232	0.52+-0.05 pCi/g
Beta	<20 pCi/g	U-234	0.42+-0.05 pCi/g
Pu-239	0.002+-0.001 pCi/g	U-238	0.38+-0.05 pCi/g

All constituents soluble unless otherwise specified:  
i=insoluble constituent, t=total constituent  
\* Gross Alpha greater than 15 pCi/l. Radiometric analyses will be run and the results reported later.

\*\*\*\*\*  
\*  
\* APPROVED: D. Keck 7/21/89 JJK \_\_\_\_\_  
\*  
\* DISTRIBUTION: J.C. STAUTER, D.M. KECK, \_\_\_\_\_  
\*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL  
This/these samples are scheduled for disposal after 30 days.  
If you want the samples retained or returned, please advise.

**APPENDIX F**  
**PHYSICAL PROPERTY ANALYSES**

808211: 9-12-89



CORPORATE OFFICE & CENTRAL LABORATORY

3400 N. Lincoln Okla. City, OK 73105 (405) 528-0541

Field Offices

902 Trails West Loop Enid, OK 73703 (405) 237-3130  
 900 S.E. 2nd Lawton, OK 73501 (405) 353-0872  
 208 Eastside Blvd. Muskogee, OK 74403 (918) 682-7853  
 660 Distributors Row Suite C, Harahan, LA 70123 (504) 734-8378

REPORT Permeability Tests Date 4/3/89  
 Structure Cimarron Corporation Site Assessment Specification ASTM DG98 & ASTM STP-479  
 Project Cimarron Corporation Site Assessment Quantity See Below  
 Station Sample PP-1 Represented See Below  
 Location Sample PP-1  
 Architect James L. Grant and Associates, Inc. Sampled by Client  
 Engineer James L. Grant and Associates, Inc.  
 Contractor (Kerr McGee) by Order of Wyndal Goodman  
 Reported To James Grant Date 4/25/89 Order Number \_\_\_\_\_

TEST RESULTS

Laboratory Number G109

Soil Sample: PP-1

Standard Proctor Test:

Percent Moisture	Dry Density, pcf
11.0	118.8
13.1	119.7
14.7	118.3
13.1 Optimum	119.7 Maximum

Permeability Results:

Percent Moisture	Percent Compaction	Coefficient of Permeability k, cm/sec.
13.4	80.8	1.02 x 10 <sup>-4</sup>
12.8	89.6	1.18 x 10 <sup>-5</sup>
14.3	96.1	3.0 x 10 <sup>-7</sup>

THIS REPORT APPLIES ONLY TO THE STANDARDS OR PROCEDURES INDICATED AND TO THE SAMPLE TESTED AND/OR OBSERVED AND ARE NOT NECESSARILY INDICATIVE OF THE QUALITIES OF APPARENTLY IDENTICAL OR SIMILAR PRODUCTS, OR PROCEDURES, NOR DO THEY REPRESENT AN ON GOING QUALITY ASSURANCE PROGRAM UNLESS SO NOTED. THESE REPORTS ARE FOR THE EXCLUSIVE USE OF THE ADDRESSED CLIENT AND ARE RENDERED UPON THE CONDITION THAT THEY WILL NOT BE REPRODUCED WHOLLY OR IN PART FOR ADVERTISING OR OTHER PURPOSES OVER OUR SIGNATURE OR IN CONNECTION WITH OUR NAME WITHOUT SPECIAL WRITTEN PERMISSION.

Charge: Kerr McGee  
 Orig. & lcc To James Grant  
 lcc To Kerr McGee  
 lcc to Lab



Respectfully Submitted 1-537  
 STANDARD TESTING AND ENGINEERING CO.

Signed By \_\_\_\_\_  
 By Richard W. Mudd, P.E.

Construction Materials, Testing & Inspections  
 Fabrications Weldment & Erection Inspections  
 Geo-technical Investigations  
 Chemical & Bacteriological Analysis

"TEST FOR ASSURANCE"

Field Offices

902 Trails West Loop Enid, OK 73703 (405) 237-3130  
 900 S.E. 2nd Lawton, OK 73501 (405) 353-0872  
 208 Eastside Blvd. Muskogee, OK 74403 (918) 682-7853  
 660 Distributors Row Suite C, Harahan, LA 70123 (504) 734-8378

REPORT Permeability Tests Date 4/3/89  
 Structure \_\_\_\_\_  
 Project Cimarron Corporation Site Assessment Specification ASTM DG98 & ASTM STP 479  
 Station \_\_\_\_\_ Quantity \_\_\_\_\_  
 Location Sample PP-2 Represented See Below  
 Architect \_\_\_\_\_  
 Engineer James L. Grant and Associates, Inc. Sampled by Client  
 Contractor (Kerr McGee) by Order of Wyndal Goodman  
 Reported To James Grant Date 4/25/89 Order Number \_\_\_\_\_

TEST RESULTS

Laboratory Number G109

Soil Sample: PP-2

Standard Proctor Test:

Percent Moisture	Dry Density, pcf
11.9	119.4
13.7	120.2
15.9	116.0
13.0 Optimum	120.5 Maximum

Permeability Results:


Percent Moisture	Percent Compaction	Coefficient of Permeability, k, cm/sec
15.3	77.9	1.98 x 10 <sup>-5</sup>
14.7	88.2	2.99 x 10 <sup>-6</sup>
14.6	97.4	3.08 x 10 <sup>-8</sup>

THIS REPORT APPLIES ONLY TO THE STANDARDS OR PROCEDURES INDICATED AND TO THE SAMPLE TESTED AND/OR OBSERVED AND ARE NOT NECESSARILY INDICATIVE OF THE QUALITIES OF APPARENTLY IDENTICAL OR SIMILAR PRODUCTS, OR PROCEDURES, NOR DO THEY REPRESENT AN ON GOING QUALITY ASSURANCE PROGRAM UNLESS SO NOTED. THESE REPORTS ARE FOR THE EXCLUSIVE USE OF THE ADDRESSED CLIENT AND ARE RENDERED UPON THE CONDITION THAT THEY WILL NOT BE REPRODUCED WHOLLY OR IN PART FOR ADVERTISING OR OTHER PURPOSES OVER OUR SIGNATURE OR IN CONNECTION WITH OUR NAME WITHOUT SPECIAL WRITTEN PERMISSION.

Charge: Kerr McGee  
 Orig. & lcc To James Grant  
 lcc to Kerr McGee  
 lcc To Lab



Respectfully Submitted  
 STANDARD TESTING AND ENGINEERING CO.  
 (Original Signed By)



By Richard W. Mudd, P.E.

Construction Materials, Testing & Inspections  
 Fabrications Weldment & Erection Inspections  
 Geo-technical Investigations  
 Chemical & Bacteriological Analysis

Field Offices

902 Trails West Loop Enid, OK 73703 (405) 237-3130  
 900 S.E. 2nd Lawton, OK 73501 (405) 353-0872  
 208 Eastside Blvd. Muskogee, OK 74403 (918) 682-7853  
 660 Distributors Row Suite C, Harahan, LA 70123 (504) 734-8378

REPORT Permeability Date 4/3/89  
 Structure Cimarron Corporation Site Assessment Specification ASTM DG98 & ASTM STP 479  
 Project Sample PB. 3 Quantity See Below  
 Station James L. Grant and Associates, Inc. Sampled by Client  
 Location James L. Grant and Associates, Inc.  
 Architect James L. Grant and Associates, Inc.  
 Engineer James L. Grant and Associates, Inc.  
 Contractor (Kerr McGee) by Order of Wyndal Goodman  
 Reported To James Grant Date 4/25/89 Order Number \_\_\_\_\_

TEST RESULTS

Laboratory Number G109

Soil Sample: PP-3  
 Standard Proctor Test:

Percent Mixture	Dry Density, pcf
12.7	116.4
14.2	117.8
15.8	116.1
14.0 Optimum	117.8 Maximum

Permeability Results:

Percent Moisture	Percent Compaction:	Coefficient of Permeability, k, cm/sec.
16.9	77.1	1.38 x 10 <sup>-4</sup>
15.5	87.7	1.60 x 10 <sup>-5</sup>
16.0	97.1	2.48 x 10 <sup>-8</sup>

THIS REPORT APPLIES ONLY TO THE STANDARDS OR PROCEDURES INDICATED AND TO THE SAMPLE TESTED AND/OR OBSERVED AND ARE NOT NECESSARILY INDICATIVE OF THE QUALITIES OF APPARENTLY IDENTICAL OR SIMILAR PRODUCTS, OR PROCEDURES, NOR DO THEY REPRESENT AN ON GOING QUALITY ASSURANCE PROGRAM UNLESS SO NOTED. THESE REPORTS ARE FOR THE EXCLUSIVE USE OF THE ADDRESSED CLIENT AND ARE RENDERED UPON THE CONDITION THAT THEY WILL NOT BE REPRODUCED WHOLLY OR IN PART FOR ADVERTISING OR OTHER PURPOSES OVER OUR SIGNATURE OR IN CONNECTION WITH OUR NAME WITHOUT SPECIAL WRITTEN PERMISSION.

Charge: Kerr McGee  
 Orig. & lcc To James Grant  
 lcc to Kerr McGee  
 lcc to Lab



Construction Materials, Testing & Inspections  
 Fabrications Weldment & Erection Inspections  
 Geo-technical Investigations  
 Chemical & Bacteriological Analysis


"TEST FOR ASSURANCE"

Respectfully Submitted  
 STANDARD TESTING AND ENGINEERING CO.  
 (Original Stored in Oklahoma)



By Richard W. Mudd, P.E.

STANDARD TESTING and ENGINEERING COMPANY



OKLAHOMA CITY • ENID • LAWTON • MUSKOGEE • NEW ORLEANS

BIOLOGICAL CHEMICAL CONSTRUCTION MATERIALS ENVIRONMENTAL FOODS GEO-TECHNICAL INDUSTRIAL HYGIENE NON-DESTRUCTIVE

# STANDARD TESTING AND ENGINEERING COMPANY

## CORPORATE OFFICE & CENTRAL LABORATORY

3400 N. Lincoln Okla. City, OK 73105 (405) 528-0541

### Branch Offices

902 Trails West Loop	Enid, OK 73701	(405) 237-3130
900 S.E. 2nd	Lawton, OK 73501	(405) 353-0872
208 Eastside Blvd.	Muskogee, OK 74403	(918) 682-7853
660 Distributors Row	Harahan, LA 70123	(504) 734-8378

2KE22  
KE22

REPORT SOIL CLASSIFICATION Date 4-3-89  
 Structure Cimarron Corporation Site Assessment Specification AASHTO M-145  
 Project Crescent, Okla. - See Below Quantity Represented  
 Station James L. Grant & Associates Sampled by Client  
 Location Kerr McGee by Order of Wyndal Goodman  
 Architect Kerr McGee Date 4-25-89 Order Number \_\_\_\_\_  
 Engineer \_\_\_\_\_


### TEST RESULTS

Page 1 of 2 Pages

Laboratory Number	5885	5886	5887	5888	5889
Field Number	PP-1	PP-2	PP-3	PP-4	PP-5
% Passing #10 Sieve	93.8	98.3	97.3	100.0	100.0
" " #40 "	90.0	95.4	93.5	94.8	95.6
" " #200 "	70.5	73.3	72.9	62.8	87.7
Liquid Limit	24	23	23	26	34
Plasticity Index	10	9	8	8	9
AASHTO Classification	A-4(4)	A-4(3)	A-4(3)	A-4(3)	A-4(8)

THIS REPORT APPLIES ONLY TO THE STANDARDS OR PROCEDURES INDICATED AND TO THE SAMPLE TESTED AND/OR OBSERVED AND ARE NOT NECESSARILY INDICATIVE OF THE QUALITIES OF APPARENTLY IDENTICAL OR SIMILAR PRODUCTS, OR PROCEDURES, NOR DO THEY REPRESENT AN ON GOING QUALITY ASSURANCE PROGRAM UNLESS SO NOTED. THESE REPORTS ARE FOR THE EXCLUSIVE USE OF THE ADDRESSED CLIENT AND ARE RENDERED UPON THE CONDITION THAT THEY WILL NOT BE REPRODUCED WHOLLY OR IN PART FOR ADVERTISING OR OTHER PURPOSES WITHOUT OUR SIGNATURE OR IN CONNECTION WITH OUR NAME WITHOUT SPECIAL WRITTEN PERMISSION.

Charge: Kerr McGee  
 Orig. & 1cc To James L. Grant  
 1-cc Kerr McGee  
 1-cc Laboratory



Respectfully Submitted  
 STANDARD TESTING AND ENGINEERING CO.  
 (Original Signed By)

**RICHARD W. MUDD**  
 REGISTERED PROFESSIONAL ENGINEER  
 OKLAHOMA  
 17527  
 By Richard W. Mudd, P.E.

"TEST FOR ASSURANCE"



# STANDARD TESTING AND ENGINEERING COMPANY

## CORPORATE OFFICE & CENTRAL LABORATORY

3400 N. Lincoln Okla. City, OK 73105 (405) 528-0541

### Branch Offices

902 Trails West Loop	Enid, OK 73701	(405) 237-3130
900 S.E. 2nd	Lawton, OK 73501	(405) 353-0872
208 Eastside Blvd.	Muskogee, OK 74403	(918) 682-7853
660 Distributors Row	Harahan, LA 70123	(504) 734-8378

2KE22  
KE22

REPORT SOIL CLASSIFICATION Date 4-3-89  
 Structure Project Cimarron Corporation Site Assessment Specification AASHTO M-145  
 Station Location Crescent, Okla. (See Below) Quantity Represented \_\_\_\_\_  
 Architect Engineer James L. Grant & Associates Sampled by Client  
 Contractor Kerr McGee by Order of Wyndal Goodman  
 Reported To Kerr McGee Date 4-25-89 Order Number \_\_\_\_\_

### TEST RESULTS

Page 2 of 2 Pages

Laboratory Number	5890	5891	5892	5893
Field Number	PP-6	PP-7	PP-8	PP-9
% Passing #10 Sieve	100.0	100.0	100.0	100.0
" " #40 "	99.9	99.2	99.9	98.5
" " #200 "	39.2	89.2	94.6	94.1
Liquid Limit	NP	NP	25	36
Plasticity Index	NP	NP	8	13
AASHTO Classification	A-4(0)	A-4(0)	A-4(6)	A-6(13)


(PP-12?)

THIS REPORT APPLIES ONLY TO THE STANDARDS OR PROCEDURES INDICATED AND TO THE SAMPLE TESTED AND/OR OBSERVED AND ARE NOT NECESSARILY INDICATIVE OF THE QUALITY OF ANY OTHER IDENTICAL OR SIMILAR PRODUCTS, OR PROCEDURES. NOR DO THEY REPRESENT AN ON GOING QUALITY ASSURANCE PROGRAM UNLESS SO NOTED. THESE REPORTS ARE FOR THE EXCLUSIVE USE OF THE ADDRESSED CLIENT AND ARE RENDERED UPON THE CONDITION THAT THEY WILL NOT BE REPRODUCED WHOLLY OR IN PART FOR ADVERTISING OR OTHER PURPOSES WITHOUT OUR SIGNATURE OR IN CONNECTION WITH OUR NAME WITHOUT SPECIAL WRITTEN PERMISSION.

Charge: Kerr McGee  
 Orig. & 1cc To J. Grant  
 1-cc Kerr McGee  
 1-cc Laboratory



Respectfully Submitted  
 STANDARD TESTING AND ENGINEERING CO.  
 (Original Signed By)



By Richard W. Mudd, P.E.

"TEST FOR ASSURANCE"

Branch Offices:

902 Trails West Loop	Enid, OK 73701	(405) 237-3130
900 S.E. 2nd	Lawton, OK 73501	(405) 353-0872
208 Eastside Blvd.	Muskogee, OK 74403	(918) 682-7853
660 Distributors Row	Harahan, LA 70123	(504) 734-8378

MAY 5 1989

2KE22  
KE22

REPORT SOIL CLASSIFICATION Date 4-28-89

Structure Project Cimarron Corporation Site Assessment Specification AASHTO M-145

Station Location Crescent, Oklahoma Quantity Represented \_\_\_\_\_

Architect Engineer James L. Grant & Associates Sampled by Client

Contractor Kerr McGee by Order of Wyndal Goodman

Reported To James L. Grant Date 5-1-89 Order Number \_\_\_\_\_


TEST RESULTS

Laboratory Number 5894 *PP#10*

<u>SIEVES</u>	<u>% PASSING</u>
#4	100.0
#10	95.9
#40	71.8
#200	44.7
Liquid Limit	NP
Plasticity Index	NP
AASHTO Classification	A-4(0)

THIS REPORT APPLIES ONLY TO THE STANDARDS OR PROCEDURES INDICATED AND TO THE SAMPLE TESTED AND/OR OBSERVED AND ARE NOT NECESSARILY INDICATIVE OF THE QUALITIES OF APPARENTLY IDENTICAL OR SIMILAR PRODUCTS, OR PROCEDURES, NOR DO THEY REPRESENT AN ON GOING QUALITY ASSURANCE PROGRAM UNLESS SO NOTED. THESE REPORTS ARE FOR THE EXCLUSIVE USE OF THE ADDRESSED CLIENT AND ARE RENDERED UPON THE CONDITION THAT THEY WILL NOT BE REPRODUCED WHOLLY OR IN PART FOR ADVERTISING OR OTHER PURPOSES OVER OUR SIGNATURE OR IN CONNECTION WITH OUR NAME WITHOUT SPECIAL WRITTEN PERMISSION.

Charge: Kerr McGee  
 Orig. & 1cc To James L. Grant  
 1-cc Kerr McGee  
 1-cc Laboratory



Respectfully Submitted  
 STANDARD TESTING AND ENGINEERING CO.

(Original Signed By)

*Thomas J. Kelly*  
 By Thomas J. Kelly, P.E.

**APPENDIX G**  
**SOIL AND ROCK MINERALOGICAL ANALYSES**

808211: 9-12-89

## GEOLOGIC DESCRIPTION

CH-1 Red (2.5YR 4/8) clay-silt mudstone, with greenish-white clasts and/or bioturbations. Moderately fissiled, fine visible mica grains.

CH-2 Light gray (10YR 7/2) clay-silt mudstone, interlayered with a few thin red layers, moderate fissility, with some low angle cross bedding

CH-5 Dark reddish brown (2.5YR 3/4) weakly consolidated sand cemented with iron oxides and calcite.

CH-6 Massive red (10R 4/6) mudstone, poor fissility, some evidence of bioturbation with light greenish gray silty material in burrows.

CH-8 Red (10R 4/8) with orange-white mottles poorly cemented mudstone, poorly layered. Visible quartz grains are well rounded.

CH-9 Massive red (2.5YR 4/6) sandy mudstone, mottled with light greenish gray. Gray material is up to 3/8 in. long, includes moderately cemented bedded quartz sand.

CH-12 Light gray (2.5Y 7/2) very fine sand - silt mudstone, poorly cemented with no layering. Includes clay clasts

CH-14 Light olive gray (5Y 6/2) and pinkish gray (10YR 7/2) conglomerate of soft sediment clasts, some layering, calcite in isolated grains.

CH-15 Red (10R 4/8) very fine sand and silt mudstone, massive, moderately consolidated. Few isolated calcite and quartz clusters. Some evidence of slickensides or pressure faces.

Table 1. Grain size distribution  
Less than 2mm fraction

Sample	Size Distribution		
	Sand	Silt	Clay
-----%			
CH-1	0.70	78.74	20.56
CH-2	15.50	64.94	19.56
CH-3	57.70	27.82	14.48
CH-4	18.70	47.22	34.08
CH-5	82.40	10.48	7.12
CH-6	2.50	58.18	39.32
CH-7	39.60	45.56	14.84
CH-8	80.00	13.08	6.92
CH-9	37.50	39.66	22.84
CH-10	74.20	16.12	9.68
CH-11	56.40	25.56	18.04
CH-12	47.00	43.44	9.56
CH-13	25.50	55.34	19.16
CH-14	59.20	24.16	16.64
CH-15	21.90	51.94	26.16

Table 2. Sand-size distribution (percent of sand)

Sample	Sand Size Distribution (mm)				
	2-1	1-.5	.5-.25	.25-.1	.1-.05
-----%					
CH-1	0.00	0.00	0.00	0.00	100.00
CH-2	5.88	8.50	7.84	14.38	63.40
CH-3	0.00	0.17	0.17	29.34	70.31
CH-4	6.95	14.97	12.83	19.25	45.99
CH-5	28.68	15.31	15.07	32.81	8.14
CH-6	20.83	12.50	4.17	41.67	20.83
CH-7	2.78	2.28	1.01	2.78	91.14
CH-8	3.51	5.89	6.14	68.30	16.17
CH-9	3.73	6.40	6.67	31.47	51.73
CH-10	0.14	0.27	3.51	78.38	17.70
CH-11	7.09	14.01	16.31	39.72	22.87
CH-12	2.77	2.13	5.74	15.11	74.26
CH-13	1.19	2.37	1.98	13.04	81.42
CH-14	20.88	21.90	18.00	19.52	19.69
CH-15	5.02	4.11	3.65	14.16	73.06

Table 3. Exchangeable cations, pH and Cation Exchange Capacity

Sample	Exchangeable Cations				CEC	pH
	Ca	Mg	K	Na		
-----meq/100g-----						
CH-1	6.96	3.29	0.32	0.30	10.83	8.43
CH-2	17.25	2.78	0.23	0.28	7.96	8.72
CH-3	5.01	1.61	0.16	0.11	7.71	6.87
CH-4	27.37	6.62	0.47	0.30	18.56	8.53
CH-5	18.84	1.14	0.08	0.21	2.55	9.18
CH-6	26.26	5.97	0.48	0.35	22.75	8.18
CH-7	8.35	1.62	0.11	0.33	4.59	7.91
CH-8	10.93	1.43	0.07	0.33	3.37	8.30
CH-9	21.14	2.94	0.25	0.21	9.93	8.76
CH-10	10.50	1.36	0.10	0.17	2.96	5.99
CH-11	17.82	5.71	0.22	0.29	6.00	8.86
CH-12	9.29	4.03	0.50	0.27	6.20	8.69
CH-13	20.24	4.95	0.34	0.47	8.02	8.89
CH-14	17.71	4.20	0.50	0.21	6.87	8.95
CH-15	12.35	5.18	0.58	0.15	11.32	8.62

Table 4. Mineralogical Composition of Whole Soils

Sample	Kaolin	Fe-Oxyhy	2:1 Exp * & Mica	Feldspars	Calcite	Quartz	Ads.H2O
----- % -----							
CH-1	15) B	4	12	17	<1	48	1.63
CH-2	12	2	8	17	<1	56	2.25
CH-5	1) B	3	3	5	29	58	0.50
CH-6	27) B	8	23	27	<1	12	3.63
CH-8	1) B	<1	3	3	1	90	0.38
CH-9	8	3	10	14	3	59	1.63
CH-12	7) C	1	6	9	3	72	1.00
CH-14	7	1	7	11	12	59	1.25
CH-15	10) B	4	11	17	3	52	1.88

\* 2:1 Exp Expanding layer silicates  
 Feldspars and mica are given as mica equivalent (10% K<sub>2</sub>O = 100%)

ELEMENTAL COMPOSITION (OXIDES)

Sample	CaO	Al <sub>2</sub> O <sub>3</sub>	Fe <sub>2</sub> O <sub>3</sub>	K <sub>2</sub> O	MgO	SiO <sub>2</sub>	MnO
-----%-----							
CH-1	0.59	11.42	3.87	1.70	1.12	66.84	0.04
Ch-2	0.45	10.90	1.73	1.72	1.14	74.92	0.01
CH-5	22.38	3.47	3.03	0.54	2.67	62.50	0.22
CH-6	1.69	18.26	7.52	2.66	2.67	51.57	0.07
CH-8	1.06	1.42	0.46	0.28	0.13	93.51	0.00
CH-9	2.91	8.50	3.49	1.38	1.23	75.86	0.05
CH-12	2.16	6.47	0.78	0.94	1.14	83.41	0.03
CH-14	7.11	6.44	1.23	1.13	3.28	72.36	0.09
CH-15	2.11	10.05	4.44	1.72	1.49	72.03	0.04



James Grant Samples

Material Description of Air-Dried Samples

- CH-1 Strongly cemented, fine-grained, massive soil material
- CH-2 Light gray, moderately to strongly cemented, fine-grained soil material
- CH-3 Unconsolidated fine-grained soil material
- CH-4 Weakly consolidated fines in thin platy layers soil material
- CH-5 Moderately consolidated, calcareous, sandstone coarse-grained soil material
- CH-6 Weakly consolidated fines in thin platy layers soil material
- CH-7 Moderately consolidated, fine-grained, massive soil material
- CH-8 Weakly cemented sandstone with some fines soil material
- CH-9 Unconsolidated sand and clay with about 5% small fragments less than one inch in diameter
- CH-10 Unconsolidated loose sand and fines
- CH-11 Unconsolidated loose sand and fines, very f?
- CH-12 Light gray, weakly cemented to unconsolidated fine-grained soil material, few very hard rock fragments and gravels.
- CH-13 Weakly cemented to unconsolidated sand and clay
- CH-14 Light gray, weakly to moderately consolidated, fine-grained soil material
- CH-15 Moderately consolidated, fine-grained, massive soil material

## Determination of soil water retention curves

Soil water retention curves (Table 1) were determined following standard procedures as outlined by Klute (Klute, A. 1986. Water Retention: Laboratory Methods. In A. Klute (ed.) Methods of Soil Analysis. Part 1. 2nd ed. Agronomy 9:635-662). Tempe pressure cells were used for soil water pressure head values ranging from 0 to -300 cm of water, while a pressure cooker was used in the range from -1,000 to -4,000 cm of water.

The soil samples were first air dried, passed through a 2-mm sieve, and then packed into cylinders to bulk density values similar to those determined on two undisturbed clods (Blake G.R. and K.H. Hartge. 1986. Bulk density. In A. Klute (ed.) Methods of Soil Analysis. Part 1. 2nd ed. Agronomy 9:371-373).

The reported bulk density values (Table 2) were calculated from the final amount of oven dry soil packed into each cylinder. The corresponding porosity values (Table 2) are based on these bulk density values and an assumed particle density of  $2.65 \text{ g/cm}^3$ .

Table 1. Volumetric water content as a function of soil water pressure head.

Soil water pressure head cm of water	Volumetric water content cm <sup>3</sup> /cm <sup>3</sup>			
	CH-16	CH-17	CH-18	CH-19
0	0.327	0.332	0.331	0.320
-10	0.327	0.332	0.331	0.320
-20	0.327	0.332	0.331	0.320
-40	0.327	0.332	0.331	0.320
-80	0.327	0.332	0.331	0.305
-100	0.316	0.332	0.331	0.273
-150	0.274	0.332	0.331	0.248
-300	0.239	0.305	0.282	0.214
-1,000	0.207	0.254	0.233	0.180
-4,000	0.177	0.206	0.200	0.147

Table 2. Bulk density and porosity.

Sample	Bulk density g/cm <sup>3</sup>	Porosity cm <sup>3</sup> /cm <sup>3</sup>
CH-16	1.78	0.328
CH-17	1.78	0.328
CH-18	1.76	0.336
CH-19	1.79	0.325


Classification for K<sub>a</sub> Analysis

Color	Red Soil Material	Calcite	Clay	Typical K <sub>a</sub> Analysis	Comp
	CH-1		X	X	A
	CH-3				E
	CH-4		XX		D
	CH-5	XX		X	B
	CH-6		XX	X	D
	CH-7				E
	CH-8			X	E
	CH-9	X	X		F
	CH-10				E
	CH-11		X		A
	CH-13		X		A
	CH-15	X	X		F
	Gray Soil Material				
	CH-2		X	X	G
	CH-12	X			C
	CH-14	XX		X	C

%Calcite \_ <3, X 3, XX>3  
 %Clay \_ < 18, X 18-30, XX >30%


# CEC as a fct of Clay

CEC at pH 7




# GRAIN SIZE DISTRIBUTION

PERCENT PASSED




# GRAIN SIZE DISTRIBUTION

PERCENT FINISH



# GRAIN SIZE DISTRIBUTION

PERCENT PASSING






Siemens Analytical X-Ray Instruments Inc.

2-MAY-89


GRANT SAMPLE CH-1, WHOLE SOIL POWDER



Siemens Analytical X-Ray Instruments Inc.

2-MAY-89


GRANT SAMPLE CH-2, WHOLE SOIL POWDER



Nicolet Instruments Corp.

18-APR-89

WHOLE SOIL POWDER, SAMPLE CH-5




CH-6 *ay*


Siemens Analytical X-Ray Instruments Inc.

*ay*

5-MAY-89




GRANT ASSOC., SAMPLE CH-6 WHOLE SOIL POWDER



Siemens Analytical X-Ray Instruments Inc.

2-MAY-89


GRANT SAMPLE CH-8, WHOLE SOIL POWDER



Siemens Analytical X-Ray Instruments Inc.

2-MAY-89


GRANT SAMPLE CH-9, WHOLE SOIL, POWDER



Siemens Analytical X-Ray Instruments Inc.

2-MAY-89

GRANT SAMPLE CH-12, WHOLE SOIL, POWDER






Siemens Analytical X-Ray Instruments Inc.

1-MAY-89


GRANT SAMPLE CH-14, WHOLE SOIL POWDER



Siemens Analytical X-Ray Instruments Inc.

1-MAY-89


GRANT SAMPLE CH-14, WHOLE SOIL, POWDER




Siemens Analytical X-Ray Instruments Inc.

2-MAY-89


GRANT SAMPLE CH-15, WHOLE SOIL POWDER




SAMPLE CH-15, CLAY FRACTION




SAMPLE CH-6, CLAY FRACTION



SAMPLE CH-5, CLAY FRACTION




SAMPLE CH-2, CLAY FRACTION



PART NO. 990090

RUN NO. _____ DATE <u>4/10/89</u>	<b>T-AXIS</b> SCALE, °C/in <u>100</u> PROG. RATE, °C/min _____ HEAT COOL ISO _____ SHIFT, in <u>0</u>	<b>DTA-DSC</b> SCALE, °C/in _____ (mcal/sec)/in _____ WEIGHT, mg _____ REFERENCE _____	<b>TGA</b> <u>% 2.5</u> SCALE, <del>mg</del> /in _____ SUPPRESSION, mg <u>10.3</u> WEIGHT, mg _____ TIME CONST., sec _____ dY, (mg/min)/in _____	<b>TMA</b> SCALE, mils/in _____ MODE _____ SAMPLE SIZE _____ LOAD, g _____ dY, (10X), (mils/min)/in _____	_____
-----------------------------------	---	--	---	--	-------



26 % 2:1  
27 % kln  
28 % CaCO<sub>3</sub>

wt. loss = 4

2.5%


same for patterns all

DUPONT Instruments

MEASURED VARIABLE %

PART NO. 990090

RUN NO. _____ DATE <u>4/15/89</u>	<b>T-AXIS</b>	<b>DTA-DSC</b>	<b>TGA</b>	<b>TMA</b>	
OPERATOR _____	SCALE, °C/in <u>100</u>	SCALE, °C/in _____	SCALE, <u>20</u> g/in <u>2.5</u>	SCALE, mils/in _____	
SAMPLE: <u>CH-1</u>	PROG. RATE, °C/min _____	(mcal/sec)/in _____	SUPPRESSION, mg <u>2200</u>	MODE _____	
HEAT _____ COOL _____ ISO _____	WEIGHT, mg _____	WEIGHT, mg _____	WEIGHT, mg _____	SAMPLE SIZE _____	
ATM _____ (t) _____	SHIFT, in <u>0</u>	REFERENCE _____	TIME CONST., sec _____	LOAD, g _____	
FLOW RATE _____			dY, (mg/min)/in _____	dY, (10X), (mils/min)/in _____	




7% 2:1 expanding  
14% kaolinite

DUPONT Instruments

MEASURED VARIABLE

PART NO. 990090

RUN NO. _____ DATE <u>4/17/89</u>	<b>T-AXIS</b>	<b>DTA-DSC</b>	<b>TGA</b>	<b>TMA</b>	
OPERATOR _____	SCALE, °C/in <u>100</u>	SCALE, °C/in _____	SCALE, <sup>2%</sup> mg/in <u>2.5</u>	SCALE, mils/in _____	
SAMPLE: <u>CH-8</u>	PROG. RATE, °C/min <u>10</u>	(mcal/sec)/in _____	SUPPRESSION, mg <u>11.69</u>	MODE _____	
ATM _____ @ _____	HEAT <input checked="" type="checkbox"/> COOL _____ ISO _____	WEIGHT, mg _____	WEIGHT, mg <u>11.69 / 1.8</u>	SAMPLE SIZE _____	
FLOW RATE _____	SHIFT, in <u>0</u>	REFERENCE _____	TIME CONST., sec <u>2</u>	LOAD, g _____	
			dY, (mg/min)/in <u>.05</u>	dY, (10X), (mils/min)/in _____	




Trace Carbonate  
Trace basinite

DUPONT Instruments

MEASURED VARIABLE

PART NO. 990090

RUN NO. _____ DATE _____	<u>T-AXIS</u>	<u>DTA-DSC</u>	<u>TGA</u>	<u>TMA</u>	
OPERATOR _____	SCALE, °C/in <u>100</u>	SCALE, °C/in _____	SCALE, %/in <u>2.5</u>	SCALE, mils/in _____	
SAMPLE: <u>CH-9</u>	PROG. RATE, °C/min _____	(mcal/sec)/in _____	SUPPRESSION, mg/L <u>0.9</u>	MODE _____	
ATM _____	HEAT _____ COOL _____ ISO _____	WEIGHT, mg _____	WEIGHT, mg _____	SAMPLE SIZE _____	
FLOW RATE _____	SHIFT, in <u>0</u>	REFERENCE _____	TIME CONST., sec _____	LOAD, g _____	
			dY, (mg/min)/in _____	dY, (10X), (mils/min)/in _____	



6% 2:1  
 0% H<sub>2</sub>  
 3% CaCO<sub>3</sub>


DUPONT Instruments

MEASURED VARIABLE



PART NO. 990090

RUN NO. _____ DATE _____	<b>T-AXIS</b> SCALE, °C/in <u>100</u> PROG. RATE, °C/min _____ HEAT _____ COOL _____ ISO _____ SHIFT, in <u>0</u>	<b>DTA-DSC</b> SCALE, °C/in _____ (mcal/sec)/in _____ WEIGHT, mg _____ REFERENCE _____	<b>TGA</b> <u>2.5</u> SCALE, <del>mg</del> /in _____ SUPPRESSION, mg <u>9.43</u> WEIGHT, mg _____ TIME CONST., sec _____ dY, (mg/min)/in _____	<b>TMA</b> SCALE, mils/in _____ MODE _____ SAMPLE SIZE _____ LOAD, g _____ dY, (10X), (mils/min)/in _____	_____
OPERATOR _____	_____	_____	_____	_____	_____
SAMPLE: <u>CH-15</u>	_____	_____	_____	_____	_____
ATM _____ (at) _____	_____	_____	_____	_____	_____
FLOW RATE _____	_____	_____	_____	_____	_____




8.5% 2:1  
10% K1,  
2.8 CaCO<sub>3</sub>

MEASURED VARIABLE ..... DUPONT Instruments

PART NO. 990090

RUN NO. _____ DATE _____	<b>T-AXIS</b> SCALE, °C/in <u>100</u> PROG. RATE, °C/min _____ HEAT _____ COOL _____ ISO _____ SHIFT, in <u>0</u>	<b>DTA-DSC</b> SCALE, °C/in _____ (mcal/sec)/in _____ WEIGHT, mg _____ REFERENCE _____	<b>TGA</b> SCALE, <sup>0.1</sup> mg/in <u>2.5</u> SUPPRESSION, <sup>80%</sup> mg <u>10.0%</u> WEIGHT, mg _____ TIME CONST., sec _____ dY, (mg/min)/in _____	<b>TMA</b> SCALE, mils/in _____ MODE _____ SAMPLE SIZE _____ LOAD, g _____ dY, (10X), (mils/min)/in _____	<u>CH-2</u>
--------------------------	---	--	--	--	-------------




12.5% K10  
10.0% 2:1 expanding

DUPONT Instruments

MEASURED VARIABLE

PART NO. 990090

RUN NO. _____ DATE _____	<b>T-AXIS</b>	<b>DTA-DSC</b>	<b>TGA</b>	<b>TMA</b>	<u>CH-5</u>
OPERATOR _____	SCALE, °C/in <u>100</u>	SCALE, °C/in _____	SCALE, %/in <u>2.5</u>	SCALE, mils/in _____	
SAMPLE: _____	PROG. RATE, °C/min _____	(mcal/sec)/in _____	SUPPRESSION, mg <u>12.88</u>	MODE _____	
ATM _____ @ _____	HEAT _____ COOL _____ ISO _____	WEIGHT, mg _____	WEIGHT, mg <u>12.88/1.8</u>	SAMPLE SIZE _____	
FLOW RATE _____	SHIFT, in <u>0</u>	REFERENCE _____	TIME CONST., sec <u>2</u>	LOAD, g _____	
			dY, (mg/min)/in <u>0.05</u>	dY, (10X), (mils/min)/in _____	




*Trace baseline  
 (5.2 \* 2.5) / 44  
 29% CoCO<sub>3</sub> equivalent*

*5.2  
 2.5  
 ---  
 130  
 178*

MEASURED VARIABLE \_\_\_\_\_ DUPONT Instruments

PART NO. 990090

RUN NO. _____ DATE _____	<u>T-AXIS</u>	<u>DTA-DSC</u>	<u>TGA</u>	<u>TMA</u>
OPERATOR _____	SCALE, °C/in <u>100</u>	SCALE, °C/in _____	SCALE, mg/in <u>2.5</u>	SCALE, mils/in _____
SAMPLE: <u>CH-6</u>	PROG. RATE, °C/min _____	(mcal/sec)/in _____	SUPPRESSION, mg <u>2.33</u>	MODE _____
ATM _____	HEAT _____ COOL _____ ISO _____	WEIGHT, mg _____	WEIGHT, mg <u>12.33 / .80</u>	SAMPLE SIZE _____
FLOW RATE _____	SHIFT, in <u>0</u>	REFERENCE _____	TIME CONST., sec _____	LOAD, g _____
			dY, (mg/min)/in _____	dY, (10X), (mils/min)/in _____



16% 2:1 expansion  
27% baseline

DUPONT Instruments

MEASURED VARIABLE

**CHAIN OF CUSTODY RECORD— ENVIRONMENTAL SAMPLES KM-4776**

<b>FACILITY</b>	<b>SAMPLING FIRM</b>	<b>SAMPLE</b>
NAME <u>CIMARRON FACILITY</u>	NAME <u>JAMES L. GRANT &amp; Assoc.</u>	<input type="checkbox"/> Effluent <input type="checkbox"/> Groundwater <input checked="" type="checkbox"/> Solid <input type="checkbox"/> Surface Water <input type="checkbox"/>
ADDRESS <u>HIGHWAY 74 N</u>	ADDRESS <u>8301 E. PRENTISS #402, ENGLEWOOD, CO. 80111</u>	
<u>CRESCENT, OK 73028</u>	SIGNATURE <u>Patricia P. Brown</u>	

NO.	LOCATION	DATE	TIME	WEATHER		SAMPLE TYPE AND METHOD				TIMES CASING CLEARED	NO OF CONTAINERS	ANALYSIS REQUIRED	REMARKS
				TEMP	PREC	COMP.	GRAB	MECH	MAN				
CH-1	WELL 1323						X				1	EXCHANGEABLE CATION (EXC) MINERALOGY (MIN) CATION EXCHANGE CAPACITY (CEC) GRAIN SIZE (GS)	
CH-2	WELL 1323					X					1	CEC, EXC, MIN, GS	
CH-3	WELL 1326					X					1	CEC, EXC, GS	
CH-4	WELL 1328						X				1	CEC, EXC, GS	
CH-5	WELL 1328						X				1	CEC, EXC, GS, MIN	
CH-6	WELL 1336						X				1	CEC, EXC, GS, MIN	
CH-7	WELL 1321						X				1	CEC, EXC, GS	
CH-8	WELL 1321						X				1	MIN.	
CH-9	BORROW MAT'L					X					1	CEC, EXC, GS, MIN	
CH-10	WELL 1324					X					1	CEC, EXC, GS	
CH-11	WELL 1325					X					1	CEC, EXC, GS	

RELINQUISHED BY (SIGNATURE) <u>Patricia P. Brown</u>	RECEIVED BY (SIGNATURE)	DATE	TIME	ADDITIONAL REMARKS
RELINQUISHED BY (SIGNATURE)	RECEIVED BY (SIGNATURE)	DATE	TIME	PLEASE CALL PAT BROWN (303) 779-0576 WITH QUESTIONS.
RELINQUISHED BY (SIGNATURE)	RECEIVED BY (SIGNATURE)	DATE	TIME	
DISPATCHED BY (SIGNATURE)	RECEIVED FOR LABORATORY (SIGNATURE)	DATE	TIME	

CARRIER <u>Fed. Exp. AIRMAIL # 3041510404</u>	LABORATORY <u>DEPT. AGRONOMY &amp; SOIL, AUBURN UNIV.</u>	ALL ANALYSIS PERFORMED BY EPA APPROVED PROCEDURES OR ASTM <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No, explain why
ADDRESS	ADDRESS <u>202 FUNCHESS HALL,</u>	
METHOD OF SHIPMENT	<u>AUBURN, ALA. 36849-5412</u>	



CHAIN OF CUSTODY RECORD— ENVIRONMENTAL SAMPLES KM-4775


FACILITY		SAMPLING FIRM		SAMPLE	
NAME CIMARRON FACILITY		NAME James L. Grant & Assoc.		<input type="checkbox"/> Effluent <input type="checkbox"/> Groundwater <input checked="" type="checkbox"/> Solid <input type="checkbox"/> Surface Water <input type="checkbox"/>	
ADDRESS HIGHWAY 74 CRESCENT, OK 73028		ADDRESS 8301 E. PRENTICE #402, ENCLAWOOD, CO. 80111			
		SIGNATURE <i>Patricia L. Beem</i>			

NO.	LOCATION	DATE	TIME	WEATHER		SAMPLE TYPE AND METHOD					TIMES CASING CLEARED	NO OF CONTAINERS	ANALYSIS REQUIRED	REMARKS
				TEMP	PREC	COMP.	GRAB	MECH	MAN					
CH-12	BORROW MAT'L					X						1	EXCHANGEABLE CATION (EXC) GRAIN SIZE (GS) CATION EXCHANGE CAPACITY (CEC) MINERALOGY (MIN)	
CH-13	WELL 1332					X						1	CEC, EXC, GS	
CH-14	WELL 1334						X					1	CEC, EXC, GS, MIN	
CH-15	WELL 1334						X					1	CEC, EXC, GS, MIN	
CH-16	BORROW MAT'L					X						1	MATRIC POTENTIAL	
CH-17	WELL 1332					X						1	MATRIC POTENTIAL	
CH-18	WELL 1336					X						1	MATRIC POTENTIAL	
CH-19	WELL 1336						X					1	MATRIC POTENTIAL	

RELINQUISHED BY (SIGNATURE) <i>Patricia L. Beem</i>	RECEIVED BY (SIGNATURE)	DATE	TIME	ADDITIONAL REMARKS  PLEASE CALL PAT BEEM (303) 779-0576 WITH QUESTIONS	
RELINQUISHED BY (SIGNATURE)	RECEIVED BY (SIGNATURE)	DATE	TIME		
RELINQUISHED BY (SIGNATURE)	RECEIVED BY (SIGNATURE)	DATE	TIME		
DISPATCHED BY (SIGNATURE)	DATE	TIME	RECEIVED FOR LABORATORY (SIGNATURE)	DATE	TIME
CARRIER FED EXP AIRBILL # 3041510464	LABORATORY DEPT OF AGRONOMY & SOIL, AUBURN UNIV. 202 FUNCHESS HALL AUBURN ALA 36849-5412		ALL ANALYSIS PERFORMED BY EPA APPROVED PROCEDURES OR ASTM <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No (explain below)		

**APPENDIX H**  
**DISTRIBUTION COEFFICIENT ANALYSES**

808211: 9-12-89



JUN 12 1989

Equilibrium Distribution Coefficients -  
Batch Determination Techniques

submitted to

Kerr McGee Tech Center  
Oklahoma City, Oklahoma

June 6, 1989

by

B. F. Hajek



## Equilibrium Distribution Coefficients - Batch Determination Techniques

B. F. Hajek

### Introduction

The equilibrium distribution coefficient ( $K_d$ ) is an easily determined equilibrium constant for trace ion adsorption on soils. In using this coefficient the assumption is made that ion exchange extends over a short, nearly linear, section of an adsorption isotherm. This assumption is usually valid since trace ions are present in small concentrations and do not occupy a significant portion of all ion exchange sites (1, 2, 3).

The  $K_d$  is calculated from data obtained in batch equilibrium tests by use of the equation,

$$K_d = \frac{C_0 - C}{C} \frac{\text{ml soln}}{\text{g soil}}$$

in which  $C_0$  is the initial concentration of radionuclide in solution and  $C$  is the equilibrium concentration after solution - soil contact.

### Batch Equilibrium Method

Five grams of soil obtained from samples collected by test borings are equilibrated with 20 ml of solution by shaking continuously for 16 hours (overnight). The solution used should simulate, as closely as possible, the solution that will actually flow through the soil. This can be groundwater or seepage water obtained on-site, simulated acid process solution, or ground water-acid process solution mixtures. The solution used is traced with ions of interest such as U, Ra, Th, and As. A higher soil-solution ratio may be required for U adsorption tests since adsorption will probably be low (<2). A 1:1 ratio may be needed in this case. A lower ratio may be needed for Ra and Th since  $K_d$ 's may exceed 500 ml/g.

Radionuclide concentration in the equilibrium solution should be such that > 10,000 counts can be accumulated in a reasonable period of time to give a counting error of less than one percent. All  $K_d$  tests should be made in duplicate.

The soil sample is usually that fraction that passes a 2 mm sieve. If porous rock or porous gravel are tested for adsorption the solid-solution ratio should be increased and a value for in-place density (bulk density) will be needed to express adsorption on a volume basis.

Solution characteristics required:

1. initial pH
2. final pH
3. concentration of major competing cations and anions

Soil characteristics:

1. grain size distribution
2. qualitative mineralogy
3. approximate bulk density
4. pH of a 1:1, soil:water suspension

References

1. D. W. Bensen. 1960. Review of soil chemistry research at Hanford. HW-67201. General Electric Co., Richland, Washington.
2. W. J. Kaufman. 1963. An appraisal of the distribution coefficient for estimating underground movement of radioisotopes. HNS-1229-21. Hazelton - Nuclear Sci. Corp., Pal Alto, California.
3. W. E. Prout. 1958. Adsorption of radioactive waste by Savannah River Plant Soil. Soil Sci. Vol. 86, pp. 13-17.

21-Jun-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 14-JUN-89

SAMPLE ID: 967479  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\14-JUN-89\CH-1R  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results by 6-21-89:1705-JAE-18F71  
20 ml Spiked Water:Spiked U232 850pCi/l

Th-228	0.60+-0.52 pCi/l	pH initial	7.45
U232	1.2+-0.60 pCi/l	pH final	7.90

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED:           *D. Keck* 6/21/89    *A. Keck* 6/27/89            
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967484  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-1RR  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results by 6-21-89:1705-JAE-18P72  
100 ml Spiked Water:Spiked U232 850pCi/l

Th-228	1.50+-0.74 pCi/l	pH initial	7.11
U232	7.5+-1.5 pCi/l	pH final	7.38

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: *Dash-Gibbs J. Kerr*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

27-Jun-1989  
SAMPLE ID: 967474  
07:53 a.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-1X  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967474  
XRD of crystalline phases  
1688-JAH-22P82;1724-SMA-6P4,5,11,12

Major	Quartz = SiO <sub>2</sub>	+20	45.72 %
Accessory	<u>I, M, F</u>	+60	73.05 %
Bulk Density	77 lbs/ft <sup>3</sup>	+100	77.60 %
pH of 1:1 soil	7.6	+200	82.41 %
+8	0.17 %	+325	87.04 %

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
\*  
\* APPROVED: CDE 6-27-89 OB 6-27-89 Dal \*  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

- I - Illite clay -  $(K, H_3O)Al_2Si_3AlO_{10}(OH)_2$
- M - Montmorillonite - Chlorite clay
- F - Feldspar -  $NaAlSi_3O_8$

SIEMENS D-500

( K H<sub>3</sub> O ) AL<sub>2</sub> S  
CH-1

SI 02 \*4


( 1.6 AL ) 0 ( 31

NA AL SI3 08\*4

MEAS50.SNO  
33-1161  
12-2-82  
10-393  
28-811

INTENSITY (CPS)

\*10



TWO - THETA (DEGREES)

21-Jun-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967480  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-5R  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results needed by 6-21-89  
20 ml Spiked Water; Spiked U232 850pCi/l

Th-228	0.90+-0.60 pCi/l	pH initial	7.45
U232	2.7+-0.90 pCi/l	pH final	7.76

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: *[Signature]* 6/21/89 *A. Kirk*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967485  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-5RR  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results needed by 6-21-89  
100 ml Spiked Water: Spiked U232 850pCi/l

Th-228	0.90+-0.60 pCi/l	pH initial	7.22
U232	3.6+-1.0 pCi/l	pH final	7.46

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.


\*\*\*\*\*  
 \*  
 \* APPROVED: *D. Keck* \_\_\_\_\_  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.







AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967481  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-6R  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results needed by 6-21-89  
20 ml Spiked Water; Spiked U232 850pCi/l

Th-228	0.60+-0.52 pCi/l	pH initial	7.50
U232	9.3+-1.7 pCi/l	pH final	7.82

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: *Derek White, J Kerr* \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967486  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-6RR  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results needed by 6-21-89  
100 ml Spiked Water; Spiked U232 850pCi/l

Th-228	0.90+-0.60 pCi/l	pH initial	7.19
U232	9.9+-1.7 pCi/l	pH final	7.40

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: *Dashley D. Kelle*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

27-Jun-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967476  
08:17 a.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-6X  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967474  
XRD on crystalline phases

Major	Quartz = SiO <sub>2</sub>	+20	41.63 %
Accessory	<u>I, M, F</u>	+60	80.97 %
Bulk Density	77 lbs/ft <sup>3</sup>	+100	88.43 %
pH of 1:1 soil	8.1	+200	94.85 %
+8	0.14 %	+325	97.83 %

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
\*  
\* APPROVED: CWE AB  
\* 6-27-89 6-27-89  
\*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

I - Illite clay -  $(K, H_3O)Al_2Si_3AlO_{10}(OH)_2$   
M - Montmorillonite - Chlorite clay  
F - Feldspar -  $NaAlSi_3O_8$

SIEMENS D-500


( K H<sub>3</sub> D ) AL<sub>2</sub> S  
CH-8 WELL 1338

SI 02 \*4

( MG AL ) 0 ( 01

NA AL SI3 08\*4

MEAS52.SMO  
33-1161  
12-0-02  
10-393  
28-811



AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967482  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-8R  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results needed by 6-21-89  
20 ml Spiked Water: Spiked U232 850pCi/l

Th-228	1.20+-0.42 pCi/l	pH initial	7.49
U232	1.2+-0.60 pCi/l	pH final	7.75

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: *Dick* *6/21/89* *D. Keck* \*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

21-Jun-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967487  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-8RR  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results needed by 6-21-89  
100 ml Spiked Water: Spiked U232 850pCi/l

Th-228	0.90+-0.60 pCi/l	pH initial	7.20
U232	1.5+-0.67 pCi/l	pH final	7.42

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: *D. K. Kerr*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.



AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

27-Jun-1989  
SAMPLE ID: 967477  
07:53 a.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-8X  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967474  
XRD of crystalline phases

Major	Quartz = SiO <sub>2</sub>	+20	11.72 %
Accessory	C, D, I, M	+60	29.35 %
Bulk Density	84 lbs/ft <sup>3</sup>	+100	57.80 %
pH of 1:1 soil	8.2	+200	91.93 %
+8	0.01 %	+325	97.14 %

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
\*  
\* APPROVED: CWE AB  
\* 6-27-89 06-27-89 \*  
\*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

- C - Calcite - CaCO<sub>3</sub>
- D - Dolomite - CaMg(CO<sub>3</sub>)<sub>2</sub>
- I - Illite clay - (K, H<sub>3</sub>O)Al<sub>2</sub>Si<sub>3</sub>AlO<sub>10</sub>(OH)<sub>2</sub>
- M - Montmorillonite - Chlorite clay

SIEMENS D-500


CA C 03 \*4  
CH-8 WELL 1321

SI 02 \*4

(HG AL.) & (SI

(K H3 O) AL2 S

MEAS53.SMO  
33-1161  
12-272  
26-911  
5-588



21-Jun-1989

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967483  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-14R  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results needed by 6-21-89  
20 ml Spiked Water: Spiked U232 850pCi/l

Th-228	1.20+-0.42 pCi/l	pH initial	7.50
U232	3.0+-0.95 pCi/l	pH final	7.82

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: *D. Keck 6/21/89* *D. Keck*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

AFE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967488  
02:27 p.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-14RR  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967479  
Results needed by 6-21-89  
100 ml Spiked Water: Spiked U232 850pCi/l

Th-228	0.60+-0.52 pCi/l	pH initial	7.23
U232	2.1+-0.99 pCi/l	pH final	7.46

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: *[Signature]*  
 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

27-Jun-1989

APE/PROJECT NUMBER: 84007  
DATE RECEIVED: 12-JUN-89

SAMPLE ID: 967478  
07:53 a.m.

LOCATION: Cimarron  
SUBMITTED BY: R. Fine

SAMPLE NAME: RF \CIM\12-JUN-89\ CH-14X  
SAMPLE DESCRIPTION: Soil

NOTES: NBR same as 967474  
XRD of crystalline phases

Major Quartz = $\text{SiO}_2$ & Dolomite = $\text{CaMg}(\text{CO}_3)$	+20	26.23 %
Accessory <u>C, I, M</u>	+60	58.53 %
Bulk Density	84 lbs/ft <sup>3</sup>	+100
		68.44 %
pH of 1:1 soil	8.7	+200
		84.63 %
+8	0.05 %	+325
		92.63 %

Where noted by a "\*", the analysis follows an indirect methodology and the concentration noted is inferred from the test protocol.

\*\*\*\*\*  
 \*  
 \* APPROVED: CQE AB  
 \* 6-27-89 6-27-89 \*  
 \*\*\*\*\*

KERR-MCGEE CORPORATION Technology Division  
Proprietary Information of the Company TO BE KEPT CONFIDENTIAL

This/these samples are being returned to you.

- C - Calcite -  $\text{CaCO}_3$
- I - Illite clay -  $(\text{K}, \text{H}_3\text{O})\text{Al}_2\text{Si}_3\text{AlO}_{10}(\text{OH})_2$
- M - Montmorillonite - Chlorite clay


SIEMENS D-500

CA C 03 \*4  
CH-14 WELL 1344

SI 02 \*4

( NG AL ) G ( 01

( K H3 O ) AL2 S



**CHAIN OF CUSTODY RECORD— ENVIRONMENTAL SAMPLES** KM-4775

6-12-89

<b>FACILITY</b>	<b>SAMPLING FIRM</b>	<b>SAMPLE</b>
NAME <b>CIMARRON FACILITY</b>	NAME <b>CIMARRON CORP</b>	<input type="checkbox"/> Effluent <input type="checkbox"/> Groundwater <input type="checkbox"/> Solid <input type="checkbox"/> Surface Water <input type="checkbox"/>
ADDRESS <b>CRESCENT, OK</b>	ADDRESS <b>CRESCENT, OK</b>	
	SIGNATURE <b>Roll J Li</b>	

NO.	LOCATION	DATE	TIME	WEATHER		SAMPLE TYPE AND METHOD				TIMES CASING CLEARED	NO OF CONTAINERS	ANALYSIS REQUIRED	REMARKS
				TEMP.	PREC.	COMP.	GRAB	MECH	MAN.				
1	1324 A	6-12-89					X			5	2	DISTRIBUTION COEFFICIENT ANALYSIS	TWO ONE GALLON CUBI- TAINERS

RELINQUISHED BY (SIGNATURE) <b>Roll J Li</b>	RECEIVED BY (SIGNATURE)	DATE	TIME	ADDITIONAL REMARKS This sample submitted at request of PAT BREENE, J.L. GRANT ASSOC., for analysis as discussed with Dr. Van de Steeg.
RELINQUISHED BY (SIGNATURE)	RECEIVED BY (SIGNATURE)	DATE	TIME	
RELINQUISHED BY (SIGNATURE)	RECEIVED BY (SIGNATURE)	DATE	TIME	
DISPATCHED BY (SIGNATURE)	RECEIVED FOR LABORATORY (SIGNATURE) <b>Quay Stewart</b>	DATE <b>6/28/89</b>	TIME <b>8:00</b>	
CARRIER	LABORATORY			ALL ANALYSIS PERFORMED BY EPA APPROVED PROCEDURES <input type="checkbox"/> Yes <input type="checkbox"/> No, explain above
ADDRESS	ADDRESS			
METHOD OF SHIPMENT				

**APPENDIX I**  
**HELP MODEL SIMULATIONS**

808211: 9-12-89



DEFAULT, UNVEGETATED, UNCOMPACTED SOIL CHARACTERISTICS

SOIL TEXTURE			DIMENSIONLESS			SAT. HYD.
HELP	USDA	USCS	POROSITY	FIELD CAPACITY	WILTING POINT	CONDUCTIVITY (CM/SEC)
1	CoS	GS	0.417	0.045	0.018	1.0E-02
2	S	SW	0.437	0.062	0.024	5.8E-03
3	FS	SM	0.457	0.083	0.033	3.1E-03
4	LS	SM	0.437	0.105	0.047	1.7E-03
5	LFS	SM	0.457	0.131	0.058	1.0E-03
6	SL	SM	0.453	0.190	0.085	7.2E-04
7	FSL	SM	0.473	0.222	0.104	5.2E-04
8	L	ML	0.463	0.232	0.116	3.7E-04
9	SiL	ML	0.501	0.284	0.135	1.9E-04
10	SCL	SC	0.398	0.244	0.136	1.2E-04
11	CL	CL	0.464	0.310	0.187	6.4E-05
12	SiCL	CL	0.471	0.342	0.210	4.2E-05
13	SC	CH	0.430	0.321	0.221	3.3E-05

ENTER RETURN TO VIEW THE REST OF THE SOIL TYPES.

11	CL	CL	0.464	0.310	0.187	6.4E-05
12	SiCL	CL	0.471	0.342	0.210	4.2E-05
13	SC	CH	0.430	0.321	0.221	3.3E-05

ENTER RETURN TO VIEW THE REST OF THE SOIL TYPES.

SOIL TEXTURE			DIMENSIONLESS			SAT. HYD.
HELP	USDA	USCS	POROSITY	FIELD CAPACITY	WILTING POINT	CONDUCTIVITY (CM/SEC)
14	SiC	CH	0.479	0.371	0.251	2.5E-05
15	C	CH	0.475	0.378	0.265	1.7E-05
16	Liner Soil		0.430	0.366	0.280	1.0E-07
17	Liner Soil		0.400	0.356	0.290	1.0E-08
18	Mun. Waste		0.520	0.294	0.140	2.0E-04
19	USER SPECIFIED SOIL CHARACTERISTICS					
20	USER SPECIFIED SOIL CHARACTERISTICS					

5.9 ENTER SOIL TEXTURE OF SOIL LAYER 1.

2.67  
.67

\*\*\*\*\*  
 \*\*\*\*\*

CIMARRON DECOMMISSIONING PROGRAM, CASE LF1  
 CIMARRON FUEL FABRICATION FACILITY  
 05-22-89

\*\*\*\*\*  
 \*\*\*\*\*

LAYER 1  
 -----

\*\*\*\*\*

AVERAGE MONTHLY VALUES IN INCHES FOR 1 THROUGH 20  
 -----

	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
<u>PRECIPITATION</u>						
TOTALS	0.87 2.88	1.25 2.27	2.09 4.40	3.04 3.27	4.85 1.77	3.03 1.13
STD. DEVIATIONS	0.55 1.97	0.75 1.59	1.10 2.55	1.90 2.00	2.74 1.67	1.27 0.77
<u>RUNOFF</u>						
TOTALS	0.011 0.010	0.012 0.000	0.045 0.013	0.357 0.120	0.883 0.159	0.039 0.039
STD. DEVIATIONS	0.050 0.044	0.052 0.000	0.119 0.037	0.707 0.347	1.398 0.597	0.120 0.122
<u>EVAPOTRANSPIRATION</u>						
TOTALS	0.790 4.491	0.882 2.456	1.456 2.689	1.789 1.727	3.284 1.044	6.254 0.857
STD. DEVIATIONS	0.384 2.071	0.479 1.330	0.617 1.202	0.611 0.563	0.705 0.384	0.672 0.421
<u>PERCOLATION FROM LAYER 2</u>						
TOTALS	0.1267 0.0440	0.1199 0.0000	0.1494 0.0049	0.1771 0.0652	0.2237 0.1075	0.1723 0.1332
STD. DEVIATIONS	0.1109	0.1096	0.1121	0.0990	0.0723	0.0702

\*\*\*\*\*

\*\*\*\*\*

AVERAGE ANNUAL TOTALS (AND STD. DEVIATIONS) FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)	PERCENT
PRECIPITATION	30.85 ( 5.709)	257075.	100.00
RUNOFF	1.687 ( 2.218)	14056.	5.47
EVAPOTRANSPIRATION	27.719 ( 3.734)	230989.	89.85
PERCOLATION FROM LAYER 2	1.3239 ( 0.5450)	11033.	4.29

\*\*\*\*\*

\*\*\*\*\*

PEAK DAILY VALUES FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)
PRECIPITATION	4.63	38583.3
RUNOFF	3.217	26805.3
PERCOLATION FROM LAYER 2	0.0103	85.5
HEAD ON LAYER 2	24.3	
SNOW WATER	1.28	10681.1
MAXIMUM VEG. SOIL WATER (VOL/VOL)	0.4200	
MINIMUM VEG. SOIL WATER (VOL/VOL)	0.1028	

\*\*\*\*\*

\*\*\*\*\*  
\*\*\*\*\*

CIMARRON DECOMMISSIONING PROGRAM, CASE LF2  
CIMARRON FUEL FABRICATION FACILITY  
5-22-89

\*\*\*\*\*  
\*\*\*\*\*

LAYER 1  
-----

VERTICAL PERCOLATION LAYER

THICKNESS	=	24.00 INCHES
POROSITY	=	0.4200 VOL/VOL
FIELD CAPACITY	=	0.2400 VOL/VOL
WILTING POINT	=	0.1040 VOL/VOL
INITIAL SOIL WATER CONTENT	=	0.1886 VOL/VOL
SATURATED HYDRAULIC CONDUCTIVITY	=	0.0000999999975 CM/SEC

LAYER 2  
-----

BARRIER SOIL LINER

THICKNESS	=	12.00 INCHES
POROSITY	=	0.3300 VOL/VOL
FIELD CAPACITY	=	0.2400 VOL/VOL
WILTING POINT	=	0.1040 VOL/VOL
INITIAL SOIL WATER CONTENT	=	0.3300 VOL/VOL
SATURATED HYDRAULIC CONDUCTIVITY	=	0.0000010000000 CM/SEC

GENERAL SIMULATION DATA  
-----

SCS RUNOFF CURVE NUMBER	=	65.00
TOTAL AREA OF COVER	=	100000. SQ FT
EVAPORATIVE ZONE DEPTH	=	24.00 INCHES
UPPER LIMIT VEG. STORAGE	=	10.0800 INCHES
INITIAL VEG. STORAGE	=	4.5275 INCHES

SOIL WATER CONTENT INITIALIZED BY PROGRAM.

CLIMATOLOGICAL DATA

---

SYNTHETIC RAINFALL WITH SYNTHETIC DAILY TEMPERATURES AND  
SOLAR RADIATION FOR                   OKLAHOMA CITY                   OKLAHOMA

MAXIMUM LEAF AREA INDEX   = 2.00  
 START OF GROWING SEASON (JULIAN DATE)                             = 98  
 END OF GROWING SEASON (JULIAN DATE)                               = 307

\*\*\*\*\*

AVERAGE MONTHLY VALUES IN INCHES FOR     1 THROUGH     20

---

	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
<u>PRECIPITATION</u>						
TOTALS	0.87 2.88	1.25 2.27	2.09 4.40	3.04 3.27	4.65 1.77	3.03 1.13
STD. DEVIATIONS	0.55 1.97	0.75 1.59	1.10 2.55	1.90 2.00	2.74 1.67	1.27 0.77
<u>RUNOFF</u>						
TOTALS	0.000 0.010	0.000 0.000	0.000 0.012	0.051 0.121	0.234 0.057	0.000 0.000
STD. DEVIATIONS	0.000 0.045	0.000 0.000	0.000 0.037	0.201 0.349	0.505 0.257	0.000 0.000
<u>EVAPOTRANSPIRATION</u>						
TOTALS	0.781 3.007	0.885 2.449	1.459 2.691	1.803 1.745	3.306 1.037	5.454 0.858
STD. DEVIATIONS	0.372 1.768	0.482 1.325	0.618 1.217	0.613 0.566	0.751 0.396	1.133 0.410
<u>PERCOLATION FROM LAYER 2</u>						
TOTALS	0.2337 0.0348	0.2089 0.0000	0.3218 0.0447	0.6076 0.5105	1.0633 0.6927	0.5912 0.5559
STD. DEVIATIONS	0.4050 0.0962	0.2692 0.0000	0.3677 0.1061	0.5195 0.7241	0.8079 0.7733	0.6397 0.6571

\*\*\*\*\*

\*\*\*\*\*

AVERAGE ANNUAL TOTALS (AND STD. DEVIATIONS) FOR     1 THROUGH     20

---

	(INCHES)	(CU. FT.)	PERCENT
PRECIPITATION	30.85     ( 5.709)	257075.	100.00

RUNOFF	0.425	( 0.923)	4043.	1.57
EVAPOTRANSPIRATION	25.477	( 3.570)	212310.	32.59
PERCOLATION FROM LAYER 2	4.8651	( 2.6231)	40542.	15.77

\*\*\*\*\*

\*\*\*\*\*

PEAK DAILY VALUES FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)
PRECIPITATION	4.63	38583.3
RUNOFF	1.566	13053.3
PERCOLATION FROM LAYER 2	0.1018	848.2
HEAD ON LAYER 2	24.1	
SNOW WATER	1.28	10681.1
MAXIMUM VEG. SOIL WATER (VOL/VOL)	0.4200	
MINIMUM VEG. SOIL WATER (VOL/VOL)	0.1028	

\*\*\*\*\*

\*\*\*\*\*  
 \*\*\*\*\*

CIMARRON DECOMMISSIONING PROGRAM, CASE LF3  
 CIMARRON FUEL FABRICATION FACILITY  
 05-22-89

\*\*\*\*\*  
 \*\*\*\*\*

LAYER 1  
 -----

VERTICAL PERCOLATION LAYER

THICKNESS = 24.00 INCHES  
 POROSITY = 0.4200 VOL/VOL  
 FIELD CAPACITY = 0.2900 VOL/VOL  
 WILTING POINT = 0.1870 VOL/VOL  
 INITIAL SOIL WATER CONTENT = 0.2544 VOL/VOL  
 SATURATED HYDRAULIC CONDUCTIVITY = 0.0000499999987 CM/SEC

LAYER 2  
 -----

BARRIER SOIL LINER

THICKNESS = 12.00 INCHES  
 POROSITY = 0.3300 VOL/VOL  
 FIELD CAPACITY = 0.2900 VOL/VOL  
 WILTING POINT = 0.1870 VOL/VOL  
 INITIAL SOIL WATER CONTENT = 0.3300 VOL/VOL  
 SATURATED HYDRAULIC CONDUCTIVITY = 0.0000001000000 CM/SEC

\*\*\*\*\*

AVERAGE MONTHLY VALUES IN INCHES FOR 1 THROUGH 20

	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
PRECIPITATION						
TOTALS	0.87	1.25	2.09	3.04	4.85	3.03
	2.68	2.27	4.46	5.27	1.77	1.13

1.97 1.59 2.55 2.00 1.67 0.77

RUNOFF

TOTALS	0.009 0.124	0.000 0.034	0.063 0.305	0.467 0.407	1.109 0.188	0.085 0.030
STD. DEVIATIONS	0.039 0.326	0.000 0.124	0.178 0.476	0.828 0.736	1.452 0.688	0.181 0.093

EVAPOTRANSPIRATION

TOTALS	0.836 3.092	0.947 2.388	1.532 2.741	1.900 1.844	3.498 1.094	5.878 0.925
STD. DEVIATIONS	0.388 1.878	0.493 1.342	0.728 1.215	0.655 0.624	0.824 0.446	1.025 0.450

PERCOLATION FROM LAYER 2

TOTALS	0.1247 0.0093	0.1184 0.0000	0.1476 0.0050	0.1765 0.0621	0.2169 0.1110	0.1328 0.1387
STD. DEVIATIONS	0.1149 0.0174	0.1046 0.0000	0.1153 0.0115	0.0964 0.0980	0.0729 0.1149	0.0639 0.1163

\*\*\*\*\*

\*\*\*\*\*

AVERAGE ANNUAL TOTALS (AND STD. DEVIATIONS) FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)	PERCENT
PRECIPITATION	30.85 ( 5.709)	257075.	100.00
RUNOFF	2.822 ( 2.657)	23513.	9.15
EVAPOTRANSPIRATION	26.676 ( 3.673)	222303.	86.47
PERCOLATION FROM LAYER 2	1.2427 ( 0.5148)	10356.	4.03

\*\*\*\*\*

\*\*\*\*\*

PEAK DAILY VALUES FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)
PRECIPITATION	4.63	38583.3
RUNOFF	3.177	26478.0
PERCOLATION FROM LAYER 2	0.0102	85.4
HEAD ON LAYER 2	24.2	



SNOW WATER

1.28

10283.1

MAXIMUM VEG. SOIL WATER (VOL/VOL) 0.4200

MINIMUM VEG. SOIL WATER (VOL/VOL) 0.1857

\*\*\*\*\*  
\*\*\*\*\*

\*\*\*\*\*  
 \*\*\*\*\*

CIMARRON DECOMMISSIONING PROGRAM, CASE LF4  
 CIMARRON FUEL FABRICATION FACILITY  
 05-22-89

\*\*\*\*\*  
 \*\*\*\*\*

LAYER 1  
 -----

VERTICAL PERCOLATION LAYER

THICKNESS = 24.00 INCHES  
 POROSITY = 0.4200 VOL/VOL  
 FIELD CAPACITY = 0.2400 VOL/VOL  
 WILTING POINT = 0.1040 VOL/VOL  
 INITIAL SOIL WATER CONTENT = 0.1876 VOL/VOL  
 SATURATED HYDRAULIC CONDUCTIVITY = 0.0000999999975 CM/SEC

LAYER 2  
 -----

BARRIER SOIL LINER

THICKNESS = 12.00 INCHES  
 POROSITY = 0.3300 VOL/VOL  
 FIELD CAPACITY = 0.2900 VOL/VOL  
 WILTING POINT = 0.1870 VOL/VOL  
 INITIAL SOIL WATER CONTENT = 0.3300 VOL/VOL  
 SATURATED HYDRAULIC CONDUCTIVITY = 0.0000000100000 CM/SEC

\*\*\*\*\*

AVERAGE MONTHLY VALUES IN INCHES FOR 1 THROUGH 20

PRECIPITATION	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
TOTALS	0.87	1.25	2.09	3.04	4.85	3.03
	2.88	2.27	4.40	3.27	1.77	1.13

1.97 1.59 2.55 2.00 1.67 0.77

RUNOFF

TOTALS	0.032	0.076	0.224	0.543	1.168	0.075
	0.010	0.000	0.013	0.127	0.176	0.063
STD. DEVIATIONS	0.102	0.229	0.469	0.946	1.525	0.251
	0.044	0.000	0.037	0.356	0.654	0.197

EVAPOTRANSPIRATION

TOTALS	0.789	0.887	1.461	1.788	3.221	6.315
	4.833	2.458	2.690	1.722	1.043	0.859
STD. DEVIATIONS	0.383	0.478	0.617	0.611	0.689	0.574
	1.990	1.338	1.199	0.560	0.384	0.422

PERCOLATION FROM LAYER 2

TOTALS	0.0137	0.0132	0.0164	0.0189	0.0235	0.0185
	0.0057	0.0000	0.0005	0.0066	0.0111	0.0140
STD. DEVIATIONS	0.0132	0.0119	0.0127	0.0106	0.0080	0.0069
	0.0047	0.0000	0.0011	0.0097	0.0124	0.0129

\*\*\*\*\*

\*\*\*\*\*

AVERAGE ANNUAL TOTALS (AND STD. DEVIATIONS) FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)	PERCENT
PRECIPITATION	30.85 ( 5.709)	257075.	100.00
RUNOFF	2.508 ( 2.687)	20899.	8.13
EVAPOTRANSPIRATION	28.066 ( 3.508)	233886.	90.98
PERCOLATION FROM LAYER 2	0.1422 ( 0.0574)	1185.	0.46

\*\*\*\*\*

\*\*\*\*\*

PEAK DAILY VALUES FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)
PRECIPITATION	4.63	38583.3
RUNOFF	3.312	27598.7
PERCOLATION FROM LAYER 2	0.0010	8.6
HEAD ON LAYER 2	24.3	

MAXIMUM VEG. SOIL WATER (VOL/VOL) 0.4200

MINIMUM VEG. SOIL WATER (VOL/VOL) 0.1028

\*\*\*\*\*  
\*\*\*\*\*

\*\*\*\*\*  
\*\*\*\*\*

CIMARRON DECOMMISSIONING PROGRAM, CASE NA1  
CIMARRON FUEL FABRICATION FACILITY  
05-22-89

\*\*\*\*\*  
\*\*\*\*\*

LAYER 1  
-----

VERTICAL PERCOLATION LAYER

THICKNESS	=	36.00 INCHES
POROSITY	=	0.4200 VOL/VOL
FIELD CAPACITY	=	0.2400 VOL/VOL
WILTING POINT	=	0.1040 VOL/VOL
INITIAL SOIL WATER CONTENT	=	0.2056 VOL/VOL
SATURATED HYDRAULIC CONDUCTIVITY	=	0.0000999999975 CM/SEC

LAYER 2  
-----

THICKNESS	=	12.00 INCHES
POROSITY	=	0.3300 VOL/VOL
FIELD CAPACITY	=	0.2400 VOL/VOL
WILTING POINT	=	0.1040 VOL/VOL
INITIAL SOIL WATER CONTENT	=	0.3300 VOL/VOL
SATURATED HYDRAULIC CONDUCTIVITY	=	0.0000010000000 CM/SEC

\*\*\*\*\*

AVERAGE MONTHLY VALUES IN INCHES FOR 1 THROUGH 20

	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
<u>PRECIPITATION</u>						
TOTALS	0.87 2.88	1.25 2.27	2.09 4.40	3.04 3.27	4.85 1.77	3.03 1.13
STD. DEVIATIONS	0.55 1.97	0.75 1.59	1.10 2.55	1.90 2.00	2.74 1.67	1.27 0.77
<u>RUNOFF</u>						
TOTALS	0.000 0.010	0.000 0.000	0.000 0.012	0.051 0.121	0.152 0.012	0.000 0.000
STD. DEVIATIONS	0.000 0.045	0.000 0.000	0.000 0.037	0.202 0.349	0.350 0.054	0.000 0.000
<u>EVAPOTRANSPIRATION</u>						
TOTALS	0.780 2.914	0.885 2.449	1.459 2.698	1.803 1.741	3.306 1.039	5.253 0.866
STD. DEVIATIONS	0.370 1.768	0.482 1.325	0.618 1.212	0.613 0.572	0.752 0.395	1.204 0.421
<u>PERCOLATION FROM LAYER 2</u>						
TOTALS	0.2733 0.2592	0.2087 0.0077	0.3131 0.0369	0.5762 0.4647	1.0641 0.6638	0.7856 0.6193
STD. DEVIATIONS	0.4515 0.4416	0.2976 0.0346	0.3449 0.0879	0.4838 0.6657	0.7934 0.7562	0.7764 0.7237

\*\*\*\*\*

\*\*\*\*\*

AVERAGE ANNUAL TOTALS (AND STD. DEVIATIONS) FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)	PERCENT
PRECIPITATION	30.85 ( 5.709)	257075.	100.00
RUNOFF	0.038 ( 0.892)	3964.	1.54

EVAPOTRANSPIRATION	25.192 ( 3.646)	209936.	31.66
PERCOLATION FROM LAYER 2	5.2727 ( 2.9241)	43939.	17.09

\*\*\*\*\*

\*\*\*\*\*

PEAK DAILY VALUES FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)
PRECIPITATION	4.63	38583.3
RUNOFF	1.519	12658.6
PERCOLATION FROM LAYER 2	0.1086	904.7
HEAD ON LAYER 2	26.4	
SNOW WATER	1.28	10681.1
MAXIMUM VEG. SOIL WATER (VOL/VOL)	0.3921	
MINIMUM VEG. SOIL WATER (VOL/VOL)	0.1028	

\*\*\*\*\*  
\*\*\*\*\*

\*\*\*\*\*  
 \*\*\*\*\*

CIMARRON DECOMMISSIONING PROGRAM, CASE NA2  
 CIMARRON FUEL FABRICATION FACILITY  
 05-22-89

\*\*\*\*\*  
 \*\*\*\*\*

LAYER 1  
 -----

VERTICAL PERCOLATION LAYER

THICKNESS = 36.00 INCHES  
 POROSITY = 0.4200 VOL/VOL  
 FIELD CAPACITY = 0.2900 VOL/VOL  
 WILTING POINT = 0.1870 VOL/VOL  
 INITIAL SOIL WATER CONTENT = 0.2497 VOL/VOL  
 SATURATED HYDRAULIC CONDUCTIVITY = 0.0000499999987 CM/SEC

LAYER 2  
 -----

BARRIER SOIL LINER

THICKNESS = 12.00 INCHES  
 POROSITY = 0.3300 VOL/VOL  
 FIELD CAPACITY = 0.2900 VOL/VOL  
 WILTING POINT = 0.1870 VOL/VOL  
 INITIAL SOIL WATER CONTENT = 0.3300 VOL/VOL  
 SATURATED HYDRAULIC CONDUCTIVITY = 0.0000010000000 CM/SEC

\*\*\*\*\*

AVERAGE MONTHLY VALUES IN INCHES FOR 1 THROUGH 20  
 -----

	JAN/JUL	FEB/AUG	MAR/SEP	APR/OCT	MAY/NOV	JUN/DEC
PRECIPITATION	-----					
TOTALS	0.87	1.25	2.09	3.04	4.85	3.03
	2.88	2.27	4.40	3.07	1.77	1.13

1.97 1.59 2.55 2.00 1.67 0.77

RUNOFF

TOTALS	0.000	0.000	0.014	0.189	0.577	0.035
	0.125	0.034	0.306	0.397	0.082	0.000
STD. DEVIATIONS	0.000	0.000	0.061	0.472	0.893	0.108
	0.326	0.124	0.476	0.750	0.355	0.000

EVAPOTRANSPIRATION

TOTALS	0.834	0.948	1.540	1.906	3.542	4.823
	2.697	2.387	2.735	1.834	1.102	0.923
STD. DEVIATIONS	0.395	0.496	0.721	0.657	0.867	1.291
	1.779	1.344	1.208	0.640	0.437	0.460

PERCOLATION FROM LAYER 2

TOTALS	0.1773	0.1476	0.2632	0.4975	0.8370	0.4777
	0.0295	0.0000	0.0339	0.3759	0.5397	0.3885
STD. DEVIATIONS	0.3343	0.1813	0.3549	0.4833	0.7287	0.5712
	0.1132	0.0000	0.0826	0.5893	0.5925	0.5714

\*\*\*\*\*

\*\*\*\*\*

AVERAGE ANNUAL TOTALS (AND STD. DEVIATIONS) FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)	PERCENT
PRECIPITATION	30.85 ( 5.709)	257075.	100.00
RUNOFF	1.759 ( 1.950)	14658.	5.70
EVAPOTRANSPIRATION	25.271 ( 3.707)	210591.	81.92
PERCOLATION FROM LAYER 2	3.7678 ( 2.1737)	31398.	12.21

\*\*\*\*\*

\*\*\*\*\*

PEAK DAILY VALUES FOR 1 THROUGH 20

	(INCHES)	(CU. FT.)
PRECIPITATION	4.63	38583.3
RUNOFF	2.789	23242.1
PERCOLATION FROM LAYER 2	0.1119	932.6
HEAD ON LAYER 2	27.6	



SNOW WATER

1.28

10681.1

MAXIMUM VEG. SOIL WATER (VOL/VOL) 0.4141

MINIMUM VEG. SOIL WATER (VOL/VOL) 0.1856

\*\*\*\*\*  
\*\*\*\*\*

**APPENDIX J**  
**TRANSS MODEL SIMULATIONS**

808211: 9-12-89

```

*****
*
*       ONE-DIMENSIONAL CONVECTIVE-DISPERSIVE EQUATION
*       *11/26/85* VERSION
*       SEMI-INFINITE PROFILE
*
*       NUCLIDE DECAY (THALF)
*       LINEAR ADSORPTION (R)
*       GENERAL NUCLIDE RELEASE CURVE
*       TRANSPORT SUM OVER PATHLINES
*
*       CIMARRON LANDFILL: Kd=2000 controlled release - U-238
*       VADOSE ZONE
*****

```

NUCLIDE: U-238

INPUT PARAMETERS  
=====

```

V =          1.38           D =          1.00
R =        10600.0         T0 = 4.4377E+05
TOTAL =1.81E+12          TDECAY=0.000E-01
THALF=  4.5000E+09       CO =  1.931E+06
XL =2.0000E+01
NUCLIDE DECAY CONSTANT = 1.54033E-10

```

CONTROL FLAGS:  
IOPTBC= 0 IFLUX= 0 ITYPE= 1 IOPT= 3

RELEASE MODEL PARAMETERS:  
PLAN VIEW AREA=8.0000E+04  
DEPTH=1.0000E+01  
WATER FLUX Q=3.3000E-01  
THETA =0.3000  
MAX CONCENTRATION=1.0000E+12  
RELEASE CURVE ERROR=1.0000E-02

FRACTION REMAINING CURVE  
TIME                    FRACTION

0.00E-01	1.00000
1.73E+03	0.98199
3.46E+03	0.96437
5.18E+03	0.94713
6.89E+03	0.93027
8.60E+03	0.91376
1.03E+04	0.89760
1.20E+04	0.88179
1.37E+04	0.86632
1.54E+04	0.85117
1.70E+04	0.83634
1.87E+04	0.82183
2.04E+04	0.80762

2.20E+04	0.79370
2.37E+04	0.78008
2.53E+04	0.76673
2.69E+04	0.75367
2.86E+04	0.74087
3.02E+04	0.72834
3.18E+04	0.71606
3.34E+04	0.70403
3.50E+04	0.69225
3.66E+04	0.68071
3.82E+04	0.66940
3.98E+04	0.65832
4.14E+04	0.64746
4.29E+04	0.63683
4.45E+04	0.62640
4.61E+04	0.61618
4.76E+04	0.60616
4.92E+04	0.59635
5.07E+04	0.58672
5.22E+04	0.57729
5.38E+04	0.56804
5.53E+04	0.55897
5.68E+04	0.55008
5.83E+04	0.54136
5.98E+04	0.53281
6.13E+04	0.52443
6.28E+04	0.51621
6.43E+04	0.50814
6.58E+04	0.50023
6.73E+04	0.49247
6.87E+04	0.48486
7.02E+04	0.47739
7.17E+04	0.47006
7.31E+04	0.46288
7.46E+04	0.45582
7.60E+04	0.44890
7.74E+04	0.44211
7.89E+04	0.43544
8.03E+04	0.42890
8.17E+04	0.42248
8.31E+04	0.41618
8.45E+04	0.40999
8.59E+04	0.40392
8.73E+04	0.39796
8.87E+04	0.39210
9.01E+04	0.38636
9.15E+04	0.38071
9.29E+04	0.37517
9.43E+04	0.36973
9.56E+04	0.36439
9.70E+04	0.35914
9.83E+04	0.35399
9.97E+04	0.34892
1.01E+05	0.34395
1.02E+05	0.33906
1.04E+05	0.33427
1.05E+05	0.32955
1.06E+05	0.32492
1.08E+05	0.32037
1.09E+05	0.31590

1.10E+05	0.31150
1.12E+05	0.30718
1.13E+05	0.30294
1.14E+05	0.29877
1.15E+05	0.29467
1.17E+05	0.29064
1.18E+05	0.28668
1.19E+05	0.28279
1.21E+05	0.27896
1.22E+05	0.27520
1.23E+05	0.27150
1.24E+05	0.26786
1.26E+05	0.26428
1.27E+05	0.26077
1.28E+05	0.25731
1.29E+05	0.25391
1.31E+05	0.25057
1.32E+05	0.24728
1.33E+05	0.24404
1.34E+05	0.24086
1.35E+05	0.23773
1.37E+05	0.23465
1.38E+05	0.23162
1.39E+05	0.22864
1.40E+05	0.22571
1.41E+05	0.22283
1.43E+05	0.21999
1.44E+05	0.21720
1.45E+05	0.00000

RELEASE INTERVAL NUMBER= 102

PATHLINE PARAMETERS:

TRAVELTIME	PATH LENGTH	VELOCITY	PDF
------------	-------------	----------	-----

1.4500E+01	2.0000E+01	1.3793E+00	1.0000E+00
------------	------------	------------	------------

ADDITIONAL ZONE PARAMETERS:

XV=2.0000E+01 TV=1.4500E+01

AVERAGES:

LENGTH=2.0000E+01 TIME=1.4500E+01 VELOCITY=1.3793E+00

\*\*\* QUANTITY IS CONCENTRATION \*\*\*

CONVERSION FACTOR = 1.4713E-06

DISTANCE (X)	TIME (T)	PORE VOLUME (VVO)	QUANTITY (Q)
2.0000E+01	1.0000E+04	6.8966E+02	6.32404E-41
2.0000E+01	1.9900E+04	1.3724E+03	4.59880E-18
2.0000E+01	2.9800E+04	2.0552E+03	1.77129E-10
2.0000E+01	3.9700E+04	2.7379E+03	9.49663E-07
2.0000E+01	4.9600E+04	3.4207E+03	1.43651E-04
2.0000E+01	5.9500E+04	4.1034E+03	3.63469E-03
2.0000E+01	6.9400E+04	4.7862E+03	3.30567E-02

2.0000E+01	7.9300E+04	5.4690E+03	1.58705E-01
2.0000E+01	8.9200E+04	6.1517E+03	4.98107E-01
2.0000E+01	9.9100E+04	6.8345E+03	1.16238E+00
2.0000E+01	1.0900E+05	7.5172E+03	2.18954E+00
2.0000E+01	1.1890E+05	8.2000E+03	3.51740E+00
2.0000E+01	1.2880E+05	8.8828E+03	5.00680E+00
2.0000E+01	1.3870E+05	9.5655E+03	6.49063E+00
2.0000E+01	1.4860E+05	1.0248E+04	7.81966E+00
2.0000E+01	1.5850E+05	1.0931E+04	8.88887E+00
2.0000E+01	1.6840E+05	1.1614E+04	9.64826E+00
2.0000E+01	1.7830E+05	1.2297E+04	1.00907E+01
2.0000E+01	1.8820E+05	1.2979E+04	1.02429E+01
2.0000E+01	1.9810E+05	1.3662E+04	1.01543E+01
2.0000E+01	2.0800E+05	1.4345E+04	9.91208E+00
2.0000E+01	2.1790E+05	1.5028E+04	9.66537E+00
2.0000E+01	2.2780E+05	1.5710E+04	9.56757E+00
2.0000E+01	2.3770E+05	1.6393E+04	9.65571E+00
2.0000E+01	2.4760E+05	1.7076E+04	9.81249E+00
2.0000E+01	2.5750E+05	1.7759E+04	9.84787E+00
2.0000E+01	2.6740E+05	1.8441E+04	9.61004E+00
2.0000E+01	2.7730E+05	1.9124E+04	9.04534E+00
2.0000E+01	2.8720E+05	1.9807E+04	8.19481E+00
2.0000E+01	2.9710E+05	2.0490E+04	7.15628E+00
2.0000E+01	3.0700E+05	2.1172E+04	6.04219E+00
2.0000E+01	3.1690E+05	2.1855E+04	4.94985E+00
2.0000E+01	3.2680E+05	2.2538E+04	3.94842E+00
2.0000E+01	3.3670E+05	2.3221E+04	3.07687E+00
2.0000E+01	3.4660E+05	2.3903E+04	2.34915E+00
2.0000E+01	3.5650E+05	2.4586E+04	1.76169E+00
2.0000E+01	3.6640E+05	2.5269E+04	1.30054E+00
2.0000E+01	3.7630E+05	2.5952E+04	9.46915E-01
2.0000E+01	3.8620E+05	2.6634E+04	6.81088E-01
2.0000E+01	3.9610E+05	2.7317E+04	4.84630E-01
2.0000E+01	4.0600E+05	2.8000E+04	3.41554E-01
2.0000E+01	4.1590E+05	2.8683E+04	2.38675E-01
2.0000E+01	4.2580E+05	2.9366E+04	1.65519E-01
2.0000E+01	4.3570E+05	3.0048E+04	1.14007E-01
2.0000E+01	4.4560E+05	3.0731E+04	7.80465E-02
2.0000E+01	4.5550E+05	3.1414E+04	5.31352E-02
2.0000E+01	4.6540E+05	3.2097E+04	3.59958E-02
2.0000E+01	4.7530E+05	3.2779E+04	2.42752E-02
2.0000E+01	4.8520E+05	3.3462E+04	1.63042E-02
2.0000E+01	4.9510E+05	3.4145E+04	1.09099E-02
2.0000E+01	5.0500E+05	3.4828E+04	7.27570E-03
2.0000E+01	5.1490E+05	3.5510E+04	4.83709E-03
2.0000E+01	5.2480E+05	3.6193E+04	3.20676E-03
2.0000E+01	5.3470E+05	3.6876E+04	2.12042E-03
2.0000E+01	5.4460E+05	3.7559E+04	1.39877E-03
2.0000E+01	5.5450E+05	3.8241E+04	9.20697E-04
2.0000E+01	5.6440E+05	3.8924E+04	6.04801E-04
2.0000E+01	5.7430E+05	3.9607E+04	3.96552E-04
2.0000E+01	5.8420E+05	4.0290E+04	2.59562E-04
2.0000E+01	5.9410E+05	4.0972E+04	1.69625E-04
2.0000E+01	6.0400E+05	4.1655E+04	1.10575E-04
2.0000E+01	6.1390E+05	4.2338E+04	7.20459E-05
2.0000E+01	6.2380E+05	4.3021E+04	4.68819E-05
2.0000E+01	6.3370E+05	4.3703E+04	3.04708E-05
2.0000E+01	6.4360E+05	4.4386E+04	1.97825E-05
2.0000E+01	6.5350E+05	4.5069E+04	1.28301E-05
2.0000E+01	6.6340E+05	4.5752E+04	8.31299E-06

2.0000E+01	6.7330E+05	4.6434E+04	5.38139E-06
2.0000E+01	6.8320E+05	4.7117E+04	3.48068E-06
2.0000E+01	6.9310E+05	4.7800E+04	2.24953E-06
2.0000E+01	7.0300E+05	4.8483E+04	1.45278E-06
2.0000E+01	7.1290E+05	4.9166E+04	9.37573E-07
2.0000E+01	7.2280E+05	4.9848E+04	6.04684E-07
2.0000E+01	7.3270E+05	5.0531E+04	3.89751E-07
2.0000E+01	7.4260E+05	5.1214E+04	2.51071E-07
2.0000E+01	7.5250E+05	5.1897E+04	1.61648E-07
2.0000E+01	7.6240E+05	5.2579E+04	1.04022E-07
2.0000E+01	7.7230E+05	5.3262E+04	6.69072E-08
2.0000E+01	7.8220E+05	5.3945E+04	4.30154E-08
2.0000E+01	7.9210E+05	5.4628E+04	2.76434E-08
2.0000E+01	8.0200E+05	5.5310E+04	1.77577E-08
2.0000E+01	8.1190E+05	5.5993E+04	1.14029E-08
2.0000E+01	8.2180E+05	5.6676E+04	7.31964E-09
2.0000E+01	8.3170E+05	5.7359E+04	4.69700E-09
2.0000E+01	8.4160E+05	5.8041E+04	3.01309E-09
2.0000E+01	8.5150E+05	5.8724E+04	1.93232E-09
2.0000E+01	8.6140E+05	5.9407E+04	1.23884E-09
2.0000E+01	8.7130E+05	6.0090E+04	7.94042E-10
2.0000E+01	8.8120E+05	6.0772E+04	5.08776E-10
2.0000E+01	8.9110E+05	6.1455E+04	3.25951E-10
2.0000E+01	9.0100E+05	6.2138E+04	2.08756E-10
2.0000E+01	9.1090E+05	6.2821E+04	1.33656E-10
2.0000E+01	9.2080E+05	6.3503E+04	8.55342E-11
2.0000E+01	9.3070E+05	6.4186E+04	5.47820E-11
2.0000E+01	9.4060E+05	6.4869E+04	3.50263E-11
2.0000E+01	9.5050E+05	6.5552E+04	2.24032E-11
2.0000E+01	9.6040E+05	6.6234E+04	1.43323E-11
2.0000E+01	9.7030E+05	6.6917E+04	9.19831E-12
2.0000E+01	9.8020E+05	6.7600E+04	5.84928E-12
2.0000E+01	9.9010E+05	6.8283E+04	3.76945E-12
2.0000E+01	1.0000E+06	6.8966E+04	2.38406E-12

```

*****
*
*       ONE-DIMENSIONAL CONVECTIVE-DISPERSIVE EQUATION
*       *11/26/85* VERSION
*       SEMI-INFINITE PROFILE
*
*       NUCLIDE DECAY (THALF)
*       LINEAR ADSORPTION (R)
*       GENERAL NUCLIDE RELEASE CURVE
*       TRANSPORT SUM OVER PATHLINES
*
*       CIMARRON LANDFILL: Kd=300 controlled release - U-238
*       VADOSE ZONE
*****

```

NUCLIDE: U-238

INPUT PARAMETERS

=====

```

V =          1.38           D =          1.00
R =          1600.0        TO = 6.6984E+04
TOTAL =1.81E+12          TDECAY=0.000E-01
THALF= 4.5000E+09        CO = 1.931E+06
XL =2.0000E+01
NUCLIDE DECAY CONSTANT = 1.54033E-10

```

CONTROL FLAGS:

IOPTBC= 0 IFLUX= 0 ITYPE= 1 IOPT= 3

RELEASE MODEL PARAMETERS:

```

PLAN VIEW AREA=8.0000E+04
DEPTH=1.0000E+01
WATER FLUX Q=3.3000E-01
THETA =0.3000
MAX CONCENTRATION=1.0000E+12
RELEASE CURVE ERROR=1.0000E-02

```

FRACTION REMAINING CURVE

TIME	FRACTION
0.00E-01	1.00000
2.62E+02	0.98199
5.22E+02	0.96437
7.82E+02	0.94713
1.04E+03	0.93027
1.30E+03	0.91376
1.55E+03	0.89760
1.81E+03	0.88179
2.06E+03	0.86632
2.32E+03	0.85117
2.57E+03	0.83634
2.82E+03	0.82183
3.07E+03	0.80762



3.32E+03	0.79370
3.57E+03	0.78008
3.82E+03	0.76673
4.07E+03	0.75367
4.31E+03	0.74087
4.56E+03	0.72834
4.80E+03	0.71606
5.04E+03	0.70403
5.29E+03	0.69225
5.53E+03	0.68071
5.77E+03	0.66940
6.01E+03	0.65832
6.24E+03	0.64746
6.48E+03	0.63683
6.72E+03	0.62640
6.95E+03	0.61618
7.19E+03	0.60616
7.42E+03	0.59635
7.65E+03	0.58672
7.89E+03	0.57729
8.12E+03	0.56804
8.35E+03	0.55897
8.58E+03	0.55008
8.80E+03	0.54136
9.03E+03	0.53281
9.26E+03	0.52443
9.48E+03	0.51621
9.71E+03	0.50814
9.93E+03	0.50023
1.02E+04	0.49247
1.04E+04	0.48486
1.06E+04	0.47739
1.08E+04	0.47006
1.10E+04	0.46288
1.13E+04	0.45582
1.15E+04	0.44890
1.17E+04	0.44211
1.19E+04	0.43544
1.21E+04	0.42890
1.23E+04	0.42248
1.25E+04	0.41618
1.28E+04	0.40999
1.30E+04	0.40392
1.32E+04	0.39796
1.34E+04	0.39210
1.36E+04	0.38636
1.38E+04	0.38071
1.40E+04	0.37517
1.42E+04	0.36973
1.44E+04	0.36439
1.46E+04	0.35914
1.48E+04	0.35399
1.50E+04	0.34892
1.52E+04	0.34395
1.55E+04	0.33906
1.57E+04	0.33427
1.59E+04	0.32955
1.61E+04	0.32492
1.63E+04	0.32037
1.64E+04	0.31590

1.66E+04	0.31150
1.68E+04	0.30718
1.70E+04	0.30294
1.72E+04	0.29877
1.74E+04	0.29467
1.76E+04	0.29064
1.78E+04	0.28668
1.80E+04	0.28279
1.82E+04	0.27896
1.84E+04	0.27520
1.86E+04	0.27150
1.88E+04	0.26786
1.90E+04	0.26428
1.91E+04	0.26077
1.93E+04	0.25731
1.95E+04	0.25391
1.97E+04	0.25057
1.99E+04	0.24728
2.01E+04	0.24404
2.03E+04	0.24086
2.04E+04	0.23773
2.06E+04	0.23465
2.08E+04	0.23162
2.10E+04	0.22864
2.12E+04	0.22571
2.13E+04	0.22283
2.15E+04	0.21999
2.17E+04	0.21720
2.19E+04	0.00000

RELEASE INTERVAL NUMBER= 102

PATHLINE PARAMETERS:

TRAVELTIME	PATH LENGTH	VELOCITY	PDF
1.4500E+01	2.0000E+01	1.3793E+00	1.0000E+00

ADDITIONAL ZONE PARAMETERS:

XV=2.0000E+01 TV=1.4500E+01

AVERAGES:

LENGTH=2.0000E+01 TIME=1.4500E+01 VELOCITY=1.3793E+00

\*\*\* QUANTITY IS CONCENTRATION \*\*\*

CONVERSION FACTOR = 1.4713E-06

DISTANCE (X)	TIME (T)	PORE VOLUME (VVO)	QUANTITY (Q)
2.0000E+01	5.0000E+03	3.4483E+02	3.80731E-08
2.0000E+01	5.9896E+03	4.1307E+02	6.21516E-06
2.0000E+01	6.9792E+03	4.8132E+02	2.23932E-04
2.0000E+01	7.9687E+03	5.4957E+02	3.12617E-03
2.0000E+01	8.9583E+03	6.1782E+02	2.31289E-02
2.0000E+01	9.9479E+03	6.8606E+02	1.09677E-01
2.0000E+01	1.0937E+04	7.5431E+02	3.76197E-01

2.0000E+01	1.1927E+04	8.2256E+02	1.01204E+00
2.0000E+01	1.2917E+04	8.9080E+02	2.25872E+00
2.0000E+01	1.3906E+04	9.5905E+02	4.35414E+00
2.0000E+01	1.4896E+04	1.0273E+03	7.46753E+00
2.0000E+01	1.5885E+04	1.0955E+03	1.16510E+01
2.0000E+01	1.6875E+04	1.1638E+03	1.68223E+01
2.0000E+01	1.7865E+04	1.2320E+03	2.27791E+01
2.0000E+01	1.8854E+04	1.3003E+03	2.92352E+01
2.0000E+01	1.9844E+04	1.3685E+03	3.58657E+01
2.0000E+01	2.0833E+04	1.4368E+03	4.23497E+01
2.0000E+01	2.1823E+04	1.5050E+03	4.84038E+01
2.0000E+01	2.2812E+04	1.5733E+03	5.38029E+01
2.0000E+01	2.3802E+04	1.6415E+03	5.83841E+01
2.0000E+01	2.4792E+04	1.7098E+03	6.20688E+01
2.0000E+01	2.5781E+04	1.7780E+03	6.48211E+01
2.0000E+01	2.6771E+04	1.8463E+03	6.66601E+01
2.0000E+01	2.7760E+04	1.9145E+03	6.76427E+01
2.0000E+01	2.8750E+04	1.9828E+03	6.78521E+01
2.0000E+01	2.9740E+04	2.0510E+03	6.74008E+01
2.0000E+01	3.0729E+04	2.1193E+03	6.64572E+01
2.0000E+01	3.1719E+04	2.1875E+03	6.52792E+01
2.0000E+01	3.2708E+04	2.2557E+03	6.41974E+01
2.0000E+01	3.3698E+04	2.3240E+03	6.35212E+01
2.0000E+01	3.4687E+04	2.3922E+03	6.34178E+01
2.0000E+01	3.5677E+04	2.4605E+03	6.38398E+01
2.0000E+01	3.6667E+04	2.5287E+03	6.45399E+01
2.0000E+01	3.7656E+04	2.5970E+03	6.51537E+01
2.0000E+01	3.8646E+04	2.6652E+03	6.53060E+01
2.0000E+01	3.9635E+04	2.7335E+03	6.47002E+01
2.0000E+01	4.0625E+04	2.8017E+03	6.31672E+01
2.0000E+01	4.1615E+04	2.8700E+03	6.06752E+01
2.0000E+01	4.2604E+04	2.9382E+03	5.73101E+01
2.0000E+01	4.3594E+04	3.0065E+03	5.32397E+01
2.0000E+01	4.4583E+04	3.0747E+03	4.86751E+01
2.0000E+01	4.5573E+04	3.1430E+03	4.38376E+01
2.0000E+01	4.6562E+04	3.2112E+03	3.89291E+01
2.0000E+01	4.7552E+04	3.2795E+03	3.41242E+01
2.0000E+01	4.8542E+04	3.3477E+03	2.95567E+01
2.0000E+01	4.9531E+04	3.4159E+03	2.53212E+01
2.0000E+01	5.0521E+04	3.4842E+03	2.14756E+01
2.0000E+01	5.1510E+04	3.5524E+03	1.80470E+01
2.0000E+01	5.2500E+04	3.6207E+03	1.50386E+01
2.0000E+01	5.3490E+04	3.6889E+03	1.24352E+01
2.0000E+01	5.4479E+04	3.7572E+03	1.02099E+01
2.0000E+01	5.5469E+04	3.8254E+03	8.32850E+00
2.0000E+01	5.6458E+04	3.8937E+03	6.75333E+00
2.0000E+01	5.7448E+04	3.9619E+03	5.44606E+00
2.0000E+01	5.8437E+04	4.0302E+03	4.36965E+00
2.0000E+01	5.9427E+04	4.0984E+03	3.48965E+00
2.0000E+01	6.0417E+04	4.1667E+03	2.77486E+00
2.0000E+01	6.1406E+04	4.2349E+03	2.19769E+00
2.0000E+01	6.2396E+04	4.3032E+03	1.73415E+00
2.0000E+01	6.3385E+04	4.3714E+03	1.36368E+00
2.0000E+01	6.4375E+04	4.4397E+03	1.06895E+00
2.0000E+01	6.5365E+04	4.5079E+03	8.35436E-01
2.0000E+01	6.6354E+04	4.5761E+03	6.51134E-01
2.0000E+01	6.7344E+04	4.6444E+03	5.06186E-01
2.0000E+01	6.8333E+04	4.7126E+03	3.92560E-01
2.0000E+01	6.9323E+04	4.7809E+03	3.03759E-01
2.0000E+01	7.0312E+04	4.8491E+03	2.34552E-01

2.0000E+01	7.1302E+04	4.9174E+03	1.80757E-01
2.0000E+01	7.2292E+04	4.9856E+03	1.39043E-01
2.0000E+01	7.3281E+04	5.0539E+03	1.06771E-01
2.0000E+01	7.4271E+04	5.1221E+03	8.18565E-02
2.0000E+01	7.5260E+04	5.1904E+03	6.26598E-02
2.0000E+01	7.6250E+04	5.2586E+03	4.78962E-02
2.0000E+01	7.7240E+04	5.3269E+03	3.65616E-02
2.0000E+01	7.8229E+04	5.3951E+03	2.78738E-02
2.0000E+01	7.9219E+04	5.4634E+03	2.12248E-02
2.0000E+01	8.0208E+04	5.5316E+03	1.61435E-02
2.0000E+01	8.1198E+04	5.5999E+03	1.22655E-02
2.0000E+01	8.2187E+04	5.6681E+03	9.30967E-03
2.0000E+01	8.3177E+04	5.7364E+03	7.05936E-03
2.0000E+01	8.4167E+04	5.8046E+03	5.34811E-03
2.0000E+01	8.5156E+04	5.8728E+03	4.04820E-03
2.0000E+01	8.6146E+04	5.9411E+03	3.06174E-03
2.0000E+01	8.7135E+04	6.0093E+03	2.31386E-03
2.0000E+01	8.8125E+04	6.0776E+03	1.74738E-03
2.0000E+01	8.9115E+04	6.1458E+03	1.31866E-03
2.0000E+01	9.0104E+04	6.2141E+03	9.94459E-04
2.0000E+01	9.1094E+04	6.2823E+03	7.48741E-04
2.0000E+01	9.2083E+04	6.3506E+03	5.63911E-04
2.0000E+01	9.3073E+04	6.4188E+03	4.24463E-04
2.0000E+01	9.4062E+04	6.4871E+03	3.19322E-04
2.0000E+01	9.5052E+04	6.5553E+03	2.40099E-04
2.0000E+01	9.6042E+04	6.6236E+03	1.80441E-04
2.0000E+01	9.7031E+04	6.6918E+03	1.35542E-04
2.0000E+01	9.8021E+04	6.7601E+03	1.01768E-04
2.0000E+01	9.9010E+04	6.8283E+03	7.63769E-05
2.0000E+01	1.0000E+05	6.8966E+03	5.72969E-05

```

*****
*
*       ONE-DIMENSIONAL CONVECTIVE-DISPERSIVE EQUATION
*       *11/26/85* VERSION
*       SEMI-INFINITE PROFILE
*
*       NUCLIDE DECAY (THALF)
*       LINEAR ADSORPTION (R)
*       GENERAL NUCLIDE RELEASE CURVE
*       TRANSPORT SUM OVER PATHLINES
*
*       CIMARRON LANDFILL: Kd=2000 controlled release - U-238
*       SATURATED ZONE
*****

```

NUCLIDE: U-238

INPUT PARAMETERS  
=====

```

V =      130.38          D =      1.00
R =     10600.0          T0 = 4.8815E+05
TOTAL =1.81E+12          TDECAY=0.000E-01
THALF= 4.5000E+09       C0 = 4.539E+05
XL =1.0000E+03
NUCLIDE DECAY CONSTANT = 1.54033E-10

```

CONTROL FLAGS:  
IOPTBC= 0 IFLUX= 0 ITYPE= 1 IOPT= 3

RELEASE MODEL PARAMETERS:  
PLAN VIEW AREA=8.0000E+04  
DEPTH=1.0000E+01  
WATER FLUX Q=3.0000E-01  
THETA =0.3000  
MAX CONCENTRATION=1.0000E+12  
RELEASE CURVE ERROR=1.0000E-02

FRACTION REMAINING CURVE  
TIME                    FRACTION

0.00E-01	1.00000
1.91E+03	0.98199
3.81E+03	0.96437
5.70E+03	0.94713
7.58E+03	0.93027
9.46E+03	0.91376
1.13E+04	0.89760
1.32E+04	0.88179
1.50E+04	0.86632
1.69E+04	0.85117
1.87E+04	0.83634
2.06E+04	0.82183
2.24E+04	0.80762

2.42E+04	0.79370
2.60E+04	0.78008
2.78E+04	0.76673
2.96E+04	0.75367
3.14E+04	0.74087
3.32E+04	0.72834
3.50E+04	0.71606
3.68E+04	0.70403
3.85E+04	0.69225
4.03E+04	0.68071
4.20E+04	0.66940
4.38E+04	0.65832
4.55E+04	0.64746
4.72E+04	0.63683
4.90E+04	0.62640
5.07E+04	0.61618
5.24E+04	0.60616
5.41E+04	0.59635
5.58E+04	0.58672
5.75E+04	0.57729
5.91E+04	0.56804
6.08E+04	0.55897
6.25E+04	0.55008
6.42E+04	0.54136
6.58E+04	0.53281
6.75E+04	0.52443
6.91E+04	0.51621
7.07E+04	0.50814
7.24E+04	0.50023
7.40E+04	0.49247
7.56E+04	0.48486
7.72E+04	0.47739
7.88E+04	0.47006
8.04E+04	0.46288
8.20E+04	0.45582
8.36E+04	0.44890
8.52E+04	0.44211
8.68E+04	0.43544
8.83E+04	0.42890
8.99E+04	0.42248
9.14E+04	0.41618
9.30E+04	0.40999
9.45E+04	0.40392
9.61E+04	0.39796
9.76E+04	0.39210
9.91E+04	0.38636
1.01E+05	0.38071
1.02E+05	0.37517
1.04E+05	0.36973
1.05E+05	0.36439
1.07E+05	0.35914
1.08E+05	0.35399
1.10E+05	0.34892
1.11E+05	0.34395
1.13E+05	0.33906
1.14E+05	0.33427
1.16E+05	0.32955
1.17E+05	0.32492
1.18E+05	0.32037
1.20E+05	0.31590

1.21E+05	0.31150
1.23E+05	0.30718
1.24E+05	0.30294
1.26E+05	0.29877
1.27E+05	0.29467
1.28E+05	0.29064
1.30E+05	0.28668
1.31E+05	0.28279
1.33E+05	0.27896
1.34E+05	0.27520
1.35E+05	0.27150
1.37E+05	0.26786
1.38E+05	0.26428
1.40E+05	0.26077
1.41E+05	0.25731
1.42E+05	0.25391
1.44E+05	0.25057
1.45E+05	0.24728
1.46E+05	0.24404
1.48E+05	0.24086
1.49E+05	0.23773
1.50E+05	0.23465
1.52E+05	0.23162
1.53E+05	0.22864
1.54E+05	0.22571
1.56E+05	0.22283
1.57E+05	0.21999
1.58E+05	0.21720
1.59E+05	0.00000

RELEASE INTERVAL NUMBER= 102

PATHLINE PARAMETERS:

TRAVELTIME	PATH LENGTH	VELOCITY	PDF
2.2010E+01	1.0190E+03	4.6297E+01	5.5556E+01
2.2019E+01	1.0200E+03	4.6324E+01	5.0000E+02
2.2020E+01	1.0210E+03	4.6367E+01	0.0000E-01

ADDITIONAL ZONE PARAMETERS:

XV=2.0000E+01 TV=1.4500E+01

AVERAGES:

LENGTH=1.0000E+03 TIME=2.2016E+01 VELOCITY=4.6329E+01

\*\*\* QUANTITY IS CONCENTRATION \*\*\*

CONVERSION FACTOR = 3.2695E-05

DISTANCE (X)	TIME (T)	PORE VOLUME (VVO)	QUANTITY (Q)
1.0000E+03	2.0699E+05	9.5897E+03	8.66687E-76
1.0000E+03	2.0799E+05	9.6360E+03	8.62836E-70
1.0000E+03	2.0899E+05	9.6823E+03	3.17715E-64
1.0000E+03	2.0999E+05	9.7286E+03	6.42212E-59
1.0000E+03	2.1099E+05	9.7748E+03	7.18788E-54

1.0000E+03	2.1199E+05	9.8211E+03	4.49258E-49
1.0000E+03	2.1298E+05	9.8674E+03	1.58123E-44
1.0000E+03	2.1398E+05	9.9136E+03	3.15993E-40
1.0000E+03	2.1498E+05	9.9599E+03	3.61465E-36
1.0000E+03	2.1598E+05	1.0006E+04	2.38584E-32
1.0000E+03	2.1698E+05	1.0052E+04	9.15884E-29
1.0000E+03	2.1798E+05	1.0099E+04	2.06094E-25
1.0000E+03	2.1898E+05	1.0145E+04	2.73963E-22
1.0000E+03	2.1998E+05	1.0191E+04	2.16808E-19
1.0000E+03	2.2097E+05	1.0238E+04	1.02935E-16
1.0000E+03	2.2197E+05	1.0284E+04	2.95472E-14
1.0000E+03	2.2297E+05	1.0330E+04	5.16805E-12
1.0000E+03	2.2397E+05	1.0376E+04	5.55195E-10
1.0000E+03	2.2497E+05	1.0423E+04	3.69344E-08
1.0000E+03	2.2597E+05	1.0469E+04	1.53464E-06
1.0000E+03	2.2697E+05	1.0515E+04	4.01964E-05
1.0000E+03	2.2797E+05	1.0561E+04	6.70478E-04
1.0000E+03	2.2896E+05	1.0608E+04	7.20154E-03
1.0000E+03	2.2996E+05	1.0654E+04	5.05334E-02
1.0000E+03	2.3096E+05	1.0700E+04	2.35763E-01
1.0000E+03	2.3196E+05	1.0747E+04	7.48886E-01
1.0000E+03	2.3296E+05	1.0793E+04	1.67476E+00
1.0000E+03	2.3396E+05	1.0839E+04	2.76649E+00
1.0000E+03	2.3496E+05	1.0885E+04	3.60737E+00
1.0000E+03	2.3596E+05	1.0932E+04	4.02280E+00
1.0000E+03	2.3695E+05	1.0978E+04	4.13995E+00
1.0000E+03	2.3795E+05	1.1024E+04	4.13679E+00
1.0000E+03	2.3895E+05	1.1070E+04	4.10350E+00
1.0000E+03	2.3995E+05	1.1117E+04	4.06559E+00
1.0000E+03	2.4095E+05	1.1163E+04	4.02750E+00
1.0000E+03	2.4195E+05	1.1209E+04	3.98973E+00
1.0000E+03	2.4295E+05	1.1256E+04	3.95232E+00
1.0000E+03	2.4395E+05	1.1302E+04	3.91525E+00
1.0000E+03	2.4494E+05	1.1348E+04	3.87853E+00
1.0000E+03	2.4594E+05	1.1394E+04	3.84216E+00
1.0000E+03	2.4694E+05	1.1441E+04	3.80613E+00
1.0000E+03	2.4794E+05	1.1487E+04	3.77043E+00
1.0000E+03	2.4894E+05	1.1533E+04	3.73507E+00
1.0000E+03	2.4994E+05	1.1579E+04	3.70004E+00
1.0000E+03	2.5094E+05	1.1626E+04	3.66534E+00
1.0000E+03	2.5194E+05	1.1672E+04	3.63097E+00
1.0000E+03	2.5293E+05	1.1718E+04	3.59692E+00
1.0000E+03	2.5393E+05	1.1765E+04	3.56318E+00
1.0000E+03	2.5493E+05	1.1811E+04	3.52977E+00
1.0000E+03	2.5593E+05	1.1857E+04	3.49667E+00
1.0000E+03	2.5693E+05	1.1903E+04	3.46387E+00
1.0000E+03	2.5793E+05	1.1950E+04	3.43139E+00
1.0000E+03	2.5893E+05	1.1996E+04	3.39921E+00
1.0000E+03	2.5993E+05	1.2042E+04	3.36733E+00
1.0000E+03	2.6092E+05	1.2088E+04	3.33575E+00
1.0000E+03	2.6192E+05	1.2135E+04	3.30447E+00
1.0000E+03	2.6292E+05	1.2181E+04	3.27347E+00
1.0000E+03	2.6392E+05	1.2227E+04	3.24278E+00
1.0000E+03	2.6492E+05	1.2273E+04	3.21237E+00
1.0000E+03	2.6592E+05	1.2320E+04	3.18224E+00
1.0000E+03	2.6692E+05	1.2366E+04	3.15240E+00
1.0000E+03	2.6792E+05	1.2412E+04	3.12283E+00
1.0000E+03	2.6891E+05	1.2459E+04	3.09354E+00
1.0000E+03	2.6991E+05	1.2505E+04	3.06453E+00
1.0000E+03	2.7091E+05	1.2551E+04	3.03579E+00



1.0000E+03	2.7191E+05	1.2597E+04	3.00732E+00
1.0000E+03	2.7291E+05	1.2644E+04	2.97912E+00
1.0000E+03	2.7391E+05	1.2690E+04	2.95118E+00
1.0000E+03	2.7491E+05	1.2736E+04	2.92350E+00
1.0000E+03	2.7591E+05	1.2782E+04	2.89609E+00
1.0000E+03	2.7690E+05	1.2829E+04	2.86893E+00
1.0000E+03	2.7790E+05	1.2875E+04	2.84202E+00
1.0000E+03	2.7890E+05	1.2921E+04	2.81537E+00
1.0000E+03	2.7990E+05	1.2968E+04	2.78896E+00
1.0000E+03	2.8090E+05	1.3014E+04	2.76281E+00
1.0000E+03	2.8190E+05	1.3060E+04	2.73690E+00
1.0000E+03	2.8290E+05	1.3106E+04	2.71123E+00
1.0000E+03	2.8390E+05	1.3153E+04	2.68580E+00
1.0000E+03	2.8489E+05	1.3199E+04	2.66062E+00
1.0000E+03	2.8589E+05	1.3245E+04	2.63567E+00
1.0000E+03	2.8689E+05	1.3291E+04	2.61095E+00
1.0000E+03	2.8789E+05	1.3338E+04	2.58646E+00
1.0000E+03	2.8889E+05	1.3384E+04	2.56220E+00
1.0000E+03	2.8989E+05	1.3430E+04	2.53818E+00
1.0000E+03	2.9089E+05	1.3477E+04	2.51437E+00
1.0000E+03	2.9189E+05	1.3523E+04	2.49079E+00
1.0000E+03	2.9288E+05	1.3569E+04	2.46743E+00
1.0000E+03	2.9388E+05	1.3615E+04	2.44429E+00
1.0000E+03	2.9488E+05	1.3662E+04	2.42137E+00
1.0000E+03	2.9588E+05	1.3708E+04	2.39866E+00
1.0000E+03	2.9688E+05	1.3754E+04	2.37617E+00
1.0000E+03	2.9788E+05	1.3800E+04	2.35388E+00
1.0000E+03	2.9888E+05	1.3847E+04	2.33181E+00
1.0000E+03	2.9988E+05	1.3893E+04	2.30994E+00
1.0000E+03	3.0087E+05	1.3939E+04	2.28828E+00
1.0000E+03	3.0187E+05	1.3986E+04	2.26682E+00
1.0000E+03	3.0287E+05	1.4032E+04	2.24556E+00
1.0000E+03	3.0387E+05	1.4078E+04	2.22450E+00
1.0000E+03	3.0487E+05	1.4124E+04	2.20364E+00
1.0000E+03	3.0587E+05	1.4171E+04	2.18297E+00
1.0000E+03	3.0687E+05	1.4217E+04	2.16250E+00
1.0000E+03	3.0787E+05	1.4263E+04	2.14222E+00
1.0000E+03	3.0886E+05	1.4309E+04	2.12213E+00
1.0000E+03	3.0986E+05	1.4356E+04	2.10223E+00
1.0000E+03	3.1086E+05	1.4402E+04	2.08251E+00
1.0000E+03	3.1186E+05	1.4448E+04	2.06298E+00
1.0000E+03	3.1286E+05	1.4495E+04	2.04363E+00
1.0000E+03	3.1386E+05	1.4541E+04	2.02447E+00
1.0000E+03	3.1486E+05	1.4587E+04	2.00548E+00
1.0000E+03	3.1586E+05	1.4633E+04	1.98667E+00
1.0000E+03	3.1685E+05	1.4680E+04	1.96804E+00
1.0000E+03	3.1785E+05	1.4726E+04	1.94959E+00
1.0000E+03	3.1885E+05	1.4772E+04	1.93130E+00
1.0000E+03	3.1985E+05	1.4818E+04	1.91319E+00
1.0000E+03	3.2085E+05	1.4865E+04	1.89525E+00
1.0000E+03	3.2185E+05	1.4911E+04	1.87747E+00
1.0000E+03	3.2285E+05	1.4957E+04	1.85987E+00
1.0000E+03	3.2385E+05	1.5004E+04	1.84242E+00
1.0000E+03	3.2484E+05	1.5050E+04	1.82515E+00
1.0000E+03	3.2584E+05	1.5096E+04	1.80803E+00
1.0000E+03	3.2684E+05	1.5142E+04	1.79107E+00
1.0000E+03	3.2784E+05	1.5189E+04	1.77428E+00
1.0000E+03	3.2884E+05	1.5235E+04	1.75764E+00
1.0000E+03	3.2984E+05	1.5281E+04	1.74115E+00
1.0000E+03	3.3084E+05	1.5327E+04	1.72482E+00

1.0000E+03	3.3184E+05	1.5374E+04	1.70865E+00
1.0000E+03	3.3283E+05	1.5420E+04	1.69262E+00
1.0000E+03	3.3383E+05	1.5466E+04	1.67675E+00
1.0000E+03	3.3483E+05	1.5512E+04	1.66103E+00
1.0000E+03	3.3583E+05	1.5559E+04	1.64545E+00
1.0000E+03	3.3683E+05	1.5605E+04	1.63002E+00
1.0000E+03	3.3783E+05	1.5651E+04	1.61473E+00
1.0000E+03	3.3883E+05	1.5698E+04	1.59959E+00
1.0000E+03	3.3983E+05	1.5744E+04	1.58459E+00
1.0000E+03	3.4082E+05	1.5790E+04	1.56973E+00
1.0000E+03	3.4182E+05	1.5836E+04	1.55500E+00
1.0000E+03	3.4282E+05	1.5883E+04	1.54042E+00
1.0000E+03	3.4382E+05	1.5929E+04	1.52597E+00
1.0000E+03	3.4482E+05	1.5975E+04	1.51166E+00
1.0000E+03	3.4582E+05	1.6021E+04	1.49749E+00
1.0000E+03	3.4682E+05	1.6068E+04	1.48344E+00
1.0000E+03	3.4782E+05	1.6114E+04	1.46953E+00
1.0000E+03	3.4881E+05	1.6160E+04	1.45575E+00
1.0000E+03	3.4981E+05	1.6207E+04	1.44210E+00
1.0000E+03	3.5081E+05	1.6253E+04	1.42857E+00
1.0000E+03	3.5181E+05	1.6299E+04	1.41518E+00
1.0000E+03	3.5281E+05	1.6345E+04	1.40190E+00
1.0000E+03	3.5381E+05	1.6392E+04	1.38876E+00
1.0000E+03	3.5481E+05	1.6438E+04	1.37573E+00
1.0000E+03	3.5581E+05	1.6484E+04	1.36283E+00
1.0000E+03	3.5680E+05	1.6530E+04	1.35005E+00
1.0000E+03	3.5780E+05	1.6577E+04	1.33739E+00
1.0000E+03	3.5880E+05	1.6623E+04	1.32485E+00
1.0000E+03	3.5980E+05	1.6669E+04	1.31242E+00
1.0000E+03	3.6080E+05	1.6716E+04	1.30011E+00
1.0000E+03	3.6180E+05	1.6762E+04	1.28792E+00
1.0000E+03	3.6280E+05	1.6808E+04	1.27584E+00
1.0000E+03	3.6380E+05	1.6854E+04	1.26388E+00
1.0000E+03	3.6479E+05	1.6901E+04	1.25202E+00
1.0000E+03	3.6579E+05	1.6947E+04	1.24028E+00
1.0000E+03	3.6679E+05	1.6993E+04	1.22865E+00
1.0000E+03	3.6779E+05	1.7039E+04	1.21713E+00
1.0000E+03	3.6879E+05	1.7086E+04	1.20571E+00
1.0000E+03	3.6979E+05	1.7132E+04	1.19441E+00
1.0000E+03	3.7079E+05	1.7178E+04	1.18321E+00
1.0000E+03	3.7179E+05	1.7225E+04	1.17211E+00
1.0000E+03	3.7278E+05	1.7271E+04	1.16112E+00
1.0000E+03	3.7378E+05	1.7317E+04	1.15023E+00
1.0000E+03	3.7478E+05	1.7363E+04	1.13944E+00
1.0000E+03	3.7578E+05	1.7410E+04	1.12875E+00
1.0000E+03	3.7678E+05	1.7456E+04	1.11817E+00
1.0000E+03	3.7778E+05	1.7502E+04	1.10768E+00
1.0000E+03	3.7878E+05	1.7548E+04	1.09729E+00
1.0000E+03	3.7978E+05	1.7595E+04	1.08700E+00
1.0000E+03	3.8077E+05	1.7641E+04	1.07681E+00
1.0000E+03	3.8177E+05	1.7687E+04	1.06671E+00
1.0000E+03	3.8277E+05	1.7734E+04	1.05671E+00
1.0000E+03	3.8377E+05	1.7780E+04	1.04681E+00
1.0000E+03	3.8477E+05	1.7826E+04	1.03726E+00
1.0000E+03	3.8577E+05	1.7872E+04	1.03246E+00
1.0000E+03	3.8677E+05	1.7919E+04	1.08024E+00
1.0000E+03	3.8777E+05	1.7965E+04	1.49252E+00
1.0000E+03	3.8876E+05	1.8011E+04	3.42473E+00
1.0000E+03	3.8976E+05	1.8057E+04	8.91009E+00
1.0000E+03	3.9076E+05	1.8104E+04	1.79456E+01

1.0000E+03	3.9176E+05	1.8150E+04	2.49223E+01
1.0000E+03	3.9276E+05	1.8196E+04	2.32933E+01
1.0000E+03	3.9376E+05	1.8242E+04	1.45954E+01
1.0000E+03	3.9476E+05	1.8289E+04	6.13730E+00
1.0000E+03	3.9576E+05	1.8335E+04	1.73579E+00
1.0000E+03	3.9675E+05	1.8381E+04	3.31003E-01
1.0000E+03	3.9775E+05	1.8428E+04	4.26679E-02
1.0000E+03	3.9875E+05	1.8474E+04	3.72808E-03
1.0000E+03	3.9975E+05	1.8520E+04	2.21190E-04
1.0000E+03	4.0075E+05	1.8566E+04	8.94757E-06
1.0000E+03	4.0175E+05	1.8613E+04	2.47445E-07
1.0000E+03	4.0275E+05	1.8659E+04	4.69373E-09
1.0000E+03	4.0375E+05	1.8705E+04	6.12791E-11
1.0000E+03	4.0474E+05	1.8751E+04	5.50359E-13

```

*****
*
*       ONE-DIMENSIONAL CONVECTIVE-DISPERSIVE EQUATION
*       *11/26/85* VERSION
*       SEMI-INFINITE PROFILE
*
*       NUCLIDE DECAY (THALF)
*       LINEAR ADSORPTION (R)
*       GENERAL NUCLIDE RELEASE CURVE
*       TRANSPORT SUM OVER PATHLINES
*
*       CIMARRON LANDFILL: Kd=300 controlled release - U-238
*       SATURATED ZONE
*****

```

NUCLIDE: U-238

INPUT PARAMETERS  
=====

```

V =      130.38           D =      1.00
R =      1600.0          TO = 7.3683E+04
TOTAL =1.81E+12         TDECAY=0.000E-01
THALF= 4.5000E+09      CO = 4.539E+05
XL =1.0000E+03
NUCLIDE DECAY CONSTANT = 1.54033E-10

```

CONTROL FLAGS:  
IOPTBC= 0 IFLUX= 0 ITYPE= 1 IOPT= 3

RELEASE MODEL PARAMETERS:  
PLAN VIEW AREA=8.0000E+04  
DEPTH=1.0000E+01  
WATER FLUX Q=3.0000E-01  
THETA =0.3000  
MAX CONCENTRATION=1.0000E+12  
RELEASE CURVE ERROR=1.0000E-02

FRACTION REMAINING CURVE  
TIME FRACTION

0.00E-01	1.00000
2.88E+02	0.98199
5.75E+02	0.96437
8.60E+02	0.94713
1.14E+03	0.93027
1.43E+03	0.91376
1.71E+03	0.89760
1.99E+03	0.88179
2.27E+03	0.86632
2.55E+03	0.85117
2.83E+03	0.83634
3.10E+03	0.82183
3.38E+03	0.80762

3.66E+03	0.79370
3.93E+03	0.78008
4.20E+03	0.76673
4.47E+03	0.75367
4.74E+03	0.74087
5.01E+03	0.72834
5.28E+03	0.71606
5.55E+03	0.70403
5.81E+03	0.69225
6.08E+03	0.68071
6.34E+03	0.66940
6.61E+03	0.65832
6.87E+03	0.64746
7.13E+03	0.63683
7.39E+03	0.62640
7.65E+03	0.61618
7.91E+03	0.60616
8.16E+03	0.59635
8.42E+03	0.58672
8.67E+03	0.57729
8.93E+03	0.56804
9.18E+03	0.55897
9.43E+03	0.55008
9.68E+03	0.54136
9.93E+03	0.53281
1.02E+04	0.52443
1.04E+04	0.51621
1.07E+04	0.50814
1.09E+04	0.50023
1.12E+04	0.49247
1.14E+04	0.48486
1.17E+04	0.47739
1.19E+04	0.47006
1.21E+04	0.46288
1.24E+04	0.45582
1.26E+04	0.44890
1.29E+04	0.44211
1.31E+04	0.43544
1.33E+04	0.42890
1.36E+04	0.42248
1.38E+04	0.41618
1.40E+04	0.40999
1.43E+04	0.40392
1.45E+04	0.39796
1.47E+04	0.39210
1.50E+04	0.38636
1.52E+04	0.38071
1.54E+04	0.37517
1.56E+04	0.36973
1.59E+04	0.36439
1.61E+04	0.35914
1.63E+04	0.35399
1.66E+04	0.34892
1.68E+04	0.34395
1.70E+04	0.33906
1.72E+04	0.33427
1.74E+04	0.32955
1.77E+04	0.32492
1.79E+04	0.32037
1.81E+04	0.31590

1.83E+04	0.31150
1.85E+04	0.30718
1.87E+04	0.30294
1.90E+04	0.29877
1.92E+04	0.29467
1.94E+04	0.29064
1.96E+04	0.28668
1.98E+04	0.28279
2.00E+04	0.27896
2.02E+04	0.27520
2.04E+04	0.27150
2.06E+04	0.26786
2.09E+04	0.26428
2.11E+04	0.26077
2.13E+04	0.25731
2.15E+04	0.25391
2.17E+04	0.25057
2.19E+04	0.24728
2.21E+04	0.24404
2.23E+04	0.24086
2.25E+04	0.23773
2.27E+04	0.23465
2.29E+04	0.23162
2.31E+04	0.22864
2.33E+04	0.22571
2.35E+04	0.22283
2.37E+04	0.21999
2.39E+04	0.21720
2.41E+04	0.00000

RELEASE INTERVAL NUMBER= 102

PATHLINE PARAMETERS:

TRAVELTIME	PATH LENGTH	VELOCITY	PDF
2.2010E+01	1.0190E+03	4.6297E+01	5.5556E+01
2.2019E+01	1.0200E+03	4.6324E+01	5.0000E+02
2.2020E+01	1.0210E+03	4.6367E+01	0.0000E-01

ADDITIONAL ZONE PARAMETERS:

XV=2.0000E+01 TV=1.4500E+01

AVERAGES:

LENGTH=1.0000E+03 TIME=2.2016E+01 VELOCITY=4.6329E+01

\*\*\* QUANTITY IS CONCENTRATION \*\*\*

CONVERSION FACTOR = 3.2695E-05

DISTANCE (X)	TIME (T)	PORE VOLUME (VVO)	QUANTITY (Q)
1.0000E+03	3.1955E+04	1.4805E+03	1.39843E-49
1.0000E+03	3.2953E+04	1.5267E+03	1.64081E-23
1.0000E+03	3.3951E+04	1.5729E+03	2.06558E-07
1.0000E+03	3.4949E+04	1.6192E+03	3.18349E+00
1.0000E+03	3.5947E+04	1.6654E+03	2.73703E+01

1.0000E+03	3.6945E+04	1.7116E+03	2.57405E+01
1.0000E+03	3.7943E+04	1.7579E+03	2.41840E+01
1.0000E+03	3.8941E+04	1.8041E+03	2.27217E+01
1.0000E+03	3.9939E+04	1.8503E+03	2.13477E+01
1.0000E+03	4.0937E+04	1.8966E+03	2.00569E+01
1.0000E+03	4.1935E+04	1.9428E+03	1.88441E+01
1.0000E+03	4.2933E+04	1.9890E+03	1.77046E+01
1.0000E+03	4.3931E+04	2.0353E+03	1.66340E+01
1.0000E+03	4.4929E+04	2.0815E+03	1.56282E+01
1.0000E+03	4.5927E+04	2.1277E+03	1.46832E+01
1.0000E+03	4.6925E+04	2.1740E+03	1.37953E+01
1.0000E+03	4.7923E+04	2.2202E+03	1.29611E+01
1.0000E+03	4.8921E+04	2.2665E+03	1.21774E+01
1.0000E+03	4.9919E+04	2.3127E+03	1.14411E+01
1.0000E+03	5.0916E+04	2.3589E+03	1.07492E+01
1.0000E+03	5.1914E+04	2.4052E+03	1.00993E+01
1.0000E+03	5.2912E+04	2.4514E+03	9.48857E+00
1.0000E+03	5.3910E+04	2.4976E+03	8.91481E+00
1.0000E+03	5.4908E+04	2.5439E+03	8.37575E+00
1.0000E+03	5.5906E+04	2.5901E+03	7.86929E+00
1.0000E+03	5.6904E+04	2.6363E+03	7.39345E+00
1.0000E+03	5.7902E+04	2.6826E+03	6.94641E+00
1.0000E+03	5.9898E+04	2.7750E+03	1.91932E+00
1.0000E+03	6.0896E+04	2.8213E+03	1.61312E-09