

Calvert Cliffs Nuclear Power Plant

Development of Evacuation Time Estimates



Prepared for:

Constellation Energy

by:

KLD Associates, Inc. 43 Corporate Drive Hauppauge, NY 11788 satya@kldcompanies.com

January, 2010

Final Report (Revision 2)

TABLE OF CONTENTS

<u>Section</u>	<u>Title</u> Page
	Executive SummaryES-1
1.	INTRODUCTION
1.1	Overview of the ETE Update Process1-1
1.2	The Calvert Cliffs Nuclear Plant Site Location
1.3	Preliminary Activities1-5
1.4	Comparison with Prior ETE Study1-9
2.	STUDY ESTIMATES AND ASSUMPTIONS
2.1	Data Estimates
2.2	Study Methodological Assumptions
2.3	Study Assumptions
3.	DEMAND ESTIMATION
4.	ESTIMATION OF HIGHWAY CAPACITY
5.	ESTIMATION OF TRIP GENERATION TIME
6.	DEMAND ESTIMATION FOR EVACUATION SCENARIOS6-1
7.	GENERAL POPULATION EVACUATION TIME ESTIMATES (ETE)
7.1	Voluntary Evacuation and Shadow Evacuation
7.2	Patterns of Traffic Congestion During Evacuation
7.3	Evacuation Rates
7.4	Guidance on Using ETE Tables
8.	TRANSIT-DEPENDENT AND SPECIAL FACILITY EVACUATION TIME
	ESTIMATES
8.1	Transit-Dependent People-Demand Estimate
8.2	School Population-Transit Demand
8.3	Special Facility Demand
8.4	Evacuation Time Estimates for Transit-Dependent People
9.	TRAFFIC MANAGEMENT STRATEGY
10.	EVACUATION ROUTES 10-1
11.	SURVEILLANCE OF EVACUATION OPERATIONS
12.	CONFIRMATION TIME
13.	RECOMMENDATIONS

.

LIST OF APPENDICES

- Appendix A Glossary of Traffic Engineering Terms
- Appendix B Traffic Assignment and Distribution Model
- Appendix C Traffic Simulation Model: PC-DYNEV
- Appendix D..... Detailed Description of Study Procedure
- Appendix E Special Facility Data
- Appendix F Telephone Survey
- Appendix G..... Traffic Management
- Appendix H..... Evacuation Region Maps
- Appendix I..... Evacuation Sensitivity Studies
- Appendix J..... Evacuation Time Estimates for all Evacuation Regions and Scenarios and Evacuation Time Graphs for Region R03, for all Scenarios
- Appendix K Evacuation Roadway Network
- Appendix L.....Zone Boundaries

LIST OF FIGURES

Number <u>Title</u>

.

ī

1-1	Calvert Cliffs Nuclear Power Plant Site Location
1-2	CCNPP Link-Node Analysis Network1-8
2-1	Voluntary Evacuation Methodology2-4
3-1	CCNPP EPZ Showing Zones3-4
3-2	Permanent Residents by Sector3-6
3-3	Permanent Resident Vehicles by Sector3-7
3-4	Transient Population by Sector3-10
3-5	Transient Vehicles by Sector3-11
3-6	Employee Population by Sector3-14
3-7	Employee Vehicles by Sector3-15
4-1	Fundamental Relationship between Volume and Density4-3
5-1	Events and Activities Preceding the Evacuation Trip5-5
5-2	Evacuation Mobilization Activities5-10
5-3	Comparison of Trip Generation Distributions
6-1	Calvert Cliffs Nuclear Power Plant Zones6-3
7-1	Assumed Evacuation Response7-14
7-2	CCNPP Shadow Evacuation Region7-15
7-3	Congestion Patterns at 1½ Hours after the Evacuation Advisory
	Scenario 1, Full EPZ 7-16
7-4	Congestion Patterns at 3½ Hours after the Evacuation Advisory
	Scenario 1, Full EPZ7-17
7-5	Congestion Patterns at 4 Hours 45 Mins. after the Evacuation Advisory
	Scenario 1, Full EPZ7-18
7-6	Congestion Patterns at 5 Hours. 40 Mins. after the Evacuation Advisory
	Scenario 1, Full EPZ7-19
7-7	Evacuation Time Estimates for CCNPP, Summer, Midweek,
	Midday, Good Weather, Evacuation of Region R03 (Entire EPZ)7-20

LIST OF FIGURES (Continued)

<u>Number</u>	Title	Page
8-1	Chronology of Transit Evacuation Operations	8-11
8-2	Proposed Transit Dependent Bus Routes	8-12
8-3	Schools within EPZ and Host Schools	8-13
10-1	General Population Reception Centers	10-2
10-2	Evacuation Route Map for Calvert County	
	(Zones 1 through 5)	10-3
10-3	Evacuation Route Map for St. Mary's County	
	(Zone 6 and 7)	10-4
10-4	Evacuation Route Map for Dorchester County	
	(Zone 8)	10-5

1

LIST OF TABLES

<u>Number</u><u>Title</u>

Page

1-1	ETE Study Comparisons	1-10
2-1	Evacuation Scenario Definitions	2-3
3-1	EPZ Permanent Resident Population	3-5
3-2	Permanent Resident Population and Evacuating Vehicles by Zone	3-5
3-3	Summary of Transients by Zone	3-9
3-4	Summary of Non-EPZ Employees by Zone	3-13
5-1	Trip Generation Time Histograms for the EPZ Population	5-14
6-1	Description of Evacuation Regions	6-2
6-2	Evacuation Scenario Definitions	6-4
6-3	Percent of Population Groups Evacuating for Various Scenarios	6-5
6-4	Vehicle Estimates by Scenario	6-6
6-5	Estimated Permanent Resident Population in 2013	6-7
7-1A	Time to Clear the Indicated Area of 50 Percent of the Affected	
	Population	7-9
7-1B	Time to Clear the Indicated Area of 90 Percent of the Affected	
	Population	7-10
7-1C	Time to Clear the Indicated Area of 95 Percent of the Affected	
	Population	7-11
7-1D	Time to Clear the Indicated Area of 100 Percent of the Affected	
	Population	7-12
7-2	Description of Evacuation Regions	7-13

LIST OF TABLES (Continued)

Number <u>Title</u>

<u>Page</u>

8-1	Transit Dependent Population Estimates 8-14
8-2	School Population Demand Estimates 8-15
8-3	Host Schools 8-16
8-4	Special Facility Transit Demand8-17
8-5A	School Evacuation Time Estimates – Good Weather 8-18
8-5B	School Evacuation Time Estimates – Rain8-20
8-6	Summary of Transit Dependent Bus Routes 8-22
8-7A	Transit-Dependent Evacuation Time Estimates – Good Weather 8-22
8-7B	Transit-Dependent Evacuation Time Estimates - Rain8-22
12-1	Estimated Number of Telephone Calls Required for
	Confirmation of Evacuation 12-2

EXECUTIVE SUMMARY

This report describes the analyses undertaken and the results obtained by a study to develop Evacuation Time Estimates (ETE) for the Calvert Cliffs Nuclear Power Plant (CCNPP) located in Lusby, Maryland. Evacuation time estimates are part of the required planning basis and provide CCNPP and State and local governments with site-specific information needed for Protective Action decision-making.

In the performance of this effort, all available prior documentation relevant to Evacuation Time Estimates was reviewed. Other guidance is provided by documents published by Federal Government agencies. Most important of these are:

- Criteria for Preparation and Evaluation of Radiological Emergency Response Plans and Preparedness in Support of Nuclear Power Plants, NUREG 0654/FEMA-REP-1, Rev. 1, November 1980.
- Analysis of Techniques for Estimating Evacuation Times for Emergency Planning Zones, NUREG/CR-1745, November 1980.
- Development of Evacuation Time Estimates for Nuclear Power Plants, NUREG/CR-6863, January 2005.

Overview of Project Activities

This project began in July, 2007 and extended over a period of 9 months. The major activities performed are briefly described in chronological sequence:

- Attended "kick-off" meetings with Constellation Energy personnel and emergency management personnel representing state and local governments.
- Reviewed prior ETE reports prepared for CCNPP and accessed U.S. Census Bureau data files for the year 2000. Studied Geographical Information Systems (GIS) maps of the area in the vicinity of CCNPP, then conducted a detailed field survey of the highway network.
- Synthesized this information to create an analysis network representing the highway system topology and capacities within the Emergency Planning Zone (EPZ), plus a "Shadow" area extending 15 miles radially from the plant.
- Designed and sponsored a telephone survey of residents within the EPZ to gather focused data needed for this ETE study that were not contained within the census database. The survey instrument was reviewed and modified by State and county personnel prior to the survey.
- The traffic demand and trip-generation rates of evacuating vehicles were estimated from the gathered data. The trip generation rates reflected the estimated mobilization time (i.e., the time required by evacuees to prepare for the

evacuation trip) computed using the results of the telephone survey of EPZ residents.

- Following Federal guidelines, the EPZ is subdivided into 8 Zones. These Zones are then grouped within circular areas or "keyhole" configurations (circles plus radial sectors) that define a total of 14 Evacuation Regions.
- The time-varying external circumstances are represented as Evacuation Scenarios, each described in terms of the following factors: (1) Season (Summer, Winter); (2) Day of Week (Midweek, Weekend); (3) Time of Day (Midday, Evening); and (4) Weather (Good, Rain, Snow). One special scenario involving construction of a new unit at the CCNPP and one special scenario involving the Air Show at the Patuxent Naval Airbase were considered.
- The Planning Basis for the calculation of ETE is:
 - A rapidly escalating accident at CCNPP that quickly assumes the status of General Emergency such that the Advisory to Evacuate is virtually coincident with the siren alert.
 - While an unlikely accident scenario, this planning basis will yield ETE, measured as the elapsed time from the Advisory to Evacuate until the last vehicle exits the impacted Region, that represent "upper bound" estimates. This conservative Planning Basis is applicable for all initiating events.
- If the emergency occurs while schools are in session, the ETE study assumes that the children will be evacuated by bus directly to specified host schools outside the EPZ. Parents, relatives, and neighbors are advised to not pick up their children at school prior to the arrival of the buses dispatched for that purpose. The ETE for school children are calculated separately.
- Evacuees who do not have access to a private vehicle will either ride-share with relatives, friends or neighbors, or be evacuated by buses provided as specified in the county evacuation plans. Those in special facilities will likewise be evacuated with public transit, as needed: bus, van, or ambulance, as required. Separate ETE are calculated for the transit-dependent evacuees and for those evacuated from special facilities.

Computation of ETE

A total of 196 ETE were computed for the evacuation of the general public. Each ETE | quantifies the aggregate evacuation time estimated for the population within one of the 14 Evacuation Regions to completely evacuate from that Region, under the circumstances defined for one of the 14 Evacuation Scenarios (14 x 14 = 196). | Separate ETE are calculated for transit-dependent evacuees, including school children

for applicable scenarios.

Except for Region R03, which is the evacuation of the entire EPZ, only a portion of the people within the EPZ would be advised to evacuate. That is, the Advisory to Evacuate applies only to those people occupying the specified impacted region. It is assumed that 100 percent of the people within the impacted region will evacuate in response to this Advisory. The people occupying the remainder of the EPZ outside the impacted region may be advised to take shelter.

The computation of ETE assumes that a portion of the population within the EPZ but outside the impacted region, will elect to "voluntarily" evacuate. In addition, a portion of the population in the "Shadow" region beyond the EPZ that extends a distance of 15 miles from CCNPP, will also elect to evacuate. These voluntary evacuees could impede those who are evacuating from within the impacted region. The impedance that could be caused by voluntary evacuees is considered in the computation of ETE for the impacted region.

The computational procedure is outlined as follows:

- A link-node representation of the highway network is coded. Each link represents a unidirectional length of highway; each node usually represents an intersection or merge point. The capacity of each link is estimated based on the field survey observations and on established procedures.
- The evacuation trips are generated at locations called "zonal centroids" located within the EPZ. The trip generation rates vary over time reflecting the mobilization process, and from one location (centroid) to another depending on population density and on whether a centroid is within, or outside, the impacted area.
- The computer models compute the routing patterns for evacuating vehicles that are compliant with federal guidelines (in general, outbound relative to the location of CCNPP), then simulate the traffic flow movements over space and time. This simulation process estimates the rate that traffic flow exits the impacted region.
- The ETE statistics provide the elapsed times for 50 percent, 90 percent, 95 percent and 100 percent, respectively, of the population within the impacted region, to evacuate from within the impacted region. These statistics are presented in tabular and graphical formats.

Traffic Management

This study includes the development of a comprehensive traffic management plan designed to expedite the evacuation of people from within an impacted region. This plan, which will be reviewed with State and local law enforcement personnel, is also designed to control access into the EPZ after returning commuters have rejoined their families.

The plan is documented in the form of detailed schematics specifying: (1) the directions of evacuation travel to be facilitated, and other traffic movements to be discouraged; (2) the traffic control personnel and equipment needed (cones, barricades) and their deployment; (3) the locations of these "Traffic Control Points" (TCP); (4) the priority assigned to each traffic control point indicating its relative importance and how soon it should be manned relative to others; and (5) the number of traffic control personnel required.

Selected Results

A compilation of selected information is presented on the following pages in the form of Figures and Tables extracted from the body of the report; these are described below.

- Figure 3-1 displays a map of the CCNPP site showing the layout of the 8 Zones that comprise, in aggregate, the Emergency Planning Zone (EPZ).
- Table 3-1 presents the estimates of permanent resident population in each Zone based on the 2000 Census data. Extrapolation to the year 2008 reflects population growth rates in each county derived from census data.
- Table 6-1 defines each of the 14 Evacuation Regions in terms of their respective groups of zones.
- Table 6-2 lists the 14 Evacuation Scenarios.
- Table 7-1D is a compilation of ETE. These data are the times needed to *clear the indicated regions* of 100 percent of the population occupying these regions. These computed ETE include consideration of mobilization time and of estimated voluntary evacuations from other regions within the EPZ and from the shadow region.
- Table 8-5A presents ETE for the schoolchildren in good weather.
- Table 8-7A presents ETE for the transit-dependent population in good weather.



CCNPP Evacuation Time Estimates ES-5

KLD Associates, Inc. Rev. 2

Table 3-1. EPZ Permanent Resident Population									
Zone	County	2000 Population	2008 Population						
1	Calvert	5,250	6,484						
2	Calvert	4,081	5,040						
3	Calvert	17,069	21,080						
4	Calvert	4,139	5,112						
5	Calvert	2,283	2,820						
6	St. Mary's	4,246	5,074						
7	St. Mary's	7,770	9,284						
8	Dorchester	295	311						
тот	AL:	45,133	55,205						
	Population G	rowth:	22.3%						

	Table 6-1. Description of E	vacua	tion F	Regio	ns				i				
Pogion	Description		ZONE										
Region	Description	1	2	3	4 ·	5	6	7	8				
R01	2-Mile Ring	X											
R02	5-Mile Ring	X	X	X									
R03	Full EPZ	X	X	X	Χ	X	X	X	X				
	Evacuate 2-Mile Ring and	5 Miles	s Dov	vnwir	nd								
Region	Wind Direction Towards:	ZONE											
		1	2	3	4	5	6	7	8				
	N, NNE, NE, ENE, E			S	ee Re	gion	1	-					
R04	ESE, SE, SSE, S	X		X									
	SSW, SW, WSW			S	ee Re	egion	2						
R05	W, WNW, NW, NNW	X	X										
	Evacuate 5-Mile Ring and Dow	nwind	to EP	Z Bo	unda	ry							
Region	Wind Direction Towards:		ZONE										
		1	2	3	4	5	6	7	8				
	NNE		·	S	ee Re	gion	2		· · · · · ·				
R06	NE, ENE, E, ESE, SE	X	X	X					X				
R07	SSE, S	X	X	X	-			X					
R08	SSW, SW	X	X	X			X	X					
R09	WSW	X	X	X	X		X	Х					
R10	W	X	X	X	X		Х						
R11	WNW	X	X	X	X	X	X						
R12	NW, NNW	X	X	X	X	X							
R13	N	X	Χ	X		X							
R14	*	X			·				X				

*This Region was added at Constellation Energy's request. It is an evacuation of the 2-Mile Ring and downwind (Towards Dorchester County) to the EPZ Boundary.

	Table 6-2 Evacuation Scenario Definitions										
Scenarios	Season	Day of Week	Time of Day	Weather	Special						
1	Summer	Midweek	Midday	Good	None						
2	Summer	Midweek	Midday	Rain	None						
3	Summer	Weekend	Midday	Good	None						
4	Summer	Weekend	Midday	Rain	None						
5	Summer	Midweek, Weekend	Evening	Good	None						
6	Winter	Midweek	Midweek Midday Good								
7	Winter	Midweek	Midday	Rain	None						
8	Winter	Weekend	Midday	Good	None						
9	Winter	Weekend	Midday	Rain	None						
10	Winter	Midweek, Weekend	Evening	Good	None						
11	Summer	Midweek	Midday	Good	New Plant Construction						
12	Summer	Weekend	Midday Good Air S		Air Show at the Naval Base						
13	Winter	Midweek	Midday	Snow	None						
14	Winter	Weekend	Midday	Snow	None						

Note: Schools are assumed to be in session for the Winter season (midweek, midday).

.

[Та	bie 7-1[D. Tim	e To Cle	ar The I	ndica	ted Area	a of 10	0 Percei	nt of the Af	fected Pop	lation		
s	ieason	Sum	mer	Sum	ner	Summer	Wint	er	Wint	er -	Winter	Summer	Summer	Winter	Winter	Season
Day	of Week	Midv	veek	Week	end	All	. Midw	eek	Week	end	AİI	Midweek	Weekend	Midweek	Weekend	Day of Week
Sc	enario:	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	Scenario
Tin	ne of Day	Mid	day	Midd	lay	Evening	Midd	ay	Midd	ay	Evening	Midday	Midday	Midday	Midday	Time of Day
Zone	Region Wind Direction	Good Weather	Rain	Good Weather	Rain	Good Weather	Good Weather	Rain	Good Weather	Rain	Good Weather	New Plant Construction	Air Show at Base	Snow	Snow	Region Wind Direction Towards
				_			Enti	re 2-Mile	Region, 5-	lile Regi	on, and EPZ					
1	R01 2-mile ring	4:10	4:10	4:05	4:15	4:05	4:10	4:15	4:10	4:10	4:15	4:30	4:00	5:15	5:15	R01 2-mile ring
1,2,3	R02 5-mile ring	5:25	6:05	5:55	6:30	5:00	5:20	5:55	5:20	5:55	4:50	5:50	6:35	6:45	6:40	R02 5-mile ring
1,2,3,4,5, 6,7,8	R03 Entire EPZ	6:00	6:45	6:25	7:10	5:30	5:50	6:20	5:50	6:30	5:25	6:30	11:30	7:25	7:25	R03 Entire EPZ
								2-Mile Ri	ng and Dow	nwind to	5 Miles					
1	N, NNE, NE, ENE, E						Re	fer to Re	gion 1							N, NNE, NE, ENE, E
1,3	R04 ESE, SE, SSE, S	5:25	6:05	5:55	6:35	4:55	5:20	5:50	5:15	5:50	4:50	5:45	6:20	6:45	6:40	R04 ESE, SE, SSE, S
1,2,3	SSW, SW, WSW		Refer to Region 2									SSW, SW, WSW				
1,2	R05 W, WNW, NW, NNW	4:15	4:20	4:15	4:15	4:15	4;15	4:20	4:10	4:15	4:10	4:50	4:10	5:20	5:15	R05 W, WNW, NW, NNW
[5-Mi	le Ring a	and Downwi	nd to EP	Z Boundary					
1,2,3	NNE						Re	fer to Re	gion 2							NNE
1,2,3,8	R06 NE, ENE, E, ESE, SE	5:25	6:05	5:55	6:30	5:00	5:20	5:55	5:20	5:55	4:50	5:50	6:35	6:45	6:40	R06 NE, ENE, E, ESE, SE
1,2,3,7	R07 SSE, S	6:00	6:35	6:20	7:00	5:20	5:45	6:15	5:45	6:20	5:20	6:20	11:25	7:15	7:20	R07 SSE, S
1,2,3,6,7	R08 SSW, SW	6:00	6:45	6:25	7:10	5:30	5:50	6:20	5:50	6:30	5:25	6:30	11:30	7:25	7:30	R08 SSW, SW
1,2,3,4,6, 7	R09 WSW	6:00	6:45	6:25	7:10	5:30	5:50	6:20	5:50	6:30	5:25	6:30	11:30	7:25	7:25	R09 WSW
1,2,3,4,6	R10 W	5:45	6:20	6:15	7:00	5:20	5:45	6:20	5:45	6:20	5:20	6:10	11:20	7:05	7:05	R10 W
1,2,3,4,5, 6	R11 WNW	5:45	6:20	6:15	7:00	5:20	5:45	6:20	5:45	6:20	5:20	6:10	11:20	7:05	7:05	R11 WNW
1,2,3,4,5	R12 NW, NNW	5:25	6:05	5:55	6:30	4:55	5:20	5:55	5:20	5:55	4:50	5:50	6:35	6:45	6:40	R12 NW, NNW
1,2,3,5	R13 N	5:25	6:05	5:55	6:30	5:00	5:20	5:55	5:20	5:55	4:50	5:50	6:35	6:45	6:40	R13 N
1,8	R14	4:10	4:10	4:10	4:15	4:10	4:10	4:20	4:10	4:10	4:15	4:35	4:05	5:15	5:15	R14

CCNPP Evacuation Time Estimate

5

.

~

Table 8-54 School Evacuation Time Estimates - Good Weather 1st Wave									
School	Driver Mobilization Time(min)	Loading Time (min)	Dist. to EPZ Boundary (mi.)	Travel Time to EPZ Bdry (min)	ETE (hr:min)	Dist. EPZ Bdry to H.S. (mi.)	Travel Time EPZ Bdry to H.S. (min)	ETE to H.S. (hr:min)	
Calvert County Schools									
Appeal Elementary School	90	5	8.0	26	2:05	40.9	62	3:05	
Dowell Elementary School	90	5	6.6	21	2300	36.7	56	2:55	
Mill Creek Middle School	90	5	6.4	21	2:00	41.3	62	3:00	
Mutual Elementary School	90	5	5.9	19	1:53	2.0	3	2:00	
Our Lady Star of the Sea School	60	5	8.9	20	1:23	49.2	74	2340	
Patuxent Elementary School	90	5	8.0	23	2:03	42.8	65	3:10	
Patuxent High School	90	5	8.8	28	2:03	48.7	74	3:20	
Southern Middle School	60	5	10.2	23	1:30	48.7	74	2:45	
St. Leonard Elementary School	90	5	7.0	22	2:00	14.6	22	2:20	
a anger nav in the triping we was seen	St. Ma	ry's Cou	nty Scho	ols	* 5k			±	
Esperanza Middle School	60	5	0.0	0	1:03	8.9	14	1:20	
Green Holly Elementary School	60	5	0.2	1	1:10	6.5	10	1:20	
Hollywood Elementary School	60	5	6.1	14	1:20	5.8	9	1:30	
St. John's Elementary School	60	5	0.7	2	1:10	5.9	9	1:20	
Town Creek Elementary School	60	5	0.7	2	1:10	15.8	24	1:36	
			Averag	e for EPZ:	1:40	A .	verage:	2:20	

Table 8-7A. Transit Dependent Evacuation Time Estimate - Good Weather										
		Single Wave	. 1				Sec	cond Wave		
Buses	Mobilization	Route Travel Time	Pickup Time	ETE	Mobilization	Unload Time	Driver Rest Time	Route travel Time	Pickup Time	ETE
Batch 1	90	183	30	5:05	140	5	10	183	30	6:10
Batch 2	120	236	30	6:30	170	5	10	236	30	7:35

ES-11

1. INTRODUCTION

This report describes the analyses undertaken and the results obtained by a study to update the existing Evacuation Time Estimates (ETE) for the Calvert Cliffs Nuclear Power Plant (CCNPP), located in Calvert County, Maryland. Evacuation time estimates are part of the required planning basis and provide State and local governments with site-specific information needed for Protective Action decision-making.

In the performance of this effort, all available prior documentation relevant to Evacuation Time Estimates was reviewed.

Other guidance is provided by documents published by Federal Government agencies. Most important of these are:

- Criteria for Preparation and Evaluation of Radiological Emergency Response Plans and Preparedness in Support of Nuclear Power Plants, NUREG 0654/FEMA-REP-1, Rev. 1, November 1980.
- Analysis of Techniques for Estimating Evacuation Times for Emergency Planning Zones, NUREG/CR-1745, November 1980.
- Development of Evacuation Time Estimates for Nuclear Power Plants, NUREG/CR-6863, January 2005.

We wish to express our appreciation to all the directors and staff members of the Calvert County, St. Mary's County and Dorchester County emergency management agencies and local and state law enforcement and planning agencies, who provided valued guidance and contributed information contained in this report.

1.1 Overview of the ETE Update Process

The following outline presents a brief description of the work effort in chronological sequence:

- 1. Information Gathering:
 - Defined the scope of work in discussion with representatives of Constellation Energy.
 - Reviewed existing reports describing past evacuation studies.
 - Attended meetings with emergency planners from the three Evacuation Planning Zone (EPZ) Counties to identify issues to be addressed.

- Conducted a detailed field survey of the EPZ highway system and of area traffic conditions.
- Obtained demographic data from census and state agencies.
- Conducted a random sample telephone survey of EPZ residents.
- Conducted a data collection effort to identify and describe schools, special facilities, major employers, transportation providers, and other important sources of information.
- 2. Estimated distributions of Trip Generation times representing the time required by various population groups (permanent residents, employees, and transients) to prepare (mobilize) for the evacuation trip. These estimates are primarily based upon the random sample telephone survey.
- 3. Defined Evacuation Scenarios. These scenarios reflect the variation in demand, trip generation distribution and in highway capacities, associated with different seasons, day of week, time of day and weather conditions.
- 4. Defined a traffic management strategy. Traffic control is applied at specified Traffic Control Points (TCP) located within the Emergency Planning Zone (EPZ), and at Access Control Points (ACP) located on the periphery of the EPZ. Local and state police personnel should review all traffic control plans.
- 5. Defined Evacuation Areas or Regions. The EPZ is partitioned into Protective Action Zones (Zones) which serve as a basis for the ETE analysis presented herein. Evacuation "Regions" are comprised of contiguous Zones for which ETE are calculated. The configuration of these Regions reflects the fact that the wind can take any direction and that the radial extent of the impacted area depends on accident-related circumstances. Each Region, other than those that approximate circular areas, approximates a "key-hole" configuration within the EPZ as required by NUREG/CR-6863.
- 6. Estimated demand for transit services for persons at "Special Facilities" and for transit-dependent persons at home.
- 7. Prepared the input streams for the IDYNEV system.
 - Estimated the traffic demand, based on the available information derived from Census data, from prior studies, from data provided by local and state agencies and from the telephone survey.
 - Applied the procedures specified in the 2000 Highway Capacity Manual (HCM) to the data acquired during the field survey, to estimate the capacity of all highway segments comprising the evacuation routes.

- Developed the link-node representation of the evacuation network, which is used as the basis for the computer analysis that calculates the ETE.
- Calculated the evacuating traffic demands for each Region and for each Evacuation Scenario. Considered the effects on demand of "voluntary evacuation" and of "shadow evacuation".
- Represented the traffic management strategy.
- Specified the candidate destinations of evacuation travel consistent with outbound movement relative to the location of the CCNPP.
- Prepared the input stream for the IDYNEV System.
- Executed the IDYNEV models to provide the estimates of evacuation routing and ETE.
- 8. Generated a complete set of ETE for all specified Evacuation Regions and Scenarios.
- 9. Documented ETE in formats responsive to the cited NUREG reports.
- 10. Calculated the ETE for all transit activities including those for special facilities (schools, health-related facilities, etc.) and for the transit-dependent.

Steps 4, 7 and 8 are iterated as described in Appendix D.

1.2 The Calvert Cliffs Nuclear Plant Site Location

The Calvert Cliffs Nuclear Power Plant is located in Lusby, MD approximately 50 miles southeast of Washington, DC. The EPZ consists of parts of three counties: Calvert County, St. Mary's County and Dorchester County. Figure 1-1 displays the area surrounding the CCNNP. This map identifies the communities in the area and the major roads.





KLD Associates, Inc. Rev. 2

1.3 <u>Preliminary Activities</u>

Since this plan constitutes an update of an existing document, it was necessary to review the prior process and findings. These activities are described below.

Literature Review

KLD Associates was provided with copies of documents describing past studies and analyses leading to the development of emergency plans and of the ETE. We also obtained supporting documents from a variety of sources, which contained information needed to form the database used for conducting evacuation analyses.

Field Surveys of the Highway Network

KLD personnel drove the entire highway system within the EPZ and for some distance outside. The characteristics of each section of highway were recorded. These characteristics include:

Number of lanes	Posted speed				
Pavement Width	Actual free speed				
Shoulder type & width	Abutting land use				
Intersection configuration	Control devices				
Lane channelization	Interchange geometries				
Geometrics: Curves, grades	Street parking				
 Unusual characteristics: Narrow bridges, sharp curves, poor pavement, flood warning signs, inadequate delineations, etc. 					

Video and audio recording equipment were used to capture a permanent record of the highway infrastructure. No attempt was made to measure such attributes as lane width and shoulder width; estimates of these measures based on visual observation and recorded images were considered appropriate for the purpose of estimating the capacity of highway sections. For example, Exhibit 20-5 in the Highway Capacity Manual (HCM) indicates that a reduction in lane width from 12 feet (the "base" value) to 10 feet can reduce free flow speed (FFS) by 1.1 mph – not a material difference – for two lane highways. Exhibit 12-15 in the HCM shows no sensitivity for the estimates of Service Volumes at Level of Service (LOS) E (near capacity), with respect to FFS. The topography of the highway (Level, Rolling, and Mountainous) is a more important factor than lane and shoulder width when estimating capacity.

The data from the audio and video recordings were used to create detailed GIS

shapefiles and databases of the roadway characteristics and of the traffic control devices observed during the road survey; this information was referenced while preparing the input stream for the IDYNEV System.

As documented on page 20-3 of the HCM, the capacity of a two-lane highway is 1700 passenger cars per hour for each direction of travel. For freeway sections, a value of 2250 vehicles per hour per lane is assigned. The road survey has identified several segments which are characterized by adverse geometrics which are reflected in reduced values for both capacity and speed. These estimates reflect the service volumes for LOS E presented in HCM Exhibit 12-15. These links may be identified by reviewing Appendix K. Link capacity is an input to IDYNEV which calculates the ETE. The locations of these sections may be identified by reference to the maps in Appendix K which are discussed below.

Telephone Survey

A telephone survey was undertaken to gather information needed for the evacuation study. Appendix F presents the survey instrument, the procedures used and tabulations of data compiled from the survey returns.

These data were utilized to develop estimates of vehicle occupancy during an evacuation and to estimate elements of the mobilization process. This database was also referenced to estimate the number of transit-dependent residents.

Developing the Evacuation Time Estimates

The overall study procedure is outlined in Appendix D. Demographic data were obtained from several sources, as detailed later in this report. These data were analyzed and converted into vehicle demand data.

Highway capacity was estimated for each highway segment based on the field surveys and on the principles specified in the 2000 Highway Capacity Manual (HCM¹). The link-node representation of the physical highway network was developed using GIS mapping software and the observations obtained from the field survey. This network representation of "links" and "nodes" is shown in Figure 1-2. Appendix K contains largescale maps detailing the link-node analysis network, with the node numbers clearly displayed.

¹ Highway Capacity Manual (HCM2000), Transportation Research Board, National Research Council, 2000.

Analytical Tools

The IDYNEV System that was employed for this study is comprised of several integrated computer models. One of these is the PC-DYNEV (<u>DY</u>namic <u>Network</u> <u>EV</u>acuation) macroscopic simulation model that was developed by KLD under contract with the Federal Emergency Management Agency (FEMA).

I-DYNEV consists of three submodels:

- A macroscopic traffic simulation model (for details, see Appendix C).
- An intersection capacity model (for details, see Highway Research Record No. 772, Transportation Research Board, 1980, papers by Lieberman and McShane & Lieberman).
- A dynamic, node-centric routing model that adjusts the "base" routing in the event of an imbalance in the levels of congestion on the outbound links.

Another model of the IDYNEV System is the TRAD (<u>TRaffic Assignment and</u> <u>Distribution</u>) model. This model integrates an equilibrium assignment model with a trip distribution algorithm to compute origin-destination volumes and paths of travel designed to minimize travel time. For details, see Appendix B.

Still another software product developed by KLD, named UNITES (<u>UNI</u>fied <u>Transportation Engineering System</u>) was used to expedite data entry.

The procedure for applying the IDYNEV System within the framework of developing an update to an ETE is outlined in Appendix D. Appendix A is a glossary of terms.



The evacuation analysis procedures are based upon the need to:

- Route traffic along paths of travel that will expedite their travel from their respective points of origin to points outside the EPZ.
- Restrict movement toward CCNPP to the extent practicable, and disperse traffic demand so as to avoid focusing demand on a limited number of highways.
- Move traffic in directions that are generally outbound, relative to the location of CCNPP.

A set of candidate destination nodes on the periphery of the EPZ is specified for each traffic origin (or centroid) within the EPZ. The TRAD model produces output that identifies the "best" traffic routing, subject to the design conditions outlined above. In addition to this information, rough estimates of travel time are provided, together with turn-movement data required by the PC-DYNEV simulation model. The evacuation routing used in the model is presented in Section 10 and also in the congestion diagrams in Section 7.

The simulation model is then executed to provide a detailed description of traffic operations on the evacuation network. This description enables the analyst to identify bottlenecks and to develop countermeasures that are designed to expedite the movement of vehicles. The outputs of this model are the volume of traffic, expressed as vehicles/hour, that exit the Evacuation Region along the various highways (links) that cross the Region boundaries. These outputs are exported into a spreadsheet, which is used to generate the ETE. Section 7 presents a further description of this process along with the ETE Tables.

As outlined in Appendix D, this procedure consists of an iterative design-analysis-redesign sequence of activities. If properly done, this procedure converges to yield an evacuation plan which best services the evacuating public.

1.4 Comparison with Prior ETE Study

Table 1-1 presents a comparison of the present ETE study with the study performed in 2002. The major factors contributing to the differences between the ETE values obtained in this study and those of the previous study can be summarized as follows:

- An increase in permanent resident population.
- Vehicle occupancy and Trip-generation rates are based on the results of a telephone survey of EPZ residents.
- Voluntary and shadow evacuations are considered.
- The highway representation is more detailed.
- Many more evacuation cases considered, responsive to NUREG/CR-6863.
- Traffic management plan included.

Table 1-1. ETE Study Comparisons				
Teele	Treatment			
горіс	Previous ETE Study	Current ETE Study		
Resident Population Basis	Maryland Department of Planning Estimate for population in 2000.	ArcGIS Software using 2000 US Census blocks; block centroid method used; population extrapolated to 2008.		
	Population = 50,058	Population = 55,205		
Resident Population Vehicle Occupancy	Average household size varies by County. Assumed, 1 vehicle/evacuating HH resulting in an average vehicle occupancy of : Calvert County = 2.91, St. Mary's County = 2.72, Dorchester County = 2.36 persons/vehicle	Based on telephone survey, Average household size within EPZ = 2.80 person/household and 1.46 vehicles/evacuating household, resulting in average vehicle occupancy of 1.92 person/vehicle		
Employee Population	Employee estimates based on information provided about major employers in EPZ. 1 employee/vehicle.	Employee estimates based on information provided about major employers in EPZ and on data provided by Census Journey-to-Work questionnaires. 1.03 employees/vehicle based on phone survey results.		
Voluntary evacuation from within EPZ in areas outside region to be evacuated	Not considered	50 percent of population within the radius being evacuated; 35 percent, in annular ring between the radius being evacuated and the EPZ boundary (See Figure 2-1).		
Shadow Evacuation	Not considered.	30% of people outside of the EPZ within the shadow area (See Figure 7-2).		
Network Size	204 links, 144 nodes	574 Internal Links; 422 Internal Nodes.		

,

•

.

,

Table 1-1. ETE Study Comparisons			
Tania	Treatment		
Горіс	Previous ETE Study	Current ETE Study	
Roadway Geometric Data	Field surveys conducted in 2001.	Field surveys conducted in 2006 and 2008. Major intersections were video archived. GIS shape-files of signal locations and roadway characteristics created during road survey. Road capacities based on 2000 HCM.	
School Evacuation	SchoolDirect evacuation to designatedDirect evacuation toEvacuationHost School.School.		
Transit Dependent Population	Not considered explicitly. Local emergency plans will provide buses for transit dependents.	Defined as households with 0 vehicles + households with 1 vehicle with commuters who do not return home + households with 2 vehicles with commuters who do not return home. Telephone survey results used to estimate transit dependent population.	
Ridesharing	100 percent of transit dependents will ride out with a friend	50 percent of transit dependent persons will ride out with a neighbor of friend.	
Trip Generation for Evacuation		Based on residential telephone survey of specific pre-trip mobilization activities:	
	Trip Generation curves created based on discussions with county emergency management officials.	Residents with commuters returning leave between 30 and 240 minutes.	
		Residents without commuters returning leave between 15 and 180 minutes.	
		Employees and transients leave between 15 and 120 minutes.	
		All times measured from the Advisory to Evacuate.	

•

Table 1-1. ETE Study Comparisons			
Topio	Treatment		
	Previous ETE Study	Current ETE Study	
Traffic and Access Control	List of Traffic control points identified.	Traffic and access control points identified and detailed schematics provided.	
Weather	Normal or Adverse. The capacity of each link in the network is reduced by 30% for adverse weather.Normal, Rain or Snow. The capa and free flow speed of all links in network are reduced by 10% in the event of rain and 20% for snow.		
Modeling	NETVAC2 IDYNEV System: TRAD and PC DYNEV.		
Special Events	None considered. Only a sensitivity analysis of the closure of the Thomas Johnson Bridge for the Full EPZ.	2 Special Events – New Plant Construction, Air Show at the Naval Base.	
Evacuation Cases	8 Regions, 2 seasons, 2 time of day, and 2 weather conditions producing 64 unique cases 14 Regions (central sec direction and each adjace technique used) and 14 producing 196 unique cases		
Evacuation Time Estimates Reporting	ETE reported for 100 th percentile population. Results presented by Region and Scenario.	ETE reported for the 50 th , 90 th , 95 th and 100 th percentile population. Results presented by Region and Scenario.	
Evacuation Time Estimates for the entire EPZ, 100 th percentile.	Full EPZ – Summer Daytime: Good weather = 5:50 Full EPZ – Summer Nightime: Good weather = 5:10 Full EPZ – Winter Daytime: Good weather = 6:10 Full EPZ – Winter Nightime: Good weather = 5:50	Summer Weekday Midday Good weather = 6: 00 Summer Evening Good weather = 5:30 Winter Weekday Midday Good weather = 5:50 Winter Evening Good weather = 5:25	

ç

2. STUDY ESTIMATES AND ASSUMPTIONS

This section presents the estimates and assumptions utilized in the development of the Evacuation Time Estimates (ETE).

- 2.1 Data Estimates
 - 1. Population estimates are based upon Census 2000 data, projected to year 2008. County-specific projections are based upon the estimates of the average annual growth rate for years between 2000 and 2010 provided by the Maryland Department of Planning, Planning Data Services. Estimates of employees who commute into the EPZ to work are based upon employment data obtained from county emergency management officials, company websites, the 2002 ETE Study Report, telephone calls to employers within the EPZ and the state Journey-to-Work census data.
 - 2. Population estimates at special facilities are based on available data from county emergency management offices, direct phone calls to the facilities, | related websites, and the 2002 ETE Study Report.
 - 3. Roadway capacity estimates are based on field surveys and the application of Highway Capacity Manual 2000¹.
 - 4. Population mobilization times are based on a statistical analysis of data acquired from the telephone survey.
 - 5. The relationship between resident population and evacuating vehicles is developed from the telephone survey. The average values of 2.80 persons per household and 1.46 evacuating vehicles per household are used.
 - 6. Where facility-specific vehicle data is unavailable, the relationship between persons and vehicles for special facilities is as follows:
 - a. Parks/Recreational: 1 vehicle per family
 - b. Employees: 1.03 employees per vehicle (telephone survey results),
 - 7. ETE are presented for the evacuation of the 100th percentile of population for each Region and for each Scenario, and for the 2-mile, 5-mile and 10-mile distances. ETE are presented in tabular format and graphically, showing the values of ETE associated with the 50th, 90th and 95th percentiles of population. An Evacuation Region is defined as a group of Zones that is issued the Advisory to Evacuate.

¹ Highway Capacity Manual (HCM2000), Transportation Research Board, National Research Council, 2000.

2.2 <u>Study Methodological Assumptions</u>

- 1. The Evacuation Time is defined as the elapsed time from the Advisory to Evacuate issued to persons within a specific Region of the EPZ, and the time that Region is clear of the indicated percentile of people.
- 2. The ETE are computed and presented in a format compliant with the guidance in the cited NUREG documentation. The ETE for each evacuation area ("Region" comprised of included Zones) is presented in both statistical and graphical formats.
- 3. Evacuation movements (paths of travel) are generally outbound relative to the power plant to the extent permitted by the highway network, as computed by the computer models. All available evacuation routes are used in the analysis.
- 4. Regions are defined by the underlying "keyhole" or circular configurations as specified in NUREG/CR-6863. These Regions, as defined, display irregular boundaries reflecting the geography of the Zones included within these underlying configurations.
- 5. Voluntary evacuation is considered as indicated in the accompanying Figure 2-1. Within the circle defined by the distance to be evacuated but outside the Evacuation Region, 50 percent of the people not advised to evacuate are assumed to evacuate within the same time-frame. In the outer annular area between the circle defined by the extent of the Evacuation Region and the EPZ boundary, it is assumed that 35 percent of people will voluntarily evacuate. In the area between the EPZ boundary and a 15-mile circular area centered at the plant (the "shadow region"), it will be assumed that 30 percent of the people will evacuate voluntarily. Sensitivity studies explored the effect on ETE, of increasing the percentage of voluntary evacuees in this area (Appendix I). The basis for our assumptions on voluntary evacuation is testimony proffered by Dennis Miletti, a professor at Colorado State University, and one of the nations top disaster response experts, at Atomic Safety and Licensing Board (ASLB) hearings, which were deemed acceptable. There are limited data pertaining to nuclear evacuations in the United States. The numbers we use are Professor Miletti's best estimates based on his years of experience in evacuation planning and emergency preparedness.
- 6. A total of 14 "Scenarios" representing different seasons, time of day, day of week and weather are considered. Two special event scenarios are studied: the peak construction period of a new unit at the CCNPP site, and the Airshow at the Patuxent Naval Air Base These Scenarios are tabulated below:

Table 2-1. Evacuation Scenario Definitions					
Scenario	Season	Day of Week	Time of Day	Weather	Special
1	Summer	Midweek	Midday	Good	None
2	Summer	Midweek	Midday	Rain	None
3	Summer	Weekend	Midday	Good	None
4	Summer	Weekend	Midday	Rain	None
5	Summer	Midweek, Weekend	Evening	Good	None
6	Winter	Midweek	Midday	Good	None
7	Winter	Midweek	Midday	Rain	None
8	Winter	Weekend	Midday	Good	None
9	Winter	Weekend	Midday	Rain	None
10	Winter	Midweek, Weekend	Evening	Good	None
11	Summer	Midweek	Midday	Good	New Plant Construction
12	Summer	Weekend	Midday	Good	Airshow at Base
13	Winter	Midweek	Midday	Snow	None
14	Winter	Weekend	Midday	Snow	None



 The models of the IDYNEV System represent the state of the art, and have been recognized as such by the Atomic Safety and Licensing Board (ASLB) in past hearings. (Sources: Atomic Safety & Licensing Board Hearings on Seabrook and Shoreham; Urbanik²).

2.3 <u>Study Assumptions</u>

- 1. The Planning Basis Assumption for the calculation of ETE is a rapidly escalating accident that requires evacuation, and includes the following:
 - a. Advisory to Evacuate is announced coincident with the siren notification.
 - b. Mobilization of the general population will commence within 10 minutes after the Advisory to Evacuate.
 - c. ETE are measured relative to the Advisory to Evacuate.
- 2. It is assumed that everyone within the group of Zones forming a Region that is issued an Advisory to Evacuate will, in fact, respond in general accord with the planned routes.
- 3. It is further assumed that:
 - a. Schools may be evacuated prior to notification of the general public, if possible.
 - b. 65 percent of households in the EPZ have at least one commuter, 58 percent of which will await the return of a commuter before beginning their evacuation trip, based on the telephone survey results.
- 4. The ETE will also include consideration of "through" (External-External) trips during the time that such traffic is permitted to enter the evacuated Region. "Normal" traffic flow is assumed to be present within the EPZ at the start of the emergency.
- 5. Access Control Points (ACP) will be staffed approximately 90 minutes after the siren notifications, to divert traffic attempting to enter the EPZ. Earlier activation of ACP locations could delay returning commuters. It is assumed that no vehicles will enter the EPZ after this 90 minute mobilization time period.
- 6. Traffic Control Points (TCP) within the EPZ will be staffed over time, beginning at the Advisory to Evacuate. Their number and location will depend on the Region to be evacuated and the personnel resources available. It is assumed that drivers will act rationally, travel in the directions identified in the plan (as documented in the public information material), and obey all control devices and traffic guides. While the manning of TCPs may expedite evacuation traffic operations relative to existing controls, the calculation of ETE does not rely on any expedited

² Urbanik, T., et. al. <u>Benchmark Study of the I-DYNEV Evacuation Time Estimate Computer Code</u>, NUREG/CR-4873, Nuclear Regulatory Commission, June, 1988

operations.

- 7. Buses will be used to transport those without access to private vehicles:
 - a. If schools are in session, transport (buses) will evacuate students directly to the assigned host schools.
 - b. School children, if school is in session, are given priority in assigning transit vehicles.
 - c. Bus mobilization time is considered in ETE calculations.
 - d. Analysis of the number of required "waves" of transit vehicles used for evacuation is presented.
- 8. It is reasonable to assume that some of the transit-dependent people will ride-share with family, neighbors, and friends, thus reducing the demand for buses. We assume that the percentage of people who rideshare is 50 percent. This assumption is based upon reported experience for other emergencies,³ which cites previous evacuation experience. The remaining transit-dependent portion of the general population will be evacuated to reception centers by bus.

9. Two types of adverse weather scenarios are considered. Rain may occur for either winter or summer scenarios. In the case of rain, it is assumed that the rain begins prior to, or at about the same time as the evacuation advisory is issued. No weather-related reduction in the number of transients who may be present in the EPZ is assumed.

Snow may occur in winter scenarios. Transient population reductions are not assumed for snow scenarios. Further, it is assumed that roads are passable and that the appropriate agencies are plowing the roads as they would normally.

Adverse weather scenarios affect roadway capacity and free flow highway speeds. The factors assumed for the ETE study are:

Scenario	Highway Capacity*	Free Flow Speed*	Mobilization Time
Rain⁴	90%	90%	No Effect
Snow⁴	80% 80%		Clear driveway before leaving home (Source: Telephone Survey)
*Adverse weather capacity and speed values are given as a percentage of good weather conditions. Roads are assumed to be passable.			

10. School buses used to transport students are assumed to have the capacity to transport 70 children per bus for elementary schools, and 50

³ Institute for Environmental Studies, University of Toronto, THE MISSISSAUGA EVACUATION FINAL REPORT, June 1981. The report indicates that 6,600 people of a transit-dependent population of 8,600 people shared rides with other residents; a ride share rate of 76% (Page 5-10).

⁴ Agarwal, M. et. Al. Impacts of Weather on Urban Freeway Traffic Flow Characteristics and Facility Capacity, Proceedings of the 2005 Mid-Continent Transportation Research Symposium, August, 2005.
children per bus for middle and high schools. Transit buses used to transport the transit-dependent general population are assumed to transport an average of 30 people per bus.

KLD Associates, Inc. Rev. 2

3. DEMAND ESTIMATION

The estimates of demand, expressed in terms of people and vehicles, constitute a critical element in developing an evacuation plan. These estimates consist of three components:

- 1. An estimate of population within the Emergency Planning Zone (EPZ), stratified into groups (resident, employee, transient).
- 2. An estimate, for each population group, of mean occupancy per evacuating vehicle. This estimate is used to determine the number of evacuating vehicles.
- 3. An estimate of potential double-counting of vehicles.

Appendix E presents much of the source material for the population estimates. Our primary source of population data, the 2000 Census, however, is not adequate for directly estimating some transient groups.

Throughout the year, vacationers and tourists enter the EPZ. These non-residents may dwell within the EPZ for a short period (e.g. a few days or one or two weeks), or may enter and leave within one day. Estimates of the size of these population components must be obtained, so that the associated number of evacuating vehicles can be ascertained.

The potential for double-counting people and vehicles must be addressed. For example:

- A resident who works and shops within the EPZ could be counted as a resident, again as an employee and once again as a shopper.
- A visitor who stays at a hotel and spends time at a park, then goes shopping could be counted three times.

Furthermore, the number of vehicles at a location depends on time of day. For example, motel parking lots may be full at dawn and empty at noon. Similarly, parking lots at area parks, which are full at noon, may be almost empty at dawn. It is clearly wrong to estimate counts of vehicles by simply adding up the capacities of different types of parking facilities, without considering such factors.

Analysis of the population characteristics of the Calvert Cliffs Nuclear Power Plant (CCNPP) EPZ indicates the need to identify three distinct groups:

- Permanent residents people who are year-round residents of the EPZ.
- Transients people who reside outside of the EPZ, who enter the area for a specific purpose (e.g., boating, camping) and then leave the area.

• Commuter-Employees - people who reside outside the EPZ and commute to businesses within the EPZ on a daily basis.

Estimates of the population and number of evacuating vehicles for each of the population groups are presented for each Zone and by polar coordinate representation (population rose). The CCNPP EPZ has been subdivided into 8 Zones as shown in Figure 3-1.

Permanent Residents

The primary source for estimating permanent population is the latest U.S. Census data. The average household size (2.80 persons/household) and the number of evacuating vehicles per household (1.46 vehicles/household) were adapted from the telephone survey results.

The rate of population change was found for each County in the EPZ and applied to project population to 2008. The estimated growth rates between 2000 and 2008 for the counties are as follows: Calvert County – 23.5%, St. Mary's County – 19.5%, and Dorchester County – 5.3%; this data was provided by the Maryland Department of Planning website, last updated in October of 2007. The data in Table 3-1 show that the EPZ population has increased by 22.3% over the last 8 years.

Permanent resident population and vehicle estimates for 2008 are presented in Table 3-2. Figures 3-2 and 3-3 present the permanent resident population and permanent resident vehicle estimates by sector and distance from the CCNPP. This "rose" was constructed using GIS software.

Construction

A "special event" scenario (Scenario 11) which represents a typical summer, mid-week, midday with good weather and with construction workers on-site during Shift 1 (7:30 AM to 4:00 PM) at the time of the emergency, is considered. This event is assumed to coincide with an outage at one of the two existing units. The peak construction period based on discussions with Unistar Nuclear - would be in the year 2013, with workforce estimates of 3,940 workers, working in 3 shifts with 70%, 25%, and 5% of workers in each shift, respectively. An average vehicle occupancy of 1.3 workers per vehicle was used to convert workers to vehicles for Shift 1-2,122 total vehicles. Additionally, 363 new employees (66% during max shift, 1.05 workers per vehicle, yielding 228 vehicles) related to the new unit and 750 employees (66% during max shift, 1.05 workers per vehicle, yielding 471 vehicles) present during the outage were considered. These employees combined with the construction staff resulted in a total of 2,821 additional vehicles. The existing roadway system is used for the construction scenario; no roadway improvements are considered; however, a new traffic signal at the entrance to the construction site along Nursery Road and Maryland Route 2/4 is used. Permanent resident population and shadow population are extrapolated to 2013 for this scenario.

Airshow at the Naval Air Base

Another special event considered (Scenario 12) is the Airshow at the Patuxent Naval Air Base. Based on information provided by the St. Mary's County Department of Public Safety, this event occurs every other year. The event lasts about 3 days and is normally during a summer weekend (May or June). The expected attendance is approximately 100,000 people for the Blue Angels performance. It is expected that nearly all the attendees will drive into the base and park their cars in the grass fields. An average occupancy of 2.3 people per vehicle is assumed based on a study conducted for a similar event in Seabrook, NH. Overall, this special event will result in a loading of 43,480 vehicles along Cedar Point Road at the intersection with Three Notch Road (Maryland Route 235).

Given the large number of transients and the close proximity of the event to the EPZ boundary, those people evacuating in an emergency will be affected by the large vehicle influx from this event as they will use the same exit route (Maryland Route 235). Thus, it is important to consider this special event, even though it takes place outside of the EPZ.

It is assumed that approximately three-quarters of the residents within the EPZ and the shadow area will attend this special event. In order to avoid double counting of the residents, the residents who attend the event are loaded at the base and only the remaining 25% are loaded within the EPZ and shadow area.

A sensitivity study was conducted to determine the effect on the ETE of changing the percentage of EPZ residents and shadow population who attend the air show from 75% to 50%. Since the balance of attendees are transients, the higher number of transient vehicles in the latter case results in an increase in vehicle demand and an increase in ETE. ETE from this sensitivity study are presented in Table I-4 of Appendix I.



Table 3-1. EPZ Permanent Resident Population			
Zone	County	2000 Population	2008 Population
1	Calvert	5,250	6,484
2	Calvert	4,081	5,040
3	Calvert	17,069	21,080
4	Calvert	4,139	5,112
5	Calvert	2,283	2,820
6	St. Mary's	4,246	5,074
7	St. Mary's	7,770	9,284
8	Dorchester	295	311
тот	TAL:	45,133	55,205
	Population G	rowth:	22.3%

Table 3-2. Permanent Resident Population and Evacuating Vehicles by Zone			
Zone	County	2008 Population	2008 Vehicles
1	Calvert	6,484	3,385
2	Calvert	5,040	2,637
3	Calvert	21,080	11,001
4	Calvert	5,112	2,669
5	Calvert	2,820	1,475
6	St. Mary's	5,074	2,648
7	St. Mary's	9,284	4,852
8	Dorchester	311	164
TOTAL:		55,205	28,831

•

- -

-



•	Resident Population			
RingTotalCumulativMilesSubtotalMilesTotal			Cumulative Total	
0-1	0	0-1	0	
1-2	2771	0-2	2771	
2-3	2711	0-3	5482	
3-4	2966	0-4	8448	
4-5	7798	0-5	16246	
5-6	7692	0-6	23938	
6-7	7606	0-7	31544	
7-8	6237	0-8	37781	
8-9	5750	0-9	43531	
9-10	7010	0-10	50541	
10-EPZ	4664	0-EPZ	55205	





KLD Associates, Inc. Rev. 2



KLD Associates, Inc. Rev. 2

Transient Population

Transients are defined as those people who are not permanent residents and who enter the EPZ for a specific purpose (shopping, recreation, business, social). Transients may spend less than one day or stay overnight or longer at rented apartments, camping facilities, hotels and motels.

The recreational areas in the CCNPP EPZ include parks, museums, recreation centers, campgrounds, a sports complex, marinas, and a historical site. Appendix E details the recreational data which were provided by the 2002 ETE Study Report, by county websites and county representatives, by phone calls to the facilities, and by websites for recreational facilities. The peak attendance at the recreational areas is estimated as 10,678 people evacuating in 3,601 vehicles. If site-specific data on the number of visitors per vehicle was not available, it was assumed that each evacuating vehicle holds one family; therefore an average vehicle occupancy of 2.8 (average household size) was used.

To avoid double counting residents, estimates were made of the number of visitors to the recreational facility that live outside the EPZ; only these people are counted as transients. These estimates were provided by some of the facilities; the percentage of transient visitors varied between 15% and 100%. Facilities for which this data was unavailable were assigned a percentage based on their similarity to other facilities.

Hotels and Motels

There are 10 major hotels (50 or more rooms), eight bed and breakfast lodgings and one cabin facility in the EPZ. Appendix E details the hotel data provided by county tourism websites as well as websites for the lodging facilities. At the hotels, motels and bed and breakfasts, we assume two people (1 evacuating vehicle) per room. The peak attendance at the hotels and motels is estimated as 2,534 people evacuating in 1,213 vehicles.

Table 3-3 summarizes the transient population and vehicles within the EPZ. This includes the major recreational areas, lodging facilities, and marinas.

Table 3-3. Summary of Transients by Zone			
Zone	Transients Transient Vehic		
1	978	274	
2	158	55	
3	5,524	1,826	
4	363	138	
5	2	1	
6	819	212	
7	2,634	1,028	
8	200	67	
TOTAL	10,678	3,601	

7

- -



	Ring	Total	Cumulativ
Miles	Subtotal	Miles	Total
0-1	0	0-1	0
1-2	533	0-2	533
2-3	201	0-3	734
3-4	632	0-4	1366
4-5	40	0-5	1406
5-6	105	0-6	1511
6-7	1373	0-7	2884
7-8	5268	0-8	8152
8-9	80	0-9	8232
9-10	365	0-10	8597
10-EPZ	2081	0-EPZ	10678



w

0 0

74

0

 $\sqrt[\circ]{\circ}$

0 / o

0

° S

KLD Associates, Inc. Rev. 2

Е

0 - 3 Miles

Detail

0

0

0 0

0

0

0

0

0

0



KLD Associates, Inc. Rev. 2

Employees

Employees who work within the EPZ fall into two categories:

- Those who live and work in the EPZ
- Those who live outside of the EPZ and commute to jobs within the EPZ.

Those of the first category are already counted as part of the permanent resident population. To avoid double counting, we focus on those commuting employees who will evacuate along with the permanent resident population.

Data for major employers (more than 50 total employees) in the EPZ was provided by the county offices of emergency management, county websites, individual employer websites, and through phone calls to the workplace. The locations of these facilities were mapped using GIS software. The GIS map was overlaid with the evacuation analysis network and employees were loaded onto appropriate links. The map of major employers in the EPZ can be seen in Appendix E.

Journey to Work data provided by the Census indicates that, on average, 25% of the employees in the Calvert County portion of the EPZ and 20% of the employees in the St. Mary's County portion of the EPZ travel to work from outside the EPZ. These percentages were applied to estimate the total number of people commuting into the EPZ to work.

An occupancy of 1.03 persons per employee-vehicle obtained from the telephone survey is used to determine the number of evacuating employee vehicles.

Table 3-4 presents non-EPZ Resident employee and vehicle estimates by zone. Figures 3-6 and 3-7 present these data by sector.

Table 3-4. Summary of Non-EPZ Employees by Zone			
Zone	Total Non-EPZ Employees Employee Vehicles		
1	558	542	
2	No employ	yment	
3	247 240		
4	. 77	75	
5	151	147	
6	56	.54	
7	365	355	
8	No employment		
TOTAL:	1,454	1,413	

. .

ſ



CCNPP Evacuation Time Estimate

- -

KLD Associates, Inc. Rev. 2



Evacuation Time Estimate

Rev. 2

Medical Facilities

There are no hospitals within the Calvert Cliffs EPZ; however, there are nursing homes and senior centers. Data for these facilities was obtained from nursing home websites and from the 2002 ETE Study Report.

Pass-Through Demand

Vehicles will be traveling through the EPZ (external-external trips) at the time of an accident. After the Advisory to Evacuate is announced, these through travelers will also evacuate. These through vehicles are assumed to travel on the major routes through the EPZ (e.g. Maryland Route 2/4 and Maryland Route 235). It is assumed that this traffic will continue to enter the EPZ during the first 90 minutes following the Advisory to Evacuate. We estimate approximately 300 vehicles per lane as the pass through demand; with 8 lanes entering the EPZ, a total of 2,400 vehicles enter the EPZ as external-external trips during this period.

4. ESTIMATION OF HIGHWAY CAPACITY

The ability of the road network to service vehicle demand is a major factor in determining how rapidly an evacuation can be completed. The capacity of a road is defined as the maximum hourly rate at which persons or vehicles can reasonably be expected to traverse a point or uniform section of a lane of roadway during a given time period under prevailing roadway, traffic and control conditions (from the 2000 Highway Capacity Manual).

In discussing capacity, different operating conditions have been assigned alphabetical designations, A through F, to reflect the range of traffic operational characteristics. These designations have been termed "Levels of Service" (LOS). For example, LOS A connotes free-flow and high-speed operating conditions; LOS F represents a forced flow condition. LOS E describes traffic operating at or near capacity.

Because of the effect of weather on the capacity of a roadway, it is necessary to adjust capacity figures to represent the prevailing conditions during inclement weather. Based on limited empirical data, weather conditions such as heavy rain reduce the values of free speed and of highway capacity by approximately 10 percent. Over the last decade new studies have been made on the effects of rain on traffic capacity. These studies indicate a range of effects between 5 and 20 percent depending on wind speed and precipitation rates.

Given the population density within the EPZ and the limited availability of major evacuation routes (only two major thoroughfares - Route 235 and Route 2/4), congestion is expected to occur within the EPZ and especially in/around the Thomas Johnson Bridge. As such, estimates of roadway capacity must be determined with great care. Because of its importance, a brief discussion of the major factors that influence highway capacity is presented in this section.

Capacity Estimations on Approaches to Intersections

At-grade intersections are apt to become the first bottleneck locations under local heavy traffic volume conditions. This characteristic reflects the need to allocate access time to the respective competing traffic streams by exerting some form of control. During evacuation, control at critical intersections will often be provided by traffic control personnel assigned for that purpose, whose directions may supersede traffic control devices. The Traffic Management Plan identifies these locations (called Traffic Control Points, TCP) and the management procedures applied.

The per-lane capacity of an approach to a signalized intersection can be expressed (simplistically) in the following form:

$$Q_{c\,ap,\,m} = \left(\frac{3600}{h_m}\right) \bullet \left[\frac{G-L}{C}\right]_m = \left(\frac{3600}{h_m}\right) \bullet P_m$$

where:

Q _{cap,m}	=	Capacity of a single lane of traffic on an approach, which executes movement, <i>m</i> , upon entering the intersection; vehicles per hour (vph)
h _m	=	Mean queue discharge headway of vehicles on this lane that are
G	=	executing movement, <i>m</i> ; seconds per vehicle The mean duration of GREEN time servicing vehicles that are
L	=	executing movement, <i>m</i> , for each signal cycle; seconds The mean "lost time" for each signal phase servicing movement, <i>m</i> ; seconds
С	=	The duration of each signal cycle; seconds
P _m	=	The proportion of GREEN time allocated for vehicles executing
		movement, m , from this lane. This value is specified as part of the control treatment
m	=	The movement executed by vehicles after they enter the intersection: through, left-turn, right-turn, diagonal.

The turn-movement-specific mean discharge headway h_m , depends in a complex way upon many factors: roadway geometrics, turn percentages, the extent of conflicting traffic streams, the control treatment, and others. A primary factor is the value of "saturation queue discharge headway", $h_{sat'}$ which applies to through vehicles that are not impeded by other conflicting traffic streams. This value, itself, depends upon many factors including motorist behavior. Formally, we can write,

$$h_m = f_m (h_{sat'}, F_1, F_2, ...)$$

where:

h _{sat}	=	Saturation discharge headway for through vehicles; seconds per vehicle
F ₁ , F ₂	=	The various known factors influencing <i>h_m</i>
f _m (·)	- =	Complex function relating h_m to the known (or estimated) values of h_{sat} , F_1 , F_2 ,

The estimation of h_m for specified values of $h_{sat'}$, $F_{1'}$, $F_{2'}$... is undertaken within the PC-DYNEV simulation model and within the TRAD model by a mathematical model¹. The resulting values for h_m always satisfy the condition:

$h_m \ge h_{sat}$

That is, the turn-movement-specific discharge headways are always greater than, or equal

¹ Lieberman, E., "Determining Lateral Deployment of Traffic on an Approach to an Intersection", McShane, W. & Lieberman, E., "Service Rates of Mixed Traffic on the far Left Lane of an Approach". Both papers appear in Transportation Research Record 772, 1980.

to the saturation discharge headway for through vehicles. These headways (or its inverse equivalent, "saturation flow rate"), may be determined by observation or using the procedures of the Highway Capacity Manual.

Capacity Estimation Along Sections of Highway

The capacity of highway <u>sections</u> -- as distinct from approaches to intersections -- is a function of roadway geometrics, traffic composition (e.g. percent heavy trucks and buses in the traffic stream) and, of course, motorist behavior. There is a fundamental relationship which relates service volume (i.e. the number of vehicles serviced within a uniform highway section in a given time period) to traffic density. Figure 4-1 describes this relationship.





Figure 4-1. Fundamental Relationship between Volume and Density

As indicated, there are two flow regimes: (1) Free Flow (left side of curve); and (2) Forced Flow (right side of curve). In the Free Flow regime, the traffic demand is fully serviced; this service volume increases as demand volume and density increase, until the service volume attains its maximum value, which is the capacity of the highway section. As traffic demand and the resulting highway density increase beyond this "critical" value, the rate at which traffic can be serviced (i.e. the service volume) can actually decline below capacity. Therefore, in order to realistically represent traffic performance during congested conditions (i.e. when demand exceeds capacity), it is necessary to estimate the service volume, V_F , under congested conditions.

The value of V_F can be expressed as:

 $V_F = R \times Capacity$

where R = Reduction factor which is less than unity.

Based on empirical data collected on freeways, we have employed a value of R=0.85. It is important to mention that some investigators, on analyzing data collected on freeways, conclude that little reduction in capacity occurs even when traffic is operating at Level of Service, *F*. While there is conflicting evidence on this subject, we adopt a conservative approach and use a value of capacity, V_F , that is applied during LOS F conditions; V_F , is lower than the specified capacity.

The estimated value of capacity is based primarily upon the type of facility and on roadway geometrics. Sections of roadway with adverse geometrics are characterized by lower free-flow speeds and lane capacity.

The procedure used here was to estimate "section" capacity, V_E , based on observations made traveling over each section of the evacuation network, by the posted speed limits and travel behavior of other motorists and by reference to the 2000 Highway Capacity Manual. It was then determined for each highway section, represented as a network link, whether its capacity would be limited by the "section-specific" service volume, V_E , or by the intersection-specific capacity. For each link, the model selects the lower value of capacity.

Application to the Calvert Cliffs Nuclear Power Plant EPZ

As part of the development of the Calvert Cliffs Nuclear Power Plant (CCNPP) EPZ traffic network, an estimate of roadway capacity is required. The source material for the capacity estimates presented herein is contained in:

2000 Highway Capacity Manual (HCM) Transportation Research Board National Research Council Washington, D.C. The highway system in the CCNPP EPZ consists primarily of two categories of roads and, of course, intersections:

- Two-lane roads: Local, State Routes
- Multi-lane Highways (at-grade)

Each of these classifications will be discussed.

Two-Lane Roads

Ref: HCM Chapter 20

Two lane roads comprise the majority of highways within the EPZ. The per-lane capacity of a two-lane highway is estimated at 1700 passenger cars per hour (pc/h). This estimate is essentially independent of the directional distribution of traffic volume except that, for extended distances, the two-way capacity will not exceed 3200 pc/h. The HCM procedures then estimate Level of Service (LOS) and Average Travel Speed. The evacuation simulation model accepts the specified value of capacity as input and computes average speed based on the time-varying demand:capacity relations.

Based on the field survey and on expected traffic operations associated with evacuation scenarios:

- Most sections of two-lane roads within the EPZ are classified as "Class I", with "level terrain"; some are "rolling terrain".
- "Class II" highways are mostly those within city limits.

<u>Multi-Lane Highway</u>

Ref: HCM Chapter 21

Exhibit 21-23 (in the HCM) presents a set of curves that indicates a per-lane capacity of approximately 2100 pc/h, for free-speeds of 55-60 mph. Based on observation, the multi-lane highways outside of urban areas within the EPZ, service traffic with free-speeds in this range. The actual time-varying speeds computed by the simulation model reflect the demand:capacity relationship and the impact of control at intersections.

Intersections

Ref: HCM Chapters 16, 17

Procedures for estimating capacity and LOS for approaches to intersections are presented in Chapters 16 (signalized intersections) and 17 (un-signalized intersections). These are the two longest chapters in the HCM 2000, reflecting the complexity of these procedures. The simulation logic is likewise complex, but different; as stated on page 31-21 of the HCM2000: "Assumptions and complex theories are used in the simulation model to represent the real-world dynamic traffic environment."

CCNPP Evacuation Time Estimate 4-6

KLD Associates, Inc. Rev. 2

5. ESTIMATION OF TRIP GENERATION TIME

Federal Government guidelines (see NUREG 0654, Appendix 4) specify that the planner estimate the distributions of elapsed times associated with mobilization activities undertaken by the public to prepare for the evacuation trip. The elapsed time associated with each activity is represented as a statistical distribution reflecting differences between members of the public. The quantification of these activity-based distributions relies largely on the results of the telephone survey (Appendix F). We define the <u>sum</u> of these distributions of elapsed times as the Trip Generation Time Distribution.

Background

In general, an accident at a nuclear power plant is characterized by the following Emergency Action Classification Levels (see Appendix 1 of NUREG 0654 for details):

- 1. Unusual Event
- 2. Alert
- 3. Site Area Emergency
- 4. General Emergency

At each level, the Federal guidelines specify a set of <u>Actions</u> to be undertaken by the Licensee, and by State and Local offsite authorities. As a <u>Planning Basis</u>, we will adopt a conservative posture, in accord with Federal Regulations, that a rapidly escalating accident will be considered in calculating the Trip Generation Time. We will assume:

- a. The Advisory to Evacuate will be announced coincident with the emergency notification.
- b. Mobilization of the general population will commence up to 10 minutes after the alert notification.
- c. Evacuation Time Estimates (ETEs) are measured relative to the Advisory to Evacuate.
- d. Schools will be evacuated prior to the Advisory to Evacuate; if circumstances permit.

We emphasize that the adoption of this planning basis is <u>not</u> a representation that these events will occur at the Calvert Cliffs Nuclear Power Plant (CCNPP) within the indicated time frame. Rather, these assumptions are necessary in order to:

- Establish a temporal framework for estimating the Trip Generation distribution as recommended in Appendix 4 of NUREG 0654.
- Identify temporal points of reference that uniquely define "Clear Time" and ETE.

It is more likely that a longer time will elapse between the various classes of an emergency at CCNPP and that the Advisory to Evacuate is announced somewhat later than the siren alert.

For example, suppose one hour elapses from the siren alert to the Advisory to Evacuate. In this case, it is reasonable to expect some degree of spontaneous evacuation by the public during this one-hour period, resulting in a lower number of people evacuating within the Emergency Planning Zone (EPZ) when the Advisory to Evacuate is announced. Thus, the time needed to evacuate the EPZ, after the Advisory to Evacuate will be less than the estimates presented in this report, since this study assumes no time lapse between the sirens and the Advisory to Evacuate.

The notification process consists of two events:

- <u>Transmitting</u> information (e.g. using sirens, EAS broadcasts, etc.).
- <u>Receiving</u> and correctly <u>interpreting</u> the information that is transmitted.

The peak permanent resident population within the EPZ approximates 55,000 persons who are deployed over an area of approximately 182 square miles and engaged in a wide variety of activities. It must be anticipated that some time will elapse between the transmission and receipt of the information advising the public of an accident.

The amount of elapsed time will vary from one individual to the next depending where that person is, what that person is doing, and related factors. Furthermore, some persons who will be directly involved with the evacuation process may be outside the EPZ at the time that the emergency is declared. These people may be commuters, shoppers and other travelers who reside within the EPZ and who will return to join the other household members upon receiving notification of an emergency.

As indicated in NUREG 0654, the estimated elapsed times for the receipt of notification can be expressed as a <u>distribution</u> reflecting the different notification times for different people within, and outside, the EPZ. By using time distributions, it is also possible to distinguish between different population groups and different day-of-week and time-of-day scenarios, so that accurate ETEs may be obtained.

For example, people at home or at work within the EPZ will be notified by siren, and/or TV and/or radio. Those EPZ residents who are outside the EPZ will be notified by telephone, radio, TV and word-of-mouth, with potentially longer time lags. Furthermore, the spatial distribution of the EPZ population will differ with time of day – families will be united in the evenings, but dispersed during the day. In this respect, weekends will also differ from weekdays.

Fundamental Considerations

The environment leading up to the time that people begin their evacuation trips consists of a sequence of <u>events</u> and <u>activities</u>. Each event (other than the first) occurs at an instant in time and is the outcome of an activity.

Activities are undertaken over a period of time. Activities may be in "series" (i.e. to undertake an activity implies the completion of all preceding activities) or may be in parallel (two or more activities may take place over the same period of time). Activities conducted in series are functionally <u>dependent</u> on the completion of prior activities; activities conducted in parallel are functionally <u>independent</u> of one-another. The relevant events associated with the public's preparation for evacuation are:

Event Number	Event Description
1	Notification-accident condition
2	Awareness of accident situation
3	Depart place of work or elsewhere, to return home
4	Arrive (or be at) home
5	Begin evacuation trip to leave the area

Associated with each sequence of events are one or more <u>activities</u>, as outlined below:

Event Sequence	Activity	Distribution
1→2	Public receives notification information	1
2 → 3	Prepare to leave work	2
2,3 → 4	Travel home*	3
2,4 → 5	Prepare to leave for evacuation trip	4
	Snow clearance	5

*If already at home, this is a null (no-time-consumed) activity.

These relationships are shown graphically in Figure 5-1.

An employee who lives outside the EPZ will follow sequence (d) of Figure 5-1; a resident of the EPZ who is at work, and will return home before beginning the evacuation trip will

follow sequence (a) of Figure 5-1. Note that event 5, "Leave to evacuate the area," is conditional either on event 2 <u>or</u> on event 4. That is, activity $2 \rightarrow 5$ by a resident at home can be undertaken in parallel with activities $2 \rightarrow 3$, $3 \rightarrow 4$ and $4 \rightarrow 5$ by a commuter returning to that home, as shown in Figure 5-1 (a). Specifically, one adult member of a household can prepare to leave home (i.e. secure the home, pack clothing, etc.), while others are traveling home from work. In this instance, the household members would be able to evacuate sooner than if such trip preparation were deferred until all household members had returned home. For this study, we adopt the conservative posture that all activities will occur in sequence.

It is seen from Figure 5-1, that the Trip Generation time (i.e. the total elapsed time from Event 1 to Event 5) depends on the scenario and will vary from one household to the next. Furthermore, Event 5 depends, in a complicated way, on the time distributions of all activities preceding that event. That is, to estimate the time distribution of Event 5, we must obtain estimates of the time distributions of all preceding events.

Estimated Time Distributions of Activities Preceding Event 5

The time distribution of an event is obtained by "summing" the time distributions of all prior contributing activities. (This "summing" process is quite different than an algebraic sum since we are operating on distributions – not scalar numbers).

Time Distribution No. 1, Notification Process: Activity $1 \rightarrow 2$

It is reasonable to expect that 85 percent of those within the EPZ will be aware of the accident within 30 minutes with the remainder notified within the following 20 minutes. The notification distribution is given below:

Distribution No.	1, Notification	Time: Activit	$y 1 \rightarrow 2$

Elapsed Time (Minutes)	Percent of Population Notified
0	0
5	7
10	13
15	26
20	46
25	65
30	85
35	90
40	95
45	98
50	100



KLD Associates, Inc. Rev. 2

Distribution No. 2, Prepare to Leave Work: Activity $2 \rightarrow 3$

It is reasonable to expect that the vast majority of business enterprises within the EPZ will elect to shut down following notification and most employees would leave work quickly. Commuters, who work outside the EPZ could, in all probability, also leave quickly since facilities outside the EPZ would remain open and other personnel would remain. Personnel or farmers responsible for equipment or livestock would require additional time to secure their facility. The distribution of Activity $2 \rightarrow 3$ reflects data obtained by the telephone survey. This distribution is plotted in Figure 5-2 and listed below.

Elapsed Time (Minutes)	Cumulative Percent Employees Leaving Work	
0	0	
5	36	
10	50	
15	60	
20	69	
25	75	
30	78	
35	82	
40	85	
45	88	
50	90	
55	92	
60	95	
65	95	
70	96	
75	97	
80	97	
85	98	
90	98	
95	99	
100	99	
105	99	
110	99	
115	100	

Distribution No. 3, Travel Home: Activity $3 \rightarrow 4$

- -

These data are provided directly by the telephone survey. This distribution is plotted in Figure 5-2 and listed below.

Elapsed Time (Minutes)	Cumulative Percent Returning Home	
0	0	
5	6	
10	17	
15	32	
· 20	44	
25	51	
30	64	
35	68	
40	72	
45	76	
50	78	
55	80	
60	84	
65	85	
70	87	
75	89	
80	91	
85	93	
90	95	
95	96	
100	97	
105	98	
110	98	
115	99	
120	100	

Distribution No. 4, Prepare to Leave Home: Activity 2, $4 \rightarrow 5$

These data are provided directly by the telephone survey. This distribution is plotted in Figure 5-2 and listed below.

Elapsed Time	Cumulative Pct.	
(iviinutes)	Ready to Evacuate	
0	0	
5	10	
10	19	
15	29	
20	41	
25	54	
30	63	
35	68	
40	72	
45	75	
50	79	
55	83	
60	87	
65	90	
70	91	
75	93	
80	93	
85	93	
90	93	
95	93	
100	94	
105	94	
110	94	
115	95	
120	96	
125	96	
130	97	
135	97	
140	140 98	
145	145 99	
150 100		

CCNPP Evacuation Time Estimate 5-8

Snow Clearance Time Distribution

Inclement weather scenarios involving snowfall must address the time lags associated with snow clearance. It is assumed that snow equipment is mobilized and deployed during the snowfall to maintain passable roads.

Consequently, it is reasonable to assume that the highway system will remain passable – albeit at a lower capacity – under the vast majority of snow conditions. Nevertheless, for the vehicles to gain access to the highway system, it may be necessary for driveways and employee parking lots to be cleared to the extent needed to permit vehicles to gain access to the roadways. These clearance activities take time; this time must be incorporated into the trip generation time distributions. The snow removal mobilization time distribution, recently obtained from the telephone survey results of the Susquehanna Steam Electric Station (SSES) EPZ, was adapted. This distribution is plotted in Figure 5-2 and listed below.

Elapsed Time	Cumulative Pct.	
(windles)	Ready to Evacuate	
0	0.0	
5	13.2	
10	26.4	
15	39.7	
20	50.4	
25	61.1	
30	71.8	
35	74.6	
40	77.5	
45	80.4	
50	83.0	
55	85.7	
60	88.4	
65	89.6	
70	90.8	
75	92.0	
80	92.6	
85	93.2	
90	93.8	
95	94.3	
100	94.8	

Cumulative Pct.	
Ready to Evacuate	
95.3	
96.0	
96.8	
97.6	
97.8	
97.9	
98.1	
98.1	
98.2	
98.3	
98.3	
98.3	
98.3	
98.6	
98.9	
99.1	
99.4	
99.7	
100.0	



Figure 5-2. Evacuation Mobilization Activities

Calculation of Trip Generation Time Distribution

The time distributions for each of the mobilization activities presented herein must be combined to form the appropriate Trip Generation Distributions. We assume that the stated events take place in sequence such that all preceding events must be completed before the current event can occur. For example, if a household awaits the return of a commuter, the work-to-home trip (Activity $3 \rightarrow 4$) must precede Activity $4 \rightarrow 5$.

To calculate the time distribution of an event that is dependent on two sequential activities, it is necessary to "sum" the distributions associated with these prior activities. The distribution summing algorithm is applied repeatedly as shown to form the required distribution. As an outcome of this procedure, new time distributions are formed; we assign "letter" designations to these intermediate distributions to describe the procedure.

Apply "Summing" Algorithm To:	Distribution Obtained	Event Defined
Distributions 1 and 2	Distribution A	Event 3
Distributions A and 3	Distribution B	Event 4
Distributions B and 4	Distribution C	Event 5
Distributions 1 and 4	Distribution D	Event 5
Distributions C and 5	Distribution E	Event 5
Distributions D and 5	Distribution F	Event 5

Distributions A through D are described below:

Distribution	Description
A	Time distribution of commuters departing place of work (Event 3). Also applies to employees who work within the EPZ who live outside, and to Transients within the EPZ.
В	Time distribution of commuters arriving home.
С	Time distribution of residents with commuters leaving home to begin the evacuation trip.
D	Time distribution of residents without commuters returning home to begin the evacuation trip.
E	Time distribution of residents with commuters who return home, leaving home to begin the evacuation trip after snow clearance activities.
F	Time distribution of residents with no commuters who return home, leaving home to begin the evacuation trip after snow clearance activities.

Figure 5-3 presents the combined trip generation distributions designated A, C, D, E and F. These distributions are presented on the same time scale. The PC-DYNEV simulation model is designed to accept varying rates of vehicle trip generation for each origin centroid, expressed in the form of histograms. These histograms, which represent Distributions A, C, D, E and F, properly displaced with respect to one another, are tabulated in Table 5-1 (Distribution B, Arrive Home, omitted for clarity).




	Table 5-1. Trip Generation Time Histograms for the EPZ Population														
-			Percent of To	tal Trips Generate	d Within Indicated	Time Period									
Time Period	Duration (Min)	Residents With Commuters (Distribution C)	Residents Without Commuters (Distribution D)	Employees (Distribution A)	Transients (Distribution A)	Residents With Commuters Snow (Distribution E)	Residents Without Commuters Snow (Distribution F)								
1	15	0	2	6	6	0	0								
2	15	0	14	28	28	0	1								
3	15	2	27	31	31	0	6								
4	15	8	23	16	16	1	15								
5	30	27	23	14	14	11	35								
6	30	26	5	5	5	22	21								
7	30	17	3	0	0	22	9								
8	30	10	3	0	0	18	6								
9	60	10	0	0	0	18	7								
10	60	0	0	0	0	8	0								
11	900	0	0	0	0	0	0								

KLD Associates, Inc. Rev. 2

6. DEMAND ESTIMATION FOR EVACUATION SCENARIOS

An evacuation "case" defines a combination of Evacuation Region and Evacuation Scenario. The definitions of "Region" and "Scenario" are as follows:

- Region A grouping of contiguous evacuation Zones, that forms either a "keyhole" sector-based area, or a circular area within the EPZ, that must be evacuated in response to a radiological emergency.
- Scenario A combination of circumstances, including time of day, day of week, season, and weather conditions. Scenarios define the number of people in each of the affected population groups and their respective mobilization time distributions.

A total of 14 Regions were defined which encompass all the groupings of Zones considered. These Regions are defined in Table 6-1. The zone configurations are identified in Figure 6-1. Each keyhole sector-based area consists of a circular area centered at the Calvert Cliffs Nuclear Power Plant (CCNPP), and three adjoining sectors, each with a central angle of 22.5 degrees. These sectors extend to a distance of 5 miles from CCNPP (Regions R4 and R5), or to the EPZ boundary (Regions R06 to R14). The azimuth of the center sector defines the orientation of these Regions.

A total of 14 Scenarios were evaluated for all Regions. Thus, there are a total of 14x14=196 evacuation cases. Table 6-2 is a description of all Scenarios.

Each combination of Region and Scenario implies a specific population to be evacuated. Table 6-3 presents the percentage of each population group assumed to evacuate for each Scenario. Table 6-4 presents the vehicle counts for each Scenario.

As discussed in Section 3, the construction scenario (Scenario 11) uses resident and shadow population numbers that are projected to 2013. Table 6-4 shows that the total number of permanent residents vehicles in 2013 is 30,959 (20,040 + 10,919); Table 6-5 lists the break-down by Zone.

	Table 6-1. Description of Ex	/acua	tion F	Regio	ns				
Pogion	Description				ZO	NE			
Region	Description	1	2	3	4	5	6	7	8
R01	2-Mile Ring	X							
R02	5-Mile Ring	X	X	Χ					
R03	Full EPZ	X	X	Х	X	X	X	Х	X
	Evacuate 2-Mile Ring and	5 Miles	s Dov	vnwir	nd				
Region	Wind Direction Towards:				ZO	NE			
		1	2	3	4	5	6	7	8
	N, NNE, NE, ENE, E			S	ee Re	gion	1		-
R04	ESE, SE, SSE, S	X		X					
	SSW, SW, WSW			S	ee Re	egion	2		
R05	W, WNW, NW, NNW	X	X						
	Evacuate 5-Mile Ring and Down	wind	to EP	Z Bo	unda	ry			
Region	Wind Direction Towards:				ZO	NE			
		1	2	3	4	5	6	7	8
	NNE		· ·	S	ee Re	egion	2		r
R06	NE, ENE, E, ESE, SE	X	X	X					X
R07	SSE, S	X	X	X				X	
R08	SSW, SW	X	Х	X			X	X	
R09	WSW	X	X	X	X		X	X	
R10	W	X	X	X	X		X		
R11	WNW	X	X	Χ	X	X	X		
R12	NW, NNW	X	X	X	X	X			
R13	N	X	X	X		X			
R14	*	X			1				X

*This Region was added at Constellation Energy's request. It is an evacuation of the 2-Mile Ring and downwind (Towards Dorchester County) to the EPZ Boundary.



	Tab	le 6-2 Evacuatio	on Scenario Del	finitions	
Scenarios	Season	Day of Week	Time of Day	Weather	Special
1	Summer	Midweek	Midday	Good	None
2	Summer	Midweek	Midday	Rain	None
3	Summer	Weekend	Midday	Good	None
4	Summer	Weekend	Midday	Rain	None
5	Summer	Midweek, Weekend	Evening	Good	None
6	Winter	Midweek	Midday	Good	None
7	Winter	Midweek	Midday	Rain	None
8	Winter	Weekend	Midday	Good	None
9	Winter	Weekend	Midday	Rain	None
10	Winter	Midweek, Weekend	Evening	Good	None
11	Summer	Midweek	Midday	Good	New Plant Construction
12	Summer	Weekend	Midday	Good	Air Show at the Naval Base
13	Winter	Midweek	Midday	Snow	None
14	Winter	Weekend	Midday	Snow	None

Note: Schools are assumed to be in session for the Winter season (midweek, midday).

. .

Scenarios	Residents With Commuters in Household 65% 65%	Residents With No Commuters in Household 35%	Employees	Transients	Shadow	Special	School	Trancit	External			
1 2 3	65% 65%	35%				Special School Events Buses		Buses	Through Traffic			
2	65% 6%		96%	50%	31%	0%	10%	100%	100%			
2	6%	35%	96%	50%	31%	0%	10%	100%	100%			
J	070	94%	47%	100%	31%	0%	0%	100%	100%			
4	6%	94%	47%	100%	31%	0%	0%	100%	100%			
5	6%	94%	10%	25%	30%	0%	0%	100%	60%			
6	65%	35%	100%	25%	31%	0%	100%	100%	100%			
7	65%	35%	100%	25%	31%	0%	100%	100%	100%			
8	6%	94%	47%	40%	31%	0%	0%	100%	100%			
9	6%	94%	47%	40%	31%	0%	0%	100%	100%			
10	6%	94%	10%	15%	30%	0%	0%	100%	60%			
11	65%	35%	96%	50%	31%	100%	10%	100%	100%			
12	6%	94%	47%	100%	31%	100%	0%	100%	100%			
13	65%	35%	100%	25%	31%	0%	100%	100%	100%			
14	6%	94%	47%	40%	31%	0%	0%	100%	100%			
esident House mployees	holds With No C	CommutersFr ev Commuters Ho co El	vacuation trip. Duseholds of E Dummuters prior to 22 employees w	PZ residents of beginning the ho live outside	who do not evacuation to of the EPZ.	have comm rip.	nuters or v	will not awa	ait the return			
ransients												
kternal Throug	ernal Through Traffic											

Evacuation Time Estimate

.

			Table	6-4. Vehicl	le Estimat	es by Sc	enario			
Scenarios	Residents with Commuters	Residents without Commuters	Employees	Transients	Shadow	Special Events	School Buses	Transit Buses	External Traffic	Total Scenario Vehicles
1	18,665	10,166	1,356	1,801	9,898	-	30	66	2,400	44,382
2	18,665	10,166	1,356	1,801	9,898	-	30	66	2,400	44,382
3	1,867	26,965	664	3,601	9,671	-	-	66	2,400	45,234
4	1,867	26,965	664	3,601	9,671	-	-	66	2,400	45,234
5	1,867	26,965	141	900	9,500	-	-	66	1,440	40,879
6	18,665	10,166	1,413	900	9,917	-	294	66	2,400	43,821
7	18,665	10,166	1,413	900	9,917	-	[·] 294	66	2,400	43,821
8	1,867	26,965	664	1,440	9,671	-	-	66	2,400	43,073
9	1,867	26,965	664	1,440	9,671	-	-	66	2,400	43,073
10	1,867	26,965	141	540	9,500	-	-	66	1,440	40,519
11 [†]	20,040	10,919	1,356	1,801	10,849	2,821	30	66	2,400	50,282
12 [*]	473	6,775	664	3,601	2,595	43,480	-	66	2,400	60,054
13	18,665	10,166	1,413	900	9,917	-	294	66	2,400	43,821
14	1,867	26,965	664	1,440	9,671	-	-	66	2,400	43,073

[†]Permanent Resident population and Shadow population have been extrapolated to the Year 2013, which is when construction workforce will be at its peak.

*Based on an assumption that 75% of the population within the EPZ and Shadow will be attending the Air Show, the loading of the residents within the EPZ and in the shadow area have been adjusted appropriately.

Populations for all Scenarios except Scenario 11 are projected to the year 2008.

Zone	2008 Population	2013 Population	2013 Vehicles
1	6,484	6,856	3,585
2	5,040	5,329	2,797
3	21,080	22,288	11,644
4	5,112	5,405	2,829
5	2,820	2,982	1,564
6	5,074	5,645	2,952
7	9,284	10,329	5,412
8	311	329	176
TOTAL:	55,205	59,162	30,959

7. GENERAL POPULATION EVACUATION TIME ESTIMATES (ETE)

This section presents the current results of the computer analyses using the IDYNEV System described in Appendices B, C and D. These results cover 14 regions within the CCNPP EPZ and the 14 Evacuation Scenarios discussed in Section 6.

The ETE for all Evacuation Cases are presented in Tables 7-1A through 7-1D. These tables present the estimated times to clear the indicated population percentages from the Evacuation Regions for all Evacuation Scenarios. The tabulated values of ETE are obtained from the PC-DYNEV simulation model outputs of vehicles exiting the specified evacuation areas. These data are generated at 10-minute intervals, then interpolated to the nearest 5 minutes.

NRC guidance suggests routing traffic during evacuation away from CCNPP and out of the EPZ to the extent practicable. Zone 3, which is the most populous of all zones within the EPZ is south of CCNPP and has only 1 evacuation route – Maryland Route 2/4. If all the traffic from this Zone were routed away from the plant in the southbound direction, they would have to use the Thomas Johnson Bridge (1-lane in either direction), which presents a significant traffic bottleneck. A sensitivity study was conducted to measure the effect of routing evacuees from Zone 3 northbound on Route 2/4. Balancing the vehicle demand from Zone 3 in the northbound and southbound directions on Route 2/4 results in a significant decrease in ETE (3 hours and 50 minutes less) than routing only southbound (See Appendix I). Although this routing moves some of the evacuees closer to CCNPP, the ETE is significantly reduced, minimizing the risk of exposure. All the results presented in this section and in Appendix J are based on routing evacuating traffic from Zone 3 northbound and southbound on Route 2/4.

7.1 Voluntary Evacuation and Shadow Evacuation

We define "voluntary evacuees" as people who are within the EPZ in Zones located outside the Evacuation Region, for which an Advisory to Evacuate *has not* been issued, yet who nevertheless elect to evacuate. We define "shadow evacuation" as the movement of people from areas *outside* the EPZ for whom no protective action recommendation has been issued. Both voluntary and shadow evacuation are assumed to take place over the same time frame as the evacuation from within the impacted Evacuation Region.

The ETE for the CCNPP addresses the issue of voluntary evacuees as discussed in Section 2.2 and displayed in Figure 7-1 (same as Figure 2-1). Figure 7-2 presents the area identified as the Shadow Evacuation Region. This region extends radially from the boundary of the EPZ to a distance of 15 miles from CCNPP.

Traffic generated within this Shadow Evacuation Region, traveling away from the CCNPP location, has the potential for impeding evacuating vehicles from within the Evacuation Region. We assume that the traffic volumes emitted within the Shadow

Evacuation Region correspond to 30 percent of the residents there plus a proportionate number of employees in that region. All ETE calculations include this shadow traffic movement.

7.2 Patterns of Traffic Congestion During Evacuation

Figures 7-3 through 7-6 illustrate the patterns of traffic congestion that arise for the case when the entire EPZ (Region R03) is advised to evacuate during the summer, midweek, midday period under good weather conditions (Scenario 1).

Traffic congestion, as the term is used here, is defined as Level of Service (LOS) F. LOS F is defined as follows (2000 HCM):

Level of Service F is used to define forced or breakdown flow. This condition exists wherever the amount of traffic approaching a point exceeds the amount that can traverse the point. Queues form behind such locations. Operations within the queue are characterized by stop-and-go waves, and they are extremely unstable. Vehicles may progress at reasonable speeds for several hundred feet or more, then be required to stop in a cyclic fashion. Level of Service F is used to describe the operating conditions within the queue, as well as the point of the breakdown. It should be noted, however, that in many cases operating conditions of vehicles or pedestrians discharged from the queue may be quite good. Nevertheless, it is the point at which arrival flow exceeds discharge flow, which causes the queue to form, and Level of Service F is an appropriate designation for such points.

This definition is general and conceptual in nature, and applies primarily to uninterrupted flow. Levels of Service for interrupted flow facilities vary widely in terms of both the user's perception of service quality and the operational variables used to describe them.

All highway "links" which experience LOS F at the indicated times are delineated in these Figures by a red line; all others are lightly indicated. Congestion develops in areas with concentrations of population and at traffic bottlenecks. Congestion develops at one and a half hours after the Advisory to Evacuate (ATE) along southbound Route 2/4 (south of CCNPP), especially around Rousby Hall Rd (State Route 760) and the Thomas Johnson Bridge. Additionally, sections of Route 2/4 around Broomes Island Road (Route 264) and Prince Frederick are congested (Figure 7-3).

Key links are labeled on Figures 7-3 to 7-6 and the average delay in minutes per vehicle is presented in a table on page 7-4.

Figure 7-4 presents the congestion pattern 3 and a half hours after the ATE. Congestion persists in the aforementioned areas within the EPZ and along Point Lookout Road (Route 5) in the shadow area. By four and three quarter hours (Figure 7-5), congestion is beginning to dissipate and only persists along Rousby Hall Rd (Route 760), the Southern/Lusby Connector, Broomes Island Road (Route 264), and Route 2/4, north of Prince Frederick. After five hours and forty minutes (Figure 7-6), congestion only remains around the Thomas Johnson Bridge. The absence of congestion on network links (white colored links) implies that traffic demand there has decreased below the roadway capacity for a period of time sufficient to dissipate any traffic queues. It does not necessarily imply that traffic has completely cleared from these roadway sections.

			Average Delay for Selected Roadways in the CC	NPP EPZ							
Congestion	Li	nk	Description	Average Delay (min/veh) at Indicated Tim (hour:min) after Advisory to Evacuate							
Point Number ¹	From Node	To Node	Description	1:30	3:00	4:30	5:30				
1	142	22	MD 264 Broomes Island Road Northbound	8.5	8.6	8.4	0.0				
2	21	22	MD 2/4 Northbound in Port Republic	2.9	2.9	2.4	0.0				
3	184	176	MD 760 Rousby Hall Road Westbound	9.2	9.0	0.0	3.1				
4	12	13	TJ Bridge Southbound	3.2	3.6	3.3	3.3				
5	293	66	MD 471 St. Andrews Church Road Southbound	0.0	0.0	0.0	0.0				
6	74	328	MD 247 Loveville Road Southbound	0.0	0.0	0.0	0.0				
7	45	16	MD 235 Three Notch Road Northbound in California	9.6	9.6	9.6	0.0				
8	24	26	MD 2/4 Northbound in Prince Frederick	0.0	1.1	0.2	0.0				

7.3 Evacuation Rates

Evacuation is a continuous process, as implied by Figures 7-3 through 7-6. Another format for displaying the dynamics of evacuation is depicted in Figure 7-7. This plot indicates the rate at which traffic flows out of the indicated areas for the case of an evacuation of the entire EPZ (Region R03) under the indicated conditions. Appendix J presents these plots for all Evacuation Scenarios for Region R03.

As indicated in Figure 7-7, there is typically a long "tail" to these distributions. Vehicles evacuate an area slowly at the beginning, as people respond to the Advisory to Evacuate at different rates. Then traffic demand builds rapidly (slopes of curves increase). When the system becomes congested, traffic exits the EPZ at rates somewhat below capacity until some evacuation routes have cleared. As more routes clear, the aggregate rate of egress slows since many vehicles have already left the EPZ. Towards the end of the process, relatively few evacuation routes service the remaining demand. It is reasonable to expect that some evacuees may delay or lengthen their mobilization activities and evacuate at a later time as a result; these ETE estimates do not (and should not) be distorted to account for these relatively few stragglers.

This decline in aggregate flow rate, towards the end of the process, is characterized by these curves flattening and gradually becoming horizontal. Ideally, it would be desirable to fully saturate all evacuation routes equally so that all will service traffic near capacity levels and all will clear at the same time. For this ideal situation, all curves would retain the same slope until the end -- thus minimizing evacuation time. In the real world, this ideal is generally unattainable reflecting the variation in population density and in highway capacity over the EPZ.

7.4 Guidance on Using ETE Tables

Tables 7-1A through 7-1D present the ETE values for all 14 Evacuation Regions and all 14 Evacuation Scenarios. They are organized as follows:

Table	Contents
7-1A	ETE represents the elapsed time required for 50 percent of the population within a Region, to evacuate from that Region.
7-1B	ETE represents the elapsed time required for 90 percent of the population within a Region, to evacuate from that Region.
7-1C	ETE represents the elapsed time required for 95 percent of the population within a Region, to evacuate from that Region.
7-1D	ETE represents the elapsed time required for 100 percent of the population within a Region, to evacuate from that Region.

The user first determines the percentile of population for which the ETE is sought. The applicable value of ETE within the chosen Table may then be identified using the following procedure:

1. Identify the applicable **Scenario**:

- The Season
 - Summer (schools not in session)
 - Winter (also Autumn and Spring)
- The Day of Week
 - Midweek (work-day)
 - Weekend, Holiday
- The Time of Day
 - Midday (work and commuting hours)
 - Evening
- Weather Condition
 - Good Weather
 - Rain
 - Snow
- Special Event
 - New Plant Construction
 - Air show at Naval Air Base

While these Scenarios are designed, in aggregate, to represent conditions throughout the year, some further clarification is warranted:

The conditions of summer evenings and rain are not explicitly identified in

Tables 7-1A through 7-1D. For these conditions, Scenario 4 provides a conservative estimate of ETE.

- Likewise, the conditions of winter evenings and rain are not explicitly identified in Tables 7-1A through 7-1D. For these conditions, Scenario 9 provides a conservative estimate of ETE.
- The seasons are defined as follows:
 - Summer implies that public schools are *not* in session.
 - Winter, Spring and Autumn imply that public schools *are* in session.
- Time of Day: Midday implies the time over which most commuters are at work.
- 2. With the Scenario (and column in the Table) identified, now identify the **Evacuation Region**:
 - Determine the projected azimuth direction of the plume (coincident with the wind direction). This direction is expressed in terms of compass orientation: *towards* N, NNE, NE ...
 - Determine the distance that the Evacuation Region will extend from the CCNPP. The applicable distances and their associated candidate Regions are given below:
 - 2 Miles (Region R01)
 - 5 Miles (Regions R02, R04 and R05)
 - to EPZ Boundary (Regions R03 and R06 through R14)
 - Enter Table 7-2 and identify the applicable group of candidate Regions based on the wind direction and on the distance that the selected Region extends from the CCNPP. Select the Evacuation Region identifier in that row from the first column of the Table.
- 3. Determine the **ETE for the Scenario** identified in Step 1 and the Region identified in Step 2, as follows:
 - The columns of Table 7-1 are labeled with the Scenario numbers. Identify the proper column in the selected Table using the Scenario number determined in Step 1.
 - Identify the row in this table that provides ETE values for the Region identified in Step 2.
 - The unique data cell defined by the column and row so determined contains the desired value of ETE expressed in Hours: Minutes.

Example

It is desired to identify the ETE for the following conditions:

- Sunday, August 10th at 4:00 AM.
- It is raining.
- Wind direction is *towards* the northeast (NE).
- Wind speed is such that the distance to be evacuated is judged to be 10 miles (to EPZ boundary).
- The desired ETE is that value needed to evacuate 95 percent of the

population from within the impacted Region.

Table 7-1C is applicable because the 95th-percentile population is desired. Proceed as follows:

- 1. Identify the Scenario parameters as: *Season*: summer; *Day of Week*: weekend; *Time of Day*: evening (non-work hours); and *Weather*. Rain. Entering Table 7-1C, it is seen that there is no match for these descriptors. However, based on the discussions above (Section 7.4, item 1), Scenario 4 provides guidance as an upper bound on ETE.
- 2. Enter Table 7-2 and locate the group entitled "Evacuate 5-Mile Ring and Downwind to EPZ Boundary". Under "Wind Direction Towards:", identify the NE (northeast) azimuth and read REGION R06 in the first column of that row.
- 3. Enter Table 7-1C to locate the data cell containing the value of ETE for Scenario 4 and Region R06. This data cell is in column (4) and in the row for Region R06; it contains the ETE value of **5:45**.

			Та	ble 7-1	A. Tim	ne To Cle	ar The	Indica	ted Are	a of 50) Percen	t of the Aff	ected Popu	lation		
· · .	Season	Sum	mer	Sumr	ner	Summer	Wint	er .	Wint	er	Winter	Summer	Summer	Winter	Winter	Season
Da	y of Week	Midv	veek	Week	end	All	Midw	eek	Week	end	Ali	Midweek	Weekend	Midweek	Weekend	Day of Week
S	icenario:	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	Scenario
Ti	me of Day	Mid	day	Midd	lay	Evening	Midd	ay 📩	Midd	ay	Evening	Midday	Midday	Midday	Midday	Time of Day
Zone	Region Wind Direction	Good Weather	Rain	Good Weather	Rain	Good Weather	Good Weather	Rain	Good Weather	Rain	Good Weather	New Plant Construction	Air Show at Base	Snow	Snow	Region Wind Direction Towards
	Towards	L		-			Enti	re 2-Mile	Region, 5-M	Aile Regio	on, and EPZ			· · · · ·		
1	R01 2-mile ring	1:30	1:35	1:25	1:30	1:20	1:30	1:30	1:20	1:30	1:20	1:50	1:00	1:55	1:50	R01 2-mile ring
1,2,3	R02 5-mile ring	2:30	2:45	2:30	2:45	2:15	2:30	2:45	2:25	2:35	2:15	2:50	1:20	3:15	3:10	R02 5-mile ring
1,2,3,4,5, 6,7,8	R03 Entire EPZ	2:20	2:30	2:15	2:30	2:10	2:20	2:30	2:10	2:20	2:05	2:35	4:20	3:00	2:50	R03 Entire EPZ
							2	2-Mile Ri	ng and Dow	nwind to	5 Miles					
1	N, NNE, NE, ENE, E						Re	fer to Re	gion 1							N, NNE, NE, ENE, E
1,3	R04 ESE, SE, SSE, S	2:20	2:30	2:20	2:35	2:05	2:15	2:30	2:15	2:25	2:05	2:40	1:25	3:00	2:55	R04 ESE, SE, SSE, S
1,2,3	SSW, SW, WSW			•	•		Re	fer to Re	gion 2							ssw, sw, wsw
1,2	R05 W, WNW, NW, NNW	1:45	1:55	1:45	1:55	1:40	1:45	1:55	1:40	1:50	1:40	2:10	1:00	2:20	2:15	R05 W, WNW, NW, NNW
							5-Mi	le Ring a	Ind Downwi	nd to EP	Z Boundary					
1,2,3	· NNE						Re	fer to Re	gion 2							NNE
1,2,3,8	R06 NE, ENE, E, ESE, SE	2:30	2:45	2:30	2:45	2:15	2:30	2:45	2:20	2:35	2:15	2:50	1:20	3:15	3:10	R06 NE, ENE, E, ESE, SE
1,2,3,7	R07 SSE, S	2:25	2:35	2:20	2:35	2:10	2:20	2:30	2:15	2:25	2:10	2:40	4:35	3:00	2:55	R07 SSE, S
1,2,3,6,7	R08 SSW, SW	2:20	2:30	2:15	2:25	2:05	2:20	2:25	2:10	2:20	2:05	2:35	4:35	2:55	2:50	R08 SSW, SW
1,2,3,4,6, 7	R09 WSW	2:20	2:30	2:20	2:30	2:10	2:20	2:30	2:10	2:20	2:10	2:35	4:25	3:00	2:50	R09 WSW
1,2,3,4,6	R10 W	2:20	2:30	2:15	2:30	2:05	2:20	2:30	2:10	2:20	2:05	2:35	4:05	3:00	2:50	R10 W
1,2,3,4,5, 6	R11 WNW	2:20	2:30	2:15	2:30	2:05	2:20	2:30	2:10	2:25	2:05	2:35	4:00	3:00	2:50	R11 WNW
1,2,3,4,5	R12 NW, NNW	2:30	2:45	2:25	2:45	2:15	2:30	2:45	2:20	2:40	2:15	2:50	1:25	3:20	3:10	R12 NW, NNW
1,2,3,5	R13 N	2:30	2:45	2:30	2:45	2:15	2:30	2:45	2:25	2:35	2:15	2:50	1:30	3:15	3:10	R13 N
1,8	R14	1:30	1:35	1:25	1:30	1:20	1:30	1:35	1:20	1:30	1:20	1:50	1:00	1:55	1:50	R14

2

		<u> </u>	Та	ble 7-11	3. Tim	e To Cle	ar The I	ndica	ted Area	a of 90) Percen	t of the Aff	ected Popu	lation		
	Season	Sum	mer	Sumr	ner	Summer	Wint	er	Wint	er	Winter	Summer	Summer	Winter	Winter	Season
Day	y of Week	Midv	veek	Week	end	AÏ	Midwo	eek	Week	end	. All	Midweek	Weekend	Midweek	Weekend	Day of Week
S	cenario:	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	Scenario
Tin	ne of Day	Mid	day	Midd	lay	Evening	Midd	ay	Midd	ay	Evening	Midday	Midday	Midday	Midday	Time of Day
Zone	Region Wind Direction	Good Weather	Rain	Good Weather	Rain	Good Weather	Good Weather	Rain	Good Weather	Rain	Good Weather	New Plant Construction	Air Show at Base	Snow	Snow	Region Wind Direction
							Entir	e 2-Mile	Region, 5-N	lile Regio	on, and EPZ					
1	R01 2-mile ring	2:45	2:50	2:30	2:45	2:25	2:50	2:50	2:25	2:40	2:25	3:25	1:50	3:40	3:20	R01 2-mile ring
1,2,3	R02 5-mile ring	4:20	4:50	4:30	5:10	3:55	4:15	4:45	4:10	4:40	3:55	5:00	4:55	5:30	5:25	R02 5-mile ring
1,2,3,4,5, 6,7,8	R03 Entire EPZ	4:30	5:00	4:35	5:05	4:10	4:30	4:50	4:20	4:45	4:05	5:10	9:55	5:40	5:35	R03 Entire EPZ
							2	-Mile Rir	ig and Dow	nwind to	5 Miles					
1	N, NNE, NE, ENE, E						Re	fer to Re	gion 1							N, NNE, NE, ENE, E
1,3	R04 ESE, SE, SSE, S	4:25	4:55	4:40	5:15	4:00	4:15	4:50	4:15	4:45	3:50	4:40	4:55	5:35	5:35	R04 ESE, SE, SSE, S
1,2,3	SSW, SW, WSW						Re	fer to Re	gion 2							ssw, sw, wsw
1,2	R05 W, WNW, NW, NNW	3:05	3:25	3:05	3:20	2:50	3:05	3:25	3:00	3:15	2:50	4:00	1:50	4:05	4:00	R05 W, WNW, NW, NNW
							5-Mil	e Ring a	nd Downwi	nd to EP2	Z Boundary					
1,2,3	NNE						Re	fer to Re	gion 2	-				·		NNE
1,2,3,8	R06 NE, ENE, E, ESE, SE	4:20	4:45	4:30	5:05	3:55	4:15	4:40	4:10	4:40	3:55	5:00	4:55	5:30	5:25	R06 NE, ENE, E, ESE, SE
1,2,3,7	R07 SSE, S	4:25	4:55	4:35	5:10	4:00	4:20	4:45	4:15	4:45	4:00	5:00	9:50	5:35	5:30	R07 SSE, S
1,2,3,6,7	R08 SSW, SW	4:25	4:55	4:35	5:10	4:00	4:20	4:40	4:10	4:40	3:55	5:00	9:55	5:30	5:30	R08 SSW, SW
1,2,3,4,6, 7	R09 WSW	4:30	5:00	4:35	5:05	4:10	4:30	4:50	4:20	4:45	4:05	5:10	9:55	5:40	5:35	R09 WSW
1,2,3,4,6	R10 W	4:30	4:55	4:35	5:10	4:10	4:25	4:55	4:20	4:45	4:05	5:05	9:40	5:40	5:35	R10 W
1,2,3,4,5, 6	R11 WNW	4:30	4:55	4:35	5:10	4:10	4:30	4:55	4:20	4:45	4:05	5:10	9:40	5:40	5:35	R11 WNW
1,2,3,4,5	R12 NW, NNW	4:30	4:55	4:35	5:05	4:10	4:30	4:55	4:20	4:45	4:05	5:15	4:40	5:45	5:35	R12 NW, NNW
1,2,3,5	R13 N	4:25	4:55	4:35	5:15	4:05	4:25	4:50	4:15	4:45	4:00	5:05	5:05	5:40	5:30	R13 N
1,8	R14	2:45	2:50	2:35	2:50	2:25	2:50	2:50	2:30	2:50	2:25	3:30	1:50	3:40	3:20	R14
4		1		1												

3

L.

2

Image: bar			-	Ta	ble 7-10	C. Tim	e To Cle	ar The I	ndica	ted Area	a of 95	Percent	t of the Affe	ected Popul	lation			
NetworkNetworkNetworkAllMideryVerbandAllMideryNetworkNetwor		Season	Sum	mer	Sumr	ner	Summer	Wint	er	Wint	er	Winter	Summer	Summer	Winter	Winter	Season	
	Da	y of Week	Midv	veek	Week	end	Ali	Midwa	eek	Week	end	AII	Midweek	Weekend	Midweek	Weekend	Day of Week	
<table-container>Varburnet<td>s</td><td>cenario:</td><td>(1)</td><td>(2)</td><td>(3)</td><td>(4)</td><td>(5)</td><td>(6)</td><td>(7)</td><td>(8)</td><td>(9)</td><td>(10)</td><td>(11)</td><td>(12)</td><td>(13)</td><td>(14)</td><td>Scenario</td></table-container>	s	cenario:	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	Scenario	
Image Reside Reside </td <td>Ti</td> <td>me of Day</td> <td>Mid</td> <td>day</td> <td>Midd</td> <td>lay</td> <td>Evening</td> <td>Midd</td> <td>ay</td> <td>Midd</td> <td>ay</td> <td>Evening</td> <td>Midday</td> <td>Midday</td> <td>Midday</td> <td>Midday</td> <td>Time of Day</td>	Ti	me of Day	Mid	day	Midd	lay	Evening	Midd	ay	Midd	ay	Evening	Midday	Midday	Midday	Midday	Time of Day	
IDENTIFY CALL VERTIFY CALL <th colspa<="" td=""><td>Zone</td><td>Region Wind Direction Towards</td><td>Good Weather</td><td>Rain</td><td>Good Weather</td><td>Rain</td><td>Good Weather</td><td>Good Weather</td><td>Rain</td><td>Good Weather</td><td>Rain</td><td>Good Weather</td><td>New Plant Construction</td><td>Air Show at Base</td><td>Snow</td><td>Snow</td><td>Region Wind Direction</td></th>	<td>Zone</td> <td>Region Wind Direction Towards</td> <td>Good Weather</td> <td>Rain</td> <td>Good Weather</td> <td>Rain</td> <td>Good Weather</td> <td>Good Weather</td> <td>Rain</td> <td>Good Weather</td> <td>Rain</td> <td>Good Weather</td> <td>New Plant Construction</td> <td>Air Show at Base</td> <td>Snow</td> <td>Snow</td> <td>Region Wind Direction</td>	Zone	Region Wind Direction Towards	Good Weather	Rain	Good Weather	Rain	Good Weather	Good Weather	Rain	Good Weather	Rain	Good Weather	New Plant Construction	Air Show at Base	Snow	Snow	Region Wind Direction
1 100 2mile ring 3:10 3:15 2:46 3:10 3:15 2:46 3:50 2:05 4:05 3:40 2mile ring 2mile ring 1.2.3 BR2 Smile ring 4:46 5:20 5:05 5:45 4:20 4:40 5:15 4:15 5:15 5:45 6:30 6:00 6:00 R02 Renting R32 Renting R32 6.7.3 Envine Eng2 4:85 5:10 5:15 4:45 5:15 4:20 6:35 10:35 6:10 6:10 6:10 R03 Renting R32 6.7.3 Envine Eng2 4:85 5:10 5:4 4:30 5:15 4:45 5:15 4:20 6:35 10:35 6:10 6:10 R03 Renting R33 1 N.NINE, NE, E Extender to Ragin Extender to Ragin Extender to R34 5:10 4:20 5:05 5:40 6:05 Extender to R34 1,3 Extender Sextender Extender to Ragin Extender to Ragin Sixtender to R34 Sixtender to R34 Sixtender to R34 Sixtender to R34								Entir	e 2-Mile	Region, 5-M	ile Regio	n, and EPZ						
1.2. 9.007 6,7.8 6.46 5.20 5.45 5.45 5.45 6.00 6.00 R02 6,7.8 R03 6,7.8 1.2.3.6 6,7.8 6,30 5.30 5.45 5.30 5.45 5.45 5.45 5.45 6.00 6.00 R03 6,7.8 1.3. 6,7.8 5.30 5.10 5.45 5.45 5.45 6.10 6.10 6.00 R03 6,7.8 1.3 E56, 5.55 5.52 5.50 5.50 5.51 5.45 5.45 5.40 5.61 5.45 5.60 <	1	R01 2-mile ring	3:10	3:15	2:45	3:00	2:45	3:10	3:15	2:45	2:55	2:45	3:50	2:05	4:05	3:40	R01 2-mile ring	
12.3.4.5 ER03 e.1.5 5.30	1,2,3	R02 5-mile ring	4:45	5:20	5:05	5:45	4:20	4:40	5:15	4:40	5:10	4:15	5:15	5:45	6:00	6:00	R02 5-mile ring	
1 N.N.E. NE. N. N.N.E. NE. S. N.N.E. N. N.E. E. S. N.N.K. N.K. E. S. N.N.K. N.K. E. S. N.N.K. N.K. E. S. N.N.K. N.K. N.E. E. S. N.N.K. N.K. N.E. E. S. N.N.K. N.K. N.E. E. S. N.N.K. N.K. N.K. N.K. N.K. N.K. N.K.	1,2,3,4,5, 6,7,8	R03 Entire EPZ	4:55	5:30	5:10	5:45	4:30	4:50	5:15	4:45	5:15	4:25	5:35	10:35	6:10	6:10	R03 Entire EPZ	
1 N, NNE, NE, ENE, E S. S. S. S. S. S. S. S. S. N, NNE, NE, ENE, E S.								2	-Mile Rin	g and Dowr	wind to	5 Miles						
1.3 ESE, SS, SS, S, SS, S, SS, S, SS, S, SS, S	1	N, NNE, NE, ENE, E						Re	fer to Re	gion 1							N, NNE, NE, ENE, E	
1.2.3 SSW, SW, WSW V	1,3	R04 ESE, SE, SSE, S	4:50	5:25	5:10	5:45	4:25	4:45	5:15	4:45	5:15	4:20	5:05	5:40	6:05	6:05	R04 ESE, SE, SSE, S	
1,2 W, WM, WW, MW, MW, MW, MW, MW, MW, WW, MWW, MW, WW, W	1,2,3	SSW, SW, WSW				•		Re	fer to Re	gion 2			<u>.</u>				SSW, SW, WSW	
NNR Set US	1,2	R05 W, WNW, NW, NNW	3:20	3:40	3:15	3:35	3:00	3:20 -	3:35	3:10	3:30	3:00	4:10	2:10	4:20	4:10	R05 W, WNW, NW, NNW	
1.2.3 NNE Refer to Regin 2 NNE 1.2.3.6 R05 RE ENE, E, ESE, SE 4:45 5:20 5:05 5:45 4:20 4:40 5:15 4:40 5:15 5:15 5:45 6:00 6:00 R06 RE ENE, E, ESE, SE 1.2.3,7 R07 SSE, S 5:00 5:30 5:15 5:15 4:45 5:20 4:25 5:25 10:30 6:10 6:10 R07 SSE, S R07 SSE, S 1.2.3,67 R08 SW, SW 5:00 5:30 5:15 5:50 4:30 4:50 5:15 4:45 5:20 10:30 6:10 6:10 R07 SSW, SW 1.2.3,4,6 R09 WSW 4:55 5:30 5:10 5:50 4:30 4:50 5:15 4:45 5:15 4:30 5:35 10:40 6:10 6:10 R08 WSW 8:05 1.2.3,4,6 R10 W 4:50 5:25 5:10 5:50 4:30 4:50 5:15 4:25 5:30 10:40 6:10 R07 WSW R10 WSW 1.2.3,4,6 R11 W 4:50 5:25 5:10								5-Mil	e Ring a	nd Downwir	nd to EPZ	Boundary						
R06 NE, ENE, E., SSE, SE 4:45 5:20 5:05 5:45 4:20 4:40 5:15 4:40 5:15 5:15 5:45 6:00 6:00 R06 NE, ENE, E. ESE SE 1,2,3,7 R07 SSE, S 5:00 5:30 5:15 5:50 4:30 4:50 5:15 4:45 5:20 4:25 5:25 10:30 6:10 6:10 R07 SSE, S 1,2,3,6,7 R08 SSW, SW 5:00 5:30 5:15 5:50 4:30 4:50 5:15 4:45 5:20 4:25 5:25 10:30 6:10 6:10 R07 SSE, S 1,2,3,6,7 R08 SW, SW 4:55 5:30 5:15 4:30 4:45 5:15 4:45 5:20 10:40 6:10 6:10 R08 SSW, SW 1,2,3,6,7 R09 WSW 4:55 5:30 5:10 5:45 4:30 4:45 5:15 4:30 5:35 10:40 6:10 R08 SW, SW 1,2,3,4,6 R10 W 4:50 5:25 5:10 5:50	1,2,3	NNÉ						Re	fer to Re	gion 2							NNE	
1,2,3,7 R07 SSE, S 5:00 5:30 5:15 5:15 4:45 5:20 4:25 5:25 10:30 6:10 6:10 R07 SSE, S 1,2,3,6,7 R08 SSW, SW 5:00 5:30 5:15 5:50 4:30 4:50 5:15 4:45 5:20 4:25 5:20 10:30 6:10 6:10 R08 SSW, SW 1,2,3,6,7 R08 SSW, SW 4:55 5:30 5:15 4:30 4:45 5:20 4:25 5:20 10:40 6:10 6:10 R08 SSW, SW 1,2,3,4,6 R09 WSW 4:55 5:30 5:10 5:45 4:30 4:50 5:15 4:45 5:15 4:30 5:35 10:40 6:10 6:10 R09 WSW 1,2,3,4,6 R10 W 4:50 5:25 5:10 5:50 4:30 4:50 5:20 4:45 5:15 4:25 5:30 10:30 6:05 6:05 R10 WSW 1,2,3,4,6 R11 WNW 4:50 5:25 5:10 5:50 4:45 5:15 4:45 5:15 4:25 5:30 10:25	1,2,3,8	R06 NE, ENE, E, ESE, SE	4:45	5:20	5:05	5:45	4:20	4:40	5:15	4:40	5:10	4:15	5:15	5:45	6:00	6:00	R06 NE, ENE, E, ESE, SE	
1,2,3,6,7 R08 SSW, SW 5:00 5:30 5:50 4:30 4:50 5:15 4:45 5:20 4:25 5:20 10:40 6:10 6:10 R08 SSW, SW 1,2,3,4,6 7 R09 WSW 4:55 5:30 5:10 5:45 4:30 4:50 5:15 4:45 5:15 4:30 5:35 10:40 6:10 6:10 R09 WSW 1,2,3,4,6 R10 W 4:50 5:25 5:10 5:50 4:30 4:50 5:15 4:45 5:15 4:30 5:35 10:40 6:10 6:10 R09 WSW 1,2,3,4,5 R10 W 4:50 5:25 5:10 5:50 4:30 4:50 5:15 4:25 5:30 10:30 6:05 6:05 R0 WSW 1,2,3,4,5 R11 WNW, NNW 4:50 5:25 5:10 5:50 4:45 5:15 4:45 5:30 10:25 6:05 6:00 R11 WNW 1,2,3,4,5 R12 WNW, NNW 4:50 5:25 5:10 5:35 4:45 5:15 4:45 5:10 4:25 5:30 5:	1,2,3,7	R07 SSE, S	5:00	5:30	5:15	5:50	4:30	4:50	5:15	4:45	5:20	4:25	5:25	10:30	6:10	6:10	R07 SSE, S	
1.2,3.4,6 $R09$ WSW $4:55$ $5:30$ $5:10$ $5:45$ $4:30$ $5:15$ $4:30$ $5:35$ $10:40$ $6:10$ $6:10$ $R09$ WSW $1.2,3,4,6$ $R10$ W $4:50$ $5:25$ $5:10$ $5:50$ $4:30$ $5:15$ $4:25$ $5:30$ $10:40$ $6:10$ $6:10$ $R09$ WSW $1.2,3,4,5$ 6 $R11$ W/NW $4:50$ $5:25$ $5:10$ $5:50$ $4:30$ $5:15$ $4:25$ $5:30$ $10:40$ $6:05$ $6:05$ $R10$ WSW $1.2,3,4,5$ 6 $R11$ W/NW $4:50$ $5:25$ $5:10$ $5:50$ $4:30$ $4:45$ $5:15$ $4:25$ $5:30$ $10:25$ $6:05$ $6:00$ $R11$ WNW $1.2,3,4,5$ $R12$ NW, NNW $4:50$ $5:20$ $5:35$ $4:45$ $5:15$ $4:45$ $5:16$ $4:25$ $5:30$ $10:25$ $6:05$ $6:00$ $R11$ WNW $1.2,3,4,5$ $R12$ NW, NNW $R13$ N $4:50$ $5:35$ $4:45$ $5:15$ $4:42$ $5:30$ $5:35$	1,2,3,6,7	R08 SSW, SW	5:00	5:30	5:15	5:50	4:30	4:50	5:15	4:45	5:20	4:25	5:20	10:40	6:10	6:10	R08 SSW, SW	
1,2,3,4,6 \mathbb{R}^{10} 4:50 5:25 5:10 5:50 4:30 4:50 5:20 4:45 5:15 4:25 5:30 10:30 6:05 6:05 6:05 \mathbb{R}^{10} 1,2,3,4,5 \mathbb{R}^{11} 4:50 5:25 5:10 5:50 4:30 4:50 5:20 4:45 5:15 4:25 5:30 10:30 6:05 6:05 \mathbb{R}^{10} 1,2,3,4,5 \mathbb{R}^{11} W/W 4:50 5:25 5:10 5:50 4:30 4:50 5:20 4:45 5:15 4:25 5:30 10:25 6:05 6:00 \mathbb{R}^{11} 1,2,3,4,5 \mathbb{R}^{12} \mathbb{R}^{13} \mathbb{R}^{12} \mathbb{R}^{13} \mathbb{R}^{12} \mathbb{R}^{12} \mathbb{R}^{12} \mathbb{R}^{12} \mathbb{R}^{12} \mathbb{R}^{13} \mathbb{R}^{12} \mathbb{R}^{12} \mathbb{R}^{13} \mathbb{R}^{12} \mathbb{R}^{12} \mathbb{R}^{12} \mathbb{R}^{12} $$	1,2,3,4,6, 7	, R09 WSW	4:55	5:30	5:10	5:45	4:30	4:50	5:15	4:45	5:15	4:30	5:35	10:40	6:10	6:10	R09 WSW	
1.2.3.4.5 R11 4:50 5:25 5:10 5:50 4:30 4:50 5:20 4:45 5:15 4:25 5:30 10:25 6:05 6:00 R11 1.2.3.4.5 R12 4:50 5:20 5:30 14:25 5:30 10:25 6:05 6:00 R11 1.2.3.4.5 R12 4:50 5:20 5:30 4:45 5:15 4:40 5:10 4:25 5:30 5:30 6:05 6:00 R11 1.2.3.4.5 R12 4:50 5:30 5:30 5:35 6:05 6:00 R12 1.2.3.4.5 R13 4:50 5:20 5:15 4:40 5:10 4:25 5:30 5:30 5:35 6:05 6:00 R12 1.2.3.6 R13 A:50 5:25 5:10 5:50 4:45 5:20 4:45 5:15 4:20 5:25 5:50 6:05 6:05 R13 1.8 R14 3:10 3:15 2:45 3:00 2:50 3:50 2:10 4:05 3:40 R14 <td>1,2,3,4,6</td> <td>R10 W</td> <td>4:50</td> <td>5:25</td> <td>5:10</td> <td>5:50</td> <td>4:30</td> <td>4:50</td> <td>5:20</td> <td>4:45</td> <td>5:15</td> <td>4:25</td> <td>5:30</td> <td>10:30</td> <td>6:05</td> <td>6:05</td> <td>R10 W</td>	1,2,3,4,6	R10 W	4:50	5:25	5:10	5:50	4:30	4:50	5:20	4:45	5:15	4:25	5:30	10:30	6:05	6:05	R10 W	
1,2,3,4,5 R12 NW, NNW 4:50 5:20 5:30 5:30 5:35 6:05 6:00 R12 NW, NNW 1,2,3,5 R13 N 4:50 5:25 5:10 5:50 4:45 5:15 4:40 5:10 4:25 5:30 5:35 6:05 6:00 R12 NW, NNW 1,2,3,5 R13 N 4:50 5:25 5:10 5:50 4:45 5:20 4:45 5:15 4:20 5:25 5:50 6:05 6:05 R13 N 1,8 R14 3:10 3:15 2:50 3:10 3:15 2:45 3:00 2:50 3:50 2:10 4:05 3:40 R14	1,2,3,4,5, 6	R11 WNW	4:50	5:25	5:10	5:50	4:30	4:50	5:20	4:45	5:15	4:25	5:30	10:25	6:05	6:00	R11 WNW	
1,2,3,5 R13 N 4:50 5:25 5:10 5:50 4:25 4:45 5:20 4:45 5:15 4:20 5:25 5:50 6:05 6:05 6:05 R13 N 1,8 R14 3:10 3:15 2:45 3:00 2:45 3:00 2:50 3:50 2:10 4:05 3:40 R14	1,2,3,4,5	R12 NW, NNW	4:50	5:20	5:00	5:35	4:25	4:45	5:15	4:40	5:10	4:25	5:30	5:35	6:05	6:00	R12 NW, NNW	
1,8 R14 3:10 3:15 2:45 3:05 2:50 3:10 3:15 2:45 3:00 2:50 3:10 2:50 3:00 2:50 3:50 2:10 4:05 3:40 R14	1,2,3,5	R13 N	4:50	5:25	5:10	5:50	4:25	4:45	5:20	4:45	5:15	4:20	5:25	5:50	6:05	6:05	R13 N	
	1,8	R14	3:10	3:15	2:45	3:05	2:50	3:10	3:15	2:45	3:00	2:50	3:50	2:10	4:05	3:40	_ R14	

-

			Та	ble 7-10	D. Tim	e To Cle	ar The I	ndica	ted Area	a of 10	0 Perce	nt of the Af	fected Pop	ulation		
	Season	Sum	mer	Sum	ner	Summer	Wint	er	Wint	er	Winter	Summer	Summer	Winter	Winter	Season
· · Day	of Week	Midv	/eek	Week	end	Alt	Midwo	eek	Week	end	All	Midweek	Weekend	Midweek	Weekend	Day of Week
S	cenario:	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	Scenario
Tin	ne of Day	Mid	day	Midd	ay	Evening	Midd	ay .	Midd	ay	Evening	Midday	Midday	Midday	Midday	Time of Day
Zone	Region Wind	Good Weather	Rain	Good Weather	Rain	Good Weather	Good Weather	Rain	Good Weather	Rain	Good Weather	New Plant Construction	Air Show at Base	Snow	Snow	Region Wind Direction Towards
							Enti	re 2-Mile	Region, 5-I	Mile Regi	on, and EPZ				• • • • • •	
1	R01 2-mile ring	4:10	4:10	4:05	4:15	4:05	4:10	4:15	4:10	4:10	4:15	4:30	4:00	5:15	5:15	R01 2-mile ring
1,2,3	R02 5-mile ring	5:25	6:05	5:55	6:30	5:00	5:20	5:55	5:20	5:55	4:50	5:50	6:35	6:45	6:40	R02 5-mile ring
1,2,3,4,5, 6,7,8	R03 Entire EPZ	6:00	6:45	6:25	7:10	5:30	5:50	6:20	5:50	6:30	5:25	6:30	11:30	7:25	7:25	R03 Entire EPZ
							:	2-Mile Ri	ng and Dow	nwind to	5 Miles					
1	N, NNE, NE, ENE, E						Re	fer to Re	gion 1			- , ·				N, NNE, NE, ENE, E
1,3	R04 ESE, SE, SSE, S	5:25	6:05	5:55	6:35	4:55	5:20	5:50	5:15	5:50	4:50	5:45	6:20	6:45	6:40	R04 ESE, SE, SSE, S
1,2,3	SSW, SW, WSW			•			Re	fer to Re	gion 2							SSW, SW, WSW
1,2	R05 W, WNW, NW, NNW	4:15	4:20	4:15	4:15	4:15	4:15	4:20	4:10	4:15	4:10	4:50	4:10	5:20	5:15	R05 W, WNW, NW, NNW
				• • • • • • • • • • • • • • • • • • • •			5-Mi	ile Ring a	and Downw	ind to EP	Z Boundary	•				
1,2,3	NNE						Re	fer to Re	gion 2							NNE
1,2,3,8	R06 NE, ENE, E, ESE, SE	5:25	6:05	5:55	6:30	5:00	5:20	5:55	5:20	5:55	4:50	5:50	6:35	6:45	6:40	R06 NE, ENE, E, ESE, SE
1,2,3,7	R07 SSE, S	6:00	6:35	6:20	7:00	5:20	5:45	6:15	5:45	6:20	5:20	6:20	11:25	7:15	7:20	R07 SSE, S
1,2,3,6,7	R08 SSW, SW	6:00	6:45	6:25	7:10	5:30	5:50	6:20	5:50	6:30	5:25	6:30	11:30	7:25	7:30	R08 SSW, SW
1,2,3,4,6, 7	R09 WSW	6:00	6:45	6:25	7:10	5:30	5:50	6:20	5:50	6:30	5:25	6:30	11:30	7:25	7:25	R09 WSW
1,2,3,4,6	R10 W	5:45	6:20	6:15	7:00	5:20	5:45	6:20	5:45	6:20	5:20	6:10	11:20	7:05	7:05	R10 W
1,2,3,4,5, 6	R11 WNW	5:45	6:20	6:15	7:00	5:20	5:45	6:20	5:45	6:20	5:20	6:10	11:20	7:05	7:05	· R11 WNW
1,2,3,4,5	R12 NW, NNW	5:25	6:05	5:55	6:30	4:55	5:20	5:55	5:20	5:55	4:50	5:50	6:35	6:45	6:40	R12 NW, NNW
1,2,3,5	R13 N	5:25	6:05	5:55	6:30	5:00	5:20	5:55	5:20	5:55	4:50	5:50	6:35	6:45	6:40	R13 N
1,8	R14	4:10	4:10	4:10	4:15	4:10	4:10	4:20	4:10	4:10	4:15	4:35	4:05	5:15	5:15	R14

•

7

/

· · · · · · · · · · · · · · · · · · ·	Table 7-2. Description of E	vacua	tion F	Regio	ns					
Region	Description		ZONE							
		1	2	- 3	4	5	6	7	8	
R01	2-Mile Ring	X								
R02	5-Mile Ring	X	X	X						
R03	Full EPZ	X	X	X	Х	X	X	X	X	
	Evacuate 2-Mile Ring and	5 Mile	s Dov	vnwii	nd					
Region	Wind Direction Towards:	ZONE								
		1	2	3	4	5	6	7	8	
	N, NNE, NE, ENE, E	See Region 1								
R04	ESE, SE, SSE, S	X		X						
	SSW, SW, WSW	See Region 2								
R05	W, WNW, NW, NNW	X	X							
	Evacuate 5-Mile Ring and Dowr	wind	to EF	PZ Bo	unda	ry				
Region	Wind Direction Towards:	ZONE								
		1	2	3	4	5	6	7	8	
	NNE	See Region 2								
R06	NE, ENE, E, ESE, SE	X	X	X					X	
R07	SSE, S	X	X	X				X		
R08	SSW, SW	X	X	X			X	X		
R09	WSW	X	X	X	X		X	X		
R10	W	X	X	Χ	X		X			
R11	WNW	X	X	X	X	X	X			
R12	NW, NNW	X	X	X	X	X				
R13	N	X	X	Χ		X				
R14	*	X							X	

*This Region was added at Constellation Energy's request. It is an evacuation of the 2-Mile Ring and downwind (Towards Dorchester County) to the EPZ Boundary.

r r















Figure 7-7. Evacuation Time Estimates for CCNPP Summer, Midweek, Midday, Good Weather Evacuation of Region R03 (Entire EPZ)

8. TRANSIT-DEPENDENT AND SPECIAL FACILITY EVACUATION TIME ESTIMATES

This section details the analyses applied and the results obtained in the form of evacuation time estimates for transit vehicles (buses). The demand for transit service reflects the needs of two population groups: (1) residents with no vehicles available; and (2) residents of special facilities such as schools, health-support facilities, institutions and child-care facilities.

These transit vehicles merge into and become a part of the general evacuation traffic environment that is comprised mostly of "passenger cars" (pc's). The presence of each transit vehicle in the evacuating traffic stream is represented within the modeling paradigm described in Appendix D as equivalent to two pc's. This equivalence factor represents the larger size and more sluggish operating characteristics of a transit vehicle relative to those of a pc.

Transit vehicles must be mobilized in preparation for their respective evacuation missions. Specifically:

- Bus drivers must be alerted
- They must travel to the bus depot
- They must be briefed there and assigned to a route or facility

These activities consume time. Based on data provided by the emergency staff for the EPZ counties, it is estimated that bus mobilization time will average between 60 and 90 minutes extending from the Advisory to Evacuate to the time when buses arrive at their respective assignments.

During this mobilization period, other mobilization activities are taking place. One of these is the action taken by parents, neighbors, relatives and friends to pick up children from school prior to the arrival of buses, so that they may join their families. Virtually all studies of evacuations have concluded that this "bonding" process of uniting family members is universally prevalent during emergencies and should be anticipated in the planning process. Many emergency plans, however, call for parents to pick up children at the host schools to speed the evacuation of the school children in the event that buses need to return to the EPZ and evacuate transit dependents. We provide estimates of buses under the assumption that no children will be picked up at school by their parents as an upper bound estimate of the transit vehicles needed.

The procedure is:

- Estimate demand for transit service
- Estimate time to perform all transit functions
- Estimate route travel times to the EPZ boundary and to the host schools.

8.1 Transit-Dependent People - Demand Estimate

The telephone survey (see Appendix F) results were used to estimate the portion of the population requiring transit service:

- Those persons in households that do not have a vehicle available.
- Those persons in households that do have vehicle(s) that would not be available at the time the evacuation is advised.

In the latter group, the vehicle(s) may be used by a commuter(s) who does not return (or is not expected to return) home to evacuate the household.

Table 8-1 presents estimates of transit-dependent people. Note:

- Estimates of persons requiring transit vehicles include school children. For those evacuation scenarios where children are at school when an evacuation is advised, separate transportation is provided for the school children. The actual need for transit vehicles by residents is thereby less than the given estimates. However, we will not reduce our estimates of transit vehicles since it would add to the complexity of the implementation procedures.
- It is reasonable and appropriate to consider that many transit-dependent persons will evacuate by ride-sharing with neighbors, friends or family. For example, nearly 80 percent of those who evacuated from Mississauga, Ontario¹ who did not use their own cars, shared a ride with neighbors or friends. Other documents report that approximately 70 percent of transit-dependent persons were evacuated via ride-sharing. We will adopt a conservative estimate that 50 percent of transit-dependent persons will ride-share.

The estimated number of bus trips needed to service transit-dependent persons is based on an estimate of average bus occupancy of 30 persons at the conclusion of the bus run. Transit vehicle seating capacities typically equal or exceed 60 children (equivalent to 40 adults). If transit vehicle evacuees are two-thirds adults and one-third children, then the number of "adult seats" taken by 30 persons is $20 + (2/3 \times 10) = 27$. On this basis, the average load factor anticipated is $(27/40) \times 100 = 68$ percent. Thus, if the actual demand for service exceeds the estimates of Table 8-1 by 50 percent, the demand for service can still be accommodated by the available bus seating capacity.

Table 8-1 indicates that transportation must be provided for 980 people. Therefore, a total of 33 bus runs are required to transport this population to reception centers.

¹ The Mississauga Evacuation – Final Report, The Institute for Environmental Studies, University of Toronto, June 1981

To illustrate this estimation procedure, we calculate the number of persons, P, requiring public transit or ride-share, and the number of buses, B, required for the CCNPP EPZ:

 $P = 19,715 \times (0.025 \times 1.50 + 0.222 \times (1.64 - 1) \times 0.645 \times 0.42 + 0.393 \times (2.81 - 2) \times (0.645 \times 0.42)^2)$ P = 19,715 * (0.09935) = 1,960 $B = (0.5 \times P) \div 30 = 33$

These calculations are explained as follows:

- All members (1.5 avg.) of households (HH) with no vehicles (2.5%) will evacuate by public transit or ride-share. The term 19,715 (number of households) x 0.025 x 1.5, accounts for these people.
- The members of HH with 1 vehicle away (22.2%), who are at home, equal (1.64-1). The number of HH where the commuter will not return home is equal to (19,715 x 0.222 x 0.645 x 0.42), as 64.5% of EPZ households have a commuter, 42% of which would not return home in the event of an emergency. The number of persons who will evacuate by public transit or ride-share is equal to the product of these two terms.
- The members of HH with 2 vehicles that are away (39.3%), who are at home, equal (2.81 2). The number of HH where neither commuter will return home is equal to 19,715 x 0.393 x (0.645 x 0.42)². The number of persons who will evacuate by public transit or ride-share is equal to the product of these two terms.
- Households with 3 or more vehicles are assumed to have no need for transit vehicles.
- The total number of persons requiring public transit is the sum of such people in HH with no vehicles, or with 1 or 2 vehicles that are away from home.

8.2 <u>School Population – Transit Demand</u>

Table 8-2 presents the school population and transportation requirements for the direct evacuation of all schools within the EPZ. The column in Table 8-2 entitled "Bus Runs Required" specifies the number of buses required for each school under the following set of assumptions and estimates:

- No students will be picked up by their parents prior to the arrival of the buses.
- Bus capacity, expressed in students per bus, is set to 70 for primary schools and 50 for middle and high schools.
- Those staff members who do not accompany the students will evacuate in their private vehicles.

• No allowance is made for student absenteeism which is in the neighborhood of 3 percent, daily.

The estimate of buses needed for ETE purposes in Table 8-2 are overstated in that no allowance is made for those high school students who drive to school on a daily basis, absentees, and students picked up by their parents.. Comparison of the information provided by the counties with the estimated bus needs in Table 8-2 indicated good agreement and representatives from St. Mary's County and Calvert County have confirmed that available bus resources can evacuate the schools in a single wave. However, for reference purposes, Tables 8-5A and 8-5B include information to show a second wave ETE for all schools. We recommend that the Counties introduce procedures whereby the schools are contacted prior to the dispatch of buses from the depot (approximately one hour after the Advisory to Evacuate), to ascertain the current estimate of students to be evacuated. In this way, the number of buses dispatched to the schools will reflect the actual number needed. Some parents will likely pick up their children at school, although they are asked to pick children up at the host schools. Those buses originally allocated to evacuate school children that are not needed due to children being picked up by their parents, can be gainfully assigned to service other facilities or those persons who do not have access to private vehicles or to ride-sharing.

Table 8-3 presents a list of the host schools for each school in the EPZ; Figure 8-3 maps all of the EPZ schools and their host schools. Those students not picked up by their parents prior to the arrival of the buses, will be transported to these host schools where they will be subsequently retrieved by their respective families.

8.3 Special Facility Demand

Table 8-4 presents the current census for special facilities obtained through phone calls to the facilities and through Internet searches. Approximately 103 people have been identified as living in, or being treated in, these facilities. This data also indicates the number of wheelchair-bound people. The transportation requirements for those people residing in special facilities are also presented. The number of bus runs estimated assumes 30 ambulatory patients per trip. Wheelchair buses can transport 15 patients while vans can transport 4 patients. There are 2 senior centers listed with a total of 59 seniors at the facilities during the day; there are no overnight accommodations at these facilities. Based on discussions with representatives from these facilities, most of the seniors drive to the facility each day. Some of the seniors, however, will require transportation. We have conservatively included all of the visitors to the senior centers as transit dependent people. In total, we estimate that 5 buses and 2 wheelchair vans are required to meet the special facility demand.

8.4 <u>Evacuation Time Estimates for Transit-Dependent People</u>

County bus resources are assigned to evacuating school children as the first priority in the event of an emergency. In the event that the allocation of buses dispatched from the depots to the various facilities and to the bus routes is somewhat "inefficient", or if there is a shortfall of available drivers, then there may be a need for some buses to return to the EPZ from the host school after completing their first evacuation trip, to complete a "second wave" of providing transport service to evacuees. Based on discussions with the EPZ counties, there are sufficient bus resources to evacuate the schools in a single wave. There are not, however, sufficient bus resources to evacuate the transit-dependent population in a single wave, as most of the buses in the counties will be allocated for the evacuation of school children. For this reason, the ETE will be calculated for both a one wave transit-dependent evacuation and for two waves (Table 8-7). Of course, if the impacted Evacuation Region is other than R03 (the entire EPZ), then there will likely be ample transit resources relative to demand in the impacted Region and this discussion of a second wave would likely not apply.

When school evacuation needs are satisfied, subsequent assignments of buses (if available) to service the transit-dependent should be sensitive to their mobilization time. Clearly, the buses should be dispatched after people have completed their mobilization activities and are in a position to board the buses when they arrive at the pick-up points.

Evacuation Time Estimates for Transit Trips were developed using both good weather and adverse weather conditions. Figure 8-1 presents the chronology of events relevant to transit operations. The elapsed time for each activity will now be discussed with reference to Figure 8-1.

Activity: Mobilize Drivers $(A \rightarrow B \rightarrow C)$

Mobilization is the elapsed time from the Advisory to Evacuate until the time the buses arrive at the facility to be evacuated. Based on data provided by the counties, for a rapidly escalating radiological emergency with no observable indication before the fact, drivers would likely require between 60 and 90 minutes (depending on the facility to be evacuated) to be contacted, to travel to the depot, be briefed, and to travel to the transitdependent facilities. Mobilization time is extended by 10 minutes when raining to account for slower travel times.

Activity: Board Passengers $(C \rightarrow D)$

Studies have shown that passengers can board a bus at headways of 2-4 seconds (Ref. HCM2000 Page 27-27). Therefore, the total dwell time to service passengers boarding a bus to capacity at a single stop (e.g., at a school) is about 5 minutes. A loading time of 10 minutes will be used for rain scenarios. For multiple stops along a pick-up route we must allow for the additional delay associated with stopping and starting at each pick-up point. This additional delay to service passengers expands this estimate of boarding time to 30 minutes in good weather, and 35 minutes in rain.

Activity: Travel to EPZ Boundary $(D \rightarrow E)$

School Evacuation

The distance from a school to the EPZ boundary is measured using Geographical Information Systems (GIS) software along the most likely route out of the EPZ. The travel times to the EPZ boundary are based on evacuation speeds output by the model (PC-DYNEV). The average speed for an evacuation of the full EPZ under Scenario 6 (winter [school in session], good weather) and Scenario 7 (with rain) at 60 minutes is 26.7 mph and 23.6 mph, respectively, and at 90 minutes is 19.1 mph and 16.9 mph, | respectively. The travel time from the EPZ boundary to the Host School is computed assuming average speeds of 40 mph and 35 mph for good weather and rain, respectively. These speeds are assumed outside of the EPZ as congestion will likely be less pronounced and travel speeds will be faster.

Tables 8-5A (good weather) and 8-5B (rain) present the following evacuation time estimates (rounded up to the nearest 5 minutes) for schools in the EPZ: (1) The elapsed time from the Advisory to Evacuate until the bus exits the EPZ; and (2) The elapsed time until the bus reaches the Host School. The evacuation time out of the EPZ can be computed as the sum of travel times associated with Activities $A \rightarrow B \rightarrow C$, $C \rightarrow D$, and $D \rightarrow E$ (For example: 90 min. + 5 + 28= 2:05, rounded to the nearest 5 minutes, for | Patuxent High School, with good weather). The evacuation time to the Host School is determined by adding the time associated with Activity $E \rightarrow F$ (discussed below), to this EPZ evacuation time. Note: the evacuation routes used for some of the schools within Calvert County that are south of CCNPP travel through St. Mary's County along Three Notch Road (State Route 235), Hallowing Point Road (State Route 2/4 because this would take the school buses directly towards the CCNPP. This results in longer routes and longer travel times than expected from the EPZ boundary to the Host Schools.

Evacuation of Transit-Dependent Population

The buses dispatched from the depots to service the transit-dependent evacuees will be scheduled so that they arrive at their respective routes after their passengers have completed their mobilization. As indicated in Section 5, about 90 percent of the evacuees will complete their mobilization when the first buses will begin their routes, 90 minutes after the Advisory to Evacuate.

Those buses servicing the transit-dependent evacuees will first travel along their pick-up routes, then proceed out of the EPZ. Table 8-7 presents the transit-dependent population evacuation time estimates for each route obtained using the procedures outlined above.

Activity: Travel to Reception Center/Host School $(E \rightarrow F)$

The distances from the EPZ boundary to the host schools are measured using GIS software along the most likely route from the EPZ to the host school. For a one-wave evacuation, this travel time outside the EPZ does not contribute to the ETE. For a two-wave evacuation, the ETE for buses must be considered separately, since it could exceed the ETE for the general public.

Activity: Passengers Leave Bus $(F \rightarrow G)$

Passengers can de-board within 5 minutes. The bus driver takes a 10 minute break.

Activity: Bus Returns to Route for Second Wave Evacuation $(G \rightarrow C)$

The buses assigned to return to the EPZ to perform a "second wave" evacuation of transit-dependent evacuees will be those buses that evacuated the school children as they will likely be the first resources available. Most of the host schools are in close proximity to the transit bus route identified below, thus the travel time to the start of the bus route is assumed to be negligible. The bus travels its route and picks up transit-dependent evacuees along the route.

Analysis of Bus Route Operations

Based on the highway network within the EPZ, the suggested route for bus operations to service the transit dependent population within the EPZ is shown in Figure 8-2. A single loop that traverses Three Notch Road (State Route 235), Hallowing Point Road (State Route 231) and State Route 2/4 would best service the transit dependent residents. These buses would be dispatched in 2 batches – one at 90 minutes after the Advisory to Evacuate and the second batch at 120 minutes. These buses would traverse this main route and circulate within the higher population areas in the EPZ. These passengers would be dropped off at the reception centers along the bus route. The mobilization times (140 minutes for good weather, 160 minutes for rain) for a second-wave evacuation are the average ETE for schools to arrive at the Host Schools, as these buses will return to the EPZ to service the transit dependent. The second batch of buses (if needed) will be delayed by 30 minutes in the second-wave also.

The ETE for good weather for each batch of buses is given in Table 8-7A. Table 8-7B provides the ETE for rain. The route length is approximately 58 miles; the average travel speeds output by PC-DYNEV are used to estimate route travel times. The average speed for an evacuation of the full EPZ under Scenario 6 (winter, good weather) and Scenario 7 (with rain) at 90 minutes is 19.1 mph and 16.9 mph, respectively, and at 120 minutes is 14.8 mph and 13 mph, respectively.

The ETE for a single wave transit-dependent evacuation in general, does not exceed the general population ETE; however, a two-wave evacuation would exceed the general population ETE.

Evacuation of Ambulatory Persons from Special Facilities

The bus operations for this group are similar to those for school evacuation except:

- Buses are assigned on the basis of 25-30 patients to allow for staff to accompany the patients.
- The passenger loading time will be longer at approximately one minute per patient to account for the time to move patients from inside the facility to the vehicles.

It is estimated that mobilization time averages 90 minutes for the "first-wave" evacuation.

The average distance of the four nursing homes and senior centers within the EPZ to the EPZ boundary is approximately 5 miles. Thus, buses will have to travel 5 miles, on average, to leave the EPZ. The average speed output by the model at 90 minutes for Region 3, Scenario 6 is 19.1 mph; thus, travel time out of the EPZ is 15 minutes.

The ETE for each medical facility is the sum of the mobilization time, loading time, and travel time out of the EPZ. For example, the calculation of ETE for the bus servicing the Southern Pines Senior Center with a census of 30 is:

ETE: 90 + 30 x 1 + 15 = 135 min. or 2:15.

A total of five buses are needed to evacuate the three special facilities in Calvert County and one bus for that in St. Mary's County (see page E-4). In the event there is a shortfall of transit vehicles for a "first-wave" evacuation, the buses used to evacuate the schools will have to return to evacuate the special facilities. In this case the mobilization time to be used for the ETE calculation is the average time that the buses reach the host schools. Given that these four facilities are south of the CCNPP, it follows that buses should be dispatched from the host schools to the south which service Zone 7. For good weather conditions, the first five buses reach the host schools in St. Mary's County at 1 hour and 20 minutes (Table 8-5A). The components of the "second-wave" evacuation are:

- 1. Unload school children (assume 5 minutes)
- 2. Driver rest/preparation (assume 10 minutes)
- 3. Return to EPZ boundary (at estimated speed of 40 mph)
- 4. Continue to facility (at 40 mph)
- 5. Load passengers (one minute per patient)
- 6. Drive to EPZ boundary (at the speed indicated by the DYNEV output)

The average distance of the host schools in Zone 7 (that would most likely service these facilities) from the EPZ boundary is about 7 miles (Table 8-5A); the average distance of the medical facilities from the EPZ boundary is approximately 5 miles. Thus, buses will have to travel about 12 miles, on average, to reach the facilities, which at 40 mph, will take 18 minutes. Measuring from the Advisory to Evacuate (ATE), the elapsed time will be 80 + 5 + 10 + 18 = 113 minutes when the bus reaches the medical facility. The loading time varies by facility; the speed exiting the EPZ is obtained from the model output for Region 3, Scenario 6.

Considering the Southern Pines Senior Center with a census of 30 (loading time of 30 minutes) the bus will leave the facility at 2 hours and 23 (113+30) minutes after the ATE, at which point the average roadway travel speed will be 14.6 mph.

ETE: 143 + 5/14.6x60 = 163 min. or 2:45, to the nearest 5 minutes.

Table 8-4 indicates that 2 wheelchair van runs are needed for the entire EPZ. Loading times are estimated at 5 minutes per wheelchair bound person as staff will have to assist them in boarding the van. The ETE for the wheelchair-bound patients is calculated in the same way as the ETE for the ambulatory patients. For example, the ETE for the wheelchair bound at Solomon's Nursing Center is:

ETE: 90 + 7 x 5 + 15 = 140 min. or 2:20.

Thus, the ETE for special facilities do not exceed the general population ETE.

ETE for Homebound Special Needs Population

Communication with the counties has yielded the following data concerning special transportation for people at home:

Within EPZ	<u>Calvert</u>	<u>St. Mary's</u>	<u>Dorchester</u>
Need ambulances	12	0	1
Wheelchair bound	25	0	0
Registered special needs	417	8	1
Ambulances available	15	26	12

The counties have mutual aid agreements with neighboring counties for resources in the event of an emergency. Therefore, it is reasonable to expect that the requisite number of vans accommodating wheelchair bound persons, or additional ambulances (the 15+26+12 ambulances available are more than needed) would be available within a 90 minute mobilization time. Note that most special needs persons living at home have their transport needs provided by other members of the household.

To calculate ETE for the homebound special needs population, assume that the 37 persons in Calvert County are serviced in 19 ambulances (assume 2 persons per ambulance), with 4 ambulances provided by St. Mary's County. As stated above, mobilization time is assumed to be 90 minutes and each ambulance servicing the homebound bed-ridden population will make 2 stops within the EPZ and travel out of the EPZ. Allowing 15 minutes to load each patient, 15 minutes to travel to the second home, then 15 minutes to travel out of the EPZ yields:

ETE: 90 + 15 + 15 + 15 + 15 = 2:30 (hr:min)



<u>Event</u>

-

Α	Advisory to Evacuate
В	Bus Dispatched from Depot
С	Bus Arrives at Facility/Pick-up Route
D	Bus Departs for Reception Center/Host School
E	Bus Exits Region
F	Bus Arrives at Reception Center/Host School
G	Bus Available for "Second Wave" Evacuation Service
<u>Activit</u>	<u>х</u>
A→B	Driver Mobilization
B→C	Travel to Facility or to Pick-up Route
C→D	Passengers Board the Bus
D→E	Bus Travels Towards Region Boundary
E→F	Bus Travels Towards Reception Center/Host School Outside the EPZ.
F→G	Passengers Leave Bus; Driver Takes a Break

Figure 8-1. Chronology of Transit Evacuation Operations

ł





					Table 8-1.	Tran	sit Dep	bende	nt Populati	on Estimate	es			
Facility Name	2008 EPZ Population	Survey Average Household Size With Indicated No. of Vehicles			Estimated	Survey Percent Households With			Survey Percent Households	Survey Percent Households	Total People	Estimated Ridesharing	People Requiring	Percent of Population Requiring
		0	1	2	Households	0 Veh- icle	1 Veh- icle	2 Veh- icle	With Commuters	With Non- Returning Commuters	Transport	Percentage	Transit	Public Transit
Calvert Cliffs Nuclear Power Plant	55,205	1.5	1.64	2.81	19,715	2.5%	22.2%	39.3%	64.5%	42%	1,960	50%	980	1.8%

*See Section 8.1 for detailed calculation.

.

~

:

.

			Table 8-2. School Population De	mand Estimates			
PAZ	Distance (miles)	Dir- ection	School Name	Municipality	Enroll- ment	Staff	Bus Runs Required
	- -		Calvert County				
1	1.8	S	Southern Middle School	Lusby	632	91	13
1	3.8	WNW	St. Leonard Elementary School	St. Leonard	739	40	11
2	5.6	WNW	Mutual Elementary School	Pt. Republic	628	82	9
- 3	4.0	S	Lusby	503	44	8	
3	4.2	S	Lusby	431	52	7	
3	4.6	S	Dowell Elementary School	Lusby	695	79	10
3	4.8	S	Mill Creek Middle School	Lusby	631	87	13
3	5.5	S	Patuxent High School	Lusby	1,366	103	28
3	7.6	S	Our Lady Star of the Sea School	Solomons	194	25	3
			Calv	vert County Total:	5,819	603	102
			St. Mary's Count	y			
7	7.8	SW	Hollywood Elementary School	Hollywood	641	66	10
7	9.4	SSW	Town Creek Elementary School	Lexington Park	272	37	4
7	9.8	SSW	Green Holly Elementary School	Lexington Park	620	96	9
7	9.9	SW	St. John's Elementary School	Hollywood	221	21	4
7	10.1	SSW	Esperanza Middle School	Lexington Park	880	93	18
			St. Mai	y's County Total:	2,634	313	45
				EPZ Total:	8,453	916	147

.

Table	8-3. H	lost Schools							
School	PAZ	Host School							
	High S	chools							
Patuxent High School	3	Northern High School							
Middle Schools									
Southern Middle School	1	Northern Middle School							
Mill Creek Middle School	3	Plum Point Middle School							
Esperanza Middle School	7	Forrest Career and Technology Center							
Elei	menta	ry Schools							
St. Leonard Elementary School	1	Windy Hill Middle School							
Mutual Elementary School	2	Calvert Elementary School							
Appeal Elementary School	3	Plum Point Elementary School							
Dowell Elementary School	3	Calvert Middle School							
Our Lady Star of the Sea School	3	Mt. Harmony Elementary School							
Patuxent Elementary School	3	Huntingtown Elementary School							
Green Holly Elementary School	7	Forrest Career and Technology Center							
Hollywood Elementary School	7	Margaret Brent Middle School							
St. John's Elementary School	7	St. Mary's Ryken							
Town Creek Elementary School	7	Margaret Brent Middle School							

.

• •

)

£

		Table 8-4.	Special	Facility Tr	ansit Dem	and							
PAZ	Facility Name	Municipality	Cap- acity	Current Census	Ambu- latory	Wheel- chair Bound	Bed- ridden	Ambu- lance Runs	Wheel- chair Bus Runs	Wheel- chair Van Runs	Bus Runs		
	CALVERT COUNTY												
3	Asbury at Solomon's Island	Solomons	6	5	5	0	0	0	0	0	1		
3	Solomon's Nursing Center	Solomons	40	39	32	7	0	0	0	2	2		
3	Southern Pines (Senior Center)	Lusby	30	30	30	0	0 '	0	0	0	1		
			ST.MAP	RYS COUN	TY								
7	Vivian Ripple Center (Senior Center)	Hollywood	29	29	29	0	0	0	0	0	1		
		Total:	105	103	96	7	0	0	0	2	5		

Table 8-5A. Schoo	Table 8-5A. School Evacuation Time Estimates - Good Weather 1st Wave												
School	Driver Mobilization Time(min)	Loading Time (min)	Dist. to EPZ Boundary (mi.)	Travel Time to EPZ Bdry (min)	ETE (hr:min)	Dist. EPZ Bdry to H.S. (mi.)	Travel Time EPZ Bdry to H.S. (min)	ETE to H.S. (hr:min)					
Calvert County Schools													
Appeal Elementary School 90 5 8.0 26 2305 40.9 62 3305													
Dowell Elementary School	90	5	6.6	21	2:00	36.7	58	2:55					
Mill Creek Middle School	90	5	6.4	21	2:00	41.3	62	3:00					
Mutual Elementary School	90	5	5.9	19	1:55	2.0		2:00					
Our Lady Star of the Sea School	60	5	8.9	20	1:25	49.2	74	2:40					
Patuxent Elementary School	90	5	8.0	26	2:05	42.8	65	3:10					
Patuxent High School	90	5	8.8	28	2:05	48.7	74	3:20					
Southern Middle School	60	5	10.2	23	1:30	48.7	74	2:45					
St. Leonard Elementary School	90	5	7.0	22	2:00	14.6	22	2:20					
	St. Ma	ry's Cou	nty Schoo	ols									
Esperanza Middle School	60	5	0.0	0	1:03	8.9	14	1:20					
Green Holly Elementary School	60	5	0.2	1	1:10	6.5	10	1:20					
Hollywood Elementary School	60	5	6.1	14	1:20	5.8	9	1:30					
St. John's Elementary School	60	5	0.7	2	1:10	5.9	9	1:20					
Town Creek Elementary School	60	5	0.7	2	1:10	15.8	24	1:35					
			Averag	e for EPZ:	1:40	A	verage:	2:20					

1 1

Table 8-5A(cont). School Evacuation Time Estimates - Good Weather 2nd Wave													
School	Driver Mobilization Time(hr:min)	Unloading Time (min)	Driver Rest (min)	Dist. to School (mi.)	Travel Time to School (min)	Time School Reached (hr:min)	Loading Time (min)	Dist. to EPZ Boundary (mi.)	Travel Time to EPZ Bdry (min)	ETE (hr:min)	Dist. EPZ Bdry to H.S. (mi.)	Travel Time EPZ Bdry to H.S. (min)	ETE to H.S. (hr:min)
Calvert County Schools													
Appeal Elementary School 3:05 5 10 48.9 74 4:35 5 8.0 24 5:00 40.9 62/// 6:05///													
Dowell Elementary School	2:55	5	10	43.3	65.+	4:15	5	6.6	23	4:40	36.7	-56.	5:40
Mill Creek Middle School	3:00	5	10	47.7	72	4:30	5	6.4	21	4:55	41.3	62	6:00
Mutual Elementary School	2:00	5	1.0	7.9	12 -	2:30		5.9	25	2:55	2.0	3	3:00
Our Lady Star of the Sea School	2:40	5	1,0	58.1	88	4:25	5	8.9	29,	4:55	49.2	.74	6:10
Patuxent Elementary School	3:10	5	1.0	50.8	77.2	4:45	÷ 5.	8.0	22	5:10	42.8	- 65	6:15
Patuxent High School	3:20	5	10	57.5	87	5:05	5	8.8	24	5:30	48.7	74	6:45
Southern Middle School	2:45	5	, _10.	58.9	89	4:30	5	10.2	33	5:05	48.7		.6:20
St. Leonard Elementary School	2:20	5	10.	21.6	33	3:10	5	7.0	28	3:40	14.6	22	4:05
	-		St. N	lary's C	ounty S	chools							
Esperanza Middle School	1:20	5.	=10	8.9	1.4	1:50	5	0.0	-0	1:50	8.9	14	2:05-
Green Holly Elementary School	1:20	5	10	6.7	11	1:50	5	0.2	13	1:55	6.5	10	2:05
Hollywood Elementary School	1:30	-5	10	11.9	18	2:05	5	6.1	25	2:30	5.8	× 9	2:40
St. John's Elementary School	1:20	5	10	6.6	10	1:45	5.	0.7	2	. 1:50	5.9	.9	2:00
Town Creek Elementary School	1:35	5	10	16.5	25	2:15	5	0.7	3	2:20	15.8	-24	2:45
							A	verage fo	or EPZ:	3:45	A	verage:	4:25

.....

Table 8-5B. S	Table 8-5B. School Evacuation Time Estimates - Rain 1st Wave											
School	Driver Mobilization Time(min)	Loading Time (min)	Dist. to EPZ Boundary (mi.)	Travel Time to EPZ Bdry (min)	ETE (hr:min)	Dist. EPZ Bdry to H.S. (mi.)	Travel Time EPZ Bdry to H.S. (min)	ETE to H.S. (hr:min)				
Calvert County Schools												
Appeal Elementary School	100	10	8.0	29	2:20	40.9	71	3:30				
Dowell Elementary School	100	10	6.6	24	2:16	36.7	63	3:20				
Mill Creek Middle School	100	10	6.4	23	2:15	41.3	71	3:25				
Mutual Elementary School	100	10	5.9	21	2:15	2.0	4	2:15				
Our Lady Star of the Sea School	70	10	8.9	23	1:45	49.2	85	3:10				
Patuxent Elementary School	100	10	8.0	29	2:20	42.8	74	3:35				
Patuxent High School	100	10	8.8	32	2:25	48.7	84	3:50				
Southern Middle School	70	10	10.2	26	1:50	48.7	84	- 3810				
St. Leonard Elementary School	100	10	7.0	25	2:13	14.6	26	2::45				
	St. Ma	ry's Cou	nty Scho	ols								
Esperanza Middle School	70	10	0.0	0	1:20	8.9	16	1:40				
Green Holly Elementary School	70	10	0.2	1	1:25	6.5	12	1:35				
Hollywood Elementary School	70	10	6.1	16	1:40	5.8	10	1:50				
St. John's Elementary School	70	10	0.7	2	1:25	5.9	11	1:36				
Town Creek Elementary School	70	10	0.7	2	1:25	15.8	23	1:50				
			Averag	e for EPZ:	1:55	A	verage:	2:40				

.

	Table 8-5B (cont). School Evacuation Time Estimates - Rain 2nd Wave												
School	Driver Mobilization Time(hr:min)	Unloading Time (min)	Driver Rest (min)	Dist. to School (mi.)	Travel Time to School (min)	Time School Reached (hr:min)	Loading Time (min)	Dist. to EPZ Boundary (mi.)	Travel Time to EPZ Bdry (min)	ETE (hr:min)	Dist. EPZ Bdry to H.S. (mi.)	Travel Time EPZ Bdry to H.S. (min)	ETE to H.S. (hr:min)
Calvert County Schools													
Appeal Elementary School 3:30 10 10 48.9 84 5:15 10 8.0 23 5:50 40.9 71 7:05													
Dowell Elementary School	3:20	10	10	43.3	-7.5.	4:55	10	6.6	22	5:30	36.7	63	6:35
Mill Creek Middle School	3:25	10	10	47.7	82	5:10	10	6.4	20>	5:40,	41.3	71	6:55
Mutual Elementary School	2:15	10	10	7.9	14	2:50	10	5.9	29	3:30*	2.0	4 .	3:35
Our Lady Star of the Sea School	3:10	10	10	58.1	100	5:10	10	8.9	27	5:50	49.2	85	7:15
Patuxent Elementary School	3:35	10	10	50.8	88	5:25	10	8.0	23	6:00	42.8	74	7:15
Patuxent High School	3:50	10	10	57.5	.99	5:50	10,	8.8	23	*6:25	48.7	84	7:50
Southern Middle School	3:10	10	10	58.9	101	5:15	10-	10.2	⇒30 <u>≗</u> -,	5:55	48.7	-84	7:20
St. Leonard Elementary School	2:45	10	10	21.6	38	3:45	10	7.0	32	4:30	14.6	26	5:00
	رادين تحجر الأبانيدر	小子的 人名	St. N	lary's C	ounty S	chools	•	4				. • • •	¥ 1
Esperanza Middle School	1:40	. 10	10	8.9	16	2:20	10	0.0	. 0 -	2:30	8.9	1.6	2:50
Green Holly Elementary School	1:35	10	1.0	6.7	12	2:10	1,0/	0.2		2:25	6.5	12 0	2:40
Hollywood Elementary School	1:50	10	10	11.9	21	2:35	10	6.1	30	3:15	5.8	10	3:25
St. John's Elementary School	1:35	10	10	6.6	12	2:10	10	0.7	3	2:25	5.9	11-3	2:40
Town Creek Elementary School	1:50	10	10	16.5	29	2:40	10	0.7	3	2:55	15.8	- 28	3:25
							4	verage fo	or EPZ:	4:25	A	verage:	5:10

	Table 8-6. Summary of Transit Dependent Bus Routes											
Route Number	Number of Buses	Route Description										
1	Batch 1 – 20 buses – after 90 minutes	Loop – State Route 235, State Route 2/4 and State Route 231										
1	Batch 2 – 20 buses – after 120 minutes	Loop – State Route 235, State Route 2/4 and State Route 231										

	Table 8-7A. Transit Dependent Evacuation Time Estimate - Good Weather												
		Single Wave				Second Wave							
Buses	Mobilization	Route Travel Time	Pickup Time	ETE	Mobilization	Unload Time	Driver Rest Time	Route travel Time	Pickup Time	ETÊ.			
Batch 1	90	183	30	5:05	140	5	10	183	30	6:10			
Batch 2	120	236	30	6:30	170	5	10	236	30	7:35			

Table 8-7B. Transit Dependent Evacuation Time Estimate - Rain										
	Single Wave					Second Wave				
Buses	Mobilization	Route Travel Time	Pickup Time	ETE	Mobilization	Unload Time	Driver Rest Time	Route travel Time	Pickup Time	ÊTE
Batch 1	90	206	35	: 5:35	160	5	10	206	35	7:00
Batch 2	120	268	35	7:05	190	5	10	268	35	8:30

٠

9. TRAFFIC MANAGEMENT STRATEGY

This section presents the current traffic control and management strategy that is designed to expedite the movement of evacuating traffic. The resources required to implement this strategy include:

- Personnel with the capabilities of performing the planned control functions of traffic guides (preferably, not necessarily, law enforcement officers).
- Traffic Control Devices to assist these personnel in the performance of their tasks. These devices should comply with the guidance of the Manual of Uniform Traffic Control Devices (MUTCD) published by the Federal Highway Administration (FHWA) of the U.S.D.O.T. All state and most county transportation agencies have access to the MUTCD (also available online). Applicable devices include, with reference to the MUTCD:
 - Traffic Barriers: Chapter 6F, section 6F.61, 62 and Figure 6F-4.
 - Traffic Cones: Chapter 3F and section 6F.56.
 - o Signs: Chapter 2I
- A plan that defines all necessary details and is documented in a format that is readily understood by those assigned to perform traffic control.

The functions to be performed in the field are:

- 1. <u>Facilitate</u> evacuating traffic movements that serve to expedite travel out of the EPZ along routes that the analysis has found to be most effective.
- 2. <u>Discourage</u> traffic movements that permit evacuating vehicles to travel in a direction which takes them significantly closer to the power plant, or which interferes with the efficient flow of other evacuees.

We employ the terms "facilitate" and "discourage" rather than "enforce" and "prohibit" to indicate the need for flexibility in performing the traffic control function. There are always legitimate reasons for a driver to prefer a direction other than that indicated. For example:

- A driver may be traveling home from work or from another location, to join other family members preliminary to evacuating.
- An evacuating driver may be taking a detour from the evacuation route in order to pick up a relative, or other evacuees.
- The driver may be an emergency worker en route to perform an important activity.

The implementation of a plan <u>must</u> also be flexible enough for the application of sound judgment by the traffic guide.

2

The traffic management strategy is the outcome of the following process:

- 1. A field survey of these critical locations.
 - The schematics describing traffic control, which are presented in Appendix G, are based on data collected during field surveys, upon large-scale maps, and on overhead photos.
- 2. Computer analysis of the evacuation traffic flow environment.

This analysis identifies the best routing and those locations that experience pronounced congestion.

3. Consultation with emergency management and enforcement personnel.

Trained personnel who are experienced in controlling traffic and are aware of the likely evacuation traffic patterns have extensively reviewed these control tactics.

4. Prioritization of TCPs.

Application of traffic control at some TCPs will have a more pronounced influence on expediting traffic movements than at other TCPs. For example, TCPs controlling traffic originating from areas in close proximity to the power plant could have a more beneficial effect on minimizing potential exposure to radioactivity than those TCPs located far from the power plant. Thus, during the mobilization of personnel to respond to the emergency situation, those TCPs which are assigned a higher priority, should be manned earlier. These priorities have been developed in conjunction with county emergency management representatives and law enforcement personnel.

The control tactic at each TCP is presented in each schematic that appears in Appendix G.

The use of Intelligent Transportation Systems (ITS) technologies can reduce manpower and equipment needs, while still facilitating the evacuation process. Dynamic Message Signs (DMS) can be placed within the EPZ to provide information to travelers regarding traffic conditions, route selection, and reception center information. DMS can also be placed outside of the EPZ to warn motorists to avoid using routes that may conflict with the flow of evacuees away from the nuclear power station. Highway Advisory Radio (HAR) can be used to broadcast information to evacuees en route through their vehicle stereo systems. Automated Traveler Information Systems (ATIS) can also be used to provide evacuees with information. Internet websites can provide traffic and evacuation route information before the evacuee begins his trip, while on board navigation systems (GPS units), cell phones, and pagers can be used to provide information en route. These are only several examples of how ITS technologies can benefit the evacuation process. Chapter 2I of the MUTCD presents guidance on Emergency Management signing. Specifically, the Evacuation Route sign, EM-1 on page 2I-3, with the word "Hurricane" removed, could be installed selectively within the EPZ, if considered advisable by local and state authorities. Similar comments apply to sign EM-3 which identifies TCP locations.

KLD Associates, Inc. Rev. 2

10. EVACUATION ROUTES

Evacuation routes are composed of two distinct components:

- Routing from a Protective Action Zone (PAZ) being evacuated to the boundary of the Evacuation Region and thence out of the Emergency Planning Zone (EPZ).
- Routing of evacuees from the EPZ boundary to the reception centers.

Evacuees should be routed within the EPZ in such a way as to *minimize their exposure to risk*. This primary requirement is met by routing traffic to move *away* from the location of the Calvert Cliffs Nuclear Power Plant, to the extent practicable, and by delineating evacuation routes that expedite the movement of evacuating vehicles. This latter objective is addressed by developing evacuation routes to achieve a balancing of traffic demand relative to the available highway capacity to the extent possible, subject to satisfying the primary requirement noted above. This is achieved by carefully specifying candidate destinations for all origin centroids where evacuation trips are generated, and applying the TRAD model effectively. See Appendices A-D for further discussion.

The routing of evacuees from the EPZ boundary to the reception centers should be responsive to several considerations:

- Minimize the amount of travel outside the EPZ, from the points where these routes cross the EPZ boundary, to the reception centers.
- Relate the anticipated volume of traffic destined to the reception center, to the capacity of the reception center facility.

Figure 10-1 presents a map showing the general population reception centers. The major evacuation routes for the three counties within the EPZ are presented in Figures 10-2 through 10-4.









11. SURVEILLANCE OF EVACUATION OPERATIONS

There is a need for surveillance of traffic operations during the evacuation. There is also a need to clear any blockage of roadways arising from accidents or vehicle disablement. Surveillance can take several forms.

- 1. Traffic control personnel, located at Traffic Control and Access Control points, provide fixed-point surveillance.
- 2. Ground patrols may be undertaken along well-defined paths to ensure coverage of those highways that serve as major evacuation routes.
- 3. Aerial surveillance of evacuation operations may also be conducted using helicopter or fixed-wing aircraft.
- 4. Cellular phone calls (if cellular coverage exists) from motorists may also provide direct field reports of road blockages.

These concurrent surveillance procedures are designed to provide coverage of the entire EPZ as well as the area around its periphery. It is the responsibility of the Counties to support an emergency response system that can receive messages from the field and be in a position to respond to any reported problems in a timely manner. This coverage should quickly identify, and expedite the response to any blockage caused by a disabled vehicle.

Tow Vehicles

In a low-speed traffic environment, any vehicle disablement is likely to arise due to a low-speed collision, mechanical failure or the exhaustion of its fuel supply. In any case, the disabled vehicle can be pushed onto the shoulder, thereby restoring traffic flow. Past experience in other emergencies indicates that evacuees who are leaving an area often perform activities such as pushing a disabled vehicle to the side of the road without prompting.

While the need for tow vehicles is expected to be low under the circumstances described above, it is still prudent to be prepared for such a need. Tow trucks with a supply of gasoline may be deployed at strategic locations within, or just outside, the EPZ. These locations should be selected so that:

- They permit access to key, heavily loaded, evacuation routes.
- Responding tow trucks would most likely travel counter-flow relative to evacuating traffic.

12. CONFIRMATION TIME

It is necessary to confirm that the evacuation process is effective in the sense that the public is complying with the advisory to evacuate. Although Calvert, St. Mary's and Dorchester Counties may use their own procedures for confirmation, we suggest an alternative or complementary approach.

The procedure we suggest employs a stratified random sample and a telephone survey. The size of the sample is dependent on the expected number of households that do not comply with the advisory to evacuate. We believe it is reasonable to assume, for the purpose of estimating sample size that at least 80 percent of the population within the EPZ will comply with the advisory to evacuate. On this basis, an analysis could be undertaken (see Table 12-1) to yield an estimated sample size of approximately 300.

The confirmation process should start at about 3 hours after the advisory to evacuate, which is when 90 percent of evacuees have completed their mobilization activities. At this time, virtually all evacuees will have departed on their respective trips and the local telephone system will be largely free of traffic.

As indicated in Table 12-1, approximately 7-1/2 person hours are needed to complete the telephone survey. If six people are assigned to this task, each dialing a different set of telephone exchanges (e.g., each person can be assigned a different set of Zones), then the confirmation process will extend over a time frame of about 75 minutes. Thus, the confirmation should be completed well before the evacuated area is cleared. Of course, fewer people would be needed for this survey if the Evacuation Region were only a portion of the EPZ. Use of modern automated computer controlled dialing equipment can significantly reduce the manpower requirements and the time required to undertake this type of confirmation survey.

Should the number of telephone responses (i.e., people still at home) exceed 20 percent, then the telephone survey should be repeated after an hour's interval until the confirmation process is completed.

TABLE 12-1 ESTIMATED NUMBER OF TELEPHONE CALLS REQUIRED FOR CONFIRMATION OF EVACUATION

Problem Definition

Estimate number of phone calls, n, needed to ascertain the proportion, F of households that have not evacuated.

Reference: Burstein, H., Attribute Sampling, McGraw Hill, 1971

<u>Given</u>:

No. of households plus other facilities, N, within the EPZ (est.) = 19,715 Est. proportion, F, of households that have not evacuated = 0.20 Allowable error margin, e: 0.05 Confidence level, α : 0.95 (implies A = 1.96)

Applying Table 10 of cited reference,

$$p = F + e = 0.25; q = 1 - p = 0.75$$

$$n = \frac{A^2 pq + e}{e^2} = 308$$

Finite population correction:

$$n_F = \frac{nN}{n+N-1} = 303$$

Thus, some 300 telephone calls will confirm that approximately 20 percent of the population has not evacuated. If only 10 percent of the population does not comply with the advisory to evacuate, then the required sample size, $n_F = 214$.

Est. Person Hours to complete 300 telephone calls

Assume: Time to dial using touch-tone (random selection of listed numbers): 30 seconds Time for 6 rings (no answer): 36 seconds Time for 4 rings plus short conversation: 60 sec. Interval between calls: 20 sec.

Person Hours: 300[30+20+0.8(36)+0.2(60)]/3600 = 7.6

13. <u>RECOMMENDATIONS</u>

The following recommendations are offered:

- 1. The traffic management plan should be reviewed by state and county emergency planners with local and state law enforcement agencies (See Section 9 and Appendix G). Specifically...
 - The number and locations of Traffic Control Points (TCP) and Access Control Points (ACP) should be reviewed in detail.
 - The indicated resource requirements (personnel, traffic control devices) should be reconciled with current assets.
- Intelligent Transportation Systems (ITS) such as Dynamic Message Signs (DMS), Highway Advisory Radio (HAR), Automated Traveler Information Systems (ATIS), etc. should be used to facilitate the evacuation process (See Section 9). The placement of additional signage should consider evacuation needs.
- 3. Counties should implement procedures whereby schools are contacted prior to dispatch of buses from the depots to obtain an accurate count of students needing transportation and the number of buses required (See Section 8).
- 4. Counties should work with the Department of Transportation to have equipment needed for traffic control duties mobilized in a timely manner should an evacuation be advised (See Section 9).
- 5. Counties should establish strategic locations to position tow trucks in the event of a disabled vehicle during the evacuation process (See Section 11) and should encourage gas stations to remain open during the evacuation.
- 6. Counties should establish a system to confirm that the Advisory to Evacuate is being adhered to (see the approach suggested by KLD in Section 12).
- 7. A sensitivity study was performed to measure the effect of routing some evacuees from Zone 3 (the most populated Zone within the EPZ) northbound on State Route 2/4 even though it brings evacuees closer to CCNPP. The ETE is 3 hours and 50 minutes shorter when allowing Zone 3 evacuees to travel northbound and southbound on State Route 2/4. It is recommended that evacuees from Zone 3 be advised to travel northbound or southbound on State Route 2/4 in order to evacuate the impacted area as quickly as possible. The ETE presented in Chapter 7 and Appendix J assume the routing of some residents within Zone 3 in the northbound direction along Route 2/4.
- 8. The ETE for an evacuation of the full EPZ exceeds the mobilization time (about 4 hours) by 2 hours, on average. This indicates that there is congestion within the EPZ during evacuation which prolongs the ETE. The efficient use of traffic control personnel and equipment is highly recommended to facilitate the evacuation process (See Recommendations 1 and 2).
- 9. Counties should implement procedures to accurately estimate the number of transit-dependent people within the EPZ and to develop bus routes to service those transit-dependent people (See the suggestions in Section 8).