

| COMPOUNDS MEASURED IN LAKE GRANBURY | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--------------------------|-----------------------|----------------------|-----------------------------------|---------------------|-----------------------|-----------------------|---------------------------------|------------------|------------------------------------|------------------------|-----------------------------|-----------------------------|----------------------|-------------------------------------|--------------------|--------------------|-------------------------|-------------------------|---------------------------|-----------------------|----------------------|----------------------|-----------------|------------------------|--------------------------|-------------------------|------------------------|----------------|------|
| Category | Total Alkalinity mg/L | Total Arsenic mg/L | Total Barium mg/L | Bicarbonate Alkalinity mg/L | Total Boron mg/L | Total Cadmium mg/L | Total Calcium mg/L | Carbonate Alkalinity mg/L | Chloride mg/L | Chlorophyll a mg/m ³ | Total Chromium mg/L | Fecal Coliform col/100ml | Total Coliform col/100ml | Total Copper mg/L | Hardness, CaCO ₃ mg/L | Total Iron mg/L | Total Lead mg/L | Total Magnesium mg/L | Total Manganese mg/L | Dissolved Mercury mg/L | Total Mercury mg/L | Total Nickel mg/L | Nitrate as N mg/L | Nitrite mg/L | Orthophosphate mg/L | Total Phosphorus mg/L | Total Potassium mg/L | Total Selenium mg/L | Silica mg/L | |
| (1) Criteria for Specific Metals in Water for Protection of Aquatic Life | 0.19 | 0.03 | 0.12 | 120 | 1,925 | 0.0005 | 71.7 | 5 | 296 | 40,542 | 0.03 | 152 | 5851 | 0.019 | 245 | 0.47 | 0.003 | 15.6 | 0.038 | 0.0001 | 0.0001 | 0.003 | 0.08 | 0.2 | 0.24 | 0.188 | 6.30 | 0.003 | 13.8 | |
| Human Health Criteria in Water | 0.05 | 2 | 0.05 | 1000 | 1000 | 0.05 | 0.05 | 5 | 584 | 260,000 | 0.03 | 1,100 | 25000 | 0.018 | 347 | 2.16 | 0.003 | 23.7 | 0.183 | 0.0001 | 0.0001 | 0.003 | 0.19 | 0.5 | 4.40 | 2,480 | 7.30 | 0.003 | 18.3 | |
| Screening Levels for Nutrient Parameters TSWQS for Lake Granbury | | | | | | | | | | | | | | | | | | | | | | | 0.37 | | | 0.2 | | | | |
| Values calculated from quarterly monitoring at various in-lake locations | 1.32 | 0.033 | 0.164 | 164 | 164 | 2,500 | 0.0005 | 96.7 | 584 | 260,000 | 0.03 | 1,100 | 25000 | 0.018 | 347 | 2.16 | 0.003 | 23.7 | 0.183 | 0.0001 | 0.0001 | 0.003 | 0.19 | 0.5 | 4.40 | 2,480 | 7.30 | 0.003 | 18.3 | |
| TSWQS | 1.41 | 0.033 | 0.164 | 164 | 164 | 2,500 | 0.0005 | 96.7 | 584 | 260,000 | 0.03 | 1,100 | 25000 | 0.018 | 347 | 2.16 | 0.003 | 23.7 | 0.183 | 0.0001 | 0.0001 | 0.003 | 0.19 | 0.5 | 4.40 | 2,480 | 7.30 | 0.003 | 18.3 | |
| (2) Concentration of chemicals added to the system and expected in the effluent | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | Low | |
| (3) Cycle Concentration | 317 | 0.005 | 0.268 | 268 | 268 | 4,679 | 0.0012 | 172.2 | 12 | 711 | 97,300 | 0.006 | 384 | 16442 | 0.022 | 598 | 1.12 | 0.006 | 37.4 | 0.091 | 0.0002 | 0.0002 | 0.006 | 0.20 | 0.4 | 0.58 | 0.447 | 15.13 | 0.006 | 33.1 |
| Mean concentration | 338 | 0.005 | 0.394 | 394 | 394 | 6,000 | 0.0012 | 239.3 | 12 | 1426 | 674,000 | 0.006 | 2640 | 60000 | 0.043 | 833 | 5.18 | 0.006 | 59.9 | 0.991 | 0.0002 | 0.0002 | 0.006 | 0.44 | 1.2 | 10.66 | 5,904 | 17.52 | 0.006 | 43.9 |
| Max concentration | 346 | 0.007 | 0.539 | 539 | 539 | 5,043 | 0.0013 | 189.0 | 13 | 776 | 116,219 | 0.007 | 399 | 17949 | 0.024 | 642 | 1.22 | 0.007 | 49.9 | 0.999 | 0.0003 | 0.0003 | 0.007 | 0.22 | 0.4 | 0.63 | 0.488 | 16.51 | 0.007 | 36.1 |
| Diluted Effluent at Low Flow | 369 | 0.007 | 0.430 | 430 | 430 | 6,550 | 0.0013 | 261.2 | 13 | 1566 | 681,993 | 0.007 | 2862 | 65499 | 0.047 | 919 | 5.66 | 0.007 | 62.1 | 0.627 | 0.0003 | 0.0003 | 0.007 | 0.46 | 1.3 | 11.53 | 6,445 | 19.13 | 0.007 | 47.9 |
| Diluted Effluent at Annual Mean Flow | 149 | 0.003 | 0.126 | 126 | 126 | 2,171 | 0.0006 | 80.9 | 6 | 334 | 45,737 | 0.003 | 171 | 7729 | 0.010 | 277 | 0.53 | 0.003 | 17.6 | 0.043 | 0.0001 | 0.0001 | 0.003 | 0.09 | 0.2 | 0.27 | 0.210 | 7.11 | 0.003 | 15.6 |
| Mean concentration | 159 | 0.003 | 0.185 | 185 | 185 | 2,620 | 0.0006 | 112.5 | 6 | 670 | 293,316 | 0.003 | 1241 | 28203 | 0.020 | 391 | 2.44 | 0.003 | 26.7 | 0.184 | 0.0001 | 0.0001 | 0.003 | 0.21 | 0.6 | 4.96 | 2,775 | 8.24 | 0.003 | 20.6 |
| Max concentration | 163 | 0.003 | 0.185 | 185 | 185 | 2,620 | 0.0006 | 112.5 | 6 | 670 | 293,316 | 0.003 | 1241 | 28203 | 0.020 | 391 | 2.44 | 0.003 | 26.7 | 0.184 | 0.0001 | 0.0001 | 0.003 | 0.21 | 0.6 | 4.96 | 2,775 | 8.24 | 0.003 | 20.6 |

cfu = cubic feet per second
 Lake = lakes per second
 CRPP = Comanche Peak Nuclear Power Plant
 Standard = Texas Surface Water Quality Standard
 TSWQS = Texas Surface Water Quality Standard

MEAN and MAX Concentrations - Calculated based on quarterly monitoring data from Lake Granbury. The mean and maximum concentrations were calculated for each analyte, based on the screening level, whichever was greater, was used in calculating the mean and max concentration for each analyte, based on Draft 2008 Guidance for Assessing and Reporting Surface Water Quality in Texas (December 21, 2007) (pg 37).

ADDITIVE - chemicals that will be added to systems and will not undergo cycle concentration. Additives with chemical concentrations estimated to be below the detection limit were reported at the detection limit. Additives that are added intermittently are not included in the dilution calculation.

EC = (ppm) x (ft) + Mean/Max Concentration
 (1) Screening Levels Used as the Primary Screening Level.
 (2) Concentration of additives are not increased by the number of cycles.
 (3) The Max or Min analyte for each cycle is increased by the number of cycles.
 (4) Analyte flow is increased by TDS/SS input.
 (5) Analyte flow is increased by TDS/SS input.

Equation for Diluted Effluent Concentration
 Cycle Mean/Max Concentration * FDP
 EC = (ppm) x (ft) + Mean/Max Concentration
 (1) Screening Levels Used as the Primary Screening Level.
 (2) Concentration of additives are not increased by the number of cycles.
 (3) The Max or Min analyte for each cycle is increased by the number of cycles.
 (4) Analyte flow is increased by TDS/SS input.
 (5) Analyte flow is increased by TDS/SS input.

This is not intended to be a scientific model after discharge into Lake Granbury and does not account for fate and transport processes.
HIGHLIGHTED ANALYTES REPRESENT AN EXCEEDENCE OF THE CORRESPONDING REGULATORY LEVEL.

For Screening Level:
 The default screening level used was the Aquatic Life Criteria or TSWQS Criteria. If neither was provided, the default screening level was the Human Health Criteria. Parameters criteria was not provided then the Human Health Criteria was used or the TSWQS criteria.

| | |
|----------------------------|-----------|
| # Cycle Concentration | 24 |
| Flow Rate (FR) | 28 cfs |
| Plant Discharge Rate (PDR) | 26100 gpm |
| Flow Rate (FR) | 28 cfs |
| Plant Discharge Rate (PDR) | 26100 gpm |
| Flow Rate (FR) | 1931 cfs |
| Plant Discharge Rate (PDR) | 26100 gpm |
| Flow Rate (FR) | 1931 cfs |
| Plant Discharge Rate (PDR) | 26100 gpm |
| Flow Rate (FR) | 1931 cfs |

Editable Cell

REFERENCES:
 Guidance for Assessing and Reporting Surface Water Quality in Texas, March 19, 2008
 Texas Surface Water Quality Standards, April 30, 1997

| Category | OTHER POTENTIAL DISCHARGE COMPOUNDS (see note below) | | | | | | | | | | | | | | | | | | | |
|---|--|----------------------|---------------------------------|-----------------|---------------------------|------------------------|------------------|--------------------|----------------|-----------------------|----------------------|----------------------------|--|----------------------------------|--------------------------------|--------------------------------|--------------------------|-------|----------------------|--|
| | Total Silver mg/L | Total Sodium mg/L | Fecal Streptococci col/100mL | Sulfate mg/L | Total Dissolved Solids | Total Nitrogen mg/L | Turbidity NTU | Total Zinc mg/L | Sodium mg/L | pH/Ls adjuster ppm | Sulfuric acid ppm | Corrosion Inhibitor ppm | Orthophosphate & Proprietary ppm | Biological Oxygen Demand mg/L | Chemical Oxygen Demand mg/L | Total Suspended Solids mg/L | Ammonia Nitrogen mg/L | pH | Temperature deg C | |
| (1) Criteria for Specific Metals in Water for Protection of Aquatic Life | | | | | | | | | | | | | | | | | | | | |
| Human Health Criteria in Water | | | | | | | | | | | | | | | | | | | | |
| Screening Levels for Nutrient Parameters | | | | | | | | | | | | | | | | | | | | |
| TSWQS for Lake Granbury | | | | | | | | | | | | | | | | | | | | |
| TSWQS for Lake Granbury | | | | | | | | | | | | | | | | | | | | |
| Values calculated from quarterly monitoring at stations in Lake Granbury | 0.001 | 195 | 7 | 121.8 | 107 | 0.490 | 42.3 | 0.012 | | | | | 145 | 24.0 | 54.7 | 0.149 | 8.03 | 83.71 | | |
| Mean Concentration | 0.001 | 368 | 80 | 232.0 | 1010 | 0.920 | 350.0 | 0.024 | | | | | 77 | 65.0 | 672.0 | 0.520 | 8.44 | 83.78 | | |
| Max Concentration | | | | | | | | | | | | | | | | | | | | |
| (2) Concentration of chemicals added to the system and expected in the effluent | | | | | | | | | | | | | | | | | | | | |
| Low | | | | | | | | | | | | | | | | | | | | |
| High | | | | | | | | | | | | | | | | | | | | |
| 2.4 - Cycle Concentration (1) | | | | | | | | | | | | | | | | | | | | |
| Mean concentration | 0.001 | 467 | 18 | 291.8 | 2429 | 1.177 | 101.6 | 0.029 | | | | | | | | | | | | |
| Max concentration | 0.001 | 893 | 192 | 596.8 | 18924 | 2.208 | 840.0 | 0.058 | | | | | | | | | | | | |
| Diluted Effluent at Low Flow | 0.001 | 510 | 20 | 378.8 | 2952 | 1.285 | 110.8 | 0.052 | 0.135 | 1.48498 | | | | | | | | | | |
| Max concentration | 0.001 | 964 | 210 | 607.8 | 18386 | 2.410 | 917.0 | 0.063 | 0.135 | 1.48498 | | | | | | | | | | |
| Diluted Effluent at Annual Mean Flow | 0.001 | 220 | 8 | 137.2 | 1142 | 0.553 | 47.8 | 0.014 | 0.01068 | 0.11746 | | | | | | | | | | |
| Max concentration | 0.001 | 415 | 90 | 281.7 | 7068 | 1.038 | 394.8 | 0.027 | 0.01068 | 0.11746 | | | | | | | | | | |

These chemicals are not considered to increase by the number of cycles and will be affected by the chemicals added to the system.

ft³ = cubic feet per second
 L/sec = liters per second
 CRPP = Comanche Peak Nuclear Power Plant
 TSWQS = Texas Surface Water Quality Standard

MEAN and MAX Concentrations - Calculated based on quarterly monitoring data from Lake Granbury. Mean and max concentrations are calculated based on the screening level, whichever was greater, was used in calculating the mean and max concentration for each analyte, based on Draft 2008 Guidance for Assessing and Reporting Surface Water Quality in Texas (December 21, 2007) (pg 37).

ADDITIVE - chemicals that will be added to system(s) and will not undergo cycle concentration. Additives with chemical concentrations estimated to be below the detection limit were reported at the detection limit. Additives that are added intermittently are not included in the dilution calculation.

--- = Not evaluated for that compound

Notes:

- (1) Screening Levels Used as the Primary Screening Level.
- (2) Concentration of additives are not increased by the number of cycles.
- (3) The Max or Max analyte by TDS50 is used in the calculation of the Diluted Effluent Concentration.
- (4) Analyte not analyzed by TDS50 is marked as ---.

Equation for Diluted Effluent Concentration

$$EC = \frac{C_{additive} \times V_{additive}}{C_{flow} \times V_{flow}} + \text{Mean/Max Concentration}$$

This is not intended to be a scientific model after discharge into Lake Granbury and does not account for fate and transport processes.

HIGHLIGHTED ANALYTES REPRESENT AN EXCEEDED OF THE CORRESPONDING REGULATORY LEVEL.

For Screening Level:
 The default screening level used was the Aquatic Life Criteria or TSWQS Criteria. If neither was provided, the Human Health Criteria was used. The Human Health Criteria was used for the TDS50 criteria was not provided then the Human Health Criteria was used or the TDS50 criteria.

| | |
|----------------------------|---------------|
| # Cycle Concentration | 2.4 |
| Flow Rate (FR) | 281.94 |
| Plant Discharge Rate (PDR) | 26100 gpm |
| Flow Rate (FR) | 28 |
| Plant Discharge Rate (PDR) | 1646.65 L/sec |
| Flow Rate (FR) | 28 |
| Plant Discharge Rate (PDR) | 1646.65 L/sec |
| Flow Rate (FR) | 1931 |
| Plant Discharge Rate (PDR) | 28194.67 |

Editable Call

REFERENCES:

Guidance for Assessing and Reporting Surface Water Quality in Texas, March

Texas Surface Water Quality Standards, April 30, 1997