

4.5.2 Groundwater Impacts

Potential environmental impacts to groundwater at the Nichols Ranch and Hank site may occur during all phases of the ISR facility's lifecycle, but primarily during operations and aquifer restoration.

ISR activities can impact aquifers at varying depths (separated by aquitards) above and below the uranium-bearing aquifer as well as adjacent surrounding aquifers in the vicinity of the uranium-bearing aquifer. Surface or near-surface activities that can introduce contaminants into soils are more likely to impact shallow aquifers while ISR operations and aquifer restoration will likely impact the deeper uranium-bearing aquifer, and potentially impact any aquifers above and below, and adjacent surrounding aquifers.

ISR facility impacts to groundwater resources can occur from surface spills and leaks, releases from shallow surface piping, consumptive water use, horizontal and vertical excursions of leaching solutions from production aquifers, degradation of water quality from changes in the production aquifer's chemistry, and waste management practices involving land application, evaporation ponds, or deep well injection. Detailed discussion of the potential impacts to groundwater resources from construction, operations, aquifer restoration, and decommissioning are provided in the following sections.

4.5.3.1 Alternative A (Proposed Action)

4.5.3.1.1 Construction Impacts to Groundwater

The GEIS (Section 4.3.4.2.1; NRC, 2009a) indicates that during construction of ISR facilities, the potential for groundwater impacts is primarily from consumptive groundwater use, introduction of drilling fluids and muds from well drilling, and spills of fuels and lubricants from construction equipment.

Groundwater use during construction is limited to routine activities such as dust suppression, mixing cements, and drilling support. The amounts of groundwater used in these activities are small relative to available water and potentially could have a SMALL adverse and temporary impact to groundwater supplies within the Nichols Ranch ISR Project. Even in instances where the water-table aquifer is shallow, groundwater quality of near-surface aquifers during construction would be protected by BMPs such as implementation of a spill prevention and cleanup plan to minimize soil contamination. Additionally, the amount of drilling fluids and muds introduced into aquifers during well construction would be limited and have a SMALL adverse impact to the water quality of those aquifers. Thus, construction impacts to groundwater resources would be SMALL based on the limited nature of construction activities and implementation of management practices to protect shallow groundwater. (Paul's alternative: Impacts during the construction phase of ISR facilities are considered SMALL and surficial in nature (i.e., restricted to surface soils and vegetation). Impacts to the groundwater quality of shallow water-table aquifers are expected to be SMALL and are related to the limited amounts of

Deleted: (near-surface)

Deleted: are more likely to

Deleted: ¶

According to the CEQ, the significance of impacts is determined by examining both context and intensity (40 CFR 1508.27). Context is related to the affected region, the affected interests, and the locality, while intensity refers to the severity of the impact, which is based on a number of considerations. In describing the significance of potential impacts in this EA, the following significance levels for groundwater impacts have been identified: ¶

¶

SMALL: Impacts (chemical, radiological, and/or hydraulic) on groundwater would not be detectable or so minor as not to alter groundwater quality or water levels in any meaningful way. ¶

MODERATE: Impacts (chemical, radiological, and/or hydraulic) would be detectable but would not adversely impact the current or potential future uses of groundwater in the area. ¶

LARGE: Chemical, radiological, and/or hydraulic impacts would be readily detectable and would result in potentially significant adverse impacts on the current or potential future uses of groundwater in the area. ¶

4.5.3.1 Alternative A (No-Action)¶

The No-Action Alternative would result in no construction or operational activities on site that might impact shallow groundwater. This alternative also would not require the injection of lixiviant into the production aquifer or the consumptive use of groundwater. The disposal of waste liquids and solids would no longer be necessary and therefore would pose no threat to groundwater quality. Consequently, Alternative A would result in no impacts to groundwater. ¶

Deleted: 2

Deleted: B

Deleted: 2

Deleted: G

C/12

drilling fluids and muds used during well construction activities.) (Allen's alternative for Lost Creek : 4.5.3.2.1 Construction Impacts to Groundwater

As indicated in the GEIS (Section 4.3.4.2.1), potential impacts to groundwater during construction is primarily from consumptive use of groundwater, injection of drilling fluids and muds during well drilling, and spills of fuels and lubricants from construction equipment. During the construction of the wellfields and facility at Lost Creek, potential impacts to groundwater could occur from the consumptive use of groundwater, introduction of drilling fluids and muds into the environment during well installation, discharge of pumped water to the surface during hydrologic testing and surface spills of fuels and lubricants.

The consumptive water use during construction at the Lost Creek site would be generally limited to dust control, drilling support, and cement mixing. Most water used for construction at the Lost Creek project would be extracted from a well completed in the FG horizon. The sands in this horizon constitute an aquifer unit located at depths from 55 to 107 m (180 to 350 ft) below surface, which are hydrologically separated from the HJ production sand and DE surficial aquifer. The consumptive water use during construction is expected to be small and temporary relative to the water supply available in the FG Sands.

The volume of drilling fluids and muds used during well installation is expected to be limited and best management practices would be applied to prevent, identify and correct impacts to soils and the surficial DE aquifer at Lost Creek. Drilling fluids and muds would be placed into mud pits to control the spread of the fluids, to minimize the area of soil contamination and to enhance evaporation. According to the site potentiometric data, the depth to the water table in the surficial DE aquifer at Lost Creek ranges from 24 to 46 m (80 to 150 ft) below ground surface and a low permeability BC horizon overlies the DE horizon. Therefore any small amount of leakage from the pits or spills from drilling activities should result in only a small amount of infiltration and not cause noticeable changes in the DE surficial aquifer water quality. The introduction of drilling fluids to the DE, FG, and HJ aquifers may occur during drilling of production wells and monitoring wells, but is expected to be minimal, as drilling muds are designed to seal the hole so that casing may be set.

As wells are installed, some water may be pumped from aquifers for hydrologic tests such as pumping tests. This water would be discharged to the surface in accordance with approved permits from the State of Wyoming that the applicant would obtain prior to any release. The surface discharge permits protect near surface aquifers by limiting the discharge volume and prescribing concentration limits to waters that can be discharged.

During all construction operations at Lost Creek, the groundwater quality of near surface aquifers would further be protected if best management practices are employed during facility construction and wellfield installation. The volume of fuels and lubricants to be kept in the license area during construction is usually small and minor leaks or spills would not be expected to contaminate the groundwater.

Based on this analysis, consumptive groundwater use during the construction phase is limited and is expected to have a SMALL and temporary impact. The impacts to soil and groundwater resources during wellfield and facility construction would be SMALL based on the limited nature

of construction activities and implementation of best management practices to protect soils and shallow groundwater.)

Deleted: 2

4.5.3.1.2 Operation Impacts to Groundwater

As indicated in Section 4.3.4.2.2 of the GEIS, during ISR operations, potential environmental impacts to shallow (near-surface) aquifers are related to leaks of lixiviant from pipelines, wells, or header houses and to waste management practices such as the use of evaporation ponds and disposal of treated wastewater by land application. In Alternative A, deep well injection is proposed as the liquid waste disposal method; therefore, impacts associated with this action should be minimal. Potential environmental impacts to groundwater resources in the production and surrounding aquifers also include consumptive water use and changes to water quality. Water quality changes would result from normal operations in the production aquifer and from possible horizontal and vertical lixiviant excursions beyond the production zone. Disposal of processing wastes by deep well injection during ISR operations also can potentially impact groundwater resources (NRC, 2009a).

Deleted: B

Deleted: 2

4.5.3.1.2.1 Operation Impacts to Shallow (Near-Surface) Aquifers

The GEIS (Section 4.3.4.2.2.1; NRC, 2009a) discusses the potential impacts to shallow aquifers during ISR operations. A network of buried pipelines is used during ISR operations for transporting lixiviant between the pump house and the satellite or main processing facility and also to connect injection and extraction wells to manifolds inside the pumping header houses. The failure of pipeline fittings or valves, or failures of well mechanical integrity in shallow aquifers could result in leaks and spills of pregnant and barren lixiviant which could impact water quality in shallow aquifers. The potential environmental impact of such pipeline, valve, well integrity failure, or pond leakage depends on a number of factors, including the depth to shallow groundwater, the use of shallow groundwater, and the degree of hydraulic connection of shallow aquifers to regionally important aquifers. As indicated in the GEIS, potential environment impacts could be MODERATE to LARGE if 1) the groundwater in shallow aquifers is close to the ground surface, 2) the shallow aquifers are important sources for local domestic or agricultural water supplies, or 3) shallow aquifers are hydraulically connected to other locally or regionally important aquifers.

As previously discussed in Section 3.4.1 and 3.5.3, the Wasatch Formation outcrops in the project area and is characterized by a series of sand layers separated by mudstones and siltstones. The more permeable sand layers serve as aquifers in this area. The applicant has identified a series of sand layers in the upper portion of Wasatch Formation present in the project area and have labeled these layers from the shallowest to the deepest as the H, G, F, C, B, A, and 1 Sands. While generally present throughout the project area, the nature and extent of these sands differ somewhat across the project area from the Nichols Ranch Unit to the Hank Unit. In addition, depth and expression of these sands at the ground surface is influenced by the topographical relief of the project area.

The depth at which groundwater is first encountered across the Nichols Ranch unit varies and depends on surface topography. The specific sand that acts as the surficial aquifer similarly varies across the project area depending on the outcropping of these sands and the surface topography. Limited groundwater level data is available to define depth to shallow groundwater across the Nichols Ranch Unit area, and additional wells are planned to better define shallow groundwater levels in this area. However, based on available data and extrapolation of sand units across the site, the applicant has estimated the depth to shallow groundwater and the sand layer acting as the surficial aquifer across the Nichols Ranch Unit area. In the southern portion of the Nichols Unit area, shallow groundwater is first encountered in the Cottonwood alluvium and has been shown to within 3 m (10 ft) of the ground surface. Moving north from the Cottonwood alluvium, shallow groundwater is first encountered in the F aquifer at depths ranging from 15 to 30 m (50 to 100 ft). However, in the northernmost portion of the Nichols Ranch Unit area, the G sand is likely to be the shallow aquifer, with depth to groundwater ranging between 30 to 60 m (100 to 200 ft). Groundwater flow in the F and G Sands is projected to be in a westerly direction.

Deleted: site

Thus, the depth to shallow groundwater in the southern portion of the Nichols Ranch Unit is limited. Data indicate that the depth to groundwater in the general area of the proposed processing plant is about 15 m (50 ft) and portions of the projected production zone extend to the area adjacent to the Cottonwood Creek alluvium, where groundwater may be as shallow as 3 m (10 ft). This limited unsaturated zone offers a limited buffer to absorbed and attenuate any releases at the ground surface. Moreover, shallow groundwater likely flows to Cottonwood Creek alluvium, and if left unchecked, shallow groundwater contamination could migrate into and along this alluvial material to the west. The groundwater quality data for the F Sand indicate that groundwater in this unit has relatively high TDS, but appears suitable for stock watering in many areas (Wyoming Class III groundwater). The well survey provided by the applicant indicates that there are a number of stock watering well within a half-mile radius of the project area. While it is uncertain how many of these wells are screened in the shallow aquifer, some of these wells may be potentially impacted by releases at the ground surface that migrate downgradient to the west.

Deleted: only

Deleted: 1

Depth to shallow groundwater at the Hank Unit Area is similarly uncertain, and the installation of additional wells are planned to identify shallow water levels in the Hank Unit area. However, the applicant has indicated that the H Sand should be the surficial aquifer in this area, with depth to groundwater ranging between 15m (50 ft) in the low lying areas to the west of the Hank Unit area to 61 m (200 ft) along the eastern border of the Hank Unit area. Groundwater flow in the H Sand at the Hank Unit is expected to flow in a westerly direction. The Willow and Dry Willow Creek alluvial materials in the Hank Unit area are not expected to contain water except during short periods of time after runoff events.

Deleted: Thus, potential environmental impact to shallow groundwater during operation at the Nichols Ranch Unit appears to be MODERATE to LARGE.¶

The depth to shallow groundwater appears somewhat greater at the Hank Unit than the Nichols Ranch Unit. There is generally a 30 m (100 ft) or more separation from the ground surface to shallow water beneath most of the production zone and planned processing facility. However, the southern portion of the ore body extends into an area where shallow water is projected to be within 15 m (50 ft) of the surface. Water quality data from the H sand indicates that this unit is suitable for agricultural uses (Wyoming Class II groundwater). The well survey provided by the

Deleted: Thus, t

Deleted: the groundwater quality in

Deleted: relatively good and

Deleted: multiple

Deleted: purposes

applicant indicates that there are a number of stock watering wells within a half-mile radius of the project area. It is uncertain how many of these wells are screened in the shallow aquifer. However, the H Sand lies over the shallow F Sand which is the production zone in the Hank Unit. Those wells in close vicinity to the site that are screened in the H Sand are also likely screened in the F Sand as well. The applicant has indicated that wells screened across the F Sand in the vicinity of the Hank will be abandoned. Thus, wells using shallow groundwater from the H Sand will likely be abandoned and will not be directly impacted by releases at the surface.

Formatted: Highlight

Deleted: Regardless, due to the shallow depth to groundwater in the southern portion of the Hank Unit area and relatively good groundwater quality in the shallow aquifer, the potential impact to shallow groundwater at the Hank Unit appears to be MODERATE.

As indicated by the GEIS, any potential impact of releases at or near the ground surface on shallow groundwater can be greatly reduced by leak detection programs required by the NRC. The applicant plans an aggressive leak detection (Section 7.5.3.1 of the TR, Uranerz 2008b) and spill cleanup program (Section 4.4 of the TR, Uranerz 2008b). In addition, preventative measures such as well mechanical integrity testing (Section 3.4.6 of the TR, Uranerz 2008b) would limit the likelihood of well integrity failure during operations. Without these mitigating measures, the resultant impact to the shallow aquifer could potentially be LARGE; however, the implementation of these measures should mitigate the potential impact (i.e., early detection and cleanup) and result in MODERATE potential operational impacts to shallow (near surface) aquifers for the Nichols Ranch and Hank Units.

Deleted: w

Deleted: would

Deleted: 2

4.5.3.1.2.2 Operation Impacts to Production and Surrounding Aquifers

The potential environmental impacts to groundwater supplies in the production and other surrounding aquifers are related to consumptive water use and groundwater quality.

Water Consumptive Use: As discussed in the GEIS (Section 4.2.4.2.2.2), groundwater is withdrawn and reinjected into the production zone during ISR operations. Most of the water withdrawn from the aquifer is returned to the aquifer. The portion that is not returned to the aquifer is referred to as consumptive use. The consumptive use is due primarily to production bleed and also includes other smaller losses. The production bleed is the net withdrawal maintained to ensure groundwater gradients toward the production network. This net withdrawal ensures there is an inflow of groundwater into the well field to minimize the potential movement of lixiviant and its associated contaminants out of the well field.

Consumptive water use during ISR operations could potentially impact a local water user who uses water from the production aquifer outside the exempted zone. This potential impact would result from lowering the water levels in nearby wells, thereby reducing the yield of these wells. In addition, if the production zone is hydraulically connected to other aquifers above and/or below the water zone, consumptive use may potentially impact the water levels in these overlying and underlying aquifers and reduce the yield in any nearby wells withdrawing water from these aquifers.

Deleted: is

Deleted: and

The applicant has provided predicted drawdowns created by production bleed during mine operation (Addendum 7A of the TR, Uranerz, 2008b). These predictions are based on a simple analytical model and relied on aquifer properties determined during aquifer testing or assumed based on local conditions. Based on an assumed production rate of 13,250 Lpm (3,500 gpm)

Deleted: ions

and a 1 percent bleed rate, a groundwater withdrawal rate of 133 Lpm (35 gpm) was used to predict drawdowns at the Nichols Ranch Unit. The drawdowns resulting from at this pumping rate were predicting using the aquifer properties of 4,350 L/day/m (350 gal/day/ft) for transmissivity and a storage coefficient of 1.8×10^{-4} . Simulations were conducted to evaluate the drawdowns resulting from concentrated drawdowns distributed at various locations in the projected wellfields. These predictions show that 9 m (30 ft) of the drawdown will extend 2,134 m (7,000 ft) outward from the center of the wellfields. The 1.5 m (5 ft) contour is projected to extend out 6,858 m (22,500 ft) or approximately 6.4 km (4 mi) from the Nichols Ranch ISR Project area.

Deleted: (PM has looked into this and discovered that wells in the affected environment generally have sufficient head (e.g., 100's of feet of water) such that this drawdown from the mine operations would not significantly impact water availability.)

Deleted:

The applicant has indicated that the primary effect of the drawdowns caused by the Nichols Ranch bleed should be limited to those wells that are located in the ore zone (A Sand) Unit (May 8, 2009 Response to Environmental RAIs, LU-1 ER Section 3.1.2). This conclusion is based on the assumption that the A Sand is well-confined and there would be little leakage from the underlying or overlying sands into the A Sand. The applicant has further indicated that the predicted drawdowns should not greatly impact production from pumping wells since, in the confined A Sand, there is a large amount of potential drawdown available. As discussed in Section 3.5.3.1.4, inspection of WSEO well data for wells within 3 miles of the Nichols Ranch site indicates an average of about 446 feet in available hydraulic head. Despite the significant amount of available head, flowing wells (i.e., those wells with a potentiometric surface above the ground surface) in the Nichols Ranch Unit area may cease flowing due to the predicted drawdowns. The applicant has indicated in Drawing, Exhibit 4-3 Nichols Ranch ISR Project "A" Sand Drawdown and Free Flowing Wells that flowing wells within the 3 m (10 ft) drawdown contour may be impacted and has identified a total of 10 wells within an 8 km (5 mi) radius that are flowing wells and screened within the A Sand. A pump or other supplement may have to be installed in a flowing well if the drawdowns cause it to cease flowing.

Deleted: The applicant has indicated that

Deleted: . A pump may have to be installed in a flowing well if the drawdowns cause it to cease flowing. The applicant

In addition to the drawdown in the A Sand, pumping of the A Sand may induce leakage from the overlying and/or underlying aquifers. Such leakage may occur in areas where the intervening aquitards are not extensive or where they are compromised by wells screened over multiple aquifers or inadequately sealed wells or boreholes are present. The result of such leakage across confining beds would produce drawdowns in these adjacent beds; however, aquifer testing at the Nichols Ranch has not indicated leakage from either the overlying B Sand or the underlying 1 Sand. Add words on multiwell pump tests. Even if leakage from under- or overlying units were to occur in off-site areas, these drawdowns are expected to a fraction of the drawdowns experienced in the A Sand. Thus, the potential short-term impact due to consumptive use at the Nichols Ranch Unit during the production phase is considered MODERATE.

Deleted: While the applicant has limited the impact to those wells screened in the A Sand, there may be some

Deleted: .

Deleted: LARGE

The net consumptive use of water at the Nichols Ranch Unit during the operational phase (production and restoration) is a small fraction of the water currently stored in the A Sand in the Powder River Basin. After production and restoration are complete and groundwater withdrawals are terminated at the Nichols Ranch Unit, groundwater levels will tend to recover with time. Thus, the potential long-term (approximately 10 years) environmental impact from consumptive use during the operational phase at Nichols Ranch Unit is considered SMALL.

Deleted: i

Deleted: However, the recharge in this area is limited and recovery may be slow.

Deleted: remains MODERATE to LARGE

The applicant has similarly provided predictions of drawdowns created by production bleed in the F Sand at the Hank Unit. Based on an assumed production rate of 9,470 Lpm (2,500 gpm) and a 3 percent bleed rate, a groundwater withdrawal rate of 284 Lpm (75 gpm) was used to predict drawdowns at the Hank Unit. The drawdowns resulting from this pumping rate were predicted using the aquifer properties of 400 gal/day/ft for transmissivity and a storage value of 0.05 for the unconfined F Sand. Simulations were conducted by assuming 284 Lpm (75 gpm) distributed over 6 locations in the northern well field for 1.5 years followed by a second set of six withdrawals in the southern wellfield for the remaining 1.5 years. The predictions indicate that drawdowns of 3 m (10 ft) will extend out only to area immediately adjacent to the southern wellfield, while the drawdowns of 1.5 m (5 ft) will extent out approximately 274 m (900 ft) from the well field. The reduced drawdowns observed in the F Sand at the Hank unit are due to the unconfined nature of the aquifer. Aquifer testing at the Hank unit has not indicated leakage from either the overlying G Sand or the underlying B Sand. ~~Ref?~~ No flowing wells have been identified in the F Sand in this area. In addition, the applicant states that any wells screened in the F Sand in the area immediately adjacent to the Hank unit area will need to be abandoned due to their close proximity to the production zone using acceptable WDEQ methods or will be used as monitoring wells in not completed in multiple sands. Thus, the potential environmental impact due to consumptive use of groundwater at the Hank Unit during the production phase is likely to be SMALL.

Formatted: Highlight

Formatted: Highlight

Formatted: Highlight

The net consumptive use of water at the Hank Unit during the operational phase (production and restoration) is a small fraction of the water currently stored in the F Sand in the Powder River Basin. After production and restoration are complete and groundwater withdrawals are terminated at the Hank Unit, groundwater levels will tend to recover with time. Thus, the potential long-term (approximately 10 years) environmental impact from consumptive use during the operational phase at Hank Unit is considered SMALL.

Deleted: ¶

Excursions and Groundwater Quality: As discussed in the GEIS, groundwater quality in the production zone is degraded as part of ISR operations. The portion of the production aquifer used for production must be exempted as an underground source of drinking water through the Wyoming UIC program. After production is completed, the licensee is required to initiate aquifer restoration activities to restore the production zone to baseline or pre-operational class-of-use conditions, if possible. If the aquifer cannot be returned to preoperational conditions, NRC requires that the production aquifer be returned to the maximum contaminant levels (MCLs) provided in Table 5C of 10 CFR 40 Appendix A or to Alternate Concentrations Limits (ACL) approved by NRC.

Deleted: As described in the Groundwater section of the Affected Environment chapter, Wyoming water standards are based on Class of Use.

Deleted: . From SER, at

Deleted:

Deleted: B and A

Deleted: s

Formatted: Font: 11 pt

Deleted: are categorized as Class VI (i.e., not suitable for drinking water, livestock or agricultural), the 1 sand aquifer is Class I, drinking water.

Current groundwater compositions at Nichols Ranch and Hank generally constrain the use of the groundwater for drinking water, agriculture or livestock use. In the Nichols Ranch area, the A, B, and C Sand aquifers contain water whose compositions (primarily for Ra226) exceed the Wyoming Ground Water Quality Class 1 (domestic use), Class II (agriculture use), and Class III (suitable for livestock) standards. In contrast, the deeper 1 Sand aquifer meets Wyoming's Class I standard. Based on cross-sections, the applicant shows the 1 Sand to be very discontinuous and thin. Consequently, the 1 Sand is not expected to be used as source of drinking water. Multi-well pump tests performed by the applicant displayed no response in the 1 Sand when the A Sand was pumped at MN-1 and MN-2. The ambient hydraulic head in A Sand is approximately 50 feet higher than 1 Sand. This head difference can suggest the degree of confinement of the production zone. If the aquitard separating the two aquifers were leaky, the head difference would be smaller. At Hank unit, the

G sand meets Wyoming's Class II standard (suitable for agriculture), while both the F Sand and underlying B and C Sands exceed Wyoming's standards for drinking water, agriculture or livestock use. Based on the generally poor preexisting water quality in both the Nichols Ranch and Hank unit areas, and the expected restoration of the production zones at both units, potential impacts to the water quality of the uranium-bearing production zone aquifer as a result of ISR operations would generally be expected to be SMALL and temporary.

To prevent horizontal excursions, inward hydraulic gradients are expected to be maintained in the production aquifer during ISR operations. These inward hydraulic gradients are created by the net groundwater withdrawals (production bleeds) maintained through continued pumping during ISR operations. Groundwater flows in response to these inward hydraulic gradients, thus ensuring that groundwater flow is toward the production zone. This inward groundwater flow toward the extraction wells prevents horizontal excursions of leaching solutions away from the production zone ([Section 3.4.8; Uranerz, 2008b](#)).

The NRC also requires the licensee to take preventive measures to reduce the likelihood and consequences of potential excursions. A ring of monitoring wells within and encircling the production zone is required for early detection of horizontal excursions. [The applicant's groundwater monitoring program is detailed in Section 5.7.8 of the TR \(Uranerz 2008b\)](#). If excursions are detected, corrective actions are required outside of the exempted portion of the production aquifer.

Vertical excursions may also potentially occur into aquifers overlying or underlying the production zone aquifer. As analysis presented in the GEIS indicates, the potential for migration of leaching solution into an overlying or underlying aquifer is small if the thickness of the aquitard separating the production zone from the overlying and underlying is sufficient and the permeability of the aquitard is low. Steep hydraulic gradients in which the hydraulic head of the production zone exceeds that of the overlying or underlying aquifers also can lead to vertical excursions. Vertical excursions can also occur due to improperly sealed boreholes, to poorly completed wells, or to a loss of mechanical integrity of ISL injection and extraction wells. To ensure the detection of vertical excursions, the NRC also requires monitoring in the overlying and underlying aquifers ([Section 5.7.1.3.1; Uranerz 2008b](#)). A program of mechanical integrity testing of all ISL wells is also required ([Section 3.4.6; Uranerz 2008b](#)). Corrective action is required if any vertical excursions are detected ([Section 5.7.8.10.3; Uranerz 2008b](#)).

The hydrogeologic conditions found in the ore-bearing A Sand at the Nichols Ranch Unit are generally similar to those found at other successful ISR facilities. Groundwater in the A Sand is confined and there is sufficient hydraulic conductivity to allow ISR mining. The drawdown created by pumping in the production zone should facilitate containment of the lixiviant in the mining zone and allow the recovery of any horizontal or vertical excursions, should they occur. The overlying BA Aquitard and underlying A1 Aquitard appear thick and extensive and should confine the lixiviant to the A Sand. Pumping tests conducted to date indicate no potential hydraulic connection between the A Sand and the overlying or underlying sands. Each mine unit will undergo further extensive testing during the Mine Unit Test required before initiating solution mine in each mine unit. The results of this further testing will be provided in the Mine Unit Data Packages, which will be reviewed and approved by the NRC. Therefore, the potential environmental impact to groundwater quality is considered SMALL at the Nichols Ranch Unit.

Deleted: is
Deleted: ,
Deleted:
Deleted: s
Deleted: is Class VI,
Deleted: underlying
Deleted: is Class VI (not suitable for
Deleted:)
Deleted:
Deleted: If the aquifer cannot be returned to preoperational conditions, NRC requires that the production aquifer be returned to the maximum contaminant levels (MCLs) provided in Table 5C of 10 CFR 40 Appendix A or to Alternate Concentrations Limits (ACL) approved by NRC. For these reasons,
Deleted: ¶

Deleted: u
Deleted: The uranium concentration in the groundwater in the A Sand is only 0.027 mg/L, less than typical of an ore-bearing aquifer; however,
Deleted: . The applicant(?) suggests that
Deleted: this may be the
Deleted: is a
Deleted: result of the A Sand well screens extending over the entire aquifer thickness
Deleted: sand
Deleted: and not limited to the ore zone. An ore zone of limited vertical extent could affect the efficiency of the extraction process, requiring larger volumes of water.

The occurrence of unconfined conditions in the production zone at the Hank Unit presents special considerations when evaluating the maintenance of the necessary inward hydraulic gradient, the reliability of monitoring around the periphery of the well field, and the capability of reversing any potential horizontal excursion by drawing the lixiviant back into the producing well. These issues result primarily from the limited drawdown that occurs in an unconfined aquifer. However, as in ISR operations in confined aquifers, Mine Unit Data Packages containing the results of aquifer testing throughout the production zone will be required to verify that hydraulic control of the production zone can be maintained with the planned production bleed. These tests must also demonstrate that hydraulic control reaches out to the proposed monitoring ring and that sufficient drawdown is available to pull back any horizontal or vertical excursion that might occur. Therefore, the potential environmental impact to groundwater quality from excursions at the Hank Unit is considered SMALL.

Deleted: an

Deleted: A

Deleted: involving multiple wells distributed

Deleted: is generally necessary

Deleted: The unsaturated conditions overlying the ore-bearing deposits also present special concerns. Normally, the production zone in an ISR project remains fully saturated and under pressure. However, in unconfined conditions such as those found at the Hank Unit, there is the potential that the oxidants injected into the production zone may volatilize and create a vapor lock. These issues are still being evaluated as part of the concurrent safety review and are the subject of ongoing discussions with the applicant. Pending the resolution of these issues, potential environmental impact due to changes in water quality and potential horizontal or vertical excursions at the Hank Unit cannot be evaluated.

4.5.3.1.2.3 Operation Impacts to Deep Aquifers Below the Production Aquifers

Potential environmental impacts to confined deep aquifers below the production aquifers could be due to deep well injection of processing wastes into deep aquifers. Under different environmental laws such as the Clean Water Act, the SDWA, and the Clean Air Act, EPA has statutory authority to regulate activities that may affect the environment. Underground injection of fluid requires a permit from EPA or from an authorized state UIC program. The WDEQ has been authorized to administer the UIC program in Wyoming and is responsible for issuing any permits for deep well disposal at the Nichols Ranch site.

The GEIS also indicates that the potential environmental impact of injection of leaching solution into deep aquifers below ore-bearing aquifers would be expected to be SMALL, if water production from deep aquifers is not economically feasible or the groundwater quality from these aquifers is not suitable for domestic or agricultural uses (e.g., high salinity), and they are confined above by sufficiently thick and continuous low permeability layers.

Deleted: 2

The GEIS (Section 4.3.4.2.2.3) indicates that in the Wyoming East Uranium Milling Region, where the Nichols Ranch ISR Project is located, the Paleozoic aquifers are hydraulically separated from the aquifer sequence that includes, from the shallowest to the deepest, the Wasatch Formation, the Fort Union Formation, the Lance Formation, and the Fox Hills Formation by thick low permeability confining layers that include the Pierre Shale, the Lewis Shale, and the Steele Shale (Whitehead, 1996). Hence, nonkarstic Paleozoic aquifers (e.g., Tensleep Sandstone) can be investigated further for suitability of disposal of leaching solutions. The GEIS has concluded that in the Wyoming West Uranium Milling Region, considering the relatively low water quality in and the reduced water yields from nonkarstic Paleozoic Aquifers and the presence of thick and regionally continuous aquitards confining them from above, the potential environmental impacts due to deep injection of leaching solution into nonkarstic Paleozoic aquifers could be SMALL.

Deleted: small

Deleted: The Pierre Shale was reported to be fractured in some places at the regional scale (Whitehead, 1996). Considering potential heterogeneities in the hydrogeologic properties of the Pierre Shale, the potential impacts could be SMALL to MODERATE where the Pierre Shale might be locally fractured.

Nichols Ranch plans to dispose of waste fluids using deep well injection and is seeking a permit for a Class 1 injection well from the WDEQ. The WDEQ will evaluate the suitability of the proposed deep injection wells. The WDEQ will only grant such a permit if the waste fluids can

be suitably isolated in a deep aquifer. Consequently, it is assumed that the potential environmental impact to deep aquifers below the production aquifers of deep well injection of waste will be SMALL.

4.5.3.1.3 Aquifer Restoration Impacts to Groundwater

As indicated in GEIS (Section 4.2.4.2.3), the potential environmental impacts to groundwater resources during aquifer restoration are related to groundwater consumptive use and waste management practices, including discharge of waste storage ponds, and potential deep disposal of brine slurries resulting from reverse osmosis. In addition, aquifer restoration directly affects groundwater quality in the vicinity of the wellfield being restored.

Nichols Ranch is planning three phases of restoration: groundwater sweep, groundwater transfer, and groundwater treatment. The sequence of the restoration methods used will be determined based on operating conditions. [Ref TR](#)

Regardless of the process, hydraulic control of the former production zone must be maintained during restoration. This is accomplished by maintaining an inward hydraulic gradient through a production bleed (see Section 4.5.3.2.2.2). As discussed in the GEIS, the impacts of consumptive use during aquifer restoration are generally greater than during ISR operations. This is particularly true during the sweep phase when a greater amount of groundwater is generally withdrawn from the production aquifer. During the sweep phase groundwater is not reinjected into the production aquifer and all withdrawals should be considered consumptive.

The applicant has indicated that restoration will be sequenced with production at the facility. Thus, initially only production will occur at each mine unit. However, as production moves from one wellfield to another, restoration and production will occur simultaneously. Eventually, after production is complete, only restoration will be undertaken. The applicant has indicated that restoration will consumed additional water, particularly during the groundwater sweep phase. Also, during restoration, approximately 20 to 25 percent of the groundwater treatment flow through the reverse osmosis unit is disposed of as brine that is sent to the deep well disposal. Based on liquid disposal rates predicted for the deep injection wells, net withdrawals may approach 379 Lpm (100 gpm) at both the Nichols Ranch and Hank Units during the combined production and restoration phase and during the restoration phase alone. The applicant has not, as yet, provided predictions of the drawdowns that such withdrawals would create or an evaluation of the impact of these drawdowns.

The analysis of the predictions of drawdown during production (see Section 4.5.3.2.2.2) has already indicated that at 133 Lpm (35 gpm), production drawdown from the Nichols Ranch Unit will likely reach a 8 km (5 mi) radius from the unit. The additional consumptive used of groundwater that will accompany aquifer restoration will accentuate these drawdown effects. Given the ample amount (446 feet on average) of available hydraulic head in the Nichols Ranch area, the temporary environmental impact due to consumptive use during restoration at the Nichols Ranch Unit has the potential to be moderate, particularly for wells located just outside the Nichols Ranch boundary. After production and restoration are complete and groundwater withdrawals are terminated at the Nichols Ranch Unit, groundwater levels will tend to recover

Deleted: 2

Deleted: Depending on the progress of restoration, it is possible that not all phases of restoration will be utilized. A reductant may be added anytime to the fluids circulated during restoration to lower the oxidation potential of the production zone. During groundwater sweep, water is pumped from the mine unit, without re-injection, resulting in an influx of baseline quality water from the perimeter of the mine unit. This baseline quality water effectively sweeps the affected portion of the aquifer. During the groundwater transfer phase, water may be transferred between a production area beginning restoration and a production area beginning mining operations. Also a groundwater transfer may occur within the same production area, if one section of the production area is in a more advanced state of restoration than another. The direct transfer of water will act to lower the TDS in the production aquifer being restored by displacing affected groundwater with pre-mining baseline quality. This water can then be used in other restoration or production areas without withdrawing additional groundwater from the production aquifer. During the treatment phase water from the restoration zone is sent for treatment by ion exchange and reverse osmosis. After treatment the water can be reinjected into the restoration zone to continue flushing of the production zone.¶

Deleted: ¶

¶ As discussed in Section 4.5.3.2.2.2 of this EA, the applicant has presented predictions of drawdown during production at both the Nichols Ranch Unit and the Hank Unit. Based ... [1]

Deleted: withdrawals

Deleted: impact the groundwater levels in wells within

Deleted: of

Deleted: , particularly those wells screened within the A Sand and are flowing

Deleted: only

Deleted: impacts

Deleted: Thus

Deleted: potential

Deleted: is

Deleted:

Deleted: LARGE

with time. Thus, the potential long-term environmental impact from consumptive use during the restoration phase at Nichols Ranch Unit will be SMALL.

Deleted: . However, the recharge in this area is limited and recovery may be slow

For the Hank Unit, the analysis of the predictions of drawdown during production (see Section 4.5.3.2.2.2) has indicated that at 284 Lpm (75 gpm), production withdrawals should result in limited, localized drawdowns. The limited drawdowns were due to the unconfined nature of the production aquifer (F-Sand) at the Hank Unit. The additional pumping amounts that may occur during restoration are not likely to increase these drawdowns significantly. Thus, the potential environmental impact due to consumptive use of groundwater during aquifer restoration at the Hank Unit is likely to be SMALL.

Deleted: remains LARGE

Deleted: ¶

Deleted: T

Deleted: from the Hank Unit

A network of buried pipelines is used during ISR restoration for transporting restoration fluids between the pump house and the satellite or main processing facility and also to connect injection and extraction wells to manifolds inside the pumping header houses. However, the fluids transported in these pipes during restoration are generally less potent than during production. The failure of pipeline fittings or valves, or failures of well mechanical integrity in shallow aquifers could result in leaks and spills of these fluids which could impact water quality in shallow aquifers. However, as discussed in Section 4.5.3.2.2.1, the applicant has committed to an aggressive leak detection (Section 7.5.3.1 of the TR, Uranerz 2008b) and spill cleanup program (Section 4.4 of the TR, Uranerz 2008b), as well as preventative measures such as well mechanical integrity testing. Consequently, the implementation of these measures should result in MODERATE potential restoration-related impacts to shallow (near surface) aquifers for the Nichols Ranch and Hank Units.

Deleted: These potential impacts to shallow groundwater during production have previously been evaluated in Section 4.5.3.2.2.1.

Deleted: w

The disposal of waste fluids via deep well injection of waste is planned during mine restoration in much the same manner as during mine operation. As previously indicated in Section 4.5.3.2.2.3, it is assumed that the potential environmental impact to deep aquifers below the production aquifers of deep well injection of waste will be SMALL.

Deleted: Although, the fluids transported in through the piping system during restoration are generally less potent than during production, the potential environmental impact to shallow groundwater during restoration is similar to that during production. Thus, the potential impact to shallow groundwater during restoration at the Nichols Ranch Unit appears to be MODERATE to LARGE. The potential impact to shallow groundwater during restoration at the Hank Unit appears to be MODERATE.¶

Deleted: 2

4.5.3.1.4 Decommissioning Impacts to Groundwater

As indicated in the GEIS (Section 4.3.4.2.4), the environmental impacts to groundwater during dismantling and decommissioning ISR facilities are primarily associated with consumptive use of groundwater, potential spills of fuels and lubricants, and well abandonment. The consumptive groundwater use could include water use for dust suppression, re-vegetation, and reclaiming disturbed areas. The potential environmental impacts during the decommissioning phase are expected to be similar to potential impacts during the construction phase. Groundwater consumptive use during the decommissioning activities would be less than groundwater consumptive use during ISR operation and groundwater restoration activities. Spills of fuels and lubricants during decommissioning activities could impact shallow aquifers. Implementation of BMPs during decommissioning can help to reduce the likelihood and magnitude of such spills and facilitate cleanup. Based on consideration of BMPs to minimize water use and spills, the potential environmental impacts to the groundwater resources in shallow aquifers from decommissioning would be expected to be SMALL.

After ISR operations are completed, improperly abandoned wells could impact aquifers above the production aquifer by providing hydrologic connections between aquifers. As part of the restoration and reclamation activities, all monitoring, injection, and production wells will be plugged and abandoned in accordance with the Wyoming UIC program requirements. The wells would be filled with cement and clay and then cut off below plough depth to ensure that groundwater does not flow through the abandoned wells (Stout and Stover, 1997). If this process is properly implemented and the abandoned wells are properly isolated from the flow domain, the potential environmental impacts would be expected to be SMALL (NRC, 2009a).

TR ref

~~Deleted: 3~~

4.5.3.2 Alternative C (No Hank Unit)

Alternative C would include issuing Uranerz a license for the construction, operation, aquifer restoration, and decommissioning of facilities for ISR uranium milling and processing as proposed by Uranerz, but only for the Nichols Ranch Unit and not the Hank Unit. This would result in the same environmental impact as identified for the Nichols Ranch Unit for Alternative B (see Section 4.5.3.3), while removing those impacts identified for the Hank Unit.

~~Deleted: 3~~

4.5.3.2.1 Construction Impacts to Groundwater

As indicated during the evaluation of the potential environmental impacts at the Nichols Ranch Unit, the potential environmental impacts to groundwater resources during construction of the Nichols Unit would be SMALL based on the limited nature of construction activities and implementation of management practices to protect shallow groundwater.

~~Deleted: 3~~

4.5.3.2.2 Operation Impacts to Groundwater

As discussed previously, during operation, the potential environmental impact to shallow groundwater quality at the Nichols Ranch Unit appears to be MODERATE. Additionally, the potential short-term environmental impact due to consumptive use during operation at the Nichols Ranch Unit is SMALL. After production and restoration are complete and groundwater withdrawals are terminated at the Nichols Ranch Unit, groundwater levels will tend to recover with time. Thus, the potential long-term impact from consumptive use during the operational phase at Nichols Ranch Unit remains SMALL. The potential environmental impact to groundwater quality in the production zone during operations is likely to be SMALL at the Nichols Ranch Unit. During operations, the potential environmental impact to deep aquifers below the production aquifers of deep well injection of waste is assumed to be SMALL.

~~Deleted: D~~

~~Deleted: MODERATE to LARGE~~

~~Deleted: Thus,~~

~~Deleted: LARGE~~

~~Deleted: However, the recharge in this area is limited and recovery may be slow.~~

~~Deleted: MODERATE to LARGE~~

~~Deleted: 3~~

4.5.3.2.3 Aquifer Restoration Impacts to Groundwater

During aquifer restoration, the short-term environmental impact due to consumptive use during restoration at the Nichols Ranch Unit has the potential to be MODERATE. After production and restoration are complete and groundwater withdrawals are terminated at the Nichols Ranch Unit, groundwater levels will tend to recover with time. Thus, the potential long-term environmental impact from consumptive use during the restoration phase at Nichols Ranch Unit is likely to be SMALL. The potential impact to shallow groundwater during restoration at the Nichols Ranch Unit appears to be MODERATE. During aquifer restoration, the potential

~~Deleted: potential~~

~~Deleted: is~~

~~Deleted: LARGE~~

~~Deleted: . However, the recharge in this area is limited and recovery may be slow.~~

~~Deleted: remains MODERATE to LARGE~~

~~Deleted: to LARGE~~

environmental impact to deep aquifers below the production aquifers of deep well injection of waste will be SMALL.

4.5.3.2.4 Decommissioning Impacts to Groundwater

During decommissioning, the potential environmental impacts to the groundwater resources in shallow aquifers at the Nichols Ranch Unit would be expected to be SMALL. The potential environmental impacts due to well abandonment at the Nichols Ranch Unit would also be expected to be SMALL (NRC, 2008).

4.5.3.3 Alternative B (No-Action)

The No-Action Alternative would result in no construction or operational activities on site that might impact shallow groundwater. This alternative also would not require the injection of lixiviant into the production aquifer or the consumptive use of groundwater. The disposal of waste liquids and solids would no longer be necessary and therefore would pose no threat to groundwater quality. Consequently, Alternative B would result in no impacts to groundwater.

References

NRC, 2009. Generic Environmental Impact Statement for In-Situ Leach Uranium Milling Facilities. NUREG-1910. Vol. 1 and 2. June 2009.

Uranerz, 2007a. Nichols Ranch ISR project U.S.N.R.C. Source Material License Application, Volume III, Environmental Report. November 2007. Casper, Wyoming. Accession No. ML080090338.

Uranerz, 2007a. Nichols Ranch ISR project U.S.N.R.C. Source Material License Application, Volume I, Technical Report. November 2007. Casper, Wyoming. Accession No. ML080080609.

Deleted: 3

Deleted: 4.5.3.4 Alternative D (Alternate Liquid Waste Disposal Method)

Alternative D would include issuing Uranerz a license for the construction, operation, aquifer restoration, and decommissioning of facilities for ISR uranium milling and processing as proposed by Uranerz, but using evaporation ponds rather than deep well injection as an alternative liquid waste disposal method. The primary potential environmental impact of evaporation ponds to groundwater would be through leakage from the ponds to shallow (near surface) groundwater. All other potential environmental impacts to groundwater identified in the evaluation of Alternative B would remain the same. ¶

¶
As indicated in the GEIS (Section 2.7.2), evaporation ponds would be constructed, operated, and monitored for leakage in accordance with NRC regulations at 10 CFR Part 40, Appendix A. Evaporation ponds at NRC-licensed ISR facilities are designed with leak detection systems to detect liner failures. The licensee also must maintain sufficient reserve capacity in the retention pond system so the contents of a pond can be transferred to other ponds in the event of a leak and the subsequent corrective action and liner repair. Licensees can minimize the likelihood of impoundment failure by designing the pond embankments in accordance with the criteria found in NRC Regulatory Guide 3.11. Sufficient freeboard height above the liquid level ensures containment during wind and rain events. As indicated in the GEIS (Section 4.3.12.2), leaks may occur over the operational life of a pond; however, the pond design helps to contain leaks and the monitoring would ... [2]

Deleted: MODERATE to LARGE

Deleted: under Alternative B. The addition of an evaporation pond would likely

Deleted: will only

Deleted: add to this potential environmental impact to shallow groundwater.¶

¶
The evaluation of Alternative B indicates that the depth to shallow groundwater appears somewhat greater at the Hank Unit than the Nichols Ranch Unit. There is ... [3]

Deleted: a

As discussed in Section 4.5.3.2.2.2 of this EA, the applicant has presented predictions of drawdown during production at both the Nichols Ranch Unit and the Hank Unit. Based on an assumed production rate of 13,250 Lpm (3,500 gpm) and a 1 percent bleed rate, the applicant has provided predictions of drawdown at the Nichols Ranch Unit based on a bleed of 133 Lpm (35 gpm). Based on an assumed production rate of 9,470 Lpm (2,500 gpm) and a 3 percent bleed rate, the applicant has provided predictions of drawdown at the Hank Unit based on a bleed of 284 Lpm (75 gpm).

4.5.3.4 Alternative D (Alternate Liquid Waste Disposal Method)

Alternative D would include issuing Uranerz a license for the construction, operation, aquifer restoration, and decommissioning of facilities for ISR uranium milling and processing as proposed by Uranerz, but using evaporation ponds rather than deep well injection as an alternative liquid waste disposal method. The primary potential environmental impact of evaporation ponds to groundwater would be through leakage from the ponds to shallow (near surface) groundwater. All other potential environmental impacts to groundwater identified in the evaluation of Alternative B would remain the same.

As indicated in the GEIS (Section 2.7.2), evaporation ponds would be constructed, operated, and monitored for leakage in accordance with NRC regulations at 10 CFR Part 40, Appendix A. Evaporation ponds at NRC-licensed ISR facilities are designed with leak detection systems to detect liner failures. The licensee also must maintain sufficient reserve capacity in the retention pond system so the contents of a pond can be transferred to other ponds in the event of a leak and the subsequent corrective action and liner repair. Licensees can minimize the likelihood of impoundment failure by designing the pond embankments in accordance with the criteria found in NRC Regulatory Guide 3.11. Sufficient freeboard height above the liquid level ensures containment during wind and rain events. As indicated in the GEIS (Section 4.3.12.2), leaks may occur over the operational life of a pond; however, the pond design helps to contain leaks and the monitoring would detect leaks before a significant release of material to the environment occurs. Based on these considerations, the potential environmental impact from the use of a pond is generally considered to be SMALL.

The potential environmental impact at the Nichlols Ranch ISR Project to shallow groundwater due to releases at the surface from piping or valve failures has already been evaluated for Alternative B (Section 4.5.3.2.2.1). As indicated in that evaluation, the potential environmental impacts to shallow water due to leaks from pipeline, valve, well integrity failure, or pond leakage depends on a number of factors, including the depth to shallow groundwater, the use of shallow groundwater, and the degree of hydraulic connection of shallow aquifers to regionally important aquifers. The evaluation of Alternative B indicates that the depth to shallow groundwater in the southern portion

of the Nichols Ranch Unit is limited. Data indicate that the depth to groundwater in the general area of the proposed processing plant is only 15.2 m (50 ft) and portions of the projected production zone extend to the area adjacent to the Cottonwood Creek alluvium, where groundwater may be as shallow as 3 m (10 ft). This limited unsaturated zone offers a limited buffer to absorb and attenuate any releases at the ground surface. Moreover, shallow groundwater likely flows to Cottonwood Creek alluvium, and if left unchecked, shallow groundwater contamination could migrate into and along this alluvial material to the west. The groundwater quality data for the F Sand indicate that groundwater in this unit has relatively high TDS, but appears suitable for stock watering in many areas. The well survey provided by the applicant indicates that there are a number of stock watering wells within a half-mile radius of the project area. While it is uncertain how many of these wells are screened in the shallow aquifer, some of these wells may be potentially impacted by releases at the ground surface that migrate downgradient to the west. Thus, potential impact to shallow groundwater during operation at the Nichols Ranch Unit was found to be MODERATE

add to this potential environmental impact to shallow groundwater.

The evaluation of Alternative B indicates that the depth to shallow groundwater appears somewhat greater at the Hank Unit than the Nichols Ranch Unit. There is generally a 30.5 m (100 ft) or more separation from the ground surface to shallow water beneath most of the production zone and planned processing facility. However, the southern portion of the ore body extends into an area where shallow water is projected to be within 15.2 m (50 ft) of the surface. Water quality data from the H Sand (the shallow aquifer) indicates that groundwater quality in this unit is relatively good and suitable for multiple purposes. The well survey provided by the applicant indicates that there are a number of stock watering wells within a half-mile radius of the project area. It is uncertain how many of these wells are screened in the shallow aquifer. However, the H Sand lies over the shallow F Sand which is the production zone in the Hank Unit. Those wells in close vicinity to the site that are screened in the H Sand are also likely screened in the F Sand as well. The applicant has indicated that wells screened across the F Sand in the vicinity of the Hank will be abandoned. Thus, wells using shallow groundwater from the H Sand will likely be abandoned and will not be directly impacted by releases at the surface. Regardless, due to the shallow depth to groundwater in the southern portion of the Hank Unit area and relatively good groundwater quality in the shallow aquifer, the potential impact to shallow groundwater at the Hank Unit is likely MODERATE under Alternative B. The addition of evaporation ponds under Alternative D would not likely change this potential impact. Consequently, potential environmental impact to shallow groundwater under Alternative D is likely MODERATE.