

Damping Ratio of SC Structure

Non-Proprietary Version

March 2010

**©2010 Mitsubishi Heavy Industries, Ltd.
All Rights Reserved**

Revision History

Revision	Page	Description
0	All	Original Issue

© 2010

MITSUBISHI HEAVY INDUSTRIES, LTD.

All Rights Reserved

This document has been prepared by Mitsubishi Heavy Industries, Ltd. ("MHI") in connection with the U.S. Nuclear Regulatory Commission's ("NRC") licensing review of MHI's US-APWR nuclear power plant design. No right to disclose, use or copy any of the information in this document, other than by the NRC and its contractors in support of the licensing review of the US-APWR, is authorized without the express written permission of MHI.

This document contains technology information and intellectual property relating to the US-APWR and it is delivered to the NRC on the express condition that it not be disclosed, copied or reproduced in whole or in part, or used for the benefit of anyone other than MHI without the express written permission of MHI, except as set forth in the previous paragraph.

This document is protected by the laws of Japan, U.S. copyright law, international treaties and conventions, and the applicable laws of any country where it is being used.

Mitsubishi Heavy Industries, Ltd.
16-5, Konan 2-chome, Minato-ku
Tokyo 108-8215 Japan

Abstract

The purpose of this technical report is to present the damping ratio of SC structure of the US-APWR standard plant.

This report describes:

- Descriptions of 1/10-scale-model Test of Inner Concrete Structure
- Comparison of the typical dimensions between US-APWR and Scale-model
- Evaluation of Damping Ratio

Table of Contents

List of Tables	ii
List of Figures	ii
List of Photo Exhibits	iii
List of Acronyms	iii
1.0 INTRODUCTION	1-1
2.0 DESCRIPTIONS OF 1/10-SCALE-MODEL TEST OF INNER CONCRETE STRUCTURE COMPOSED OF CONCRETE FILLED STEEL BEARING WALL (SC STRUCTURE)	2-1
2.1 Preface	2-1
2.2 Test Overview	2-2
2.2.1 Test model	2-2
2.2.2 Test description	2-9
2.3 Test Results and Discussion	2-10
2.3.1 Test progress	2-10
2.3.2 Discussion of test results	2-16
2.3.3 Comparison of SC test results to existing RC inner concrete structure model test values	2-20
2.4 Conclusion	2-26
2.5 Bibliography	2-26
3.0 COMPARISON OF THE TYPICAL DIMENSIONS	3-1
4.0 EVALUATION OF DAMPING RATIO	4-1

List of Tables

Table 2.2-1	Concrete material testing results	2-3
Table 2.2-2	Steel strength	2-3
Table 2.2-3	Stud punching shear strength	2-3
Table 2.3-1	Loading program	2-10
Table 2.3-2	Elastic rigidity	2-16
Table 2.3-3	Concrete crack-generating loads (wall bottoms)	2-17
Table 2.3-4	Steel plate yield loads (wall bottoms)	2-18
Table 3-1	Comparison of dimensions	3-1

List of Figures

Figure 2.2-1	Overview of actual facility's inner concrete structure (1)	2-4
Figure 2.2-2	Overview of actual facility's inner concrete structure (2)	2-5
Figure 2.2-3	Comparison of geometry and dimensions of actual facility structure and test model	2-2
Figure 2.2-4	Basic plan view of SC reduced-scale model of actual facility's inner concrete structure	2-6
Figure 2.2-5	Basic elevation view of SC reduced-scale model of actual facility's inner concrete structure	2-7
Figure 2.2-6	Standard detailed drawings of SC walls	2-8
Figure 2.3-1	Load-displacement relationship	2-12
Figure 2.3-2	Ultimate shear strength of each wall	2-19
Figure 2.3-3	Comparison of load-deformation relationships	2-23
Figure 2.3-4	Comparison of changes in rigidity	2-24
Figure 2.3-5	Comparison of changes in equivalent damping ratio	2-25
Figure 3-1	Plan of US-APWR I/C SC modules	3-2
Figure 3-2	Plan of 1/10 model SC modules	3-3

List of Photo Exhibit

Photo Exhibit 2.2-1	Test setup	2-9
Photo Exhibit 2.3-1(1)	Test progress photo and diagrams	2-13
Photo Exhibit 2.3-1(2)	Test progress photos and diagrams	2-14
Photo Exhibit 2.3-2	Final state of test model	2-15

List of Acronyms

The following list defines the acronyms used in this document.

APWR	Advanced Pressurized Water Reactor
FEM	finite element method
I/C	inner concrete
JIS	Japanese Industrial Standards
MHI	Mitsubishi Heavy Industries, Ltd.
MW	mega watt
NRC	Nuclear Regulatory Commission
PCCV	prestressed concrete containment vessel
PWR	Pressurized Water Reactor
RV	reactor vessel
R	relative rotation angle
R&D	Research and development
SC	Steel concrete
SG	steam generator
US, U.S.	United States

1.0 INTRODUCTION

This report shows study and evaluation of the damping ratio used for dynamic response analysis of US-APWR I/C using the SC modules, based on the experimental results.

Data on damping ratio of SC structure has been obtained by 1/10 model test performed by Mitsubishi Heavy Industries, LTD. However the model used in the test was designed to simulate configuration of I/C structure adopted in Japanese 1000 MW power plant at that time. There is a slight difference between configurations of I/C structures of the model and US-APWR.

To evaluate the adequacy to adopt the damping ratio obtained by the experiment for US-APWR I/C structure, comparison of the both structures for dimension has been performed. Based on the comparison it was concluded that the damping ratio of the SC structure obtained by the experiment can be applied to US-APWR I/C structure.

2.0 DESCRIPTIONS OF 1/10-SCALE-MODEL TEST OF INNER CONCRETE STRUCTURE COMPOSED OF CONCRETE FILLED STEEL BEARING WALL (SC STRUCTURE)

2.1 Preface



2.2 Test Overview

2.2.1 Test model




Figure2.2-3 Comparison of geometry and dimensions of actual facility structure and testmodel



Table 2.2-1 Concrete material testing results




Table 2.2-2 Steel strength




Table 2.2-3 Stud punching shear strength






Figure 2.2-1 Overview of actual facility's inner concrete structure (1)




Figure 2.2-2 Plan&Sideview of actual facility's inner concrete structure (2)




Figure 2.2-4 Basic plan view of SC reduced-scale model of actual facility's inner concrete structure




Figure 2.2-5 Basic elevation view of SC reduced-scale model of actual facility's inner concrete structure




Figure 2.2-6 Standard detailed drawings of SC walls

2.2.2 Test description



Photo Exhibit 2.2-1 Test setup

2.3 Test Results and Discussion

2.3.1 Test progress



Table 2.3-1 Loading program






Figure 2.3-1 Load-displacement relationship



Photo Exhibit 2.3-1(1) Test progress photo and diagrams



Photo Exhibit 2.3-1(2) Test progress photo and diagrams



Photo Exhibit 2.3-2 Final satate of test model

2.3.2 Discussion of test results



Table 2.3-2 Elastic rigidity

A large, empty, vertically-oriented bracketed area, consisting of two large square brackets facing each other, spanning the lower half of the page. It appears to be a placeholder for a table or other content that is not present in this version of the document.

Table 2.3-3 Concrete crack-generating loads (wall bottoms)



Table 2.3-4 Steel plate yield loads (wall bottoms)

A large, empty rectangular area enclosed by a thin black line with rounded corners, occupying the central portion of the page. It contains the caption for Table 2.3-4.





Figure 2.3-2 Ultimate shear strength of each wall



2.3.3 Comparison of SC test results to existing RC inner concrete structure model test values










Figure 2.3-3 Comparison of load-deformation relationships



Figure 2.3-4 Comparison of changes in rigidity




Figure 2.3-5 Comparison of changes in equivalent damping ratio

2.4 Conclusion

2.5 Bibliography

3.0 COMPARISON OF THE TYPICAL DIMENSIONS


Table 3-1 shows comparison of the typical dimensions of SC I/C structures adopted in the 1/10-scale-model and US-APWR. Figure 3-1 to 3-2 show the plans and sections of SC I/C structures of both US-APWR and 1/10-scale-model.

Table 3-1 Comparison of dimensions

	Component	Symbol	US-APWR(a)	1/10 model(b)	Ratio(a/b)
			(mm)	(mm)	
Comparison to dimension and thickness of plan	Primary Shield Wall	X1	12548	1130	11.1
		Y1	12065	1080	11.2
	Refueling Canal Wall	X2	15697	1390	11.3
		Y2	11735	1080	10.9
	Pressurizer Wall	X3	6833	850	8.0
		Y3	8992	840	10.7
	Secondary Shield Wall	X4	28194	2400	11.7
		Y4	29921	3760	8.0
	SG Wall	X5	19588	1700	11.5
		Y5	9322	891.4	10.5

The comparison in the above table shows that the dimensions of US-APWR slightly exceed the basic scale ratio of 10 for the dimensions of scale-model adopted in the experiment, except dimensions of Secondary Shield Wall and Pressurizer Wall. However the difference or excess from the basic ratio are small. Basically it is thought that the typical dimensions of US-APWR are approximately 10 times to those of 1/10-scale-model.

It is concluded that the typical dimensions of US-APWR are approximately 10 times to those of 1/10-scale-model and the experimental result of the scale model can be applied to the SC I/C structure of the US-APWR.



Security-Related Information - Withhold Under 10 CFR 2.390

Figure 3-1 Plan of US-APWR I/C SC modules

(SRI)




Figure 3-2 Plan of 1/10 model SC modules

4.0 EVALUATION OF DAMPING RATIO

As evaluated in Sec. 3, the damping ratio that has been assured by the experiment described in Sec.2 can be applied to SC I/C structure.

Summary of the 1/10 model test has been also reported at SMiRT10 Conference*¹.

In the report there are descriptions on the damping ratio of the SC structure obtained by the experiment that;

The hysteresis characteristics of SC structure have a spindle-shape like steel structure and show a good behavior.

In the tested SC structure, the equivalent damping ratio was about five percent before the steel yielded while it increased dramatically after the steel yielded.

Which means that as the experimental results, for loads within the design values, the equivalent damping ratio determined from the load-displacement curve loop is about 5% for SC structure. SC structure maintains this ratio at about 5% until steel plates yielded. After yielding, damping gave way to a preponderance of hysteresis damping, resulting in a rapid increase in the equivalent damping ratio.

*¹: 1/10th Scale Model Test of Inner Concrete Structure Composed of Concrete Filled Steel Bearing Wall, SMiRT10, pp73-78, 1989