

SOUTHWEST RESEARCH INSTITUTE®

6220 Culebra Road, P.O. Drawer 28510 Institute Quality Systems Institute Calibration Laboratory Phone: 210-522-5215 Fax 210-522-4834

## **Certificate of Calibration**



Cost Center / Customer: DIV20 / DON BANNON Mail Stop: B51 Manufacturer/Model: FISHER SCIENTIFIC / 15-077-26 Description: TEMPERATURE METER Serial Number: 51046103 Asset Number: 011674 Procedure: DIGITAL THERMOMETERS (TC/RTD) - 12 JUN 09 Work Order: 303093954 Date Issued: 20-Apr-2010 Date Calibrated: 20-Apr-2010 \* Date Due : 20-Apr-2011 \*\* Results: FOUND-LEFT Temperature: 77.0 °F Humidity: 38 %RH Barometer: N/A

This certificate documents traceability to the National Institute of Standards and Technology (NIST) and the International System of Units (SI). The Laboratory quality system conforms to ISO/IEC 17025, 2005, ANSI/NCSL Z540-1-1994 and relevant requirements of the ISO 9000-2000 standard. This certificate shall not be reproduced, except in full, without the written approval of the Southwest Research Institute Calibration Laboratory. This certificate shall not be used to claim product endorsement by Southwest Research Institute, American Association for Laboratory Accreditation (A2LA) or any agency of the U. S. Government. Results of this calibration relate only to the instrument described above at the time of calibration and does not imply any long term stability of the instrument.

\*Determined by the customer, does not imply the instrument will remain within tolerance as any number of factors may cause an out-of-tolerance condition before this date. \*\*Data type found in this certificate or attached measurement report must be interpreted as: Found-left - adjustment and/or repair was not performed, As-found - data is before unit is adjusted and/or repaired, As-left - data is after adjusted and/or repaired was performed. The customer has sole responsibility for determination of in-/out-of-tolerance or compliance/noncompliance.

Measurement uncertainty calculated in accordance with the method described in the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM), for a confidence level of approximately 95 percent using a coverage factor of k=2.

Remarks: None

## Standards Used

<u>Asset #</u>	Manufacturer	Model	Description	Cal Date	Due Date
010329	FLUKE	525A	TEMPERATURE/PRESSURE CALIBRATOR	12-May-2009	12-May-2010

h/na

Walt Hill Laboratory Manager m:VA2LA OCT\_08.rpt

Mark Romero Metrology Technician

Page 1 of 1

## Southwest Research Institute Calibration Laboratory Measurement Report

. .

Work Order: Asset No: Serial No:	303093954 011674 51046103	Mfr: Model: Type:	Iodel: 15-077-26		Technician: Type Data: Cal Date:	Mark Romero Found-left 20-Apr-10	
Remarks:	01040100		memocoupie			201101	
Function/Range	Test Point	TI Reading	Difference	+/- Limit	+/- Uncertainty	/ Result	% Limit
T1 Input Type K	°C	°C	°C	°C	°C		
	-50.0	-49.6	0.4	1.4	0.24	Pass	29%
	190.0	190.6	0.6	2.4	0.32	Pass	25%
	575	575	0	5	0.66	Pass	0%
	960	961	1	8	0.66	Pass	12%
	1200	1201	1	10	0.75	Pass	10%
T2 Input Type K	°C	°C	°C	°C	°C		
, ,,	-50.0	-50.5	-0.5	1.4	0.24	Pass	36%
	190.0	190.0	0.0	2.4	0.32	Pass	0%
	575	574	-1	5	0.66	Pass	19%
	960	960	0	8	0.66	Pass	0%
	1200	1200	0	10	0.75	Pass	0%
T1 Input Type K	°F	°F	°F	°F	°F		
· · · · · · · · · · · · · · · · · · ·	-58.0	-57.8	0.2	2.4	0.39	Pass	8%
	310	311	1	4	0.80	Pass	23%
	1025	1024	-1	10	0.80	Pass	10%
	1740	1740	0	15	0.80	Pass	0%
	1900	1902	2	16	1.0	Pass	12%
T2 Input Type K	°F	°F	°F	°F	°F		
iz nipat i jpo i t	-58.0	-59.0	-1.0	2.4	0.39	Pass	41%
	310	310	0	4	0.80	Pass	0%
	1025	1024	-1	10	0.80	Pass	10%
	1740	1742	2	15	0.80	Pass	13%
	1900	1902	2	16	1.0	Pass	12%
Difference	°F	۴F	°F	°F	۴		
T1-T2	0.0	0.9	0.9	2.0	0.39	Pass	45%
	°C	°C	°C	°C	°C		
T4 T0	-	-	-	-		Dooo	500/
T1-T2	0.0	0.5 END	0.5 OF REPORT	1.0	0.22	Pass	50%