Safety Analysis Report
for
Century Industries
Versa-Pac Shipping Container

Application for License
Docket No. 71-9342

Revision 3
April 09, 2010

Designed and Submitted By:
Century Industries,
Bristol, Virginia

TABLE OF CONTENTS

1 GENERAL INFORMATION……..1-1

1.1 Introduction……...……...1-1
1.2 Package Description……..……..1-2
1.2.1 Packaging……..……..1-2
1.2.2 Contents……...…….……...1-5
1.2.3 Special Requirements for Plutonium….……..1-5
1.2.4 Operational Features……1-6
1.3 List of Appendices……..……1-7
1.3.1 Versa-Pac Shipping Container Drawings, Century Industries Drawing No. VP-55-LD-1 & 2, VP-110-LD-1 & 2.…….1-13
1.3.2 General Notes,……...1-18
1.3.3 SOP 6.11 – Polyurethane Closed Cell Foam Specification for Century Industries Products…….....1-20
1.3.4 SOP 6.12 Ceramic Fiber Insulation Specification for Century Industries Products…….……..……..1-27
1.3.5 SOP 6.13 – Structural Fiberglass Component Specification for Century Industries Products……..….1-31

List of Tables and Figures

Figure 1-1 Versa-Pac Component Illustration…….……..1-6

Table 1-1 Versa-Pac Shipping Container Gross Weights.…….……..1-8
Table 1-2 55 Gallon Versa-Pac Materials of Construction…….….1-9
Table 1-3 110 Gallon Versa-Pac Materials of Construction…….....1-10
Table 1-4 Auto-Ignition Temperature for Selected Materials for Packaging within the Versa-Pac……1-11
Table 1-5 Summary of Uranium Isotope Limits for U-234 & U236.1-12

2 STRUCTURAL EVALUATION

2.1 Description of Structural Design……...…..2-1
2.1.1 Discussion…….…...2-1
2.1.2 Design Criteria...……..…2-2
2.1.3 Weights and Centers of Gravity…….…….2-3
2.1.4 Identification of Codes and Standards for Package Design……..2-3
2.2 Materials……..2-4
2.2.1 Mechanical Properties of Materials…….2-4
2.2.2 Chemicals, Galvanic Reactions and Other Reactions.....2-4
2.2.3 Effects of Radiation on Materials…….....2-4
2.3 Fabrication and Examination…….....2-4
2.3.1 Fabrication……,,2-4
2.3.2 Examination……2-5

2.4 General Requirements for All Packages……..2-5
2.4.1 Minimum Package Size……...2-5
2.4.2 Tamper-Indicating Feature……..2-5
2.4.3 Positive Closure……..……2-5
2.5 Lifting and Tie-Down Standards for All Packages.....2-6
2.5.1 Lifting Devices……2-6
2.5.2 Tie-Down Devices……...2-6
2.6 Normal Condition of Transport……...2-6
Evaluation by Test……...2-6
Evaluation by Analysis……2-6
2.6.1 Heat……..2-7
2.6.1.1 Summary of Pressures and Temperatures……...2-7
2.6.1.2 Differential Thermal Expansion……..2-7
2.6.1.3 Stress Calculations……...2-7
2.6.1.4 Comparison with Allowable Stresses……..2-7
2.6.2 Cold……2-8
2.6.3 Reduced External Pressure……..2-8
2.6.4 Increased External Pressure……2-8
2.6.5 Vibration…….....2-8
2.6.6 Water Spray……2-9
2.6.7 Free Drop……2-9
2.6.8 Corner Drop……2-9
2.6.9 Compression……2-9
2.6.10 Penetration…….2-10
2.7 Hypothetical Accident Conditions…….2-10
2.7.1 Free Drop……...2-11
2.7.1.1 End Drop……2-11
2.7.1.2 Side Drop……...2-12
2.7.1.3 Corner Drop……...2-12
2.7.1.4 Oblique Drops……2-13
2.7.1.5 Summary of Results……...2-13
2.7.2 Crush……..…2-14
2.7.3 Puncture……..…2-14
2.7.4 Thermal……..…2-19
2.7.4.1 Summary of Pressure and Temperatures……..….2-19
2.7.4.2 Differential Thermal Expansion.....…..2-19
2.7.4.3 Stress Calculations…….……2-19
2.7.5 Immersion - Fissile Material…….……2-20
2.7.6 Immersion – All Packages…….……2-20
2.7.7 Deep Water Immersion Test (for Type B Packages Containing More than 10^5 A_2)……...2-20
2.7.8 Summary of Damage…….2-20
2.8 Accident Conditions for Air Transport of Plutonium……2-21
2.9 Accident Conditions for Fissile Material Packages for Air Transport…….2-21
2.10 Special Form……..2-21
2.11 Fuel Rods……...2-21

2.12 Appendix…...……2-21
2.12.1 MATEC Report on Material Compatibility…….2-26
2.12.2 Century Industries Performance Test Report for the Versa-Pac…….2-29
2.12.3 Excerpted from Safety Analysis Report for the Century Champion Type B Package Immersion Test.2-30
2.12.4 Century Industries Test Report for the 55-Gallon Versa-Pac Shipping Container (Shallow Angle Drops)……2-31
2.12.5 NCT Versa-Pac Test Report for Compression & Penetration……..2-32

List of Tables and Figures

Table 2-1 Evaluation Results……...2-23
Table 2-1 Mechanical Properties of Materials…….2-25

3 THERMAL EVALUATION……3-1
3.1 Description of Thermal Design……..3-1
3.1.1 Design Features……..……..3-1
3.1.2 Content's Decay Heat…….……3-1
3.1.3 Summary Tables of Temperatures…….……..3-2
3.1.4 Summary Tables of Maximum Pressures……3-2
3.2 Material Properties and Component Specifications……3-2
3.2.1 Material Properties……..3-2
3.2.2 Component Specifications……...3-2
3.3 Thermal Evaluation under Normal Conditions of Transport……...3-3
3.3.1 Heat and Cold……..3-3
3.3.2 Maximum Normal Operating Pressure……3-4
3.4 Thermal Evaluation under Hypothetical Accident Conditions…...3-4
3.4.1 Initial Conditions……3-4
3.4.2 Fire Test Conditions……....3-4
3.4.3 Cool-down Conditions…….……3-4
3.4.4 Maximum HAC Temperature and Pressures ……..3-5
3.4.4.1 HAC Temperatures……..3-5
3.4.4.2 HAC Pressures……3-5
3.4.5 Maximum Thermal Stresses……3-5
3.4.6 Accident Conditions for Fissile Material Packages for Air Transport……...3-5
3.5 Appendix……....3-5
3.5.1 Description of Thermal Model……3.5
3.5.2 Excerpted from ALGOR Non-Linear Thermal Transient Heat Transfer Analysis Manual, *"Emulation of body-to-body radiation as temperature dependent conduction"*……..….3-5
3.5.3 Summary of thermal testing of the Champion for demonstration of thermal stress acceptability…….3-5
3.5.4 Heat Sources and Boundary Illustrations……3-5
3.6 References……..3-5

3.6.1 MatWeb material database, a division of Automation Creations, Inc. (ACI) of Blacksburg, Virginia……...….3-5
3.6.2 ALGOR FEMPRO FEA Software by Autodesk, Pittsburg, PA, Version 18.1…….3-5
3.6.3 Inropera & DeWitt, Fundamentals of Heat and Mass Transfer 3rd Edition, John Wiley & Sons, New York, 1990……..3-5

List of Tables and Figures

Table 3-1 Evaluation Results…….3-7
Table 3-2 Applied Heat Loads and Initial Conditions……...3-8

Figure 3-1 Normal Hot Package Peak Temperature Distribution, 55-gallon Versa-Pac……..3-9
Figure 3-2 Normal Hot Outer Surface Peak Temperature Distribution, 55-gallon Versa-Pac……3-10
Figure 3-3 Normal Hot Contents Peak Temperature Distribution, 55-gallon Versa-Pac.……...3-11
Figure 3-4 Maximum Fire Event Temperature at 30 Minutes, Contents..3-12
Figure 3-5 Fire Event Temperature at 30 Minutes, Payload Cavity and Flanges (including Polyurethane Plug Area)……...3-13
Figure 3-6 Fire Event Temperature at 30 Minutes, Package Lid……..3-14
Figure 3-7 Fire Event Temperature at 30 Minutes, Package Side View...3-15
Figure 3-8 Fire Event Temperature at 30 Minutes, Polyurethane Plug….3-15
Figure 3-9 Fire Event Temperature at 30 Minutes, Isometric View of Temperature Distribution……3-16
Figure 3-10 Fire Event and Cool-down Temperature at 55 Total Minutes, Package Side View……3-17
Figure 3-11 Fire Event Temperature at 30 Minutes, Polyurethane Plug...3-18
Figure 3-12 Fire Event and Cool-down Temperature at 55 Minutes, Polyurethane Plug……..3-18
Figure 3-13 Fire Event Temperature at 30 Minutes, Isometric View of Temperature Distribution……..3-19
Figure 3-14 Fire Event and Cool-down Temperature at 55 Total Minutes, Isometric View of Temperature Distribution……3-20
Figure 3-15 Fire Event and Cool-down Temperature as a Function of Seconds (Beginning of Cool-down = 0 sec) for Payload Cavity Nodes 72302 (at the Bottom of the Polyurethane Insert) and 14619 (at the Center of the Payload Cavity Floor Part PB)…….3-21

4 CONTAINMENT……..4-1
4.1 Description of the Containment System……..4-1
4.2 Containment Under Normal Conditions of Transport……..…..4-1
4.3 Containment Requirements for Hypothetical Accident Conditions……..….4-1
4.4 Leakage Rate Tests for Type B Packages……...…4-2
4.5 List of Appendices……...4-2

5 SHIELDING EVALUATION……..5-1

6 CRITICALITY EVALUATION……..6-1
6.1 Description of Criticality Design..……...6-3
6.1.1 Design Features..…….6-3
6.1.2 Summary Table of Criticality Evaluation……6-3
6.1.3 Criticality Safety Index……6.4
6.2 Fissile Material Contents…….6-4
6.3 General Considerations……6-5
6.3.1 Model Configuration……...6-5
6.3.2 Material Properties……..6-7
6.3.3 Computer Codes and Cross Section Libraries……6-7
6.3.4 Demonstration of Maximum Reactivity…….6-7
6.4 Single Package Evaluation……6-9
6.4.1 Configuration……..6-9
6.4.2 Results……...6-10
6.5 Evaluation of Package Arrays Under Normal Conditions of Transport……6-10
6.5.1 Configuration……..610
6.5.2 Results……...6-11
6.6 Evaluation of Package Under Hypothetical Accident Conditions.6-11
6.6.1 Configuration…….6-11
6.6.2 Results……...6-13
6.7 Fissile Material Packages for Air Transport……..6-21
6.8 Benchmark Evaluations……..……...6-21
6.8.1 Benchmark Experiments and Applicability……...6-21
6.8.2 Bias Determination……6-22
6.8.3 Benchmark Results……6-22
6.9 List of Appendices……6-23
6.9.1 SCALE 4-4a Input Decks – Bounding Cases…….…...6-74
6.9.2 [6-1] Montgomery, Richard D., Validation of SCALE-PC for High Enriched Uranium (HEU) Systems MTS 423, Rev. 1 5/30/09……6-107
6.10 References……6-23

List of Tables and Figures

Table 6-1 Summary of Results……6-24
Table 6-2 Century Versa-Pac Shipping Container – Test Package Dimensional Changes……..6-26
Table 6-3 Century Versa-Pac Shipping Container Dimensions and Materials……..6-27
Table 6-4 Package Regional Densities……6-29
Table 6-5 Summary of Single Package Results……...6-30
Table 6-6 Summary of Hypothetical Accident Condition Package Results for Homogeneous Models……...6-32
Table 6-7 Summary of Hypothetical Accident Condition Package Results for Lumped Fissile Mass Models……6-34
Table 6-8 Summary of Hypothetical Accident Condition Package Results for Lumped Fissile Mass Models – Increased Array Size and Increased Poly-Moderation Sensitivity ……6-38
Table 6-9 Summary of Hypothetical Accident Condition Package Results for Lumped Fissile Mass Models – Cross Section, Fissile Mass, Interspersed Moderation, Fissile Moderator Density, and Package Carbon Steel Sensitivity……...6-41
Table 6-10 Summary of Sphere Sensitivity Placement Calculations for MOD0, MOD1, MOD2, MOD3, and MOD4 Arrays (Note: Yellow high-lighted cells represent the bounding case)……..6-43
Table 6-11 Summary of Sphere Sensitivity Placement Calculations for MOD0, MOD1, MOD2, MOD3, and MOD4 Arrays (Note: Yellow high-lighted cells represent the bounding case, interspersed moderator VF=0.0001, poly-moderation density-0.98 g/cc)……6-46
Table 6-12 Summary of Region Dependent Interspersed Moderation Calculations for MOD0 and MOD1 Array Configurations (Note: Yellow high-lighted cells represent the bounding case)……6-47

Figure 6-1 Illustration of the KENO Model of Century Versa-Pac Shipping Container for the Normal Condition of Transport and hypothetical Accident Condition……..6-60
Figure 6-2 KENO VI results for single model calculation as a function of drum fill percentage for the Normal Condition of Transport and Hypothetical Condition……6-61
Figure 6-3 KENO VI results for single model calculation as a function of poly-moderator (20% filled drum) for the Normal Condition of Transport and Hypothetical Condition..6-61
Figure 6-4 KENO VI results for single model calculation as a function of interspersed moderator (20% filled drum) for the Normal Condition of Transport and Hypothetical Condition……6-62

Figure 6-5 KENO VI results for fully reflected spheres representing the Normal Condition of Transport and Hypothetical Condition for a single package...…….6-62
Figure 6-6 KENO VI results for infinite array model calculation as a function of drum fill percentage for the Normal Condition For Transport and Hypothetical Condition……..6-63
Figure 6-7 KENO VI results for infinite array model calculation as a function of poly-moderator density (10% filled drum) for the Normal Condition of Transport and Hypothetical Condition…….6-63
Figure 6-8 KENO VI results for triangular package array model calculation with lumped spheres as a function of package array size for the Normal Condition of Transport and Hypothetical Condition……6-64
Figure 6-9 KENO VI results for triangular package array model calculation with lumped spheres as a function of sphere diameter for the Normal Condition of Transport and Hypothetical Condition……6-64
Figure 6-10 KENO VI results for square package array model calculation with lumped spheres as a function of package array size for Normal Condition of Transport and Hypothetical Condition……...6-65
Figure 6-11 KENO VI results for triangular package array model calculation with lumped cylinders as a function of package array size for the Normal Condition of Transport and Hypothetical Condition……...6-65
Figure 6-12 KENO VI results for triangular package array model calculation with lumped cylinders as a function of cylinder diameter for the Normal Condition of Transport and Hypothetical Condition……..6-66
Figure 6-13 KENO VI results for triangular package array model calculation with lumped cylinders as a function of cylinder height to diameter ratio for the Normal Condition of Transport and Hypothetical Condition……...6-66
Figure 6-14 KENO VI results for triangular package array model calculation with poly-moderated (0.92 g/cc) lumped spheres as a function of package array size for the Normal Condition of Transport and Hypothetical Condition……..6-67
Figure 6-15 KENO VI results for triangular package array model calculation with poly-moderated (0.98 g/cc) lumped spheres as a function of package array size for the Normal Condition of Transport and Hypothetical Condition……..6-67
Figure 6-16 Illustration of KENO VI triangular package array model with orientation of lumped fissile mass for the Normal Conditions of Transport And Hypothetical Condition…….6-68

Figure 6-17 Illustration of KENO VI square package array model with orientation of lumped fissile mass for Normal Condition of Transport and Hypothetical Conditions……..…6-68
Figure 6-18 Illustration of KENO VI stacked X-Z view of the inverted bottom package and normally orientated top package in a triangular package array model with orientation of lumped fissile mass for the NCT and HAC (Initial MODO Configuration)……...6-69
Figure 6-19 Illustration of KENO VI stacked X-Z view for the triangular package array model with orientation of lumped fissile mass for the NCT and HAC (MOD1 Configuration)……..….6-70
Figure 6-20 Illustration of KENO VI stacked X-Z view for the triangular package array model with orientation of lumped fissile mass for the NCT and HAC (MOD2 Configuration)……..….6-71
Figure 6-21 Illustration of KENO VI stacked X-Z view for the triangular package array model with orientation of lumped fissile mass for the NCT and HAC (MOD3 Configuration – note centered spheres as opposed to overlapping view as observed in Figure 6-19)……...6-72
Figure 6-22 Illustration of KENO VI stacked X-Z view for the triangular package array model with orientation of lumped fissile mass for the NCT and HAC (MOD4 Configuration)……...6-73

7 **PACKAGE OPERATIONS……..7-1**
7.1 Package Loading……..7-1
7.1.1 Preparation for Loading……..…….7-1
7.1.2 Loading of Contents……7-2
7.1.3 Preparation for Transport…….7-2
7.2 Package Unloading……..7-3
7.2.1 Receipt of Package from Carrier…….7-3
7.2.2 Removal of Contents……...7-3
7.3 Preparation of Empty Package for Transport……..7-3
7.4 Other Operations……..7-3
7.5 Appendix…….7-3

8 ACCEPTANCE TESTS AND MAINTENANCE PROGRAM……8-1
8.1 Fabrication Acceptance Tests……..8-1
8.1.1 Visual Inspection and Measurements……..8-1
8.1.2 Weld Inspection……...8-1
8.1.3 Structural and Pressure Tests……...8-2
8.1.4 Leakage Tests……..8-2
8.1.5 Component and Materials Tests……..8-2
8.1.6 Tests for Shielding Integrity……8-2
8.1.7 Thermal Acceptance Tests……...8-2
8.1.8 Miscellaneous Tests……8-2
8.2 Maintenance Program……..8.2
8.2.1 Structural and Pressure Tests……...8-3
8.2.2 Leakage Tests……..8-3
8.2.3 Component and Material Tests……8-3
8.2.4 Thermal Tests……..8-4
8.2.5 Miscellaneous Tests……8-4
8.3 List of Appendices……...8-4