August 23, 2010 10-096

ATTN: Document Control Desk Director, Office of Nuclear Material Safety & Safeguards U. S. Nuclear Regulatory Commission Washington, DC 20555-0001

Reference: License No. SNM-42, Docket 70-27

Subject: Semi-Annual Effluent Monitoring Report

#### Dear Madam:

The Semi-Annual Effluent Report for Babcock & Wilcox Nuclear Operations Group, Inc. (B&W NOG), Lynchburg facility, covering the first semi-annual effluent monitoring period for 2010 is enclosed. This report is being submitted in accordance with the requirements of 10 CFR 70.59.

If you have any questions regarding this report, please contact me at 434.522.5665.

Sincerely,

Barry L. Cole

Manager, Licensing & Safety Analysis

(Licensing Officer)

1. loke

Babcock & Wilcox Nuclear Operations Group, Inc. - Lynchburg

Enclosure

cc: NRC, Region II

NRC, Resident Inspector

NRC, M. Baker

B&W NOG, K. Conway B&W NOG, C. England

NM5502

## **ENCLOSURE**

7 pages

Reporting Period: 01/04/10 to 07/04/10 (Weeks Ending 01/10/10 to 07/04/10)

Stack: WASTE MGMT CENTER (# 39)

Average Flow Rate:

1.22 cubic meters/second

Average 1 low	icaic.	1.22 Cubic Meters/secor	iu		
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	<1.00E-14	<1.00E-14	<1.00E-14	9.00E-02	4.8E-05
Stack: MFP LO Average Flow	, ,	1.14 cubic meters/secor	nd		
Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (µCi)	Off-Site Dose (mrem)
U-234 (S)	1.00E-14	<1.00E-14	<1.00E-14	1.30E-01	7.0E-05
Stack: 2A STAC Average Flow F	` '	1.06 cubic meters/secor	nd		
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	2.00E-14	2.00E-14	2.00E-14	3.60E-01	1.9E-04
Stack: 2A PRO Average Flow	DUCTION SUPPORate:	ORT (# 44) 2.31 cubic meters/secor	nd		
Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (µCi)	Off-Site Dose (mrem)
U-234 (S)	<1.00E-14	<1.00E-14	<1.00E-14	3.00E-02	1.6E-05
Stack: 1A MAI Average Flow	INTENANCE (# 4) Rate:	3) 5.33 cubic meters/secor	nd		
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	<1.00E-14	<1.00E-14	<1.00E-14	1.00E-01	5.4E-05

Reporting Period: 01/04/10 to 07/04/10 (Weeks Ending 01/10/10 to 07/04/10)

Stack: RECLAMATION (# 20)

Average Flow Rate:

0.30 cubic meters/second

Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	<1.00E-14	<1.00E-14	<1.00E-14	1.00E-02	5.6E-06
Stack: PHARM Average Flow	` '	1.73 cubic meters/secor	nd		
Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	<1.00E-14	<1.00E-14	<1.00E-14	1.10E-01	5.9E-05
Stack: NMC STAVERAGE Flow	ΓORAGE (# 42) Rate:	0.82 cubic meters/secor	nd		
Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	(x E-12 μCi/ml) (μCi)	Off-Site Dose (mrem)
U-234 (S)	<1.00E-14	<1.00E-14	<1.00E-14	5.00E-02	2.4E-05
Stack: MET LA Average Flow		4.81 cubic meters/secor	nd		
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	1.00E-14	<1.00E-14	<1.00E-14	4.30E-01	2.3E-04
Stack: RTRT ( Average Flow)	• •	6.77 cubic meters/secor	nd		
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	<1.00E-14	<1.00E-14	<1.00E-14	3.10E-01	1.5E-04

Reporting Period: 01/04/10 to 07/04/10 (Weeks Ending 01/10/10 to 07/04/10)

Stack: SFF (# 11)

Average Flow Rate:

10.49 cubic meters/second

Tiverage 1 low 1		to.45 cable meters/secor	14		
Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (µCi)	Off-Site Dose (mrem)
U-234 (S)	1.00E-14	1.00E-14	1.00E-14	1.50E+00	8.9E-04
Stack: 13A/14A Average Flow l	A/15A DRY (# 38) Rate:	16.03 cubic meters/secor	nd		
Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	1.00E-14	1.00E-14	2.00E-14	3.09E+00	1.8E-03
Stack: CHEM I Average Flow I	LAB SCRUBBER ( Rate:	# 37) 11.58 cubic meters/secor	nd		
	Concentration	Error Estimate	LLD	Quantity Released	Off-Site Dose
Radionuclide	(μCi/ml)	(μCi/ml)	(μCi/ml)	(μCi)	(mrem)
U-234 (S)	1.00E-14	<1.00E-14	<1.00E-14	1.84E+00	1.1E-03
Stack: 14A MA Average Flow	AINTENANCE (# 3 Rate:	5) 3.00 cubic meters/secon	nd		
	Concentration	Error Estimate	LLD	Quantity Released	Off-Site Dose
Radionuclide	(μCi/ml)	(μCi/ml)	(μCi/ml)	(μCi)	(mrem)
U-234 (S)	1.00E-14	1.00E-14	2.00E-14	4.00E-01	2.4E-04
Stack: RECOVERY (# 15) Average Flow Rate:		12.46 cubic meters/seco	nd		
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (µCi)	Off-Site Dose (mrem)
U-234 (F)	1.16E-12	4.00E-14	3.00E-14	2.28E+02	1.2E-03

Reporting Period: 01/04/10 to 07/04/10 (Weeks Ending 01/10/10 to 07/04/10)

Stack: DOWNBLEND SCRUBBER (# 40)

Average Flow Rate:

0.91 cubic meters/second

Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (F)	7.00E-14	3.00E-14	1.00E-13	9.90E-01	1.5E-05
Stack: LAUND Average Flow I	RY STACK (# 30) Rate:	2.39 cubic meters/second	d		
Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	4.00E-14	2.00E-14	2.00E-14	1.53E+00	9.9E-04
Stack: COMPA Average Flow I					
Radionuclide	Concentration (µCi/ml)	Error Estimate (µCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	<1.00E-14	<1.00E-14	<1.00E-14	5.00E-02	3.2E-05
Stack: RETENTION TANKS (# 36) Average Flow Rate: 0.55 cubic meters/second					
Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	<1.00E-14	<1.00E-14	<1.00E-14	1.00E-02	6.5E-06
Stack: WT SCRUBBER (# 31) Average Flow Rate: 2.93 cubic meters/second					
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	9.00E-14	<1.00E-14	1.00E-14	4.19E+00	2.6E-03

## I. GASEOUS EFFLUENTS (Continuously Sampled Stacks) Reporting Period: 01/04/10 to 07/04/10 (Weeks Ending 01/10/10 to 07/04/10)

Stack: DECON (# 33)

Average Flow Rate:		1.99 cubic meters/secon	d		
Radionuclide	Concentration (μCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S)	3.00E-14	2.00E-14	2.00E-14	9.20E-01	5.8E-04
Stack: LTC 50 METER STACK Average Flow Rate:		15.54 cubic meters/secon	nd		
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S) Sr-90(S)	<1.00E-14 2.18E-14	<1.00E-14 1.00E-14	<1.00E-14 1.00E-14	1.32E+00 1.29E+01	1.2E-04
Stack: LTC AC Average Flow l		1.42 cubic meters/secon	d		
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (µCi/ml)	Quantity Released (μCi)	Off-Site Dose (mrem)
U-234 (S) Sr-90(S)	<1.00E-14 1.31E-14	1.00E-14 2.22E-14	<1.00E-14 1.00E-14	2.85E-01 8.01E-01	2.1E-04
Stack: LTC RCL STACK Average Flow Rate:		1.62 cubic meters/secon	nd		
Radionuclide	Concentration (µCi/ml)	Error Estimate (μCi/ml)	LLD (μCi/ml)	Quantity Released (µCi)	Off-Site Dose (mrem)
U-234 (S) Sr-90(S)	1.00E-14 1.95E-14	1.00E-14 1.13E-14	<1.00E-14 1.00E-14	4.60E-01 1.35E+00	3.5E-04

# I. GASEOUS EFFLUENTS (Continuously Sampled Stacks) Reporting Period: 01/04/10 to 07/04/10 (Weeks Ending 01/10/10 to 07/04/10)

#### NOTES:

- The total exposure from all stacks is 0.01098 mrem. Doses were determined using the EPA COMPLY code. Actual stack and building heights were used. A distance from source to receptor of 540 meters was used, with wind blowing towards the receptor at a speed of 2 meters/sec, 25% of the time. Other default parameters such as temperature were used if prompted. Comply itself is conservative.
- (2) All alpha activity is conservatively reported as U-234 as this is the predominant uranium nuclide and has the most conservative dose conversion factor of the various uranium isotopes.
- Beta/Gamma nuclides are not reported unless they exceed the respective MDC based on isotopic analysis. All beta activity for the LTC stacks is conservatively reported as Sr-90 as this has the most conservative dose conversion factor.
- Average concentrations, errors and LLDs are quoted as 1E-14  $\mu$ Ci/ml for stacks when these values are between 5E-15  $\mu$ Ci/ml and 1E-14  $\mu$ Ci/ml, and they are quoted as <1E-14  $\mu$ Ci/ml when the values are less than 5E-15  $\mu$ Ci/ml.
- (5) Activities are quoted as 1E-02  $\mu$ Ci when these values are between 5E-03  $\mu$ Ci and 1E-02  $\mu$ Ci, and they are quoted as <1E-02  $\mu$ Ci when the values are less than 5E-03  $\mu$ Ci.
- (6) The error estimate is the daily error at the 95% confidence interval propagated over the six month period.
- (7) Quantity released (uCi) is the sum of the activities calculated daily based on the calculated daily concentration for all concentrations > 0.
- (8) Twenty four (24) stacks were monitored during this monitoring period.
- (9) Average concentrations, errors and LLDs are quoted to one significant digit except for the Recovery, Waste Treatment, and three LTC stacks.

#### II. LIQUID EFFLUENT

A. Reporting Period: 01/01/10 through 06/30/10

B. Location of Sample: Collection Prior to Discharge into the James River.

C. Total Liquid Flow: 2.983E+08 liters

D. Sample Collection: Batch composite sampler.

				Quantity	
Radionuclide	Concentration	Error Estimate	LLD	Released	Total Dose
	(pCi/l)	(±pCi/l)	(pCi/l)	(μCi)	(mrem)
U-234	1.14E+01	3.64E+00	2.08E-01	3,398.76	3.70E-02
U-235	2.49E-01	4.53E-01	2.38E-01	74.19	7.57E-04
U-236	4.83E-02	2.73E-01	1.90E-01	14.42	1.49E-04
U-238	9.89E-02	2.95E-01	1.85E-01	29.50	2.88E-04

#### Total 3.81E-02

#### NOTES:

- The total dose calculated for liquid release uses a dilution factor of 18:1. Regulatory Guide 1.109 was used as guidance, with conservative assumptions to estimate the exposure.
- The semi-annual concentration reported above is a volume-weighted average for the six months and may be less than the averaged MDC for the same period.
- Isotopic analysis is performed on the monthly composite samples for the most commonly utilized beta/gamma nuclides such as Sr-90, Tc-99 and Cs-137. The analysis of these nuclides typically indicates results less than minimum detectable concentration (MDC). Only nuclides with concentration above the respective MDC are reported. No beta/gamma nuclides exceeded their MDC for the reporting period.