NRC FORM 374

U.S. NUCLEAR REGULATORY COMMISSION

PAGE 1 OF 7 PAGES
Amendment No. 11

MATERIALS LICENSE

Pursuant to the Atomic Energy Act of 1954, as amended, the Energy Reorganization Act of 1974 (Public Law 93-438), and Title 10, Code of Federal Regulations, Chapter I, Parts 30, 31, 32, 33, 34, 35, 36, 39, 40, and 70, and in reliance on statements and representations heretofore made by the licensee, a license is hereby issued authorizing the licensee to receive, acquire, possess, and transfer byproduct, source, and special nuclear material designated below; to use such material for the purpose(s) and at the place(s) designated below; to deliver or transfer such material to persons authorized to receive it in accordance with the regulations of the applicable Part(s). This license shall be deemed to contain the conditions specified in Section 183 of the Atomic Energy Act of 1954, as amended, and is subject to all applicable rules, regulations, and orders of the Nuclear Regulatory Commission now or hereafter in effect and to any conditions specified below

applicable rules, regulations, and orders of the Nuclear Regulatory Cobelow.	ommission now or hereafter in effect and to any conditions specified					
Licensee	In accordance with letter dated					
	September 14, 2010					
1. Hecla Greens Creek Mining Company	3. License number 50-23276-01 is amended in					
	its entirety to read as follows:					
2. 3000 Vintage Blvd, Suite 200 P.O. Box 32199	4. Expiration date August 31, 2013					
P.O. Box 32199	5. Docket No. 030-20447					
Juneau, Alaska 99803-2199	Reference No.					
6. Byproduct, source, and/or special 7. Chemical and/or physical form nuclear material 8. Maximum amount that licensee may possess at any one time under this license						
No. CDCW55	SA, Inc. Model single source to exceed the					

- B. Americium-241

 B. Sealed neutron sources (AEA Technology/QSA, Inc. Model No. AMNV.997; Isotope Product Model Nos. Am1.NO2, 3021 or 3027)
- C. Cesium-137

 C. Sealed source (CPN International, Inc. CPN Model CPN-131)
- D. Americium-241

 D. Sealed source (CPN International, Inc. CPN Model CPN-131)

- B. 50 millicuries total. No single source to exceed the maximum activity specified in the certificate of registration issued by NRC or an Agreement State.
- C. 10 millicuries total. No single source to exceed the maximum activity specified in the certificate of registration issued by NRC or an Agreement State.
- D. 50 millicuries total. No single source to exceed the maximum activity specified in the certificate of registration issued by NRC or an Agreement State.

NRC FORM 374A	U.S. NUCLEAR REGULATORY COMMISSION		PAGE	2	of	7	PAGES
MATERIALS LICENSE	License Number 50-23276-01						
	Docket or Reference Num 030-20447	ber					
		Amendment No. 11					
		•					

- 6. Byproduct, source, and/or special nuclear material
- 7. Chemical and/or physical form
- Maximum amount that licensee may possess at any one time under this license

E. Cesium-137

- E. Sealed sources (TN
 Technologies Model 57157C;
 Kay-Ray/Sensall Source
 Series Model 7700-Y; Ohmart
 Models A-2100 or A-2102;
 Minnesota Mining and
 Manufacturing Model 4F6S or
 4F3D; Monsanto Model
 24148; Amersham Model
 CDC.700/CDC.711m;
 Gamma Industries Model
 S-10-1A; Amersham Model
 CKC.P1; or U.S. Nuclear
 Model 3280)
- E. 880 millicuries total. No single source to exceed the maximum activity specified in the certificate of registration issued by the U.S. Nuclear Regulatory Commission or an Agreement State.

- 9. Authorized use:
 - A. and B. In Troxler Electronic Laboratories, Model No. 3400 Series portable gauging devices for

measuring physical properties of materials.

C. and D. In CPN International, Inc., Model 500 Series portable gauging devices for measuring

physical properties of materials.

E. For the measurement of physical properties of materials, in compatible fixed gauging devices in accordance with the certificate of registration issued by the U.S. Nuclear Regulatory Commission under 10 CFR 32.210 or with an Agreement State and which have been distributed in accordance with a Commission or Agreement State specific license authorizing distribution to persons specifically authorized by a Commission or Agreement State license to receive, possess, and use the devices.

CONDITIONS

- 10. Licensed material may be used or stored at the licensee's facilities located at:
 - A. For material described in Items 6.A. through 6.D., licensee's warehouse and water building located at the Hawk Inlet facility on Admiralty Island.
 - B. For material described in Item 6.E., Green's Creek Mine/Mill site on Admiralty Island, 18 air miles southwest of Juneau, Alaska, and at Hawk Inlet Warehouse on Admiralty Island.
 - C. For material described in Items 6.A. through 6.D., temporary job sites anywhere in the United States where the U.S. Nuclear Regulatory Commission maintains jurisdiction for regulating the use of licensed material, including areas of exclusive Federal jurisdiction within Agreement States.

NRC FORM 374A	U.S. NUCLEAR REGULATORY COMMISSION		PAGE	3	of	7	PAGES
		License Number 50-23276-01					
	MATERIALS LICENSE SUPPLEMENTARY SHEET	Docket or Reference Numb 030-20447	er				
		Amendment No. 11					

If the jurisdiction status of a Federal facility within an Agreement State is unknown, the licensee should contact the federal agency controlling the job site in question to determine whether the proposed job site is an area of exclusive Federal jurisdiction. Authorization for use of radioactive materials at job sites in Agreement States not under exclusive Federal jurisdiction shall be obtained from the appropriate state regulatory agency.

- 11. A. Licensed material shall only be used by, or under the supervision and in the physical presence of, individuals who have received the training described in application dated February 10, 2003.
 - B. Licensed material shall be used by, or under the supervision of individuals who have received the training described in facsimile dated August 13, 2003. The licensee shall maintain records of individuals designated as users for 3 years following the last use of licensed material by the individual.
- 12. A. The Radiation Safety Officer (RSO) for this license is Michael Weaver.
 - B. Before assuming the duties and responsibilities as RSO for this license, the individual shall have successfully completed one of the training courses described in Criteria in Section 8.7.1 of NUREG-1556, Volume 4, dated October 1998
- 13. A. Sealed sources shall be tested for leakage and/or contamination at intervals not to exceed the intervals specified in the certificate of registration issued by U.S. Nuclear Regulatory Commission under 10 CFR 32.210 or by an Agreement State.
 - B. In the absence of a certificate from a transferor indicating that a leak test has been made within the intervals specified in the certificate of registration issued by U.S. Nuclear Regulatory Commission under 10 CFR 32.210 or by an Agreement State prior to the transfer, a sealed source or detector cell received from another person shall not be put into use until tested and the results received.
 - C. Sealed sources need not be leak tested if they are in storage and are not being used. However, when they are removed from storage for use or transferred to another person, and have not been tested within the required leak test interval, they shall be tested before use or transfer. No sealed source shall be stored for a period of more than 10 years without being tested for leakage and/or contamination.
 - D. The leak test shall be capable of detecting the presence of 0.005 microcurie (185 becquerels) of radioactive material on the test sample. If the test reveals the presence of 0.005 microcurie (185 becquerels) or more of removable contamination, a report shall be filed with the U.S. Nuclear Regulatory Commission in accordance with 10 CFR 30.50(c)(2), and the source shall be removed immediately from service and decontaminated, repaired, or disposed of in accordance with Commission regulations. The report shall be filed within 5 days of the date the leak test result is known with the U.S. Nuclear Regulatory Commission, Region IV, 612 East Lamar Boulevard, Suite 400, Arlington, Texas 76011-4125, ATTN: Director, Division of Nuclear Materials Safety. The report shall specify the source involved, the test results, and corrective action taken.

PAGE 4 of 7 PAGES	
License Number 50-23276-01	
Docket or Reference Number 030-20447	
Amendment No. 11	_
	License Number 50-23276-01 Docket or Reference Number 030-20447

- E. Tests for leakage and/or contamination shall be performed by persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. In addition, the licensee is authorized to collect leak test samples but not perform the analysis; analysis of leak test samples must be performed by persons specifically licensed by the Commission or an Agreement State to perform such services.
- F. Records of leak test results shall be kept in units of microcuries and shall be maintained for 3 years.
- 14. Sealed sources or source rods containing licensed material shall not be opened or sources removed or detached from source rods or gauges by the licensee, except as specifically authorized.
- 15. The licensee shall conduct a physical inventory every 6 months, or at other intervals approved by the U.S. Nuclear Regulatory Commission, to account for all sealed sources and/or devices received and possessed under the license. Records of inventories shall be maintained for 5 years from the date of each inventory, and shall include the radionuclides, quantities, manufacturer's name and model numbers, and the date of the inventory.
- 16. Except for maintaining labeling as required by 10 CFR Part 20 or 71, the licensee shall obtain authorization from the U.S. Nuclear Regulatory Commission before making any changes in the sealed source, device, or source-device combination that would alter the description or specifications as indicated in the respective Registration Certificates issued either by the Commission pursuant to 10 CFR 32.210 or by an Agreement State.
- 17. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gauge or its container must be locked when in transport. A minimum of two independent physical controls that form tangible barriers to secure portable gauges from unauthorized removal whenever the portable gauge is not under the control and constant surveillance of the licensee are required.
- 18. When performing tests at temporary job sites, the authorized user shall not leave the moisture/density gauge unattended. Upon completion of tests the device shall be locked in the licensee's vehicle or a secure building to prevent unauthorized use, loss, or theft.
- 19. Any cleaning, maintenance, or repair of the gauges that requires detaching the source or source rod from the gauge shall be performed only by the manufacturer or other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services.
- 20. A. If the licensee uses unshielded sealed sources extended more than 3 feet below the surface, the licensee shall use surface casing that extends from the lowest depth to 12 inches above the surface and other appropriate procedures to reduce the probability of the source or probe becoming lodged below the surface. If it is not feasible to extend the casing 12 inches above the surface, the licensee shall implement procedures to ensure that the cased hole is free of obstruction before making measurements.

PAGES

- B. If a sealed source or probe containing sealed sources becomes lodged below the surface and it becomes apparent that efforts to recover the sealed source or probe may not be successful, the licensee shall notify the U.S. Nuclear Regulatory Commission and submit the report required by 10 CFR 30.50(b)(2) and (c). The licensee shall not abandon the sealed source or probe without obtaining the Commission's prior written consent.
- 21. A. Each gauge shall be tested for the proper operation of the on-off mechanism (shutter) and indicator, if any, at intervals not to exceed 6 months or at such longer intervals as specified in the certificate of registration issued by the U.S. Nuclear Regulatory Commission pursuant to 10 CFR 32.210 or the equivalent regulations of an Agreement State.
 - B. Notwithstanding the periodic on-off mechanism (shutter) and indicator test, the requirement does not apply to gauges that are stored, not being used, and have the shutter lock mechanism in a locked position. The gauges exempted from this periodic test shall be tested before use.
- 22. A. Installation, initial radiation surveys, relocation, or removal from service shall be performed only by Michael Weaver, Jimmy Hancock, Carl Tenney, Justin Erickson, Ted Morales, Sherri Williamson, or Pascuala Asetre, or by persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services.
 - B. The following services shall not be performed by the licensee: dismantling, alignment, replacement, disposal of the sealed sources and non-routine maintenance or repair of components related to the radiological safety of the gauge. These services shall be performed only by persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services.
- 23. The licensee may initially mount a gauge if permitted by the certificate of registration issued by the U.S. Nuclear Regulatory Commission or an Agreement State and under the following conditions:
 - A. the gauge must be mounted in accordance with written instructions provided by the manufacturer.
 - B. the gauge must be mounted in a location compatible with the "Conditions of Normal Use" and "Limitations and/or Other Considerations of Use" in the certificate of registration issued by the U.S. Nuclear Regulatory Commission or an Agreement State.
 - C. the on-off mechanism (shutter) must be locked in the off position, if applicable, or the source must be otherwise fully shielded.
 - D. the gauge must be received in good condition (i.e., package was not damaged).
 - E. the gauge must not require any modification to fit in the proposed location.

Mounting does not include electrical connection, activation or operation of the gauge. The source must remain fully shielded and the gauge may not be used until it is installed and made operational by a person specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such operations.

U.S. NUCLEAR REGULATORY COMMISSION		PAGE	6	of	7	PAGES
MATERIALS LICENSE	License Number 50-23276-01					
	Docket or Reference Numb 030-20447	er				
	Amendment No. 11					
	MATERIALS LICENSE	License Number 50-23276-01 MATERIALS LICENSE Docket or Reference Number 030-20447	License Number 50-23276-01 MATERIALS LICENSE Docket or Reference Number 030-20447	MATERIALS LICENSE SUPPLEMENTARY SHEET License Number 50-23276-01 Docket or Reference Number 030-20447	License Number 50-23276-01 MATERIALS LICENSE SUPPLEMENTARY SHEET License Number 50-23276-01 Docket or Reference Number 030-20447	License Number 50-23276-01 MATERIALS LICENSE Docket or Reference Number 030-20447

- 24. A. The licensee may maintain, repair, or replace device components that are not related to the radiological safety of the device containing byproduct material and that do not result in the potential for any portion of the body to come into contact with the primary beam or in increased radiation levels in accessible areas.
 - B. The licensee may not maintain, repair, or replace any of the following device components: the sealed source, the source holder, source drive mechanism, on-off mechanism (shutter), shutter control, or shielding, or any other component related to the radiological safety of the device, except as provided otherwise by specific condition of this license.
- 25. Prior to initial use and after installation, relocation, dismantling, alignment, or any other activity involving the source or removal of the shielding, the licensee shall assure that a radiological survey is performed to determine radiation levels in accessible areas around, above, and below the gauge with the shutter open. This survey shall be performed only by persons authorized to perform such services by the U.S. Nuclear Regulatory Commission or an Agreement State.
- 26. The licensee shall operate each device containing licensed material within the manufacturer's specified temperature and environmental limits such that the shielding and shutter mechanism of the source holder are not compromised.
- 27. The licensee shall assure that the shutter mechanism of each device is locked in the closed position during periods when a portion of an individual's body may be subject to the direct radiation beam. The licensee shall review and modify, as appropriate, its "lock-out" procedures whenever a new device is obtained to incorporate the device manufacturer's recommendations.

28. The licensee is authorized to transport licensed material only in accordance with the provisions of 10 CFR Part 71, "Packaging and Transportation of Radioactive Material."

NRC FORM 374A	U.S. NUCLEAR REGULATORY COMMISSION	PAG	E	7	of	7	PAGES
	License Number 50-23276-01					_	
MATERIALS LICENSE SUPPLEMENTARY SHEET		Docket or Reference Number 030-20447					
	Amendment No. 11						

- 29. Except as specifically provided otherwise in this license, the licensee shall conduct its program in accordance with the statements, representations, and procedures contained in the documents, including any enclosures, listed below. The U.S. Nuclear Regulatory Commission's regulations shall govern unless the statements, representations, and procedures in the licensee's application and correspondence are more restrictive than the regulations.
 - A. Application dated February 10, 2003 (ML030930265)
 - B. Facsimile dated August 13, 2003 (ML032260703)
 - C. Application and letter dated March 6, 2008 (ML081020162)
 - D. Letter dated May 1, 2008 (ML081440068)



FOR THE U.S. NUCLEAR REGULATORY COMMISSION

Date November 19, 2010

Ву

/RA/

Michelle Simmons, Health Physicist Nuclear Materials Safety, Branch B Region IV Arlington, Texas 76011