

Facility: Monticello			Date of Exam: 12/06/10			Operating Test Number: MNGP 2010											
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M (*)		
		1			2			3			4						
		CREW POSITION			CREW POSITION			CREW POSITION			CREW POSITION						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P		R	I	U
RO <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX													1	1	0	
	NOR			1			1			1			1	1	1	1	
	I/C			3 4			3 5			6 9			3 4	4	4	2	
	MAJ			7			7			8			8	2	2	1	
	TS													0	2	2	
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX		6			6			2			5		1	1	0	
	NOR													1	1	1	
	I/C		2 5			2 8			3 7			6 7		4	4	2	
	MAJ		7			7			8			8		2	2	1	
	TS													0	2	2	
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX													1	1	0	
	NOR	1			1			1			1			1	1	1	
	I/C	2 3 4 5			2 5			3 6 7			3 4			4	4	2	
	MAJ	7			7			8			8			2	2	1	
	TS	2 3			2 4			4 5			2 3			0	2	2	
Instructions: <ol style="list-style-type: none"> Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls (ATC)" and "balance-of-plant (BOP)" positions. Instant SROs must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an Instant SRO <i>additionally</i> serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position. Reactivity manipulations may be conducted under normal or <i>controlled</i> abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis. Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns. 																	

Facility: Monticello Date of Exam: 12/06/10 Operating Test Number: 10-1

A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M(*)		
		5			6												
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N						
		S R O	A T C	B O P													
													R	I	U		
RO <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U	RX													1	1	0	
	NOR			1			1							1	1	1	
	I/C			4 5			3							4	4	2	
	MAJ			6										2	2	1	
	TS													0	2	2	
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/> SRO-U	RX		2			4								1	1	0	
	NOR													1	1	1	
	I/C		3 7			2								4	4	2	
	MAJ		6											2	2	1	
	TS													0	2	2	
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/> SRO-U	RX													1	1	0	
	NOR	1												1	1	1	
	I/C	3 4												4	4	2	
	MAJ	6												2	2	1	
	TS	3 4			2									0	2	2	

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls (ATC)" and "balance-of-plant (BOP)" positions. Instant SROs must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an Instant SRO *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.