



Nuclear Regulatory Commission
 Exhibit # - NRC000057-MA-BD01
 Docket # - 07007015
 Identified: 01/25/2011

Admitted: 01/25/2011
 Rejected:

Withdrawn:
 Stricken:

NUCLEAR REGULATORY COMMISSION
 Copyrighted material - used with permission of the American Nuclear Society
 CODES AND STANDARDS

NRC000057
ANSI/ANS-8.1-1998


REFERENCE

American Nuclear Society

**nuclear criticality safety in operations
 with fissionable material outside reactors**

an American National Standard

ANSI/ANS-8.1-1998



published by the
American Nuclear Society
 555 North Kensington Avenue
 La Grange Park, Illinois 60525 USA

ANSI/ANS-8.1-1998

**American National Standard
for Nuclear Criticality Safety
in Operations with Fissionable
Materials Outside Reactors**

Secretariat
American Nuclear Society

Prepared by the
**American Nuclear Society
Standards Committee
Working Group ANS-8.1**

Published by the
**American Nuclear Society
555 North Kensington Avenue
La Grange Park, Illinois 60526 USA**

Approved September 9, 1998
by the
American National Standards Institute, Inc.

American National Standard

Designation of this document as an American National Standard attests that the principles of openness and due process have been followed in the approval procedure and that a consensus of those directly and materially affected by the standard has been achieved.

This standard was developed under procedures of the Standards Committee of the American Nuclear Society; these procedures are accredited by the American National Standards Institute, Inc., as meeting the criteria for American National Standards. The consensus committee that approved the standard was balanced to ensure that competent, concerned, and varied interests have had an opportunity to participate.

An American National Standard is intended to aid industry, consumers, governmental agencies, and general interest groups. Its use is entirely voluntary. The existence of an American National Standard, in and of itself, does not preclude anyone from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard.

By publication of this standard, the American Nuclear Society does not insure anyone utilizing the standard against liability allegedly arising from or after its use. The content of this standard reflects acceptable practice at the time of its approval and publication. Changes, if any, occurring through developments in the state of the art, may be considered at the time that the standard is subjected to periodic review. It may be reaffirmed, revised, or withdrawn at any time in accordance with established procedures. Users of this standard are cautioned to determine the validity of copies in their possession and to establish that they are of the latest issue.

The American Nuclear Society accepts no responsibility for interpretations of this standard made by any individual or by any ad hoc group of individuals. Requests for interpretation should be sent to the Standards Department at Society Headquarters. Action will be taken to provide appropriate response in accordance with established procedures that ensure consensus on the interpretation.

Comments on this standard are encouraged and should be sent to Society Headquarters.

Published by

**American Nuclear Society
555 North Kensington Avenue
La Grange Park, Illinois 60526 USA**

Copyright © 1998 by American Nuclear Society. All rights reserved.

Any part of this standard may be quoted. Credit lines should read "Extracted from American National Standard ANSI/ANS-8.1-1998 with permission of the publisher, the American Nuclear Society." Reproduction prohibited under copyright convention unless written permission is granted by the American Nuclear Society.

Printed in the United States of America

Table 6
Limits for Uniform Aqueous Solutions of Low-Enriched Uranium
 (see Reference [3])

Parameter	Enrichment, wt% ²³⁵ U	Subcritical Limit	
		UO ₂ F ₂	UO ₂ (NO ₃) ₂
Mass, kg ²³⁵ U	10.0	1.07	1.47
	5.0	1.64	3.30
	4.0	1.98	6.50
	3.0	2.75	--
	2.0	8.00	--
Cylinder diameter, cm	10.0	20.1	25.2
	5.0	26.6	42.7
	4.0	30.2	58.6
	3.0	37.4	--
	2.0	63.0	--
Slab thickness, cm	10.0	8.3	11.9
	5.0	12.6	23.4
	4.0	15.1	33.7
	3.0	20.0	--
	2.0	36.5	--
Volume, L	10.0	14.8	26.7
	5.0	30.6	111.0
	4.0	42.7	273.0
	3.0	77.0	--
	2.0	340.0	--
Concentration, g U/L	10.0	123.0	128.0
	5.0	261.0	283.0
	4.0	335.0	375.0
	3.0	470.0	--
	2.88	--	594.9 ^(a)
	2.0	770.0	--
	1.45	1190.0 ^(a)	--

(a) Saturated solution

Table 7
Limits for Uniform Aqueous Solutions of Pu(NO₃)₄ Containing ²⁴⁰Pu
 (see Reference [4])

Parameter	Subcritical Limit		
	≥5 wt% ²⁴⁰ Pu ≤1 wt% ²⁴¹ Pu	≥15 wt% ²⁴⁰ Pu ≤6 wt% ²⁴¹ Pu	≥25 wt% ²⁴⁰ Pu ≤15 wt% ²⁴¹ Pu
Mass, kg Pu	0.57	0.78	1.02
Cylinder diameter, cm	17.4	19.5	21.3
Slab thickness, cm	6.7	8.0	9.2
Volume, L	10.0	13.6	17.2
Concentration, g Pu/L	7.8	8.9	10.2
H/Pu	3400	2980	2600
Areal density, g Pu/cm ²	0.28	0.34	0.4