

**PR 52  
(76FR03540)**

DOCKETED  
USNRC

March 16, 2011 (4:00 pm)

OFFICE OF SECRETARY  
RULEMAKINGS AND  
ADJUDICATIONS STAFF

# PUBLIC SUBMISSION

**As of:** March 16, 2011  
**Received:** March 15, 2011  
**Status:** Pending\_Post  
**Tracking No.** 80c078c0  
**Comments Due:** April 05, 2011  
**Submission Type:** Web

**Docket:** NRC-2010-0134  
ABWR Aircraft Impact Design Certification

**Comment On:** NRC-2010-0134-0001  
U.S. Advanced Boiling Water Reactor Aircraft Impact Design Certification Amendment

**Document:** NRC-2010-0134-DRAFT-0012  
Comment on FR Doc # 2011-00993

---

## Submitter Information

**Name:** Thomas Shadis  
**Address:**  
715 Buckland Ct  
Denville, NJ, 07834

---

## General Comment

In light of the recent events in Japan, and the level of water repeatedly exposing the nuclear rods - isn't there a simpler solution to relying on pumps to supply the cooling water? If the plant was mandated to have a reservoir of water that could gravity feed water via manual valves to keep the rods covered - diesel backups and battery backups would be a non issue.

Template = SECY-067

DS10