Docket Nos: 50-438 and 50-439

Tennessee Valley Authority ATTN: Mr. Godwin Williams, Jr. Manager of Power 830 Power Building Chattanooga, Tennessee 37201

Gentlemen:

NRC FORM 318 (9.76) NRCM 0240

SUBJECT: FUEL HANDLING ACCIDENT - BELLEFONTE NUCLEAR PLANT, UNITS 1 AND 2

MAR 1 6 1977

We are in the process of evaluating a refueling accident inside the containment building since it may not have been adequately considered in the licensing review.

Based on our preliminary review, potential site boundary radiation exposures due to such an accident at your facility would be within the exposure guidelines of 10 CFR Part 100 if containment isolation can be effected in a timely fashion.

In order to confirm these results and determine if the acceptance criteria of Standard Review Plan 15.7.4 are met, and to document the factors involved in the evaluation, we request that you provide a detailed evaluation of the potential consequences of such an accident at your facility in your PSAR. Your analysis should utilize assumptions comparable to those given in Regulatory Guide 1.25, "Assumptions Used for Evaluating the Potential Radiological Consequences of a ruel Handling Accident in the Fuel Handling and Storage Pacility for Boiling and PRESSurized Water Reactors," assuming the worst Single failure. It should consider, in a conservative manner, any mixing in the containment atmosphere which would delay release of material, any filtration of effluent which would reduce releases, and any automatic isolation of the containment which would limit releases. Your analysis should utilize parameters (e.g., maximum allowable valve closure times) as limited by the proposed technical specifications. Clearly indicate any credit taken in the analyses for nonsafety grade equipment and provide appropriate justification for this credit. Detailed questions which should be addressed in your response are enclosed.

OFFICE HB-30 PM	LWR-3 BC		*	
SURNAME WPike/cz	OPERI FES			2
DATE → 3////77	3/// 177			
		a share and a start of the	 L	

You should compare proposed technical specifications (e.g., valve closure times, filter-testing) with results of the above analyses to show that parameters important in the evaluation are maintained at levels which will assure that conservatively calculated offsite consequences are well within the exposure guidelines of 10 CFR Part 100 over the plant lifetime.

This request for generic information was approved by GAO under a blanket clearance number B-180225 (R0072). This clearance expires July 31, 1977.

Original sleved by A.W. Drozerick

Olan D. Parr, Chief Light Water Reactors Branch No. 3 Division of Project Management Office of Nuclear Reactor Regulation

1 6 97

Enclosure: Information Needed to Evaluate Containment Refueling Accident

cc w/enclosures: See Next Page

			1.	- S. (1997)			10		1	and the second second	2	~	<u> </u>				
		OFFIC	E≯								*		÷				
1. A. A.	and	SURNAM	E 🍽	20 ° 50 50 7 K						arta Barrado de Carlos		* *				λ.	
		DAT	<u>)</u>						61 2 - But							i di serie d Serie di serie di seri	
					*	<u>^</u>	r	2				19 Jahr 1		16.00	 		<u> </u>

NRC FORM 318 (9-76) NRCM 0240

Tennessee Valley Authority

12

cc: Herbert S. Sanger, Jr., Esq. General Counsel Tennessee Valley Authority 629 New Sprankle Building Knoxville, Tennessee 37902

> Mr. E. G. Beasley Tennessee Valley Authority 400 Commerce Avenue, W9C 165 Knoxville, Tennessee 37902

Mr. T. Spink Licensing Engineer Tennessee Valley Authority 303 Power Building Chattanooga, Tennessee 37401

AR 1 6 1977

2

INFORMATION NEEDED TO EVALUATE CONTAINMENT ISOLATION CAPABILITY DURING REFUELING ACCIDENT

- Describe all instrumentation which would detect a fuel-handling accident (FHA) inside containment. Your response should include the following information:
 - a) instrumentation function, e.g., close containment isolation valves;
 - b) type of instruments and setpoints, e.g., mr/hr, and normal background reading;
 - c) safety class, redundancy, power sources, and technical specification
 requirements;
 - d) a description of instrument response following a FHA taking into account instrument location;
 - e) response time for the instrument to signal containment isolation after the FHA.
- 2) Describe the response of the containment isolation and ventilation values following the FHA. Include value closure times including expected value closure time as well as technical specification requirements.
- 3) Provide the transit time from the point where a monitor can respond to a release from the FHA to the inboard isolation valve based on the maximum air velocity (peak centerline velocity) at maximum exhaust flow. Also include the transit time based on average velocity and normally expected air flows. Conservatively assume that the FHA is a puff release from the pool at a point closest to an exhaust grill.
- 4) Provide drawings of the containment which clearly show the location of the radiation monitors relative to the ventilation exhaust system including all exhaust inlets, filters, dampers, and duct arrangement up to the outboard isolation values.

- 5) If the summation of the instrument response time (question 1.e) and value dampers closure time (question 2) is greater than the gas transit time (question 3), provide an analysis as to the volume and amount of radioactive exhaust air which could be released. Your response should include the following:
 - a) duct sizes;
 - b) maximum (peak) air velocity;
 - c) average air velocity;
 - d) containment isolation valve closure characteristics;
 - e) exhaust system flow rates;
 - f) methodology used to calculate gas transit times from the pool surface to the exhaust system;
 - g) air velocity profiles over the pool surface. You should consider the effects of pool water temperature on air flow trajectories.
- 6) Describe any charcoal filters which would mitigate the consequence of the FHA. If so, include the following information: type (e.g., kidney), redundancy, power sources, safety grade, technical specification requirements.

In responding to the above, reference can be made to specific pages or figures in the Safety Analysis Report.

DISTRIBUTION w/enclosures

MAR 1 6 1977

 ${\cal G}_{i} = {\cal G}_{i}$

Docket File NRC PDR Local PDR OELD LWR-3 File 0. Parr L. Crocker R. Boyd D. Vassallo F. Williams H. Smith R. Heineman H. Denton R. Vollmer R. Tedesco W. Gammill .D. Bunch G. Chipman J. Miller IE (3) K. Goller V. Stello J. Yore, ASLBP A. Rosenthal, ASCAB M. Rushbrook bcc: ACRS (16) J. Buchanan, NSIC T. Abernathy, TIC Project Manager W. Pile