

Facility: Point Beach U1/U2		Date of Exam: 04/25 – 05/05/2011		Operating Test No.: 2011301													
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U M (*)		
		1			2			3			4						
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P				
														R	I	U	
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX	1				1								1	1	1	0
	NOR	1				1				1				2	1	1	1
	I/C	5				1				5				11	4	4	2
	MAJ	1				2				1				4	2	2	1
	TS	4												4	0	2	2
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX		1					1						2	1	1	0
	NOR					1	1							2	1	1	1
	I/C		2			4	6							12	4	4	2
	MAJ		1			2	1							4	2	2	1
	TS						4							4	0	2	2
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX				1			1						2	1	1	0
	NOR			2	2									4	1	1	1
	I/C			3	5			1						9	4	4	2
	MAJ			1	2			1						4	2	2	1
	TS				3									3	0	2	2
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX														1	1	0
	NOR														1	1	1
	I/C														4	4	2
	MAJ														2	2	1
	TS														0	2	2

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls (ATC)" and "balance-of-plant (BOP)" positions; Instant SROs must do one scenario, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.

Facility: Point Beach U1/U2		Date of Exam: 04/25 – 05/05/2011			Operating Test No.: 2011301												
A P P L I C A N T	E V E N T T Y P E	Scenarios												T O T A L	M I N I M U		
		1			2			3			4						
		CREW POSITION			CREW POSITION			CREW POSITION			CREW POSITION						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P				
															M(*)		
															R	I	U
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX							1					1	2	1	1	0
	NOR							1						1	1	1	1
	I/C							6				2		8	4	4	2
	MAJ							1				2		3	2	2	1
	TS							4						4	0	2	2
RO <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX								1					1	1	1	0
	NOR												1	1	1	1	1
	I/C								1				6	7	4	4	2
	MAJ								1				2	3	2	2	1
	TS													0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX													1	1	0	
	NOR													1	1	1	
	I/C													4	4	2	
	MAJ													2	2	1	
	TS													0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX													1	1	0	
	NOR													1	1	1	
	I/C													4	4	2	
	MAJ													2	2	1	
	TS													0	2	2	

Instructions:

3. Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls (ATC)" and "balance-of-plant (BOP)" positions; Instant SROs must do one scenario, including at least two instrument or component (I/C) malfunctions and one major transient, in the TC position.
4. Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
4. Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.