



AMERICAN WARNING AND VENTILATING, INC.
SUN-P-4950-87
(BY VENTILATION CONTRACTOR)

SPECIFICATIONS
BLADES: 18 GAUGE STEEL
FRAME: 18 GAUGE STEEL
ANLES: 90° CHAMFERED VITEL
BEARINGS: 3/16" DIA. BALL BEARINGS STANDARD
LUBRICANT: 1 QUART PER HOUR
FINISH: 1 SPRAY AFTER DEGRASSING & BLASTING
MAXIMUM STATIC PRESSURE: 1.5" H₂O
MAXIMUM VELOCITY: 4500 FPM
MAXIMUM TEMPERATURE: 270°

NO.	DESCRIPTION	DATE
1	ISSUED FOR CONSTRUCTION	11-15-68
2	ISSUED FOR CONSTRUCTION	11-15-68
3	ISSUED FOR CONSTRUCTION	11-15-68
4	ISSUED FOR CONSTRUCTION	11-15-68
5	ISSUED FOR CONSTRUCTION	11-15-68
6	ISSUED FOR CONSTRUCTION	11-15-68
7	ISSUED FOR CONSTRUCTION	11-15-68
8	ISSUED FOR CONSTRUCTION	11-15-68
9	ISSUED FOR CONSTRUCTION	11-15-68
10	ISSUED FOR CONSTRUCTION	11-15-68
11	ISSUED FOR CONSTRUCTION	11-15-68
12	ISSUED FOR CONSTRUCTION	11-15-68
13	ISSUED FOR CONSTRUCTION	11-15-68
14	ISSUED FOR CONSTRUCTION	11-15-68
15	ISSUED FOR CONSTRUCTION	11-15-68
16	ISSUED FOR CONSTRUCTION	11-15-68
17	ISSUED FOR CONSTRUCTION	11-15-68
18	ISSUED FOR CONSTRUCTION	11-15-68
19	ISSUED FOR CONSTRUCTION	11-15-68
20	ISSUED FOR CONSTRUCTION	11-15-68