

REGULATORY INFORMATION DISTRIBUTION SYSTEM (RIDS)
DISTRIBUTION FOR INCOMING MATERIAL 50-305

REC: STELLO V
NRC

ORG: JAMES E W
WI PUB SVC

DOCDATE: 02/20/78
DATE RCVD: 02/23/78

DOCTYPE: LETTER NOTARIZED: NO
SUBJECT:
RESPONSE TO NRC REQUEST FOR INFO. CONCERNING THE REACTOR CAVITY
ANNULUS SEAL RING & BIOLOGICAL SHIELDING.

COPIES RECEIVED
LTR 1 ENCL 0

PLANT NAME: KEWAUNEE

REVIEWER INITIAL: XRL
DISTRIBUTOR INITIAL:

***** DISTRIBUTION OF THIS MATERIAL IS AS FOLLOWS *****

NOTES:

1. SEND 4 COPIES OF ALL MATERIAL TO I&E
2. LAWRENCE(OELD) - 1 COPY ALL MATERIAL

GENERAL DISTRIBUTION FOR AFTER ISSUANCE OF OPERATING LICENSE.
(DISTRIBUTION CODE A001)

FOR ACTION: BR CHIEF SCHWENCER**LTR ONLY(7)

INTERNAL:	REG FILE**LTR ONLY(1)	NRC PDR**LTR ONLY(1)
	I & E**LTR ONLY(2)	OELD**LTR ONLY(1)
	HANAUER**LTR ONLY(1)	CHECK**LTR ONLY(1)
	EISENHUT**LTR ONLY(1)	SHAO**LTR ONLY(1)
	BAER**LTR ONLY(1)	BUTLER**LTR ONLY(1)
	GRIMES**LTR ONLY(1)	J COLLINS**LTR ONLY(1)
	J. MCGOUGH**LTR ONLY(1)	

EXTERNAL: LPDR'S
KEWAUNEE, WI**LTR ONLY(1)
TIC**LTR ONLY(1)
NSIC**LTR ONLY(1)
ACRS CAT B**LTR ONLY(16)

DISTRIBUTION: LTR 40 ENCL 0
SIZE: 1P

CONTROL NBR: 780550083 MA 4

***** THE END *****

60


WISCONSIN PUBLIC SERVICE CORPORATION

Public Service

P.O. Box 1200, Green Bay, Wisconsin 54305

February 20, 1978

Mr. Victor Stello, Jr., Director
 Division of Operating Reactors
 Office of Nuclear Reactor Regulation
 U. S. Nuclear Regulatory Commission
 Washington, D. C. 20555



Dear Sir:

Docket 50-305
 Operating License DPR-43
 Letter to all PWR Licensees from
Mr. Victor Stello, Jr. dated February 2, 1978

The referenced letter requested information in regard to the Kewaunee Plant's reactor cavity annulus seal ring and biological shielding.

A description of the reactor vessel seal ring is included in the FSAR on page 9.5-5, which states:

"The reactor vessel flange is sealed at the bottom of the reactor refueling cavity by an elastomeric seal ring which prevents leakage of refueling water from the refueling cavity. This seal is installed after reactor cooldown but prior to flooding the cavity for refueling operations."

Figure 9.5-1 of the FSAR provides clarification as to the type of seal employed at the Kewaunee Plant.


As indicated in the FSAR, the reactor cavity seal ring is designed to be removed except for refueling periods.

No additional biological shielding is assembled on the refueling pool floor about the reactor vessel head at the Kewaunee Plant during plant operation.

Very truly yours,

E. W. James
 Senior Vice President
 Power Supply & Engineering

sa



A001/s *
 1/0

RECEIVED DOCUMENT
SEP 11 1952

570 SE. 23 PM 2 02

U.S. AIR
DISTRIBUTION SERVICES
BRANCH