

SAFETY EVALUATION REPORT
Docket No. 71-3043
Model No. MFC-1
Japanese Competent Authority Certificate No. J/105/AF-96
Revision 2

SUMMARY

The Department of Transportation (DOT) requested NRC's recommendation concerning the revalidation of the Type B configuration of the Model No. MFC-1 package, Japanese Competent Authority Certificate No. J/105/AF-96, Rev. 2. The package is currently licensed under International Atomic Energy Agency (IAEA) *Regulations for Safe Transport of Radioactive Material*, TS-R-1, Rev. 2005, by the Japanese Competent authority. The package is designed to transport unirradiated Pressurized Water Reactor (PWR) fuel assemblies. The PWR fuel is fabricated from either uranium dioxide (UO₂) pellets or Gadolinia UO₂ pellets. The allowable Uranium-235 enrichment in the fuel assemblies is five weight percent or less. The package is suitable for both sea and road transport.

Based on the statements and representations in the application, as supplemented, the NRC recommends revalidation of the Type B configuration of Japanese Competent Authority Certificate No. J/105/AF-96, Rev. 2, for use in the United States, with the following conditions:

- (1) packages must be fabricated in accordance with Figures III-A-2, -5, and -8 in Appendix III and Table 1-C.1 in Section 1 of the Safety Analysis Report;
- (2) the package contents are limited to those specified in the Japanese Competent Authority Certificate; and
- (3) transport by air is prohibited.

1.0 GENERAL INFORMATION

1.1 Packaging

The NRC previously recommended revalidation of a Type A configuration of the package which has slight differences in design [ML110980406]. Engineering drawings for the two configurations were reviewed. Slight differences for internal components between the Type B configuration and the Type A configuration were identified. These differences included small dimensional changes and the use of different designs for both clamps and frames. The air valve design employed in the Type B configuration also differed from the design used in the Type A configuration.

1.2 Findings

Based on review of the statements and representations in the application, the staff concludes the Type B configuration of the MFC-1 package has been adequately described per the International Atomic Energy Agency (IAEA) requirements of TS-R-1,

Rev. 2005. The TS-R-1 regulations relevant to this package with respect to general information are listed in Section 1.3.

1.3. IAEA Regulations Applicable to General Information Evaluation

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
813	An application for approval shall include all information necessary to satisfy the competent authority that the design meets the requirements of para. 671 and a specification of the applicable quality assurance program as required in para. 310.	Requirement met. The staff reviewed the application, as supplemented, and finds that the requirements of para. 671 are met and that the applicant's quality assurance program is satisfactory.

2.0 STRUCTURAL EVALUATION

2.1. Packaging

NRC staff reviewed the application which tabulated and illustrated the differences between the Type A and Type B configurations of the MFC-1 package. These differences included variations between the clamping frame, top edge of cross frame, length of cross frame, shock mount frame, lateral side stabilizers, and air valves. These differences were also described in Section I-C, Chapter C.2, of the Safety Analysis Report (SAR) submitted with the original DOT revalidation request letter dated February 24, 2010. Figures I-C.8 through I-C.20 also illustrate the differences between the Type A and Type B configurations. The only difference between the two configurations which had an impact on safety was the modification of the top edge of the cross frame under Normal Conditions of Transport. This difference was evaluated in Section A.5.3 of the SAR and was bounded by the Type A configuration due to size.

Staff also reviewed the description of the prototype testing for the MFC-1 package in Section II-F of the SAR. Staff did not see if the Type A and/or Type B configuration was used for testing. However, staff did note that the prototype packaging was almost identical in weight, dimension, and materials of construction per Table II-F.3.

2.2. Structural Findings

The Type B configuration of the MFC-1 package and its authorized contents, restricted to unirradiated PWR fuel assemblies as described in the SAR, complies with the IAEA regulatory criteria for a Type A package with fissile content. The TS-R-1 regulations relevant to the structural evaluation of this package are listed in Section 2.3.

2.3. IAEA Regulations Applicable to Structural Evaluation

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
606	<i>Package</i> mass, volume and shape shall be such that it can be easily and safely transported. In addition, the <i>package</i> needs to be properly secured in or on the <i>conveyance</i> during transport.	Requirement met. SAR Section I-A (11)
607	Any lifting attachments on the <i>package</i> will not fail when used in the intended manner and that, if failure of the attachments should occur, the ability of the <i>package</i> to meet other requirements of these Regulations would not be impaired. Take account of appropriate safety factors to cover snatch lifting.	Requirement met. SAR II-A, para. A.4.4
608	Attachments and any other features on the outer surface of the <i>package</i> which could be used to lift it, shall be designed either to support its mass in accordance with the requirements of para. 607 or shall be removable or otherwise rendered incapable of being used during transport.	N/A
609	As far as practicable, the <i>packaging</i> shall be so designed and finished that the external surfaces are free from protruding features and can be easily decontaminated.	Requirement met. See SAR II, para. 1(A)(c)
610	As far as practicable, the outer layer of the <i>package</i> shall be so designed as to prevent the collection and the retention of water.	Requirement met. Outer enclosure of the packaging is cylindrical.
612	The <i>package</i> shall withstand the effects of any acceleration, vibration or vibration resonance which may arise under routine conditions of transport without any deterioration in the effectiveness of the closing devices on the various receptacles or in the integrity of the <i>package</i> as a whole. In particular, nuts, bolts and other securing devices shall be so designed as to prevent them from becoming loose or being released unintentionally, even after repeated use.	Requirement met. SAR II-A, para. A.4.7
613	The materials of the <i>packaging</i> and any components or structures shall be physically and chemically compatible with each other and with the <i>radioactive contents</i> . Account shall be taken of their behavior under irradiation.	Requirement met. SAR II-A, para. A.4.1
614	All valves through which the <i>radioactive contents</i> could otherwise escape shall be protected against unauthorized operation.	Requirement met. The valve is protected by a cover prohibiting an unauthorized manipulation. See SAR I-C para. C-2-4.
615	The design of the <i>package</i> shall take into account ambient temperatures and pressures that are likely to be encountered in routine conditions of transport.	Requirement met. See SAR II-B and II-C.
617	For <i>packages</i> to be transported by air, the temperature of the accessible surfaces shall not exceed 50°C at an ambient temperature of 38°C, with no account taken for insulation.	N/A

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
618	<i>Packages</i> to be transported by air shall be so designed that, if they were exposed to ambient temperatures ranging from -40°C to $+55^{\circ}\text{C}$, the integrity of containment would not be impaired.	N/A
619	<i>Packages</i> containing <i>radioactive material</i> , to be transported by air, shall be capable of withstanding, without leakage, an internal pressure that produces a pressure differential of not less than the <i>maximum normal operating pressure</i> plus 95 kPa.	N/A
629 thru 632	Applicable to Fissile UF_6 only. For Details see TS-R-1	N/A
633	Type A packages shall be designed to meet the requirements specified in paras. 606–616 and, in addition, the requirements of paras. 617–619 if carried by air, and of paras. 634–649.	Requirement met - as applicable. See SAR.
634	The smallest overall external dimension of the package shall not be less than 10 cm.	Requirement met. Smallest dimension is 1275 mm. See SAR I-A (7).
635	The outside of the package shall incorporate a feature such as a seal, which is not readily breakable and which, while intact, will be evidence that it has not been opened.	Requirement met. Security seals are provided. See SAR II-A A.4.3.
636	Any tie-down attachments on the package shall be so designed that, under normal and accident conditions of transport, the forces in those attachments shall not impair the ability of the package to meet the requirements of these Regulations.	Requirement met. SAR II-A, para. A.4.5.
637	The design of the package shall take into account temperatures ranging from -40°C to $+70^{\circ}\text{C}$ for the components of the packaging. Attention shall be given to freezing temperatures for liquids and to the potential degradation of packaging materials within the given temperature range.	Design temperature was -20°C to 80°C per II-A A.3.
638	The design and manufacturing techniques shall be in accordance with national or international standards, or other requirements, acceptable to the competent authority.	Requirement met. See SAR III-A.
639	The design shall include a containment system securely closed by a positive fastening device which cannot be opened unintentionally or by a pressure which may arise within the package.	Requirement met. Security seals are provided. See SAR II-A A4.3.
640	Special form radioactive material may be considered as a component of the containment system.	N/A
641	If the containment system forms a separate unit of the package, it shall be capable of being securely closed by a positive fastening device which is independent of any other part of the packaging.	Requirement met by rod cladding.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
642	The design of any component of the containment system shall take into account, where applicable, the radiolytic decomposition of liquids and other vulnerable materials and the generation of gas by chemical reaction and radiolysis.	As each fuel rod has cladding, do not contain liquid, and has only UO ₂ pellets and inert gas, the requirement is met. See SAR II-C C.2.1.
644	All valves, other than pressure relief valves, shall be provided with an enclosure to retain any leakage from the valve.	Requirement met. The valve is protected by a cover prohibiting an unauthorized manipulation. See SAR I-C para. C-2-4.
645	A radiation shield which encloses a component of the package specified as a part of the containment system shall be so designed as to prevent the unintentional release of that component from the shield. For details see TS-R-1.	Requirement met. See SAR I-C C.2.2 and II-A A.4.3.
646	A package shall be so designed that if it were subjected to the tests specified in paras. 719–724, it would prevent: (a) Loss or dispersal of the radioactive contents; and (b) Loss of shielding integrity which would result in more than a 20% increase in the radiation level at any external surface of the package.	Requirement met. See SAR II-A A.5
647	The design of a package intended for liquid radioactive material shall make provision for ullage to accommodate variations in the temperature of the contents, dynamic effects, and filling dynamics.	N/A
648~670	Requirements for packages containing Fissile Material – as applicable	N/A – Package is Type A, fresh fuel.
671~682	Requirements for packages containing Fissile Material – as applicable	Requirement met. See SAR
675	Geometry and temperature requirements: The packaging, after being subject to the tests specified in paras. 719-724, must prevent the entry of a 10 cm cube.	Requirement met. See SAR II-A A.5.7.
676	A package for fissile material shall be designed for an ambient temp. range of -40 degrees C to +38 degrees.	Design temperature was -20C to 80C per II-A A.3
677,678, 679	The package shall be subcritical under the conditions of paras. 677 and 678 with the package conditions that result in the maximum neutron multiplication consistent with: (a) routine conditions of transport (incident free); (b) the tests specified in para. 681(b); and (c) the test specified in para. 682(b).	Requirement met. See SAR II-E E.4.4.
701	Demonstration of compliance with the performance standards required in Section VI shall be accomplished by any of the methods listed below or by a combination thereof. For details see TS-R-1.	Requirement met. See SAR II-A A.5 and A.9.
702	After the specimen, prototype or sample has been subjected to the tests appropriate methods of assessment shall be used to ensure that the requirements of this section have been fulfilled in compliance with the performance and acceptance standards prescribed in Section VI.	Requirement met. See SAR II-A A.5.7 and A.9.2.5.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
704	Specimens that comprise or simulate special form radioactive material shall be subjected to the impact test, the percussion test, the bending test, and the heat test specified in paras 705–709. A different specimen may be used for each of the tests. For further details see TS-R-1.	N/A – not special form
705	Impact test: The specimen shall drop onto the target from a height of 9 m. The target shall be as defined in para. 717.	N/A
706	Percussion test: For details see TS-R-1	N/A
707	Bending test: The test shall apply only to long, slender sources with both a minimum length of 10 cm and a length to minimum width ratio of not less than 10. For details see TS-R-1.	N/A
708	Heat test: The specimen shall be heated in air to a temperature of 800°C and held at that temperature for a period of 10 minutes and shall then be allowed to cool.	N/A
709	Specimens that comprise or simulate radioactive material enclosed in a sealed capsule may be excepted from: see TS-R-1 for details.	N/A
713	All specimens shall be inspected before testing in order to identify and record faults or damage including the following: (a) divergence from the design; (b) defects in manufacture; (c) corrosion or other deterioration; and (d) distortion of features.	Requirements met. See SAR II-F 4.1.
714	The containment system of the package shall be clearly specified.	Requirements met. See SAR II-C C.2.
715	The external features of the specimen shall be clearly identified so that reference may be made simply and clearly, to any part of such specimen.	Requirement met. Only 2 specimens.
716	After each of the applicable tests specified in paras. 718–737: (a) faults and damage shall be identified and recorded; (b) it shall be determined whether the integrity of the containment system and shielding has been retained to the extent required in Section VI for the package under test; and (c) for packages containing fissile material, it shall be determined whether the assumptions and conditions used in the assessments required by paras. 671–682 for one or more packages are valid.	Requirement met. See SAR II-A A.5 and A.9.
717	The target for the drop test specified in paras. 705, 722, 725(a), 727, and 735 shall be a flat, horizontal surface of such a character that any increase in its resistance to displacement or deformation upon impact by the specimen would not significantly increase damage to the specimen.	Requirements met. See SAR II-F 4.2.1(1).

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
718	Specimens that comprise or simulate packaging designed to contain 0.1 kg or more of uranium hexafluoride shall be tested hydraulically at an internal pressure of at least 1.38 MPa but, when the test pressure is less than 2.76 MPa, the design shall require multilateral approval. For retesting packaging, any other equivalent nondestructive testing may be applied subject to multilateral approval.	N/A
719	The tests are: the water spray test, the free drop test, the stacking test and the penetration test. Specimens of the package shall be subjected to the free drop test, the stacking test, and the penetration test, preceded in each case by the water spray test. One specimen may be used for all the tests, provided that the requirements of para. 720 are fulfilled.	Requirements met. See SAR II-A A.5.
720	The time interval between the conclusion of the water spray test and the succeeding test: For details see TS-R-1.	N/A as outer enclosure of the packaging is cylindrical.
721	Water spray test: The specimen shall be subjected to a water spray test that simulates exposure to rainfall of approximately 5 cm per hour for at least one hour.	N/A as outer enclosure of the packaging is cylindrical.
722 (a), (b), (c)	Free drop test: The specimen shall drop onto the target so as to suffer maximum damage in respect of the safety features to be tested. For details see TS-R-1.	Requirements met. See SAR II-A A.5.3.
723	Stacking test: For details see TS-R-1.	Requirements met. See SAR II-A A.5.4.
724	Penetration test: For details see TS-R-1.	Requirements met. See SAR II-A A.5.5.
725	Additional tests for Type A packages designed for liquids and gases: (a) Free drop test, (b) Penetration test: For details see TS-R-1.	N/A
726	The specimen shall be subjected to the cumulative effects of the tests specified in para. 727 and para. 728, in that order. Following these tests, either this specimen or a separate specimen shall be subjected to the effect(s) of the water immersion test(s) as specified in para. 729 and, if applicable, para. 730.	Requirements met. See SAR II-A A.9.2.
727	Mechanical test: The mechanical test consists of three different drop tests. Each specimen shall be subjected to the applicable drops as specified in para. 656 or para. 682. For details of Drop I, II, and III see TS-R-1.	Requirements met. See SAR II-A, A.9.2.1 and A.9.2.2. No test (c) per TS-R-1 para. 656 (b)(i).
728	Thermal test: For details of the thermal test see TS-R-1.	Requirements met. See SAR II-A A.9.2.3.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
729	Water immersion test: The specimen shall be immersed under a head of water of at least 15 m for a period of not less than eight hours in the attitude which will lead to maximum damage. For demonstration purposes, an external gauge pressure of at least 150 kPa shall be considered to meet these conditions.	Requirements met. See SAR II-A A.9.2.4.
730	Enhanced water immersion test for Type B(U) and Type B(M) packages containing more than 105 A2 and Type C packages: Enhanced water immersion test: The specimen shall be immersed under a head of water of at least 200 m for a period of not less than one hour. For demonstration purposes, an external gauge pressure of at least 2 MPa shall be considered to meet these conditions.	N/A
731	Water leakage test for packages containing fissile material. For details see TS-R-1.	Exempt - See SAR II-E E.4.2 and E.4.4.
732	Water leakage test for packages containing fissile material. For details see TS-R-1.	Requirements met. See SAR II-A A.9.2.
733	Water leakage test for packages containing fissile material. For details see TS-R-1.	Requirements met. See SAR II-A A.9.2.4.
734	Specimens shall be subjected to the effects of each of the following test sequences in the orders specified: (a) the tests specified in paras. 727(a), 727(c), 735, and 736; and (b) the test specified in para. 737. Separate specimens are allowed to be used for each of the sequences (a) and (b).	N/A
735	Puncture/tearing test: The specimen shall be subjected to the damaging effects of a solid probe made of mild steel. The orientation of the probe to the surface of the specimen shall be such as to cause maximum damage at the conclusion of the test sequence specified in para. 734(a). See TS-R-1 for details.	N/A
737	Impact test: The specimen shall be subject to an impact on a target at a velocity of not less than 90 m/s, at such an orientation as to suffer maximum damage. The target shall be as defined in para. 717, except that the target surface may be at any orientation as long as the surface is normal to the specimen path.	N/A

2.4. Materials Evaluation

A materials review for revalidation of the Type B configuration of the MFC-1 package was conducted. In addition to reviewing the differences between the Type A configuration and the Type B configuration of the package, the findings from the Materials section of the SER issued for revalidation of the Type A configuration of the MFC-1 package was also reviewed. From these reviews, it was determined that the findings in the Materials section of the original SER issued for revalidation of the Type A configuration of the MFC-1 package are applicable to the Type B configuration of the MFC-1 package.

2.5. Materials Findings

The staff agrees that all the materials TS-R-1 regulations applicable to a Type A package are met as limited by the conditions listed in the letter.

2.6. IAEA Regulations Applicable to Materials Evaluation

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
507	Sets the requirements of other dangerous properties of the package contents, such as explosiveness, flammability, pyrophoricity, chemical toxicity, and corrosiveness that should be taken into account in the packing, labeling, marking, placarding, storage, and transport in order to be in compliance with the transport regulations for dangerous goods of each of the countries through or into which the materials will be transported, and, where applicable, with the regulations of the cognizant transport organizations, as well as these Regulations.	The staff finds that this package or its fresh fuel contents contains no explosive, chemically toxic, or corrosive substances. The only flammable material is the balsa wood used as a shock absorber outside the package. In the form of fuel rods, the Zircaloy fuel rods are not pyrophoric. The only chemically toxic material is the Cd in the control rod absorber alloy where it is not available for interaction or release. The staff finds this requirement is met.
607	Specifies that the design shall be such that any lifting attachment on the package will not fall when used in the intended manner and that, if failure of the attachments should occur, the ability of the package to meet other requirements of these Regulations would not be impaired. The design shall take account of appropriate safety factors to cover snatch lifting.	Not applicable - This package has no trunnions.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
613	States that the materials of the packaging and any components or structures shall be physically and chemically compatible with each other and with the radioactive contents. Account shall be taken of their behavior under irradiation.	<p>The package is constructed of steels, balsa wood, neoprene, and ethylene propylene. The contents are fresh fuel assemblies containing Zircaloy clad fuel rods and assembly components of steel and inconel. The staff is aware that hydrogen and fluorine (neoprene) generation are only possible, in the polymer materials, only if the gamma field is well above what is experienced in a fresh fuel package. Therefore these gases will not be generated.</p> <p>SAR Table II-A.10 lists the various dissimilar components in contact with each other. They are all stable in air and compatible with each other. The staff agrees with the conclusion in the SAR that there are no chemical or galvanic interactions that will occur.</p> <p>During sea transport, the entrance of water is precluded by the neoprene seals (SAR Section II-B.3). During normal transport, the moisture in the container is removed by the use of desiccants (SAR Section D.5). Without the presence of water, the staff agrees that corrosion of the internal package components or fuel will not occur.</p>
615	States that the design of the package shall take into account ambient temperatures and pressures that are likely to be encountered in routine conditions of transport.	See #637
637	The design of the package shall take into account temperatures ranging from -40°C to +70°C for the components of the packaging. Attention shall be given to freezing temperatures for liquids and to the potential degradation of packaging materials within the given temperature range.	The neoprene in the o-rings and valves has a usable range between -50°C and 150°C. Since the temperature range to use the package is between -20°C and 73°C, the neoprene will withstand the operating conditions neoprene can stand the usage (SAR Sections B.3, B.4.3). The mechanical properties of the SS400 carbon steel show no decrease at temperatures down to -40 °C (SAR Fig. 11-A.5). The staff agrees with these conclusions. This package contains no liquids that can freeze. The 637 requirements are met.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
638	The design and manufacturing techniques shall be in accordance with national or international standards, or other requirements, acceptable to the competent authority.	SAR Section III-A states that a QA management system based on ISO9001 shall be established. The first document in this system is a QA manual "that defines standards of QA activities required at each stage of design, fabrication, handling, inspection, and maintenance. The materials of construction are specified to Japanese standards in the SAR. The RSI response gave equivalent US standards.
642	The design of any component of the containment system shall take into account, where applicable, the radiolytic decomposition of liquids and other vulnerable materials and the generation of gas by chemical reaction and radiolysis.	See #613
646(b)	A package shall be so designed that if it were subjected to the tests specified in paras. 719-724 [Type A package tests], it would prevent loss of shielding integrity which would result in more than a 20% increase in the radiation level at any external surface of the package.	Only the fuel assemblies and external cylinder of the package are considered shielding (SAR Section II D.3.1 (1)). The mechanical and thermal properties of the fuel assembly, and confinement system components in various tables throughout the SAR were spot checked, by the staff, and found to be correct. The physical parameters (dimensions, internal pressures) were also spot checked and found to be correct.
648(b)	Either be provided with sufficient absorbent material to absorb twice the volume of the liquid contents. Such absorbent material must be suitably positioned so as to contact the liquid in the event of leakage; or be provided with a containment system composed of primary inner and secondary outer containment components designed to ensure retention of the liquid contents, within the secondary outer containment components, even if the primary inner components leak.	This package is transporting fresh fuel assemblies. They have never been in water and contain no liquids. The only available moisture would be from condensation from the air since the assemblies are shipped in dry air (SAR Section 1.D.5). Since no liquids are present this regulation is met.

3.0 THERMAL EVALUATION

3.1. Packaging Evaluation

The purpose of the thermal review is to verify that the package design satisfies the thermal safety requirements of the IAEA *Regulations for the Safe Transport of Radioactive Material*, TS-R-1. The staff reviewed the differences between the Type A configuration of the MFC-1 package and the Type B configuration of the MFC-1 package. The differences between the Type A configuration and the Type B configuration do not impact either the thermal material properties, the descriptions of the thermal modeling, the assumptions used in the thermal analyses, or the calculations

reviewed for the revalidation effort associated with the Type A configuration of the MFC-1 package.

3.2. Conclusions

Therefore, the staff believes that the thermal design of the Type B configuration of the MFC-1 package generally meets the requirements for thermal performance outlined in IAEA TS-R-1 for the transportation of the fuel assemblies. The staff has reasonable assurance that the Type B configuration of the MFC-1 package will perform as designed for shipments made in accordance with the applicable Certificate of Compliance.

The summary of the TS-R-1 requirements related to the thermal evaluation of the MFC-1, along with the staff's findings, is provided in Section 3.3.

3.3. IAEA Regulations Applicable to Thermal Evaluation

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
501	REQUIREMENTS BEFORE THE FIRST SHIPMENT (501) Sets requirements that must be fulfilled before the first shipment of any package.	Requirement met.
501 (b)	For each Type B(U), Type B(M), and Type C package and for each package containing fissile material, it shall be ensured that the effectiveness of its shielding and containment and, where necessary, the heat transfer characteristics and the effectiveness of the confinement system, are within the limits applicable to or specified for the approved design.	Requirement met. MFC-1 transport type A fresh fuel.
502	REQUIREMENTS BEFORE EACH SHIPMENT (502) Sets requirements that must be fulfilled prior to each shipment of any package.	Requirement met.
502(a)	For any package it shall be ensured that all the requirements specified in the relevant provisions of these Regulations have been satisfied.	Requirement met.
502(c)	For each Type B(U), Type B(M), and Type C package and for each package containing fissile material, it shall be ensured that all the requirements specified in the approval certificates have been satisfied.	Requirement met.
502(d)	Each Type B(U), Type B(M), and Type C package shall be held until equilibrium conditions have been approached closely enough to demonstrate compliance with the requirements for temperature and pressure unless an exemption from these requirements has received unilateral approval.	Regulation is not applicable. MFC-1 is a type A package.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
507	<p>OTHER DANGEROUS PROPERTIES OF CONTENTS (507)</p> <p>Sets the requirements of other dangerous properties of the package contents, such as explosiveness, flammability, pyrophoricity, chemical toxicity, and corrosiveness that should be taken into account in the packing, labeling, marking, placarding, storage, and transport in order to be in compliance with the transport regulations for dangerous goods of each of the countries through or into which the materials will be transported, and, where applicable, with the regulations of the cognizant transport organizations, as well as these Regulations.</p>	Requirement met. MFC-1 is to deliver fresh fuel, in compliance with transport regulations.
617	<p>ADDITIONAL REQUIREMENTS FOR PACKAGES TRANSPORTED BY AIR (617-619)</p> <p>Sets requirements for packages transported by air. For packages to be transported by air, the temperature of the accessible surfaces shall not exceed 50°C at an ambient temperature of 38°C with no account taken for insulation.</p>	Regulation is not applicable. The MFC-1 is not transported by air.
618	Packages to be transported by air shall be so designed that, if they were exposed to ambient temperatures ranging from -40°C to + 55°C, the integrity of containment would not be impaired.	Regulation is not applicable. The MFC-1 is not transported by air.
631	Packages designed to contain 0.1 kg or more of UF ₆ shall not be provided with pressure relief devices.	Regulation is not applicable. The MFC-1 is not used to transport UF ₆ .
637	The design of the package shall take into account temperatures ranging from -40°C to +70°C for the components of the packaging. Attention shall be given to freezing temperatures for liquids and to the potential degradation of packaging materials within the given temperature range.	Regulation met. The initial ambient temperature is -20°C for cold test and 38°C for NCT.
642	The design of any component of the containment system shall take into account, where applicable, the radiolytic decomposition of liquids and other vulnerable materials and the generation of gas by chemical reaction and radiolysis.	Regulation met. No gas is generated by radiolysis.
643	The containment system shall retain its radioactive contents under a reduction of ambient pressure to 60 kPa.	Regulation is not applicable. The MFC-1 is a Type A package.
644	All valves, other than pressure relief valves, shall be provided with an enclosure to retain any leakage from the valve.	Regulation met.
651(a)	Alter the arrangement, the geometrical form or the physical state of the radioactive contents or, if the radioactive material is enclosed in a can or receptacle (for example, clad fuel elements), cause the can, receptacle or radioactive material to deform or melt; or	Regulation is not applicable.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
651(b)	Lessen the efficiency of the packaging through differential thermal expansion or cracking or melting of the radiation shielding material; or	Regulation is not applicable.
651(c)	In combination with moisture, accelerate corrosion.	Regulation is not applicable.
652	A package shall be so designed that the temperature of the accessible surfaces of a package shall not exceed 50°C, unless the package is transported under exclusive use.	Regulation is not applicable.
653	The ambient temperature shall be assumed to be 38°C.	Regulation is not applicable.
654	The solar insulation conditions shall be assumed to be as specified in Table XI.	Regulation is not applicable.
655	Requires that for a package which includes thermal protection in order to satisfy the 30 minute thermal test, the protection on the exterior of the package shall not be rendered ineffective by ripping, cutting, skidding, abrasion, or rough handling.	Regulation is not applicable.
676	A package for fissile material shall be designed for an ambient temp. range of -40 degrees C to +38 degrees.	Regulation met.
728(a)	Exposure of a specimen for a period 30 minutes to a thermal environment which provides a heat flux at least equivalent to that of a hydrocarbon fuel/air fire in sufficiently quiescent ambient conditions to give a minimum average flame emissivity coefficient of 0.9 and an average temperature of at least 800 °C, fully engulfing the specimen, with a surface absorptivity coefficient of 0.8 or that value which the package may be demonstrated to possess if exposed to the fire specified, followed by:	Regulation met.
728(b)	Exposure of the specimen to an ambient temperature of 38°C, subject to the solar insulation conditions specified in Table XI and subject to the design maximum rate of internal heat generation within the package by the radioactive contents for a sufficient period to ensure that temperatures in the specimen are everywhere decreasing and/or are approaching initial steady state conditions.	Regulation met.
736	Enhanced thermal test: The conditions for this test shall be as specified in para 728, except that the exposure to the thermal environment shall be for a period of 60 minutes.	Regulation is not applicable. A 60 minute thermal test is not required.
807 (a)	A detailed description of the proposed radioactive contents with reference to their physical and chemical states and the nature of the radiation emitted;	Requirement met. (1-D Contents of Packaging)
807 (b)	A detailed statement of the design, including complete engineering drawings and schedules of materials and methods of manufacture;	N/A

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
807 (c)	A statement of the tests which have been done and their results, or evidence based on calculative methods or other evidence that the design is adequate to meet the applicable requirements;	N/A
807 (d)	The proposed operating and maintenance instructions for the use of the packaging;	N/A
807 (e)	If the package is designed to have a maximum normal operating pressure in excess of 100 kPa gauge, a specification of the materials of manufacture of the containment system, the samples to be taken, and the tests to be made...	N/A
807 (g)	Any special stowage provisions necessary to ensure the safe dissipation of heat from the package considering the various modes of transport to be used and type of conveyance or freight container...	N/A
810 (d)	The range of ambient conditions (temperature, solar radiation) which are expected to be encountered during transport and which have been taken into account in the design.	N/A
813	An application for approval shall include all information necessary to satisfy the competent authority that the design meets the requirements of para. 671 and a specification of the applicable quality assurance program as required in para. 310.	Requirement met.

4.0 CRITICALITY EVALUATION

4.1. Packaging Evaluation

The applicant provided a list of the differences between the Type A configuration of the MFC-1 package and the Type B configuration. The differences were reviewed. Staff determined that the differences between the Type A configuration of the MFC-1 package and the Type B configuration impacted neither the assumptions (e.g., close-fitting water reflection) nor the fuel assembly characteristics (e.g., pitch) employed in the criticality models reviewed during the revalidation efforts of the Type A configuration of the MFC-1 package. Because the criticality models were not affected by the differences between the two configurations of the MFC-1 package, the Upper Subcritical Limit (USL) results reviewed during revalidation efforts for the Type A configuration of the MFC-1 package are also unaffected by the differences between the Type A configuration of the MFC-1 package and the Type B configuration.

4.2. Criticality Findings

The staff agrees that the Type B configuration of the MFC-1 package meets the standards in IAEA Safety Standards Series No. TS-R-1, Rev. 2005, subject to the conditions in the letter. The summary of the TS-R-1 requirements related to the criticality evaluation of the MFC-1, along with the staff's findings, is provided in Section 4.3.

4.3. IAEA Regulations Applicable to Criticality Evaluation

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
501	Sets requirements that must be fulfilled before the first shipment of any package.	The application (see Table IV-A.1 and Appendix III-B) describes acceptance tests that affect components relied upon for the criticality analysis, such as checks performed for the neutron absorbers. The staff finds these tests to be acceptable and adequate to ensure the criticality design of the fabricated package.
501 (b)	For each Type B(U), Type B(M), and Type C package and for each package containing fissile material, it shall be ensured that the effectiveness of its shielding and containment and, where necessary, the heat transfer characteristics and the effectiveness of the confinement system, are within the limits applicable to or specified for the approved design.	The proposed contents are unirradiated reactor fuel elements. Thus, the contents do not generate heat or pressure, and the radiation is very low (<0.006 mSv/h at 1 meter from the outer surface of the package). Therefore, this paragraph does not apply.
501 (c)	For packages containing fissile material, where, in order to comply with the requirements of para. 671, neutron poisons are specifically included as components of the package, checks shall be performed to confirm the presence and distribution of those neutron poisons.	The cradle assembly contains four borated stainless steel plates, which serve as neutron absorbers for the fuel assemblies. Table IV-A.1 and Appendix III-B describes the acceptance tests that are performed for the neutron absorbers.
502	Sets requirements that must be fulfilled prior to each shipment of any package.	The competent authority's certificate lists in Conditions 7(4) and 10 the actions to be performed prior to each shipment. The application describes these actions in greater detail in Table IV-A.1.
502(a)	For any package it shall be ensured that all the requirements specified in the relevant provisions of these Regulations have been satisfied.	The competent authority's certificate lists in Conditions 7(4) and 10 the actions to be performed prior to each shipment. The application describes these actions in greater detail in Table IV-A.1.
502(c)	For each Type B(U), Type B(M), and Type C package and for each package containing fissile material, it shall be ensured that all the requirements specified in the approval certificates have been satisfied.	The competent authority's certificate lists in Conditions 7(4) and 10 the actions to be performed prior to each shipment. The application describes these actions in greater detail in Table IV-A.1.
502(g)	For packages containing fissile material, measurements of isotopic composition (if burnup credit is allowed) and tests of the closure of the package (if special features are used to avoid in-leakage of water) shall be performed.	The contents are fresh fuel, and no special features are relied upon in the criticality assessment (other than an appearance check of the confinement system to confirm integrity of the confinement system). Therefore, the paragraph is not applicable.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
528	The CSI for packages containing fissile material shall be obtained by dividing the number 50 by the smaller of the two values of N derived in paras. 681 and 682. The value of the CSI may be zero, provided that an unlimited number of packages is subcritical.	Criticality evaluations in the applicant's safety analysis demonstrate that an infinite array of damaged packages under hypothetical accident conditions, are adequately subcritical. The limiting value of "N" is therefore ∞ , resulting in a CSI of $50/\infty = 0$.
530	The transport index of any package or overpack shall not exceed 10, nor shall the CSI of any package or overpack exceed 50 except for consignments under exclusive use.	The CSI of the package is 0 and the TI is 0.6, therefore, the staff finds the requirement of this paragraph is met for criticality for non-exclusive use.
601	Requirements for LSA-III material (601) LSA-III material shall be a solid of such a nature that if the entire contents of a package were subject to the test specified in para. 703 the activity in the water would not exceed 0.1 A2.	This paragraph is not applicable as the current package is a fissile (type A) package.
629	Sets requirements for packages containing uranium hexafluoride (UF ₆). Uranium hexafluoride shall be packaged and transported in accordance with the provision ISO 7195 [10], and the requirements of paras. 630-631. The package shall also meet the requirements prescribed elsewhere in these Regulations which pertain to the radioactive and fissile properties of the material.	The current package is not a UF ₆ package; therefore, this paragraph does not apply.
632(a)	The packages are designed to requirements other than those given in ISO 7195 [10] and paras. 630-631 but, notwithstanding, the requirements of paras. 630-631 are met as far as practicable...	The current package is not a UF ₆ package; therefore, this paragraph does not apply.
632(c)	For packages designed to contain 9000 kg or more of uranium hexafluoride, the packages do not meet the requirement of para. 630(c).	The current package is not a UF ₆ package; therefore, this paragraph does not apply.
651(a)	Alter the arrangement, the geometrical form or the physical state of the radioactive contents or, if the radioactive material is enclosed in a can or receptacle (for example, clad fuel elements), cause the can, receptacle or radioactive material to deform or melt; or	The proposed contents are unirradiated reactor fuel elements. Thus, the contents do not generate heat. Therefore, this paragraph does not apply.
651(b)	Lessen the efficiency of the packaging through differential thermal expansion or cracking or melting of the radiation shielding material; or...	The proposed contents are unirradiated reactor fuel elements. Thus, the contents do not generate heat. Therefore, this paragraph does not apply.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
671(a)	Maintain subcriticality during normal and accident conditions of transport; in particular, the following contingencies shall be considered: water leaking into or out of packages; the loss of efficiency of built-in neutron absorbers or moderators; rearrangement of the contents either within the package or as a result of loss from the package; reduction of spaces within or between packages; packages becoming immersed in water or buried in snow; and temperature changes; and	The applicant's analysis includes consideration of water leakage into the package, including the effects of preferential flooding due to features that may restrict water flow into or from different void spaces within the package. Variation of moderator density was also considered as well as the effects of tolerances on the fuel contents and eccentric positioning of the contents. Based upon its review of the applicant's evaluation and independent confirmatory analyses, staff finds the evaluation to be acceptable and that it demonstrates that the package remains subcritical.
671(b)	Meet the requirements: of para. 634 for fissile material contained in packages; prescribed elsewhere in these Regulations which pertain to the radioactive properties of the material; and specified in paras. 673-682, unless excepted by para. 672.	Smallest external dimension of the package is larger than 10 cm; package meets regulations pertaining to the radioactive properties of the contents; paras. 673 – 682 discussed in the appropriate rows for each TS-R-1 paragraph below.
672	Fissile material meeting one of the provisions (a)–(d) of this para. is excepted from the requirement to be transported in packages that comply with paras. 673-682 as well as the other requirements of these Regulations that apply to fissile material. Only one type of exception is allowed per consignment.	The current package is a type A package; therefore, based upon the package designation and the package contents, this paragraph does not apply.
672(a)	A mass limit per consignment such that: Refer to equation and Table XII - Consignment Mass Limits for Exception from the Requirements for Packages Containing Fissile Material.	The current package is a type A package; therefore, based upon the package designation and the package contents, this paragraph does not apply.
672(b)	Uranium enriched in uranium-235 to a maximum of 1% by mass, and with a total plutonium and uranium-233 content not exceeding 1% of the mass of uranium-235, provided that the fissile material is distributed essentially homogeneously through the material. In addition, if uranium-235 is present in metallic, oxide, or carbide forms, it shall form a lattice arrangement.	The current package is a type A package; therefore, based upon the package designation and the package contents, this paragraph does not apply
672(c)	Liquid solutions of uranyl nitrate enriched in uranium-235 to a maximum of 2% by mass, with a total plutonium and uranium-233 content not exceeding 0.002% of the mass of uranium, and with a minimum nitrogen to uranium atomic ratio (N/U) of 2.	The current package is a type A package; therefore, based upon the package designation and the package contents, this paragraph does not apply

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
672(d)	Packages containing, individually, a total plutonium mass not more than 1 kg, of which not more than 20% by mass may consist of plutonium-239, plutonium-241 or any combination of those radionuclides.	The current package is a type A package; therefore, based upon the package designation and the package contents, this paragraph does not apply.
673	Contains requirements for fissile material for which the chemical or physical form, isotopic composition, mass or concentration, moderation ratio or density, or geographic configuration is not known.	N/A – fresh fuel chemical and physical form, isotopic composition, mass, concentration, and geometric configuration are well known.
674	For irradiated nuclear fuel the assessment of paras. 677-682 shall be based on an isotopic composition demonstrated to provide (a) the maximum neutron multiplication during the irradiation history, or (b) a conservative estimate of the neutron multiplication for the package assessments. After irradiation but prior to shipment, a measurement shall be performed to confirm the conservatism of the isotopic composition.	The MFC-1 fuel element contents are fresh (i.e., unirradiated) fuel; therefore, this paragraph does not apply.
677	For a package in isolation, it shall be assumed that water can leak into or out of all void spaces of the package, including those within the containment system. However, if the design incorporates, special features to prevent such leakage of water into or out of certain void spaces, even as a result of error, absence of leakage may be assumed in respect of those void spaces. Special features shall include the following:...	The package does not incorporate special features to prevent in-leakage of water (other than an appearance check of the confinement system to confirm integrity of the confinement system). The criticality analysis assumes flooding of all package voids; therefore, the requirements of this paragraph are met. It is assumed that the water exists both inside and outside the package and the accommodated fuel assemblies are completely flooded with the water, but no water leaks into the fuel rods because the integrity of the containment system (fuel rods) can be maintained.
677(a)	Multiple high standard water barriers, each of which would remain watertight if the package were subject to the tests prescribed in para. 682(b), a high degree of quality control in the manufacture, maintenance, and repair of packagings and tests to demonstrate the closure of each package before each shipment; of...	This package does not include special features to prevent in-leakage of water (other than an appearance check of the confinement system to confirm integrity of the confinement system), and the criticality analysis assumes flooding of all package voids; therefore, this paragraph is not applicable. It is assumed that the water exists both inside and outside the package and the accommodated fuel assemblies are completely flooded with the water, but no water leaks into the fuel rods because the integrity of the containment system (fuel rods) can be maintained.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
678	It shall be assumed that the confinement system shall be closely reflected by at least 20 cm of water or such greater reflection as may additionally be provided by the surrounding material of the packaging. However, when it can be demonstrated that the confinement system remains within the packaging following the tests prescribed in para. 682(b), close reflection of the package by at least 20 cm of water may be assumed in para 679(c).	Individual package is modeled with at least 20 cm of water external to the package outer shell.
679	The package shall be subcritical under the conditions of paras. 677 and 678 with the package conditions that result in the maximum neutron multiplication consistent with: (a) routine conditions of transport (incident free); (b) the tests specified in para. 681(b); (c), the test specified in para. 682(b)	The applicant has demonstrated that the maximum reactivity associated with the package under routine conditions of transport or hypothetical accident conditions, is adequately subcritical, per the criticality analysis described in Section II-E.
680	For packages to be transported by air: (1) the package shall be subcritical under conditions consistent with the tests prescribed in para. 734 assuming reflection by at least 20 cm of water but no water inleakage; and (b) allowance shall not be made for special features of para. 677 unless, following the tests specified in para. 734 and, subsequently, para. 733, leakage of water into or out of the void spaces is prevented.	No criticality analyses were performed to demonstrate compliance with this paragraph, nor were the necessary tests performed for demonstrating acceptability for transport by air. Therefore, this package may not be transported by air. This restriction will be a condition of staff's recommendation for revalidation.
681	A number "N" shall be derived, such that five times "N" shall be subcritical for the arrangement and package conditions that provide the maximum neutron multiplication consistent with the following:	An array of packages under normal conditions of transport was not evaluated explicitly; the applicant considered that this array would be bounded by the applicant's analysis of arrays of damaged packages under hypothetical accident conditions. The staff finds this to be acceptable based upon the clearances between the contents becoming smaller due to the deformation of the damaged packages under hypothetical accident conditions, resulting in more conservative calculations than those for normal conditions. Therefore, the requirements of this paragraph are met by a demonstration of the subcriticality of the arrays of damaged packages under hypothetical accident conditions. The applicant's analysis of arrays of damaged packages under hypothetical accident conditions demonstrates that an infinite array of packages remain subcritical. Therefore, $N = \infty$.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
681(a)	There shall not be anything between the packages, and the package arrangement shall be reflected on all sides by at least 20 cm of water, and	See comments for 681.
681(b)	The state of the packages shall be their assessed or demonstrated condition if they had been subjected to the test specified in paras. 719-724.	See comments for 681.
682	A number "N" shall be derived, such that two times "N" shall be subcritical for the arrangement and package conditions that provide the maximum neutron multiplication consistent with the following:	The applicant has demonstrated that an infinite array of damaged packages under hypothetical accident conditions, are adequately subcritical. The limiting value of "N" is therefore ∞ , resulting in a CSI of $50/\infty = 0$.
682(a)	Hydrogenous moderation between packages, and the package arrangement reflected on all sides by at least 20 cm of water; and	The applicant's model considers moderation between packages and the array is reflected by 20 cm of water on all sides. It is assumed that water exists both inside and outside the package, and the accommodated fuel assemblies are completely flooded with water, but no water leaks into the fuel rods because the integrity of the containment system (fuel rods) is maintained.
682(b)	The tests specified in paras. 719-724 followed by whichever of the following is the more limiting: the tests specified in para. 727(b) and, either para. 727(c) for packages having a mass not greater than 500 kg and an overall density not greater than 1000 kg/m ³ based on the external dimensions, or para. 727(a) for all other packages; followed by the test specified in para. 728 and completed by the tests specified in paras. 731-733; or the test specified in para. 729; and	The applicant neglected everything outside the package inner shell. The hypothetical accident condition tests did not result in any deformation to the package inner shell, the basket, or the dummy fuel element used in the tests. Based upon there being no changes to the packaging and that silicone rubber spacers are placed above and below the fuel element to maintain its vertical location in the basket, the staff finds this model to be acceptable for the criticality analysis. The applicant considers flooding of all void spaces within the package. The applicant considered uniform partial density moderation in the package and preferential flooding with varying moderator densities. Staff reviewed the analysis and finds that the applicant adequately considered preferential flooding for the fuel contents.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
682(c)	Where any part of the fissile material escapes from the containment system following the tests specified in para. 682(b), it shall be assumed that fissile material escapes from each package in the array and all of the fissile material shall be arranged in the configuration and moderation that results in the maximum neutron multiplication with close reflection by at least 20 cm of water.	No fissile material escaped after the tests specified in para. 682(b), therefore, this paragraph does not apply.
731	Packages for which water in-leakage or out-leakage to the extent which results in greatest reactivity has been assumed for purposes of assessment under paras. 677-682 shall be excepted from the test.	Water in-leakage is assumed in the criticality analysis for the package, therefore this test is not performed.
733	The specimen shall be immersed under a head of water of at least 0.9 m for a period of not less than eight hours and in the attitude for which maximum leakage is expected.	The applicant's criticality analysis assumes water in-leakage into the package. Therefore, the result of this test does not impact the criticality evaluation.
806(a)	A package design for fissile material, which is also subject to paras. 812-814, shall require multilateral approval; and	This package is a type A package; therefore, this paragraph does not apply.
807	Provides the requirements for the information which must be contained in an application for approval for Type B(U) and Type C packages.	This package is a type A package; therefore, this paragraph does not apply.
807 (a)	A detailed description of the proposed radioactive contents with reference to their physical and chemical states and the nature of the radiation emitted;	This package is a type A package; therefore, this paragraph does not apply.
807 (b)	A detailed statement of the design, including complete engineering drawings and schedules of materials and methods of manufacture;	This package is a type A package; therefore, this paragraph does not apply.
807 (c)	A statement of the tests which have been done and their results, or evidence based on calculative methods or other evidence that the design is adequate to meet the applicable requirements;	This package is a type A package; therefore, this paragraph does not apply.
807 (d)	The proposed operating and maintenance instructions for the use of the packaging;	This package is a type A package; therefore, this paragraph does not apply.
807 (f)	Where the proposed radioactive contents are irradiated fuel, the applicant shall state and justify any assumption in the safety analysis relating to the characteristics of the fuel and describe any pre-shipment measurement required by para. 674(b);...	This paragraph does not apply because the proposed contents are fresh (i.e., unirradiated) fuel elements.

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
810 (b)	Any proposed supplementary operational controls to be applied during transport not regularly provided for in these Regulations, but which are necessary to ensure the safety of the package or to compensate for the deficiencies listed in (a) above;	This package is a type A package; therefore, this paragraph does not apply.
810 (c)	A statement relative to any restrictions on the mode of transport and to any special loading, carriage, unloading or handling procedures; and...	This package is a type A package; therefore, this paragraph does not apply.
812	Each package design for fissile material which is not excepted according to para. 672 from the requirements that apply specifically to packages containing fissile material shall require multilateral approval.	This paragraph does not describe a requirement that is applied as part of the review of the criticality safety design of a package.
813	An application for approval shall include all information necessary to satisfy the competent authority that the design meets the requirements of para. 671, and a specification of the applicable quality assurance program as required in para. 310.	As described in the foregoing sections of this table, the staff finds that the application meets this requirement with respect to the criticality safety design of the package.

5.0 OPERATIONS AND MAINTENANCE EVALUATION

5.1. Operations

Design differences in both internal components and the package stabilizers were identified between the Type B configuration and the Type A configuration. However, these design differences do not result in operational differences between the two configurations.

5.2. Maintenance

The periodic inspections performed for the Type B configuration of the MFC-1 package are identical to the periodic inspections performed on the Type A configuration. In addition, the periodic inspections are performed at the same intervals for the two configurations.

5.3. Operations and Maintenance Findings

Based on a review of the statements and representations contained in the application, the staff agrees that the Type B configuration of the MFC-1 package meets the standards in IAEA Safety Standards Series No. TS-R-1, Rev. 2005, subject to the conditions in the letter. The TS-R-1 regulations relevant to this package with respect to package operations, acceptance tests, and maintenance program are listed in Section 5.4.

5.4. IAEA Regulations Applicable to Operation and Maintenance Evaluation

TS-R-1 Regulation	Summary of TS-R-1 Regulation	Applicability to MFC-1 Package
807 (d)	The proposed operating and maintenance instructions for the use of the packaging;...	Regulation met. Staff reviewed the operating and maintenance instructions and determined them to be adequate.
807 (g)	Any special stowage provisions necessary to ensure the safe dissipation of heat from the package considering the various modes of transport to be used and type of conveyance or freight container;...	Regulation is not applicable. The proposed contents do not generate heat.

CONDITIONS

The NRC recommends revalidation of the Type B configuration of Japanese Competent Authority Certificate J/105/AF-96, Rev. 2, for use in the United States with the following conditions:

- (1) packages must be fabricated in accordance with Figures III-A-2, -5, and -8 in Appendix III, and Table 1-C.1 in Section 1 of the Safety Analysis Report;
- (2) the package contents are limited to those specified in the Japanese Competent Authority Certificate; and
- (3) transport by air is prohibited.

CONCLUSIONS

Based on the statements and representations contained in the application, the staff concludes that Type B of the Model No. MFC-1 package design, with the above stated conditions meets the IAEA requirements of TS-R-1, Rev. 2005.

Issued with letter to R. Boyle, Department of Transportation, on December 30, 2011.