

**Package Contents Specification
for Safkeg-HS
Package Design No 3977A**

Title	Package Contents Specification for Safkeg-HS - Package Design No 3977A	Number	PCS 038
		Issue	C
		File Ref	PCS038-A-v1-Safkeg-HS-Contents.doc
Compiled	 R A Vaughan	Checked	 A L Ferguson
Approved	 R A Vaughan	Date	28 th Sept 2012
Croft Associates Ltd, F4 Culham Science Centre, Abingdon, Oxfordshire, OX14 3DB. 01865 407740			

1 Specification of contents

1.1 General nature of contents

The Safkeg-HS 3977A package is designed as a general purpose package for radioactive material that requires limited shielding and, with optional shielding inserts, for radioactive material that requires a significant amount of shielding.

The package is designed for radioactive material that emits alpha, beta or gamma radiation. The specified contents do not include materials that emit a significant amount of neutrons.

The contents may be in solid, liquid or gaseous form and carried in various inserts as specified in the Table 1 below.

Table 1 Contents Types

Contents Type Designation	Material Form	Shielding Insert	General Requirements for each Contents Type (1)	Activity Limits for each Contents Type
CT-1	Solid	HS-12x95-Tu Design No 3982	See Table 1-3-1	See Table 3
CT-2	Solid	HS-31x114-Tu Design No 3985	See Table 1-3-2	See Table 4
CT-3	Solid	HS-55x138-SS Design No 3987	See Table 1-3-3	See Table 5
CT-4	Liquid	HS-31x114-Tu Design No 3985	See Table 1-3-4	See Table 6
CT-5	Liquid	HS-55x138-SS Design No 3987	See Table 1-3-5	See Table 7
CT-6	Gas	HS-31x114-Tu Design No 3985	See Table 1-3-6	See Table 8
CT-7	Solid/ Fissile Normal Form	HS-55x138-SS Design No 3987	See Table 1-3-7	See Table 9
CT-8	Solid/ Fissile Special Form	HS-55x138-SS Design No 3987	See Table 1-3-8	See Table 10

1 These are the tables in the SARP [1].

1.2 Shielding inserts

The shielding inserts specified in Section 1 of the SARP for Safkeg-HS 3977A [1] and listed in Table 1 above are required for all contents.

Under NCT, the shielding inserts, together with the user defined product containers, provide confinement of the radioactive material within the shielding.

Under HAC, the shielding inserts, together with the user defined product containers, provide confinement of radioactive material as solid, liquid or gas within the shielding.

1.3 Radionuclides included

See Tables 3 to 9.

1.4 Quantity

The maximum mass (and volume for gases) of each radionuclide is detailed in Table 2 and Tables 3 to 9 for specific contents types CT-1 to CT-8.

1.5 Activity limit

The package activity limits for individual nuclides, according to the insert used, are given in Tables 3 to 9. The activity limit is determined in accordance with the methodology in Section 2 below.

1.6 Other limiting factors

Various restrictions and limits of quantity of radionuclides apply according to the insert used and for the form of the radioactive material (solid, liquid or gas). These restrictions and contents limits are detailed in Section 1 of the SARP for Safkeg-HS 3977A in Section 1.2.2 in the tables for contents types CT-1 to CT-8.

2 Calculation of allowable contents

The package activity limit in Tables 3 to 9 is the least of the limits determined on the basis of heat output, mass limit, shielding limit and, for gas contents, the limit based on allowable leakage under NCT or HAC.

2.1 Heat limits

The heat limit for solid and gaseous contents is 30 W and for liquid contents the heat limit is 5 W.

2.2 Mass limit

The upper limit on the mass is different for each insert - as specified in section 1.4 above.

The maximum mass of the radionuclides is set at nominally 50% the mass of a steel cylinder that would fill the cavity of the insert (see Table 1-2).

Table 2 Maximum mass of the radionuclides

Shielding Insert	Mass of a steel cylinder that would fill the cavity of the insert	Maximum mass of the radionuclides
	g	g
HS-12x95-Tu Design No 3982	90	45
HS-31x114-Tu Design No 3985	690	345
HS-55x138-SS Design No 3987	2,630	1,300

2.3 Shielding limit

The package design is such that the surface dose rate, as opposed to the TI, is the limiting factor under HAC. The shielding limits in Tables 3 to 9 for each radionuclide and each insert, are based on an assessment in Report CTR 2011/01 [2] of the maximum activity to give the maximum allowable package surface dose rate (for β , γ and n emitters) of 2mSv/h (200 mrem/h). These calculations are based on the worst case assumption of the radioactive material being a point source at the centre of the base of the insert (neglecting spacing due to use of product containers). This location has been shown to produce the highest package surface dose rate in report SERCO/TAS/003191/002 [3].

2.4 Leakage limit

For solid and liquid contents, the contents are completely contained as the O-ring seal of the CV meets the requirement of Leaktight as defined in ANSI N 14.5 [4].

For gaseous radionuclides, it is assumed that they will escape from their product containers under HAC and leak past the seal in the insert within the CV and leak from the CV and the package past the O-ring seal of the CV.

The allowable gas leakage rates in 10CFR Part 71 [5][4] are 1×10^{-6} A₂/h under NCT and A₂/week under HAC.

The maximum gas contents are determined as the contents that would leak at the HAC rate of A_2 /week from a “Leaktight” seal (as defined in ANSI N14.5 [4] as a leakage rate less than or equal to 1×10^{-7} ref·cm³/s, of air at an upstream pressure of 1 atmosphere (atm) absolute (abs) and a downstream pressure of 0.01 atm abs or less). The calculation of the maximum gas contents is given in report CS 2012/05 [6].

2.5 Criticality Limits

The quantities of fissile material are restricted to the limits in this document and according to the criteria specified in Section 1 of the SARP for Safkeg-HS 3977A [1] in Section 1.2.2 in the tables for Contents Types CT-7 and CT-8 Fissile solid.

3 References

- [1] CTR 2008/11, Revision 0, SARP for Safkeg-HS 3977A, Docket No. 71-9337
- [2] Croft, CTR 2011/01, Issue A, SAFKEG LS 3977A, Package Activity Limits Based on Shielding
- [3] SERCO/TAS/003191/002, Monte Carlo Modelling of Safkeg-HS Container
- [4] ANSI N14.5, American National Standard for Radioactive Materials - Leakage Test on Packages for Shipment, American National Standards Institute, Inc., 1997
- [5] 10CFR PART 71, Packaging And Transportation Of Radioactive Material, U.S. Nuclear Regulatory Commission
- [6] CS 2012/05, Issue A, SAFKEG-HS 3977A - Gas contents limit for leaktight condition

Table 3 Activity Limits for Contents Type 1 - CT-1 - Solid in heavy tungsten insert – Design No 3984

Contents Type 1 - CT-1 - Solid in heavy tungsten insert										Package limits calculations for each nuclide												
1	2	3	4	5	6	7	8	9	10	Contents heat limit			Contents mass limit		Shielding limit	Package limit						
Nuclide	Max	Activity	A2	# A2s	Spec Ac	Mass	Heat gen	Heat output	PackageType	Heat output	Act	Act	Mass	Act	Act	Act	Act	Code				
	TBq	Ci	TBq		TBq/g	g	W/Ci	W	A or B	W	Ci	Bq	g	Bq	Bq	Bq	Bq	H	M	S		
Ac-225	8.37E+00	2.26E+02	6.00E-03	1394.38	2.10E+03	3.98E-03	3.46E-02	7.82E+00	B	30.00	8.68E+02	3.2105E+13	45	9.45E+16	8.37E+12	8.37E+12	8.37E+12			S		
Ac-227	1.22E+02	3.28E+03	9.00E-05	1350000.00	2.70E+00	4.50E+01	4.72E-04	1.55E+00	B	30.00	6.35E+04	2.3513E+15	45	1.22E+14	7.21E+14	1.22E+14	1.22E+14		M			
Ac-228	1.36E+00	3.67E+01	5.00E-01	2.72	8.40E+04	1.62E-05	8.04E-03	2.95E-01	B	30.00	3.73E+03	1.3807E+14	45	3.78E+18	1.36E+12	1.36E+12	1.36E+12			S		
Am-241	5.85E+00	1.58E+02	1.00E-03	5850.00	1.30E-01	4.50E+01	3.28E-02	5.19E+00	B	30.00	9.14E+02	3.3828E+13	45	5.85E+12	3.88E+23	5.85E+12	5.85E+12		M			
As-77	7.90E+02	2.13E+04	7.00E-01	1128.38	3.90E+04	2.03E-02	1.41E-03	3.00E+01	B	30.00	2.13E+04	7.8987E+14	45	1.76E+18	9.43E+19	7.90E+14	7.90E+14	H				
Au-198	2.56E+02	6.92E+03	6.00E-01	426.50	9.00E+03	2.84E-02	4.34E-03	3.00E+01	B	30.00	6.92E+03	2.5590E+14	45	4.05E+17	6.99E+14	2.56E+14	2.56E+14	H				
Ba-131	1.88E+02	5.08E+03	2.00E+00	94.05	3.10E+03	6.07E-02	3.06E-03	1.55E+01	B	30.00	9.82E+03	3.6334E+14	45	1.40E+17	1.88E+14	1.88E+14	1.88E+14			S		
C-14	7.20E+00	1.95E+02	3.00E+00	2.40	1.60E-01	4.50E+01	2.93E-04	5.71E-02	B	30.00	1.02E+05	3.7850E+15	45	7.20E+12	6.92E+27	7.20E+12	7.20E+12		M			
Co-60	2.48E-02	6.70E-01	4.00E-01	0.06	4.20E+01	5.90E-04	1.54E-02	1.03E-02	A	30.00	1.95E+03	7.1970E+13	45	1.89E+15	2.48E+10	2.48E+10	2.48E+10			S		
Cs-131	6.71E+03	1.81E+05	3.00E+01	223.73	3.80E+03	1.77E+00	1.65E-04	3.00E+01	B	30.00	1.81E+05	6.7118E+15	45	1.71E+17	8.39E+35	6.71E+15	6.71E+15	H				
Cs-134	7.05E+00	1.90E+02	7.00E-01	10.07	4.80E+01	1.47E-01	1.02E-02	1.94E+00	B	30.00	2.95E+03	1.0905E+14	45	2.16E+15	7.05E+12	7.05E+12	7.05E+12			S		
Cs-137	1.44E+02	3.89E+03	6.00E-01	240.00	3.20E+00	4.50E+01	1.01E-03	3.94E+00	B	30.00	2.96E+04	1.0966E+15	45	1.44E+14	1.59E+15	1.44E+14	1.44E+14		M			
Cu-67	6.91E+02	1.87E+04	7.00E-01	986.75	2.80E+04	2.47E-02	1.61E-03	3.00E+01	B	30.00	1.87E+04	6.9073E+14	45	1.26E+18	6.50E+25	6.91E+14	6.91E+14	H				
Hg-203	5.58E+02	1.51E+04	1.00E+00	557.87	5.10E+02	1.09E+00	1.99E-03	3.00E+01	B	30.00	1.51E+04	5.5787E+14	45	2.30E+16	1.10E+35	5.58E+14	5.58E+14	H				
Ho-166	1.73E+01	4.67E+02	4.00E-01	43.20	2.60E+04	6.65E-04	4.29E-03	2.01E+00	B	30.00	6.99E+03	2.5852E+14	45	1.17E+18	1.73E+13	1.73E+13	1.73E+13			S		
I-125	3.19E+03	8.61E+04	3.00E+00	1062.52	6.40E+02	4.98E+00	3.48E-04	3.00E+01	B	30.00	8.61E+04	3.1875E+15	45	2.88E+16	4.49E+35	3.19E+15	3.19E+15	H				
I-129	2.93E-04	7.91E-03	unlimited	unlimited	6.50E-06	4.50E+01	4.68E-04	3.70E-06	B	30.00	6.41E+04	2.3720E+15	45	2.93E+08	3.31E+26	2.93E+08	2.93E+08		M			
I-131	3.28E+02	8.85E+03	7.00E-01	468.01	4.60E+03	7.12E-02	3.39E-03	3.00E+01	B	30.00	8.85E+03	3.2761E+14	45	2.07E+17	1.07E+16	3.28E+14	3.28E+14	H				
In-111	4.27E+02	1.15E+04	3.00E+00	142.34	1.50E+04	2.85E-02	2.60E-03	3.00E+01	B	30.00	1.15E+04	4.2702E+14	45	6.75E+17	1.45E+28	4.27E+14	4.27E+14	H				
Ir-192	1.81E+02	4.90E+03	6.00E-01	302.02	3.40E+02	5.33E-01	6.13E-03	3.00E+01	B	30.00	4.90E+03	1.8121E+14	45	1.53E+16	1.11E+16	1.81E+14	1.81E+14	H				
Ir-194	3.87E+01	1.04E+03	3.00E-01	128.87	3.10E+04	1.25E-03	5.35E-03	5.59E+00	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	3.87E+13	3.87E+13	3.87E+13			S		
Kr-79	6.00E+01	1.62E+03	3.00E-01	200.05	3.10E+04	1.94E-03	5.35E-03	8.67E+00	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	6.00E+13	6.00E+13	6.00E+13			S		
Lu-177	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	1.56E+24	2.08E+14	2.08E+14	H				
Mo-99	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	7.74E+14	2.08E+14	2.08E+14	H				
Na-24	2.64E-02	7.13E-01	3.00E-01	0.09	3.10E+04	8.51E-07	5.35E-03	3.81E-03	A	30.00	5.61E+03	2.0766E+14	45	1.40E+18	2.64E+10	2.64E+10	2.64E+10			S		
Np-237	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	4.02E+18	2.08E+14	2.08E+14	H				
P-32	5.58E+00	1.51E+02	3.00E-01	18.59	3.10E+04	1.80E-04	5.35E-03	8.06E-01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	5.58E+12	5.58E+12	5.58E+12			S		
P-33	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	5.10E+37	2.08E+14	2.08E+14	H				
Pb-203	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	1.18E+17	2.08E+14	2.08E+14	H				
Pb-210	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	5.21E+18	2.08E+14	2.08E+14	H				
Pd-109	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	9.18E+20	2.08E+14	2.08E+14	H				
Pu-238	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	6.85E+14	2.08E+14	2.08E+14	H				
Pu-239	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	2.33E+25	2.08E+14	2.08E+14	H				
Pu-240	2.64E+01	7.14E+02	3.00E-01	88.00	3.10E+04	8.52E-04	5.35E-03	3.81E+00	B	30.00	5.61E+03	2.0766E+14	45	1.40E+18	2.64E+13	2.64E+13	2.64E+13			S		
Pu-241	2.08E+02	5.61E+03	3.00E-0																			

Notes

Column	
1	Identifies nuclide
2	Package activity limit for this Contents Type - from Col 17
3	Calculated from Bq amount in Col 2
4	A2 from 10CFR71
5	# of A2's of nuclide at package activity limit
6	Specific activity from 10CFR71
7	Mass of nuclide at package activity limit
8	Heat generation rate of nuclide - from Microshield.
9	Heat output of nuclide at package activity limit
10	Package Type [A or B] based on individual nuclide limit
11	Mass limit of nuclide based on package heat limit
12	Calculated from limit in Col 11
13	Calculated from Bq amount in Col 12
14	Mass limit of nuclide based on capacity of insert
15	Calculated from Bq amount in Col 14
16	Package shielding limit from CTR2011/01
17	Package limit = least of heat, mass and shielding limits in Cols 13, 15 & 16
18	H shown where package limit is Heat limit
19	M shown where package limit is Mass limit
20	S shown where package limit is Shielding limit

Colour codes

	Radionuclides
	Package limit
	Physics data
	Contents limit based on heat, mass or shielding

RAV Notes

This spreadsheet updated26/09/2012

Table 4 Activity Limits for Contents Type 2 - CT-2 - Solid in light tungsten insert – Design No 3983

Contents Type 2 - CT-2 - Solid in light tungsten insert										Package limits calculations for each nuclide									
										Contents heat limit			Contents mass limit		Shielding limit	Package limit			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Nuclide	Max	Activity	A2	# A2s	Spec Ac	Mass	Heat gen	Heat output	PackageType	Heat output	Act	Act	Mass	Act	Act	Act	Code		
	TBq	Ci	TBq		TBq/g	g	W/Ci	W	A or B	W	Ci	Bq	g	Bq	Bq	Bq	H	M	S
Ac-225	3.54E+00	9.57E+01	6.00E-03	590.11	2.10E+03	1.69E-03	3.46E-02	3.31E+00	B	30.00	8.68E+02	3.2105E+13	345	7.25E+17	3.54E+12	3.54E+12			S
Ac-227	3.57E+02	9.64E+03	9.00E-05	3964427.30	2.70E+00	1.32E+02	4.72E-04	4.55E+00	B	30.00	6.35E+04	2.3513E+15	345	9.32E+14	3.57E+14	3.57E+14			S
Ac-228	5.43E-01	1.47E+01	5.00E-01	1.09	8.40E+04	6.46E-06	8.04E-03	1.18E-01	B	30.00	3.73E+03	1.3807E+14	345	2.90E+19	5.43E+11	5.43E+11			S
Am-241	3.38E+01	9.14E+02	1.00E-03	33828.06	1.30E-01	2.60E+02	3.28E-02	3.00E+01	B	30.00	9.14E+02	3.3828E+13	345	4.49E+13	1.64E+23	3.38E+13	H		
As-77	7.90E+02	2.13E+04	7.00E-01	1128.38	3.90E+04	2.03E-02	1.41E-03	3.00E+01	B	30.00	2.13E+04	7.8987E+14	345	1.35E+19	1.14E+19	7.90E+14	H		
Au-198	2.43E+02	6.57E+03	6.00E-01	405.30	9.00E+03	2.70E-02	4.34E-03	2.85E+01	B	30.00	6.92E+03	2.5590E+14	345	3.11E+18	2.43E+14	2.43E+14			S
Ba-131	6.12E+01	1.65E+03	2.00E+00	30.60	3.10E+03	1.97E-02	3.06E-03	5.05E+00	B	30.00	9.82E+03	3.6334E+14	345	1.07E+18	6.12E+13	6.12E+13			S
C-14	5.52E+01	1.49E+03	3.00E+00	18.40	1.60E-01	3.45E+02	2.93E-04	4.38E-01	B	30.00	1.02E+05	3.7850E+15	345	5.52E+13	6.13E+27	5.52E+13		M	
Co-60	9.69E-02	2.62E+00	4.00E-01	0.24	4.20E+01	2.31E-03	1.54E-02	4.04E-02	A	30.00	1.95E+03	7.1970E+13	345	1.45E+16	9.69E+10	9.69E+10			S
Cs-131	6.71E+03	1.81E+05	3.00E+01	223.73	3.80E+03	1.77E+00	1.65E-04	3.00E+01	B	30.00	1.81E+05	6.7118E+15	345	1.31E+18	7.43E+35	6.71E+15	H		
Cs-134	2.63E+00	7.11E+01	7.00E-01	3.76	4.80E+01	5.48E-02	1.02E-02	7.24E-01	B	30.00	2.95E+03	1.0905E+14	345	1.66E+16	2.63E+12	2.63E+12			S
Cs-137	3.17E+02	8.58E+03	6.00E-01	528.95	3.20E+00	9.92E+01	1.01E-03	8.68E+00	B	30.00	2.96E+04	1.0966E+15	345	1.10E+15	3.17E+14	3.17E+14			S
Cu-67	6.91E+02	1.87E+04	7.00E-01	986.75	2.80E+04	2.47E-02	1.61E-03	3.00E+01	B	30.00	1.87E+04	6.9073E+14	345	9.66E+18	2.84E+24	6.91E+14	H		
Hg-203	5.58E+02	1.51E+04	1.00E+00	557.87	5.10E+02	1.09E+00	1.99E-03	3.00E+01	B	30.00	1.51E+04	5.5787E+14	345	1.76E+17	5.32E+34	5.58E+14	H		
Ho-166	7.24E+00	1.96E+02	4.00E-01	18.10	2.60E+04	2.78E-04	4.29E-03	8.40E-01	B	30.00	6.99E+03	2.5852E+14	345	8.97E+18	7.24E+12	7.24E+12			S
I-125	3.19E+03	8.61E+04	3.00E+00	1062.52	6.40E+02	4.98E+00	3.48E-04	3.00E+01	B	30.00	8.61E+04	3.1875E+15	345	2.21E+17	3.98E+35	3.19E+15	H		
I-129	2.24E-03	6.06E-02	unlimited	unlimited	6.50E-06	3.45E+02	4.68E-04	2.84E-05	B	30.00	6.41E+04	2.3720E+15	345	2.24E+09	2.93E+26	2.24E+09		M	
I-131	3.28E+02	8.85E+03	7.00E-01	468.01	4.60E+03	7.12E-02	3.39E-03	3.00E+01	B	30.00	8.85E+03	3.2761E+14	345	1.59E+18	2.31E+15	3.28E+14	H		
In-111	4.27E+02	1.15E+04	3.00E+00	142.34	1.50E+04	2.85E-02	2.60E-03	3.00E+01	B	30.00	1.15E+04	4.2702E+14	345	5.18E+18	1.29E+28	4.27E+14	H		
Ir-192	1.81E+02	4.90E+03	6.00E-01	302.02	3.40E+02	5.33E-01	6.13E-03	3.00E+01	B	30.00	4.90E+03	1.8121E+14	345	1.17E+17	2.63E+15	1.81E+14	H		
Ir-194	1.47E+01	3.96E+02	3.00E-01	48.84	3.10E+04	4.73E-04	5.35E-03	2.12E+00	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	1.47E+13	1.47E+13			S
Kr-79	2.30E+01	6.21E+02	3.00E-01	76.58	3.10E+04	7.41E-04	5.35E-03	3.32E+00	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	2.30E+13	2.30E+13			S
Lu-177	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	1.38E+24	2.08E+14	H		
Mo-99	1.88E+02	5.07E+03	3.00E-01	625.74	3.10E+04	6.06E-03	5.35E-03	2.71E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	1.88E+14	1.88E+14			S
Na-24	1.28E-02	3.45E-01	3.00E-01	0.04	3.10E+04	4.12E-07	5.35E-03	1.85E-03	A	30.00	5.61E+03	2.0766E+14	345	1.07E+19	1.28E+10	1.28E+10			S
Np-237	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	1.70E+18	2.08E+14	H		
P-32	2.49E+00	6.73E+01	3.00E-01	8.30	3.10E+04	8.03E-05	5.35E-03	3.60E-01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	2.49E+12	2.49E+12			S
P-33	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	3.61E+37	2.08E+14	H		
Pb-203	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	2.45E+16	2.08E+14	H		
Pb-210	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	1.36E+18	2.08E+14	H		
Pd-109	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	1.05E+20	2.08E+14	H		
Pu-238	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	6.05E+14	2.08E+14	H		
Pu-239	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	6.04E+24	2.08E+14	H		
Pu-240	2.34E+01	6.32E+02	3.00E-01	78.00	3.10E+04	7.55E-04	5.35E-03	3.38E+00	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	2.34E+13	2.34E+13			S
Pu-241	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	1.90E+20	2.08E+14	H		
Ra-223	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	1.07E+19	3.57E+14	2.08E+14	H		
Ra-224	4.77E-02	1.29E+00	3.00E-01	0.16	3.10E+04	1.54E-06	5.35E-03	6.90E-03	A	30.00	5.61E+03	2.0766E+14	345	1.07E+19	4.77E+10	4.77E+10			S
Ra-226	8.02E-02	2.17E+00	3																

Notes

Column	
1	Identifies nuclide
2	Package activity limit for this Contents Type - from Col 17
3	Calculated from Bq amount in Col 2
4	A2 from 10CFR71
5	# of A2's of nuclide at package activity limit
6	Specific activity from 10CFR71
7	Mass of nuclide at package activity limit
8	Heat generation rate of nuclide - from Microshield.
9	Heat output of nuclide at package activity limit
10	Package Type [A or B] based on individual nuclide limit
11	Mass limit of nuclide based on package heat limit
12	Calculated from limit in Col 11
13	Calculated from Bq amount in Col 12
14	Mass limit of nuclide based on capacity of insert
15	Calculated from Bq amount in Col 14
16	Package shielding limit from CTR2011/01
17	Package limit = least of heat, mass and shielding limits in Cols 13, 15 & 16
18	H shown where package limit is Heat limit
19	M shown where package limit is Mass limit
20	S shown where package limit is Shielding limit

Colour codes

	Radionuclides
	Package limit
	Physics data
	Contents limit based on heat, mass or shielding

RAV Notes

This spreadsheet updated26/09/2012

Table 5 Activity Limits for Contents Type 3 - CT-3 - Solid in steel insert – Design No 3986

Contents Type 3 - CT-3 - Solid in steel insert										Package limits calculations for each nuclide									
										Contents heat limit			Contents mass limit		Shielding limit	Package limit			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Nuclide	Max	Activity	A2	# A2s	Spec Ac	Mass	Heat gen	Heat output	PackageType	Heat output	Act	Act	Mass	Act	Act	Act	Code		
	TBq	Ci	TBq		TBq/g	g	W/Ci	W	A or B	W	Ci	Bq	g	Bq	Bq	Bq	H	M	S
Ac-225	7.65E-01	2.07E+01	6.00E-03	127.45	2.10E+03	3.64E-04	3.46E-02	7.15E-01	B	30.00	8.68E+02	3.2105E+13	1300	2.73E+18	7.65E+11	7.65E+11			S
Ac-227	3.18E+01	8.59E+02	9.00E-05	353036.59	2.70E+00	1.18E+01	4.72E-04	4.05E-01	B	30.00	6.35E+04	2.3513E+15	1300	3.51E+15	3.18E+13	3.18E+13			S
Ac-228	1.02E-01	2.75E+00	5.00E-01	0.20	8.40E+04	1.21E-06	8.04E-03	2.21E-02	A	30.00	3.73E+03	1.3807E+14	1300	1.09E+20	1.02E+11	1.02E+11			S
Am-241	3.38E+01	9.14E+02	1.00E-03	33828.06	1.30E-01	2.60E+02	3.28E-02	3.00E+01	B	30.00	9.14E+02	3.3828E+13	1300	1.69E+14	3.54E+22	3.38E+13	H		
As-77	7.90E+02	2.13E+04	7.00E-01	1128.38	3.90E+04	2.03E-02	1.41E-03	3.00E+01	B	30.00	2.13E+04	7.8987E+14	1300	5.07E+19	2.50E+17	7.90E+14	H		
Au-198	3.64E+01	9.85E+02	6.00E-01	60.73	9.00E+03	4.05E-03	4.34E-03	4.27E+00	B	30.00	6.92E+03	2.5590E+14	1300	1.17E+19	3.64E+13	3.64E+13			S
Ba-131	8.20E+00	2.22E+02	2.00E+00	4.10	3.10E+03	2.65E-03	3.06E-03	6.77E-01	B	30.00	9.82E+03	3.6334E+14	1300	4.03E+18	8.20E+12	8.20E+12			S
C-14	2.08E+02	5.62E+03	3.00E+00	69.33	1.60E-01	1.30E+03	2.93E-04	1.65E+00	B	30.00	1.02E+05	3.7850E+15	1300	2.08E+14	1.40E+28	2.08E+14		M	
Co-60	1.81E-02	4.90E-01	4.00E-01	0.05	4.20E+01	4.32E-04	1.54E-02	7.56E-03	A	30.00	1.95E+03	7.1970E+13	1300	5.46E+16	1.81E+10	1.81E+10			S
Cs-131	6.71E+03	1.81E+05	3.00E+01	223.73	3.80E+03	1.77E+00	1.65E-04	3.00E+01	B	30.00	1.81E+05	6.7118E+15	1300	4.94E+18	5.94E+35	6.71E+15	H		
Cs-134	4.20E-01	1.14E+01	7.00E-01	0.60	4.80E+01	8.75E-03	1.02E-02	1.16E-01	A	30.00	2.95E+03	1.0905E+14	1300	6.24E+16	4.20E+11	4.20E+11			S
Cs-137	1.73E+01	4.68E+02	6.00E-01	28.88	3.20E+00	5.42E+00	1.01E-03	4.74E-01	B	30.00	2.96E+04	1.0966E+15	1300	4.16E+15	1.73E+13	1.73E+13			S
Cu-67	6.91E+02	1.87E+04	7.00E-01	986.75	2.80E+04	2.47E-02	1.61E-03	3.00E+01	B	30.00	1.87E+04	6.9073E+14	1300	3.64E+19	9.23E+21	6.91E+14	H		
Hg-203	5.58E+02	1.51E+04	1.00E+00	557.87	5.10E+02	1.09E+00	1.99E-03	3.00E+01	B	30.00	1.51E+04	5.5787E+14	1300	6.63E+17	1.14E+30	5.58E+14	H		
Ho-166	1.54E+00	4.15E+01	4.00E-01	3.84	2.60E+04	5.91E-05	4.29E-03	1.78E-01	B	30.00	6.99E+03	2.5852E+14	1300	3.38E+19	1.54E+12	1.54E+12			S
I-125	3.19E+03	8.61E+04	3.00E+00	1062.52	6.40E+02	4.98E+00	3.48E-04	3.00E+01	B	30.00	8.61E+04	3.1875E+15	1300	8.32E+17	3.18E+35	3.19E+15	H		
I-129	8.45E-03	2.28E-01	unlimited	unlimited	6.50E-06	1.30E+03	4.68E-04	1.07E-04	B	30.00	6.41E+04	2.3720E+15	1300	8.45E+09	6.65E+26	8.45E+09		M	
I-131	1.42E+02	3.83E+03	7.00E-01	202.60	4.60E+03	3.08E-02	3.39E-03	1.30E+01	B	30.00	8.85E+03	3.2761E+14	1300	5.98E+18	1.42E+14	1.42E+14			S
In-111	4.27E+02	1.15E+04	3.00E+00	142.34	1.50E+04	2.85E-02	2.60E-03	3.00E+01	B	30.00	1.15E+04	4.2702E+14	1300	1.95E+19	1.03E+28	4.27E+14	H		
Ir-192	1.76E+02	4.74E+03	6.00E-01	292.54	3.40E+02	5.16E-01	6.13E-03	2.91E+01	B	30.00	4.90E+03	1.8121E+14	1300	4.42E+17	1.76E+14	1.76E+14			S
Ir-194	2.55E+00	6.89E+01	3.00E-01	8.50	3.10E+04	8.23E-05	5.35E-03	3.68E-01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	2.55E+12	2.55E+12			S
Kr-79	4.04E+00	1.09E+02	3.00E-01	13.46	3.10E+04	1.30E-04	5.35E-03	5.84E-01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	4.04E+12	4.04E+12			S
Lu-177	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	1.10E+24	2.08E+14	H		
Mo-99	1.47E+01	3.96E+02	3.00E-01	48.88	3.10E+04	4.73E-04	5.35E-03	2.12E+00	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	1.47E+13	1.47E+13			S
Na-24	3.47E-03	9.39E-02	3.00E-01	0.01	3.10E+04	1.12E-07	5.35E-03	5.02E-04	A	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	3.47E+09	3.47E+09			S
Np-237	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	3.67E+17	2.08E+14	H		
P-32	1.69E+00	4.58E+01	3.00E-01	5.64	3.10E+04	5.46E-05	5.35E-03	2.45E-01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	1.69E+12	1.69E+12			S
P-33	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	1.03E+38	2.08E+14	H		
Pb-203	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	1.45E+15	2.08E+14	H		
Pb-210	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	1.22E+17	2.08E+14	H		
Pd-109	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	2.03E+18	2.08E+14	H		
Pu-238	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	4.85E+14	2.08E+14	H		
Pu-239	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	5.38E+23	2.08E+14	H		
Pu-240	1.87E+01	5.05E+02	3.00E-01	62.33	3.10E+04	6.03E-04	5.35E-03	2.70E+00	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	1.87E+13	1.87E+13			S
Pu-241	2.08E+02	5.61E+03	3.00E-01	692.20	3.10E+04	6.70E-03	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	1.72E+19	2.08E+14	H		
Ra-223	3.18E+01	8.59E+02	3.00E-01	105.91	3.10E+04	1.02E-03	5.35E-03	4.59E+00	B	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	3.18E+13	3.18E+13			S
Ra-224	1.36E-02	3.68E-01	3.00E-01	0.05	3.10E+04	4.39E-07	5.35E-03	1.97E-03	A	30.00	5.61E+03	2.0766E+14	1300	4.03E+19	1.36E				

Notes

Column	
1	Identifies nuclide
2	Package activity limit for this Contents Type - from Col 17
3	Calculated from Bq amount in Col 2
4	A2 from 10CFR71
5	# of A2's of nuclide at package activity limit
6	Specific activity from 10CFR71
7	Mass of nuclide at package activity limit
8	Heat generation rate of nuclide - from Microshield.
9	Heat output of nuclide at package activity limit
10	Package Type [A or B] based on individual nuclide limit
11	Mass limit of nuclide based on package heat limit
12	Calculated from limit in Col 11
13	Calculated from Bq amount in Col 12
14	Mass limit of nuclide based on capacity of insert
15	Calculated from Bq amount in Col 14
16	Package shielding limit from CTR2011/01
17	Package limit = least of heat, mass and shielding limits in Cols 13, 15 & 16
18	H shown where package limit is Heat limit
19	M shown where package limit is Mass limit
20	S shown where package limit is Shielding limit

Colour codes

	Radionuclides
	Package limit
	Physics data
	Contents limit based on heat, mass or shielding

RAV Notes

This spreadsheet updated 26/09/2012

Table 6 Activity Limits for Contents Type 4 - CT-4 - Liquid in light tungsten insert – Design No 3983

Contents Type 4 - CT-4 - Liquid in light tungsten insert										Package limits calculations for each nuclide									
										Contents heat limit			Contents mass limit		Shielding limit	Package limit			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Nuclide	Max	Activity	A2	# A2s	Spec Ac	Mass	Heat gen	Heat output	PackageType	Heat output	Act	Act	Mass	Act	Act	Act	Code		
	TBq	Ci	TBq		TBq/g	g	W/Ci	W	A or B	W	Ci	Bq	g	Bq	Bq	Bq	H	M	S
Ho-166	7.24E+00	1.96E+02	4.00E-01	18.10	2.60E+04	2.78E-04	4.29E-03	8.40E-01	B	5.00	1.16E+03	4.3087E+13	345	8.97E+18	7.24E+12	7.24E+12			S
Lu-177	3.46E+01	9.35E+02	3.00E-01	115.37	3.10E+04	1.12E-03	5.35E-03	5.00E+00	B	5.00	9.35E+02	3.4610E+13	345	1.07E+19	1.38E+24	3.46E+13	H		
Mo-99	3.46E+01	9.35E+02	3.00E-01	115.37	3.10E+04	1.12E-03	5.35E-03	5.00E+00	B	5.00	9.35E+02	3.4610E+13	345	1.07E+19	1.88E+14	3.46E+13	H		
Se-75	3.46E+01	9.35E+02	3.00E-01	115.37	3.10E+04	1.12E-03	5.35E-03	5.00E+00	B	5.00	9.35E+02	3.4610E+13	345	1.07E+19	7.87E+18	3.46E+13	H		
Tl-201	2.42E+02	6.54E+03	4.00E+00	60.45	7.90E+03	3.06E-02	7.65E-04	5.00E+00	B	5.00	6.54E+03	2.4181E+14	345	2.73E+18	1.41E+22	2.42E+14	H		

Notes

Column	
1	Identifies nuclide
2	Package activity limit for this Contents Type - from Col 17
3	Calculated from Bq amount in Col 2
4	A2 from 10CFR71
5	# of A2's of nuclide at package activity limit
6	Specific activity from 10CFR71
7	Mass of nuclide at package activity limit
8	Heat generation rate of nuclide - from Microshield.
9	Heat output of nuclide at package activity limit
10	Package Type [A or B] based on individual nuclide limit
11	Mass limit of nuclide based on package heat limit
12	Calculated from limit in Col 11
13	Calculated from Bq amount in Col 12
14	Mass limit of nuclide based on capacity of insert
15	Calculated from Bq amount in Col 14
16	Package shielding limit from CTR2011/01
17	Package limit = least of heat, mass and shielding limits in Cols 13, 15 & 16
18	H shown where package limit is Heat limit
19	M shown where package limit is Mass limit
20	S shown where package limit is Shielding limit

Colour codes

	Radionuclides
	Package limit
	Physics data
	Contents limit based on heat, mass or shielding

RAV Notes	
This spreadsheet updated	26/09/2012

Table 7 Activity Limits for Contents Type 5 - CT-5 - Liquid in steel insert – Design No 3986

Contents Type 5 - CT-5 - Liquid in steel insert										Package limits calculations for each nuclide									
										Contents heat limit			Contents mass limit		Shielding limit	Package limit			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Nuclide	Max	Activity	A2	# A2s	Spec Ac	Mass	Heat gen	Heat output	PackageType	Heat output	Act	Act	Mass	Act	Act	Act	Code		
	TBq	Ci	TBq		TBq/g	g	W/Ci	W	A or B	W	Ci	Bq	g	Bq	Bq	Bq	H	M	S
Ho-166	1.54E+00	4.15E+01	4.00E-01	3.84	2.60E+04	5.91E-05	4.29E-03	1.78E-01	B	5.00	1.16E+03	4.3087E+13	1300	3.38E+19	1.54E+12	1.54E+12			S
Lu-177	3.46E+01	9.35E+02	3.00E-01	115.37	3.10E+04	1.12E-03	5.35E-03	5.00E+00	B	5.00	9.35E+02	3.4610E+13	1300	4.03E+19	1.10E+24	3.46E+13	H		
Mo-99	1.47E+01	3.96E+02	3.00E-01	48.88	3.10E+04	4.73E-04	5.35E-03	2.12E+00	B	5.00	9.35E+02	3.4610E+13	1300	4.03E+19	1.47E+13	1.47E+13			S
Se-75	3.46E+01	9.35E+02	3.00E-01	115.37	3.10E+04	1.12E-03	5.35E-03	5.00E+00	B	5.00	9.35E+02	3.4610E+13	1300	4.03E+19	5.84E+18	3.46E+13	H		
Tl-201	2.42E+02	6.54E+03	4.00E+00	60.45	7.90E+03	3.06E-02	7.65E-04	5.00E+00	B	5.00	6.54E+03	2.4181E+14	1300	1.03E+19	1.13E+22	2.42E+14	H		

Notes

Column	
1	Identifies nuclide
2	Package activity limit for this Contents Type - from Col 17
3	Calculated from Bq amount in Col 2
4	A2 from 10CFR71
5	# of A2's of nuclide at package activity limit
6	Specific activity from 10CFR71
7	Mass of nuclide at package activity limit
8	Heat generation rate of nuclide - from Microshield.
9	Heat output of nuclide at package activity limit
10	Package Type [A or B] based on individual nuclide limit
11	Mass limit of nuclide based on package heat limit
12	Calculated from limit in Col 11
13	Calculated from Bq amount in Col 12
14	Mass limit of nuclide based on capacity of insert
15	Calculated from Bq amount in Col 14
16	Package shielding limit from CTR2011/01
17	Package limit = least of heat, mass and shielding limits in Cols 13, 15 & 16
18	H shown where package limit is Heat limit
19	M shown where package limit is Mass limit
20	S shown where package limit is Shielding limit

Colour codes

	Radionuclides
	Package limit
	Physics data
	Contents limit based on heat, mass or shielding

RAV Notes

This spreadsheet updated26/09/2012

Table 8 Activity Limits for Contents Type 6 - CT-6 - Gas in light tungsten insert – Design No 3983

Contents Type 6 - CT-6 - Gas in light tungsten insert										Package limits calculations for each nuclide												
										Contents heat limit			Contents mass limit		Shielding limit	Gas limit	Package limit					
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	15a	17	18	19	19a	20	
Nuclide	Max	Activity	A2	# A2s	Spec Ac	Mass	Heat gen	Heat output	PackageType	Heat output	Act	Act	Mass	Act	Act	Act	Act	Act	Code			
	TBq	Ci	TBq		TBq/g	g	W/Ci	W	A or B	W	Ci	Bq	g	Bq	Bq	Bq	Bq	Bq	H	M	L	S
Kr-79	2.30E+01	6.21E+02	2.00E-02	1148.71	9.24E+04	2.49E-04	5.35E-03	3.32E+00	B	30.00	5.61E+03	2.0766E+14	345	3.19E+19	2.30E+13	3.07E+14	2.30E+13					S
Xe-133	2.08E+02	5.61E+03	1.00E+01	20.77	6.90E+03	3.01E-02	5.35E-03	3.00E+01	B	30.00	5.61E+03	2.0766E+14	345	2.38E+18	1.99E+33	6.97E+15	2.08E+14	H				

Notes

Column	
1	Identifies nuclide
2	Package activity limit for this Contents Type - from Col 17
3	Calculated from Bq amount in Col 2
4	A2 from 10CFR71
5	# of A2's of nuclide at package activity limit
6	Specific activity from 10CFR71
7	Mass of nuclide at package activity limit
8	Heat generation rate of nuclide - from Microshield.
9	Heat output of nuclide at package activity limit
10	Package Type [A or B] based on individual nuclide limit
11	Mass limit of nuclide based on package heat limit
12	Calculated from limit in Col 11
13	Calculated from Bq amount in Col 12
14	Mass limit of nuclide based on capacity of insert
15	Calculated from Bq amount in Col 14
16	Package shielding limit from CTR2011/01
17	Package limit = least of heat, mass and shielding limits in Cols 13, 15 & 16
18	H shown where package limit is Heat limit
19	M shown where package limit is Mass limit
20	S shown where package limit is Shielding limit

Colour codes	
	Radionuclides
	Package limit
	Physics data
	Contents limit based on heat, mass or shielding

RAV Notes	
This spreadsheet updated	26/09/2012

Table 9 Activity Limits for Contents Type 7 - CT-7 - Fissile solid in Normal Form in steel insert – Design No 3986

Contents Type 7 - CT-7 - Fissile solid in steel insert										Package limits calculations for each nuclide									
										Contents heat limit			Contents mass limit		Shielding limit	Package limit			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Nuclide	Max	Activity	A2	# A2s	Spec Ac	Mass	Heat gen	Heat output	PackageType	Heat output	Act	Act	Mass	Act	Act	Act	Code		
	TBq	Ci	TBq		TBq/g	g	W/Ci	W	A or B	W	Ci	Bq	g	Bq	Bq	Bq	H	M	S
Pu-238	3.41E+01	9.21E+02	1.00E-03	34062.66	6.30E-01	5.41E+01	3.26E-02	3.00E+01	B	30.00	9.21E+02	3.4063E+13	1300	8.19E+14	4.85E+14	3.41E+13	H		
Pu-239	2.99E+00	8.08E+01	1.00E-03	2990.00	2.30E-03	1.30E+03	3.06E-02	2.47E+00	B	30.00	9.82E+02	3.6333E+13	1300	2.99E+12	5.38E+23	2.99E+12		M	
Pu-240	1.09E+01	2.95E+02	1.00E-03	10920.00	8.40E-03	1.30E+03	3.06E-02	9.04E+00	B	30.00	9.80E+02	3.6258E+13	1300	1.09E+13	1.87E+13	1.09E+13		M	
Pu-241	4.94E+03	1.34E+05	6.00E-02	82333.33	3.80E+00	1.30E+03	3.10E-05	4.14E+00	B	30.00	9.68E+05	3.5803E+16	1300	4.94E+15	1.72E+19	4.94E+15		M	
U-235	1.04E-04	2.81E-03	unlimited	unlimited	8.00E-08	1.30E+03	2.71E-02	7.62E-05	B	30.00	1.11E+03	4.0937E+13	1300	1.04E+08	2.12E+16	1.04E+08		M	

Notes

Column	
1	Identifies nuclide
2	Package activity limit for this Contents Type - from Col 17
3	Calculated from Bq amount in Col 2
4	A2 from 10CFR71
5	# of A2's of nuclide at package activity limit
6	Specific activity from 10CFR71
7	Mass of nuclide at package activity limit
8	Heat generation rate of nuclide - from Microshield.
9	Heat output of nuclide at package activity limit
10	Package Type [A or B] based on individual nuclide limit
11	Mass limit of nuclide based on package heat limit
12	Calculated from limit in Col 11
13	Calculated from Bq amount in Col 12
14	Mass limit of nuclide based on capacity of insert
15	Calculated from Bq amount in Col 14
16	Package shielding limit from CTR2011/01
17	Package limit = least of heat, mass and shielding limits in Cols 13, 15 & 16
18	H shown where package limit is Heat limit
19	M shown where package limit is Mass limit
20	S shown where package limit is Shielding limit

Colour codes

	Radionuclides
	Package limit
	Physics data
	Contents limit based on heat, mass or shielding

RAV Notes

This spreadsheet updated26/09/2012

Table 10 Activity Limits for Contents Type 8 - CT-8 - Fissile solid in Special Form in steel insert – Design No 3986

Contents Type 7 - CT-7 - Fissile solid in steel insert										Package limits calculations for each nuclide									
										Contents heat limit			Contents mass limit		Shielding limit	Package limit			
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Nuclide	Max	Activity	A2	# A2s	Spec Ac	Mass	Heat gen	Heat output	PackageType	Heat output	Act	Act	Mass	Act	Act	Act	Code		
	TBq	Ci	TBq		TBq/g	g	W/Ci	W	A or B	W	Ci	Bq	g	Bq	Bq	Bq	H	M	S
Pu-238	3.41E+01	9.21E+02	1.00E-03	34062.66	6.30E-01	5.41E+01	3.26E-02	3.00E+01	B	30.00	9.21E+02	3.4063E+13	1300	8.19E+14	4.85E+14	3.41E+13	H		
Pu-239	2.99E+00	8.08E+01	1.00E-03	2990.00	2.30E-03	1.30E+03	3.06E-02	2.47E+00	B	30.00	9.82E+02	3.6333E+13	1300	2.99E+12	5.38E+23	2.99E+12		M	
Pu-240	1.09E+01	2.95E+02	1.00E-03	10920.00	8.40E-03	1.30E+03	3.06E-02	9.04E+00	B	30.00	9.80E+02	3.6258E+13	1300	1.09E+13	1.87E+13	1.09E+13		M	
Pu-241	4.94E+03	1.34E+05	6.00E-02	82333.33	3.80E+00	1.30E+03	3.10E-05	4.14E+00	B	30.00	9.68E+05	3.5803E+16	1300	4.94E+15	1.72E+19	4.94E+15		M	
U-235	1.04E-04	2.81E-03	unlimited	unlimited	8.00E-08	1.30E+03	2.71E-02	7.62E-05	B	30.00	1.11E+03	4.0937E+13	1300	1.04E+08	2.12E+16	1.04E+08		M	

Notes

Column	
1	Identifies nuclide
2	Package activity limit for this Contents Type - from Col 17
3	Calculated from Bq amount in Col 2
4	A2 from 10CFR71
5	# of A2's of nuclide at package activity limit
6	Specific activity from 10CFR71
7	Mass of nuclide at package activity limit
8	Heat generation rate of nuclide - from Microshield.
9	Heat output of nuclide at package activity limit
10	Package Type [A or B] based on individual nuclide limit
11	Mass limit of nuclide based on package heat limit
12	Calculated from limit in Col 11
13	Calculated from Bq amount in Col 12
14	Mass limit of nuclide based on capacity of insert
15	Calculated from Bq amount in Col 14
16	Package shielding limit from CTR2011/01
17	Package limit = least of heat, mass and shielding limits in Cols 13, 15 & 16
18	H shown where package limit is Heat limit
19	M shown where package limit is Mass limit
20	S shown where package limit is Shielding limit

Colour codes

	Radionuclides
	Package limit
	Physics data
	Contents limit based on heat, mass or shielding

RAV Notes

This spreadsheet updated 26/09/2012