


Nonproprietary


Fuel Design Methodology



Larry Linik

December 6, 2012

Nonproprietary



© 2012 NuScale Power, LLC

Agenda

- Purpose of the meeting
- Background
- Plant overview
- Fuel design team
- Schedule implications

{{ }}^{3(a)}

- Design-Specific Review Standard for DCD Section 4.2
- Feedback and next steps

Purpose of the Meeting

- Describe fuel code methodology
 - Present {{ }}^{3(a)} code to NRC
- Present design team to NRC
- Communicate status of fuel design activities
 - Current status
 - Upcoming activities
- Open the discussion for DSRS on DCD Section 4.2
- NRC feedback on the NuScale approach leading to agreement on path for Design Certification


Background

Review of Topics from the May Meeting

{{


}}^{3(a)}

Plant Overview



Reactor Building


Reactor building houses reactor modules, spent fuel pool, and reactor pool




Reactor Module Overview

- Natural Convection for Cooling
 - Passively safe, driven by gravity, natural circulation of water over the fuel
 - No pumps, no need for emergency generators
- Seismically Robust
 - System submerged in a below-ground pool of water in an earthquake resistant building
- Simple and Small
 - Reactor is 1/20th the size of large reactors
 - Integrated reactor design, no large-break loss-of-coolant accidents
- Defense-in-Depth
 - Multiple additional barriers to protect against the release of radiation to the environment

45 MWe Reactor Module




Plant Overview – Natural Circulation




* NC: Natural Circulation

- **Natural circulation in the reactor coolant system (RCS)**
- **Natural circulation in the decay heat removal system (DHRS)**
- **Natural circulation in the emergency core cooling system (ECCS)**

Passive Decay Heat Removal System




- Main steam and main feedwater isolated
- Decay heat removal (DHR) isolation valves opened
- Decay heat passively removed via the steam generators and DHR heat exchangers to the reactor pool



ECCS/Containment Heat Removal

- Reactor vent valves opened on safety signal
- When containment liquid level is high enough, reactor recirculation valves open.
- Decay heat removed
 - condensing steam on inside surface of containment vessel
 - convection and conduction through liquid and both vessel walls




Stable Long-Term Cooling Under All Conditions

Reactor and nuclear fuel cooled indefinitely without pumps or power





No Pumps • No External Power • No External Water



* Based on conservative calculations assuming all 12 modules in simultaneous upset conditions and reduced pool water inventory.

NuScale Core Design

- 17x17 lattice
- Approximately half-height
- 37 assemblies / 16 control rod clusters
- UO₂ fuel pellets
- Clad material – Zr-4 or advanced clad
- Negative reactivity coefficients
- 24 month cycle length at 95% capacity factor (695 effective full power day)
- U-235 enrichment < 4.95 %





Fuel Design Team

Fuel Design Team

{

}}^{3(a)}

Roles and Responsibilities

{{

}}^{3(a)}

Quality Assurance

- NuScale has adopted ASME NQA-1 2008/2009 Addenda
- {{
}}^{3(a)}
- {{
}}^{3(a)}
- The audit identified four non-compliances
 - Design assumptions
 - Independently review and requirements traceability
 - Authentication of records
 - Definition of basic component not properly implemented
- {{
– All four to be completed Dec 31, 2012
}}^{3(a)}
- {{
}}^{3(a)}

Software Quality Assurance

- {{

}}^{3(a)}

- {{

}}^{3(a)}

- {{

}}^{3(a)}

- All future development work will be performed in accordance with ASME NQA-1 2008/2009

Interactions

{

}}^{3(a)}



Schedule Implications

Fuel Design Schedule

- Pre-submittal activities
 - Fuel mechanical design
 - Fuel mechanical testing
 - Fuel rod design
- Post-submittal activities
 - Confirmatory fuel mechanical testing
 - If required, fuel mechanical and rod design

Schedule Overview

{

}}^{3(a)}

Schedule Overview

{

}}^{3(a)}

Pre-Submittal Activities

{{

}}^{3(a)}

Post-Submittal Activities

{

}}3(a)

Key Milestones

{{

}}3(a)

Opportunities for Testing Observations

{{


}}^{3(a)}

Summary

- Competent, experienced team functioning as planned
- Detailed schedule provides a path for success
- Making tangible progress

Questions?

{



3(a)

Contents

I Introduction

II Code Description

III Application Analyses to NuScale SMR

IV Assessment of Design Methodology

V Quality Assurance

{{

}}3(a)

I. Introduction

{{

}}3(a)





}}3(a)



{{

}}^{3(a)}

II. Code Description

{{

}}^{3(a)}

{{

}}^{3(a)}



}}3(a)

II-2. Fuel rod design codes

{{

{{

}}^{3(a)}

}}^{3(a)}

II-3. Summary of development

{{

}}^{3(a)}

}}^{3(a)}







}}3(a)



II-8. Coolant/Cladding temperature

{{

}}3(a)

{{

}}3(a)

II-9. Pellet-clad gap conductance

{{

}}^{3(a)}

{{

}}^{3(a)}

II-10. Pellet temperature

{{



}}^{3(a)}

{{

}}^{3(a)}

II-11. Fission gas release (1)

{



}}^{3(a)}

{

}}^{3(a)}

II-11. Fission gas release (2)

{{



{{

}}^{3(a)}

}}^{3(a)}

II-12. Mechanical models

{{



}}^{3(a)}

{{

}}^{3(a)}

II-13. Clad creep

{



}}^{3(a)}

{

}}^{3(a)}

II-14. Clad corrosion

{{



{{

}}3(a)

}}3(a)





}}3(a)

{{

}}3(a)

III. Application Analyses to NuScale SMR

{{

}}3(a)



}}3(a)



}}^{3(a)}



{{

}}^{3(a)}

IV. Assessment of Design Methodology

{{

}}^{3(a)}

IV-1. Fuel rod design criteria

- NUREG-0800, US NRC SRP 4.2, II. Acceptance Criteria (Mar. 2007, Rev. 03)
- Applicable Regulatory Guide

➤ Fuel system damage criteria

- I. Stress/Strain, or loading limits
- II. Strain fatigue
- III. Fretting wear
- IV. Oxidation, hydriding, and crud
- V. Dimensional change
- VI. Internal pressure
- VII. Hydraulic loads
- VIII. Control rod reactivity and insertability

➤ Fuel rod failure criteria

- I. Hydriding
- II. Cladding collapse
- III. Overheating of cladding
- IV. Overheating of fuel pellets
- V. Excessive fuel enthalpy
- VI. Pellet/cladding interaction
- VII. Bursting
- VIII. Mechanical fracturing

IV-2. {{ [redacted] }}^{3a} fuel rod/system design criteria (1)

{{



}}^{3(a)}

{{

}}^{3(a)}

IV-2. {{ [redacted] }}^{3(a)} fuel rod/system design criteria (2)

{{

{{

}}^{3(a)}

}}^{3(a)}

IV-2. {{ [redacted] }}^{3(a)} fuel rod/system design criteria (3)

{{

}}^{3(a)}

}}^{3(a)}

IV-3. Fuel rod design methodology

{{

}}^{3(a)}

}}^{3(a)}

{{

}}3(a)

V. Quality Assurance

{{

}}3(a)

VI-1. Quality Assurance

{



}}^{3(a)}

{

}}^{3(a)}



Design-Specific Review Standard

Objective

Achieve agreement on the appropriate set of Specified Acceptable Fuel Design Limits (SAFDLs) for the NuScale fuel for the Design Control Document (DCD) Design-Specific Review Standard (DSRS)

Benefits

- NuScale
 - Design focused on issues directly related to plant safety
 - Streamlined DCD development
 - Reduced cost
- NRC
 - Review focused on issues directly related to plant safety
 - Streamlined DCD review
 - Focused combined operating license review
 - More efficient use of staff resources
- Customers
 - Plant operation focused on issues directly related to plant safety

NuScale SAFDL Approach

Recommended strategy for development of the NuScale DSRS:

- **Group-1:** Analyses to be performed in support of Design Certification and Operating License Application
 - Analyses directly related to demonstrating plant safety
- **Group-2:** Analyses required by SRP not relevant
 - Demonstrate conditions underpinning acceptance criteria are precluded by inherent design features, e.g., LBLOCA
 - Operating regime limitations change acceptance criteria relevance to NuScale design

Group 1 Examples

{{

}}3(a)

Group 2 Examples

{{

}}^{3(a)}

Group 2 Examples (continued)

{{

}}^{3(a)}

A. Fuel System Damage

{{

}}^{3(a)}

B. Fuel Rod Failure

{{

}}3(a)

C. Fuel Coolability

{{

}}^{3(a)}

Feedback and Next Steps

- Staff feedback
 - Design team
- $\{\{\}$ $\}\}^{3(a)}$
 - Schedule
- Continue to develop detailed justification
 - E-room
- DSRS and plans for next interaction with the staff