NUREG-xxxx

United States Nuclear Regulatory Commission Spent Fuel Transportation Risk Assessment

Draft Report for Comment



U.S. Nuclear Regulatory Commission Office of Nuclear Material Safety and Safeguards Washington, DC 20555-0001



I-29

NUREG-xxxx

United States Nuclear Regulatory Commission Spent Fuel Transportation Risk Assessment

Draft Report for Comment

Manuscript Completed: Month 2011 Date Published: Month 2011

Division of Spent Fuel Storage and Transport Office of Nuclear Materials Safety and Safeguards U.S. Nuclear Regulatory Commission Washington, DC 20555-0001



COMMENTS ON DRAFT REPORT

Any interested party may submit comments on this report for consideration by the NRC staff. Comments may be accompanied by additional relevant information or supporting data. Please specify the report number, Draft NUREG-xxxx, in your comments, and send them by Month, 2011, to the following address:

Chief, Rules, Inspection, and Operations Branch U.S. Nuclear Regulatory Commission Mail Stop E3-D2M Washington, DC 20555-0001

You may also provide comments at the NRC Web site:

http://www.nrc.gov/public-involve/doc-comment/form.html. For any questions about the material in this report, please contact:

Mr. John Cook Mail Stop E3-D2M U.S. Nuclear Regulatory Commission Washington, DC 20555-0001 Phone: 301-492-3318 Fax: 301-492-xxxx E-mail: John.Cook@nrc.gov

iii

ABSTRACT

iv

·

· · · ·

Table of Contents

e

ABSTR	ACT IV
LIST OF	FIGURES IX
LIST OF	TABLESXIII
ACRON	YMS XVI
CHEMI	CAL SYMBOLSXVII
PUBLIC	SUMMARY XIX
CHAPT	ER 1 INTRODUCTION1
1.1	History and Purpose of this Analysis
1.2	Risk 2 1.2.1 Accident Data 3 1.2.2 Radioactive Materials Transportation Scenarios 4
1.3	Regulation of Radioactive Materials Transportation
1.4	Selection of Casks
1.5	Organization of this Report. 10 1.5.1 Chapter 1 and Appendix I 10 1.5.2 Chapter 2 and Appendix II 10 1.5.3 Chapter 3 and Appendix III 11 1.5.4 Chapter 4 and Appendix IV 11 1.5.5 Chapter 5 and Appendix V 11 1.5.6 Chapter 6 and Appendix VI 11 1.5.7 Bibliography 11
CHAPT	ER 2 RISK ANALYSIS OF ROUTINE TRANSPORTATION
2.1	Introduction
2.2	Radiation Emitted during Routine Transportation
2.3.	The RADTRAN Model of Routine, Incident-Free Transportation 17 2.3.1 The Basic RADTRAN Model 17 2.3.2 Individual and Collective Doses 17 2.3.3 Doses to members of the public occupying vehicles that share the route 26 2.3.4 Doses at Stops 30
2.4	Doses to Workers
2.5	Unit Risk

v

2.6	Conclusions	
СНАРТ	FR 3 CASK RESPONSE TO IMPACT ACCIDENTS	38
31	Introduction	38
2.1	Finite Element Analyses of Casks	20
5.2	3.2.1 Rajl-Steel Cask	
	3.2.2 Rail-Pb Cask	
	3.2.3 Truck-DU Cask	
3.3	Impacts onto Yielding Targets	
3.4	Effect of Impact Angle	
3.5	Impacts with Objects	
3.6	Response of Spent Fuel Assemblies (Kalan et al., 2005)	60
3.7	Conclusions	62
CHAPT	ER 4 CASK RESPONSE TO FIRE ACCIDENTS	65
4.1	Introduction	
4.2	Description of Accident Scenarios	65
	4.2.1 Pool size	65
	4.2.2 Fire duration.	
	4.2.3 Hypothetical accident configurations for the rall casks	
4.3	Analysis of Fire Scenarios Involving Rail Casks	
	4.3.1 Simulations of the tries	
	4.3.3 Simulations of the spent fuel region	
	4.3.4 Rail-Steel cask results	
	4.3.5 Rail-Pb cask results	
4.4	Truck Cask Analysis	
4.5	Conclusions	
CHAPT	ER 5 TRANSPORTATION ACCIDENTS	95
5.1	Types of Accidents and Incidents	95
5.2	Accident probabilities	95
5.3	Accidents With No Attributable Radiation Dose	
5.4	Accidental Loss of Shielding	
	5.4.1 Loss of Lead Gamma Shielding	
	5.4.2 Neutron shielding	
5.6	Conclusions	113
СНАРТ	FR 6 OBSERVATIONS AND CONCLUSIONS	116
41 61	Pouting Transportation	
0.1	Tenerestation Assilute	
0.2	Transportation Accidents	

vi

APPENDIX I	119
APPENDIX II	197
APPENDIX III	239
APPENDIX IV	
APPENDIX V	
BIBLIOGRAPHY	421

1

vii

•

LIST OF FIGURES

Figure PS-1. Model of a spent fuel cask in routine, incident-free transportation and radiation dose to a member of the public
Figure PS-2 Collective doses (nerson-Sv) from routine truck transportation vvi
Figure PS-3. Correction backs (person of) and target at 07 kpl (60 mph) accident scenario for a scent
Figure 13-5. Content impact onto a rigid target at 97 kpm (oo minn) accident scenario for a spent
The case and the deformations produced by the impact. $x_{\rm eff}$ is the cash following a 2 hours
Figure FS-4. Enguining fire scenario and the temperature contours in the cask following a 3-nour
fire duration. The transparency of the flames has been increased so the cask can be seen. In
the actual fire simulation, and in a real fire, the flames are opaque
Figure PS-5. Accident collective dose risks
Figure 1-1. The four tests for Type B casks
Figure 1-2. NAC-STC cask (courtesy of NAC International)
Figure 1-3. Basic layout of the HI-STAR 100 rail transport cask (from Haire and Swaney, 2005, and Holtec International, 2004)
Figure 1-4. GA-4 cask (courtesy of General Atomics)
Figure 2-1. The upper figure is an exploded view of a generic spent fuel cask. The lower figure is
a cross-section of the layers of the cask wall. (Sandia National Laboratories archive)
Figure 2-2. RADTRAN model of the vehicle in routine, incident-free transportation. The cask in
this diagram is positioned horizontally, and the critical dimension is the cask length
Figure 2-3. Diagram of a truck route as modeled in RADTRAN (not to scale)
Figure 2-4. A segment of U.S.1 along the Florida coast (courtesy of G. Scott Mills)
Figure 2-5. Diagram for calculating radiation doses to occupants of other vehicles (from
Neuhauser et al. 2000)
Figure 2-6. Diagram of truck stop model (not to scale)
Figure 3-1. Impact orientations analyzed 39
Figure 3-2 Finite element mesh of the Bail-Steel cask 40
Figure 3-3 Details of the finite element mesh for the impact limiters of the Bail-Steel cask 41
Figure 3-4. Finite element mesh of the Rail-Steel closure bolts and the closure end impact limiter
attachment holts. The highly refined mesh in these critical parts assures an accurate
assessment of the closure response 42
Figure 3-5 Plastic strain in the welded canister of the Rail-Steel for the 193 kph side impact case
Figure 3-6 Finite element mesh of the Rail-Ph cask 44
Figure 3-7. Details of the finite element mesh for the impact limiters of the Rail-Ph 45
Figure 3-8 Finite element mesh of the Rail-Ph closure bolts for both the inner and outer lids. The
longer bolts are for the inner lid and the scotter ones for the outer lid 46
Figure 3-9. Deformed shape of the Bail-Ph cask following the 103 kph impact onto an unvielding
trate in the end on orientation
Figure 2 10 Deformed shape of the Dail Db following the 102 lmb impact onto an unviolding
target in the comparison of the Kan-ro following the 195 kph impact onto an unyleiding
Target in the content of the Dail Dh following the 145 km impact anto an unviated and
rigure 5-11. Deformed snape of the Kan-Po following the 145 kpn impact onto an unyielding
target in the side offentiation
Figure 5-12. Deformed snapes and plastic strains in the generic steel-DU-steel truck cask from
NUKEG/UK-00/2 (impact limiter removed)

ix

Figure 3-13. Force generated by the Rail-Pb cask penetrating hard desert soil	. 55
Figure 3-14. Probability distribution for impact angles	. 57
Figure 3-15. Influence of impact angle on effective velocity	. 57
Figure 3-16. Deformations to the GA-4 truck cask after a 96 kph side impact onto a rigid semi	i-
circular column, from (NRC, 2003b).	. 58
Figure 3-17, Configuration of locomotive impact analysis (from Ammerman et al., 2005)	. 59
Figure 3-18. Sequential views of a 129 kph impact of a locomotive into a GA-4 truck cask (fro	om
Ammerman et al., 2005)	. 59
Figure 3-19. Results of a finite element simulation of an elevated freeway collapse onto a GA-	-4
spent fuel cask (from Ammerman and Gwinn 2004)	. 60
Figure 3-20. Finite element model of a PWR fuel assembly.	. 61
Figure 3-21. Detailed finite element model of a single fuel rod.	. 61
Figure 3-22. Maximum strains in the rod with the highest loads.	. 62
Figure 4-1. Cask on ground concentric with fuel pool	. 67
Figure 4-2. Cask on ground and the 3m offset pool fire	. 67
Figure 4-3. Cask on ground and the 18m offset pool fire	. 68
Figure 4-4. Regulatory pool fire configuration	. 68
Figure 4-5. Finite element models of the two rail casks. The left figure is the Rail-Steel and the	e
right figure is the Rail-Pb	. 71
Figure 4-6. Temperature distribution of the Rail-Steel cask at the end of the 30-minute 800°C	
regulatory uniform heating	. 73
Figure 4-7. Temperature of key cask regions, Rail-Steel cask - Regulatory uniform heating	. 73
Figure 4-8. Temperature distribution of the Rail-Steel cask at the end of the 30-minute regulate	ory
CAFE fire	. 74
Figure 4-9. Temperature of key cask regions, Rail-Steel cask - Regulatory CAFE fire	. 75
Figure 4-10. Comparison of regulatory fire analysis - Rail-Steel cask: Uniform heating vs. CA	FE
fire	. 75
Figure 4-11. Gas temperature plots from the regulatory CAFE fire analysis	. 76
Figure 4-12. Fuel concentration plots from the regulatory CAFE fire analysis	. 77
Figure 4-13. Temperature distribution of the Rail-Steel cask at the end of the 3-hour concentri-	с
CAFE fire - cask on ground	. 78
Figure 4-14. Temperature of key cask regions, Rail-Steel cask - Cask on ground, concentric fi	re
	. 79
Figure 4-15. Gas temperature plots from the CAFE fire analysis of the cask on ground	. 80
Figure 4-16. Fuel concentration plots from the CAFE fire analysis of the cask on ground	. 81
Figure 4-17. Temperature distribution of the Rail-Steel cask at the end of the 3-hour 3m offset	l.
CAFE fire - cask on ground	. 82
Figure 4-18. Temperature of key cask regions, Rail-Steel cask – Cask on ground, 3m offset fir	re . 82
Figure 4-19. Temperature distribution of the Rail-Steel cask at the end of the 3-hour 18m offse CAFE fire - cask on ground	et 83
Figure 4-20. Temperature of key cask regions, Rail-Steel cask – Cask on ground, 18m offset f	ire 83
Figure 4-21. Temperature distribution of the Rail-Pb cask at the end of the 30-minute 800°C regulatory uniform heating	. 85
Figure 4-22. Temperature of key cask regions, Rail-Pb cask – Regulatory uniform heating	. 85

x

Figure 4-23. Temperature distribution of the Rail-Pb cask at the end of the 30-minute regulatory	
Figure 4.24 Temperature of low each regions, Bail Dheadh Begulatery CAFE fire	
Figure 4-24. Temperature of Key Cask regions, Rail-PD cask – Regulatory CAFE life	
Figure 4-23. Comparison of regulatory fire analysis – Kan-Po cask: Uniform heating VS. CAFE	
Figure 4.26 Temperature distribution of the Dail Db cask at the end of the 3 hour concentric	
CAFE fire _ cask on ground	
CALL INC - Cask on ground	
Figure 4-27. Temperature distribution of the Dail Db cack at the and of the 2 hour 2m official	
CAFE fire cosk on ground	
CATE Inc - cask on ground	
Figure 4.20. Temperature distribution of the Dail Db cock at the and of the 2 hour 19m official	
CAFE fire least on ground	
CAPE Int - cask on ground	
Figure 4.37. Boil Ph cosk lead commo shield region - maximum lead malt at the middle of the	
right 4-52. Kail-10 cask lead gaining sheld region - maximum lead men at the middle of the	
Figure 4-33 Rail Ph cask lead common shield region maximum lead malt at the middle of the	
rigure 4-55. Kail-r o cask leau gamma sinclu region - maximum leau men at the midule of the	
Figure 5-1 Accident frequencies in the U.S. from 1991 until 2007	
Figure 5-7. Rediation dose to the maximally exposed individual (MEI) from loss of lead comma	
shielding at distances from one to five meters from the cask carrying spent fiel. The	
borizontal axis represents the fraction of shielding lost the shielding gap, and is not to	
scale	
Figure 5-3. Padiation dose to the maximally exposed individual from loss of lead gamma	
shielding at distances from 20 to 100 meters from the cask carrying spent fuel. The vertical	·
axis is logarithmic so that all of the doses can be shown on the same graph. The borizontal	
axis is logarithmic, so that all of the doses can be shown on the same graph. The horizontal	
Eigure 5.4 Air and ground concentrations of radioactive material following on release	•
Figure 6-1 Collective doses (person-Sy) from routine truck transportation 117	
Figure 6-2 Collective doses (person-Sv) from routine rail transportation 117	
Figure 6-3. Collective doses (person-sy) to train and railyard crew in routine transportation 110	
Figure 6-4 Maximum individual dose (Sv) from routine transportation	
Figure 6-5 Accident collective dose risks	
· · · · · · · · · · · · · · · · · · ·	

xi

xii

LIST OF TABLES

Table 1-1, NRC Certified Commercial Light Water Power Reactor Spent Fuel Casks	7
Table 2-2. Maximum individual in-transit doses	. 19
Table 2-3. Characteristics of rural, suburban, and urban routes used in RADTRAN	. 20
Table 2-4. Route segment lengths and population densities, Kewaunee NP to ORNL	. 21
Table 2-5. Specific routes modeled. Urban kilometers are included in total kilometers	. 22
Table 2-6. Collective doses (person-Sv) for rail transportation	. 24
Table 2-7. Collective doses (person-Sv) for truck transportation (1 Sv = 10^5 mrem)	. 25
Table 2-8. Collective doses (person-Sv) to occupants of trains sharing the route	. 27
Table 2-9. Collective doses (person-Sy) to occupants of vehicles sharing truck routes	. 29
Table 2-10. Some sample data for calculating doses at stops	. 31
Table 2-11, Collective doses at rail stops on the Maine Yankee-to-Hanford route (person-Sv).	. 32
Table 2-12. Collective doses to residents near truck stops (person-Sy)	. 33
Table 2-13. Occupational doses per shipment from routine incident-free transportation	. 34
Table 3-1. Maximum lead slump for the Rail-Pb from each analysis case*	47
Table 3-2. Available areas for leakage from the Rail-Pb cask	. 50
Table 3-3. Comparison of analyses between this study and NUREG/CR-6672	52
Table 3-4. Deformation of the closure region of the steel-DU-steel truck cask from NUREG/C	R-
6672 in mm	54
Table 3.5. Peak contact force for the Rail-Pb cask impacts onto an unvielding target (hold	
numbers are for the cases where there may be seal leaks)	. 55
Table 3-6. Equivalent velocities for impacts onto various targets with the Rail-Ph cask kph	56
Table 3-7. Accident speeds that result in the same damage as a perpendicular impact, kph	57
Table 5-1. Illustrations of net probability	. 96
Table 5-2. Scenarios and conditional probabilities of rail accidents involving the Rail-Pb cask	. 98
Table 5-3. Dose to an emergency responder from a cask in a no-shielding loss, no-release	
accident	. 99
Table 5-4. Collective doses to the public from a no-shielding loss, no-release accident involvi	ng
rail casks (person-Sv)	.99
Table 5-5. Collective doses to the public from a no-shielding loss, no-release accident involvi	ng
a truck cask (person-Sv).	100
Table 5-6. Average railcar accident frequencies and accidents on the routes studied.	104
Table 5-7. Collective dose risks in person-Sy for a loss of lead shielding accident	104
Table 5-8. Doses to an emergency responder or other individual five meters from the cask	105
Table 5-9. Radionuclide inventory for accident analysis of the Rail-Pb cask (TBa)	107
Table 5-10. Parameters for determining release functions for the accidents that would result in	107
release of radioactive material	108
Table 5-11. Doses (consequences) in Sy to the maximally exposed individual from accidents t	hat
involve a release	110
Table 5-12. Total collective dose risk (person-Sv) for release accidents for each route	111
Table 5-13. Total collective dose risk (person-Sv) for each route from a loss of shielding accid	lent
<i>a a b b b b b b b b b b</i>	111
Table 5-14. Total collective dose risk (person-Sv) from release and loss of shielding accidents	
	111

xiii

Table 5-15. Total collective dose risk (person-Sv) from no-release, no-loss of shielding accidents
Table 5-16. Total collective dose risk (person-Sv) from loss of neutron shielding 112
Table 5-17. Total collective dose risk (person-Sv) from all accidents

xiv

1

•

× 1

.

XV

ACRONYMS

activity median aerodynamic diameter
becquerel
boiling water [nuclear] reactor
Code of Federal Regulations
curie
Certificate of Compliance
[U.S.] Department of Energy
[U.S.] Department of Transportation
depleted uranium
[U.S.] Environmental Protection Agency
equivalent plastic strain
high-level [radioactive] waste
International Atomic Energy Agency
[U.S.] Interagency Steering Committee on Radiation Standards
kilometers per hour
latent cancer fatalities
maximally exposed individual
multi-purpose canister
miles per hour
millirem
metric tons of uranium
megawatt-days
[U.S.] Nuclear Regulatory Commission
pressurized water [nuclear] reactor
Roentgen equivalent man
sievert

CHEMICAL SYMBOLS

Cm	curium
Со	cobalt
Cs	cesium
I ·	iodine
Kr	krypton
Pb	lead
Pu	plutonium
U	uranium

xvii

.

xviii

PUBLIC SUMMARY

Spent nuclear fuel is extremely radioactive. People are understandably concerned when spent fuel is moved in trucks and by rail over public roads and railroads. Thirty-five years ago the Nuclear Regulatory Commission responded to this concern by estimating what the radiation impact of transporting radioactive materials, including spent fuel, would be. The result was the Final Environmental Statement on the Transportation of Radioactive Material by Air and Other Modes, NUREG-0170, published in 1977, an environmental impact statement for transportation of all types of radioactive material by road, rail, air, and water. This EIS concluded that:

- The average radiation dose to members of the public from routine transportation of radioactive materials is a fraction of the background dose.
- The radiological risk from accidents in transporting radioactive materials is very small compared to the non-radiological risk from accidents involving large trucks or freight trains.

On the basis of this EIS, 1981 regulations were considered "adequate to protect the public against unreasonable risk from the transport of radioactive materials." The adequacy of these regulations was questioned, however, because the EIS was based mostly on estimates of radiation dose and accident rate, and not much data or information was available to support those estimates. Questions about "reasonable" risk and about accident consequences ("what if the accident does happen?") have also been raised.

Trucks and railcars carrying casks of spent nuclear fuel can have accidents like any other truck or railcar of similar size and weight. The Nuclear Regulatory Commission recognizes this, and requires that spent fuel casks be designed and built to withstand very severe accidents. Nonetheless, questions have been raised about accidents that are worse than what the cask is designed for. The NUREG 0170 and later studies of casks have considered accident conditions more severe than those the regulations require the cask to meet.

A 1987 study applied actual accident statistics to projected spent fuel transportation. This "Modal Study" also recognized that accidents could be described in terms of the strains they produced in the cask (for impacts) and the increase in cask temperature (for fires). Like NUREG-0170, the 1987 study based risk estimates on models, because spent fuel shipments had not had enough accidents to support projections or predictions. A 2000 study of two generic truck casks and two generic rail casks analyzed the cask structures and response to accidents a computer modeling technique. Truck and rail accident statistics for general freight shipments were used because even by 2000 there had been too few accidents involving spent fuel shipments to provide statistically valid data.

The dispersion of material released from the cask in an accident was also modeled with increasing refinement. NUREG-0170 assumed that most very severe accidents would result in release of all of the releasable cask contents to the environment; this engineering judgment was known to overstate the release but was nevertheless used because analytical capabilities at the time did not permit a more accurate assessment of the release. The 2000 study analyzed the physical properties of spent fuel rods in a severe accident, and revised estimates of material released to one percent or less of the NUREG-0170 estimates. Accordingly, risk estimates were

Comment [JRC1]: Before introducing the 2000 study, what were the results of the 1987 study? Deleted: using finite element modeling, Deleted: relatively sophisticated

Deleted: the calculated risk then depended on accident rate

xix

revised downward. The 2000 study also verified that an accidental release of radioactive material could only be through the seals at the end of the cask where the lid is attached: an accident could cause seal failure, but no breach in the cask body.

The present study models real casks and the commercial spent nuclear fuel that these casks are certified to transport. Two rail casks and a truck cask are evaluated. <u>Rail casks are believed</u> <u>likely to be used for most future shipments.</u>

Almost all spent fuel casks are shipped without incident. However, even this routine, incident free transportation causes radiation exposures, because all loaded spent fuel casks emit some external radiation. The radiation dose rates for spent fuel shipments are measured before each shipment and kept below regulatory limits. The radiation dose from this external radiation to any member of the public during routine transportation, including stops, is barely discernible compared to natural background radiation. Figure PS-1 shows an example cask and the way the radiation to a member of the public is modeled.



Deleted	from routine, incident free transportation
Deleted	, as the regulations allow

Deleted: Measured external dose rates determine

Comment [JRC2]: Delete: "TI" and "0.5 CD = "Virtual" Cask Radius are not explained and too technical for public summary.

Figure PS-1. Model of a spent fuel cask in routine, incident-free transportation and radiation dose to a member of the public

The external radiation from the spent fuel cask results in a very small dose to each <u>person along</u> the route traveled by the cask. The collective dose <u>from routine</u> transportation is the sum of all of these doses. For this study, several example transportation routes were examined. Table PS-1 gives the total dose to all of the exposed people for one of these routes, the truck shipment from the Maine Yankee Nuclear Power Plant to Oak Ridge National Laboratory. The background radiation dose the exposed people experience during the time of the shipment is also included.

Deleted:	person along	
Deleted:	from routine	

Comment [JRC3]: Relabel person as member of
public near shipment. Is the person and distance
drawn to scale? Remove following page (now

Exposed Population	Rural	Suburban	Urban	Urban Rush Hour	Total
Residents near route	7.9x10 ⁻⁶	1.4×10^{-4}	2.9 x10 ⁻⁶	6.5 x10 ⁻⁸	1.5×10^{-4}
Traffic on the route	1.3×10^{-4}	2.3×10^{-4}	5.4 x10 ⁻⁵	5.0 x10 ⁻⁶	4.2×10^{-4}
Residents near truck stops	1.1x10 ⁻⁶	2.3 x10 ⁻⁵	*	*	2.4 x10 ⁻⁵
Truck Crew	5.6x10 ⁻⁸		4.8x10 ⁻⁹		6.1x10 ⁻⁸
Escort	4.7x10 ⁻⁸		4.3x10 ⁻⁹		5.1x10 ⁻⁸
Inspectors (10 inspections)					3.2x10 ⁻⁸
Truck stop workers					2.0x10 ⁻⁹
Background					8.81

Table PS-1. Collective dose from routine transport for the truck route from Maine Yankee Nuclear Power Plant to Oak Ridge National Lab (person-Sv)

*Most truck stops are located in rural or suburban areas

.

The collective doses calculated for routine transportation have gone down with each successive study of the risks from spent fuel transportation. Figure PS-2 shows a comparison of the collective doses calculated in the three studies for truck transportation.



Figure PS-2. Collective doses (person-Sv) from routine truck transportation

The study uses current (2006 to 2008) truck and rail accident statistics to determine the probability of an accident and the severity of that accident. Detailed analyses are performed to evaluate how the cask responds to the accident. Figure PS-3 shows one impact scenario, a 97 kph

Comment [JRC4]: This table is too complicated for public summary. Perhaps a pie chart just showing background total and shipment total - may have to show zoom-in on shipment wedge.

Comment [JRC5]: What is the total of the listed transport-related doses? ~5.9x10-4?

Comment [JRC6]: Why is this value used in the figure below

Comment [JRC7]: A statement of comparison between the transport total and this value should be included in the text. Confirm this is background collective dose to population exposed to routine transport only and does not include background collective dose to population potentially exposed in an accident. Might add that the population receives this dose whether there is any shipment or not.

Comment [JRC8]: What do you mean by "This study normalized"?

Comment [JRC9]: The change in colors for the same cask regions in the two illustrations is distracting, if not confusing. Can this be corrected?

(60 mph) corner impact onto a rigid target, and the resulting deformations. Almost all of the deformation is in the impact limiter, a device that is added to the cask to absorb energy, much like the bumper of a car. Similar analyses were performed for impacts at 48, 97,145, and 193 kilometers per hour (kph)—equal to 30, 60, 90, and 120 mph—in end-on, corner, and side-on orientations for two cask designs. These impact speeds encompass all accidents for truck and rail transportation. Figure PS-4 shows one fire scenario, a three-hour engulfing fire, and the resulting temperature distribution in the cask. Additional simulations were performed with the fire offset from the cask. These fires include all fire-related <u>accidents in</u> rail transportation. The longest duration for an engulfing fire during truck transportation is one hour, due to the smaller amount of fuel that is carried on board a tanker truck.

Deleted: accidents in

The detailed simulations were performed for two spent fuel casks that are intended for transportation by railroad, the NAC-STC and the HI-STAR 100. In addition, the results for a third cask, the GA-4, which is intended for transportation by truck, are inferred from earlier analyses.



Figure PS-3. Corner impact onto a rigid target at 97 kph (60 mph) accident scenario for a spent fuel cask and the deformations produced by the impact.



Figure PS-4. Engulfing fire scenario and the temperature contours in the cask following a 3-hour fire duration. The transparency of the flames has been increased so the cask can be seen. In the actual fire simulation, and in a real fire, the flames are opaque.

The impact and thermal analysis results indicate that for the truck transportation cask no accident results in release of radioactive material or reduction in the effectiveness of the gamma shielding. The only radiological consequence of an accident is due to the long duration stop that is associated with the accident for responders to clear the accident scene and to arrange for shipment resumption. During this stop emergency responders could be fairly close to the cask. Because there is no loss in effectiveness of the gamma shielding, the radiation dose to these responders is quite small.

For rail transport of spent fuel enclosed within an inner welded canister, the detailed impact and thermal analyses indicate there would be no release of radioactive material in any accident. For some very improbable impacts and some long duration fires there could be a small reduction in the effectiveness of the lead gamma shielding, leading to an elevated external radiation level. This loss of shielding results in a maximum dose to a person 20 meters from the cask of $2x10^{-5}$ Sv and a collective population dose risk of less than $6x10^{-9}$ person-Sv.

For rail transport of spent fuel that is not enclosed within an inner welded canister, there is the possibility for some release of radioactive material following exceptionally severe (and improbable) impacts. The maximum dose to an individual from this release is 1.6 Sv and the collective population dose risk is less than 5×10^{-7} person-Sv.

Similar to the routine transportation collective doses, the collective dose risk from accidents has decreased with each successive risk assessment. Figure PS-5 shows a comparison of collective

Comment [JRC10]: The left and right cask images need to be explained better – e.g., right cask looks like a stand-off example. Perhaps 2 figures would be better than the combined figure shown.

Comment [JRC11]: Replace with rail cask model.

Comment [JRC12]: Check throughout report: consistent use regarding dual units. Comment [JRC13]: Per shipment from Table

Comment [JRC14]: Use "lead" instead of "Pb" Comment [JRC15]: Many bars, multiple colors, scientific notation – this figure does not appear sufficiently clear/suitable for the public summary.

xxiii

doses from the three studies. This study considered accident doses from one source that was neglected in the prior studies, the dose that results from accidents where there is no release and no loss of shielding (LOS), but increased exposure to a cask that is stopped for an extended period of time. Considering this scenario is important because over 99.999 percent of all accident scenarios do not lead to release or loss of shielding.



Figure PS-5. Accident collective dose risks

A final point of comparison between the studies is the maximum consequence of an accident. For NUREG-0170 this was about 110 person-Sv, for NUREG/CR-6672 it was about 9000 person-Sv, and for this study it is about 2 person-Sv. Not only is the estimated risk of spent fuel transportation exceedingly small, but the estimated maximum consequence is also very small.

In sum:

provide bullet list of take-aways

The analyses and results described in this report provide assurance that spent fuel shipments can be completed safely, and that the excellent safety record for spent fuel shipments can be maintained.

xxiv

Deleted: One other

Comment [JRC16]: Add to acronyms

CHAPTER 1

INTRODUCTION

1.1 History and Purpose of this Analysis

The purpose of this study is analysis of the radiological risks of transporting spent nuclear fuel, in both routine transportation and transportation accidents, using the latest available data and modeling techniques. This study is the latest in a series of such assessments and rounds out this series by analyzing the behavior of certified casks carrying fuel of known isotopic composition and burnup. The studies that preceded this one were based on conservative and generic

assumptions. <u>This</u> study is not intended to be a risk assessment for any particular transportation campaign, like transportation from reactors to a permanent repository, and does not include the probabilities or consequences of malevolent acts.

The Nuclear Regulatory Commission (NRC) <u>certifies</u> casks used to transport spent nuclear fuel under Title 10 of the Code of <u>Federal</u> Regulations Part 71 (10 CFR Part 71). Part of the technical basis for this regulation was NUREG-0170, the Final Environmental Statement on the Transportation of Radioactive Material by Air and Other Modes (NRC, 1977), an environmental impact statement for transportation of all types of radioactive material by road, rail, air, and water. The conclusions drawn from this environmental <u>impact statement</u> were:

- The average radiation dose to members of the public from routine transportation of radioactive materials is a fraction of the background dose.
- The radiological risk from accidents in transporting radioactive materials is very small compared to the non-radiological risk from accidents involving large trucks or freight trains.
- The regulations in force at the time (1981) were "adequate to protect the public against unreasonable risk from the transport of radioactive materials." (46 FR 21629, April 13, 1981)

The risk assessment of NUREG-0170 was based on very conservative estimates of risk parameters, and on the imprecise models available at the time. The NRC concluded that the regulations were adequate because even very conservative estimates of risk parameters did not result in unacceptable risk. NRC also recognized that the agency's policies on radioactive materials transportation should be "subject to close and continuing review." In the spirit of continuing review, two comprehensive contractor reports dealing with <u>spent fuel</u> transportation have been issued since 1977: the Modal Study (Fischer et al., 1987) and NUREG/CR-6672 (Sprung et al., 2000)¹. Both were advances in transportation risk assessment. The Modal Study was the first intensive examination of vehicle accident statistics, and the first to organize the frequency of severe accidents by structural and thermal response of the cask. Using documented accident frequencies of large trucks and railcars, the Modal Study organized the probability of accidents by the structural and thermal response of the casks in the accident. The Modal Study concluded that the frequency of accidents severe enough to produce significant cask damage was considerably less than NUREG-0170 had estimated. Although the Modal Study was not a risk

Deleted: real	
Deleted: The	
Deleted: nor does it attempt to ascribe a probability to them	
Deleted: licenses	
Deleted: the regulation of	M 141041.
Deleted: federal	

Comment [JRC17]: Confirm in	ntent of sentence.
Deleted: ,	
Deleted: in part	
Deleted: assessment	
Deleted: ,	

Deleted: radioactive materials

Deleted:

¹ "Modal Study" and "NUREG/CR-6672" are the names by which these documents are referred to in the general transportation literature. The actual titles are in the bibliography of this document.

analysis, since it did not consider the radiological consequence of accidents, risks less than those estimated in NUREG-0170 could be inferred.

NUREG/CR-6672 built on the Modal Study by refining the mechanical stress/thermal stress combinations and recasting them as a matrix of impact speed and temperature. In addition, NUREG/CR-6672 developed expressions for the behavior of spent fuel in accidents and potential release of this material and analyzed the potential releases. The enhanced modeling capability available for NUREG/CR-6672 allowed analysis of the detailed structural and thermal damage to transportation casks. NUREG/CR-6672 also used results of experiments by Lorenz (1980), Sandoval, et al (1988), and Sanders, et al (1992) to estimate releases of radioactive material from the fuel rods to the cask interior and from the cask interior to the environment following very severe accidents. The radionuclides available for release in the accidents studied in NUREG/CR-6672 are from relatively low burnup (30 GWD/MTU) and relatively high burnup (60 GWD/MTU) PWR and BWR fuel, although the transportability of the high burnup fuel was not considered. [The particular characteristics of high-burnup fuel shown by Einziger (2007) and Einziger and Beyer (2007) were investigated after the publication of NUREG/CR-6672 and therefore were not included in the NUREG/CR-6672 analysis.] NUREG/CR-6672 studied the behavior of two generic truck casks and two generic rail casks which were each composites of several certified casks.

The results of the NUREG/CR-6672 risk assessment were several orders of magnitude less than the estimates of NUREG-0170, and concluded that no radioactive material would be released in more than 99.99 percent of accidents involving spent fuel shipments. These low risk estimates resulted from the use of refined and improved analytical and modeling techniques, exemplified by the finite element analyses of cask structure, and limited experimental data,

The present study analyzed the behavior of three currently certified casks carrying Westinghouse 17x17 pressurized water reactor (PWR) fuel <u>assemblies</u> with 45,000 megawatt-days per metric ton of uranium (MWD/MTU) burnup, the highest burnup that any of the three casks are certified to carry. The resulting radiological risks are less than those reported in NUREG/CR-6672. For routine transportation, the risks are slightly less than those estimated in NUREG/CR-6672, because the actual external dose rates are less than the regulatory maximum used in the other studies, and because of code and modeling improvement. For accidents, the radiological risks calculated in the current study are at least an order of magnitude less. The <u>reduction in the estimates of risk from those in NURGE-0170 and NUREG/CR-6672</u> is the result of new data and observations, and improved modeling techniques.

1.2 Risk

Risk provides understanding of events that might happen in the future. Because risks are projections of potential future events, calculations of risk are estimates and <u>based on</u> approximations taken from historical, experimental, or analytical data.

Understanding transportation risk is integral to understanding the environmental and related human health impact of radioactive materials transportation. A large amount of data exists for deaths, injuries, and damage from traffic accidents, but there are no data on health effects caused by radioactive materials transportation because no such effects have ever occurred. Therefore,

Deleted: matrix
Deleted: it

Deleted: 6673	
Deleted: could	
Deleted: have been	

Deleted			 	
Deleteu:	 	 		

Comment	[JRC18]: What does limited	
experimental	data exemplify? Something missing	
hora?		

Deleted: estimates of	
veleteu, estimates of	

Deleted: It is always a projection. Once an even happens, it is no longer a risk.	vent
Deleted: based on	

both regulators and the public rely on risk estimates to gauge the impact of radioactive materials transportation. The risk estimates project potential accidents and events, when and where they will happen, and how severe they will be. Risk estimates include estimating the likelihood and the severity of transportation accidents, as well as the likelihood of exposure to ionizing radiation from routine transportation.

Risk is usually defined by <u>answering</u> the risk "triplet":

- What can happen (the scenario)?
- How likely is it (the probability)?
- What if it happens (the consequence)?

A risk number (quantitative risk) is calculated by multiplying the probability and consequence for a particular scenario. The probability of a scenario is always less than or equal to one, because the maximum probability of an event is one (100%); an event with 100% probability of occurrence is an event that is certain to happen. In reality, very few events are certain to happen or certain not to happen (zero probability). The probability of most events is between these two extremes. Transportation accidents involving large trucks, for example, have a very low probability (or we would hesitate to drive on the same freeway as a large truck). The probability of a traffic accident is about 1/100,000 per mile according to the Department of Transportation Bureau of Transportation Statistics (DOT, 2007), and the probability of a particular traffic accident scenario that includes vehicles carrying casks of radioactive material is much smaller still, as shown in the event trees in Appendix II of this document.

1.2.1 Accident Data

The only data available to estimate the future probability of a scenario is how often that scenario has occurred in the past. The frequency of the scenario can be considered the same as its probability. In the case of transportation accidents, there must be enough accidents in the data that the accidents per kilometer can predict future accidents per kilometer with reasonable accuracy. That is, the sample must be large enough to be sampled randomly. The most applicable frequency would be the frequency of accidents involving vehicles carrying spent nuclear fuel, but there have been too few of these for a statistically valid prediction.² Even accidents involving all hazardous materials transportation do not provide a large enough data base for statistical validity. The database used in this study is the frequency of highway accidents involving large semi-detached trailer trucks and the frequency of freight rail accidents (DOT, 2007). Freight rail accident frequency is based on accidents per railcar-mile.

Comment [JRC19]: Did any of the "76 class 7 (radioactive materials) rail and highway incidents and one Class 7 highway accident in the past ten years" involve spent fuel?

² The Bureau of Transportation Statistics lists accidents per year for all classes of hazardous materials. The 2009 database lists 76 class 7 (radioactive materials) rail and highway incidents and one Class 7 highway accident in the past ten years <u>http://www.phmsa.dot.gov/staticfiles/PHMSA/DownloadableFiles/Files/tenyr_ram.pdf</u>.

Deleted: : Deleted: ions of

1.2.2 Radioactive Materials Transportation Scenarios

Transportation risk is defined in several scenarios, the most probable of which is routine transportation of a cargo without incidents or accidents between the beginning and end of the trip. Routine transportation is an example of the risk triplet:

- What can happen? The scenario is routine incident-free transportation.
- How likely is it? The probability is 99.999% (see Chapter 5).
- What if it happens? The consequence is a radiation dose about one percent of background to
 individuals near the cask or along the route.

The doses and risks from routine transportation are analyzed in Chapter 2.

The accident scenarios discussed in this study are:

- Accidents in which there is no release of radioactive material. These include minor traffic
 accidents (fender-benders) and more severe accidents in which the vehicle is badly damaged
 but there is no release of radioactive material.
- · Accidents in which there is loss of gamma shielding but no release of radioactive materials
- Accidents in which there is a release of radioactive material.

It is not the purpose of this study to analyze traffic accidents that do not involve radioactive material, Traffic accident statistics (accident frequencies) are used in the accident analysis to calculate risks from accidents. Traffic accident frequencies for large semi-detached trailer trucks are about five per 10,0000 highway kilometers and for freight rail, about four per thousand railcar kilometers. The net accident probability is the product of the traffic accident probability and the conditional probability. The conditional probability that, if an accident happens, it is an accident of a certain type or severity and results in a particular release. The conditional probability that there is no release is more than 99%.

The consequence of an accident scenario is a dose of ionizing radiation. The risk is the product of the net accident probability and the consequence, and is called "dose risk." Accident risks are discussed in Chapters 3, 4, and 5.

1.3 Regulation of Radioactive Materials Transportation

Transportation of radioactive materials on public rights of way is regulated by the NRC under 10 CFR Part 71 and by the DOT, as part of hazardous materials transport regulations, under 49 CFR Parts 173 to 178. The regulations of 10 CFR Part 20 are also relevant. In general, the DOT regulations apply to industrial packaging and Type A packaging, and the NRC regulations apply to Type A(F) fissile materials packaging and Type B packaging. Industrial and Type A non-fissile packages are designed for routine transportation and are not certified to maintain their integrity in accidents, though many do. Type B packages are used to transport very radioactive materials. They are designed to maintain their integrity in severe accidents, because the NRC recognizes that any transport package and vehicle may be in traffic accidents. This study addresses the transportation of spent nuclear fuel, and thus concerns itself only with Type B packaging.

Comment [JRC20]: Why this broad term - we've only studied spent fuel here.

Comment [JRC21]: On the previous page risk is defined by the triplet, of which scenarios are only one part.

Comment [JRC22]: Why this different broad term – see comment above.

Comment [JRC23]: What number did you nean?	
Comment [JRC24]: So there is one traffic accident every 250 rail-car kilometers?! Didn't know trains were so dangerous.	
Comment [JRC25]: Unclear.	
Comment [JRC26]: This does not appear to be sentence.	be a
Comment [JRC27]: What is this paragraph rying to convey?	
Comment [JRC28]: The previous sentence mplies that the consequence of 99% of all accide s no release, so how is it that the consequence of accident scenario is a dose?	nts `an
Comment [JRC29]: The introduction to that mportant topic here is choppy at best.	
Comment [JRC30]: Given our Understanding Basics website, I'm surprised by the relatively po- quality of this section.	g or

Comment [JRC31]: Don't you mean packages? Don't DOT regulations apply to much more than packages?

Deleted: guaranteed

Deleted:

Nuclear fuel that has undergone fission (<u>"burned</u>") in a reactor is both extremely hot and extremely radioactive when it is removed from the reactor. In order to cool thermally and to allow the very radioactive and very short-lived fission products in the fuel to decay away, the fuel is discharged from the reactor into a large pool of water. The fuel remains in this pool for at least three to five years, until it can be remotely handled safely. The fuel usually remains in the pool as long as there is space for it. After the fuel has cooled sufficiently it can be removed from the pool to dry surface storage at the reactor, or can be transported to a storage site or other destination. Fuel is almost never transported before it has cooled for five years. The transportation casks used are rated for heat load, and this rating determines the cooling time needed for the fuel to be transported.

10 CFR Part 20

This section of the Code of Federal Regulations prescribes the largest radiation dose that a member of the public should receive from NRC-licensed facilities, exclusive of background radiation, diagnostic or therapeutic radiation, or material that has been discharged to the environment in accordance with NRC regulation. These doses are:

- 1 mSv per year (100 mrem per year) total effective dose equivalent (TEDE), including both external and committed internal dose.
- 0.02 mSv per hour (2 mrem per hour) in any unrestricted area from external sources. As for example, Table 2-12 shows, the doses from routine, incident-free transportation are considerably below these limits.
- 5 mSv per year (500 mrem per year) from a licensed facility if the licensee can show the need and expected duration of doses larger than 1 mSv per year.

Although the regulations state clearly that these dose limits do not include background, background is a useful measure of radiation exposure, since it affects everyone. This <u>Part</u> also regulates occupational doses to:

- 0.05 Sv per year (5 rem per year) TEDE
- 0.15 Sv/year (15 rem/year) to the lens of the eye
- 0.5 Sv/year (50 rem/year) to the skin.

10 CFR Part 71

The NRC recognizes that vehicles carrying radioactive materials are as likely to be in accidents as any vehicles of similar size traveling on similar routes. Transportation containers for very radioactive materials like spent nuclear fuel are therefore designed to maintain their integrity in severe accidents, Containers that can meet this requirement are Type B containers, and include the casks considered in this analysis, the NAC-STC and Rail-Steel cask rail casks and the GA-4 overweight truck cask.

Type B containers are designed to pass the series of tests described in 10 CFR 71.73 and shown in Figure 1-1.

Comment [JRC32]: Part 20 is at best tangential to the regulation of radioactive materials transportation, yet precedes Part 71 in this section?

Deleted: " humed

Comment [JRC33]: Implies that this useful measure is going to be provided, but it is not. Deleted: section

Comment [JRC34]: Untrue. Part 71 permits A2/wk release after HAC. Designed to contain radioactive materials. Deleted: so that no radioactive material is released

Deleted: the diagram of

- A 30-foot drop onto an unyielding surface. "Unyielding" means that the cask absorbs all the impact energy when it drops, and the surface does not absorb any impact energy. This drop is followed by
- A 40-inch drop onto a 6-inch-diameter steel cylinder, to test resistance to punctures. This test is followed by
- A 1475 °F fire that fully engulfs the cask for 30 minutes .
- Immersion for eight hours under three feet of water.



Figure 1-1. The four tests for Type B casks

Every cask used is not tested. The cask must withstand the tests without a leak or breach, but it would come through the test series dented, discolored and sooty from the fire, and mechanically weakened. Full-size and smaller scale prototype casks and critical features of the cask, like pressure welds, are tested. New cask design and structure <u>may be</u> compared to the design and structure of similar certified casks, and applicants for certification are required to show the results of tests with prototypes. New cask designs are modeled using models that have been benchmarked by physical tests; modeling is described in Chapters 3 and 4. Physical testing of prototypes and components, comparison with existing certified casks, and modeling by benchmarked thermal and structural models are all used to determine that a cask meets the test requirements

NRC regulations specify that total release of material from the cask over a period of one week following the tests can be no more than that allowed to be shipped in a non-accident resistant Type A package, allow slow release of certain amounts of each radionuclide and certain radioactive emissions from Type B casks in the event of an accident. Releases of a number of

Comment [JRC35]: Placeholder: Basically, to qualify as unyielding, an object would have to be as hard as the cask and weigh ten times as much. Since the casks are made of steel many inches thick and weigh many tons, there are few objects on the roadways and railways that are considered unyielding relative to the cask.

Better approach is that design is demonstrated by physical test, analysis, or comparison to satisfy the test conditions, and all casks used are manufactured to a certified design. Comment [JRC37]: Again, untrue. Comment [JRC38]: How do you define breach? Comment [JRC39]: News to me. We do not test to failure. Deleted: The tests are designed to destroy the cask. Comment [JRC40]: Not necessarily. Deleted: are also Comment [JRC41]: The rest of this paragraph appears erroneous, redundant, or both. Comment [JRC42]: My alternative: insert The test acceptance criteria are as stringent as the test conditions are severe.

Comment [JRC36]: And no tested cask is used.

Actually, every cask used is (leak) tested

radionuclides are allowed by 10 CFR 71.51. The regulation also permits a maximum post-test external radiation dose <u>rate</u> of 0.01 Sv per hour (one rem per hour).

1.4 Selection of Casks

Past generic risk assessments for the transportation of spent fuel have used generic casks with features similar to real casks, but generally without all of the conservatisms that are part of real cask designs. In this effort, we performed the generic risk assessment using actual cask designs with all of the features that contribute to their robustness. Because it is too costly and time consuming to examine all casks, a sub-set of casks to be used was chosen. Appendix I lists the various spent fuel casks that were certified by the NRC at the time the study began, gives options for the method of choosing the casks to be used, gives some of the important features of the various cask designs, and finally concludes with the chosen casks.

Table 1-1 lists the casks that were certified by the NRC as of 2006 (the date when the cask selections for this study were made) for the transportation of irradiated commercial light water power reactor fuel assemblies. Those above the heavy line are older designs that are no longer used, but still had valid certificates. Those below the heavy line are more modern and additional casks of these designs could be built. The casks for use in this study came from this last group. A brief description of each of these casks is included in Appendix I.

Cask	Package ID	Canister	Contents (Number of assemblies)	Туре
IF-300	USA/9001/B()F	No	7 PWR, 17 BWR	Rail
NLI-1/2	USA/9010/B()F	No	1 PWR, 2 BWR	Truck
TN-8	USA/9015/B()F	No	3 PWR	Overweight ^a
TN-9	USA/9016/B()F	No	7 BWR	Overweight ^a
NLI-10/24	USA/9023/B()F	No	10 PWR, 24 BWR	Rail
NAC-LWT	USA/9225/B(U)F-96	No	1 PWR, 2 BWR	Truck
GA-4	USA/9226/B(U)F-85	No	4 PWR	Truck
NAC-STC	USA/9235/B(U)F-85	Both	26 PWR	Rail
NUHOMS®-MP187	USA/9255/B(U)F-85	Yes	24 PWR	Rail
HI-STAR 100	USA/9261/B(U)F-85	Yes	24 PWR, 68 BWR	Rail
NAC-UMS	USA/9270/B(U)F-85	Yes	24 PWR, 56 BWR	Rail
TS125	USA/9276/B(U)F-85	Yes	21 PWR, 64 BWR	Rail
TN-68	USA/9293/B(U)F-85	No	68 BWR	Rail
NUHOMS®-MP197	USA/9302/B(U)F-85	Yes	61 BWR	Rail

Table 1-1. NRC Certified Commercial Light Water Power Reactor Spent Fuel Casks

^aOverweight truck

The casks chosen for detailed analysis are the NAC-STC (Figure 1-2) and the HI-STAR 100 (Figure 1-3) rail casks. The GA-4 truck cask (Figure 1-4) will be used to evaluate truck shipments, but detailed finite element analyses of this cask will not be performed. The complete Certificates of Compliance (as of April 12, 2010) for each of these casks is included in Appendix I. The NAC-STC cask was chosen because it is certified for transport of spent fuel either with or without an internal welded canister and, for transport or spent fuel without an

Comment [JRC43]: insert above	Would delete in favor of
Deleted: allows	
Deleted: n	

Comment [JRC44]: I agree with use of past tense...revise following paragraphs use of present tense for consistency.

Comment [JRC45]: Because.

internal canister, its certificate of compliance allows use of either elastomeric o-rings or metallic o-rings. Even though there are five casks in the group that use lead as their gamma shielding, of this group only the NAC-STC can transport fuel that is not contained within an inner welded canister. The HI-STAR 100 rail cask is chosen because it is the only all-steel cask in the group that is certified for transport of fuel in an inner welded canister. The GA-4 truck cask is chosen because it has a larger capacity than the NAC-LWT, and therefore is more likely to be used in any large transportation campaign.

The choice of rail casks allows comparison between directly loaded and canistered fuel, comparison between a steel-lead-steel cask and an all-steel cask, and comparison between elastomeric o-ring seals and metallic o-ring seals.





Figure 1-2. NAC-STC cask (courtesy of NAC International)



Figure 1-3. Basic layout of the HI-STAR 100 rail transport cask (from Haire and Swaney, 2005, and Holtec International, 2004)



Figure 1-4. GA-4 cask (courtesy of General Atomics)

The NAC-STC rail cask is chosen because of the flexibility of its certificate of compliance. This cask can be used for both directly loaded fuel and for canistered fuel and is certified with either elastomeric o-rings or metallic ones. The HI-STAR 100 <u>rail</u> cask is chosen because it is the more modern of the two all-steel walled casks. The GA-4 <u>truck</u> cask is chosen because it has a higher capacity and has depleted uranium shielding. The chosen casks include all three of the most common shielding options; lead, depleted uranium, and steel

1.5 Organization of this Report

Each chapter in this study has an associated appendix that describes the analytical methods and calculations used to arrive at the results discussed in the chapters. Descriptions of programs, calculations and codes used are in the relevant appendices.

1.5.1 Chapter 1 and Appendix I

This chapter provides an introduction to the study, a brief background discussion, a discussion of risk as applied to transportation of radioactive materials, a discussion of cask selection, and a review of the organization of the report. Appendix I contains a glossary of special terms used in this study.

1.5.2 Chapter 2 and Appendix II

Chapter 2 and Appendix II discuss RADTRAN analysis of incident-free transportation. During routine ("incident-free") transportation, spent fuel transportation packages deliver an external dose, which is virtually entirely a gamma dose. In most studies to date the regulatory maximum dose rate, 10 mrem/hour at 2 meters from the cask, was assumed to be the external dose rate from every intact cask evaluated in the particular study. The present study uses the external dose rate from commercial certified casks as reported in the Safety Analysis Reports of those casks.

Comment [JRC46]: Seems to come out of the

Comment [JRC47]: True, but needed here?

1.5.3 Chapter 3 and Appendix III

Chapter 3 and Appendix III address the structural analyses used to determine the cask response to accidents and the parameters that determine loss of lead gamma shielding and releases of radioactive material. The results of detailed analyses of impacts onto rigid targets at speeds of 48, 97, 145, and 193 kph (30, 60, 90, and 120 mph) in end, corner, and side-on orientations are given. Also provided are results for impacts onto other surfaces or other objects. The response of the fuel assemblies carried by the casks is also discussed.

1.5.4 Chapter 4 and Appendix IV

Chapter 4 and Appendix IV address the thermal analyses used to determine the cask response to these accidents and the parameters that determine loss of lead gamma shielding and releases of radioactive material. The results from analyses of fires that completely engulf the cask as well as ones that are off-set from the cask are given. The temperature response of the cask seals, the shielding material, and the spent fuel is provided.

1.5.5 Chapter 5 and Appendix V

Chapter 5 and Appendix V address RADTRAN analysis of transportation accidents, development of accident event trees and conditional probabilities, development of the radionuclide inventory and radioactive materials releases and dispersion of released material in the environment. The chapter also discusses accidents in which there are no releases – the most likely accidents – in which the radioactive cargo is not affected at all, and an essentially undamaged <u>cask and conveyance</u> sits for many hours at the accident location.

1.5.6 Chapter 6 and Appendix VI

Chapter 6 summarizes the results of the analyses. Appendix VI includes a comparison between NUREG-0170 (NRC, 1977), the Modal Study (Fischer et al., 1987), NUREG/CR-6672 (Sprung et al., 2000) and this study.

1.5.7 Bibliography

The bibliography is placed after the appendices. It contains all cited references and other bibliographic material. Citations in the text (e.g., Sprung et al., 2000, Figure 7.1) include specific page, figure, or table references where appropriate.

Deleted: these

Comment [JRC48]: Conveyance, especially truck, could be heavily damaged with no damage to cask
, . .

12

6

· · ·

. . .

CHAPTER 2

RISK ANALYSIS OF ROUTINE TRANSPORTATION

2.1 Introduction

NUREG-0170 (NRC, 1977) was the first comprehensive assessment of the environmental and health impact of transporting radioactive materials, and documented estimates of the radiological consequences and risks associated with the shipment by truck, train, plane, or barge of about 25 different radioactive materials, including power reactor spent fuel. However, not much actual data on spent nuclear fuel transportation was available in 1977 and computational modeling of such transportation was, relatively speaking, in its infancy.

The RADTRAN computer code (Taylor and Daniel, 1977) is the computational tool used in this chapter to estimate risks from routine³ transportation of spent nuclear fuel. RADTRAN was initially developed by NRC for the NUREG-0170 risk assessment. During the past several decades, the calculation method and RADTRAN code have been improved to stay current with computer technology, and supporting input data have been collected and organized. The basic RADTRAN analysis approach has not changed since the original development of the code, and the risk assessment method employed in the RADTRAN code is accepted worldwide; about 25 percent of the five hundred RADTRAN users are international.⁴

RADTRAN 6.0, integrated with the input file generator RADCAT, (Neuhauser et al., 2000;³ Weiner et al., 2009) is the version used in this study. The incident-free module of RADTRAN, the model used for the analysis in this chapter, was validated by measurement (Steinman et al., 2002), and verification and validation of RADTRAN 6.0 are documented in Dennis, et al.

This chapter discusses the risks to the public and workers when the transportation of the casks containing spent fuel takes place without incident (casks are undamaged). Non-radiological vehicular accident risk, which is orders of magnitude larger than the radiological transportation risk, is not discussed in this study. The risks and consequences of accidents and incidents interfering with routine transportation are discussed in Chapter 5.

This chapter includes the following:

- A brief discussion of ionizing radiation emitted during transportation.
- A description of the RADTRAN model of routine transportation.
- Radiation doses from a single routine shipment to:

Members of the public who live along the transportation route and near stops

³ The term "routine transportation" is used throughout this document to mean incident or accident-free transportation,
 ⁴The currently registered RADTRAN users are listed on a restricted access web site at Sandia National Laboratories.
 ⁵ Neuhauser, et al (2000) is the technical manual for RADTRAN 5, and is cited because the basic equations for the incident-free analyses in RADTRAN 6 are the same as those in RADTRAN 5. The technical manual for RADTRAN 6 is not yet available.

Deleted: "
Deleted: "
Deleted: , in order to avoid burdening the reader
with RADTRAN terms of art.

Comment [JRC49]: Ongoing?

Deleted: As described in Chapter 1, an ongoing study of the environmental impact of transporting radioactive materials is needed.

Deleted: the

Comment [JRC50]: Better phrasing than footnote 3?

Deleted: and the transportation of the fuel takes place without incident

Comment [JRC51]: But perhaps this should be used as one basis of comparison?

Occupants of vehicles that share the route with the radioactive shipment

Various groups of people at stops

Workers

Detailed results of the RADTRAN calculations for this analysis are provided in Appendix II. All references are listed in the bibliography. A discussion of RADTRAN use and applications are provided in Weiner, et al (2009).

2.2 Radiation Emitted during Routine Transportation

The RADTRAN model for calculating radiation doses is based on the well-understood behavior of ionizing radiation. Like all radiation, ionizing radiation moves in straight lines. It can be absorbed by various materials, including air. Absorption of ionizing radiation depends on the energy and type of radiation and on the absorbing material.

Spent nuclear fuel, the subject of this analysis, is extremely radioactive, emitting ionizing radiation in the form of alpha, beta, gamma, and neutron radiation. The casks that are used to transport spent nuclear fuel have exceedingly thick walls that absorb most of the emitted ionizing radiation and thereby shield the public and the workers. Figure 2-1 shows two generic cask diagrams on which the shielding is identified.



Figure 2-1. The upper figure is an exploded view of a generic spent fuel cask. The lower figure is a cross-section of the layers of the cask wall. (Sandia National Laboratories archive)

Alpha and beta radiation cannot penetrate the walls of the casks (both are actually absorbed well by a few millimeters of paper and plastic). The steel and lead layers of the cask wall absorb most of the gamma and neutron radiation emitted by spent fuel, although adequate neutron shielding also requires a layer of a neutron absorber like a polymer or boron compound. In certifying spent fuel casks, the NRC allows emission of gamma and neutron radiation at a very low dose rate. For spent uranium-based fuel, the allowed dose rate is almost entirely due to gamma radiation.

Absorbed radiation dose is measured in sieverts (Sv) in the Standard International system, rem or millirem in the historic English unit system (millirem—mrem—in this document). Average U. S. background radiation from naturally occurring and some medical sources is 0.0036 Sv (360 mrem) per year (Shleien et al., 1998, Figure 1.1),⁶ A single dental x-ray delivers a dose of 4 x 10⁻⁵ Sv (4 mrem), and a single mammogram delivers 1.3×10^{-4} Sv (13 mrem) (Stabin, 2009). The average radiation dose rate from a spent fuel cask allowed by regulation is 10^{-4} Sv per hour (10 mrem/hour), measured at two meters (about six feet) from the outside of the cask (10 CFR 71.4)), or about 0.00014 Sv/hour (14 mrem per hour) at one meter from a cask four to five meters long.

The measured external radiation doses from the casks in this study (Figures 1-3 to 1-5) are shown in Table 2-1. Measured values for the Truck-DU cask were not available, but it was assumed to meet the NRC standard of 10 CFR Part 71 (Holtec, 2004; NAC, 2004, General Atomics, 1998).

Table 2-1. External radiation doses from the casks in this study

	Truck-DU	Rail-Pb	Rail-All Steel
Transportation mode	Highway	Rail	Rail
Dose rate Sv/hr (mrem/hr) at 1 m	0.00014 (14)	0.00014(14)	0.000103 (10.3)
Gamma fraction	0.77	0.89	0.90
Neutron fraction	0.23	0.11	0.10

The radiation dose to workers and members of the public from a routine shipment is based only on the external dose from the spent fuel cask. Doses from the external radiation from the <u>cask</u> therefore depend on the distance of the receptor from the <u>cask</u> and on the exposure time, as well as on the external dose rate.

Comment [JRC52]: This is the Definitions section. It does not specify dose rate limits.

Comment [JRC53]: Confirm these are measured and not calculated.

The contents determine the ally describing what the arity.
e radioactive content of the
A.

⁶ Recent increased diagnostic use of ionizing radiation, as in computerized tomography, has suggested increasing the average background to 0.006Sv (600 mrem).

2.3. The RADTRAN Model of Routine, Incident-Free Transportation

2.3.1 The Basic RADTRAN Model

For analysis of routine transportation, RADTRAN models the vehicle as a sphere with a radiation source at its center. The emission rate of the radiation source is the dose rate in Sv/hour (mrem/hour) at one meter from the cask, which NRC identifies as the transport index (TI). The TI is modeled as a virtual source at the center of the sphere, as shown in Figure 2-2. The diameter of this spherical model, called the "critical dimension," is the longest dimension of the actual spent fuel cask.



Figure 2-2. RADTRAN model of the vehicle in routine, incident-free transportation. The cask in this diagram is positioned horizontally, and the critical dimension is the cask length.

When the distance to the receptor (*r* in Figure 2-2) is much larger than the critical dimension, RADTRAN models the dose to the receptor as proportional to $1/r^2$. When the distance to the receptor *r* is similar to or less than the critical dimension, as for crew or first responders, RADTRAN models the dose to the receptor as proportional to 1/r. The dose calculated by the RADTRAN spherical model overestimates the measured dose by a few percent (Steinman et al., 2002).

2.3.2 Individual and Collective Doses

The dose to workers and the public from a cask during routine transportation depends on the time that the workers or public are exposed to the cask and the distance from the cask, as well as the cask's external radiation. When the vehicle carrying the cask is traveling along the route, the faster the vehicle goes, the less anyone along the vehicle's route is exposed. Therefore, an individual member of the public gets the largest dose from a moving vehicle when he or she is as close as possible to the vehicle, and the vehicle is traveling as slowly as possible. For trucks and

Comment [JRC55]: The Figure shows cask modeled as a sphere, not the vehicle (rail car).

Comment [JRC56]: The figure shows the TI modeled from the cask surface, not the center of the sphere.

trains carrying spent fuel, a speed of 24 km per hour (15 mph) and distance of 30 meters (about 100 feet) are assumed for maximum exposure.⁷ Table 2-1, shows the dose to an individual member of the public under these conditions. These doses are about the same as one minute of average background: 6.9×10^{-9} Sv (6.9×10^{-4} mrem).

Deleted: Table 2-2

⁷ Thirty meters is typically as close as a person on the side of the road can get to a vehicle traveling on an interstate highway.

Table	2-1.	Maximum	individual	in-transit	doses
		IT A GO / A A A A A A A A A A A A A A A A A A	AAA CAA T ACA CA CA CA	ARE LA CERESTE	u o o o

Package	Dose
Rail-Pb (rail)	5.7E-09 Sv (5.7E-04 mrem)
Rail-All Steel (rail)	4.3E-09 Sv (4.3E-04 mrem)
Truck - DU (truck)	6.7E-09 Sv (6.7E-04 mrem)

When a vehicle carrying a spent fuel cask travels along a route, the people who live along that route and the people in vehicles that share the route are exposed to the external radiation from the cask. Doses to groups of people are collective doses; the units of collective dose are person-Sv (person-mrem). A collective dose, sometimes called a population dose, is essentially an average individual dose multiplied by the number of people exposed.⁸ As shown in Figure 2-3, RADTRAN calculates collective doses along transportation routes by integrating over the width of a band along the route where the population resides (the *r* in Figure 2-2) and then integrating along the route, Collective doses to people on both sides of the route are included. The exposed population is in a band 770 meters (about a half mile) on either side of the route: from 30 meters (10 feet) from the center of the route to 800 meters.

Deleted: (the *r* in Figure 2-2)





Occupants of vehicles that share the route with the radioactive shipment also receive a radiation dose from the spent fuel cask. The collective dose to occupants depends on the average number

⁸ A detailed discussion of collective dose is in Appendix II.

of occupants per vehicle and the number of vehicles per hour that pass the radioactive shipment in both directions.

Any route can be divided into as many sections as desired for dose calculation; e.g., the dose to residents of a single house or city block. However, as a practical matter, routes are divided into rural, suburban, and urban segments according to the population per square mile (population density). <u>Table 2-2</u>, summarizes the characteristics of each population type that are part of the dose calculation by RADTRAN. References for these parameter values are in the Table 2-3 footnotes.

Deleted: Table 2-3

	Highway			Rail			
	Rural	Suburban	Urban	Rural	Suburban	Urban	
Population density per km ² (per mi ²) ^a	0 to 54 (0 to 139)	54 to 1286 (139 to 3326)	>1286 (>3326)	0 to 54 (0 to 139)	54 to 1286 (139 to 3326)	>1286 (>3326)	
Nonresident/ resident ratio ^b	NA	NA	6	NA	NA	6	
Shielding by buildings ^b	0	13%	98.2%	0	13%	98.2%	
U.S. average vehicle speed ^c kph (mph) ^{c,d}	108 (67)	108 (67)	101(63)	40 (27)	40 (27)	24 (15)	
U.S . average vehicles per hour. ^{e,f}	1119	2464	5384	17	17	17	
Occupants of other vehicles ^e , ^g	1.5	1.5	1.5	1	1	5	

Table 2-2. Characteristics of rural, suburban, and urban routes used in RADTRAN

^aJohnson and Michelhaugh, 2003, .^bWeiner, et al. 2009, ^cDOT, 2004a, .^dDOT, 2004b,

^e Weiner, et al. 2009, Appendix D, ^fDOT, 2009; these are average railcars per hour, ^gDOT, 2008, Table 1-11.

Each route clearly has a distribution of rural, urban and suburban areas, as shown by the example of the truck route in Figure 2-4.



Figure 2-4. A segment of U.S.1 along the Florida coast (courtesy of G. Scott Mills)

Figure 2-4 shows a segment of U.S.1 along the Florida coast from West Palm Beach to Fort Pierce. The broad stripe along the coastline is the half-mile band on either side of the coastal highway. The red areas are urban populations, the blue areas are suburban, and the gray areas are rural. Instead of analyzing each separate, rural, urban, and suburban segment of this stretch of highway, the rural, suburban, and urban areas are each combined for RADTRAN dose

calculations. The routing code WebTRAGIS (Johnson and Michelhaugh, 2003) provides these combinations for each state traversed by a particular route. <u>Table 2-3</u> shows this WebTRAGIS output for a <u>sample</u> rail route from Kewaunee Nuclear Plant, WI to Oak Ridge National Laboratory.

State	Kilometers (miles)			Persons/km ² (persons/mi ²)				
和学校	Rural	Suburban	Urban	Rural	Suburban	Urban		
Illinois	12 (7.5)	63 (39)	45 (28)	26 (67)	504 (1305)	2593 (6710)		
Indiana	171 (106)	51 (32)	11 (6.6)	17 (44)	351 (909)	2310 (5977)		
Kentucky	254 (158)	84 (52)	13 (7.8)	17(45)	312 (806)	2532 (6551)		
Ohio	201 (125)	117 (73)	29 (18)	15 (38)	402 (1041)	2243 (5802)		
Tennessee	56 (35)	23 (14)	1 (0.6)	17 (44)	330 (855)	2084 (5392)		
Wisconsin	148 (92)	92 (57)	28 (17)	18 (46)	434 (1124)	2410 (6234)		

Comment [JRC57]: Unlcear. Too "zoomed out". Rural route appears to be in waterway? Does not show 2 bands on either side of highway?

Deleted: Table 2-4

Comment [JRC58]: Include a map of this route.

The route segment lengths and population densities are entered into RADTRAN, which then calculates the collective doses to residents along these route segments. Collective doses are reported as person-Sv.

Collective doses were calculated for one shipment over each of sixteen routes. These routes represent a variety of route lengths and populations, and are typical of routes that these trucks travel. Collective doses depend on route length and on the populations along the route.

The sites where the shipments originated include two nuclear generating plants (Indian Point and Kewaunee), a storage site at a fully decommissioned nuclear plant (Maine Yankee), and a National Laboratory (Idaho National Laboratory). The destination sites include two proposed repository sites (Deaf Smith County, TX and Hanford, WA) (DOE, 1986), the site of the proposed Private Fuel Storage facility (Skull Valley, UT), and a National Laboratory site (Oak Ridge, TN; ORNL). The routes modeled are shown in <u>Table 2-4</u>, Both truck and rail versions of each route are analyzed.

Route segments and population densities are provided by WebTRAGIS. Population densities were updated from the 2000 census using the 2008 Statistical Abstract (U.S. Bureau of the Census 2008, Tables 13 and 21), though updates were made only when the difference between the 2008 and 2000 population densities was one percent or more. The collective doses reported in Table 2-5 and Table 2-6 are in units of person-Sv.

Table 2-4. Specific routes modeled. Urban kilometers are included in total kilometers.

Origin	Destination	Population 800 m (1	Kilo	meters	Urban Kilometers		
		Rail	Truck	Rail	Truck	Rail	Truck
Maine	Hanford, WA	1,146,479	980,355	5051	5011	235	116
Yankee	Deaf Smith County, TX	1,321,023	1,248,079	3360	3593	210	164
Site, ME	Skull Valley, UT	1,199,091	934,336	4248	4173	235	115
	Oak Ridge, TN	1,119,154	1,336,208	2124	1747	161	135
Kewaunee	Hanford, WA	779,613	419,951	3026	3451	60	57
NP, WI	Deaf Smith County, TX	677,072	418,424	1881	2145	110	60
	Skull Valley, UT	472,098	354,911	2753	2619	125	51
ii M	Oak Ridge, TN	806,116	522,128	1394	1272	126	92
Indian	Hanford, WA	1,146,246	751,189	4779	4512	228	97
Point NP,	Deaf Smith County, TX	1,027,974	376,259	3071	3071	204	207
NY	Skull Valley, UT	956,210	705,170	3975	3671	229	97
	Oak Ridge, TN	1,517,759	464,070	1263	1254	207	60
Idaho National	Hanford, WA	593,681	107,325	1062	958	20	15
	Deaf Smith County, TX	298,589	310,351	1912	2290	40	52
Lab, ID	Skull Valley, UT	164,399	102,341	454	466	26	19
	Oak Ridge, TN	169,707	494,068	3304	3286	74	62

Comment [JRC59]: We need a clear map of these routes. Are there 16 origin/destination pairs and 32 routes (one road and rail route for each pair)?

Comment [JRC60]: Need to expand explanation for selection of 16 routes, e.g., do not represent any particular spent fuel shipments plans, but are believed to be representative of (surrogates for?) the lengths and population densities of spent fuel road and rail routes.

Deleted: Table 2-5 Comment [JRC61]: See comment on pairs/routes above.

Deleted: Table 2-6	
Deleted: Table 2-7	

Table	<u>2-5</u> and	Table 2-6 present	collective doses	for trail a	and truck,	respectively,	for the sixteen
routes.	State b	y state collective	doses are tabulate	ed in App	endix II.		

4	Deleted: Table 2-6
1	Deleted: Table 2-7
4	Comment [JRC62]: These tables need route totals.

FROM	ТО	Rail-Pb			Rail-All Stee	l.	
		Rural	Suburban	Urban	Rural	Suburban	Urban
MAINE	ORNL	2.5E-05	3.0 E-04	1.4 E-04	1.9 E-05	2.2 E-04	1.1 E-05
YANKEE	DEAF SMITH	3.3 E-05	3.9 E-04	1.9 E-04	2.3 E-05	2.8 E-04	1.4 E-05
	HANFORD	3.8 E-05	4.1 E-04	2.1 E-04	2.9 E-05	3.0 E-04	1.5 E-05
	SKULL VALLEY	4.2 E-05	4.2 E-04	1.1 E-04	3.2 E-05	2.9 E-04	1.1 E-05
KEWAUNEE	ORNL	1.7 E-05	1.7 E-04	1.1 E-04	1.0 E-05	1.1 E-04	8.1E-06
	DEAF SMITH	1.3 E-05	1.5 E-04	9.2E-05	8.0E-06	9.6 E-05	7.0E-06
	HANFORD	1.6 E-05	1.5 E-04	4.7E-05	1.2 E-05	2.7 E-05	4.0 E-06
	SKULL VALLEY	2.3 E-05	1.9 E-04	1.1 E-04	1.5 E-05	9.3 E-05	8.0E-06
INDIAN	ORNL	1.2 E-05	2.3 E-04	2.3 E-04	9.0E-06	1.7 E-04	1.7 E-05
POINT	DEAF SMITH	2.7 E-05	2.8 E-04	1.9 E-04	2.0 E-05	2.0 E-04	1.4 E-05
	HANFORD	3.2 E-05	3.4 E-04	2.1 E-04	2.4 E-05	1.3 E-04	1.4 E-05
	SKULL VALLEY	3.6 E-05	3.2 E-04	2.1 E-04	2.9 E-05	2.1 E-04	2.1 E-05
IDAHO	ORNL	2.8 E-05	1.8 E-04	6.0 E-05	2.2 E-05	1.4 E-04	4.5E-06
NATIONAL	DEAF SMITH	1.1 E-05	9.4 E-05	4.0 E-05	3.6 E-05	7.1 E-05	2.8 E-06
LAB	HANFORD	8.5 E-06	4.7 E-05	1.9 E-05	1.7 E-05	5.6 E-06	1.4 E-06
	SKULL VALLEY	4.9 E-06	4.1 E-05	2.5 E-05	2.3 E-05	2.4 E-05	1.8 E-06

Table 2-5. Collective doses (person-Sv) for rail transportation

		Truck - DU				
FROM	то	Rural	Suburban	Urban	Urban Rush Hour ^a	
MAINE	ORNL	7.9E-06	1.4E-04	2.9E-06	6.5E-08	
YANKEE	DEAF SMITH	1.4E-05	1.9E-04	3.3E-06	7.3E-08	
	HANFORD	2.2E-05	1.7E-04	2.3E-06	5.2E-08	
	SKULL VALLEY	1.8E-05	1.5E-04	2.3E-06	5.2E-08	
KEWAUNEE	ORNL	6.5E-06	7.4E-05	1.8E-06	4.0E-08	
	DEAF SMITH	1.1E-05	6.3E-05	1.2E-06	2.6E-08	
	HANFORD	1.4E-05	6.6E-05	1.1E-06	2.5E-08	
	SKULL VALLEY	1.2E-05	5.0E-05	1.1E-06	2.3E-08	
INDIAN	ORNL	6.1E-06	8.9E-05	1.2E-06	2.6E-08	
POINT	DEAF SMITH	1.1E-05	1.1E-04	1.6E-06	3.4E-08	
	HANFORD	2.1E-05	1.2E-04	1.9E-06	4.2E-08	
	SKULL VALLEY	1.7E-05	1.1E-04	1.9E-06	4.2E-08	
IDAHO	ORNL	1.4E-05	8.4E-05	1.2E-06	2.7E-08	
NATIONAL	DEAF SMITH	7.3E-06	4.9E-05	1.1E-06	2.5E-08	
LAB	HANFORD	4.2E-06	2.0E-05	3.0E-07	6.6E-09	
	SKULL VALLEY	2.0E-06	1.6E-05	4.3E-07	9.5E-09	

Table 2-6. Collective doses (person-Sv) for truck transportation (1 Sv = 10⁵ mrem)

^aDuring rush hour the truck speed is halved and the vehicle density is doubled.

Collective dose is best used in making comparisons; e.g., in comparing the risks of routine transportation along different routes, by different modes (truck or rail), or in different casks. Several such comparisons can be made from the results shown in Tables 2-6 and 2-7.

- Urban residents sustain a Jarger (but still small) dose from a single rail shipment than from a truck shipment on the same state route, even though urban population densities are similar and the external dose rates from the cask are nearly the same. As shown in <u>Table 2-4</u>, most (though not all) rail routes have more urban miles than the analogous truck route. Train tracks go from city center to city center, while trucks carrying spent fuel must use interstates and bypasses. In several cases shown in <u>Table 2-4</u>, the rail route had twice as many urban miles as the corresponding truck route.
- Overall, collective doses are larger for a single shipment on rail routes than truck routes because the rail routes are often longer, especially in the western U.S., where there is rarely a choice of railroads.,
- Any particular shipment campaign will need fewer rail shipments than truck shipments, because rail casks hold about six times as many fuel assemblies as truck shipments.

Comment [JRC63]: Then why are the rush hour doses 100 times *less* than the urban doses?

Deleted: slightly

Deleted: Table 2-5

Deleted: In several cases shown in Table 2-5, the rail route had twice as many urban miles as the corresponding truck route.

Comment [JRC64]: Don't disagree, but how is this deduced from Tables 2-6 and 2-7?

The collective doses shown in <u>Table 2-5</u> and <u>Table 2-6</u> are all very small. <u>However</u>, they are not the only doses the people along the route receive. Background radiation is 0.0036 Sv per year (360 mrem per year) in the U.S., or 4.1×10^{-7} Sv/ hour. The <u>contribution</u> of a single shipment to the <u>population's</u> collective dose is illustrated by the following example of the Maine Yankee to ORNL truck route:

- From Table 2-7 the total collective dose for this segment 1.5 x 10⁻⁵ person-Sv
- From Table 2-5, there are 1.34 million people within a half mile of the route.
- Background is 4.1 x 10⁻⁷ Sv/hour. Everyone is exposed to this background all the time, whether a shipment occurs or not.
- A truck traveling at an average of 108 kph travels the 1747 km in 16 hours.
- During those 16 hours, the 1.34 million people will have received a collective background dose of 8.81 person-Sv, about 600,000 times the collective dose from the shipment.
- The total collective dose during a shipment to this 1.34 million people is not 1.5 x 10⁻⁵ person-Sv), but 8.81015 person-Sv.
- The NRC recommends that collective dose be used only in comparisons (NRC, 2008).
- The appropriate comparison between the collective dose from this shipment of spent fuel is thus not a comparison between 1.5 x 10⁻⁵ person-Sv from the shipment and zero dose if there is no shipment, but between 8.81015 person-Sv if there is a shipment and 8.81000 person-Sv if there is no shipment.

A more complete discussion of collective dose is in Appendix II, Section II.6.

2.3.3 Doses to members of the public occupying vehicles that share the route

Rail

Much of the United States rail is either double track or equipped with "passing tracks" that let one train pass another. When a train passes the train carrying the spent fuel cask, occupants of the passing train will receive some of the external radiation. The great majority of trains in United States carry freight, and the only occupants of the passing train are crew members. Only about one railcar in 60 has an occupant.

The dose to occupants of other trains in this situation depends on train speed and the external dose rate from the spent fuel casks. <u>Table 2-7</u>, shows the collective dose to public passengers of trains sharing the route, assuming for calculation purposes that occupants of passenger trains are represented by one <u>person</u> in each passing railcar in rural and suburban areas, and five people in urban areas. The rural and about half of the suburban collective doses are probably unrealistically large, since most freight rail going through rural and many suburban areas never encounters a passenger train. Data were not available to account for the occupancy of actual passenger trains, including light rail, that share rail routes with freight trains.

Deleted: Table 2-6	
Deleted: Table 2-7	
Deleted: Moreover	
Deleted: effect	
Deleted: on	10 T

Comment [JRC65]: Very good.

Deleted:

Deleted: net

Deleted: Table 2-8	
Deleted: persons	
Comment [JRC66] passenger trains seem v	: These occupancy rates for very low?
Comment [JRC67]	: Why about half?

SHIPMENT	SHIPMENT	Rail-Pb			Rail-All Steel		
ORIGIN	DESTINATION	Rural	Suburban	Urban	Rural	Suburban	Urban
MAINE	ORNL	5.3E-06	1.6E-05	1.1E-04	4.0E-06	1.2E-05	7.6E-06
YANKEE	DEAF SMITH	1.0E-05	1.8E-05	1.4E-04	7.7E-06	1.4E-05	9.9E-06
	HANFORD	1.5E-05	2.2E-05	1.5E-04	1.2E-05	1.7E-05	1.1E-05
	SKULL VALLEY	1.3E-05	2.4E-05	1.2E-04	9.9E-06	1.9E-05	8.5E-06
KEWAUNEE	ORNL	3.7E-06	9.4E-06	8.5E-05	2.8E-06	7.1E-06	5.9E-06
· · · · · · · · · · · · · · · · · · ·	DEAF SMITH	6.4E-06	7.0E-06	7.4E-05	4.8E-06	5.3E-06	5.2E-06
	HANFORD	6.7E-06	9.0E-06	4.1E-05	5.0E-06	6.9E-06	2.8E-06
	SKULL VALLEY	9.4E-06	1.0E-05	8.5E-05	7.2E-06	7.9E-06	5.9E-06
INDIAN	ORNL	2.5E-06	1.1E-05	1.4E-04	1.9E-06	8.2E-06	9.7E-06
POINT	DEAF SMITH	9.8E-06	1.4E-05	1.4E-04	7.4E-06	1.1E-05	9.6E-06
	HANFORD	1.2E-05	1.9E-05	1.5E-04	8.8E-06	1.5E-05	1.1E-05
	SKULL VALLEY	5.9E-06	4.2E-05	7.1E-05	4.4E-06	3.2E-05	2.7E-05
IDAHO	ORNL	4.0E-06	5.3E-05	5.5E-05	3.0E-06	4.0E-05	3.8E-06
NATIONAL	DEAF SMITH	7.3E-06	4.4E-06	2.7E-05	5.6E-06	3.3E-06	1.9E-06
LAB	HANFORD	4.1E-06	2.3E-06	1.4E-05	3.1E-06	1.8E-06	9.4E-07
	SKULL VALLEY	1.5E-06	2.0E-06	1.7E-05	1.1E-06	1.5E-06	1.2E-06

Table 2-7. Collective doses (person-Sv) to occupants of trains sharing the route

<u>Truck</u>

Unlike the train situation, a truck carrying spent fuel shares the primary highway system with many cars, light trucks, and other vehicles, as shown in Figure 2-5, a model of the RADTRAN calculation. The occupants of any car or truck that passes the spent fuel cask in either direction will sustain a small radiation dose.

The radiation dose to occupants of other vehicles depends on the exposure distance and time, the number of other vehicles on the road, and the number of people in the other vehicles. Although occupants of the vehicles that share the route are closer to the cask than residents or others beside the route, they are exposed to radiation from the cask for considerably less time because the vehicles involved are moving past each other.

The number of other vehicles that share truck routes is very large: the average number of vehicles per hour on U.S. interstate and primary highways in 2004⁹ (Weiner, et al., 2009, Appendix D) were:

• 1119 on rural segments, about 2 1/2 times the 1977 vehicle density.

Comment [JRC68]: What about cars traveling in same direction as truck, e.g., trailing truck or in adjacent lane, as shown in Fig 2-5?

⁹ 2004 is the most recent year for which data have been validated.

• 2464 on suburban segments, almost four times the 1977 vehicle density.

• 5384 on urban segments, about twice the 1977 vehicle density.

Each vehicle was assumed to have an average of one and a half occupants, since the majority of cars and light trucks traveling on freeways have one or two occupants. State highway departments provide traffic count data but do not provide vehicle occupancy data. If two occupants had been assumed, the collective doses would have been one-third larger.



Figure 2-5. Diagram for calculating radiation doses to occupants of other vehicles (from Neuhauser et al., 2000)

Detailed discussion and state-by-state results are presented in Appendix II. The collective doses for truck traffic are shown in Table 2-8.

Deleted: Table 2-9

ORIGIN	DESTINATION	TRUCK - DU				
		Rural	Suburban	Urban	Urban Rush Hour	
MAINE	ORNL	1.3E-04	2.3E-04	5.4E-05	5.0E-06	
YANKEE	DEAF SMITH	2.9E-04	3.6E-04	7.5E-05	1.5E-05	
	HANFORD	4.4E-04	2.9E-04	4.1E-05	4.0E-06	
	SKULL VALLEY	5.0E-04	2.8E-04	4.3E-05	4.0E-06	
KEWAUNEE	ORNL	9.6E-05	1.4E-04	4.8E-05	4.0E-06	
	DEAF SMITH	1.8E-04	8.9E-05	2.2E-05	2.0E-06	
	HANFORD	3.4E-04	1.4E-04	3.3E-05	3.0E-06	
	SKULL VALLEY	2.5E-04	8.6E-05	2.5E-05	1.0E-05	
INDIAN	ORNL	1.8E-04	2.1E-04	3.3E-05	3.0E-06	
POINT	DEAF SMITH	2.8E-04	3.1E-04	5.6E-05	5.0E-06	
	HANFORD	4.2E-04	2.2E-04	4.8E-05	4.0E-06	
	SKULL VALLEY	3.6E-04	2.2E-04	4.5E-05	4.0E-06	
IDAHO	ORNL	3.0E-04	1.5E-04	2.4E-05	2.0E-06	
NATIONAL	DEAF SMITH	2.2E-04	7.3E-05	2.7E-05	1.8E-05	
LAB	HANFORD	1.0E-04	8.5E-05	9.0E-06	1.0E-06	
	SKULL VALLEY	3.7E-05	2.3E-05	8.0E-06	1.0E-06	

Table 2-8. Collective doses (person-Sv) to occupants of vehicles sharing truck routes

The collective doses to vehicle occupants on rural routes (Table 2-9), are an average of 25 times the collective doses to residents in rural areas (Table 2-7), even though the population in vehicles sharing the route is about the same as the resident population. The difference in collective dose is that vehicles on the road are much closer to the shipment than residents, particularly in rural areas. For suburban areas, the relationship is more complex. Suburban residents are further from the shipment, like rural residents, but the population in vehicles sharing the suburban routes is only one-tenth the resident population. Thus, as expected, the collective doses differ by a smaller factor.

Collective doses to vehicle occupants in urban areas are about 25 times the collective doses to residents, except for rush hour. During rush hours, the doses to vehicle occupants, as modeled, are about 100 times the doses to residents, rather than 25 times. This factor of four reflects the way rush hours are modeled, which is:

- Ten percent of the time spent on urban routes is assumed to be during rush hours.
- Vehicle density during rush hours is assumed to be twice the vehicle density in urban areas at other times.
- Vehicle speed during rush hours is assumed to be half of the vehicle speed in urban areas at other times.

Comment [JRC69]: Seems to contradict second para under Truck section, in which you implied lower dose to occupants due to vehicle passing speed.

Comment [JRC70]: This factor was discounted earlier – see above comment.

Deleted: only

That is, rush hour traffic is assumed to be twice as heavy and traveling at half the speed, so that the collective dose is increased by a factor of four. Even with such extremely conservative assumptions, collective doses during rush hours are 10 percent of the urban collective doses or less. Collective doses to occupants of other vehicles are still very small.

2.3.4 Doses at Stops

Both trucks and trains stop occasionally on long trips. Common carrier freight trains stop to exchange freight cars, to change crews, and, when necessary, to change railroads. The rail stops at the origin and destination of a trip are called "classification stops" and are generally 20 to 30 hours long. Spent fuel casks may be carried on dedicated trains as well as on regular freight trains, although in practice, previous spent fuel shipments have been carried on dedicated trains. A dedicated train is a train that carries a single cargo from origin to destination; coal unit trains

are a good example of dedicated trains.

When a train is stopped, the dose to anyone nearby depends on the distance between that person and the cask and the time that the individual is exposed. The people exposed at a rail stop include:

- Railyard workers (including inspectors)
- Train crew
- · Residents who live near the rail yard.

The semi-tractor trucks that carry TRUCK - DU casks each have two 80-gallon fuel tanks, and generally stop to refuel when half of the fuel is gone, approximately every 525 miles (DOE, 2002). Trucks carrying spent fuel are also stopped at the origin and destination of each trip. Mandatory rest and crew changes are combined with refueling stops whenever possible.

The people likely to be exposed at a refueling truck stop are:

- The truck crew of two; usually one crew member at a time will fill the tanks.
- Other people who are using the truck stop, since these trucks stop at public truck stops.
- Residents of areas near the stop.

A number of states inspect spent fuel cask<u>shipments</u> when the trucks enter the state. Inspection stations may be combined with truck weigh stations, so that inspectors of both the truck carrying spent fuel and trucks carrying other goods can be exposed as well as the crew from other trucks. When the vehicle is stopped, doses to receptors depend only on distance from the source and exposure time, so that any situation in which the cask and the receptor stay at a fixed distance from each other can be modeled as a stop. Such <u>stop-like exposure</u> situations include inspections, vehicle escorts, vehicle crew when the vehicle is in transit, and occupants of other vehicles near the stopped vehicle. Any of these situations can be modeled in RADTRAN. Details of the calculations performed for these situations in this analysis may be found in Appendix II.

Comment [JRC71]: The assumption that 10% of urban route is rush hour is a coincidence?

Figure 2-6 is a diagram of the model used to calculate doses at truck stops. The inner circle defines the area occupied by people who share the stop with the spent fuel truck, who are between the truck and the building, and who are not shielded from the truck's external radiation.



Figure 2-6. Diagram of truck stop model (not to scale)

Table 2-9 lists some sample input data used to calculate doses at stops.

Data	Interstate Highway	Freight Rail
Minimum distance from nearby residents (m)	30	200
Maximum distance from nearby residents (m)	800	800
Stop time for rail classification (hours)	NA	27
Stop time in transit for railroad change (hours)	NA	0.5
Stop time at truck stops (hours)	0.83	NA
Minimum distance to people sharing the stop (m.)	1 ^a	NA
Maximum distance to people sharing the stop (m.)	15 ^a	NA

Table 2-9. Some sample data for calculating doses at stops

^aFrom Griego et al., 1996

Deleted: Table 2-10

Rail

Trains are stopped for classification for 27 hours at the beginning and end of a trip. The collective dose to the railyard workers at these classification stops from the radioactive cargo, for the two rail casks studied, is:

- For the Rail-Pb: 1.5 x 10⁻⁵ person-Sv (1.5 person-mrem)
- For the Rail-All Steel: 1.1 x 10⁻⁵ person-Sv (1.1 person-mrem)

The average dose to an individual living 200 to 800 meters from a classification yard, as calculated by RADTRAN, is

- 0.35 x 10⁻⁵ Sv (0.35 mrem) from the Rail-Pb
- 0.27 x 10⁻⁵ Sv (0.27 mrem) from the Hi-STAR 100

<u>Table 2-10</u> shows the doses at stops to yard workers and residents near the stop for the Maine Yankee-to Hanford rail route. Because different routes have different stops and stop times, a representative result is given here instead of presenting results for an entire route or for all sixteen routes.

Table 2-10. Collective dos	ses at rail stops on the N	Iaine Yankee-to-Hanford	1 route (person-
Sv)			

Stop Route type (R, S, U)		oute typeTimeR, S, U)(hours)	Railya	Railyard worker		Residents near stop	
			Rail-Pb	HISTAR	NAC-STC	HISTAR	
1	S, ME	4.0	2.2 E-05	1.6 E-05	3.4 E-05	2.6 E-05	
2	R, NY	4.0	2.2 E-05	1.6 E-05	9.2 E-06	6.9 E-06	
3	S, IL	2.0	1.1 E-05	8.1 E-06	1.2 E-04	9.4 E-05	

Truck

<u>Table 2-11</u> shows the collective doses to residents near stops for the rural and suburban segments of the 16 routes studied. Urban stops were not modeled because trucks carrying Truck - DU casks of spent fuel are unlikely to stop in urban areas. A more detailed discussion of these calculations is in Appendix II.

Deleted: Table 2-11
Comment [JRC73]: Are these classification
stops? If so, stop times are 27 hours as stated above?

Comment [JRC72]: 20-30 hours was stated previously.

Deleted: ¶ Table 2-12

Origin	Route	Туре	Persons/km ²	Number of stops	Dose
MAINE	ORNL	Rural	19.9	1.73	1.1E-06
YANKEE		Suburban	395	2.09	2.3 E-05
	Deaf Smith	Rural	18.6	2.47	1.5 E-06
		Suburban	371	1.6	1.7 E-05
	Hanford	Rural	15.4	4.33	2.2 E-06
		Suburban	325	1.5	1.4 E-05
	Skull Valley	Rural	16.9	3.5	1.9 E-06
		Suburban	332.5	1.3	1.2 E-05
KEWAUNEE	ORNL	Rural	19.8	0.81	5.2 E-07
		Suburban	361	0.59	6.0 E-06
	Deaf Smith	Rural	13651.0	2.0	8.6 E-07
		Suburban	339	0.52	5.0 E-06
	Hanford	Rural	10.5	3.4	1.2 E-06
		Suburban	316	0.60	5.4 E-06
	Skull Valley	Rural	12.5	2.6	1.1 E-06
		Suburban	324.5	0.44	4.1 E-06
INDIAN	ORNL	Rural	20.5	0.71	4.7 E-07
POINT		Suburban	388	0.71	7.8 E-06
	Deaf Smith	Rural	17.1	2.3	1.3 E-06
		Suburban	370	1.2	1.3 E-05
	Hanford	Rural	13.0	4.1	1.8 E-06
		Suburban	338	1.1	1.1 E-05
	Skull Valley	Rural	14.2	3.3	1.5 E-06
		Suburban	351	0.93	9.3 E-06
IDAHO	ORNL	Rural	12.4	3.1	1.3 E-06
NATIONAL		Suburban	304	0.72	6.3 E-06
LAB	Deaf Smith	Rural	7.8	2.3	5.8 E-07
		Suburban	339	0.35	3.4 E-06
	Hanford	Rural	6.5	0.43	9.0E-08
		Suburban	200	0.57	3.2 E-06
	Skull Valley	Rural	10.1	0.42	1.4 E-07
		Suburban	343	0.11	1.1 E-06

Table 2-11. Collective doses to residents near truck stops (person-Sv)

The rural and suburban population densities in Table 2-12 are the averages for the entire route. An analogous calculation can be made for each state traversed. However, in neither case can one determine beforehand exactly where the truck will stop to refuel. In some cases (e.g., INL to Skull Valley) the truck may not stop at all; the total distance from INL to the Skull Valley site is only 466.2 km (290 miles). The route from Indian Point to ORNL illustrates another situation. This route is 1028 km (639 miles) long, and would thus include one truck stop, which could be in

either a rural or a suburban area. The results shown in <u>Table 2-11</u>, are general average doses at stops.

2.4 Doses to Workers

Radiation doses to workers are limited in accordance with the regulations of 10 CFR Part 20 and the practice of ALARA: maintaining the worker exposure to ionizing radiation "as low as reasonably achievable." ALARA applies to occupational doses because workers are potentially exposed to much larger doses than the general public. For example, the cab of a truck carrying a loaded TRUCK - DU cask is shielded so that 63% of the radiation from the end of the cask is blocked. In addition, the time that a truck crew can spend in the vehicle with a loaded cask is limited.

Occupational doses from routine, incident-free radioactive materials transportation include doses to truck and train crew, railyard workers, inspectors and escorts. Workers who handle spent fuel containers in storage, loading and unloading casks from vehicles or during intermodal transfer are not addressed in this analysis. Truck refueling stops in the U.S. no longer have attendants who refuel trucks.¹⁰ Gas station and truck stop workers are in concrete or brick buildings and would be shielded from the radiation with the same shielding as in urban housing (83% shielded).

Cask and route type	Rail crew : 3 people (person- Sv/hour)	Truck crew: 2 people; (person- Sv/hour)	Escort: (Sv/hour)	Inspector (Sv per inspection)	Truck stop worker (Sv/hour per stop)	Rail classification yard workers: (person-Sv) (see p. 16)
Rail-Pb rural/suburban	5.4E-09	2	5.8 E-06			1.5E-05
Rail-Pb urban	9.1E-08		5.8 E-06			
Rail-All Steel rural/suburban	4.1E-09		4.4 E-06			1.1E-05
Rail-All Steel urban	6.8E-09		4.4 E-06			and Manufacture of the American
TRUCK - DU rural/suburban		3.8E-09	3.2E-09	3.2E-09	2.0E-09	
TRUCK - DU urban		3.6E-09	3.2E-09			

Table 2-12 summarizes the occupational doses.

Table 2-12. Occupational doses per shipment from routine incident-free transportation

¹⁰ The State of Oregon still requires gas station attendants to refuel cars and light duty vehicles, but heavy truck crew do their own refueling. **Comment [JRC74]:** Table 2-2 shows 98.2% shielding by buildings in urban areas?

Deleted: Table 2-13

2.5 Unit Risk

RADTRAN, the model used for the calculation of transportation risk, multiplies numbers. The only calculation that RADTRAN makes which is not a simple multiplication is calculating emissions from the spherical model shown in Figure 2-2. For routine transportation, all other parameters multiply the result of this calculation. RADTRAN can be programmed to calculate the collective dose from a passing vehicle for a population density of one person per square kilometer and one kilometer of a route. This type of calculation is called a unit risk calculation. The result may then be multiplied by the population per square kilometer and the route length in kilometers (if the area along the route is 800 meters wide on either side of the route), and divided by the vehicle speed.

2.6 Conclusions

As Chapter 1 states, risk is a projection of possible effects, and a code that estimates risk can never be <u>completely</u> precise because the input data are themselves estimates and projections. The risk assessment code RADTRAN overestimates doses, and no estimate of dose can substitute for an actual measurement. Therefore, the doses calculated in this chapter should be regarded as overestimates.

Both the individual and collective doses calculated are for a single shipment and, even though overestimated, they are uniformly very small. They are comparable to background and less than doses from many medical diagnostic procedures. The NRC recommends that collective doses (average doses integrated over a population) only be used only for comparisons (NRC, 2008). The proper comparison for collective doses is between the background collective dose plus the shipment dose and the background dose if there is no shipment. The collective dose is not zero in the absence of a shipment.

Deleted: A

Comment [JRC75]: The comparison on p26 illustrates that background collective dose is many of orders of magnitude greater than routine shipment collective dose?

÷

37

.

. .

CHAPTER 3

CASK RESPONSE TO IMPACT ACCIDENTS

3.1 Introduction

Spent fuel casks are required to be accident resistant. During the certification process by the NRC the cask designer must demonstrate, among other things, that the cask would survive a free fall from a height of nine meters impacting onto a flat essentially unyielding target in the orientation that is most likely to damage the cask (10 CFR 71.73). The high standards and conservative approaches required by the NRC for this demonstration include the use of minimum material properties, allowing only small amounts of yielding, and requiring materials with high ductility. These approaches ensure that the casks will not only survive a nine-meter drop, but will also survive much higher speed impacts. In addition to the conservative designs assured by the certification process, there are two additional aspects of the nine-meter drop that provide safety when compared to actual accidents. The first of these is the requirement that the impact be onto an essentially unyielding target. This implies that all of the kinetic energy of the impact will be absorbed by the cask and none by the target. For impacts onto real surfaces, the kinetic energy is absorbed by both the cask and the target. The second aspect is the requirement that the vertical impact is onto a horizontal target. This requirement assures that at some point during the impact the velocity of the cask will be zero, and all of the kinetic energy is converted into strain energy (absorbed by the cask). Most real accidents occur at an angle, and the kinetic energy of the cask is absorbed by multiple impacts instead of all in one impact. In this chapter, all three of these factors will be discussed.

3.2 Finite Element Analyses of Casks

Previous risk studies have been carried out using generic casks. In the case of the Modal Study (Fischer et al, 1987) it was assumed any accident that was more severe than the regulatory hypothetical impact accident would lead to a release from the cask. In NUREG/CR-6672 (Sprung et al., 2000) the impact limiters of the generic casks were assumed to be unable to absorb more energy than the amount from the regulatory hypothetical impact accident (a ninemeter free fall onto an essentially rigid target). Modeling limitations at the time of the studies required both of these assumptions In reality, casks and impact limiters each have excess capacity to resist impacts. In this study, three NRC certified casks were used instead of generic casks, and the actual excess capacity of those cask designs was included in the analyses.

The response to impacts of 48, 97,145, and 193 kilometers per hour (kph)—equal to 30, 60, 90, and 120 mph— onto an unyielding target in the end, corner, and side orientations for the Rail-Steel and Rail-Pb spent fuel transportation casks were determined using the non-linear transient dynamics explicit finite element code PRESTO (SIERRA, 2009). PRESTO is a Lagrangian code, using a mesh that follows the deformation to analyze solids subjected to large, suddenly applied loads. The code is designed for a massively parallel computing environment and for problems with large deformations, nonlinear material behavior, and contact. Presto has a versatile element library that incorporates both continuum elements and structural elements, such as beams and shells.

In addition to the detailed analyses performed for this study, the response of the Truck-DU spent fuel transportation cask was inferred based upon the finite element analyses performed for the generic casks in NUREG/CR-6672. All analyses were performed with the direction of the cask travel perpendicular to the surface of the unyielding target. Figure 3-1 is a pictorial representation of the three impact orientations analyzed. In all of the analyses, the spent fuel basket and fuel elements were treated as a homogenous material. The density of this material was adjusted to achieve the correct weight of the loaded basket. The overall behavior of this material was conservative (because it acts as a single entity that impacts the cask all at once instead of many smaller parts that impact the cask over a longer period of time) for assessing the effect the contents of the cask had on the behavior of the cask—the main focus of this study. Detailed response of the fuel assemblies was calculated using a sub-model of a single assembly.



Figure 3-1. Impact orientations analyzed

3.2.1 Rail-Steel Cask

Finite element model

Figure 3-2 shows the overall finite element model of the Rail-Steel cask. This cask uses steel for its gamma-shielding material and transports 24 PWR assemblies in a welded multi-purpose canister. The impact limiters on each end of the cask are designed to absorb the kinetic energy of the cask during the regulatory hypothetical impact accident. They are made of an interior stainless steel support structure, aluminum honeycomb energy absorber, and a stainless steel skin. Figure 3-3 shows the finite element mesh of the closure end impact limiter (the one on the other end of the cask differs only in how it is attached to the cask). The cask has a single solid steel lid that is attached with 54 1-5/8 inch diameter bolts and sealed with dual metallic o-rings. Figure 3-4 shows the finite element mesh of the closure bolts (also shown are the bolts used to attach the closure end impact limiter) and the level of mesh refinement included in these important parts. Details of the finite element models, including material properties, contact surfaces, gaps, and material failure, are included in Appendix III.



Figure 3-2. Finite element mesh of the Rail-Steel cask



Impact limiter showing the various blocks of honeycomb



Impact limiter with the honeycomb removed to reveal the inner support structure Figure 3-3. Details of the finite element mesh for the impact limiters of the Rail-Steel cask



Figure 3-4. Finite element mesh of the Rail-Steel closure bolts and the closure end impact limiter attachment bolts. The highly refined mesh in these critical parts assures an accurate assessment of the closure response.

Analysis results

As expected, for all of the 48 kph impact analyses (the impact velocity from the regulatory hypothetical impact accident) the impact limiter absorbed almost all of the kinetic energy of the cask and there was no damage (permanent deformation) to the cask body or canister. As the impact velocity increases there is first additional damage to the impact limiter because it is absorbing more kinetic energy (this shows the margin of safety in the impact limiter design). At 97 kph there is still no significant damage to the cask body or canister. At an impact speed of 145 kph damage to the cask and canister appears to begin. The impact limiter has absorbed all the kinetic energy it can and any additional kinetic energy must be absorbed by plastic deformation in the cask body.

For the side impact at 145 kph several of the lid bolts fail in shear (discussion of the failure model is included in Appendix III), but the lid remains attached. At this point the metallic seal no longer maintains the leak-tightness of the cask, but the spent fuel remains contained within the welded canister. Even at the highest impact speed, 193 kph, the welded canister remains intact. Figure 3-5 shows the deformed shape and plastic strain in the canister for the 193 kph impact in a side orientation. This is the case that has the most plastic strain in the canister. The peak value of plastic strain (EQPS=Equivalent Plastic Strain, a representation of the magnitude of local permanent deformation) in this case is 0.7. The stainless steel material of the canister can easily withstand plastic strains greater than one. These results demonstrate that no impact accident will

lead to release of material from the Rail-Steel canister. Similar figures for the other orientations and speeds are included in Appendix III.



Figure 3-5. Plastic strain in the welded canister of the Rail-Steel for the 193 kph side impact case

3.2.2 Rail-Pb Cask

Finite Element Model

Figure 3-6 shows the overall finite element model of the Rail-Pb cask. This cask uses lead for its gamma-shielding material and transports either 26 directly loaded PWR assemblies or 24 PWR assemblies in a welded multi-purpose canister. The impact limiters on each end of the cask are designed to absorb the kinetic energy of the cask during the regulatory hypothetical impact accident. They are made up of redwood and balsa wood energy absorbing material and a stainless steel skin. Figure 3-7 shows the finite element mesh of the closure end impact limiter (the impact limiter on the other end of the cask is identical). The cask has a dual lid system. The inner lid is attached with 42 1-1/2 inch diameter bolts and sealed with dual o-rings that are elastomeric if the cask is used only for transportation and metallic if the cask is used for storage before transportation case. The outer lid is attached with 36 1-inch diameter bolts and sealed with a single o-ring that is elastomeric if the cask is used only for transportation and metallic if the cask is used for storage before transportation case. Figure 3-8 shows the finite element mesh of the closure bolts and the level of mesh refinement included in these important parts. Details of the finite element models are included in Appendix III.



Figure 3-6. Finite element mesh of the Rail-Pb cask



Impact limiter showing the two different types of wood. The yellow is balsa and the red is redwood.



Impact limiter with the wood removed to reveal the inner attachment bolts Figure 3-7. Details of the finite element mesh for the impact limiters of the Rail-Pb



Figure 3-8. Finite element mesh of the Rail-Pb closure bolts for both the inner and outer lids. The longer bolts are for the inner lid and the shorter ones for the outer lid.

Analysis results

For the 48 kph impact analyses (the impact velocity from the regulatory hypothetical impact accident) the impact limiter absorbed almost all of the kinetic energy of the cask and there was no damage to the cask body. The response of the Rail-Pb cask is more complicated than that of the Rail-Steel cask. For the end orientation, as the impact velocity increases there is first additional damage to the impact limiter because it is absorbing more kinetic energy (this shows the margin of safety in the impact limiter design). At 97 kph there is no significant damage to the cask body or canister. At an impact speed of 145 kph damage to the cask and canister appears to begin. The impact limiter has absorbed all the kinetic energy it can and any additional kinetic energy is absorbed by plastic deformation in the cask body. At this speed there is significant slumping of the lead gamma shielding material, resulting in a loss of shielding near the end of the cask away from the impact point (this is discussed in Chapter 5 and Appendix V). As the impact velocity is increased to 193 kph, the lead slump becomes more pronounced and there is enough plasticity in the lids and closure bolts to result in a loss of sealing capability. For the directly loaded cask (without a welded multi-purpose canister) there could be some loss of radioactive contents if the cask has metallic seals but not for the case with elastomeric seals. A more detailed discussion of leakage is provided later in this section. Figure 3-9 shows the deformed shape of the Rail-Pb following the 193 kph impact in the end-on orientation. The amount of lead slump from this impact is 35.5 cm, and the area without lead shielding is visible in Figure 3-9. Table 3-1 gives the amount of lead slump in each of the analysis cases.



Figure 3-9. Deformed shape of the Rail-Pb cask following the 193 kph impact onto an unyielding target in the end-on orientation

Speed (kph)	Max. Slump End (cm)	Max. Slump Corner (cm)	Max. Slump Side (cm)
48	0.64	0.17	0.01
97	1.83	2.51	0.14
145	8.32	11.45	2.09
193	35.55	31.05	1.55

Table 3-1. M	laximum leac	l slump for	r the Rail-Pl	b from eac	ch analysis case ⁴
--------------	--------------	-------------	---------------	------------	-------------------------------

*The measurement locations for each impact orientation are given in Appendix III.

For the corner impacts at 97 and 145 kph there is some damage to the cask body, in addition to deformation of the impact limiter, that results in lead slump and closure bolt deformation. The amount of deformation to the closure in these two cases is not sufficient to cause a leak if the cask is sealed with elastomeric o-rings, but is enough to cause a leak if the cask is sealed with metallic o-rings. For a corner impact at 193 kph there is more significant deformation to the cask, more lead slump, and a larger gap between the lid and the cask body. Figure 3-10 shows the deformed shape of the cask for this impact analysis. The deformation in the seal region is


sufficient to cause a leak if the cask has metallic o-rings but not if it has elastomeric o-rings. The maximum amount of lead slump is 31 cm.

Figure 3-10. Deformed shape of the Rail-Pb following the 193 kph impact onto an unyielding target in the corner orientation

In the side impact as the impact velocity increases from 48 kph to 97 kph, the impact limiter ceases to absorb energy and there is permanent deformation of the cask and closure bolts. The resulting gap in between the lids and the cask body is sufficient to allow leakage if there is a metallic seal, but not enough to leak if there is an elastomeric seal. When the impact speed is increased to 145 kph the amount of damage to the cask increases significantly. In this case many of the bolts from both the inner and outer lid fail in shear and there is a gap between each of the lids and the cask. This gap is sufficient to allow leakage if the cask is sealed with either elastomeric or metallic o-rings. Figure 3-11 shows the deformed shape of the cask following this impact. The response of the cask to the 193 kph impact is similar to that from the 145 kph impact, only the gaps between the lids and the cask are larger. Deformed shapes for all of the analysis cases are shown in Appendix III.



Figure 3-11. Deformed shape of the Rail-Pb following the 145 kph impact onto an unyielding target in the side orientation

Leak area

The Certificate of Compliance for the Rail-Pb cask allows transportation of spent fuel in three different configurations. The analyses conducted for this study were all for the direct-loaded fuel case, but the results can be applied to the case with an internal canister. The impact limiter and cask body are the same for that case. The addition of the internal canister adds strength and stiffness to the cask in the closure region (the canister has a 203-mm thick lid) that will inhibit the rotation of the cask wall and reduce any gaps between the closure lids and the cask. None of the analyses show sufficient deformation into the interior volume of the cask to cause a failure of the internal welded canister. So for this cask, like the Rail-Steel cask, if the spent fuel is transported in an inner welded canister there would be no release from any of the impacts.

In the cases without an inner canister the cask can be used for dry spent fuel storage before shipment or to transport fuel that is removed from pool storage and immediately shipped. In the first of these two cases metallic o-rings provide the seal between each of the lids and the cask body. This type of seal is less tolerant to movement between the lids and the cask, and closure opening greater than 0.25 mm will cause a leak. If the cask is used for direct shipment of spent fuel, elastomeric o-rings provide the seal between each of the lids and the cask body. This type of seal can withstand closure openings of 2.5 mm without leaking (Sprung et al., 2000). Table 3-2 gives the calculated axial gap in each analysis and the corresponding leak area for both metallic and elastomeric seals.

Deleted: Table 3-2

Orientation	Speed (kph)	Location	Lid Gap (mm)	Seal Type	Hole Size (mm ²)
	48	Inner	0.226	Metal**	none
		Outer	0	Elastomer	none
	07	Inner	0.056	Metal	none
End	97	Outer	0.003	Elastomer	none
End	145	Inner	2.311	Metal	none
	145	Outer	0.047	Elastomer	none
	102	Inner	5.588	Metal	8796
×	195	Outer	1.829	Elastomer	none
	48	Inner	0.094	Metal	none
		Outer	0.089	Elastomer	none
	97	Inner	0.559	Metal	65
Como		Outer	0.381	Elastomer	none
Comer	145	Inner	0.980	Metal	599
		Outer	1.448	Elastomer	none
		Inner	2.464	Metal	1716
	195	Outer	1.803	Elastomer	none
	48	Inner	0.245	Metal	none
Side		Outer	0.191	Elastomer	none
	97	Inner	0.914	Metal	799
		Outer	1.600	Elastomer	none
	145	Inner	8*	Metal	>10000
	145	Outer	25*	Elastomer	>10000
	193	Inner	15*	Metal	>10000
		Outer	50*	Elastomer	>10000

Table 3-2. Available areas for leakage from the Rail-Pb cask

*Estimated; the method used to calculate the gaps for the other cases is explained in Appendix III.

**The metal seal for the Rail-Pb cask is only installed when the cask has been used for dry storage prior to transportation. Currently there are none of these casks being used for dry storage and there are no plans for using them in that way in the future.

3.2.3 Truck-DU Cask

Detailed finite element analyses of the Truck-DU cask were not performed for this study, because the response of the truck casks in NUREG/CR-6672 indicated no gaps between the lid and the cask body at any impact speed. Therefore, the results discussed here are based upon the finite element analysis of the generic steel-DU-steel truck cask performed for NUREG/CR-6672. In general, the results from the analyses performed for this study have shown that the analyses

performed for NUREG/CR-6672 were conservative (see Table 3-3), so the results discussed below are likely to be an overestimate of the damage to the Truck-DU cask from severe impacts. Figure 3-12 shows the deformed shape and plastic strain contours for the generic steel-DU-truck cask from Appendix A of NUREG/CR-6672 (Figures A-15, A-19, and A-22). None of the impacts caused strains that are great enough to fail the cask wall, and in all cases the deformation in the closure region was insufficient to cause seal failure. Table 3-4 (extracted from Table 5.6 of NUREG/CR-6672) provides the deformation in the seal region for each case. For all of these cases there would be no release of radioactive contents.

Item/Cask	Rail-Steel	6672 Monolithic Steel
Deformed Shape 145 kph		(Figure A-35 of NUREG/CR-6672)
Failed Bolts	No	Yes
Item/Cask	Rail-Pb	6672 SLS Rail
Deformed Shape 145 kph		Figure A-24 of NUREG/CR-6672)
Gap Size	Inner Lid - 0.980 mm Outer Lid - 1 448 mm	6.096 mm
Failed	No	Yes

Table 3-3. Comparison of analyses between this study and NUREG/CR-6672





Contraction Procession	Analysis	Corner Impact		End Impact		Side Impact	
Cask	Velocity	Opening	Sliding	Opening	Sliding	Opening	Sliding
	48 kph	0.508	1.778	0.127-0.305	0.025-0.127	0.254	0.508
Steel DU Steel Truck	97 kph	2.032	1.778	0.254-0.508	0.076-0.152	0.254	0.254
Sieel-DU-Sieel Huck	145 kph	0.508	2.540	-	-	0.254	0.508
	193 kph	0.762	3.810	0.330	0.762	0.102	0.508

Table 3-4. Deformation of the closure region of the steel-DU-steel truck cask from NUREG/CR-6672, in mm

3.3 Impacts onto Yielding Targets

All of the analysis results discussed in Section 3.2 were for impacts onto an unyielding essentially rigid target. All real impact accidents involve targets that are to some extent yielding. When a cask impacts a real target the amount of the impact energy that is absorbed by the target and the amount that is absorbed by the cask depend on the relative strength and stiffness of the two objects. For an impact onto a real target to produce the same amount of damage as the impact onto an unyielding target, the force applied to the cask has to be the same. If the target is not capable of sustaining that level of force, it cannot produce the corresponding level of damage in the cask. For the Rail-Pb cask (the only one of the three investigated in this study that has any release) the peak force associated with each of the impact analyses performed is given in <u>Error!</u> <u>Reference source not found</u>. In this table the cases that have non-zero hole sizes from Table 3 5 have bold text. It can be seen, that in order to produce sufficient damage for the cask to release any material, the yielding target has to be able to apply a force to the cask greater than 146 MN (33 million pounds). Very few real targets are capable of applying this amount of force.

If the cask hits a flat target, such as the ground, roadway, or railway, it will penetrate into the surface. The greater the penetration depth, the more force the target can exert on the cask. Figure 3-13 shows the relationship between penetration depth and force for the Rail-Pb cask impacting onto hard desert soil. As the cask penetrates the surface, some of its kinetic energy is absorbed by the surface. The amount of energy absorbed by the target is equal to the area underneath the force vs. penetration curve of Figure 3-13. As an example, the end impact at 97 kph onto an unyielding target requires a contact force of 123.9 MN. A penetration depth of approximately 2.2 meters will cause the soil to exert this amount of force. The soil absorbs 142 MJ of energy in being penetrated this distance. Adding the energy absorbed by the soil to the 41 MJ of energy absorbed by the cask gives a total absorbed energy of 183 MJ. For the cask to have this amount of kinetic energy it would have to be traveling at 205 kph. Therefore, a 205 kph impact onto hard desert soil causes the same amount of damage as a 97 kph impact onto an unyielding target. A similar calculation can be performed for other impact speeds, orientations and target types. Table 3-6 provides the resulting equivalent velocities. Where the calculated velocity is more than 250 kph the value in the table is listed as greater than 250. No accident velocities are more than this. The concrete target used is a 23 cm thick slab on engineered fill. This is typical of many concrete roadways and concrete retaining walls adjacent to highways. Details on the calculation of equivalent velocities are included in Appendix III.

Deleted: Table 3-18

Orientation	Speed (kph)	Accel. (G)	Contact Force (Millions of Pounds))	Contact Force (MN)
End	48	58.5	14.6	65.0
	97	111.6	27.9	123.9
	145	357.6	89.3	397.1
	193	555.5	138.7	616.8
Corner	48	36.8	9.2	40.9
	97	132.2	33.0	146.8
	145	256.7	64.1	285.1
	193	375.7	93.8	417.2
Side	48	76.1	19.0	84.5
	97	178.1	44.5	197.8
	145	411.3	102.7	456.7
Γ	193	601.1	150.0	667.4

Table 3 5. Peak contact force for the Rail-Pb cask impacts onto an unyielding target (bold numbers are for the cases where there may be seal leaks)





Orientation	Rigid	Soil	Concrete
End	48	102	71
	97	205	136
	. 145	>250	>250
	193	>250	>250
Corner	48	. 73	70
	97	236	161
	145	>250	>250
· · · ·	193	>250	>250
Side	48	103	79
	97	246	185
· .	145	>250	>250
	193	>250	. >250

Table 3-6. Equivalent velocities for impacts onto various targets with the Rail-Pb cask, kph

3.4 Effect of Impact Angle

The regulatory hypothetical impact accident requires the cask's velocity to be perpendicular to the impact target. All of the analyses were also conducted with this type of impact. During transport the usual scenario is that the velocity is parallel to the nearby surfaces, and therefore, most accidents that involve impact with surfaces occur at a shallow angle (this is not necessarily true for impacts with structures or other vehicles). Accident databases do not include impact angle as one of their parameters, so there is no information on the relative frequency of impacts at various angles. Given that vehicles usually travel parallel to the nearby surfaces, for this study a triangular distribution of impact angles was used. Figure 3-14 shows the assumed step-wise distribution of impact angle probabilities. For impacts onto hard targets, which are necessary to damage the cask, the component of the velocity that is parallel to the impact surface has very little effect on the amount of damage to the cask. This requires the accident speed to be higher for a shallow angle impact then a perpendicular one in order to achieve the same amount of damage. Figure 3-15 depicts an example of an impact at a shallow angle and the components of the velocity parallel and perpendicular to the surface. Table 3-7 provides the cumulative probability of exceeding an impact angle range and the accident speeds that are required to have the velocity component in the direction perpendicular to the target.







Figure 3-15. Influence of impact angle on effective velocity

Angle	Prob.	Cum. Prob.	V _{Acc} so V _{Perp} = 48 kph	V _{Acc} so V _{Perp} = 97 kph	V _{Acc} so V _{Perp} = 145 kph	V _{Acc} so V _{Perp} = 193 kph
0 - 10	0.2000	1.0000	278	556	834	1112
10 - 20	0.1778	0.8000	141	282	423	565
20 - 30	0.1556	0.6222	97	193	290	386
30 - 40	0.1333	0.4667	75	150	225	300
40 - 50	0.1111	0.3333	63	126	189	252
50 - 60	0.0889	0.2222	56	111	167	223
60 - 70	0.0667	0.1333	51	103	154	206
70 - 80	0.0444	0.0667	49	98	147	196
80 - 90	0.0222	0.0222	48	97	145	193

Table 3-7. Accident speeds that result in the same damage as a perpendicular impact, kph

3.5 Impacts with Objects

The discussions in the preceding sections all dealt with impacts onto flat surfaces. A large number of impacts deal with surfaces that are not flat. These include impacts into columns and other structures, impacts by other vehicles, and, more rarely, impacts by collapsing structures. These types of impacts were not explicitly included in this study, but recent work by Sandia National Laboratories (NRC, 2003b, Ammerman and Gwinn, 2004, Ammerman et al., 2005) has shown the response of the GA-4 cask to some of these impacts. The result of an impact into a large, semi-circular, rigid column is shown in Figure 3-16 (NRC, 2003b). While this impact led to significant permanent deformation of the cask, the level of strain was not high enough to cause tearing of the containment boundary and there was no permanent deformation in the closure region and no loss of containment.



Figure 3-16. Deformations to the GA-4 truck cask after a 96 kph side impact onto a rigid semi-circular column, from (NRC, 2003b).

Another type of accident that could potentially damage a cask is the collision by a railroad locomotive. This is probably the most severe type of collision with another vehicle that is possible. Several different scenarios of this type of collision were investigated by Ammerman et al. (2005). The overall configuration of the general analysis case is shown in Figure 3-17. Variations on the general configuration included using the two most common types of locomotives, having a level crossing (such that the tires of the truck and the wheels of the locomotive are at the same elevation), having a raised crossing where the bottom of the main beams of the trailer at the same elevation as the top of the tracks, and having a skewed crossing so the impact is at 67° instead of at 90°. For all analyses the truck was assumed to be stopped. Train velocities of 113 kph and 129 kph were considered. None of the analyses led to deformations that would cause a release of radioactive material from the cask and none of them resulted in cask accelerations that were high enough to fail the fuel rod cladding. Figure 3-18 shows a sequence of the impact. The front of the locomotive is severely damaged and the trailer is totally destroyed, but there is very little deformation of the cask—only minor denting where the collision posts of the locomotive hit.



Figure 3-17. Configuration of locomotive impact analysis (from Ammerman et al., 2005)



Figure 3-18. Sequential views of a 129 kph impact of a locomotive into a GA-4 truck cask (from Ammerman et al., 2005)

A type of accident that occurs less frequently, but also has the potential to damage a cask is the collapse of a bridge onto the cask. This type of accident occurred when an elevated portion of the Nimitz Freeway collapsed during the Loma Prieta earthquake. This accident scenario was analyzed to determine if it would cause a release of spent fuel from the GA-4 truck cask (Ammerman and Gwinn, 2004). The analysis assumed the cask was lying directly on the

roadway (neglecting the cushioning effect of the trailer and impact limiters) and one of the main beams of the elevated freeway fell and impacted the middle of the cask. The stresses in the cask and damage to the beam are shown in Figure 3-19. As in the other analyses for impacts with objects, there would be no loss of containment from this accident.

Time=0.100



Figure 3-19. Results of a finite element simulation of an elevated freeway collapse onto a GA-4 spent fuel cask (from Ammerman and Gwinn 2004)

3.6 Response of Spent Fuel Assemblies (Kalan et al., 2005)

The finite element analyses did not include the individual components of the spent fuel assemblies. Instead, the total mass of the fuel and its support structure were combined into an average material. To determine the response of individual components, a detailed model of a spent fuel assembly was developed. Figure 3-20 shows this model. The loads associated with a 100 G cask impact in a side orientation were then applied to this detailed model. Kalan et al. only analyzed side impacts because the strains associated with buckling of the rods during an end impact are limited by the constrained lateral deformations provided by the basket. The side impact results in forces in each fuel rod at their supports and in many of the fuel rods midway between the supports where they impact onto the rods above or below them. The response of the rod with the highest loads was determined by a detailed finite element model, shown in Figure 3-21. There is slight yielding of the rod at each support location and slightly more yielding where the rods impact each other. Figure 3-22 shows the maximum plastic strain at each location. The largest of these strains is slightly below 2%, which is half the plastic strain capacity of irradiated zircaloy at the maximum burn-up allowed in the Rail-Pb cask (45,000 MWD/MTU) (Sanders et al., 1992), so fuel rods will not crack. For cladding to fail, the peak acceleration of the cask would have to be above 200G. The only impacts that are severe enough to crack the rods are



those with impact speeds onto an essentially unyielding target of 145 kph or higher. A detailed description of the fuel assembly modeling is included in Appendix III.

Figure 3-20. Finite element model of a PWR fuel assembly.



Figure 3-21. Detailed finite element model of a single fuel rod.



Figure 3-22. Maximum strains in the rod with the highest loads.

3.7 Conclusions

The finite element analyses performed indicate that casks are very robust structures that are capable of withstanding almost all impact accidents without release of radioactive material. In fact, when spent fuel is transported within an inner welded canister or in a truck cask, there are no impacts that result in release. Even the rail cask without an inner welded canister can withstand impacts that are much more severe than the regulatory impact without releasing any material. In the worst orientation (side impact) an impact speed onto a rigid target more than 97 kph is required to cause seal failure. A 97 kph side impact onto a rigid target produces a force of about 200 MN (45 million pounds) and is equivalent to a 185 kph impact onto a concrete roadway or abutment or a 246 kph impact onto hard soil. For impacts onto hard rock, which may be able to resist these large forces, impacts at angles less than 30 degrees require a speed more than 193 kph in order to be equivalent. In summary, the sequence of events that is needed for there to be the possibility of any release is: a rail transport cask, no welded canister, an impact velocity greater than 97 kph, the cask impacting in a side orientation, the impact surface being hard rock, and the impact angle being greater than 30 degrees.

CHAPTER 4

CASK RESPONSE TO FIRE ACCIDENTS

4.1 Introduction

Certified Type B casks are designed to survive a fully-engulfing fire for thirty minutes. This is more severe than the majority of the thermal environments a cask may be exposed to in an accident that results in a fire. Certification analyses of the hypothetical fire environment specified in 10 CFR 71.73 impose on the cask a similar or more severe thermal environment than a real fully-engulfing fire. Large open pool fires can burn at temperatures higher than the 800°C specified in the regulations. Real fire plumes have location- and time-varying temperature distributions that vary from about 600°C to more than 1200°C (Koski, 2000; Lopez et al., 1998). Therefore, the evenly-applied 800°C fire environment used in certification analysis can be more severe for seal and fuel rod response than a real fire.

For this risk study, computer codes capable of modeling fires and the thermal response of casks exposed to fires in a realistic fashion are used to analyze the response of the Rail-Steel and the Rail-Pb casks to three different hypothetical fire configurations. These configurations are described in this chapter and the temperature responses of the casks are presented and discussed. A discussion of the thermal performance of the Truck-DU cask exposed to a severe hypothetical fire is also presented, using the analyses in NUREG/CR-6672 (Sprung et al., 2000).

The thermal response of each cask is compared to two characteristic temperature limits. These are the seal failure temperature (350°C for elastomeric seals used in the Rail-Pb cask and the Truck-DU and 649°C for the metallic seal used in the Rail-Steel cask) and the fuel rod burst rupture temperature (750°C for all casks). The values selected for these temperature limits are the same as those used in NUREG/CR-6672 for the elastomeric seal and fuel rod burst temperature. The Rail-Steel cask seal temperature limit is obtained from Table 2.1.2 and Table 4.1.1 in the HI-STAR 100 SAR (Holtec International, 2004). Section 7.2.5.2 in NUREG/CR-6672 explains that 350°C is a conservative temperature limit for elastomeric seals typically used in the spent nuclear fuel transportation industry. NUREG/CR-6672 also provides the rationale for the use of 750°C as the fuel rod burst rupture temperature. These temperature limits are used in this study to determine if the cask seals or fuel rods would be compromised, allowing release of radioactive material under any of the accident scenarios analyzed.

4.2 Description of Accident Scenarios

4.2.1 Pool size

Three hypothetical fire accident scenarios are analyzed for each rail cask and one for the truck cask. A fuel pool that conforms to the regulatory requirement in 10 CFR 71.73 is used as the basis for each scenario. This regulation specifies a fuel pool that extends between one and three meters horizontally beyond the external surface of a cask. In this study, all fuel pools were assumed to extend three meters from the sides of each package analyzed to ensure the casks would be fully engulfed.

4.2.2 Fire duration

The duration of the hypothetical fires for the rail cask analysi is based on the capacity of a large rail tank car. Typical large rail tank cars can carry about 30,000 gallons of flammable liquid. To estimate the duration of the fires, this amount of fuel is assumed to form a pool with the dimensions of a regulatory pool fire for the rail casks that were analyzed. That is, fuel pools that extend horizontally three meters beyond the surfaces of the casks are used in the computer models. Provided that there are relatively small differences between the overall dimensions of the Rail-Steel cask and the Rail-Pb cask, these fuel pools are similar in size and are nominally 14m x 9m. A pool of this size would need to be 0.9m deep to pool 30,000 gallons of liquid fuel, a condition that is extremely unlikely to be met in an accident scenario. If the fuel in such pool were to ignite, this pool fire would burn for about 3 hours. This fire duration is estimated using a nominal hydrocarbon fuel recession (evaporation) rate of 5mm per minute, typical of large pool fires (SFPE, 2002; Lopez et al., 1998; Quintiere, 1998). Another way this large pool area could burn for up to three hours would be the even more unlikely case in which fuel flows at exactly the right rate to feed and maintain the pool area for the duration of the fire. Provided that both of these pooling conditions are very difficult to obtain, the fire duration presented here is considered to be conservative. Nevertheless, a 3-hour fire that is not moving over time and is capable of engulfing a rail cask over the duration of the fire is conservatively used for the analysis of the two rail casks considered in this study.

In the case of the Truck-DU cask, the fire duration is based on the fuel capacity of a typical petroleum tank truck. About 9,000 gallons of gasoline can be transported on the road by one of these tank trucks. Provided that the overall dimensions of the Truck-DU cask are 2.3m x 6m, a regulatory pool that extends horizontally 3 meters beyond the outer surface of the cask would be 8.3m x 12m. To pool 9,000 gallons of gasoline in a pool of this area, the pool would need to be 0.3m deep, a configuration that is difficult to obtain in an accident scenario and therefore unlikely to occur. Such a pool fire would burn for a little more than an hour. As discussed for the rail cask pool fire, the other possibility of maintaining a fire that can be engulfing and that can burn for that duration is if gasoline were to flow at the right rate to maintain the necessary fuel pool conditions. Again, this scenario is very unlikely also. However, one hour is used as the duration of a fire that is not moving over time for the conservative analysis of the Truck-DU cask.

4.2.3 Hypothetical accident configurations for the rail casks

Three hypothetical fire accident scenarios different from the regulatory configuration are analyzed in this study for the rail casks. These are:

1. Cask on the ground and concentric with the fuel pool as depicted in Figure 4-1.

This scenario represents the hypothetical case in which the liquid fuel spilled as a consequence of the accident flows to the location where the cask came to rest after the accident and forms a large pool under (and concentric with) the cask.

2. Cask on the ground with the fuel pool offset three meters (side of cask to side of fuel pool) as depicted in Figure 4-2.

This scenario represents the hypothetical case in which the fuel pool and the cask are separated by one rail car width. This could be the case of an accident in which the train jackknifes or a pile-up accident.

3. Cask on the ground with the fuel pool offset 18 meters (side of cask to side of fuel pool) as depicted in Figure 4-3.

This scenario represents the hypothetical case in which the fuel pool and the cask are separated by one rail car length. This represents an accident in which the tank car carrying the flammable liquid maintains the distance of a buffer rail car after the accident. For this scenario, the most damaging cask position is assumed. That is, the side of the cask is assumed to face the fire.



Figure 4-1. Cask on ground concentric with fuel pool



Figure 4-2. Cask on ground and the 3m offset pool fire



Figure 4-3. Cask on ground and the 18m offset pool fire

In each scenario, only the cask and the fuel pool are present. There are no other objects (such as other rail cars) that are likely to be present that could shield (protect) the cask from the fire. Calm wind conditions are also assumed.

In addition to these hypothetical accident scenarios, two 30-minute regulatory fire analyses are performed as described in 10 CFR 71.73. In the first analysis a commercially-available finite element (FE) heat transfer code is used to apply an 800°C uniform-heating fire condition to the casks. In the second analysis, a benchmarked computational fluid dynamics (CFD) and radiation heat transfer computer model are used. In this model, the cask is positioned one meter above the fuel pool and the fire is realistically modeled as shown in Figure 4-4.



Figure 4-4. Regulatory pool fire configuration.

4.3 Analysis of Fire Scenarios Involving Rail Casks

Advanced computational tools are employed to generate the data necessary for this risk study by simulating the heat transport in the fire and the cask body. Two computer codes that include all the relevant heat transfer and fire physics are used in a coupled manner. This allows for the simultaneous detailed modeling of realistic external fire environments and heat transfer within complex casks. Brief descriptions of the models are presented in this section. Detailed information of the computer models including material properties, geometry, boundary conditions, and the assumptions used for model generation and subsequent analyses are presented in Appendix IV.

Results from the fire and heat transfer analyses that are performed on the Rail-Steel and the Rail-Pb casks are presented in this section. The temperature range of the legends in the temperature distribution plots of all the Rail-Steel cask analysis results are made the same to make relative comparisons easier. The same is done for the Rail-Pb cask plots. However, the temperature scale for the Rail-Steel cask differs slightly from the scale for the Rail-Pb cask.

Results of the analyses are presented in the following order:

- 1. Regulatory 800°C uniform heating (30 minutes)
- 2. Regulatory CAFE fire (30-minute fire)
- 3. Cask on the ground and concentric with a three-hour pool fire
- 4. Cask on the ground with a three-hour pool fire offset three meters
- 5. Cask on the ground with a three-hour pool fire offset 18 meters

4.3.1 Simulations of the fires

Fire simulations are performed with the Container Analysis Fire Environment (CAFE) code (Suo-Anttila, et al., 2005). CAFE is a CFD and radiation heat transfer computer code that is capable of modeling fires realistically and that has been successfully coupled to commercially-available finite-element analysis computer codes. It can be used for the design and risk analysis of packages for the transportation of radioactive material (RAM). CAFE has been benchmarked against large-scale fire tests specifically designed to obtain data for the calibration of fire codes (del Valle, 2009; del Valle, et al., 2007; Are et al., 2005; Lopez et al., 2003). Appendix IV contains the details of the benchmark exercises that were performed to ensure that proper input parameters are used to realistically represent the engulfing and offset fires assumed for this study.

As described in Section 4.2.3, in addition to the regulatory configuration, three other hypothetical fire scenarios are analyzed. These are: 1) a cask on the ground engulfed by a pool fire for three hours, 2) a cask on the ground offset from a fire by 3-meters for three hours, and 3) a cask on the ground offset from a fire by 18-meters for three hours. Calm wind conditions are assumed for all cases.

4.3.2 Simulations of the rail casks

The heat transfer within the Rail-Steel and the Rail-Pb casks is modeled with the computer code MSC PATRAN-Thermal (P-Thermal) (MSC, 2008). This code is commercially available and is used to solve a wide variety of heat transfer problems. P-Thermal has been coupled with CAFE, allowing for a refined heat transfer calculation within complex objects, such as spent fuel casks, with realistic external fire boundary conditions.

Both the Rail-Steel cask and the Rail-Pb cask have a polymeric neutron shield that is assumed to disintegrate completely and be replaced by air at its operational temperature limit. (see Appendix IV).

The Rail-Pb cask has a lead gamma shield that is allowed to melt if it reached its melting temperature. Unlike the neutron shield, the thermal energy absorbed in the process of melting the gamma shield is included in the analyses. The effects of the thermal expansion of the lead are not included in the heat transfer calculations but are considered in the estimation of the reduction of the gamma shielding. Gamma shielding in the Rail-Steel cask is provided by the thick multi-layered carbon steel wall. Therefore, melting is not a consideration for this cask under any of the conditions to which it is exposed.

Impact limiters are modeled as undamaged (not deformed). The Rail-Steel cask has aluminum honeycomb impact limiters and the Rail-Pb cask has wood impact limiters. Large gaps within cask components are explicitly modeled in both casks as these could have a significant effect on the thermal response of the cask. The finite element models of the two casks are shown in Figure 4-5. Cask modeling details are presented in Appendix IV.



Figure 4-5. Finite element models of the two rail casks. The left figure is the Rail-Steel and the right figure is the Rail-Pb.

4.3.3 Simulation of the spent fuel region

The fuel region comprising the fuel basket and the fuel assemblies is not modeled explicitly. Instead, a homogenized fuel region is used. All materials and geometric features of the fuel basket of the casks that are analyzed are represented as a solid cylinder inside the cask. The thermal response of the homogenized fuel region is very similar to the overall response of the actual fuel region and provides sufficient information for this study. The details of how the effective properties of the homogenized fuel region are determined and applied to the model are presented in Appendix IV.

4.3.4 Rail-Steel cask results

The results for the Rail-Steel cask are presented in the order specified at the beginning of Section 4.3 in Figure 4-6 through Figure 4-20, Figure 4-6 through Figure 4-9 contain the temperature distribution and transient temperature response of key cask regions for the regulatory 800°C uniform heating and the regulatory CAFE fire. The uniform external heating produces an even temperature response around the circumference of the seal. However, the realistic uneven fire heating of the exterior produces temperatures at the seal that vary around the circumference. For comparison, the results obtained from the uniform regulatory fire simulation are plotted against the hottest regional temperatures obtained from the regulatory CAFE (non-uniform) fire simulation. This thermal response comparison is presented in Figure 4-10. This figure illustrates that the uniform heating thermal environment described in 10 CFR 71.73 heats up the seal region of the Rail-Steel cask more than a real fire may, even though a real fire can impart to the cask a localized thermal environment that is hotter than 800°C. A real fire applies a time- and spacevarying thermal load to an object engulfed by it. In particular, large fires have an internal region where fuel in the form of gas exists but sufficient oxygen for that fuel to burn is not available. This region is typically called the vapor dome. The lack of oxygen in the vapor dome is attributed to poor air entrainment in larger diameter fires, where much of the oxygen is consumed in the perimeter of the plume region. Since combustion is inefficient inside the vapor dome, this region stays cooler than the rest of the fire envelop. Thus, the presence of regions that are cooler than 800°C within a real fire makes it possible for fires with peak flame temperatures above 800°C to have an overall effect on internal temperatures of a thermally massive object that is similar to those obtained by applying a simpler heating condition such as the one specified in 10 CFR 71.73.

The effects of the vapor dome on the temperature distribution within a fire and the concentration of unburned fuel available in the vapor dome for the CAFE regulatory analysis can be seen in Figure 4-11 and Figure 4-12. Note that these plots are snapshots of the distributions at an arbitrary time during the fire simulation. In reality, the fire moves slightly throughout the simulation causing these distributions to vary over time. Nevertheless, these plots show representative distributions for the cask and fire configuration shown.

Additional plots with more information about temperature distributions at different locations in the cask are shown in Appendix IV.

Deleted: Figure 4-5	
Deleted: Figure 4-19	
Deleted: Figure 4-5	
Deleted: Figure 4-8	

100	ia na ia	60		
Je	etea		Figure	4-9



Figure 4-6. Temperature distribution of the Rail-Steel cask at the end of the 30-minute 800°C regulatory uniform heating



Figure 4-7. Temperature of key cask regions, Rail-Steel cask – Regulatory uniform heating



Figure 4-8. Temperature distribution of the Rail-Steel cask at the end of the 30-minute regulatory CAFE fire







Figure 4-10. Comparison of regulatory fire analysis - Rail-Steel cask: Uniform heating vs. CAFE fire



Figure 4-11. Gas temperature plots from the regulatory CAFE fire analysis





The results from the analysis of the cask on the ground and concentric with a pool fire that burns for three hours are presented in Figure 4-13 and Figure 4-14. As in the regulatory configuration, in which the cask is elevated 1 meter above the fuel pool, the vapor dome had an effect on the temperature distribution of the cask in this case. This is evident by the cooler temperatures observed at the bottom of the cask. In this scenario, even after three hours in the fire, the temperatures at the bottom of the package are cooler than the temperatures observed in the

regulatory configuration. However, the top of the cask in this configuration heats up more than the rest of the cask. This is different from what is observed in the regulatory configuration, in which the hotter regions are found on the sides of the cask. Figure 4-15 and Figure 4-16 are the fire temperature distribution and fuel concentration plots at an arbitrary time during the CAFE fire simulation of this scenario. In this case, the concentration of unburned fuel under the cask is high and therefore the temperature of the fire under the cask is lower than what is observed in the regulatory configuration.



Figure 4-13. Temperature distribution of the Rail-Steel cask at the end of the 3-hour concentric CAFE fire - cask on ground



Figure 4-14. Temperature of key cask regions, Rail-Steel cask – Cask on ground, concentric fire









The results of the offset fire analyses are summarized in Figure 4-17 through Figure 4-20. In the case of the three-meter offset, the side of the cask facing the fire received heat by thermal radiation. The heat absorbed by the cask during the 3-hour exposure caused the temperature of the cask to rise as depicted in Figure 4-17 and Figure 4-18. Similarly, the 18-meter offset fire caused the cask temperature to rise as illustrated in Figure 4-19 and Figure 4-20. These results show that offset fires, even as close to the cask as three meters, do not represent a threat to this thermally-massive spent nuclear fuel transportation cask. The maximum temperatures observed

~ 81

Ċ



in the seal and fuel region did not reach the temperature limits discussed at the beginning of this chapter. Therefore, offset scenarios will not cause this package to fail.

Figure 4-17. Temperature distribution of the Rail-Steel cask at the end of the 3-hour 3m offset CAFE fire - cask on ground



Figure 4-18. Temperature of key cask regions, Rail-Steel cask – Cask on ground, 3m offset fire



Figure 4-19. Temperature distribution of the Rail-Steel cask at the end of the 3-hour 18m offset CAFE fire - cask on ground



Figure 4-20. Temperature of key cask regions, Rail-Steel cask – Cask on ground, 18m offset fire
Summary of Rail-Steel cask analysis results

The results presented here show that the Rail-Steel cask is capable of protecting the fuel rods from burst rupture and is also capable of maintaining containment when exposed to the severe fire environments that are analyzed as part of this study. That is, the fuel region stayed below 750°C and the seal region stayed under 649°C for all the scenarios that are considered. Furthermore, this cask uses a welded canister that will not be compromised under these thermal loads. This cask will not experience loss of gamma shielding because in this cask shielding is provided by the thick multi-layered carbon steel wall, which is not affected in a way that could reduce its ability to provide shielding.

4.3.5 Rail-Pb cask results

The thermal response of the Rail-Pb cask to the same fire environments discussed above for the Rail-Steel cask is presented in this section. The 30-minute regulatory fire results are summarized in Figure 4-21 through Figure 4-25.

The results obtained from the uniform regulatory fire simulation are plotted against the hottest regional temperatures obtained from the CAFE (non-uniform) regulatory fire simulation. This plot is shown in Figure 4-25. As with the Rail-Steel cask, this figure illustrates that the uniform heating thermal environment described in 10 CFR 71.73 heats up the seal region of the Rail-Pb cask more than a non-uniform real fire may, even though a real fire may impart to the cask a localized thermal environment that is hotter than 800°C.

The results of the analyses of cask on the ground heated by the concentric and offset fires are summarized in Figure 4-26 through Figure 4-31. These plots show similar trends to those observed in the Rail-Steel cask for the same configurations.

Two of the scenarios that are analyzed show melting of the lead gamma shield in the Rail-Pb cask. Lead melts at 328°C and during that process, it absorbs (stores) heat while maintaining its temperature relatively constant at 328°C. As a result, the heat-up rate of portions of the cask slows down while the lead melts. That is why the curve of the region inward from the gamma shield region (i.e., the edge of the fuel region) in Figure 4-27 and Figure 4-29 show a change in slope at about 328°C. This effect is more clearly seen in the slower heating case shown in Figure 4-29. Once the lead melting process is complete, the cask resume heating up as before if the external source is still at a higher temperature. Note that a similar effect is observed when the lead solidifies at 328°C during the post fire cooling period. In this case, the cooling rate of portions of the cask slows down while the lead solidifies. This can also be clearly seen in Figure 4-29.

Another effect considered in the cases where lead melted is the gradual thermal expansion and contraction of the gamma shield region during the heating and cooling of the cask. This effect is discussed in the next subsection.

Appendix IV contains additional plots with more information about temperature distributions at more locations in the cask.



Figure 4-21. Temperature distribution of the Rail-Pb cask at the end of the 30-minute 800°C regulatory uniform heating







Figure 4-23. Temperature distribution of the Rail-Pb cask at the end of the 30-minute regulatory CAFE fire







Figure 4-25. Comparison of regulatory fire analysis – Rail-Pb cask: Uniform heating vs. CAFE fire



Figure 4-26. Temperature distribution of the Rail-Pb cask at the end of the 3-hour concentric CAFE fire - cask on ground



Figure 4-27. Temperature of key cask regions, Rail-Pb cask – Cask on ground, concentric fire



Figure 4-28. Temperature distribution of the Rail-Pb cask at the end of the 3-hour 3m offset CAFE fire - cask on ground



Figure 4-29. Temperature of key cask regions, Rail-Pb cask – Cask on ground, 3m offset fire



Figure 4-30. Temperature distribution of the Rail-Pb cask at the end of the 3-hour 18m offset CAFE fire - cask on ground



Figure 4-31. Temperature of key cask regions, Rail-Pb cask – Cask on ground, 18m offset fire

Melting of the lead gamma shield

There are two cases in which a portion of the lead gamma shield melts. These are the three-hour concentric fire and the three-hour three meter offset fire. The region of the lead gamma shield that melted for each case is shown in red in Figure 4-32 and Figure 4-33. Note that these two figures only show the portion of the cask wall that has lead. Due to melting and thermal expansion of some of the lead gamma shield, some loss of shielding is observed, which translates to an increase in gamma radiation exposure. The width of the streaming path (gap created due to lead melt, expansion, and subsequent contraction as it solidifies) is estimated. For this estimate, the assumption is made that the thermal expansion of the lead buckled the interior wall of the cask, enabling the calculation of the gap in the lead gamma shield.

The gap in the lead region caused by the concentric fire case is assumed to appear on the top portion of the cask. That is, after the lead melts and buckles the interior wall due to its thermal expansion, molten lead is assumed to flow to the lower portions of the gamma shield region of the cask, which allows a gap to be formed on the top portion of the cask. This gap is estimated to be about 0.5m (20 inches), which translates to an 8.1% loss of shielding. In the case of the three-meter offset fire, the gap is assumed to form on the top portion of the molten lead region shown in Figure 4-33. For this case, the gap is estimated to be about 0.127m (5 inches), which translates to a 2% loss of shielding. These loss-of-shielding fractions are used as part of the work presented in Chapter 5 to estimate the consequences.



Figure 4-32. Rail-Pb cask lead gamma shield region - maximum lead melt at the middle of the cask - Scenario: Cask on ground, 3-hour concentric pool fire



Figure 4-33. Rail-Pb cask lead gamma shield region - maximum lead melt at the middle of the cask - Scenario: Cask on ground, 3-hour 3-meter offset pool fire

Summary of Rail-Pb cask analysis results

The results presented here show that the Rail-Pb cask is also capable of protecting the fuel rods from burst rupture and capable of maintaining containment when exposed to the severe fire environments that are analyzed as part of this study. However, some reduction of gamma shielding is estimated to occur in two cases. Partial loss of shielding is expected for the case in which the cask is exposed to an engulfing fire that burns for longer than 65 minutes and for the case in which the cask receives heat from a fire that is offset by three meters and burns for longer than two hours and 15 minutes. Nevertheless, no release of radioactive material is expected if this cask were to be exposed to any of these severe thermal environments, as the elastomeric seals did not reach their temperature limit. This ensures that the cask is capable of maintaining containment under any of the fire environments that are analyzed.

4.4 Truck Cask Analysis

Unlike for the rail casks, detailed three-dimensional FE analyses of the Truck-DU cask are not performed for this risk study. However, NUREG/CR-6672 provides the information necessary to determine the capacity of this cask to withstand the conservative one hour fire duration calculated in Section 4.2.2 of this document.

A comparison of the results obtained from the analyses performed for this study with those found in NUREG/CR-6672 show that the analyses performed for NUREG/CR-6672 were conservative. For example, in NUREG/CR-6672 the seal temperature of the all steel rail cask reached 350°C in about 2.37 hours and in this study the seal temperature of the Rail-Steel cask is about 275°C at the same time. In addition, after the package is exposed to the fire for one hour, the inner surface temperature of the NUREG/CR-6672 cask was 265°C compared to 229°C in this study. Another example, in NUREG/CR-6672 the seal temperature of the steel-lead-steel cask reached 350°C in about 1.69 hours and in this study the inner and outer seal temperatures of the Rail-Pb cask are about 233°C and about 129°C, respectively, at the same time. In addition, after the package was exposed to the fire for one hour, the inner surface temperature of the NUREG/CR-6672 steellead-steel cask was 314°C compared to 310°C for the Rail-Pb cask in this study. These results show that the analyses conducted for NUREG/CR-6672 predicted shorter times to seal failure temperature than the more accurate three-dimensional analyses performed for this study. They also show that the analysis in NUREG/CR-6672 was conservative in estimating the inner wall temperature. Therefore, utilizing the results from NUREG/CR-6672 to estimate the response of the Truck-DU cask leads to a conservative estimate of time to seal failure.

From Table 6.7 in NUREG/CR-6672, the duration of fire to cause seal failure is 1.06 hours. The conservative nature of the results in 6672 imply that a longer than a 1.06-hour fire would be required to cause seal failure of the Truck-DU cask. From Section 4.2.2 of this document, the maximum duration of an engulfing fire resulting from a typical petroleum tank truck is estimated to be about one hour. Therefore, the Truck-DU cask is expected to maintain containment in highway fire accidents.

4.5 Conclusions

This chapter presents the realistic analyses of four hypothetical fire accident scenarios. These are the regulatory fire described in 10 CFR 71.73, a cask on the ground concentric with a fuel pool sufficiently large to engulf the cask, a cask on the ground with a pool fire offset by the width of a rail car (3 meters), and a cask on the ground with a pool fire offset by the length of a rail car (18 meters). These analyses are performed for the Rail-Steel and the Rail-Pb casks. Results show that neither the Rail-Steel cask nor the Rail-Pb cask would lose the containment boundary seal in any of the accidents considered in this study. In addition, the fuel rods did not reach burst rupture temperature. However, some loss of gamma shielding is expected with the Rail-Pb cask in the event of a three-hour engulfing fire and a three-hour, three-meter offset fire. Nevertheless, because containment is not lost in any of the cases studied, no release of radioactive material is expected from these hypothetical fire accidents. In addition, the Truck-DU cask is able to maintain containment if it were to be exposed to a realistically maximum truck accident fire duration of about an hour. These results demonstrate the adequacy of current regulations to ensure the safe transport of radioactive material.

CHAPTER 5

TRANSPORTATION ACCIDENTS

5.1 Types of Accidents and Incidents

The different types of accidents can interfere with routine transportation of spent nuclear fuel are:

- Minor traffic accidents ("fender-benders," flat tires), resulting in minor damage to the vehicle. These are usually called "incidents."¹¹
- Accidents which damage the vehicle and or trailer enough that the vehicle cannot move from the scene of the accident under its own power, but do not result in damage to the spent fuel cask.
- Accidents involving a death or injury, but no damage to the spent fuel cask.
- Accident in which there may be a loss of lead gamma shielding but no release of radioactive material.
- Accidents in which there is a release of radioactive material.

In this analysis the first three types are considered together, since neither type involves a release of radioactive material. In addition, the rail-canistered cask is loaded with canistered fuel, so that even in an accident there would be no release of radioactive material.

Accident risk is expressed as "dose risk:" a combination of the dose and the probability of that dose. The units used for accident risk are dose units (Sv, rem).

An accident happens at a particular spot on the route. When the accident happens, the vehicle carrying the spent fuel cask stops. Thus, there can be no more than one accident for a shipment. Accidents can result in damage to spent fuel in the cask even if no radioactive material is released. While this would not result in additional exposure of members of the public, workers unloading or otherwise opening the cask would be affected. The risk to workers opening a cask of fuel damaged in transit is not included in this study.

5.2 Accident probabilities

Risk is the product of probability and consequence of a particular accident scenario. The probability – likelihood – that a spent fuel cask will be in a particular type of accident is a combination of two factors:

The probability that the vehicle carrying the spent fuel cask will be in an accident, and

¹¹ In Department of Transportation parlance, an "accident" is an event that results in a death, an injury, or enough damage to the vehicle that it cannot move under its own power. All other events that result in non-routine transportation are "incidents." This document uses the term "accident" for both accidents and incidents.

Deleted: and cask severely

Comment [JRC76]: Sentence states cask is, and is not, damaged?

Comment [JRC77]: The fourth type does not involve a release of radioactive material either?

Comment [JRC78]: Recovery is off-topic for 5.1. If retained, move to Appendix.

• The conditional probability that the accident will be a certain type of accident. This is a conditional probability because it depends on the vehicle being in an accident.

The net accident probability is the product of the probability <u>of an accident</u> and the conditional probability <u>of a particular type of accident</u>. A few hypothetical examples are given in Table 5-1 to illustrate the probability calculation.

Accident Probability For a 3000-Mile Cross-Country Trip ^a	Accident Type	Net Probability	Conditional Probability Of Accident Type ^b
0.0165	Truck collision with a gasoline tank truck	0.000041	$\begin{array}{l} 0.82*0.003*0.0165 \\ = 0.000041 \end{array}$
0.00138	Rail/truck 50 mph collision at grade crossing	0.0000067	0.7355*0.985*0.0604*0.0113*0.00138 = 0.0000067
0.00087	Railcar falling off bridge at 30 mph	0.00017	0.7355*0.2665*0.9887*0.00087 = 0.00017

Table 5-1. Illustrations of net probability

Calculated from DOT, 2005, Table 1-32. ^bFrom event trees in Appendix V.

Accident probability is calculated from the number of accidents per mile (accident frequency) for a particular type of vehicle as recorded by the DOT and reported by the Bureau of Transportation Statistics. Large truck accidents and freight rail accidents are the two data sets used in this analysis. The accident frequency varies somewhat from state to state: the U.S. average for large trucks for the period 1991 to 2007 is 0.0032 large truck accidents per thousand miles. For rail accidents, the average is 0.0018 per thousand railcar miles (DOT, 2008). The DOT has compiled and validated national accident data for truck and rail from 1971 through 2007, but the accident rates declined so sharply between 1971 and the 1990s that, for this analysis, rates from 1991 through 2008 are used. Figure 5-1 shows the accidents per truck mile and per railcar mile for this period. The logarithmic scale is used on the vertical axis in order to show the entire range.

Comment [JRC79]: So Net = Accident * Conditional

Comment [JRC80]: Confuses. Why are the net probabilities equal to the conditional probabilities?

н В

Comment [JRC81]: Is the last factor in each

expression from the event trees?

Comment [JRC82]: Rates are through 2007 fi previous sentence is correct. Comment [JRC83]: Unclear. Why was 1971-

1991 excluded?

Comment [JRC84]: x-axis labels blur together. Too compressed vertically. Do you need 1.E-08 on Y-axis?



Figure 5-1. Accident frequencies in the U.S. from 1991 until 2007

As Chapters 3 and 4 show, however, the only accidents that could result in either the loss of radiation shielding or release of radioactive material are rail accidents involving the Rail-Pb cask. These are:

- Some collisions with hard rock or equivalent at impact speeds greater than 97 km/hour (60 mph) that result in some loss of lead gamma radiation shielding.
- · Fires of long enough duration to compromise the seals.

Whether or not these accidents happen depends on the likelihood (probability) of the accident scenario as well as on the accident frequency. The event trees for truck and rail, Figures V-1 and V-2 of Appendix V, show some of the elements of accident scenarios in each branch of the respective event tree. The dependence on probability is illustrated by Figure V-5, which shows the sequence of events needed for a pool fire that can burn long enough to compromise the seals and the lead shielding.

The sum of all conditional accident probabilities is one (100 percent).

Table 5-2. Scenarios and conditional probabilities of rail accidents involving the Rail-Pb cask

, shows the conditional probabilities of accidents that could result in a radiation dose to a member of the public and the conditional probability of an accident in which there is neither loss of lead shielding nor a release of radioactive material; that is, there is no radiation dose to anyone from the accident. The analysis that results in these conditional probabilities may be found in Appendix V, Sections V.3 to V.5. **Comment [JRC85]:** Confirm using hard rock as unyielding target.

Deleted: Table 5-2Table 5-2

Accident Scenario for the Rail-Pb Cask	Conditional probability of gamma shield loss or <u>radioactive material content</u> release exceeding 10 CFR 71.51 quantities		
Loss of lead shielding from impact	5.1 x 10 ⁻⁶		
Loss of lead shielding from fire	10^{-14} to 10^{-10}		
Radioactive materials release from impact	3.6 x 10 ⁻⁶		
Radioactive materials release from fire	10^{-14} to 10^{-10}		
No radiation dose attributable to the accident: no loss of lead shielding and no release of	0.999991		

Table 5-2. Scenarios and conditional probabilities of rail accidents involving the Rail-Pb cask

5.3 Accidents With No Attributable Radiation Dose

The conditional probability that an accident will be this type of accident, with no release and no lead shielding loss is as table 5-2 shows, 99.999 percent. The only type of cask that could lose gamma shielding is a lead shielded cask like the Rail-Pb rail cask. The only type of cask that could release radioactive material in an accident is a cask carrying uncanistered spent fuel. The Truck-DU cask would not release any radioactive material under any scenario postulated in this report. The Rail-All Steel cask carries canistered fuel and would not release any radioactive material. Neither Truck-DU casks nor Rail All-Steel casks are lead-shielded, so that shielding loss would not occur.

The doses to the public and to emergency responders from an accident in which no material is released and there is no loss of lead gamma shield are shown in Tables 5-3 and 5-4. These doses depend only on the external dose rate from the cask in the accident. The radiation dose depends on:

- The external dose rate from the cask (Table 2-1).
- A ten-hour stop (DOE, 2002) at the scene of the accident, until the vehicle and/or cask can be moved safely.
- An average distance of five meters between the cask and the first responders and others who
 remain with the cask.
- For collective doses, the average rural, urban, and suburban population densities for each route.

The radiation doses in Table 5-3, Table 5-4, and Table 5-5 are the consequences of all Truck-DU accidents, all Rail-All Steel accidents, and 99.999% of the Rail-Pb accidents.

Comment [JRC88]: Table should be expanded to include other results described in this paragraph.

Comment [JRC86]: Why is material release from fire probability identical to that for loss of shielding from fire? Combine?

Comment [JRC87]: What?

Deleted: each

Table 5-3. Dose to an emergency responder from a cask in a no-shielding loss, no-release accident

Cask	Dose in Sv	Ten-hour allowed dose in Sv
		(mrem) from 10 CFR 71.51
Truck-DU	1.0 E-03	0.10
Rail-Pb	9.2E-04	0.10
Rail-All Steel	6.9E-04	0.10

Table 5-4 and Table 5-5 show collective doses in sieverts (Sv) for the ten-hour stop that follows the accident. Doses are shown for rural, suburban, and urban segments of each route, but an accident is only going to happen at one place on any route. Each listed dose is thus the collective dose that residents on that route segment could receive if the accident happened at a spot on that <u>type of route</u> segment.

Table 5-4. Collective doses to the public from a no-shielding loss, no-release accident involving rail casks (person-Sv)

FROM TO		20 0 S 20	Rail-Pb	A STATISTICS	Rail-All Steel		
		Rural	Suburba	Urban	Rural	Suburba	Urban
MAINE	ORNL	3.1E-06	5.3E-05	6.6E-	2.3E-06	4.0E-05	5.0E-06
YANKEE	DEAF SMITH	2.3E-06	5.7E-05	6.8E-	1.7E-06	4.3E-05	5.2E-06
	HANFORD	3.7E-06	5.3E-05	6.4E-	2.8E-06	4.0E-05	4.8E-06
	SKULL	2.8E-06	5.1E-05	5.3E-	2.1E-06	3.9E-05	4.0E-06
KEWAUNE	ORNL	3.1E-06	5.7E-05	7.2E-	2.3E-06	4.3E-05	5.4E-06
E	DEAF SMITH	1.5E-06	6.1E-05	7.2E-	1.2E-06	4.6E-05	5.4E-06
	HANFORD	1.5E-06	5.3E-05	6.6E-	1.2E-06	4.0E-05	5.0E-06
	SKULL	2.0E-06	6.2E-05	6.0E-	1.5E-06	4.7E-05	4.5E-06
INDIAN	ORNL	2.6E-06	7.2E-05	8.7E-	2.0E-06	5.4E-05	6.6E-06
POINT	DEAF SMITH	1.9E-06	5.9E-05	7.5E-	1.4E-06	4.5E-05	5.7E-06
	HANFORD	1.9E-06	5.6E-05	7.2E-	1.4E-06	4.3E-05	5.5E-06
	SKULL	2.2E-06	6.0E-05	6.6E-	1.7E-06	4.6E-05	5.0E-06
IDAHO	ORNL	1.9E-06	6.0E-05	5.8E-	1.4E-06	4.6E-05	4.4E-06
NATIONAL	DEAF SMITH	8.0E-07	6.0E-05	5.3E-	6.0E-07	4.6E-05	4.0E-06
LAB	HANFORD	1.0E-06	6.0E-05	6.7E-	7.5E-07	4.6E-05	5.1E-06
	SKULL	2.0E-06	5.9E-05	7.1E-	1.5E-06	4.4E-05	5.4E-06
AVI	ERAGE	2.1E-06	5.8E-05	6.7E-	1.6E-06	4.4E-05	5.1E-06

CFR 71.51.		J
Comment	[JRC91]: No mrem values provided?)

Comment [JRC90]: Is this period specified in 10

Comment [JRC89]: Public and emergency

responders?

Deleted:	particular	
Deleted:	of the route	
Commen	t [JRC92]: Isn't th	is dose risk?

Comment [JRC93]: Original does not show exponents. May be track-changes artifact.

FROM	TO	Truck-DU				
		Rural	Suburban	Urban		
MAINE	ORNL	3.8E-06	6.6E-05	8.1E-06		
YANKEE	DEAF SMITH	2.8E-06	7.0E-05	8.4E-06		
Γ	HANFORD	4.5E-06	6.5E-05	7.9E-06		
	SKULL VALLEY	3.5E-06	6.3E-05	6.6E-06		
KEWAUNEE	ORNL	3.8E-06	7.1E-05	8.9E-06		
[DEAF SMITH	1.9E-06	7.4E-05	8.9E-06		
	HANFORD	1.9E-06	6.5E-05	8.2E-06		
	SKULL VALLEY	2.4E-06	7.6E-05	7.4E-06		
INDIAN	ORNL	3.2E-06	8.8E-05	1.1E-05		
POINT	DEAF SMITH	2.3E-06	7.3E-05	9.2E-06		
T T T T	HANFORD	2.3E-06	6.9E-05	8.9E-06		
	SKULL VALLEY	2.7E-06	7.4E-05	8.2E-06		
IDAHO	ORNL	2.4E-06	7.4E-05	7.2E-06		
NATIONAL	DEAF SMITH	9.8E-07	7.4E-05	6.6E-06		
LAB	HANFORD	1.2E-06	7.4E-05	8.3E-06		
	SKULL VALLEY	2.4E-06	7.2E-05	8.8E-06		
AV	/ERAGE	2.6E-06	7.2E-05	8.3E-06		

Table 5-5. Collective doses to the public from a no-shielding loss, no-release accident involving a truck cask (person-Sv)

The average individual U.S. background dose for ten hours is 4.1×10^{-6} Sv (0.41 mrem). Average background doses for the 16 routes analyzed are:

- Rural: 6.9 x 10⁻⁵ person-Sv
- Suburban: 1.9 x 10⁻³ person-Sv
- Urban: 0.011 person-Sv

If the Truck-DU cask, for example, is in a no-shielding loss, no-release accident, the average collective dose (the sum of the background dose and the dose due to the accident) to residents for the 10 hours following the accident would be:

- Rural: 7.2 x 10⁻⁵ person-Sv
- Suburban: 2.0 x 10⁻³ person-Sv
- Urban: 0.011 person-Sv

The <u>background and accident</u> suburban and urban collective doses would be indistinguishable from the collective background dose. Any dose to an individual is well below the doses allowed by 10 CFR 71.51, as one would expect. The total collective doses may be slightly less from Rail-Pb and Rail-All Steel casks than from a Truck-DU cask.

Comment [JRC95]: For distinguishable from 2.0?	suburban isn't 1.9
Comment [JRC96]: If no based on what?	ot analyzed, predicted

Comment [JRC94]: For ten hours?

5.4 Accidental Loss of Shielding

The details of the calculation of doses from shielding losses are provided in Appendix V, Section V.3.1 (loss of gamma shielding) and Section V.3.2 (loss of neutron shielding).

5.4.1 Loss of Lead Gamma Shielding

Type B transportation packages are designed to carry very radioactive material and need shielding in additional to that provided by the steel shell of the package. Spent nuclear fuel is extremely radioactive and requires shielding that absorbs both gamma radiation and neutrons. The sum of the external radiation doses from gamma radiation and neutrons should not exceed 0.0001 Sv (10 mrem) per hour at two meters from the cask, by regulation (10 CFR 71.4). The three cask types tested in this assessment meet this criterion.

Each spent fuel transportation cask analyzed each uses a different gamma shield. The Rail-All Steel has a stainless steel wall thick enough to attenuate gamma radiation to acceptable levels. The Truck-DU uses metallic depleted uranium (DU). Neither of these shields would be damaged or even affected by, an accident. The Rail-Pb has a lead gamma shield which can be damaged in an accident. Lead is relatively soft compared to DU or steel, and melts at a considerably lower temperature (330 °C) than either DU or steel.

In a hard impact, the lead shield will slump, and a small section of the spent fuel in the cask will be shielded only by the steel shells. Figure 5-2 and Figure 5-3 show the maximum individual radiation dose at various distances from the damaged cask, for a range of gaps, or fractions of shield lost. In the figures, the <u>dose estimates for the largest gaps are depicted on</u> the left end of the graph, and the <u>fraction of lead shield lost (gap size)</u> decreases from left to right. Figure 5-2 and Figure 5-3 show that doses larger than the external dose in 10 CFR 71.51 occur when the lead shielding gap is more than two percent of the shield.

Comment [JRC97]: Is this generalization true for all Type B packages?

Comment [JRC98]: Correct?

Comment [JRC99]: Don't you mean analyzed?

Comment [JRC100]: Don't we assume shipments will be in compliance with applicable regulations?

Comment [JRC101]: Doesn't this contradict above para? Why does the above para mention gamma and neutrons, but only gamma here? Doesn't this suggest there is a separate neutron shield?

Comment [JRC102]: Doesn't "lost" suggest the shield has been lost from the package? Would slump, compaction, or degradation be better terms?

Deleted: at

Comment [JRC103]: Why the odd collection of x-axis values? Why 0.0164 and 0.0170? Why is there no change from 0.0164 and 0.0234? What do we learn past 0.0013? Why does Fig 5-3 use scientific notation, but Fig 5-2 does not? Why does the distance order of the colors change (other than dark blue)?

Comment [JRC104]: It does not appear that any dose in figure 5-3 exceeds 10 mSv/h

Comment [JRC105]: This is a dose rate – you are comparing to dose? Over what time period?



Figure 5-2. Radiation dose to the maximally exposed individual (MEI) from loss of lead gamma shielding at distances from one to five meters from the cask carrying spent fuel. The horizontal axis represents the fraction of shielding lost-the shielding gap—and is not to scale.



Figure 5-3. Radiation dose to the maximally exposed individual from loss of lead gamma shielding at distances from 20 to 100 meters from the cask carrying spent fuel. The vertical axis is logarithmic, so that all of the doses can be shown on the same graph. The horizontal axis represents the fraction of shielding lost-the shielding gap—and is not to scale.

Doses that are larger than the 10 CFR 71.51 accident doses pose a greater risk than the doses from routine transportation (Chapter 2) or those from an accident in which there is neither a release nor loss of shielding (Section 5.3 of this chapter). The probability of an accident resulting in these doses is a significant component of the risk. Table 5-2 shows that the probability of an impact accident causing loss of lead shielding is five per million (5×10^{-6}), or one in 200,000 accidents. The probability that the dose from that accident will be larger than allowed by 10 CFR 71.51 is less: about three per hundred million (3×10^{-8}) because the dose resulting from most accidents is less than the limit in 10 CFR 51.71.

One of every 200,000 accidents could be an impact accident that causes loss of lead shielding; the "one in 200,000" is a conditional probability, conditional on an accident happening. The total probability of such an accident includes both this conditional probability and the probability that there will be an accident. The probability of an accident is shown in the right-hand column of

Table 5-6. Average railcar accident frequencies and accidents on the routes studied

, For example, the probability that an accident resulting in lead shielding loss will happen on the route from Indian Point Nuclear Plant to Hanford is:

$(5 \times 10^{-6})^*(0.00178) = 8.9 \times 10^{-9}$

or about one in 100 million per Main Yankee to Hanford shipment. The probability that the lead shielding loss is large enough to deliver an acute dose is:

$$(3 \times 10^{-8})(0.00178) = 5.34 \times 10^{-11}$$

or about one in 10 billion per Main Yankee to Hanford shipment.

These very small probabilities <u>indicate</u> that such severe accidents, which are more traumatic to the cask than the tests shown in Figure 1-1, are not likely to happen. The conditions which can cause enough loss of lead shielding to challenge human health are extreme conditions.

Comment [JRC106]: This specifies postaccident test dose rate acceptance criterion.

Comment [JRC107]: Obviously. What is the point here?

Comment [JRC108]: Where does this come

Comment [JRC109]: Did you mean 71.51?

Deleted: ¶ Table 5-6Table 5-6

Yankee, not Indian Point

Comment [JRC111]: Why introduce this new

Comment [JRC110]: Isn't his value for Maine

term here? What do you mean by it? Earlier on this page you meant greater than 71.51 (which refers to a dose rate, not a dose)?

Deleted: reflect the conclusion

Comment [JRC112]: A vague, and perhaps misleading, term?

ORIGIN	DESTINATION	AVERAGE ACCIDENTS PER KM	AVERAGE
MAINE	ORNL	6.5 x 10 ⁻⁷	0.00328
YANKEE	DEAF SMITH	5.8 x 10 ⁻⁷	0.00195
	HANFORD	4.2 x 10 ⁻⁷	0.00178
	SKULL VALLEY	5.1 x 10 ⁻⁷	0.00108
KEWAUNEE	ORNL	4.3 x 10 ⁻⁷	0.00328
	DEAF SMITH	3.3 x 10 ⁻⁷	0.00130
	HANFORD	2.4 x 10 ⁻⁷	0.00062
lien milili . dallanini mili	SKULL VALLEY	3.7 x 10 ⁻⁷	0.00066
INDIAN	ORNL	8.8 x 10 ⁻⁶	0.00052
POINT	DEAF SMITH	6.2 x 10 ⁻⁷	0.04206
	HANFORD	5.1 x 10 ⁻⁷	0.00190
	SKULL VALLEY	5.5 x 10 ⁻⁷	0.00203
INL	ORNL	3.6 x 10 ⁻⁷	0.00069
	DEAF SMITH	3.5 x 10 ⁻⁷	0.00038
	HANFORD	3.2 x 10 ⁻⁷	0.00067
	SKULL VALLEY	2.8 x 10 ⁻⁷	0.00015

Table 5-6. Average railcar accident frequencies and accidents on the routes studied

The overall collective dose risks to the resident population from a lead shielding loss accident on the sixteen routes studied, are shown in Table 5-7. These include some accidents whose resultant dose rates would be within regulatory limits. The expected dose to any member of the populations along the routes, at least 10 m. from the cask, is within the limits of 10 CFR 71.51. The Indian Point-to-ORNL collective dose risk is comparatively large, because the suburban and urban populations along this route are about 20 percent larger than along the other routes and the rail accident rate per km is an order of magnitude larger

Table 5-7. Collective dose risks in person-Sv for a loss of lead shielding accident

SHIPMENT ORIGIN	ORNL	DEAF SMITH	HANFORD	SKULL VALLEY
MAINE YANKEE	4.4E-10	2.7E-10	2.4E-10	1.4E-10
KEWAUNEE	1.9E-10	9.1E-11	8.6E-11	7.7E-11
INDIAN POINT	7.4E-09	2.8E-10	2.8E-10	1.0E-10
IDAHO NATIONAL LAB	5.6E-11	9.5E-11	2.1E-11	1.3E-10

The conditional probability that lead shielding will be lost in a fire involving the cask is about 10^{-19} . The conditional probability is so small because the following has to happen before a fire is

Comment [JRC115]: Do you mean lost from the package, or melted and redistributed within the package?

Comment [JRC114]: Following sentence

suggests all?

Deleted: that are

close enough to the cask, and hot enough, and burns long enough, to do any damage to the lead shield.

- The train must be in an accident that results in a major derailment
- The train carrying the spent fuel cask must also be carrying at least one tank car of flammable material.
- The derailment must result in a pileup. Railcars carrying spent fuel casks are always located between buffer cars and never located next to a railcar carrying hazardous or flammable material.
- The flammable material must leak out so that it can ignite.
- The pileup must be such that the resulting fire is no further from the cask than a railcar length.

If there is no pileup and if the cask is more that a railcar length from the fire, although still close enough that the lead shield could be damaged, the probability is increased to about 10^{-10} —about one in ten billion.

The event trees and probabilities for fire accident are discussed in detail in Appendix V.

5.4.2 Neutron shielding

The type of fuel which can be transported in the three casks considered has relatively low neutron emission but does require neutron shielding. This usually a hydrocarbon or carbohydrate polymer of some type that often contains a boron compound. All three of the casks studied have polymer neutron shields. Table 5-8 shows the neutron doses to individuals who are about five meters from a fire-damaged cask for ten hours. The dose allowed by 10 CFR 71.51 is provided for comparison.

Impacts, even those that cause breaches in the seals, will not damage the neutron shield significantly. However, the neutron shielding on any of the three casks is flammable and could be destroyed in a fire.

Table 5-8. Doses	to an	emergency	responde	r or	other	individual	five meters	s from
the cask								

Cask	Dose in Sv	Ten-hour allowed dose in Sv from 10 CFR 71.51
Truck-DU	0.0073	1.00
Rail-Pb	0.0076	1.00
Rail-All	0.0076	1.00

The neutron doses do not exceed the dose cited in the regulation following an accident, so the loss of neutron shield is not included in the overall risk assessment. Essentially, these are not extra-regulatory accidents.. The conditional probability of this neutron dose is 0.0063 for a truck

Comment [JRC116]: Doesn't this mean the probability that lead shielding will be lost is 9 orders of magnitude greater than stated above?

Deleted: (borax is a good neutron absorber) Deleted: Water is an excellent neutron absorber, but is no longer used.

Comment [RPDC117]: Why just one distance for neutron shield degradation, whereas many more shown for gamma?

Comment [RPDC119]: Why no net probability

Comment [RPDC118]: 100 rem?

for shipment routes like that shown for gamma above?

fire accident and 0.0000001 for a rail fire_accident. The rail fire is less probable because of the series of events needed to produce a rail fire. Details are discussed in Appendix V Section V.3.2.

5.5 Accidental Release of Radioactive Materials

Radioactive materials released into the environment are dispersed in the air, and some deposit on the ground. If a spent fuel cask is in a severe enough accident, spent fuel rods can tear or be otherwise damaged, releasing fission products and very small particles of spent fuel into the cask. If the cask seals are damaged, these radioactive substances can be swept from the interior of the cask through the seals into the environment. Release to the environment requires that the accident be severe enough to damage the fuel rods and release the pressure in the rods, or there will be no positive pressure to sweep material from the cask to the environment.

The potential accidents that could result in such a release are discussed in Chapters 3 and 4. This chapter discusses the probability of such accidents and the consequences of releasing these radionuclides.

5.5.1 Spent fuel inventory

Spent nuclear fuel contains a great many different radionuclides. The amount of each fission product nuclide in the spent fuel depends on the type of reactor fuel and how much ²³⁵U was in the fuel (the enrichment) when it was loaded into the reactor. The amount of each fission product in the spent fuel also depends on how much nuclear fission has taken place in the reactor (the burnup). Finally, the amount of each radionuclide in the spent fuel depends on the time that has passed between removal of the fuel from the reactor and transportation in a cask (the cooling time) because the fission products undergo radioactive decay during this time. Plutonium, americium, curium, thorium, and other actinides produced in the reactor decay to a sequence of radioactive elements which are the progeny of the actinide. These progeny increase in concentration as the original actinide decays. However, there is never more radioactive material as a result of decay than there was initially; mass and energy are conserved.

The fuel studied in this analysis is pressurized water reactor (PWR) fuel that has "burned" 45,000 megawatt-days per metric ton of uranium (MWD/MTU) and has been cooled for nine years. The Rail-Pb cask, the only cask studied that could release radioactive material in an accident, is certified to carry more than 20 PWR assemblies. In this study, the Rail-Pb cask was loaded with 26 PWR assemblies.

The spent fuel inventory for accident analysis was selected by normalizing the radionuclide concentrations in the spent fuel by radiotoxicity. The resulting inventory is shown in Table 5-9.

Comment [RPDC120]: What is the relationship between the fire accidents that cause gamma shield failure and those that cause lead shield failure? Not clear how this has been treated.

Comment [RPDC121]: But moat importantly, the damage must be severe enough to fail the closure bolts an dislodge the lid. Further, for the analyzed casks with canisters, eve n the huge forces required to cause that degree of closure system failure do not result in release because the canister does not fail. Where is the focus on these results?

Comment [RPDC122]: See comment above – an oblique reference at best; reading this Chapter alone, I have no idea why this is true.

Raulonuchue	IDY				
例。例:###################################	26 Assemblies				
²⁴⁰ Pu	7.82E+03				
²³⁹ Pu	1.84E+02				
¹³⁷ Cs	4.38E+04				
²³⁸ Pu	7.18E+01				
²⁴³ Cm	2.50E+01				
⁶⁰ Co	5.56E+01				
¹⁵⁴ Eu	9.01E+02				
¹³⁴ Cs	4.03E+02				
⁸⁵ Kr	2.26E+03				
²⁴¹ Am	1.58E-01				
²⁴² Cm	1.00E+00				
¹⁵⁵ Eu	2.63E+02				
²³¹ Pa	3.12E-02				
¹⁰⁶ Ru	7.50E+00				
²³⁶ U	1.92E-01				
²³³ U	8.99E+02				
²⁴¹ Pu	5.75E-01				
113mCd	6 13E 01				

Table 5-9. Radionuclide inventory for accident analysis of the Rail-Pb cask (TBq)

Dedionuelide

The 60 Co inventory listed is not part of the nuclear fuel. It is the main constituent of a corrosion product that accumulates on the outside of the rods, and is formed by corrosion of hardware in the fuel pool. It is listed here with the inventory because it is released to the environment under the same conditions that spent fuel particles are released.

5.5.2 Conditional probabilities and release fractions

Seven accident scenarios, described in Chapter 3, <u>could</u> result in releases of material to the environment. The details of these scenarios that are important to calculating the resulting doses are shown in Table 5-10. A detailed description of the movement of radionuclide particles from fuel rods to the cask interior and from the cask interior to the environment is found in Appendix V Sections V.5.4.1 and V.5.4.2.

Comment [RPDC123]: I think you identify this as CRUD elsewhere,

	Deleted: can
The second secon	Comment [RPDC124]: For shipments using the Rail Steel-Lead cask?
-	Deleted: r

	Cask Orientation Impact Speed (kph)	End 193	Corne r 193	Side 193	Side 193	Side 145	Side 145	Corner 145
	Seal	metal	metal	elastome r	metal	elastome r	metal	metal
Cask to	Gas	0.800	0.800	0.800	0.800	0.800	0.800	0.800
Environme	Particles	0.70	0.70	0.70	0.70	0.70	0.70	0.64
nt Release	Volatiles	0.50	0.50	0.50	0.50	0.50	0.50	0.45
Fraction	Crud	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Rod to	Gas	0.005	0.005	0.005	0.005	0.005	0.005	0.005
Cask Release	Particles	4.80E-06	4.80E- 06	4.80E-06	4.80E- 06	4.80E-06	4.80 E-06	2.40E-06
Fraction	Volatiles	3.00E-05	3.00E- 05	3.00E-05	3.00E- 05	3.00E-05	3.00 E-05	1.50E-05
	Crud	1.00	1.00	1.00	1.00	1.00	1.00	1.00
	Conditional Probability	2.68E-08	1.61E- 07	8.02E-08	8.02E- 08	8.02E-08	8.02 E-08	3.06E-06

Table 5-10. Parameters for determining release functions for the accidents that would result in release of radioactive material

Comment [RPDC125]: Minimum cask impact speed into hard, massive (rigid, unyielding) object required to result in release?

Comment [RPDC126]: No description of equivalent velocity?

Comment [RPDC127]: I like seeing the net probability results for shipment routes as well.

5.5.3 Dispersion

When material is swept from the cask and released into the environment, it is dispersed by wind and weather. The dispersion is modeled using the accident model in RADTRAN 6, which is a Gaussian dispersion model. The release would be at about 1.5 meters above ground level, since the cask is sitting on a railcar. The gas sweeping from the cask is warmer than ambient, so that release is elevated, The maximum air concentration and ground deposition are 21 m downwind from the release. The dispersion was modeled using neutral weather conditions (Pasquill stability D, wind speed 4.7 m/sec). It was repeated using very stable meteorology (Pasquill stability F, wind speed 0.5 m/sec) but the difference was negligible, because of the relatively low elevation of the release. The maximally exposed individual would be located directly downwind from the accident, 21 meters from the cask.

Figure 5-4 shows air and ground concentrations of released material as a function of downwind distance. These concentrations are along the plume centerline and are the maximum concentrations in the plume. The figure shows the exponential decrease of airborne concentrations as the downwind distance increases. The ground (deposited) concentration also decreases in the downwind direction.

19 A.

Deleted: and t

Comment [RPDC128]: Why the odd x-axis values?



a. Airborne concentration of radioactive material released from the cask in an accident.



b. Concentration of radioactive material deposited after release from the cask in an accident.

Figure 5-4. Air and ground concentrations of radioactive material following a release

Deleted: n

5.5.4. Consequences and Risks from Accidents Involving Release of Radioactive Material

The dose from each of the accidents that would involve a release is shown in Table 5-11.

Table 5-11. Doses (consequences) in Sv	to the maximally	exposed individual from	1 accidents
that involve a release		···	

Cask Orientatio n	Impac t Speed (kph)	Dose from No- release, No- shielding- loss Accident	Inhalatio n	Resus- pension	Cloud- shine	Ground- shine	Total
End	193	0.001	1.59	0.0137	0.0001	0.0009	1.60
Corner	193	0.001	1.59	0.0137	0.0001	0.0009	1.60
Side	193	0.001	1.59	0.0137	0.0001	0.0009	1.60
Side	193	0.001	1.59	0.0137	0.0001	0.0009	1.60
Side	145	0.001	1.58	0.0137	4.53E-06	3.61E-05	1.59
Side	145	0.001	1.59	0.0137	8.78E-05	9.42E-04	1.60
Corner	145	0.001	0.7270	0.0063	0.0001	0.0009	0.7340

Comment [RPDC129]: Why is this here?

The doses listed in Table 5-11 are consequences, not risks. The dose to the maximally exposed individual is not the sum of the doses. Each cask orientation is a different accident scenario and results in a different set of inhalation and external doses. These are significant doses, but they are not acute, and none would result in either acute illness or death (Shleien et al., 1998, p. 15-3). The inhalation and groundshine doses are listed separately because they have different

physiological effects. External doses are exactly that, and the receptor would <u>receive</u> a dose only as long as he or she is exposed to the deposited or airborne material. If people near the accident are evacuated, and evacuation can take as much as a day, then they only receive an external dose for a day.

Inhaled radioactive particles lodge in the body and are eliminated slowly through physiological processes that depend on the chemical form of the radionuclide. The inhaled dose is called a "committed" dose, because the exposure is for as long as the radionuclide is in the body, though the activity of the nuclide decreases exponentially as it decays. The NRC uses the total effective dose equivalent, the sum of the inhalation and external doses, as a measure.

A pool fire co-located with the cask and burning for a long enough time, could damage the seals severely. However, as has already been mentioned, and is discussed in detail in Appendix V Section V.3.1.2, the condictional probability of the series of events required to produce such a fire scenario is about 10^{-19} . Even a fire offset from the cask but close enough to damage lead shielding has a conditional probability of between 10^{-14} and 10^{-10} .

The total dose risk from the universe of release accidents is shown in Table 5-12.



Comment [RPDC131]: Something cut off here?

Fable 5-12. Total collective dose risk	(person-Sv) for release accidents	for each route
---	------------	-------------------------	----------------

	ORNL	DEAF SMITH	HANFORD	VALLEY
MAINE YANKEE	2.3E-10	1.4E-10	1.2E-10	6.1E-11
KEWAUNEE	9.8E-11	4.7E-11	4.6E-11	3.3E-11
INDIAN POINT	3.9E-09	1.5E-10	1.5E-10	4.9E-11
IDAHO NATIONAL LAB	1.9E-05	7.6E-07	8.6E-10	2.6E-08

Comment [RPDC132]: So these dose risks are per shipment? Can't tell which is origination and which is destination?

Comment [RPDC133]: Why so high?

Comment [RPDC134]: What cancer risks?

These dose risks and cancer risks are negligible by any standard.

The total dose risks from loss-of-lead shielding accidents is shown in Table 5-13, and the sum of the two is shown in Table 5-14.

Table 5-13. Total collective d	ose risk (person-Sv) for	r each route from a	loss of shielding
accident			

	ORNL	DEAF SMITH	HANFORD	SKULL VALLEY
MAINE YANKEE	4.4E-10	2.7E-10	2.4E-10	1.4E-10
KEWAUNEE	1.9E-10	9.1E-11	8.6E-11	7.7E-11
INDIAN POINT	7.4E-09	2.8E-10	2.8E-10	1.0E-10
IDAHO NATIONAL LAB	5.6E-11	9.5E-11	2.1E-11	1.3E-10

Table 5-14. Total collective dose risk (person-Sv) from release and loss of shielding accidents

	ORNL	DEAF SMITH	HANFORD	SKULL VALLEY
MAINE YANKEE	6.7E-10	4.1E-10	3.6E-10	2.0E-10
KEWAUNEE	2.9E-10	1.4E-10	1.3E-10	1.1E-10
INDIAN POINT	1.1E-08	4.3E-10	4.4E-10	1.5E-10
IDAHO NATIONAL LAB	1.9E-05	7.6E-07	8.8E-10	2.6E-08

Table 5-15 shows the total collective dose risk for an accident where there is neither loss of lead shielding nor a release;

at the second	ORNL	DEAF SMITH	HANFORD	SKULL VALLEY
MAINE YANKEE	2.07E-07	1.29E-07	1.12E-07	6.42E-08
KEWAUNEE	2.22E-07	9.00E-08	3.80E-08	4.62E-08
INDIAN POINT	4.31E-08	2.88E-06	1.24E-07	1.40E-07
IDAHO NATIONAL LAB	4.71E-08	2.52E-08	4.56E-08	1.02E-08

Table 5-15. Total collective dose risk (person-Sv) from no-release, no-loss of shielding accidents

Table 5-16 shows the collective accident risk for the 16 routes from loss of neutron shielding

Table 5-16.	Total	collective dose	risk (n	erson-Sv)	from los	s of neu	tron shielding
1 4010 5-10.	A OLAI	concente dose	I ION (P	ci son orj	11 0111 103	o or neu	er on smerung

	ORNL	DEAF SMITH	HANFORD	SKULL VALLEY
MAINE YANKEE	5.2E-09	3.5E-09	3.6E-09	1.5E-09
KEWAUNEE	3.3E-09	1.9E-09	2.2E-09	1.1E-09
INDIAN POINT	4.5E-09	2.9E-09	3.2E-09	1.1E-09
IDAHO NATIONAL LAB	7.6E-10	1.9E-09	2.4E-10	2.9E-09

Table 5-17 shows the collective dose risk for the 16 routes for all accidents, for the Rail-Pb cask.
Of the three casks in this study, only the Rail-Pb <u>cask could result in a release</u> in each kind of accident considered.

Deleted: is damaged

Table 5-17. Total collective dose risk (person-S	Sv)	from al	l accidents
--	-----	---------	-------------

	ORNL	DEAF SMITH	HANFORD	SKULL VALLEY 6.6E-08
MAINE YANKEE	2.1E-07	1.3E-07	1.2E-07	
KEWAUNEE	2.3E-07	9.2E-08	4.0E-08	4.7E-08
INDIAN POINT	5.9E-08	2.9E-06	1.3E-07	1.4E-07
IDAHO NATIONAL LAB	1.9E-05	7.9E-07	4.7E-08	3.9E-08

5.6 Conclusions

The conclusions that can be drawn from the risk assessment presented in this chapter, keeping in mind that these apply to the three types of casks studied are:

- The sixteen routes selected for study are an adequate representation of U.S. routes for spent nuclear fuel, and there was relatively little variation in the risks per km over these routes.
- The overall collective dose risks are vanishingly small.
- The collective dose risks for the two types of extra-regulatory accidents, accidents involving a release of radioactive material and loss of lead shielding accidents, are negligible compared to the risk from a no-release, no-loss of shielding accident. There is no expectation of any release from spent fuel shipped in inner welded canisters from any impact or fire accident analyzed.
- The collective dose risk from loss of lead shielding is comparable to the collective dose risk from a release, though both are very small. The doses and collective dose risks from loss of lead shielding are larger than were calculated in NUREG/CR-6672 as a result of better precision in the finite element modeling and a more accurate model of the dose from a gap in the lead shield.
- The conditional risk of either a release or loss of shielding from a fire is negligible.
- The consequences (doses) of some releases and some loss of shielding scenarios are larger than cited in the regulation of 10 CFR 71.51, and are significant, but are neither acute nor lethal.
- These results are not unexpected.

Deleted:

Comment [RPDC135]: .. are in agreement with

previous studies'

CHAPTER 6

OBSERVATIONS AND CONCLUSIONS

The present document is an assessment (or evaluation) of the risks of transporting spent nuclear fuel, <u>updating that found in</u> NUREG-0170, the 1977 Final Environmental Statement on the Transportation of Radioactive Material by Air and Other Modes. Both NUREG-0170 and this document provide a technical basis for the regulations of 10 CFR Part 71.

Regulations and regulatoy compliance analysesare different from risk assessment, A regulation must be conservative, because its purpose is to ensure safety, and 10 CFR Part 71, which regulates transportation, requires a conservative estimate (i.e., over-estimate) of the damage to a cask in an accident and the radiation emitted from the cask during routine transportation. The original technical basis for 10 CFR Part 71, NUREG-0170, was also conservative, but for a different reason: only limited data were available to perform the required assessment, so NUREG-0170 deliberately used conservative parameter estimates. The NRC's conclusion was that NUREG-0170 showed transportation of radioactive materials to be safe enough, even with conservative assumptions, to support the regulation.

However, assessments are not regulations; they serve a different purpose. An assessment should be as realistic as possible so as to provide information needed to confirm, or to revise, regulations. Realistic assessment depends on the data availability and accurate and precise modeling techniques that have become increasingly available in the years since 1977. Consequently, the Modal Study and NUREG/CR-6672 made good progress in assessing transportation risks more realistically. As a result, both the calculated consequences and risks of radioactive materials transportation decreased. The decrease in risk means that the regulations provide a greater level of safety than previously recognized.

The present study is closer to a "real world" analysis than the previous analyses. Certified spent fuel cask types are analyzed, rather than generic designs. Recent (2005 or later) accident frequency data and population data are used in the analyses, and the modeling techniques have been upgraded as well. This study, the Spent Fuel Transportation Risk Assessment, is another step in building a complete picture of spent nuclear fuel transportation <u>safety</u>, and an addition to the technical basis for 10 CFR Part 71. The results of this study are compared with preceding risk assessments in the figures that follow.

6.1 Routine Transportation

Figure 6-1 and Figure 6-2 show results of routine truck and rail transportation of a single shipment of spent nuclear fuel; Figure 6-1 plots average collective radiation dose (person-Sv) from truck transportation and Figure 6-2 from rail transportation. These average doses include the doses to the population along the route, doses to occupants of vehicles sharing the route, doses at stops, and doses to vehicle crew.

Collective doses from routine transportation depend directly on the population along the route and the number of other vehicles that share the route, and inversely on the vehicle speed. Doses to occupants of vehicles that share the route depend inversely on the square of the vehicle speed. Deleted: is Deleted: , and the technical basis for a regulation

Deleted: . It is also an update to

s not the regulation itself

Deleted: the risks of

Deleted: and evaluation
Deleted: and

 Deleted: Figure 6-1

 Deleted: Figure 6-2

 Deleted: Figure 6-1

 Deleted: Figure 6-2

As Figure 6-1 shows, the doses in this study from routine transportation are about 35 percent of the analogous collective doses in NUREG/CR-6672 and about 10% of the analogous NUREG-0170 results. When the doses in the truck analysis are normalized to the population, vehicle density, and vehicle speed used in the NUREG/CR-6672 analysis, the collective doses are about seven percent of the NUREG/CR-6672 doses.



Figure 6-1. Collective doses (person-Sv) from routine truck transportation

The NUREG-0170 results for truck transportation were based on a single long route, constant values of rural, suburban, and urban population densities, on different and conservative vehicle speeds on rural, urban, and suburban roads, on a fixed rate of vehicle stops, and on 1975 estimates of vehicle density (vehicles per hour), all of which led to conservative results.

NUREG/CR-6672 <u>used more realistic</u> distributed route lengths, population densities, vehicle occupancy and density, vehicle dose rate and stop time and used the means of the distributions as parameters. As the figure shows, the conservatism was decreased by over a factor of three.

The collective average dose in the present study might have been larger than the NUREG/CR-6672 result, because <u>present</u> populations are generally larger, particularly along rural routes, and the vehicle densities are much larger (see Chapter 2). These increases were offset by the considerably <u>greater</u> vehicle speeds used in the present study. The difference made by

normalizing to the NUREG/CR-6672 input parameter values demonstrates that the collective dose depends on the number of people exposed, not on the dose <u>rate</u> to which they are exposed. The population exposed to the transportation cask is also exposed to background radiation. Thus, even in comparisons, collective dose is an artificial construct with limited relevance to an assessment of radiological effects.

Figure 6-2, shows a more predictable difference between the present study's results and NUREG/CR-6672. This difference reflects primarily the increase in population density along the rail routes. Doses to rail crew are considerably larger because crew are exposed during travel

Comment [JRC136]: What is the (shipment?)

Comment [JRC137]: Spelled out earlier in this

basis for the comparison

Deleted: Figure 6-1

Deleted: the Deleted: larger Comment [JRC138]: to a greater degree than? Comment [JRC139]: Both sentences appear true, but does the first cause the second?

Comment [JRC140]: What is it?

Comment [JRC141]: What is the basis for normalization – same as for truck above?

Deleted: Figure 6-2

Comment [JRC142]: Larger than what? What value in Figure 6-2 are you referring to? If rail-pb, 10% is considerably larger? All other results smaller?

If Figure 6-3, doses are smaller, not larger?



over the entire route (although this involves different individuals) Crew doses, including railyard worker doses, are shown in Figure 6-3,



Figure 6-2. Collective doses (person-Sv) from routine rail transportation



Figure 6-3. Collective dose (person-sv) to train and railyard crew in routine transportation

The difference in dose between the Rail-Pb cask and the Rail-Steel cask occurs because the latter cask has a smaller TI (Chapter 2). The differences in crew doses between the studies reflect the considerable difference between the methods used in the different studies.

The differences in the collective doses from routine transportation between the cited studies are not the result of differences in external radiation from the spent fuel casks. The 1975 version of 10 CFR Part 71¹² specified the same limit on external radiation (the transport index) as Part 71 specifies today. The differences in results are due primarily to the following factors:

- Differences in vehicle speed. The faster the cask moves past a receptor, the less that receptor is exposed. NUREG-0170 and NUREG/CR 6672 used 80 kph for all truck routes and 64 kph on rural rail routes, 40 kph on suburban rail routes, and 24 kph on urban rail routes. The truck speeds used in this study are 108 kph on rural routes, 102 kph on suburban routes, and 97 kph on urban routes and the rail speed is 40 kph on all <u>routes</u>.
- Differences in populations along the routes. NUREG-0170 used six persons per km² for rural populations, 719 per km² for suburban routes, and 3861 per km² for urban routes. NUREG/CR-6672 used 1990 census data provided by the code WebTRAGIS and used the mean values of Gaussian distributions of population densities on 200 routes in the United States. This study uses 2000 census data, updated to 2009, for the rural, suburban, and urban truck and rail route segments in each state traversed in each of the sixteen routes <u>studied</u>. The variation from the NUREG-0170 values is considerable.
- Differences in vehicles per hour on highways. NUREG-0170 and NUREG/CR-6672 both used the 1975 values of 470 vehicles per hour on rural routes, 780, on suburban routes, and

Deleted: defines

Comment [JRC144]: Are you explaining why previous results are greater or present results are lower? It matters.

Deleted: defines

Comment [JRC145]: Justify the change, e.g., believed to be more accurate.

Deleted: routes

Deleted: studies

Comment [JRC146]: What is it? Didn't the populations increase? How does that explain a decrease in the collective dose estimates?

Comment [JRC147]: So why doesn't this difference lead to increased doses in the present study?

¹² A copy is provided in NUREG-0170.
2800 on urban routes. This study used 2002 state vehicle density data for each state traversed. The national average vehicle density is 1119 vehicles per hour on rural routes, 2464, on suburban routes, and 5384, on urban routes.

• Differences in calculating doses to rail crew. NUREG-0170 calculated doses to rail and railyard crew by estimating the distance between the container carrying radioactive material and the crew member. NUREG/CR-6672 used the Wooden (1980) calculation of doses to railyard workers, and did not calculate a dose to the crew on the train. This study calculated all doses using the formulations in RADTRAN 6.

Dose to the maximally exposed individual is a better indication of the radiological effect of routine transportation than collective dose. The dose to the maximally exposed individual is shown in Figure 6-4 for NUREG-0170 and for the three cask types of this study. NUREG/CR-6672 did not calculate this dose for routine transportation.

Comment [JRC148]: Again, so why doesn't this difference lead to increased doses in the present study?

Comment [JRC149]: What is the (shipment?) basis for the comparison? Deleted: Figure 6-4



Figure 6-4. Maximum individual dose (Sv) from routine transportation.

6.2 Transportation Accidents

Radiological accident risk is expressed in units of "dose risk" that include the probability of an accident and the conditional probability of certain types of accidents. The units used are dose units (Sv) because probability is a unitless number. NUREG-0170, NUREG/CR-6672, and this study all used the version of RADTRAN the available at the time of the study to calculate dose risk, but the input parameters differed widely. In addition, improvements in RADTRAN and in other modeling codes described in earlier chapters resulted in a more accurate analysis of cask behavior in an accident.

Deleted: in a	
Deleted: currently	
Deleted: version	

120

The results shown in Figure 6-5 for this study are averages over the 16 routes studied. As was discussed in Chapters 3, 4, and 5, a lead-shielded rail cask, the Rail-Pb cask in this study, is the only cask type of the three studied that can either release radioactive material or can lose lead gamma shielding in a traffic accident.



Comment [JRC150]: This is needed for other figures. Deleted: Figure 6-5 Deleted: in a traffic accident Comment [JRC151]: Does this term apply to rail accidents?

Figure 6-5. Accident collective dose risks

Unlike the results for routine transportation, the results shown in Figure 6-5 depend on different amounts of radioactive material released and different amounts of lead shielding lost. NUREG-0170 used a scheme of eight different accident scenarios, four of which postulated release of the entire releasable contents of the cask, two of which postulated no release, one postulated a ten percent release, and one, a one percent release. The range of conditional probabilities was from 1×10^{-5} for the most severe (100 percent release) accident to 80 percent for the two no-release

accident scenarios. The NUREG-0170 "universe" of accidents and their consequences was based primarily on engineering judgment and was clearly conservative.

NUREG/CR-6672 analyzed the structural and thermal behavior of four generic cask designs – two truck and two rail casks—in great detail, and analyzed the behavior of the five groups that best describe the physical and chemical nature of the radioactive materials potentially released from the spent fuel through the casks. These five groups are particulate matter, semi-volatile substances, ruthenium, gas, and Chalk River Unidentified Deposits (CRUD). The spent fuels considered were high burnup and low burnup PWR and BWR fuel. This analysis resulted in 19

121

truck accident scenarios and 21 rail accident scenarios, each with an attendant possibility, including a no-release scenario with better than 99.99 percent probability.

The present study followed the analytical outline of the NUREG/CR 6672 analysis, but analyzed the structural and thermal behavior of a certified lead-shielded cask design loaded with fuel that the cask is certified to transport. Instead of the 19 truck scenarios and 21 rail scenarios that included potential releases of radioactive material, the current study resulted in only seven rail scenarios that included releases, as described in Chapters 3 and 5. The only parts of the cask structure that could be damaged enough to allow a release are the seals. Release could take place through the seals only if the seals fail and if the cask is carrying uncanistered fuel. No potential truck accident scenario resulted in seal failure, nor did any fire scenario. In the present study, only the Rail-Pb cask design met criteria necessary for a release. A comparison of the collective dose risks from potential releases in this study to both NUREG-0170 and NUREG/CR-6672, is appropriate, since the latter two studies considered only potential releases. The collective dose risks decrease with each succeeding study as expected, since the overall conditional probability of release and the quantity of material potentially released decreases with each successive study.

The collective dose risk from a release depends on dispersion of the released material, which then either remains suspended in the air, producing cloudshine, or is deposited on the ground, producing groundshine, or is inhaled. All three studies used the same basic Gaussian dispersion model in RADTRAN, although the RADTRAN 6 model is much more flexible than the previous versions and can model elevated releases. NUREG-0170 calculated only doses from inhaled and resuspended material. NUREG/CR-6672 included groundshine and cloudshine as well as inhaled material, but overestimated the dose from inhaled resuspended material. The combination of improved assessment of cask damage and improved dispersion modeling has resulted in the decrease in collective dose risk from releases shown in Figure 6-5.

Frequently, <u>public interest in the transportation of spent fuel focuses on the consequences of</u> <u>possible accidents (without regard to their likelihood)</u>. The average <u>estimated consequences</u> (collective doses) from potential accidents involving release for the present study is 2 person-Sv. This is consequence is orders of magnitude less than the 110 person-Sv in NUREG-0170 and 9000 person-Sv estimated from Figure 8.27 in NUREG/CR-6672,

NUREG-0170 did not consider loss of <u>spent fuel cask</u> lead shielding, which can <u>result in a</u> <u>significant</u> increase the dose from gamma radiation <u>being emitted by the cask contents</u>. NUREG/CR-6672 analyzed 10 accident scenarios in which the lead gamma shield could be compromised and calculated a fractional shield loss for each. An accident dose risk was calculated for each potential fractional shield loss. The present study followed the same general calculation scheme, but with a more sophisticated model of gamma radiation from the damaged shield and with 18 potential accident scenarios instead of 10. Much of the difference between the NUREG/CR-6672 dose risks from shield loss and this study is the inclusion of accident scenarios that have a higher conditional probability than any such scenarios in NUREG/CR-6672. The consequence of loss of lead shielding estimated in NUREG/CR-6672 Table 8.13 is 41,200 person-Sv, about 100 times the 690 person-Sv estimated in this study. Lead shield loss clearly affects only casks that have a lead gamma shield; casks using DU or thicker steel shielding would not be affected. Comment [JRC152]: response to accident conditions resulted in?

Deleted: and the overall conditional probability of release

Deleted: p	eople who are concerned about
Deleted: v	vant to know about
Deleted: i	nstead of risk
Deleted: .	
Deleted: a	bout
Deleted: a	ibout
Deleted: a person-Sv e	re orders of magnitude larger than the 2 stimated from release in the current study
Deleted: g	zamma
Deleted:	significantly

More than 99.999 percent of potential accident scenarios do not affect the cask at all and would not result in either release of radioactive material nor increased dose from loss of lead shielding. However, these accidents would result in an increased dose from the cask external radiation to the population near the accident, because the cask remains at the location of the accident until it can be moved. A nominal ten hours was assumed for this <u>delay in this</u> study. The resulting collective dose risk from this accident is shown in Figure 6-5 for all three cask types studied. Even including this additional consequence type, the collective dose risk from this study is less than that reported in either NUREG-0170 or NUREG/CR-6672.

In conclusion, the three studies reviewed here show that the NRC regulation of transportation casks ensures safety and health. The use of data in place of engineering judgment shows that accidents severe enough to cause loss of shielding or release of radioactive material are improbable and the consequences of such unlikely accidents are serious but not dire. Moreover, these consequences depend on the <u>size of the population</u> exposed rather than on the radiation or radioactive material released. The consequences (doses) to the maximally exposed individual, 1.6 Sv from a release and 1.1 Sv from loss of lead shielding, are chronic rather than acute doses.

The most significant consequence of an accident, in addition to any non-radiological consequence of the accident itself, is the external dose from a cask immobilized at the accident location. The most significant parameters contributing to this dose are the accident frequency and the length of time that the cask sits at the accident location. Even in this case, the significant parameter in the radiological effect of the accident is not the amount or rate of radiation released, but the exposure time.

Public perception of radiological risk of transportation does not appear to recognize that such risk depends much more on artifacts of calculation, parameter selection, and assumption than on the amount of radiation emitted. The conservative estimates of NUREG-0170 may have inadvertently contributed to this misperception. The more realistic the analysis, the greater the likelihood of redirecting public perception.

Comment [JRC153]: But they are acute (received in a short time span) doses?

Comment [JRC154]: Not a particularly strong closing. Don't' disagree with public perception/risk estimate mismatch, but not sure we want to end on this note. How study authoritatively reassures safety may be what public is looking for.