

The Reno Creek Project - Monitor Well Sampling Report

AUC LLC

| | | | | | | | |
|--------------|---------|--------------|--------|-------------------|------|---------------|----|
| Location ID | UM7 | Sample Date: | 3/7/12 | Sampling Company: | TREC | Sampled By 1: | TN |
| Sample Event | Q3-2011 | | | | | Sampled By 2: | WC |
| | | | | | | Sampled By 3: | |

Well Information:

| | | | | |
|-----------------------|-----------------|-----------------------|-------------------------------------|-------------------|
| Well Total Depth (TD) | 405 | ft | Well Measuring Point (MP) Location: | North Side-Marked |
| Sampled From: | Monitoring Well | Well Inside Diameter: | 4.5 | inches |
| Screened Interval: | 385 | Feet to | 405 | Feet |
| | | Pump Type Used: | Dedicated Low Flow Bladder | |
| | | Pump Intake Depth: | 395 | ft |
| | | Tubing Type: | Dedicated Plastic | |

Well Fluid Measurements:

| | | | | | | | |
|---------------------------------|-----------------|----------|----------|----|------|-------------|----------------------|
| Time (military): | 10:30 | Weather: | Air Temp | 24 | (°F) | Conditions: | Breezy, 10mph, sunny |
| Water level gauged using: | Electronic tape | | | | | | |
| Depth to Water (DTW) below MP: | 186.3 | ft | | | | | |
| Water Column Height (TD-DTW): | 0 | ft | | | | | |
| Water volume = $\pi r^2 h$ (cf) | 0.00 | gallons | | | | | |
| 3 Well Volumes: | 0.00 | gallons | | | | | |

| | | | | | |
|--|-------------|-------------|-------------|-------------|------------|
| Well volume (in gal / LF) = $\pi r^2 (cf)$ where: π = pi (approximately 3.14); r = radius of monitoring well (feet) cf = conversion factor (7.48 gal/ft ³); | | | | | |
| Well ID (in) | 2 | 3 | 4 | 4.5 | 5 |
| Water Volume (gal/LF) | 0.163188147 | 0.367173331 | 0.652752589 | 0.826139995 | 1.01992592 |

Purging:

| | | | | | | | | |
|----------------------------------|----------------------------|------------------|-------|------------------------------------|----------------|----------------|-------------------------|---------|
| Purge Date | 3/7/12 | Purge Time Begin | 10:40 | Low Flow Pump Controller Settings: | Charge Time | 4 | Exhaust Time | 26 |
| Purge Pump Type: | Dedicated Low Flow Bladder | Pumping Rate: | 180 | ml/min | Meter Type(1): | YSI Multi | Meter Calibration Date: | 1/24/12 |
| Volume Purged Prior to Sampling: | 2 | gallons | | | Meter Type(2): | Hach Turbidity | Meter Calibration Date: | 1/24/12 |
| | | | | | Meter Type(3): | | Meter Calibration Date: | |

Field Stabilization Measurements:

| Sample ID | Purge Date | Time (min.) | Purge Rate (ml/min) | Purge Rate (gal/min) | Temp (°C) | Conductivity (µmhos/cm) | DO (mg/L) | pH (su) | ORP (mV) | Turbidity (NTU) | Water Level (ft) | Comments |
|---------------------------------|------------|-------------|---------------------|----------------------|-----------|-------------------------|-----------|---------|----------|-----------------|------------------|-------------------|
| UM7-004-120307 | 03/07/12 | 10:45 | 400 | | 9.59 | 607 | 5.80 | 10.64 | 103.9 | 3.8 | 187.55 | |
| | | 10:48 | 400 | | 10.05 | 632 | 3.22 | 10.67 | 81.1 | 4.7 | 187.80 | |
| | | 10:51 | 180 | | 9.79 | 628 | 3.24 | 10.63 | 73.9 | 6.0 | 188.00 | Changed ET and CT |
| | | 10:54 | 180 | | 9.29 | 627 | 3.43 | 10.64 | 67.1 | 4.6 | 188.08 | |
| | | 10:57 | 180 | | 9.34 | 630 | 3.39 | 10.6 | 59.6 | 4.1 | 188.16 | |
| | | 11:00 | 180 | | 9.46 | 628 | 3.48 | 10.6 | 56.4 | 3.9 | 188.26 | |
| | | | | | | | | | | | | |
| Repeat Last Stabilization Meas. | | | | | | | | | | | | |

Sampling:

| | | | | | | | |
|-------------------|----------------------------|------------------------------|-------|----------------|----------------|---------------------------|---------|
| Sample Date | 3/7/2012 | Sample Collection Time (MT): | 11:15 | Meter Type(1): | YSI Multi | Meter 1 Calibration Date: | 1/24/12 |
| Sample Pump Type: | Dedicated Low Flow Bladder | | | Meter Type(2): | Hach Turbidity | Meter 2 Calibration Date: | 1/24/12 |
| | | | | Meter Type(3): | | Meter 3 Calibration Date: | |

Analysis:

| | | | | | | | |
|----------------|----|-----------------------|--|--------|---------|-------|-----|
| QA/QC Sample | No | QA/QC Type | | COC#1: | RC08269 | Lab 1 | IML |
| Duplicate Name | | Duplicate Sample Time | | COC#2: | | Lab 2 | ALS |
| | | | | COC#3: | | Lab 3 | |

Analysis: Table 1- 4.14, Guide 8, & Radon 222

Comments:

Slow recharge, sampled with minimal draw down. High pH- 10.60

Stabilization Parameters

| | |
|-----------|--------------------------|
| Temp | = +/- 3% in celcius |
| pH | = +/- 0.1 unit |
| SC | = +/- 3% in µmhos/cm |
| ORP/Eh | = +/- 10 millivolts |
| DO | = +/- 10% in mg/L |
| Turbidity | = +/- 10% for values > 5 |

Range values for data entry

| Conductivity Range (mS/cm) | Turbidity (NTU) | Dissolve Oxygen (DO) (mg/L) | Temperature Range (°C) | Ox/Reduc Potential (mV) |
|----------------------------|-----------------|-----------------------------|------------------------|-------------------------|
| Min 0 | Min 0 | Min 0.01 | Min -20 | Min -400 |
| Max 2000 | Max 1000 | Max 2000 | Max 80 | Max 700 |