7						mac
2 	REGUL	ATORY DI	FORMATI	ON DISTRIBUTION S	SY EM (RIDS)	54
ACCESSIO	N NBR:8211010	159 D(DC.DATE	82/10/28 NOTAF	RIZED: NO	DOCKET #
FACIL:5	0-361 San Ono	fre Nucl	ear Sta	tion, Unit 2, Sou	thern Califor	n 0500036 <u>1</u>
5	0-362 San Ono	fre Nucle	ear Sta	tion, Unit 3, Sou	uthern⊴Califo	n 05000362
AUTH,N	AME AU	THUR AFF.	ILIATIO		Υ.,	
RECTP	NAME DE	CTETENT	AFFTI TA	FICN		
KNIGHTO	N.G.W.	Licensin	Branc	n 3	ана. Спорта страна страна Страна страна	
				· •	· · · · · · · · ·	
SUBJECT	: Advises tha	t fine p	rotecti	on sys not in lit	teral complian	nce
	W/Branch je	cnnical I unations	POSITIO differ	from position at	internal <u>con</u> contable fin	
	protection	provided	• ·	Trom position/a	ceptable in	-
					,	2.
DISTRIB TITLE:	UTION CODE: B Licensing Sub	0018 CO mittal:	PIES REP PSAR/FS	CEIVED:LTR ENC AR Amdts & Relate	CL _/ SIZE: d Corresponde	ence
NOTES:J	Hanchett 1cy	PDR Doc	uments.	ELD Chandler 1cy	· •	05000361
N	RR Scaletti 1	CY.	~			
J	PR Seclett 1cy	PUR UOCI	uments,	ELD Chandler 1Cy	*	05000362
14	KN VGaletti I	G Y +				
				х - с	•	
	RECIPIENT	C01	PIES	RECIPIENT	COPIES	•
	ID CODE/NAM	E LT	TR ENCL	ID CODE/NAME	LTTR ENG	
	NRK/DL/ADL		1 0	NRR LB3 BC	1 () .
	NKK LOS LA		L O	RUUD, H.	01 1 1	
INTERNAL:	ELD/HDS2		1 ×0 ·	IE FILE	1 1	
	IE/DEP EPDS	35	1 1	IE/DEP/EPLB	36 3 3	3
	NRR/DE/AEAB		L -0	NRR/DE/CEB	11 1 1	L
	NRR/DE/EQB	13	3 3	NRR/DE/GB	28 2 2	2
• •	NRR/DE/HGEB	30 2	2 ²	NRR/DE/MEB	18 1 1	
	NRR/DE/MTEB	17 .;	1 1	NRR/DE/QAB	21 1 1	
	NRR/DE/SAB	24	1	NRR/DE/SEB	25 1 1	
	NRR/DHFS/HFE	B40 1	1	NRRZDHFSZLQB	32 1 1	
	NRR/DHFS/ULB	34 1		NRR/DHFS/PTRE		
	NER/DOI/ACD	20	k k	NRR/DSI/ASB		1
. •		10	6 A			
	NRR/DST/PSB	10	i 1		20 I I	ч
	NRR/DSI/RSB	23	1	NRR/DST/LGB	33 1 1	,
	REG FILE)	-04 1		RGN5	2 2	
	RM/DDAMI/MIB	1	L -0			
EXTERNAL :	ACRS	41. 4	· · · · ·	BNI (AMDTS ONI	Y.) 1 1	
	DMB/DSS (AMD	TS)	1	FEMA-REP DIV	39 1 1	
	LPDR	03 1	1	NRC PDR	02 1 1	,
•	NSIC	05 1	1	NTIS	1 1	•
NOTEC			,	•		
NUPES	••		5 ⁻ 3			

TOTAL NUMBER OF COPIES REQUIRED: LTTR

58 ENCL

:52

Southern California Edison Company

P 0 B0X 800 2244 WALNUT GROVE AVENUE ROSEMEAD, CALIFORNIA 91770

K. P. BASKIN MANAGER OF NUCLEAR ENGINEERING, SAFETY, AND LICENSING

October 28, 1982

Director, Office of Nuclear Reactor Regulation Attention: Mr. George W. Knighton, Branch Chief Licensing Branch No. 3 U. S. Nuclear Regulatory Commission Washington, D.C. 20555

Gentlemen:

8211010159 821028 PDR ADDCK 05000361

PDR

Docket Nos. 50-361 and 50-362 Subject: San Onofre Nuclear Generating Station Units 2 and 3

License Condition 2.C(14)c of the San Onofre Nuclear Generating Station Unit 2 (SONGS 2) Operating License, NPF-10, required that Southern California Edison Company (SCE) identify and describe any deviations of the SONGS 2 fire protection system from the acceptance criteria of Section 9.5-1 of the Standard Review Plan (NUREG-0800, dated July 1981). On July 22, 1982 SCE submitted a letter to the NRC to satisfy this license condition.

Subsequently, it has been brought to SCE's attention that an additional area of SONGS 2 and 3 fire protection is not in literal compliance with the Branch Technical Position (BTP) 9.5-1 guidelines. Specifically, BTP 9.5-1, item C.5.a(3) recommends that, for conduit penetrations through fire barriers, openings inside conduit 4 inches or less in diameter should be sealed at the fire barrier unless the conduit extends at least 5 feet on each side of the fire barrier and is sealed at both ends or at the fire barrier with noncombustible material to prevent the passage of smoke and hot gas. This is a new requirement over previous guidelines which were not specific as to the configuration of the conduit seals and only required that the seal fire rating be at least equivalent to that of the penetrated fire barrier. The purpose for internal sealing of conduit is to restrict the passage of smoke and hot gases, thus preventing fire from propagating through fire barriers and affecting redundant trains of safety related equipment. While the configuration of internal conduit seals at SONGS 2 and 3 differs from that recommended in BTP 9.5-1, it meets these functional criteria.



TELEPHONE (213) 572-1401

Rool

Mr. George W. Knighton

All conduit used at SONGS 2 and 3 is 4 inches or less in diameter. Conduits which penetrate fire barriers are internally sealed at or near the fire barrier with noncombustible silicone foam which provides an equivalent fire rating to that of the penetrated barrier and restricts the passage of smoke. The noncombustible silicone foam sealing material is the same as that used for fire barrier penetration seals. The penetration seals have been tested to demonstrate that the penetration seal is of equivalent fire rating to that of the penetrated barrier and that it remains intact and does not allow the projection of water beyond the unexposed surface. In addition to internal sealing of conduits, the use of cable with self-extinguishing flame retardent insulation further reduces the probability of fire propagating past fire barriers through conduit. All cable insulation used at SONGS 2 and 3 meets the requirements of IEEE 383-1974 with the exception of the PVC insulation used on a limited number of non-safety related communications cables which are identified in the Fire Hazards Analysis.

Based upon the above, SCE considers that the conduit internal sealing criteria used at SONGS 2 and 3 effectively prevents fire from propagating through conduit and affecting redundant trains of safety related equipment. Even though the configurations of internal conduit seals at SONGS 2 and 3 differ from those recommended by BTP 9.5-1, SCE believes that acceptable fire protection has been provided.

Should you have any questions regarding this information, please call me.

Very truly yours,

WP Bastini

cc: Harry Rood, NRC (to be opened by addressee only)
R. H. Engelken, NRC Region V