

Southern California Edison Company




P. O. BOX 800
2244 WALNUT GROVE AVENUE
ROSEMEAD, CALIFORNIA 91770

W. C. MOODY
MANAGER, NUCLEAR LICENSING

April 20, 1981

TELEPHONES
(213) 572-1817
(213) 572-1806

Director of Nuclear Reactor Regulation
Attention: Mr. D. M. Crutchfield, Chief
Operating Reactors Branch No. 5
Division of Licensing
U.S. Nuclear Regulatory Commission
Washington, D.C. 20555



Gentlemen:

Subject: Docket No. 50-206
SEP Topics II-3.A and II-3.B
San Onofre Nuclear Generating Station
Unit 1

Enclosed for your use in connection with the subject SEP topics is the following information:

1. Drawings showing the beach walkway which is currently under construction in front of the seawall.

5180940-0	Beach Walkway General Notes & Drawing List
5180941-0	Beach Walkway Permanent and Temporary Plan
5180942-0	Beach Walkway Details
5180943-0	Beach Walkway Sections and Details
5180944-0	Beach Walkway Sections and Details
5180945-A	Beach Walkway Permanent Walkway Details

2. Information pertaining to the maximum ground water level at the San Onofre site. This information was previously provided to the NRC in connection with the structural audit of San Onofre Units 2 and 3.

If you have any questions on this information please let me know.

Sincerely,

W.C. Moody

A035

*3
1/5*

Aperture Dist.

*SEND DRAWINGS to
Reg F/ES*

BC (4)

Enclosures

8104270355

P

NRC STRUCTURAL AUDIT REQUEST ITEMS

SONGS 243

INTAKE STRUCTURE AND BOX CONDUIT

Item #2: Provide basis for establishing the maximum ground water level used in determining hydrostatic pressures on structural walls.

Response

A number of observations for ground water level has been made at the sites for Unit 1 and Units 2 and 3 over the past 10 years. These observations were made during various investigations such as soil explorations, pumping tests for evaluating field permeability of native soils, installation of the Units 2 and 3 dewatering system and investigations during demobilization of the Units 2 and 3 dewatering system. A summary of these observations is presented in Table 1. Figure 1 presents the locations of various observations points. The data presented in Table 1 indicate a maximum value of +5.8 feet. Only a few of the measurements indicated a level above +5 feet and those were made on the dewatering wells or test piezometers and may reflect transient conditions related to a rapid inflow of water occurring when dewatering was terminated. For this reason, and based on the majority of the data, it is concluded that elevation +5 feet represents a reasonable maximum for the ground water level at the site. This conclusion is also consistent with areal observations as follows:

(1) ground water contours for typical high and low ground water conditions are presented in Figures 2.4-27 and 2.4-28 of the FSAR (presented as Figures 2 and 3 here for completeness) indicate a maximum ground water elevation of +5 feet in the immediate vicinity of the site; and (2) a

report by California Department of Water Resources (Reference 1) provides regional data indicating an average ground water elevation in the vicinity of the site is +5 feet.

Ground water sources for the general area of the site are described in Section 2.4.6.13 of the FSAR. Because the foundation soil at the site (San Mateo Sand) is free draining and because the site is adjacent to the ocean, the fluctuations in the ground water are primarily controlled by tidal fluctuations. Further, because of the free draining nature of the foundation soils and the surface drainage facilities at the site, direct rainfall on the site is not expected to have an influence on the ground water level. In view of the above information and the observed ground water levels in the various wells summarized in Table 1, it is concluded that an elevation of +5 feet represents a reasonable maximum level for the ground water at the plant site.

References

1. California Department of Water Resources, 1968, Reclamation of water from wastes - central San Diego County: Bulletin 80-2.

TABLE 1
SUMMARY OF GROUND WATER LEVEL OBSERVATIONS


<u>Well/Boring Designation</u>	<u>Date of Observation</u>	<u>Elev. of Observed Water Level</u>	<u>Remarks</u>
Water Well #1	May 1967	+3.9	Well #1 through 5 are located in area of Unit 1 (see Figure 1)
	June 1967	+4.0	
	March 1970	+4.1	
	Dec 1970	+3.9	
Water Well #2	April 1967	+2.6	
	May 1967	+3.1	
	June 1967	+3.3	
	March 1970	+3.3	
	Dec 1970	+3.5	
Water Well #3	April 1967	+3.0	
	May 1967	+3.3	
	June 1967	+3.5	
	March 1970	+3.7	
	Dec 1970	+3.7	
Water Well #4	April 1967	+1.2	
	May 1967	+2.1	
	June 1967	+1.7	
	March 1970	+2.5	
	Dec 1970	+2.2	
Water Well #5	April 1967	+0.8	
D-M Boring #2	March 1970	+5.0	Soil boring.
Piezometer Well #1	May 1974	+5.60*	Observation wells #1 through 7 installed for pump tests. The observations represent initial readings before pump tests.
Piezometer Well #2	May 1974	+3.09	
Piezometer Well #3	May 1974	+5.80*	
Piezometer Well #3A	May 1974	+5.24*	
Piezometer Well #4	May 1974	+5.60*	Test well.


Table 1
Page 2

<u>Well/Boring Designation</u>	<u>Date of Observation</u>	<u>Elev. of Observed Water Level</u>	<u>Remarks</u>
Piezometer Well #5	May 1974	+5.76*	
Piezometer Well #6	May 1974	+5.34*	
Piezometer Well #7	May 1974	+5.47*	
Deep Well #1	July 1977	+4.5	Deep wells installed for dewatering system.
Deep Well #2	Aug 1977	+4.5	
Deep Well #3	Nov 1977	+5.5	
Deep Well #3A	Sept 1977	+5.0	
Deep Well #4	May 1976	-0.50**	
Deep Well #5	April 1976	0.0**	
Deep Well #6	July 1976	-1.5**	
Deep Well #7	June 1976	-3.0**	
Deep Well #8	June 1976	-3.0**	
Deep Well #9	Nov 1976	-3.5**	
Deep Well #10	July 1977	+4.5	
Deep Well #11	July 1977	+2.5	
Deep Well #12	July 1977	+2.5	

* Values above Elev. +5 feet may be affected by testing operation (i.e., rapid water inflow after test covering a local high)

** Readings represent maximum values monitored over a period from 1974 to 1977. Low values may be related to dewatering from adjacent wells.





EXPLANATION

- Permanent formation
- Semi-permanent formation
- Boundary of neotectonic formation
- Camp supply or irrigation well
- Domestic, stock, or shaded well
- Destroyed or dry well
- Stream-gaging station
- Ground-water contour March 1952 (5 foot interval)
- Location of cross-section

SCALE: 1" = 36000
DATUM IS MEAN SEA LEVEL

0 100 200 300 400 500 600 700 800 900 1000 FEET

0 100 200 300 400 500 600 700 800 900 1000 METERS


COMPILED FROM S. F. WORTS ET AL., 1953
R. F. BOSS ET AL., 1958

SAN ONOFRE
NUCLEAR GENERATING STATION
Units 2 & 3

GROUNDWATER CONTOUR MAP
SAN ONOFRE VALLEY BASIN
TYPICAL HIGH-WATER CONDITION

Figure 2-A-27

FIGURE 2



EXPLANATION

- Permeable formation
- Semi-impermeable formation
- Boundary of impermeable formation
- Camp supply or irrigation well
- Domestic, stock, or unlined well
- Destroyed or dry well
- Stream-gaging station
- Ground-water contour, August 1981
(5 foot interval)
- Location of cross-section

SCALE: 1" = 36,000
 DATUM IS MEAN SEA LEVEL

0 1000 2000 3000 FEET

0 1000 2000 3000 METERS

COMPILED FROM: G. F. WORTS ET AL., 1983
 R. F. WOOD ET AL., 1986

SAN ONOFRE
 NUCLEAR GENERATING STATION
 Units 2 & 3
 GROUNDWATER CONTOUR MAP
 SAN ONOFRE VALLEY BASIN
 TYPICAL LOW-WATER CONDITION
 Figure 2.4-28

FIGURE 3