

Facility: Dresden		CREW #1		Date of Exam: Oct 2013		Operating Test No.:											
A P P L I C A N T	E V E N T  T Y P E	Scenarios												T O T A L	M I N I M U M (*)		
		1			2			3			4						
		CREW P O S I T I O N			CREW P O S I T I O N			CREW P O S I T I O N			CREW P O S I T I O N						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P				
												R	I	U			
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input checked="" type="checkbox"/>	RX	2														1	1
	NOR	1											1	1	1	1	
	I/C	3,4,5, 6,8				1,5							7	4	4	2	
	MAJ	7				7							2	2	2	1	
	TS	3,4,6											3	0	2	2	
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX		2		2								2	1	1	0	
	NOR				1								1	1	1	1	
	I/C		3,5,8		1,3,5, 6,8								8	4	4	2	
	MAJ		7		7								2	2	2	1	
	TS				1,4								2	0	2	2	
RO <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX				2								1	1	1	0	
	NOR			1									1	1	1	1	
	I/C			4,6, 8		3,6, 8							6	4	4	2	
	MAJ			7		7							2	2	2	1	
	TS												0	2	2		
RO <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX												1	1	0		
	NOR												1	1	1		
	I/C												4	4	2		
	MAJ												2	2	1		
	TS												0	2	2		

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls (ATC)" and "balance-of-plant (BOP)" positions; Instant SROs must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an Instant SRO *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (\*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.

Facility: **Dresden**    **CREWS #2 & 3**    Date of Exam:    Oct 2013    Operating Test No.:

A P P L I C A N T	E V E N T  T Y P E	Scenarios													T O T A L	M I N I M U M (*)		
		1			2			3			4							
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N							
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P					
													R	I	U			
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX	2							1					2	1	1	0	
	NOR	1							3					2	1	1	1	
	I/C	3,4,5,6,8					1,5		3,5					7	4	4	2	
	MAJ	7					7		7,8					3	2	2	1	
	TS	3,4,6												3	0	2	2	
RO <input type="checkbox"/> SRO-I <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX		2		2			1						3	1	1	0	
	NOR				1			3						2	1	1	1	
	I/C		3,5		1,3,5,6									6	4	4	2	
	MAJ		7		7			7,8						4	2	2	1	
	TS				1,4			4,5						4	0	2	2	
RO <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX					2								1	1	1	0	
	NOR			1										1	1	1	1	
	I/C			4,6,8		3,6,8			2,5,7					9	4	4	2	
	MAJ			7		7			7,8					4	2	2	1	
	TS													0	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX													1	1	1	0	
	NOR													1	1	1	1	
	I/C													4	4	4	2	
	MAJ													4	2	2	1	
	TS													0	0	2	2	

Instructions:

- Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the "at-the-controls (ATC)" and "balance-of-plant (BOP)" positions; Instant SROs must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an Instant SRO *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
- Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (\*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
- Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant's competence count toward the minimum requirements specified for the applicant's license level in the right-hand columns.