

APPENDIX 2AA

BORING LOGS

FROM

ESPA INVESTIGATION

SOIL CLASSIFICATION CHART

MAJOR DIVISIONS			SYMBOLS		TYPICAL DESCRIPTIONS	
			GRAPH	LETTER		
<p>COARSE GRAINED SOILS</p> <p>MORE THAN 50% OF MATERIAL IS LARGER THAN NO. 200 SIEVE SIZE</p>	<p>GRAVEL AND GRAVELLY SOILS</p> <p>MORE THAN 50% OF COARSE FRACTION RETAINED ON NO. 4 SIEVE</p>	<p>CLEAN GRAVELS</p> <p>(LITTLE OR NO FINES)</p>		GW	WELL-GRADED GRAVELS, GRAVEL - SAND MIXTURES, LITTLE OR NO FINES	
		<p>GRAVELS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		GP	POORLY-GRADED GRAVELS, GRAVEL - SAND MIXTURES, LITTLE OR NO FINES	
		<p>GRAVELS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		GM	SILTY GRAVELS, GRAVEL - SAND - SILT MIXTURES	
		<p>GRAVELS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		GC	CLAYEY GRAVELS, GRAVEL - SAND - CLAY MIXTURES	
	<p>SAND AND SANDY SOILS</p> <p>MORE THAN 50% OF COARSE FRACTION PASSING ON NO. 4 SIEVE</p>	<p>CLEAN SANDS</p> <p>(LITTLE OR NO FINES)</p>		SW	WELL-GRADED SANDS, GRAVELLY SANDS, LITTLE OR NO FINES	
			<p>CLEAN SANDS</p> <p>(LITTLE OR NO FINES)</p>		SP	POORLY-GRADED SANDS, GRAVELLY SAND, LITTLE OR NO FINES
		<p>SANDS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		SM	SILTY SANDS, SAND - SILT MIXTURES	
			<p>SANDS WITH FINES</p> <p>(APPRECIABLE AMOUNT OF FINES)</p>		SC	CLAYEY SANDS, SAND - CLAY MIXTURES
			<p>SILTS AND CLAYS</p> <p>LIQUID LIMIT LESS THAN 50</p>		ML	INORGANIC SILTS AND VERY FINE SANDS, ROCK FLOUR, SILTY OR CLAYEY FINE SANDS OR CLAYEY SILTS WITH SLIGHT PLASTICITY
				<p>SILTS AND CLAYS</p> <p>LIQUID LIMIT LESS THAN 50</p>		CL
<p>SILTS AND CLAYS</p> <p>LIQUID LIMIT GREATER THAN 50</p>	<p>SILTS AND CLAYS</p> <p>LIQUID LIMIT GREATER THAN 50</p>		OL	ORGANIC SILTS AND ORGANIC SILTY CLAYS OF LOW PLASTICITY		
		<p>SILTS AND CLAYS</p> <p>LIQUID LIMIT GREATER THAN 50</p>		MH	INORGANIC SILTS, MICACEOUS OR DIATOMACEOUS FINE SAND OR SILTY SOILS	
	<p>SILTS AND CLAYS</p> <p>LIQUID LIMIT GREATER THAN 50</p>		CH	INORGANIC CLAYS OF HIGH PLASTICITY		
		<p>SILTS AND CLAYS</p> <p>LIQUID LIMIT GREATER THAN 50</p>		OH	ORGANIC CLAYS OF MEDIUM TO HIGH PLASTICITY, ORGANIC SILTS	
<p>HIGHLY ORGANIC SOILS</p>				PT	PEAT, HUMUS, SWAMP SOILS WITH HIGH ORGANIC CONTENTS	

NOTE: DUAL SYMBOLS ARE USED TO INDICATE BORDERLINE SOIL CLASSIFICATIONS

KEY TO CLASSIFICATION OF SOILS				
Soils classified under the Unified Soil Classification System (USCS) and in accordance with ASTM D 2488-06				
CORRELATION OF SPT RESISTANCE WITH RELATIVE DENSITY-CONSISTENCY				MOISTURE CONTENT
GRANULAR MATERIAL		SILTS AND CLAYS		DRY-Absence of moisture
RELATIVE DENSITY	SPT N Value (blows/ft)	CONSISTENCY	SPT N Value (blows/ft)	MOIST-Damp/no visible H ₂ O
VERY LOOSE	0 - 4	VERY SOFT	0 - 2	WET-Visible free water
LOOSE	5 - 10	SOFT	3 - 4	
MEDIUM DENSE	11 - 30	MED. STIFF	5 - 8	HCl Reaction
DENSE	31 - 50	STIFF	9 - 15	NONE - No visible reaction
VERY DENSE	> 50	VERY STIFF	16 - 30	WEAK - Some reaction/slow
		HARD	> 30	STRONG - Violent reaction
MODIFIERS			INDURATION	
Modifiers provide an estimate of the percentages of gravel, sand, and fines (silt or clay size particles) or other material such as organics, shells, glauconite, indurated material, etc.			For sedimentary rocks, induration is the hardening of the material by cementing, heat, pressure, etc.	
TRACE	<5%	FRIABLE	Rubbing with finger frees numerous grains; gentle blow by hammer disintegrates sample.	
FEW	5 to 10%	MODERATELY INDURATED	Grains can be separated from sample with steel probe/knife; breaks easily when hit with hammer.	
LITTLE	15 to 25%	INDURATED	Grains are difficult to separate with steel probe/knife; difficult to break with hammer.	
SOME	30 to 45%	EXTREMELY INDURATED	Sharp hammer blows required to break sample; sample breaks across grains.	
MOSTLY	50 to 100%	SPT Sample Numbering: SS-1, SS-2, SS-3, etc.		
		Undisturbed Sample Numbering: UD-1, UD-2, UD-3, etc.		
COLOR of Soil: see Munsell Soil Color Charts		MEASUREMENTS: Horizontal measurements and vertical measurements, such as SPT sample recovery or penetration, sample depths, etc., are rounded to nearest tenth of a foot (0.1 ft).		
Particle Size Range for Sand: Fine, Medium, Coarse				
Particle Size Range for Gravel: Fine or Coarse				
GROUND WATER: Fluid level observations were recorded at the boring locations at the start of each work day, when possible. Due to the use of drilling fluid additives, these values may not represent the ground water conditions at the site. See observation wells for measured ground water levels.		HORIZONTAL COORDINATES (Northing and Easting) = NAD83 (2007), New Jersey State Plane Coordinate System Zone (2900), US Survey Feet.		
FLUID LEVELS (ft) : 0 HR = Measured fluid level in boring immediately after drilling completed 24 HR = Measured fluid level in boring prior to grouting		ELEVATIONS = North American Vertical Datum of 1988 (NAVD88), US Survey Feet.		
		ABBREVIATIONS USED: Run = Soil cored length during rotosonic drilling TV = Torvane Test (tsf) PP = Pocket Penetrometer Test (tsf) tsf = tons per square foot ND = Not Determined		



GEOTECHNICAL BORING LOG

Prepared By MJM Date 7/10/09

Checked By JAS Date 7/10/09

SHEET 1 OF 11

PERMIT NO.: P200900084		DRILLER: G. McAneny / R. Bartholomew			NJ LICENSE NO.: 0024058 / 0001383			GEOLOGIST: R. Clark / S. Johnson										
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)									
BORING NO.: NB-1		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND										
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)			EASTING: 198469.1 US ft (NAD83)			24 HR. 11.0										
TOTAL DEPTH: 600.9 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.5 ft			HAMMER (ID): 140 lb Auto. (CTB-2)										
DATE STARTED: 1/13/09		COMPLETED: 2/9/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit										
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION						
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100					
12.8					Ground Surface							12.8	0.0					
12.8	0.0	4	7	8														
10.3	2.5																	
		3	6	6														
7.8	5.0																	
		2	4	6														
5.3	7.5																	
		WOH	WOH	WOH														
2.8	10.0																	
		WOH	8	12														
0.3	12.5																	
		7	16	20														
-2.2	15.0																	
		WOH	WOH	WOH														
		WOH																
-7.2	20.0																	
		WOH	WOH	WOH														
		WOH																
-12.2	25.0																	
		WOH	WOH	WOH														
		WOH																
-17.2	30.0																	
		WOH	WOH	WOH														
		WOH																
-22.2	35.0																	
		1	2	2														
		WOH	WOH	WOH														
-27.2	40.0																	
		WOH	WOH	WOH														
		WOH																
-32.2	45.0																	
		WOH	4	12														
		WOH																
-37.2	50.0																	
		6	16	18														
		WOH	WOH	WOH														
-42.2	55.0																	
		WOH	WOH	WOH														

PSEG ESP BORE PSEG ESP 7-07-09.GPI PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900084	DRILLER: G. McAneny / R. Bartholomew	NJ LICENSE NO.: 0024058 / 0001383	GEOLOGIST: R. Clark / S. Johnson
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-1	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT	
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)	EASTING: 198469.1 US ft (NAD83)
TOTAL DEPTH: 600.9 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 13.5 ft	HAMMER (ID): 140 lb Auto. (CTB-2)
DATE STARTED: 1/13/09	COMPLETED: 2/9/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag Bit			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-43.3					Continued from previous page							
-47.2	60.0	WOH	WOH	WOH								KIRKWOOD FORMATION: FAT CLAY (CH), olive (5Y 5/3), very soft, moist, no HCl reaction (continued)
-52.2	65.0	5	12	17						SS-16		60.0ft: Dark gray (5Y 4/1), trace fine sand
-57.2	70.0	6	5	5						SS-17		KIRKWOOD FORMATION: Silty SAND (SM), olive gray (5Y 5/2), medium dense, wet, fine sand, little subrounded to rounded gravel, no HCl reaction
-62.2	75.0	9	15	15						SS-18		VINCENTOWN FORMATION: Clayey SAND (SC), brown (7.5YR 4/3), loose, wet, fine sand, trace subrounded to rounded gravel, weak HCl reaction, strongly oxidized
-67.2	80.0	2	4	11						SS-19		VINCENTOWN FORMATION: Silty SAND (SM), light olive brown (2.5Y 5/4), medium dense, wet, fine sand, weak HCl reaction, strongly oxidized
-72.2	85.0	12	8	9						SS-20		80.0ft: Yellowish brown (10YR 5/4), fine to medium sand, weak HCl reaction, moderately oxidized
-77.2	90.0	2	5	9						SS-21		85.0ft: Greenish gray (10Y 5/1), trace friable to moderately indurated layers, trace glauconite, no oxidation
-82.2	95.0	9	8	9						SS-22		VINCENTOWN FORMATION: Silty, clayey SAND (SC-SM), greenish gray (10Y 6/1), medium dense, wet, fine to medium sand, weak HCl reaction, trace glauconite
-87.2	100.0	21	14	12						SS-23		95.0ft: Trace moderately indurated layers, strong HCl reaction
-92.2	105.0	11	8	16						SS-24		100.0ft: Greenish gray (10Y 5/1), little friable to moderately indurated layers
-97.2	110.0	7	8	18						SS-25		105.0ft: Trace friable layers
										SS-26		

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900084		DRILLER: G. McAneny / R. Bartholomew		NJ LICENSE NO.: 0024058 / 0001383		GEOLOGIST: R. Clark / S. Johnson						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251						
BORING NO.: NB-1		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		FLUID LEVEL (ft)						
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)		EASTING: 198469.1 US ft (NAD83)		0 HR. ND						
TOTAL DEPTH: 600.9 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-2)						
DATE STARTED: 1/13/09		COMPLETED: 2/9/09		HOLE DIA.: 4"		ROD TYPE: NWJ						
						BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-99.4					Continued from previous page							
-102.2	115.0	8	10	16						SS-27		VINCENTOWN FORMATION: Silty, clayey SAND (SC-SM), greenish gray (10Y 6/1), medium dense, wet, fine to medium sand, weak HCl reaction, trace glauconite (continued) 115.0ft: Dark greenish gray (10Y 4/1)
-107.2	120.0	18	50/0.3						60/0.3	SS-28		HORNERSTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), very dense, wet, fine to medium sand, strong HCl reaction, trace to few glauconite
-112.2	125.0	4	6	12						SS-29		125.0ft: Medium dense
-117.2	130.0	6	11	15						SS-30		
-122.2	135.0	9	11	20						SS-31		135.0ft: Dense, few to little glauconite
-127.2	140.0	16	23	25						SS-32		NAVESINK FORMATION: Clayey SAND (SC), very dark greenish gray (10GY 3/1), dense, wet, few shell fragments, strong HCl reaction, mostly glauconite
-132.2	145.0	27	36	42						SS-33		NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (10GY 3/1), very dense, wet, fine to coarse sand, few shell fragments, weak HCl reaction, mostly glauconite
-137.2	150.0	18	21	23						SS-34		NAVESINK FORMATION: Clayey SAND (SC), very dark greenish gray (10Y 3/1), dense, moist, trace shells, strong HCl reaction, mostly glauconite
-142.2	155.0	18	28	37						SS-35		NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (10Y 3/1), very dense, wet, weak HCl reaction, mostly glauconite
-147.2	160.0	23	38	44						SS-36		
-152.2	165.0	22	33	45						SS-37		MOUNT LAUREL FORMATION: Clayey SAND (SC), dark olive gray (5Y 3/2), very dense, moist to wet, fine to medium sand, few subangular to subrounded coarse sand, strong HCl reaction, trace to few glauconite

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900084		DRILLER: G. McAneny / R. Bartholomew		NJ LICENSE NO.: 0024058 / 0001383		GEOLOGIST: R. Clark / S. Johnson						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251						
BORING NO.: NB-1		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT								
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)		EASTING: 198469.1 US ft (NAD83)		FLUID LEVEL (ft) 0 HR. ND 24 HR. 11.0						
TOTAL DEPTH: 600.9 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-2)						
DATE STARTED: 1/13/09		COMPLETED: 2/9/09		HOLE DIA.: 4"		ROD TYPE: NWJ						
						BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-155.5					Continued from previous page							
-157.2	170.0	50/0.3								50/0.3	SS-38	MOUNT LAUREL FORMATION: Clayey SAND (SC), dark olive gray (5Y 3/2), very dense, moist to wet, fine to medium sand, few subangular to subrounded coarse sand, strong HCl reaction, trace to few glauconite (continued)
-162.2	175.0	50/0.3								50/0.3	SS-39	175.0ft: Trace shell fragments
-167.2	180.0	50/0.3								50/0.3	SS-40	
-172.2	185.0	12	20	44						64	SS-41	185.0ft: Trace coarse sand S. Johnson takes over as Rlg Geologist
-177.2	190.0	13	24	35						59	SS-42	190.0ft: Dark gray (5Y 4/1), weak HCl reaction
-182.2	195.0	8	23	28						51	SS-43	195.0ft: No HCl reaction, trace glauconite
-187.2	200.0	20	80/0.5							100/1.0	SS-44	185.2 MOUNT LAUREL FORMATION: Silty SAND (SM), dark greenish gray (5GY 4/1), very dense, wet, fine to medium sand, no HCl reaction, trace to few glauconite
-192.2	205.0											192.2 MOUNT LAUREL FORMATION: Poorly graded SAND with silt (SP-SM), dark greenish gray (10GY 4/1), very dense, wet, fine to medium sand, no HCl reaction, trace glauconite
-197.2	210.0	48	52/0.2							100/0.7	SS-45	
-207.2	220.0	55	45/0.2							100/0.7	SS-46	220.0ft: Weak HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09 GFJ PSEG ESP.GDI 7/10/09



PERMIT NO.: P200900084		DRILLER: G. McAneny / R. Bartholomew			NJ LICENSE NO.: 0024058 / 0001383		GEOLOGIST: R. Clark / S. Johnson					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)				
BORING NO.: NB-1		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND				
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)		EASTING: 198469.1 US ft (NAD83)		24 HR. 11.0						
TOTAL DEPTH: 600.9 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-2)					
DATE STARTED: 1/13/09		COMPLETED: 2/9/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-211.6					Continued from previous page							
-217.2	230.0	36	64/0.3							100/0.8	SS-47	MOUNT LAUREL FORMATION: Poorly graded SAND with silt (SP-SM), dark greenish gray (10GY 4/1), very dense, wet, fine to medium sand, no HCl reaction, trace glauconite (<i>continued</i>) 230.0ft: Trace friable layers, no HCl reaction
-227.2	240.0	25	38	62/0.4						100/0.8	SS-48	MOUNT LAUREL FORMATION: Silty SAND (SM), very dark greenish gray (5GY 3/1), very dense, wet, fine to medium sand, weak HCl reaction, trace glauconite
-237.2	250.0	8	9	14						23	SS-49	MOUNT LAUREL FORMATION: Clayey SAND (SC), very dark gray (2.5Y 3/1), medium dense, wet, fine to medium sand, weak HCl reaction
-247.2	260.0	7	17	32						49	SS-50	MOUNT LAUREL FORMATION: Silty SAND (SM), dark gray (5Y 4/1), dense, wet, fine sand, weak HCl reaction
-257.2	270.0	5	12	14						26	SS-51	WENONAH FORMATION: Sandy LEAN CLAY (CL), very dark gray (N 3/), very stiff, wet, fine sand, weak HCl reaction
-267.2	280.0											

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900084		DRILLER: G. McAneny / R. Bartholomew			NJ LICENSE NO.: 0024058 / 0001383		GEOLOGIST: R. Clark / S. Johnson						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)				
BORING NO.: NB-1		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND					
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)		EASTING: 198469.1 US ft (NAD83)			24 HR. 11.0						
TOTAL DEPTH: 600.9 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.5 ft			HAMMER (ID): 140 lb Auto. (CTB-2)					
DATE STARTED: 1/13/09		COMPLETED: 2/9/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-267.7					Continued from previous page								
		8	20	42							SS-52		MARSHALLTOWN FORMATION: Clayey SAND (SC), very dark gray (N 3/), very dense, wet, fine sand, trace friable zones, strong HCl reaction, trace glauconite (continued)
													285.0ft: Bit chatter to 289.0ft
-277.2	290.0	9	17	17							SS-53		MARSHALLTOWN FORMATION: Silty SAND (SM), very dark gray (N 3/), dense, wet, fine to medium sand, strong HCl reaction, few glauconite
-287.2	300.0	15	32	68/0.4						100/0.9	SS-54		300.0ft: Greenish black (10Y 2.5/1), very dense, weak HCl reaction, trace to few glauconite
-297.2	310.0	5	14	20							SS-55		ENGLISHTOWN FORMATION: Clayey SAND (SC), very dark gray (N 3/), dense, moist, fine sand, no HCl reaction, trace glauconite
-307.2	320.0	32	45	55/0.3							SS-56		ENGLISHTOWN FORMATION: FAT CLAY (CH), black (N 2.5/), hard, moist, few fine sand, weak HCl reaction
-317.2	330.0	8	11	14							SS-57		330.0ft: Very stiff, no HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09.GP! PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900084		DRILLER: G. McAneny / R. Bartholomew			NJ LICENSE NO.: 0024058 / 0001383		GEOLOGIST: R. Clark / S. Johnson					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)				
BORING NO.: NB-1		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND				
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)		EASTING: 198469.1 US ft (NAD83)			24 HR. 11.0					
TOTAL DEPTH: 600.9 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-2)					
DATE STARTED: 1/13/09		COMPLETED: 2/9/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-323.8					Continued from previous page							
-327.2	340.0	5	16	30							SS-58	340.0ft: Hard
-337.2	350.0	19	23	26							SS-59	349.0ft: WOODBURY FORMATION: FAT CLAY (CH), black (N 2.5/), hard, moist, few fine sand, weak HCl reaction (continued)
-347.2	360.0	5	10	17							SS-60	360.0ft: Very dark gray (10Y 3/1), very stiff
-357.2	370.0	4	9	12							SS-61	370.0ft: Trace mica, PP=4.0 tsf
-367.2	380.0	5	5	14							SS-62	380.0ft: Trace shell fragments, PP=4.5 tsf
-377.2	390.0	20	23	25							SS-63	385.0ft: MERCHANTVILLE FORMATION: Sandy LEAN CLAY (CL), greenish black (10GY 2.5/1), hard, moist, fine sand, no HCl reaction, few glauconite

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900084		DRILLER: G. McAneny / R. Bartholomew		NJ LICENSE NO.: 0024058 / 0001383		GEOLOGIST: R. Clark / S. Johnson						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251						
BORING NO.: NB-1		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		FLUID LEVEL (ft)						
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)		EASTING: 198469.1 US ft (NAD83)		0 HR. ND						
TOTAL DEPTH: 600.9 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-2)						
DATE STARTED: 1/13/09		COMPLETED: 2/9/09		HOLE DIA.: 4"		ROD TYPE: NWJ						
BITS USED: 3-7/8" Drag Bit												
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-379.9					Continued from previous page							
-387.2	400.0	15	22	30						SS-64		MERCHANTVILLE FORMATION: Sandy LEAN CLAY (CL), greenish black (10GY 2.5/1), hard, moist, fine sand, no HCl reaction, few glauconite (continued)
-397.2	410.0	8	14	17						SS-65		400.0ft: PP=4.5 tsf
-407.2	420.0	42	58/0.3							SS-66		410.0ft: Black (N 2.5/), very stiff, trace glauconite, PP=3.0 tsf
-417.2	430.0	12	27	45						SS-67		415.0ft: Bit chatter to 416.0ft
-427.2	440.0	40	60/0.3							SS-68		402.2ft: Bit chatter to 416.0ft
												MAGOTHY FORMATION: SILT with sand (ML), gray (7.5YR 5/1), very dense, wet, fine sand, no HCl reaction
												415.2ft: Bit chatter to 416.0ft
												MAGOTHY FORMATION: Clayey SAND (SC), dark gray (2.5Y 4/1), very dense, moist, trace of lignite
												430.0ft: PP=3.0 tsf
												440.0ft: No recovery-sample pulled out, catcher inverted; replaced with steel catcher
												441.0ft: Hard drilling to 443.0ft
												MAGOTHY FORMATION: Silty SAND (SM), very dark gray (2.5Y 3/1), very dense, moist, fine sand, trace lignite, no HCl reaction
												445.0ft: Bit chatter to 446.0ft

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900084		DRILLER: G. McAneny / R. Bartholomew			NJ LICENSE NO.: 0024058 / 0001383		GEOLOGIST: R. Clark / S. Johnson						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)					
BORING NO.: NB-1		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND					
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)		EASTING: 198469.1 US ft (NAD83)		24 HR. 11.0							
TOTAL DEPTH: 600.9 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-2)						
DATE STARTED: 1/13/09		COMPLETED: 2/9/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-436.0					Continued from previous page								
-437.2	450.0	75	25/0.5							100/1.0	SS-69		MAGOTHY FORMATION: Silty SAND (SM), very dark gray (2.5Y 3/1), very dense, moist, fine sand, trace lignite, no HCl reaction (continued)
-456.5	469.3	24	38	42						80	SS-70		POTOMAC FORMATION: LEAN CLAY (CL), dark gray (2.5Y 4/1), hard, moist, trace fine sand seams, no HCl reaction -Top of Potomac Formation interpreted from geophysical log. 469.3 ft: PP=4.0 tsf
-477.1	489.9									100/0.2	SS-71		POTOMAC FORMATION: Silty SAND (SM), dark gray (2.5Y 4/1), very dense, wet, fine sand, trace lignite, no HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09.GPI PSEG ESP.GDI 7/10/09



PERMIT NO.: P200900084		DRILLER: G. McAney / R. Bartholomew		NJ LICENSE NO.: 0024058 / 0001383		GEOLOGIST: R. Clark / S. Johnson							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251							
BORING NO.: NB-1		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT									
GROUND SURFACE ELEV.: 12.8 US ft (NAVD88)		NORTHING: 234567.6 US ft (NAD83)		EASTING: 198469.1 US ft (NAD83)		FLUID LEVEL (ft) 0 HR. ND 24 HR. 11.0							
TOTAL DEPTH: 600.9 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-2)							
DATE STARTED: 1/13/09		COMPLETED: 2/9/09		HOLE DIA.: 4"		ROD TYPE: NWJ							
						BITS USED: 3-7/8" Drag Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-492.1					Continued from previous page								
-496.7	509.5	100/0.3								100/0.3	SS-72		POTOMAC FORMATION: Silty SAND (SM), dark gray (2.5Y 4/1), very dense, wet, fine sand, trace lignite, no HCl reaction (continued) 509.5ft: Dark gray (10YR 4/1), fine to medium sand
-512.2													POTOMAC FORMATION: SILT (ML), gray (7.5YR 5/1), hard, moist, few fine sand, no HCl reaction
-516.8	529.6	100/0.5								100/0.5	SS-73A/B		POTOMAC FORMATION: Poorly graded SAND with silt (SP-SM), gray (2.5Y 6/1), very dense, wet, fine sand, no HCl reaction -Drill without sampling from 530.1ft to 600.0ft for geophysical testing
-525.2													POTOMAC FORMATION: LEAN CLAY (CL)-Interpreted from geophysical log

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/1/09



PERMIT NO.: P200901783		DRILLER: G. McAneny / J. Schuster			NJ LICENSE NO.: 0024058 / 482821			GEOLOGIST: S. Johnson					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ			MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: NB-1UD		DRILL METHOD: Mud Rotary			SAMPLE METHODS: Shelby Tube/Pitcher Barrel			0 HR.	ND				
GROUND SURFACE ELEV.: 12.7 US ft (NAVD88)		NORTHING: 234556.0 US ft (NAD83)			EASTING: 198459.0 US ft (NAD83)			24 HR.	8.5				
TOTAL DEPTH: 232.3 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.5 ft			HAMMER (ID): 140 lb Auto. (CTB-2)					
DATE STARTED: 3/4/09		COMPLETED: 3/13/09		HOLE DIA.: 6"		ROD TYPE: NWJ		BITS USED: 5-7/8" Drag Bit					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT						SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100			
-43.5					Continued from previous page								
-46.5	59.1										UD-8		55.8ft: Shelby tube UD-8 pushed to 57.8ft in Sandy LEAN CLAY (CL), very dark gray (5Y 3/1), wet, trace gravel, no HCl reaction; recovery=1.9ft; TV=0.6 tsf; PP=0.75 tsf
-49.4	62.0										UD-9		KIRKWOOD FORMATION (continued) 59.1ft: Shelby tube UD-9 pushed to 61.1ft; recovery=0.0ft-lost tube in hole
-55.5	68.1										UD-10		62.0ft: Shelby tube UD-10 pushed to 64.0ft in FAT CLAY (CH), very dark gray (5Y 3/1)wet, no HCl reaction to 63.0ft, then Silty SAND (SM), olive gray (5Y5/2), wet, fine sand, no HCl reaction; recovery=1.8ft -Change sample method to Pitcher Barrel Sampler
-56.4											UD-11	-56.4	68.1ft: Pitcher tube UD-11 advanced to 70.6ft; recovery=0.0ft
-59.4	72.0										UD-12		VINCEN TOWN FORMATION 72.0ft: Pitcher tube UD-12 advanced to 74.5ft in Silty SAND (SM), brown (7.5YR 4/3), wet, strong HCl reaction; recovery=1.0ft
-62.4	75.0										UD-13		75.0ft: Pitcher tube UD-13 advanced to 77.5ft in Silty SAND (SM), yellowish brown (10YR 5/6) wet, fine sand, strong HCl reaction; recovery=1.4ft
-65.4	78.0										UD-14		78.0ft: Pitcher tube UD-14 advanced to 80.5ft in Silty SAND (SM), light gray (2.5Y 7/2), wet, fine sand, strong HCl reaction; recovery=1.3ft
-68.4	81.0										UD-15		81.0ft: Pitcher tube UD-15 advanced to 83.5ft in Silty SAND (SM), yellowish brown (10YR 5/4), wet, fine sand, few indurated zones, strong HCl reaction; recovery=1.7ft
-71.9	84.5										UD-16		84.5ft: Pitcher tube UD-16 advanced to 86.8ft in Silty SAND (SM), yellowish brown (10YR 5/4), wet, fine sand, few indurated zones, strong HCl reaction; recovery=1.2ft
-76.0	88.6										UD-17		88.6ft: Pitcher tube UD-17 advanced to 91.1ft in Silty SAND (SM), greenish gray (10GY 5/1), wet, fine sand, few indurated zones, strong HCl reaction; recovery=1.7ft
-80.0	92.6										UD-18		92.6ft: Pitcher tube UD-18 advanced to 95.1ft in Silty SAND (SM), greenish gray (10GY 5/1), wet, fine sand, few indurated zones, strong HCl reaction; recovery=1.4ft
-83.8	96.4										UD-19		96.4ft: Pitcher tube UD-19 advanced to 98.9ft in Silty SAND (SM), greenish gray (10GY 5/1), wet, fine sand, strong HCl reaction; recovery=2.1ft
-88.0	100.6										UD-20		100.6ft: Pitcher tube UD-20 advanced to 103.1ft in Silty SAND (SM), greenish gray (10GY 5/1), wet, fine sand, mostly indurated, strong HCl reaction; recovery=0.5ft
-91.7	104.3										UD-21		104.3ft: Pitcher tube UD-21 advanced to 106.5ft in Silty SAND (SM), greenish gray (10GY 5/1), wet, fine sand, few indurated to friable zones, strong HCl reaction; recovery=2.0ft
-94.6	107.2										UD-22		107.2ft: Pitcher tube UD-22 advanced to 108.7ft in Silty SAND (SM), greenish gray (10GY 5/1), wet, fine sand, few indurated zones, strong HCl reaction, trace glauconite; recovery=1.0ft

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200901783		DRILLER: G. McAney / J. Schuster			NJ LICENSE NO.: 0024058 / 482821		GEOLOGIST: S. Johnson								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)							
BORING NO.: NB-1UD		DRILL METHOD: Mud Rotary			SAMPLE METHODS: Shelby Tube/Pitcher Barrel			0 HR. ND							
GROUND SURFACE ELEV.: 12.7 US ft (NAVD88)		NORTHING: 234556.0 US ft (NAD83)		EASTING: 198459.0 US ft (NAD83)		24 HR. 8.5									
TOTAL DEPTH: 232.3 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-2)								
DATE STARTED: 3/4/09		COMPLETED: 3/13/09		HOLE DIA.: 6"		ROD TYPE: NWJ		BITS USED: 5-7/8" Drag Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100		
-99.6					Continued from previous page										
-99.9	112.5										UD-23	VINCENTOWN FORMATION (continued) 112.5ft: Pitcher tube UD-23 advanced to 114.4ft in Silty SAND (SM), greenish gray (10GY 5/1), wet, fine sand, few indurated zones, strong HCl reaction; recovery=0.8ft			
												-105.4	HORNERSTOWN FORMATION	118.0	
-108.9	121.5										UD-24	121.5ft: Pitcher tube UD-24 advanced to 124.0ft in Poorly graded SAND with silt (SP-SM), greenish gray (10GY 5/1), wet, fine sand, few indurated to friable zones, strong HCl reaction, trace glauconite; recovery=2.4ft			
-113.0	125.6										UD-25	125.6ft: Pitcher tube UD-25 advanced to 128.1ft in Silty SAND (SM), greenish gray (10GY 5/1), wet, fine sand, strong HCl reaction, trace glauconite; recovery=2.2ft			
-117.1	129.7										UD-26	129.7ft: Pitcher tube UD-26 advanced to 132.2ft in Silty SAND (SM), greenish gray (10GY 5/1), wet, fine sand, few indurated zones, weak HCl reaction, trace glauconite; recovery=1.1ft			
												-126.4	NAVESINK FORMATION	139.0	
-127.4	140.0										UD-27	140.0ft: Pitcher tube UD-27 advanced to 142.5ft in Silty SAND (SM), very dark grayish green (5G 3/2), wet, fine sand, strong HCl reaction, mostly glauconite; recovery=2.3ft			
-131.3	143.9										UD-28	143.9ft: Pitcher tube UD-28 advanced to 146.4ft in Silty SAND (SM), very dark grayish green (5G 3/2), wet, fine sand, strong HCl reaction, trace shell fragments, mostly glauconite; recovery=2.4ft			
-135.0	147.6										UD-29	147.6ft: Pitcher tube UD-29 advanced to 150.1ft in Clayey SAND (SC), very dark grayish green (5G 3/2), wet, fine sand, strong HCl reaction, little shell fragments, mostly glauconite; recovery=0.8ft			
-139.5	152.1										UD-30	152.1ft: Pitcher tube UD-30 advanced to 154.6ft in Clayey SAND (SC), greenish black (5G 2.5/1), wet, fine sand, weak HCl reaction, trace shell fragments, mostly glauconite; recovery=1.3ft			
-143.3	155.9										UD-31	155.9ft: Pitcher tube UD-31 advanced to 158.4ft in Silty SAND (SM), very dark grayish green (5G 3/2), wet, fine sand, strong HCl reaction, mostly glauconite; recovery=1.9ft			
-147.5	160.1										UD-32	160.1ft: Pitcher tube UD-32 advanced to 162.6ft in Clayey SAND (SM), very dark grayish green (5G 3/2), to black (5Y 2.5/1), wet, fine sand, strong HCl reaction, little shell fragments, mostly glauconite; recovery=2.3ft			
-150.7	163.3										UD-33	163.3ft: Pitcher tube UD-33 advanced to 165.8ft in Clayey SAND (SC), very dark gray (5Y 3/1), moist, fine to coarse sand, trace gravel, strong HCl reaction; recovery=1.6ft			
-154.9	167.5										UD-34		-150.4	MOUNT LAUREL FORMATION	163.0

PSEG ESP BORE PSEG ESP 7-07-09.GPI PSEG ESP.GDT 7/10/09



PERMIT NO.: P200901783		DRILLER: G. McAneny / J. Schuster			NJ LICENSE NO.: 0024058 / 482821		GEOLOGIST: S. Johnson						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)					
BORING NO.: NB-1UD		DRILL METHOD: Mud Rotary			SAMPLE METHODS: Shelby Tube/Pitcher Barrel			0 HR. ND					
GROUND SURFACE ELEV.: 12.7 US ft (NAVD88)		NORTHING: 234556.0 US ft (NAD83)		EASTING: 198459.0 US ft (NAD83)		24 HR. 8.5							
TOTAL DEPTH: 232.3 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-2)						
DATE STARTED: 3/4/09		COMPLETED: 3/13/09		HOLE DIA.: 6"		ROD TYPE: NWJ		BITS USED: 5-7/8" Drag Bit					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT						SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100			
-155.7					Continued from previous page								
-170.9	183.5										UD-35		167.5ft: Pitcher tube UD-34 advanced to 168.9ft in Clayey SAND (SC), dark olive gray (5Y 3/2), moist, fine to coarse sand, strong HCl reaction; recovery=1.1ft MOUNT LAUREL FORMATION (continued)
-175.6	188.2										UD-36		183.5ft: Pitcher tube UD-35 advanced to 186.0ft in Silty SAND (SM), dark olive gray (5Y 3/2), moist, fine to coarse sand, trace fine gravel, strong HCl reaction, trace glauconite; recovery=1.8ft
-204.2	216.8										UD-37		188.2ft: Pitcher tube UD-36 advanced to 190.7ft in Silty SAND (SM), dark olive gray (5Y 3/2), wet, fine to coarse sand, trace fine gravel, strong HCl reaction, trace glauconite; recovery=1.1ft
-209.2	221.8										UD-38		216.8ft: Pitcher tube UD-37 advanced to 219.3ft in Poorly graded SAND with silt (SP-SM), dark greenish gray (10GY 4/1), wet, fine to medium sand, no HCl reaction, trace glauconite; recovery=1.8ft
													221.8ft: Pitcher tube UD-38 advanced to 224.3ft in Poorly graded SAND with silt (SP-SM), dark greenish gray (10GY 4/1), wet, fine to coarse sand, no HCl

PSEG ESP BORE PSEG ESP 7-07-09_GPI PSEG ESP.GDI 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MB Date 7/10/09

Checked By JAJ Date 7/10/09

SHEET 1 OF 6

PERMIT NO.: P200900085		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard / S. Johnson								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION			COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)							
BORING NO.: NB-2		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT/Shelby Tube			0 HR. ND							
GROUND SURFACE ELEV.: 8.2 US ft (NAVD88)		NORTHING: 235205.0 US ft (NAD83)		EASTING: 197764.7 US ft (NAD83)		24 HR. ND	ND							
TOTAL DEPTH: 301.5 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 14.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)								
DATE STARTED: 2/20/09		COMPLETED: 3/4/09		HOLE DIA.: 4"	ROD TYPE: NWJ	BITS USED: 3-7/8" Drag Bit								
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
8.2	0.0	6	7	8	Ground Surface							8.2	0.0	
5.7	2.5	6	6	9	15					SS-1		ARTIFICIAL FILL: Sandy CLAY (CL), very dark brown (10YR 2/2), stiff, moist, weak HCl reaction		
3.8	4.4				15					SS-2		2.5ft: Very dark grayish brown (10YR 3/2), no HCl reaction		
1.2	7.0	1	WOH	1	1					UD-1		4.2	4.0	HYDRAULIC FILL: Sandy CLAY (CL), very dark grayish brown (10YR 3/2), very soft, moist, no HCl reaction
-0.8	9.0				1					SS-3		2.2	6.0	-Pushed shelby tube UD-1 from 4.4ft to 6.4ft; recovery=0.2ft
-3.3	11.5				1					UD-2		HYDRAULIC FILL: FAT CLAY (CH), black (N 2.5), very soft, moist, trace fine sand, no HCl reaction		
-5.8	14.0	WOH	WOH	WOH	WOH					UD-3		11.5ft: Pushed shelby tube UD-3 to 13.5ft; recovery=0.0ft		
-11.7	19.9	WOH	WOH	WOH	WOH					SS-4		14.0ft: Trace mica, PP=0.0 tsf		
-16.8	25.0	WOH	WOH	2	2					SS-5				
-21.8	30.0	2	2	2	2					SS-6		25.0ft: Soft		
-23.9	32.1				4					SS-7		30.0ft: PP=0.0 tsf		
-26.8	35.0	WOH	1	WOH	1					UD-4		32.1ft: Pushed shelby tube UD-4 to 34.1ft; recovery=1.9ft		
-31.8	40.0	1	2	1	1					SS-8		35.0ft: Very soft, trace fine sand lenses		
-36.8	45.0	4	3	4	7					SS-9		40.0ft: Very dark gray (N 3/), soft		
-41.7	49.9	WOH	1	1	2					SS-10		-35.3	43.5	ALLUVIUM: Clayey SAND (SC), very dark gray (N 3/), loose, moist, no HCl reaction
-46.8	55.0	5	5	9	14					SS-11A/B		-39.8	48.0	ALLUVIUM: PEAT (PT), brown (10YR 4/3), very soft, moist
										SS-12		-42.3	50.5	ALLUVIUM: Silty SAND (SM), dark gray (N 4/), very loose, wet, fine to medium sand, no HCl reaction
														55.0ft: Medium dense

PSEG ESP BORE PSEG ESP 7-07-09 GPH PSEG ESP GDT 7/10/09



PERMIT NO.: P200900085		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard / S. Johnson						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251						
BORING NO.: NB-2		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT/Shelby Tube		FLUID LEVEL (ft)						
GROUND SURFACE ELEV.: 8.2 US ft (NAVD88)		NORTHING: 235205.0 US ft (NAD83)		EASTING: 197764.7 US ft (NAD83)		0 HR. ND						
TOTAL DEPTH: 301.5 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 14.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)						
DATE STARTED: 2/20/09		COMPLETED: 3/4/09		HOLE DIA.: 4"		ROD TYPE: NWJ						
						BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-47.9					Continued from previous page							
-51.7	59.9	5	9	12								ALLUVIUM: Silty SAND (SM), dark gray (N 4), very loose, wet, fine to medium sand, no HCl reaction (continued)
-56.9	65.1	12	12	7								59.9ft: Greenish gray (10Y 5/1), fine to coarse subrounded sand, trace gravel
-61.8	70.0	7	4	4								KIRKWOOD FORMATION: Silty SAND (SM), dark greenish gray (10GY 4/1), medium dense, wet, fine to medium sand, no HCl reaction
-67.1	75.3	3	2	3								70.0ft: Dark yellowish brown (10YR 4/4), loose
-71.8	80.0	13	19	10								75.3ft: Greenish gray (10GY 5/1), loose, trace glauconite
-73.9	82.1											VINCENTOWN FORMATION: Silty SAND (SM), light yellowish brown (2.5Y 6/3), medium dense, wet, fine to medium sand, few friable to indurated zones, strong HCl reaction, strongly oxidized
-76.8	85.0	15	5	6								82.1ft: Pushed shelly tube UD-5 to 84.1ft; recovery=1.9 ft
-78.7	86.9											85.0ft: Brown (10YR 5/3), moist, trace moderately indurated layers, moderately oxidized
-81.9	90.1	4	4	7								86.9ft: Pushed shelly tube UD-6 to 87.1ft; recovery=0.1ft (Refused on indurated layer)
-83.8	92.0											90.1ft: Grayish brown (10YR 5/2), wet, trace glauconite, weakly oxidized
-86.9	95.1	5	4	27								92.0ft: Shelby tube UD-7 pushed to 93.4ft; recovery=1.4ft
-91.8	100.0	5	6	15								95.1ft: Light grayish brown (10YR 6/2), dense, trace friable to moderately indurated layers
-96.8	105.0	8	8	17								100.0ft: Dark greenish gray (10Y 4/1), medium dense, no oxidation
-101.8	110.0	16	11	14								

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP GDI 7/10/09



PERMIT NO.: P200900085	DRILLER: T. Ward	NJ LICENSE NO.: 0001105	GEOLOGIST: J. Howard / S. Johnson
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-2	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT/Shelby Tube	
GROUND SURFACE ELEV.: 8.2 US ft (NAVD88)		NORTHING: 235205.0 US ft (NAD83)	EASTING: 197764.7 US ft (NAD83)
TOTAL DEPTH: 301.5 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 14.0 ft	HAMMER (ID): 140 lb Auto. (CBT-1)
DATE STARTED: 2/20/09	COMPLETED: 3/4/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag Bit			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION						
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100					
-104.0		Continued from previous page																
-104.8												-104.8	113.0	HORNERSTOWN FORMATION: Silty SAND (SM), dark greenish gray (10Y 4/1), dense, wet, fine to medium sand, trace friable layers, strong HCl reaction, few to little glauconite				
-106.8	115.0	21	14	19							SS-24							
-111.8	120.0	7	9	15							SS-25			120.0ft: Medium dense				
-116.8	125.0	6	13	20							SS-26			125.0ft: Very dark greenish gray (10GY 3/1), dense, few shell fragments, some glauconite				
-121.7	129.9	18	24	25							SS-27			-120.8	129.0	NAVESINK FORMATION: Silty SAND (SM), very dark grayish green (5G 2.5/2), dense, moist, fine sand, trace shell fragments, weak HCl reaction, mostly glauconite		
-126.7	134.9	23	30	45							SS-28					134.9ft: Greenish black (5G 2.5/1), very dense, wet, fine to medium sand, few shell fragments		
-131.8	140.0	19	25	31							SS-29					140.0ft: Trace shell fragments		
-136.8	145.0	19	29	36							SS-30							
-141.7	149.9	22	29	38							SS-31					149.9ft: No HCl reaction		
-146.8	155.0	100/0.5									SS-32					-144.8	153.0	MOUNT LAUREL FORMATION: Silty, Clayey SAND (SC-SM), dark grayish brown (10YR 4/2), very dense, moist, fine to coarse subrounded sand, strong HCl reaction, little glauconite
-151.7	159.9	100/0.2									SS-33						159.9ft: Greenish gray (10Y 5/1), dry, trace shell fragments	
-156.8	165.0	100/0.3									SS-34						165.0ft: Moist, few shell fragments, no HCl reaction	

PSEG ESP BORE PSEG ESP 7-07-09 GPI PSEG ESP.GDI 7/10/09



PERMIT NO.: P200900085	DRILLER: T. Ward	NJ LICENSE NO.: 0001105	GEOLOGIST: J. Howard / S. Johnson
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-2	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT/Shelby Tube	
GROUND SURFACE ELEV.: 8.2 US ft (NAVD88)		NORTHING: 235205.0 US ft (NAD83)	EASTING: 197764.7 US ft (NAD83)
TOTAL DEPTH: 301.5 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 14.0 ft	HAMMER (ID): 140 lb Auto. (CBT-1)
DATE STARTED: 2/20/09	COMPLETED: 3/4/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag Bit			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-160.1		Continued from previous page											
-161.8	170.0										100/0.3	SS-35	MOUNT LAUREL FORMATION: Silty, Clayey SAND (SC-SM), dark grayish brown (10YR 4/2), very dense, moist, fine to coarse subrounded sand, strong HCl reaction, little glauconite (continued)
-166.8	175.0	19	33	60							93	SS-36	175.0ft: Strong HCl reaction, few glauconite
-171.8	180.0	16	25	30							55	SS-37	
-176.8	185.0	15	24	35							59	SS-38	185.0ft: Greenish gray (10Y 6/1)
-181.8	190.0	39	61	0.5							100/1.0	SS-39	MOUNT LAUREL FORMATION: Silty SAND (SM), greenish gray (5GY 5/1), very dense, dry, fine to medium sand, trace indurated layers, strong HCl reaction, trace glauconite
-186.9	195.1	57	43	0.3							100/0.8	SS-40	195.1ft: Moist, no HCl reaction
-191.8	200.0	80	20	0.1							100/0.6	SS-41	200.0ft: Weak HCl reaction
-201.8	210.0	52	48	0.3							100/0.8	SS-42	
-211.7	219.9	40	60	0.5							100/1.0	SS-43	219.9ft: Strong HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900085		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard / S. Johnson						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)					
BORING NO.: NB-2		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT/Shelby Tube					0 HR. ND				
GROUND SURFACE ELEV.: 8.2		US ft (NAVD88)		NORTHING: 235205.0		US ft (NAD83)		EASTING: 197764.7		24 HR. ND				
TOTAL DEPTH: 301.5 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 14.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)						
DATE STARTED: 2/20/09		COMPLETED: 3/4/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-216.2		Continued from previous page												
-221.8	230.0	8	20	35						SS-44		MOUNT LAUREL FORMATION: Silty SAND (SM), greenish gray (5GY 5/1), very dense, dry, fine to medium sand, trace indurated layers, strong HCl reaction, trace glauconite (continued)		
-231.8	240.0	9	19	28						SS-45		230.0ft: Greenish black (10Y 2.5/1), trace mica		
-241.8	250.0	10	14	26						SS-46		240.0ft: Dense		
-251.8	260.0	11	16	21						SS-47		-249.8 258.0 WENONAH FORMATION: Sandy LEAN CLAY (CL), greenish black (10Y 2.5/1), hard, moist, strong HCl reaction, trace mica, trace to few glauconite		
-261.8	270.0	7	16	24						SS-48		-259.8 268.0 WENONAH FORMATION: Silty, Clayey SAND (SC-SM), greenish black (10Y 2.5/1), dense, moist, fine to medium sand, strong HCl reaction, trace to few glauconite		
-271.8	280.0													-264.8 273.0 MARSHALLTOWN FORMATION: Sandy LEAN CLAY (CL), black (N 2.5/), very stiff, moist, strong HCl reaction, trace glauconite

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900085		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard / S. Johnson				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: NB-2		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT/Shelby Tube			0 HR. ND				
GROUND SURFACE ELEV.: 8.2		US ft (NAVD88)		NORTHING: 235205.0		US ft (NAD83)		EASTING: 197764.7		US ft (NAD83)	24 HR. ND	
TOTAL DEPTH: 301.5 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 14.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)				
DATE STARTED: 2/20/09		COMPLETED: 3/4/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-272.3					Continued from previous page							
		9	11	15						SS-49		MARSHALLTOWN FORMATION: Sandy LEAN CLAY (CL), black (N 2.5/), very stiff, moist, strong HCl reaction, trace glauconite (<i>continued</i>)
-281.8	290.0											
		16	22	34						SS-50		MARSHALLTOWN FORMATION: Silty SAND (SM), black (N 2.5/), very dense, moist, fine to medium sand, strong HCl reaction, trace glauconite
-291.8	300.0											
		7	11	17						SS-51		ENGLISHTOWN FORMATION: Sandy LEAN CLAY (CL), black (N 2.5/), very stiff, moist, trace shell fragments, no HCl reaction
												Boring terminated at 301.5 feet.
												Boring closed by tremie method with cement-bentonite grout on 3/05/09.

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDI 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MAN Date 7/10/09

Checked By JAN Date 7/10/09

SHEET 1 OF 4

PERMIT NO.: P200900086		DRILLER: R. Bartholomew		NJ LICENSE NO.: 0001383		GEOLOGIST: S. Johnson								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)						
BORING NO.: NB-3		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT				0 HR. ND						
GROUND SURFACE ELEV.: 7.4 US ft (NAVD88)		NORTHING: 234554.7 US ft (NAD83)		EASTING: 197895.8 US ft (NAD83)		24 HR. 9.0								
TOTAL DEPTH: 200.3 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 13.7 ft		HAMMER (ID): 140 lb Auto. (CTB-2)								
DATE STARTED: 2/17/09		COMPLETED: 2/20/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
7.4					Ground Surface							7.4	0.0	
4.9	2.5	8	14	25	● 39					SS-1		ARTIFICIAL FILL: Silty SAND (SM), light olive brown (2.5Y 5/3), dense, moist, fine to coarse sand, little angular gravel, weak HCl reaction		
2.4	5.0	2	6	5	● 11					SS-2		2.5ft: Black (N 2.5/), medium dense, fine to medium sand		
-0.1	7.5	WOH	WOH	WOH	● 00					SS-3		HYDRAULIC FILL: LEAN CLAY (CL), very dark gray (N 3/), very soft, wet, trace fine sand, no HCl reaction	5.0	
-2.2	9.6	WOH	WOH	WOH	● 00					SS-4		HYDRAULIC FILL: SILT (ML), very dark gray (N 3/), very soft, wet, trace fine sand, trace organic matter, no HCl reaction	9.0	
-4.4	11.8	WOH	WOH	WOH	● 00					SS-5		HYDRAULIC FILL: FAT CLAY with sand (CH), very dark gray (N 3/), very soft, wet, fine to medium sand, trace organics, no HCl reaction	11.5	
-7.6	15.0	WOH	WOH	WOH	● 00					SS-6		11.8ft: PP=0.0 tsf		
-12.8	20.2	WOH	WOH	WOH	● 00					SS-7		HYDRAULIC FILL: SILT (ML), very dark gray (N 3/), very soft, wet, trace organics, no HCl reaction, trace fine sand	18.0	
-17.7	25.1	2	4	2	● 06					SS-8		25.1ft: Medium stiff	25.6	
-22.7	30.1	WOH	WOH	WOH	● 00					SS-9A/B		HYDRAULIC FILL: Silty SAND (SM), dark greenish gray (N 4/), loose, wet, fine sand	28.0	
-27.7	35.1	WOH	WOH	WOH	● 00					SS-10		HYDRAULIC FILL: SILT with sand (ML), very dark gray (N 3/), very soft, wet, no HCl reaction, little fine sand partings		
-32.3	39.7	1	1	1	● 02					SS-11		ALLUVIUM: Silty SAND (SM), dark gray (N 4/), very loose, wet, fine to coarse sand	38.0	
-37.3	44.7	WOH	2	3	● 05					SS-12A/B		ALLUVIUM: FAT CLAY (CH), very dark gray (N 3/), very soft, wet, trace organics, no HCl reaction	40.2	
-42.2	49.6	6	7	6	● 13					SS-13		ALLUVIUM: Sandy SILT (ML), dark gray (N 4/), medium stiff, wet, fine to medium subrounded to angular sand, trace organics	43.0	
-47.2	54.6	WOH	WOH	WOH	● 00					SS-14A/B		ALLUVIUM: Poorly graded SAND with silt (SP-SM), gray (N 6/), medium dense, wet, fine to medium sand, no HCl reaction	48.0	
										SS-15		KIRKWOOD FORMATION: FAT CLAY (CH), greenish gray (5G 5/1), stiff, wet, few fine to medium sand, no HCl reaction, PP=1.5 tsf	50.6	
												54.6ft: PP=1.0 tsf		

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900086		DRILLER: R. Bartholomew			NJ LICENSE NO.: 0001383			GEOLOGIST: S. Johnson						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)					
BORING NO.: NB-3		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND						
GROUND SURFACE ELEV.: 7.4 US ft (NAVD88)		NORTHING: 234554.7 US ft (NAD83)		EASTING: 197895.8 US ft (NAD83)			24 HR. 9.0							
TOTAL DEPTH: 200.3 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.7 ft			HAMMER (ID): 140 lb Auto. (CTB-2)						
DATE STARTED: 2/17/09		COMPLETED: 2/20/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-48.7		Continued from previous page												
-50.6	59.6	WOH	WOH	WOH							SS-16	-50.6	58.0	KIRKWOOD FORMATION: SILT (ML), dark gray (5YR 4/1), very soft, wet, trace fine sand, trace mica, no HCl reaction 59.6ft: PP=0.75 tsf
-57.2	64.6	5	2	4							SS-17	-56.6	64.0	64.0ft: Bit chatter to 64.6ft VINCENTOWN FORMATION: Silty SAND (SM), olive brown (2.5Y 4/4), loose, wet, fine to medium sand, strong HCl reaction, trace glauconite, moderately oxidized
-62.2	69.6	5	3	5							SS-18			
-67.2	74.6	10	8	8							SS-19	-65.6	73.0	VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), dark greenish gray (5GY 3/1), medium dense, wet, fine to medium sand, trace indurated layers, strong HCl reaction, trace to few glauconite
-72.2	79.6	11	17	16							SS-20			79.6ft: Dark greenish gray (5GY 4/1), dense, trace friable layers
-77.2	84.6	14	9	8							SS-21	-75.6	83.0	VINCENTOWN FORMATION: Silty SAND (SM), dark greenish gray (5GY 4/1), medium dense, wet, fine to medium sand, trace indurated layers, strong HCl reaction, trace glauconite
-82.2	89.6	10	10	25							SS-22	-80.6	88.0	VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), dark greenish gray (5GY 4/1), dense, wet, fine to medium sand, weak HCl reaction, trace glauconite, trace indurated layers
-87.2	94.6	25	24	25							SS-23	-85.6	93.0	VINCENTOWN FORMATION: Silty SAND (SM), dark greenish gray (5GY 4/1), dense, wet, fine sand, trace friable layers, strong HCl reaction, trace glauconite
-92.2	99.6	8	9	11							SS-24			99.6ft: Greenish gray (10Y 5/1), medium dense
-97.2	104.6	5	66	33							SS-25			104.6ft: Very dense, few friable to indurated layers
-102.2	109.6	50/0.5									SS-26	-100.6	108.0	VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), dark greenish gray (5GY 4/1), very dense, wet, fine to medium sand, strong HCl reaction, trace glauconite
-104.2	111.6										SS-27			111.6ft: No recovery, indurated layer

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900086		DRILLER: R. Bartholomew		NJ LICENSE NO.: 0001383		GEOLOGIST: S. Johnson									
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)							
BORING NO.: NB-3		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT				0 HR. ND							
GROUND SURFACE ELEV.: 7.4 US ft (NAVD88)		NORTHING: 234554.7 US ft (NAD83)		EASTING: 197895.8 US ft (NAD83)		24 HR. 9.0									
TOTAL DEPTH: 200.3 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 13.7 ft		HAMMER (ID): 140 lb Auto. (CTB-2)									
DATE STARTED: 2/17/09		COMPLETED: 2/20/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100		
-104.8					Continued from previous page										
-107.2	114.6	10	12	14								-105.6	113.0	HORNERSTOWN FORMATION: Silty SAND (SM), dark greenish gray (5GY 4/1), medium dense, wet, fine to medium sand, strong HCl reaction, trace to few glauconite	
-112.2	119.6	13	30	19										119.6ft: Dense	
-117.2	124.6	10	12	16										124.6ft: Medium dense	
-122.2	129.6	25	21	21										129.6ft: Dense, trace friable layers	
-127.2	134.6	18	28	33									-124.6	132.0	NAVESINK FORMATION: Clayey SAND (SC), very dark greenish gray (5G 3/2), very dense, wet, fine sand, trace to few shell fragments, mostly glauconite
-132.2	139.6	30	40	40									-129.6	137.0	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (10BG 2.5/1), very dense, wet, fine sand, weak HCl reaction, little shell fragments, mostly glauconite
-137.2	144.6	11	20	18									-135.6	143.0	NAVESINK FORMATION: Clayey SAND (SC), very dark greenish gray (10Y 3/1), dense, wet, fine to medium sand, weak HCl reaction, mostly glauconite
-142.2	149.6	20	37	52									-140.6	148.0	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (5G 3/2), very dense, wet, fine sand, weak HCl reaction, mostly glauconite
-147.2	154.6	37	38	45									-150.6	158.0	MOUNT LAUREL FORMATION: Clayey SAND (SC), dark greenish gray (10Y 4/1), very dense, moist, fine to coarse subrounded sand, strong HCl reaction
-152.2	159.6	30	39	61/0.3									-155.6	163.0	MOUNT LAUREL FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), very dense, wet, fine to coarse subangular to subrounded sand, trace indurated layers, trace shell fragments, weak HCl reaction, little glauconite
-157.2	164.6	100/0.3													

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900086		DRILLER: R. Bartholomew			NJ LICENSE NO.: 0001383			GEOLOGIST: S. Johnson					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)				
BORING NO.: NB-3		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND					
GROUND SURFACE ELEV.: 7.4 US ft (NAVD88)		NORTHING: 234554.7 US ft (NAD83)		EASTING: 197895.8 US ft (NAD83)			24 HR. 9.0						
TOTAL DEPTH: 200.3 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 13.7 ft			HAMMER (ID): 140 lb Auto. (CTB-2)					
DATE STARTED: 2/17/09		COMPLETED: 2/20/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-160.9					Continued from previous page								
-162.2	169.6	100/0.2								100/0.2	SS-39	MOUNT LAUREL FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), very dense, wet, fine to coarse subangular to subrounded sand, trace indurated layers, trace shell fragments, weak HCl reaction, little glauconite (continued) 169.6ft: Dark greenish gray (10Y 4/1)	
-167.2	174.6	100/0.4								100/0.4	SS-40		
-172.2	179.6	18	48	52/0.4						100/0.9	SS-41	MOUNT LAUREL FORMATION: Clayey SAND (SC), dark greenish gray (5GY 4/1), very dense, wet, fine sand, trace indurated layers, strong HCl reaction, trace glauconite	
-177.2	184.6	16	24	45						69	SS-42	184.6ft: Weak HCl reaction	
-182.2	189.6	19	24	42						66	SS-43		
-187.2	194.6	43	57/0.3							100/0.8	SS-44	MOUNT LAUREL FORMATION: Silty SAND (SM), greenish gray (5GY 6/1), very dense, wet, fine to coarse subrounded sand, no HCl reaction, trace glauconite	
-192.2	199.6	75	25/0.2							100/0.7	SS-45	MOUNT LAUREL FORMATION: Poorly graded SAND with silt (SP-SM), dark green gray (5GY 4/1), very dense, wet, fine to coarse sand, no HCl reaction, trace glauconite	
												193.0	Boring terminated at 200.3 feet.
												197.0	Boring closed by tremie method with cement-bentonite grout on 2/20/09.
												200.3	

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDI 7/10/09



GEOTECHNICAL BORING LOG

Prepared By mm Date 7/10/09

Checked By Jo J Date 7/10/09

SHEET 1 OF 4

PERMIT NO.: P200900087	DRILLER: D. Osuch	NJ LICENSE NO.: 0024289	GEOLOGIST: M. Lear / S. Johnson
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-4	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT/Shelby Tube	
GROUND SURFACE ELEV.: 11.5 US ft (NAVD88)		NORTHING: 233960.4 US ft (NAD83)	EASTING: 198139.0 US ft (NAD83)
TOTAL DEPTH: 201.3 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 13.5 ft	HAMMER (ID): 140 lb Auto. (CTB-3)
DATE STARTED: 2/19/09	COMPLETED: 2/25/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag Bit			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
11.5					Ground Surface							11.5	0.0	
11.5	0.0	25	47	52							SS-1	ARTIFICIAL FILL: Silty GRAVEL (GM), dark grayish brown (10YR 4/2), very dense, dry to moist, angular, trace organics	9.5	2.0
9.0	2.5	2	2	2							SS-2	HYDRAULIC FILL: FAT CLAY (CH), very dark gray (5Y 3/1), soft to very soft, moist, trace to little organics, trace to few fine sand, PP=0.25 tsf		
6.5	5.0	WOH	WOH	WOH							SS-3	PP=0.0 tsf for samples SS-3 to SS-12		
4.0	7.5	WOH	WOH	WOH							SS-4			
1.5	10.0	WOH	WOH	WOH							SS-5			
-1.0	12.5	WOH	WOH	WOH							SS-6			
-3.5	15.0	WOH	WOH	WOH							SS-7			
-6.0	17.5	WOH	WOH	WOH							SS-8	17.5ft: Dark gray (5Y 4/1)		
-8.5	20.0	WOH	WOH	WOH							SS-9			
-11.0	22.5	WOH	WOH	WOH							SS-10			
-13.5	25.0	WOH	WOH	WOH							SS-11	25.0ft: Trace fine sand partings		
-16.0	27.5	WOH	WOH	WOH							SS-12			
-18.5	30.0	2	4	4							SS-13	HYDRAULIC FILL: Silty SAND (SM), very dark gray (5Y 3/1), loose, wet, fine sand, no HCl reaction	-18.0	29.5
-21.0	32.5	WOH	WOH	WOH							SS-14	HYDRAULIC FILL: FAT CLAY with sand (CH), very dark gray (5Y 3/1), very soft, wet, little fine sand, no HCl reaction	-20.5	32.0
-23.5	35.0	WOH	WOH	WOH							SS-15	35.0ft: Few fine sand partings, PP=0.0 tsf		
-26.0	37.5	2	2	3							SS-16	ALLUVIUM: Clayey SAND (SC), very dark gray (5Y 3/1), loose, wet, fine to coarse sand, trace gravel, no HCl reaction	-25.5	37.0
-28.5	40.0	2	2	2							SS-17	ALLUVIUM: Sandy FAT CLAY (CH), very dark gray (5Y 3/1), soft, wet, fine to coarse sand, trace organics	-28.0	39.5
-31.0	42.5	WOH	2	3							SS-18	42.5ft: Medium stiff		
-33.5	45.0	4	9	11							SS-19	ALLUVIUM: Poorly graded SAND (SP), greenish gray (10Y 5/1), medium dense, wet, fine to coarse sand, trace subrounded fine gravel	-33.0	44.5
-36.0	47.5	14	11	9							SS-20	ALLUVIUM: Clayey SAND (SC), light greenish gray (5GY 7/1), medium dense, moist, fine to medium sand, trace gravel	-35.5	47.0
-38.5	50.0	5	11	12							SS-21	ALLUVIUM: Clayey GRAVEL (GC), brown (7.5YR 5/2), medium dense, wet, fine to coarse subrounded to angular gravel, few fine sand	-38.0	49.5
-41.0	52.5	5	6	6							SS-22			
-43.5	55.0	2	2	2							SS-23			54.5

PSEG ESP BORE PSEG ESP 7-07-09 GRJ PSEG ESP GDT 7/10/09



PERMIT NO.: P200900087	DRILLER: D. Osuch	NJ LICENSE NO.: 0024289	GEOLOGIST: M. Lear / S. Johnson
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-4	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT/Shelby Tube	
GROUND SURFACE ELEV.: 11.5 US ft (NAVD88)		NORTHING: 233960.4 US ft (NAD83)	EASTING: 198139.0 US ft (NAD83)
TOTAL DEPTH: 201.3 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 13.5 ft	HAMMER (ID): 140 lb Auto. (CTB-3)
DATE STARTED: 2/19/09	COMPLETED: 2/25/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag Bit			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-44.6					Continued from previous page							
-45.5	57.0										UD-1	KIRKWOOD FORMATION: FAT CLAY (CH), Olive Gray (5Y 5/2), soft, moist, trace organics, trace fine sand, PP=0.0 tsf (continued) 57.0ft: Pushed shelly tube UD-1 to 59.0ft; recovery=2.0ft, PP=1.75 tsf, TV=0.7 tsf 59.0ft: Pushed shelly tube UD-2 to 61.0ft; recovery=2.0ft, PP=0.75 tsf, TV=0.4 tsf 61.0ft: Medium stiff, PP=0.5 tsf
-47.5	59.0										UD-2	
-50.0	61.5										SS-24	
-53.5	65.0	WOH	WOH	6							SS-25	65.0ft: Very soft, few to little organics, few fine sand, PP=0.25 tsf
-56.0	67.5										SS-26	55.5
-58.5	70.0	4	10	32							SS-27	58.0
-60.5	72.0	4	4	10							UD-3	KIRKWOOD FORMATION: Silty GRAVEL with sand (GM), dark gray (5Y 4/1), and brown (7.5YR 4/3), dense, moist, to wet, subangular gravel, fine to coarse sand, few organics, trace glauconite VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), medium dense, moist to wet, fine to medium sand, trace gravel, trace friable zones, weak HCl reaction, trace to few glauconite 72.0ft: Pushed shelly tube UD-3 to 73.6ft; recovery=1.5ft
-63.5	75.0	5	15	8							SS-28	
-65.5	77.0	13	5	7							UD-4/SS-29	77.0ft: Attempted shelly tube UD-4, refused with no penetration; Few friable to moderately indurated layers
-68.5	80.0	11	15	11							SS-30	80.0ft: Trace friable layers, strong HCl reaction, trace glauconite
-71.0	82.5	5	8	12							SS-31	82.5ft: Weak HCl reaction
-73.5	85.0	6	6	30							SS-32	85.0ft: Dense
-76.0	87.5	8	9	28							SS-33	
-78.5	90.0	13	10	12							SS-34	90.0ft: Medium dense
-81.0	92.5	6	7	11							SS-35	
-83.5	95.0	19	78	22							SS-36	95.0ft: Very dense, few moderately indurated zones, strong HCl reaction
-86.0	97.5	6	8	13							SS-37	97.5ft: Medium dense, trace friable zones, weak HCl reaction
-88.5	100.0	7	7	9							SS-38	
-91.0	102.5	5	6	7							SS-39	102.5ft: Strong HCl reaction
-93.0	104.5										UD-5	104.5ft: Pushed shelly tube UD-5 to 105.5ft; recovery=0.0ft
-96.0	107.5	5	8	12							SS-40	
-98.5	110.0	13	12	86							SS-41	110.0ft: Very dense, trace to few moderately indurated layers

PSEG ESP BORE PSEG ESP 7-07-09 GPI PSEG ESP GDT 7/10/09



PERMIT NO.: P200900087	DRILLER: D. Osuch	NJ LICENSE NO.: 0024289	GEOLOGIST: M. Lear / S. Johnson
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-4	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT/Shelby Tube	
GROUND SURFACE ELEV.: 11.5 US ft (NAVD88)		NORTHING: 233960.4 US ft (NAD83)	EASTING: 198139.0 US ft (NAD83)
TOTAL DEPTH: 201.3 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 13.5 ft	HAMMER (ID): 140 lb Auto. (CTB-3)
DATE STARTED: 2/19/09	COMPLETED: 2/25/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag Bit			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-100.7		Continued from previous page												
-101.0	112.5	49	24	20							SS-42	VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), medium dense, moist to wet, fine to medium sand, trace gravel, trace friable zones, weak HCl reaction, trace to few glauconite		
-103.5	115.0	6	10	15							SS-43	(continued) 112.5ft: Dense, trace to few friable layers 115.0ft: Medium dense		
-106.0	117.5	100/0.4									SS-44	VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), greenish gray (10Y 5/1), very dense, wet, mostly indurated, trace glauconite		
-108.5	120.0	6	9	10							SS-45	VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), medium dense, wet, fine sand, strong HCl reaction, trace glauconite		
-111.0	122.5	100/0.3									SS-46	122.5ft: Mostly indurated		
-113.5	125.0	8	10	13							SS-47	HORNERSTOWN FORMATION: Silty SAND (SM), dark greenish gray (10Y 4/1), medium dense, wet, fine sand, strong HCl reaction, trace glauconite		
-116.0	127.5	10	12	15							SS-48	HORNERSTOWN FORMATION: Poorly graded SAND with silt (SP-SM), dark greenish gray (10Y 4/1), medium dense, wet, fine to medium sand, strong HCl reaction, trace to few glauconite		
-118.5	130.0	10	12	17							SS-49			
-121.0	132.5	65	35/0.1								SS-50	HORNERSTOWN FORMATION: Silty SAND (SM), dark greenish gray (5GY 4/1), very dense, wet, fine sand, little friable layers, weak HCl reaction, few glauconite		
-123.5	135.0	12	15	17							SS-51	HORNERSTOWN FORMATION: Poorly graded SAND with silt (SP-SM), very dark greenish gray (5GY 3/1), dense, wet, fine to medium sand, weak to strong HCl reaction, few glauconite		
-126.0	137.5	10	17	22							SS-52			
-128.5	140.0	12	17	22							SS-53	140.0ft: Trace shell fragments		
-131.0	142.5	17	22	32							SS-54	NAVESINK FORMATION: Clayey SAND (SC), very dark greenish gray (10BG 3/1), very dense, wet, fine sand, trace shell fragments, weak HCl reaction, mostly glauconite		
-133.5	145.0	26	35	40							SS-55	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (10BG 3/1), very dense, wet, fine sand, trace shell fragments, no to weak HCl reaction, mostly glauconite		
-136.0	147.5	22	33	37							SS-56	147.5ft: Greenish black (10BG 2.5/1)		
-138.5	150.0	16	28	35							SS-57			
-141.0	152.5	14	20	28							SS-58	NAVESINK FORMATION: Clayey SAND (SC), greenish black (10BG 2.5/1), dense, wet, fine sand, weak HCl reaction, mostly glauconite		
-143.5	155.0	20	27	37							SS-59	155.0ft: Very dense, trace shell fragments		
-146.0	157.5	25	37	46							SS-60	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (5G 3/2), very dense, wet, fine sand, weak HCl reaction, mostly glauconite		
-148.5	160.0	28	31	37							SS-61	NAVESINK FORMATION: Clayey SAND (SC), very dark grayish green (5G 3/2), very dense, wet, fine sand, no to weak HCl reaction, mostly glauconite		
-151.0	162.5	28	36	49							SS-62	162.5ft: Trace shell fragments		
-153.5	165.0	16	28	65							SS-63	MOUNT LAUREL FORMATION: Clayey SAND (SC), very dark gray (5Y 3/1), very dense, moist, fine to coarse sand, strong HCl reaction, trace to few glauconite		
-156.0	167.5	70	30/0.3								SS-64			

PSEG ESP BORE PSEG ESP 7-07-09 GPT PSEG ESP GDT 7/10/09

100/0.8



PERMIT NO.: P200900087		DRILLER: D. Osuch		NJ LICENSE NO.: 0024289		GEOLOGIST: M. Lear / S. Johnson							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251							
BORING NO.: NB-4		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT/Shellby Tube		FLUID LEVEL (ft)							
GROUND SURFACE ELEV.: 11.5 US ft (NAVD88)		NORTHING: 233960.4 US ft (NAD83)		EASTING: 198139.0 US ft (NAD83)		0 HR. ND							
TOTAL DEPTH: 201.3 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 13.5 ft		HAMMER (ID): 140 lb Auto. (CTB-3)							
DATE STARTED: 2/19/09		COMPLETED: 2/25/09		HOLE DIA.: 4"		ROD TYPE: NWJ							
BITS USED: 3-7/8" Drag Bit													
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-156.8					Continued from previous page								
-158.5	170.0	45	55/0.1							100/0.6	SS-65	-158.0 MOUNT LAUREL FORMATION: Sandy LEAN CLAY (CL), very dark gray (5Y 3/1), hard, moist, fine to coarse sand, strong HCl reaction, PP=4.0 tsf (continued)	169.5
-161.0	172.5	100/0.2								100/0.2	SS-66	-160.5 MOUNT LAUREL FORMATION: Clayey SAND (SC), dark greenish gray (10Y 4/1), very dense, moist, fine to coarse sand, weak HCl reaction, trace glauconite	172.0
-163.5	175.0	100/0.3								100/0.3	SS-67	MOUNT LAUREL FORMATION: Silty SAND (SM), dark greenish gray (10Y 4/1), very dense, moist, fine to coarse sand, weak HCl reaction, trace glauconite	
-166.0	177.5	100/0.2								100/0.2	SS-68	175.0ft: Trace shell fragments	
-168.5	180.0	100/0.5								160/0.5	SS-69		
-171.0	182.5	33	60	40/0.2						160/0.7	SS-70		
-173.5	185.0	23	33	38						71	SS-71		
-176.0	187.5	16	31	39						70	SS-72		
-178.5	190.0	15	29	36						65	SS-73	-178.0 MOUNT LAUREL FORMATION: Clayey SAND (SC), dark gray (5Y 4/1), very dense, wet, fine to coarse sand, weak HCl reaction, trace glauconite	189.5
-181.0	192.5	14	30	38						68	SS-74		
-183.5	195.0	15	25	31						56	SS-75		
-186.0	197.5	19	33	45						78	SS-76		
-188.5	200.0	33	53	47/0.3						100/0.8	SS-77	-187.5 MOUNT LAUREL FORMATION: Silty SAND (SM), gray (5Y 5/1), very dense, wet, fine sand, weak HCl reaction, trace glauconite	199.0
												-189.8 Boring terminated at 201.3 feet.	201.3
												Boring closed by tremie method with cement-bentonite grout on 2/25/09.	

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



GEOTECHNICAL BORING LOG

Prepared By *MMH* Date *7/10/09*

Checked By *JOJ* Date *7/10/09*

SHEET 1 OF 4

PERMIT NO.: P200900091	DRILLER: M. Adams	NJ LICENSE NO.: 0001350	GEOLOGIST: R. Clark
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-5	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT	
GROUND SURFACE ELEV.: 7.8 US ft (NAVD88)		NORTHING: 234891.0 US ft (NAD83)	EASTING: 198445.7 US ft (NAD83)
TOTAL DEPTH: 200.0 ft	DRILL MACHINE: CME-850 ATV	CASING DEPTH: 69.5 ft	HAMMER (ID): 140 lb Auto. (CTB-4)

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
7.8					Ground Surface							7.8	0.0
7.8	0.0	22	25	19	●44					SS-1	▼	ARTIFICIAL FILL: Clayey SAND (SC), yellowish brown (10YR 5/4), dense, moist, fine to coarse sand, few angular gravel, little organics, no HCl reaction	2.0
5.2	2.6	7	5	6	●11					SS-2		ARTIFICIAL FILL: LEAN CLAY with sand and gravel (CL), dark greenish gray (5GY 4/1), stiff, moist, angular gravel, trace organics, PP=1.0 tsf	4.5
2.8	5.0	4	3	3	●6					SS-3		HYDRAULIC FILL: FAT CLAY with sand (CH), greenish black (10Y 3/1), medium stiff, moist, no HCl reaction, PP=1.0 tsf	
0.3	7.5	WOH	WOH	WOH	●0					SS-4		7.5ft: FAT CLAY (CH), very soft, few organics, PP=0.5 tsf	
-2.2	10.0	WOH	WOH	WOH	●0					SS-5		10.0ft: Very dark greenish gray (5GY 3/1), trace organics, PP=0.25 tsf	
-4.7	12.5	WOH	WOH	WOH	●0					SS-6			
-7.2	15.0	WOH	WOH	WOH	●0					SS-7		-6.7	14.5
		WOH	WOH	WOH	●0					SS-8		HYDRAULIC FILL: ELASTIC SILT (MH), very dark greenish gray (5GY 3/1), very soft, moist, trace fine sand, PP=0.25 tsf	
-12.2	20.0	WOR	WOH	WOH	●0					SS-9		20.0ft: PP=0.15 tsf	
-16.7	24.5	WOH	1	1	●2					SS-10		24.5ft: Dark olive gray (5Y 3/2), PP=0.5 tsf	
-21.7	29.5	WOH	WOH	WOH	●0					SS-11		29.5ft: PP=0.25 tsf	
-26.7	34.5	WOH	3	5	●8					SS-12		34.5ft: Medium stiff, few fine sand, trace organics, PP=0.5 tsf	
-31.7	39.5	9	29	36	●65					SS-13A/B		-29.2	37.0
-36.7	44.5	6	4	2	●6					SS-14		ALLUVIUM: Poorly graded SAND with silt and gravel (SP-SM), greenish gray (5GY 5/1), very dense, wet, fine to coarse subangular to subrounded sand, fine to coarse subrounded to angular gravel, trace glauconite	
-41.7	49.5	3	3	4	●7					SS-15		-37.2	45.0
-46.7	54.5	4	4	5	●9							KIRKWOOD FORMATION: FAT CLAY (CH), dark olive gray (5Y 3/2), medium stiff, moist, few fine sand, no HCl reaction, PP=0.5 tsf	
												49.5ft: PP=0.25 tsf	
												54.5ft: Stiff, PP=1.0 tsf	

PSEG ESP BORE PSEG ESP 7-07-09 GPI PSEG ESP GDT 7/10/09



PERMIT NO.: P200900091		DRILLER: M. Adams			NJ LICENSE NO.: 0001350			GEOLOGIST: R. Clark				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION					COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)		
BORING NO.: NB-5		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR.		ND		
GROUND SURFACE ELEV.: 7.8		US ft (NAVD88)		NORTHING: 234891.0		US ft (NAD83)		EASTING: 198445.7		US ft (NAD83)		
TOTAL DEPTH: 200.0 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 69.5 ft			HAMMER (ID): 140 lb Auto. (CTB-4)				
DATE STARTED: 2/6/09		COMPLETED: 2/8/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-48.3					Continued from previous page							
-51.7	59.5	3	4	6							SS-16	KIRKWOOD FORMATION: FAT CLAY (CH), dark olive gray (5Y 3/2), medium stiff, moist, few fine sand, no HCl reaction, PP=0.5 tsf (continued) 59.5ft: FAT CLAY with sand (CH), few subrounded gravel, trace organics, PP=0.25 tsf
-56.7	64.5	15	8	9							SS-17	KIRKWOOD FORMATION: Silty SAND with gravel (SM), dark greenish gray (5GY 4/1), medium dense, wet, fine sand, little subrounded to rounded gravel, no HCl reaction, trace glauconite
-61.7	69.5	36	49	16							SS-18	VINCENTOWN FORMATION: Silty SAND (SM), reddish brown (5Y 4/3), very dense, moist to wet, fine to medium sand, no HCl reaction, strongly oxidized
-66.7	74.5	8	11	19							SS-19	74.5ft: Reddish brown (5Y 4/3) and light yellowish brown (2.5Y 6/3), medium dense, wet, fine sand, trace cross-bedding, no to strong HCl reaction
-71.7	79.5	7	6	10							SS-20	79.5ft: Yellowish brown (10Y 5/4) to light yellowish brown (2.5Y 6/4), strong HCl reaction, weakly oxidized
-76.7	84.5	11	7	9							SS-21	84.5ft: Yellowish brown (10YR 5/6) and light brownish gray (2.5Y 6/2), weakly oxidized
-81.7	89.5	15	16	15							SS-22	89.5ft: Greenish gray (10Y 6/1), dense, few to little glauconite, no oxidation
-86.7	94.5	41	7	12							SS-23	VINCENTOWN FORMATION: Poorly graded SAND with clay (SP-SC), greenish gray (10Y 6/1), medium dense, moist, fine sand, trace moderately indurated layers, strong HCl reaction, few glauconite
-91.7	99.5	12	28	39							SS-24	VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), greenish gray (10Y 5/1), very dense, wet, fine sand, strong HCl reaction, few glauconite
-96.7	104.5	6	19	24							SS-25	104.5ft: Dense
-101.7	109.5	12	12	13							SS-26	109.5ft: Medium dense

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP GDI 7/10/09



PERMIT NO.: P200900091		DRILLER: M. Adams			NJ LICENSE NO.: 0001350			GEOLOGIST: R. Clark							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)						
BORING NO.: NB-5		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND							
GROUND SURFACE ELEV.: 7.8 US ft (NAVD88)		NORTHING: 234891.0 US ft (NAD83)		EASTING: 198445.7 US ft (NAD83)			24 HR. 2.5								
TOTAL DEPTH: 200.0 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 69.5 ft			HAMMER (ID): 140 lb Auto. (CTB-4)							
DATE STARTED: 2/6/09		COMPLETED: 2/8/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100		
-104.4					Continued from previous page										
-106.7	114.5	9	11	13								-105.2	113.0	HORNERSTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), medium dense, wet, fine to medium sand, strong HCl reaction, few glauconite	
-111.7	119.5	12	11	15										119.5ft: Few to little glauconite	
-116.7	124.5	17	19	21										124.5ft: Dense, few to little glauconite	
-121.7	129.5	12	13	16										129.5ft: Medium dense, little to some glauconite	
-126.7	134.5	21	22	32									-124.2	132.0	NAVESINK FORMATION: Poorly graded SAND with silt (SP-SM), very dark greenish gray (5GY 3/1), very dense, wet, fine sand, trace to little shell fragments, strong HCl reaction, mostly glauconite
-131.7	139.5	23	28	42											
-136.7	144.5	17	19	27									-135.2	143.0	NAVESINK FORMATION: Clayey SAND (SC), very dark greenish gray (5GY 3/1), dense, moist, fine sand, strong HCl reaction, mostly glauconite
-141.7	149.5	32	36	49									-140.2	148.0	NAVESINK FORMATION: Poorly graded SAND with silt (SP-SM), very dark greenish gray (10GY 3/1), very dense, wet, fine sand, strong HCl reaction, mostly glauconite
-146.7	154.5	24	25	40											154.5ft: Very dark greenish gray (5GY 3/1)
-151.7	159.5	36	40	50/0.2									-149.2	157.0	MOUNT LAUREL FORMATION: Clayey SAND (SC), very dark grayish brown (2.5Y 3/2), very dense, moist, fine to coarse subrounded sand, strong HCl reaction, little glauconite
-156.7	164.5	50/0.2													164.5ft: Dark olive gray (5Y 3/2), some glauconite -Observed apparent artesian flow of drill fluids from boring, possibly tidal influenced, driller thickens drill mud. -Mud tub overflowing due to artesian added flow at

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900091		DRILLER: M. Adams			NJ LICENSE NO.: 0001350			GEOLOGIST: R. Clark					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION					COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: NB-5		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND					
GROUND SURFACE ELEV.: 7.8 US ft (NAVD88)		NORTHING: 234891.0 US ft (NAD83)		EASTING: 198445.7 US ft (NAD83)			24 HR. 2.5						
TOTAL DEPTH: 200.0 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 69.5 ft			HAMMER (ID): 140 lb Auto. (CTB-4)					
DATE STARTED: 2/6/09		COMPLETED: 2/8/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-160.5					Continued from previous page								
-161.7	169.5	50/0.2								50/0.2	SS-38	174.5 feet. MOUNT LAUREL FORMATION: Clayey SAND (SC), very dark grayish brown (2.5Y 3/2), very dense, moist, fine to coarse subrounded sand, strong HCl reaction, little glauconite (<i>continued</i>)	
-166.7	174.5	50/0.3								50/0.3	SS-39		
-171.7	179.5	17	32	47						79	SS-40	179.5ft: Wet, trace shell fragments, little glauconite	
-176.7	184.5	17	27	28						55	SS-41	184.5ft: Olive gray (5Y 4/2), fine to coarse sand, trace shell fragments, few glauconite	
-181.7	189.5	17	24	32						56	SS-42	189.5ft: Olive gray (5Y 5/2), little glauconite	
-186.7	194.5	38	50/0.4							50/0.4	SS-43		
-191.7	199.5	50/0.5								50/0.5	SS-44		
												-192.2	200.0
Boring terminated at 200.0 feet.													
Boring closed by tremie method with cement-bentonite grout on 2/09/09.													

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900088		DRILLER: M. Adams			NJ LICENSE NO.: 0001350			GEOLOGIST: B. Deobald							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)						
BORING NO.: NB-6		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT/Shelby Tube			0 HR. ND							
GROUND SURFACE ELEV.: 9.3		US ft (NAVD88)		NORTHING: 235251.5		US ft (NAD83)		EASTING: 198315.4		US ft (NAD83)	24 HR. 13.0				
TOTAL DEPTH: 200.0 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 14.5 ft			HAMMER (ID): 140 lb Auto. (CTB-4)							
DATE STARTED: 2/19/09		COMPLETED: 2/22/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100		
-46.8					Continued from previous page										
-47.4	56.7	5	5	6									(2.5Y 3/1) KIRKWOOD FORMATION: FAT CLAY (CH), gray (2.5Y 5/1) and light olive brown (2.5Y 5/4), medium stiff, moist, trace fine sand, no HCl reaction <i>(continued)</i> 56.7ft: Very dark gray (2.5Y 3/1), and dark olive brown (2.5Y 3/3), stiff, few to little organics		
-52.7													62.0	KIRKWOOD FORMATION: Well graded SAND with gravel (SW), gray (2.5Y 5/1), medium dense, moist to wet, little subangular gravel, no HCl reaction	
-55.3	64.6	8	11	12											
-58.7														68.0	KIRKWOOD FORMATION: Poorly graded SAND with silt (SP-SM), grayish green (5G 4/2), medium dense, wet, fine to medium sand, no HCl reaction
-60.3	69.6	10	8	6											
-62.7														72.0	VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), dark yellowish brown (10YR 4/6), dense, wet, fine to medium grained, no HCl reaction, strongly oxidized
-65.3	74.6	29	24	15											
-67.3	76.6														
-68.6	77.9	22	9	10											
-70.9	80.2														
-73.3	82.6	8	9	15											
-76.6															
-77.9															
-80.3	89.6	7	10	12											
-82.6															
-83.7															
-85.3	94.6	50/0.4													
-88.6															
-89.6															
-90.3	99.6	12	14	16											
-92.6															
-95.3	104.6	8	10	15											
-97.6															
-100.3	109.6	12	17	21											
-102.6															
-104.6															
-106.6															
-109.6															
-111.6															
-114.6															
-117.6															
-120.6															
-123.6															
-126.6															
-129.6															
-132.6															
-135.6															
-138.6															
-141.6															
-144.6															
-147.6															
-150.6															
-153.6															
-156.6															
-159.6															
-162.6															
-165.6															
-168.6															
-171.6															
-174.6															
-177.6															
-180.6															
-183.6															
-186.6															
-189.6															
-192.6															
-195.6															
-198.6															
-200.0															

PSEG ESP BORE PSEG ESP 7-07-09.GPI PSEG ESP.GDI 7/10/09



PERMIT NO.: P200900088		DRILLER: M. Adams		NJ LICENSE NO.: 0001350		GEOLOGIST: B. Deobald								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)						
BORING NO.: NB-6		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT/Shellby Tube				0 HR. ND						
GROUND SURFACE ELEV.: 9.3		US ft (NAVD88)		NORTHING: 235251.5		US ft (NAD83)		24 HR. 13.0						
TOTAL DEPTH: 200.0 ft		DRILL MACHINE: CME-850 ATV		CASING DEPTH: 14.5 ft		HAMMER (ID): 140 lb Auto. (CTB-4)								
DATE STARTED: 2/19/09		COMPLETED: 2/22/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-102.9					Continued from previous page									
-105.3	114.6	50/0.3									SS-26	-103.7	113.0	VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), dark greenish gray (5G 4/1), very dense, moist, fine to medium sand, trace friable zones, weak to strong HCl reaction, little glauconite
-110.3	119.6	9	10	34							SS-27	-107.7	117.0	HORNERSTOWN FORMATION: Poorly graded SAND with silt (SP-SM), dark greenish gray (5G 4/1), dense, moist, fine to medium sand, trace friable zones, weak to strong HCl reaction, little glauconite
-115.3	124.6	12	14	42							SS-28			124.6ft: Dark greenish gray (5G 4/1), very dense, trace shell fragments, strong HCl reaction
-120.3	129.6	13	17	28							SS-29			129.6ft: Very dark greenish gray (5GY 3/1), dense, trace to few shell fragments, weak HCl reaction, some glauconite
-125.3	134.6	20	35	46							SS-30	-124.7	134.0	NAVESINK FORMATION: Silty SAND (SM), grayish green (5G 4/2), to greenish black (5G 2.5/1), very dense, moist, fine to medium sand, trace shell fragments, no HCl reaction, mostly glauconite
-130.3	139.6	22	24	32							SS-31			139.6ft: Greenish black (5G 2.5/1), fine sand, trace to few shell fragments
-135.3	144.6	17	21	29							SS-32			144.6ft: Dense
-140.3	149.6	24	31	36							SS-33			149.6ft: Very dense
-145.3	154.6	24	30	33							SS-34	-143.7	153.0	NAVESINK FORMATION: Clayey SAND (SC), grayish green (5G 5/1) to greenish black (5G 2.5/1), very dense, moist, fine to medium sand, trace shell fragments, no HCl reaction, mostly glauconite
-150.3	159.6	48	50/0.3								SS-35	-148.7	158.0	MOUNT LAUREL FORMATION: Clayey SAND (SC), dark greenish gray (5GY 4/1), very dense, dry to moist, fine to coarse subrounded sand, trace subangular gravel, strong HCl reaction, glauconite
-155.3	164.6	50/0.2									SS-36			164.6ft: Few shell fragments

PSEG ESP BORE PSEG ESP 7-07-09 GPI PSEG ESP GDI 7/10/09



PERMIT NO.: P200900088		DRILLER: M. Adams			NJ LICENSE NO.: 0001350			GEOLOGIST: B. Deobald				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: NB-6		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT/Shelby Tube					0 HR. ND		
GROUND SURFACE ELEV.: 9.3		US ft (NAVD88)		NORTHING: 235251.5		US ft (NAD83)		EASTING: 198315.4		24 HR. 13.0		
TOTAL DEPTH: 200.0 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 14.5 ft			HAMMER (ID): 140 lb Auto. (CTB-4)				
DATE STARTED: 2/19/09		COMPLETED: 2/22/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-159.0					Continued from previous page							
-160.3	169.6	50/0.2			50/0.2					SS-37		MOUNT LAUREL FORMATION: Clayey SAND (SC), dark greenish gray (5GY 4/1), very dense, dry to moist, fine to coarse subrounded sand, trace subangular gravel, strong HCl reaction, glauconite (continued) 169.6ft: Weak HCl reaction, trace shell fragments
-165.3	174.6	33	45	50/0.3	50/0.3					SS-38		
-170.3	179.6	20	33	50	83					SS-39		MOUNT LAUREL FORMATION: Silty SAND (SM), dark greenish gray (5GY 4/1), very dense, dry to moist, fine to coarse sand, trace shell fragments, weak HCl reaction, trace glauconite
-175.3	184.6	20	30	35	65					SS-40		MOUNT LAUREL FORMATION: Clayey SAND (SC), dark greenish gray (5GY 4/1), very dense, moist, fine to coarse sand, trace shell fragments, weak HCl reaction, trace glauconite
-180.3	189.6	18	28	37	65					SS-41		MOUNT LAUREL FORMATION: Silty SAND (SM), dark greenish gray (5GY 4/1), very dense, moist, fine to coarse sand, trace shell fragments, no to weak HCl reaction, trace glauconite
-185.3	194.6	37	50/0.4		50/0.4					SS-42		194.6ft: Dark greenish gray (5GY 4/1) and greenish gray (10Y 6/1), dry to moist, no HCl reaction
-190.3	199.6	50/0.4			50/0.4					SS-43		Boring terminated at 200.0 feet. Boring closed by tremie method with cement-bentonite grout on 2/22/09.

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MAN Date 7/10/09

Checked By JG2 Date 7/10/09

SHEET 1 OF 4

PERMIT NO.: P200900089		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)						
BORING NO.: NB-7		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT				0 HR. ND						
GROUND SURFACE ELEV.: 6.2		US ft (NAVD88)		NORTHING: 234965.7		US ft (NAD83)		EASTING: 199685.6		US ft (NAD83)		24 HR. ND		
TOTAL DEPTH: 201.2 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 44.0 ft				HAMMER (ID): 140 lb Auto. (CBT-1)						
DATE STARTED: 1/24/09		COMPLETED: 1/27/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
6.2	0.0	27	17	9	Ground Surface							6.2	0.0	
3.7	2.5	2	3	3	● 26					SS-1A/B		ARTIFICIAL FILL: Poorly graded GRAVEL with sand (GP), yellow (10YR 8/8), medium dense, dry to wet, angular gravel, no HCl reaction	0.8	
1.5	4.7	WOH	WOH	WOH	● 6					SS-2		ARTIFICIAL FILL: Sandy LEAN CLAY (CL), black (10YR 2/1), very stiff, moist, no HCl reaction	4.0	
-1.3	7.5	WOH	WOH	WOH	● 0					SS-3		2.5ft: Greenish Black (5GY 2.5/1), medium stiff	4.0	
-4.1	10.3	WOH	WOH	WOH	● 0					SS-4		HYDRAULIC FILL: Sandy LEAN CLAY (CL), greenish black (5GY 2.5/1), very soft, moist, no HCl reaction	7.0	
-6.6	12.8	WOH	1	1	● 2					SS-5		HYDRAULIC FILL: FAT CLAY (CH), very dark greenish gray (10Y 3/1), very soft, moist, few organics, no HCl reaction		
-9.1	15.3	WOH	WOH	WOH	● 0					SS-6				
-14.0	20.2	WOH	WOH	WOH	● 0					SS-7				
-19.1	25.3	WOH	WOH	WOH	● 0					SS-8				
-24.0	30.2	2	3	3	● 6					SS-9		HYDRAULIC FILL: Silty SAND (SM), black (N 2.5), loose, wet, fine sand, no HCl reaction	18.0	
-29.0	35.2	13	17	18	● 12					SS-10		HYDRAULIC FILL: ELASTIC SILT (MH), very dark gray (N 3), very soft, moist, no HCl reaction	23.0	
-33.8	40.0	WOH	3	2	● 5					SS-11		ALLUVIUM: Silty SAND with Gravel (SM), greenish gray (10Y 5/1), medium dense, wet, fine to medium sand, fine subrounded gravel, no HCl reaction	28.0	
-38.8	45.0	7	7	9	● 16					SS-12		ALLUVIUM: Clayey GRAVEL with sand (GC), dark grayish brown (10YR 4/2), dense, moist, subrounded gravel, fine to medium sand, no HCl reaction	34.0	
-43.8	50.0	7	7	7	● 14					SS-13		VINCEN TOWN FORMATION: Silty SAND (SM), yellowish brown (10YR 5/8), loose, wet, fine to medium sand, weak HCl reaction, trace glauconite, strongly oxidized	39.0	
-48.8	55.0	7	8	10	● 18					SS-14		45.0ft: Medium dense, strong HCl reaction	53.0	
										SS-15		50.0ft: Dark yellowish brown (10YR 4/6), fine to coarse sand		
												VINCEN TOWN FORMATION: Poorly Graded SAND with Silt (SP-SM), dark yellowish brown (10YR 4/6), medium dense, wet, fine to medium sand, strong HCl reaction, trace glauconite, strongly oxidized		

PSEG ESP BORE PSEG ESP 7-07-09 GPH PSEG ESP GDT 7/10/09



PERMIT NO.: P200900089		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION			COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)					
BORING NO.: NB-7		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		0 HR.	ND					
GROUND SURFACE ELEV.: 6.2		US ft (NAVD88)		NORTHING: 234965.7		US ft (NAD83)	EASTING: 199685.6					
US ft (NAVD88)		NORTHING: 234965.7		US ft (NAD83)		EASTING: 199685.6	US ft (NAD83)					
TOTAL DEPTH: 201.2 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 44.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)						
DATE STARTED: 1/24/09		COMPLETED: 1/27/09		HOLE DIA.: 4"		ROD TYPE: NWJ						
COMPLETED: 1/27/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-49.9					Continued from previous page							
-53.8	60.0	13	8	13							SS-16	VINCENTOWN FORMATION: Poorly Graded SAND with Silt (SP-SM), dark yellowish brown (10YR 4/6), medium dense, wet, fine to medium sand, strong HCl reaction, trace glauconite, strongly oxidized (continued) 60.0ft: Yellowish red (5YR 5/8)
-58.9	65.1	7	7	9							SS-17	65.1ft: Brownish yellow (10YR 6/6), trace friable layers, weak to strong HCl reaction, moderately oxidized
-63.8	70.0	7	20	19							SS-18	VINCENTOWN FORMATION: Clayey SAND (SC), light yellowish brown (10YR 6/4), dense, moist, fine to medium sand, strong HCl reaction, trace glauconite, weakly oxidized
-68.8	75.0	14	11	34							SS-19	VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), dense, wet, fine to medium sand, trace friable layers, strong HCl reaction, trace glauconite, no oxidation
-73.8	80.0	11	27	19							SS-20	
-79.0	85.2	19	13	15							SS-21	85.2ft: Medium dense
-84.0	90.2	8	92/0.3								SS-22	90.2ft: Dark greenish gray (10Y 4/1), very dense, trace shell fragments, trace moderately indurated layers
-89.0	95.2	7	12	30							SS-23	95.2ft: Dense
-93.8	100.0	13	13	14							SS-24	100.0ft: Medium dense
-98.9	105.1	9	16	29							SS-25	105.1ft: Greenish gray (10Y 5/1), very dense, trace friable cemented layers, weak HCl reaction
-103.9	110.1	6	26	16							SS-26	110.1ft: Dense, trace shell fragments, strong HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900089		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251						
BORING NO.: NB-7		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT								
GROUND SURFACE ELEV.: 6.2		US ft (NAVD88)		NORTHING: 234965.7		US ft (NAD83)						
EASTING: 199685.6		US ft (NAD83)		TOTAL DEPTH: 201.2 ft		DRILL MACHINE: CME-75 Truck						
CASING DEPTH: 44.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)		DATE STARTED: 1/24/09								
COMPLETED: 1/27/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-106.0					Continued from previous page							
-108.8	115.0	12	12	16							SS-27	VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), dense, wet, fine to medium sand, trace friable layers, strong HCl reaction, trace glauconite, no oxidation (continued) 115.1ft: Medium dense, few glauconite
-113.8	120.0	6	25	27							SS-28	HORNERSTOWN FORMATION: Silty SAND (SM), Greenish Gray (10Y 5/1), very dense, wet, fine to medium sand, trace friable layers, strong HCl reaction, few to little glauconite
-118.8	125.0	7	9	15							SS-29	125.0ft: Medium dense, trace shell fragments, little glauconite
-123.8	130.0	7	12	13							SS-30	
-128.8	135.0	9	15	19							SS-31	
-133.8	140.0	21	60	40/0.4							SS-32	138.0ft: NAVESINK FORMATION: Silty SAND (SM), very dark grayish green (5G 2.5/2), very dense, moist, fine to medium sand, few shell fragments, weak HCl reaction, mostly glauconite
-138.8	145.0	19	30	40							SS-33	145.0ft: Trace shell fragments
-143.8	150.0	27	29	42							SS-34	
-148.9	155.1	26	32	46							SS-35	
-153.8	160.0	33	49	51/0.3							SS-36	160.0ft: Very dark grayish green (5G 3/2), few shell fragments
-158.8	165.0	35	65/0.2								SS-37	156.8ft: MOUNT LAUREL FORMATION: Clayey SAND (SC), very dark greenish gray (10Y 3/1), very dense, moist, fine to medium sand, trace coarse sand, trace fine gravel, trace shell fragments, weak HCl reaction, little glauconite

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP GDI 7/10/09



PERMIT NO.: P200900089		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION					COUNTY: Salem, NJ			MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)		
BORING NO.: NB-7		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND		24 HR. ND		
GROUND SURFACE ELEV.: 6.2		US ft (NAVD88)			NORTHING: 234965.7		US ft (NAD83)		EASTING: 199685.6		US ft (NAD83)	
TOTAL DEPTH: 201.2 ft			DRILL MACHINE: CME-75 Truck			CASING DEPTH: 44.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)			
DATE STARTED: 1/24/09		COMPLETED: 1/27/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-162.1					Continued from previous page							
-163.8	170.0	100/0.4								100/0.4	SS-38	MOUNT LAUREL FORMATION: Clayey SAND (SC), very dark greenish gray (10Y 3/1), very dense, moist, fine to medium sand, trace coarse sand, trace fine gravel, trace shell fragments, weak HCl reaction, little glauconite (continued)
-168.8	175.0	100/0.5								100/0.5	SS-39	175.0ft: Dark greenish gray (10Y 4/1)
-173.8	180.0	40	60/0.4							100/0.9	SS-40	180.0ft: Weak to strong HCl reaction, trace glauconite
-178.8	185.0	23	35	41						76	SS-41	185.0ft: Few shell fragments, strong HCl reaction
-183.8	190.0	15	26	46						72	SS-42	190.0ft: Weak HCl reaction
-188.8	195.0	34	42	58/0.3						100/0.8	SS-43	185.8 MOUNT LAUREL FORMATION: Silty SAND (SM), Greenish Gray (10Y 5/1), very dense, moist, fine to medium sand, weak HCl reaction
-193.8	200.0	38	53	47/0.2						100/0.7	SS-44	191.8 MOUNT LAUREL FORMATION: Poorly Sorted SAND with silt (SP-SM), greenish gray (10Y 5/1), very dense, moist, fine to medium sand, no HCl reaction
												195.0 Boring terminated at 201.2 feet.
												Boring closed by tremie method with cement-bentonite grout on 1/27/09.

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDI 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MR Date 7/10/09

Checked By Jaw Date 7/10/09

SHEET 1 OF 6

PERMIT NO.: P200900090		DRILLER: D. Osuch			NJ LICENSE NO.: 0024289			GEOLOGIST: S. Johnson / M. Lear					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)				
BORING NO.: NB-8		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND					
GROUND SURFACE ELEV.: 8.9		US ft (NAVD88)		NORTHING: 234140.4		US ft (NAD83)		EASTING: 199745.9		US ft (NAD83)	24 HR. 5.4		
TOTAL DEPTH: 315.3 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 8.5 ft			HAMMER (ID): 140 lb Auto. (CTB-3)					
DATE STARTED: 1/9/09		COMPLETED: 1/13/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag & Roller Cone Bits					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
8.9					Ground Surface							8.9	0.0
8.9	0.0	8	10	50							SS-1	ARTIFICIAL FILL: Silty GRAVEL with sand (GM), very dark gray (5Y 3/1), very dense, moist, fine to coarse gravel, little fine sand	
6.4	2.5	3	4	4							SS-2	HYDRAULIC FILL: LEAN CLAY with sand (CL), very dark gray (10Y 3/1), medium stiff, moist, little fine sand	
3.9	5.0	2	2	2							SS-3	5.0ft: Soft, wet	
1.4	7.5	7	9	5							SS-4	HYDRAULIC FILL: Silty SAND (SM), gray (N 5), medium dense, wet, few gravel	
-1.1	10.0	WOH	WOH	WOH							SS-5	HYDRAULIC FILL: FAT CLAY (CH), very dark gray (N 3), very soft, wet, trace to few organics	
-3.3	12.2	3	5	4							SS-6	HYDRAULIC FILL: Silty, Clayey SAND (SC-SM), very dark gray (N 3), loose, wet, fine to medium sand, trace fine gravel, trace organics	
-5.6	14.5	WOH	WOH	WOH							SS-7	HYDRAULIC FILL: FAT CLAY (CH), dark greenish gray (10Y 4/1), very soft, wet, few organics	
-11.1	20.0	WOH	WOH	WOH							SS-8	20.0ft: Trace organics	
-15.6	24.5	WOH	WOH	WOH							SS-9	24.5ft: Trace fine sand	
-20.6	29.5	WOH	WOH	WOH							SS-10		
-25.6	34.5	1	1	1							SS-11A/B	ALLUVIUM: Sandy SILT (ML), dark gray (N 4), very soft, wet, fine sand	
-30.6	39.5	1	3	7							SS-12	ALLUVIUM: PEAT (PT), very dark brown (5Y 4/2), very soft, wet	
-35.6	44.5	10	11	4							SS-13A/B	ALLUVIUM: Silty SAND (SM), olive gray (5Y 4/2), loose, wet, fine to medium sand	
-40.6	49.5	WOH	2	3							SS-14	ALLUVIUM: Silty GRAVEL with sand (GM), very dark gray (10YR 3/1), medium dense, wet, fine to coarse sand, fine to coarse gravel	
-45.6	54.5	WOH	WOH	WOH							SS-15	ALLUVIUM: Sandy LEAN CLAY (CL), very dark greenish gray (10G 3/1), stiff, wet, fine to medium sand, trace of gravel	
												KIRKWOOD FORMATION: Clayey SAND (SC), dark brown (7.5YR 3/2), loose, wet, fine to medium sand, trace gravel	
												54.5ft: Reddish brown (5YR 4/4), very loose	

PSEG ESP BORE PSEG ESP. 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900090	DRILLER: D. Osuch	NJ LICENSE NO.: 0024289	GEOLOGIST: S. Johnson / M. Lear
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-8	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT	
GROUND SURFACE ELEV.: 8.9 US ft (NAVD88)		NORTHING: 234140.4 US ft (NAD83)	EASTING: 199745.9 US ft (NAD83)
TOTAL DEPTH: 315.3 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 8.5 ft	HAMMER (ID): 140 lb Auto. (CTB-3)
DATE STARTED: 1/9/09	COMPLETED: 1/13/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag & Roller Cone Bits			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-47.2		Continued from previous page											
-50.6	59.5	WOH	WOH	WOH							SS-16	KIRKWOOD FORMATION: Clayey SAND (SC), dark brown (7.5YR 3/2), loose, wet, fine to medium sand, trace gravel (continued)	
-55.6	64.5	8	10	12							SS-17		
-60.6	69.5	8	8	7							SS-18	VINCENTOWN FORMATION: Silty SAND (SM), reddish yellow (7.5YR 6/8), medium dense, wet, fine to medium sand, trace friable layers, strong HCl reaction, trace of glauconite, strongly oxidized	
-65.6	74.5	19	9	9							SS-19		
-70.6	79.5	7	20	15							SS-20	74.5ft: Reddish yellow (7.5YR 6/6)	
-75.6	84.5	6	6	18							SS-21	68.1	VINCENTOWN FORMATION: Clayey SAND (SC), light gray (2.5Y 7/2), dense, wet, fine to medium sand, trace indurated layers, strong HCl reaction, trace glauconite, weakly oxidized
-80.6	89.5	100/0.5									SS-22	84.5ft: Medium dense	
-85.6	94.5	11	11	65							SS-23	89.5ft: Very dense, mostly indurated	
-90.6	99.5	48	12	14							SS-24	83.1	VINCENTOWN FORMATION: Silty, Clayey SAND (SC-SM), light greenish gray (5GY 8/1), very dense, wet, fine to medium sand, trace indurated layers, strong HCl reaction, trace glauconite, no oxidation
-95.6	104.5	7	12	50							SS-25	99.5ft: Medium dense, few friable layers	
-100.6	109.5	100/0.2									SS-26	104.5ft: Light greenish gray (5GY 7/1), very dense	
												109.5ft: Mostly friable to indurated	

PSEG ESP BORE PSEG ESP 7-07-09.CPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900090	DRILLER: D. Osuch	NJ LICENSE NO.: 0024289	GEOLOGIST: S. Johnson / M. Lear
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-8	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT	
GROUND SURFACE ELEV.: 8.9 US ft (NAVD88)		NORTHING: 234140.4 US ft (NAD83)	EASTING: 199745.9 US ft (NAD83)
TOTAL DEPTH: 315.3 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 8.5 ft	HAMMER (ID): 140 lb Auto. (CTB-3)
DATE STARTED: 1/9/09	COMPLETED: 1/13/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag & Roller Cone Bits			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-103.3		Continued from previous page										
-105.6	114.5	8	14	19							SS-27	VINCENTOWN FORMATION: Silty, Clayey SAND (SC-SM), light greenish gray (5GY 8/1), very dense, wet, fine to medium sand, trace indurated layers, strong HCl reaction, trace glauconite, no oxidation (continued) 114.5ft: Greenish gray (5GY 5/1), dense, trace to few glauconite
-110.6	119.5	43	21	21							SS-28	119.5ft: Greenish gray (5GY 5/1), dense, trace friable layers
-115.6	124.5	8	12	17							SS-29	HORNERSTOWN FORMATION: Silty SAND (SM), dark greenish gray (10Y 5/1), medium dense, wet, fine to medium sand, strong HCl reaction, trace of glauconite
-120.6	129.5	6	10	16							SS-30	129.5ft: Few to little glauconite
-125.6	134.5	8	14	42							SS-31	134.5ft: Very dense
-130.6	139.5	33	22	20							SS-32	139.5ft: Dark greenish gray (5GY 4/1), dense, trace friable layers, little glauconite
-135.6	144.5	13	16	31							SS-33	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (5G 3/2), dense, wet, fine sand, trace shell fragments, weak HCl reaction, mostly glauconite
-140.6	149.5	20	29	32							SS-34	149.5ft: Very dense, little shell fragments
-145.6	154.5	28	40	40							SS-35	NAVESINK FORMATION: Silty, Clayey SAND (SC-SM), very dark greenish gray (5G 3/2), very dense, wet, fine to coarse sand, trace fine gravel, trace shell fragments, weak HCl reaction, mostly glauconite
-150.6	159.5	23	39	36							SS-36	
-155.6	164.5	27	36	43							SS-37	NAVESINK FORMATION: Clayey SAND (SC), very dark greenish gray (5G 3/2), very dense, wet, fine to coarse sand, trace fine gravel, trace shell fragments, no HCl reaction, mostly glauconite
												MOUNT LAUREL FORMATION: Sandy LEAN CLAY (CL), dark gray (2.5Y 4/1), hard, moist, fine to coarse sand, little glauconite, strong HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900090	DRILLER: D. Osuch	NJ LICENSE NO.: 0024289	GEOLOGIST: S. Johnson / M. Lear
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-8	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT	
GROUND SURFACE ELEV.: 8.9 US ft (NAVD88)		NORTHING: 234140.4 US ft (NAD83)	EASTING: 199745.9 US ft (NAD83)
TOTAL DEPTH: 315.3 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 8.5 ft	HAMMER (ID): 140 lb Auto. (CTB-3)
DATE STARTED: 1/9/09	COMPLETED: 1/13/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag & Roller Cone Bits			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-159.4		Continued from previous page											
-160.6	169.5	30	40	60/0.2							100/0.7	SS-38	MOUNT LAUREL FORMATION: Sandy LEAN CLAY (CL), dark gray (2.5Y 4/1), hard, moist, fine to coarse sand, little glauconite, strong HCl reaction (continued)
-165.6	174.5	100/0.2									100/0.2	SS-39	MOUNT LAUREL FORMATION: Clayey SAND (SC), dark greenish gray (10Y 4/1), very dense, moist, fine to coarse sand, trace shell fragments, strong HCl reaction, little glauconite
-170.6	179.5	100/0.3									100/0.3	SS-40	
-175.6	184.5	60	40/0.2							100/0.2	SS-41	MOUNT LAUREL FORMATION: Silty SAND (SM), very dark greenish gray (5GY 3/1), very dense, wet, fine sand, strong HCl reaction, mostly glauconite	
-180.6	189.5	25	33	53						86	SS-42	MOUNT LAUREL FORMATION: Clayey SAND (SC), very dark greenish gray (5GY 3/1), very dense, wet, fine to medium sand, trace shell fragments, strong HCl reaction, little glauconite	
-185.6	194.5	23	33	41						74	SS-43	194.5ft: Trace glauconite	
-190.6	199.5	19	35	57						92	SS-44	199.5ft: Greenish gray (5GY 5/1), weak HCl reaction	
-200.6	209.5	50	50/0.2							100/0.7	SS-45	MOUNT LAUREL FORMATION: Poorly graded SAND with silt (SP-SM), greenish gray (10GY 5/1), very dense, wet, fine to coarse subangular sand, few friable layers, no HCl reaction, trace of glauconite	
-210.6	219.5	75	25/0.1							100/0.6	SS-46	219.5ft: Very dark greenish gray (5GY 3/1), moist to wet, weak HCl reaction	

PSEG ESP BORE PSEG ESP 7-07-09.GPI PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900090	DRILLER: D. Osuch	NJ LICENSE NO.: 0024289	GEOLOGIST: S. Johnson / M. Lear
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NB-8	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT	
GROUND SURFACE ELEV.: 8.9 US ft (NAVD88)		NORTHING: 234140.4 US ft (NAD83)	EASTING: 199745.9 US ft (NAD83)
TOTAL DEPTH: 315.3 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 8.5 ft	HAMMER (ID): 140 lb Auto. (CTB-3)
DATE STARTED: 1/9/09	COMPLETED: 1/13/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag & Roller Cone Bits			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-215.5		Continued from previous page											
-220.6	229.5	55	45	0.3							100/0.8	SS-47	MOUNT LAUREL FORMATION: Poorly graded SAND with silt (SP-SM), greenish gray (10GY 5/1), very dense, wet, fine to coarse subangular sand, few friable layers, no HCl reaction, trace of glauconite (continued) 229.5ft: trace to few glauconite
-230.6	239.5	30	53	47/0.4							100/0.9	SS-48	
-240.6	249.5	39	44	48							92	SS-49	MOUNT LAUREL FORMATION: Silty, Clayey SAND (SC-SM), very dark greenish gray (5G 3/1), very dense, wet, fine to medium sand, weak HCl reaction, trace to few glauconite
-250.6	259.5	17	30	43							73	SS-50	MOUNT LAUREL FORMATION: Silty SAND (SM), very dark greenish gray (5GY 3/1), very dense, wet, fine to medium sand, weak HCl reaction, trace glauconite
-260.6	269.5	5	5	13							18	SS-51	WENONAH FORMATION: FAT CLAY with sand (CH), very dark gray (N 3/), very stiff, wet, little fine sand, strong HCl reaction
-270.6	279.5	2	3	4								SS-52	WENONAH FORMATION: Clayey SAND (SC), very dark gray (N 3/), loose, wet, fine to medium sand, strong HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



GEOTECHNICAL BORING LOG

Prepared By NB Date 7/10/09

Checked By JA Date 7/10/09

SHEET 1 OF 7

PERMIT NO.: P200900125		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)							
BORING NO.: EB-1		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND								
GROUND SURFACE ELEV.: 15.9 US ft (NAVD88)		NORTHING: 232316.7 US ft (NAD83)		EASTING: 202774.1 US ft (NAD83)			24 HR. 3.1									
TOTAL DEPTH: 351.5 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 4"=38.5' / 6"=18.5'			HAMMER (ID): 140 lb Auto. (CBT-1)								
DATE STARTED: 1/9/09		COMPLETED: 1/21/09		HOLE DIA.: 4"-6"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit								
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT						SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100						
15.9					Ground Surface											
15.9	0.0	7	11	9										15.9	0.0	
13.4	2.5	3	5	5										15.0	0.9	ARTIFICIAL FILL: Silty SAND with gravel (SM), greenish gray (10Y 5/1), medium dense, wet, fine to coarse sand, subangular gravel, no HCl reaction, few organics
10.9	5.0	1	WOH	1										10.9	5.0	ARTIFICIAL FILL: Poorly graded SAND with silt (SP-SM), reddish yellow (7.5YR 6/6), medium dense, wet, fine to medium sand, no HCl reaction
8.4	7.5	WOH	WOH	WOH												HYDRAULIC FILL: FAT CLAY (CH), very dark greenish gray (5GY 3/1), very soft, moist, no HCl reaction
5.9	10.0	WOH	WOH	1												
3.4	12.5	1	WOH	1												
0.9	15.0	WOH	1	WOH												13.0ft: Silty SAND (SM) layer to 13.4ft
-4.1	20.0	WOH	1	1												15.0ft: Wet
-9.1	25.0	WOH	WOH	WOH												25.0ft: Moist
-14.1	30.0	WOH	WOH	WOH												30.0ft: Trace mica
-19.1	35.0	WOH	WOH	WOH												
-24.1	40.0	12	16	13										-22.1	38.0	ALLUVIUM: Silty SAND (SM), dark greenish gray (5GY 4/1) and yellowish brown (10YR 5/6), medium dense, wet, fine to medium sand, no HCl reaction
-29.1	45.0	6	8	9										-29.1	45.0	ALLUVIUM: Poorly graded SAND (SP), greenish gray (5GY 6/1), medium dense, wet, fine to medium sand, trace coarse sand and fine gravel, no HCl reaction
-34.1	50.0	5	11	13										-36.1	52.0	KIRKWOOD FORMATION: Poorly graded SAND (SP), Light greenish gray (5GY 7/1), medium dense, wet, fine to medium sand, no HCl reaction
-39.1	55.0	7	8	13												

PSEG ESP BORE 7-07-09-GPI PSEG ESP-GDT 7/10/09



PERMIT NO.: P200900125		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-1		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT					0 HR. ND		
GROUND SURFACE ELEV.: 15.9 US ft (NAVD88)		NORTHING: 232316.7 US ft (NAD83)		EASTING: 202774.1 US ft (NAD83)						24 HR. 3.1		
TOTAL DEPTH: 351.5 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 4"=38.5' / 6"=18.5'			HAMMER (ID): 140 lb Auto. (CBT-1)				
DATE STARTED: 1/9/09		COMPLETED: 1/21/09		HOLE DIA.: 4"-6"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-40.2		Continued from previous page										
-44.1	60.0	10	9	10							SS-16	KIRKWOOD FORMATION: Poorly graded SAND (SP), Light greenish gray (5GY 7/1), medium dense, wet, fine to medium sand, no HCl reaction (continued)
-49.1	65.0	6	10	13							SS-17	65.0ft: Greenish gray (5GY 6/1), fine to medium sand
-53.9	69.8	4	10	10							SS-18	69.8ft: Gray (N 5)
-59.1	75.0	NA	NA	NA							SS-19	-57.1 KIRKWOOD FORMATION: Sandy ELASTIC SILT (MH), dark greenish gray (10Y 4/1), soft, moist, no HCl reaction
-60.6	76.5	1	2	12							SS-20	75.0ft: Rods dropped, penetrated 1.5ft, no SPT values
-64.3	80.2	1	4	4							SS-21	-61.7 KIRKWOOD FORMATION: Silty SAND (SM), dark gray (N 4), medium dense, wet, fine to medium sand, no HCl reaction, trace wood fragments and organics
-69.1	85.0	2	4	5							SS-22	-64.3 KIRKWOOD FORMATION: FAT CLAY (CH), dark greenish gray (10Y 4/1), medium stiff, moist, no HCl reaction
-74.1	90.0	2	1	4							SS-23	85.0ft: Greenish gray (10Y 5/1), stiff
-79.2	95.1	3	5	6							SS-24	90.0ft: Dark greenish gray (10Y 4/1), medium stiff, trace organics
-84.1	100.0	5	7	12							SS-25	95.1ft: Stiff, trace to few organics, trace mica
-89.1	105.0	100/0.4									SS-26	100.0ft: Very stiff, trace organics, few mica 100.9ft: silty SAND (SM) layer to 101.1ft
-93.9	109.8	7	10	12							SS-27	-87.1 VINCENTOWN FORMATION: Clayey SAND (SC), greenish gray (10Y 6/1), very dense, moist, fine to medium sand, mostly indurated, weak HCl reaction, trace shell fragments, trace glauconite
												-92.1 VINCENTOWN FORMATION: ELASTIC SILT (MH), greenish gray (5GY 5/1), very stiff, wet, trace fine sand, no HCl reaction, trace glauconite

PSEG ESP BORE PSEG ESP 7-07-09.GPI PSEG ESP.GDI 7/10/09



PERMIT NO.: P200900125		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)					
BORING NO.: EB-1		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT					0 HR. ND				
GROUND SURFACE ELEV.: 15.9 US ft (NAVD88)		NORTHING: 232316.7 US ft (NAD83)		EASTING: 202774.1 US ft (NAD83)			24 HR. 3.1							
TOTAL DEPTH: 351.5 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 4"=38.5' / 6"=18.5'			HAMMER (ID): 140 lb Auto. (CBT-1)						
DATE STARTED: 1/9/09		COMPLETED: 1/21/09		HOLE DIA.: 4"-6"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-96.3		Continued from previous page												
-99.0	114.9	17	14	16							SS-28	-97.1	113.0	VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (5GY 5/1), medium dense, wet, fine to medium sand, no HCl reaction, trace glauconite
-104.2	120.1	41	28	18							SS-29			120.1ft: Greenish gray (10Y 5/1), dense, moist, no to weak HCl reaction, few friable to moderately indurated layers
-109.3	125.2	9	24	15							SS-30			125.2ft: Weak to strong HCl reaction, trace shell fragments, few moderately indurated layers
-114.1	130.0	9	76	24					100/1.0		SS-31			130.0ft: Greenish gray (10Y 6/1), very dense, wet, few friable layers
-119.1	135.0	7	93/0.4						100/0.9		SS-32			135.0ft: Greenish gray (10Y 5/1), strong HCl reaction, few friable to moderately indurated layers
-124.1	140.0	9	12	13							SS-33			140.0ft: Greenish gray (10Y 6/1), medium dense, no to weak HCl reaction
-129.1	145.0								100/0.1		SS-34	-127.1	143.0	HORNERSTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 6/1), very dense, moist, fine to medium sand, weak HCl reaction, trace to few glauconite
-134.1	150.0	6	11	16							SS-35			145.0ft: Moderately indurated to friable
-139.2	155.1	6	12	19							SS-36			150.0ft: Medium dense, strong HCl reaction, few glauconite
-144.0	159.9	7	36	26							SS-37			155.1ft: Greenish gray (10Y 5/1), dense
-149.1	165.0	41	28	32							SS-38			159.9ft: Dark greenish gray (5GY 4/1), very dense, trace shell fragments, few to little glauconite
												-147.1	163.0	NAVESINK FORMATION: Silty, Clayey SAND (SC-SM), dark bluish gray (5B 4/1), very dense, moist, fine to medium sand, trace shell fragments, weak HCl reaction, mostly glauconite

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900125		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard									
SITE DESCRIPTION: PSEG SITE ESP APPLICATION			COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)								
BORING NO.: EB-1		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT			0 HR. ND								
GROUND SURFACE ELEV.: 15.9 US ft (NAVD88)		NORTHING: 232316.7 US ft (NAD83)		EASTING: 202774.1 US ft (NAD83)			24 HR. 3.1								
TOTAL DEPTH: 351.5 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 4"=38.5' / 6"=18.5'		HAMMER (ID): 140 lb Auto. (CBT-1)									
DATE STARTED: 1/9/09		COMPLETED: 1/21/09		HOLE DIA.: 4"-6"		ROD TYPE: NWJ									
BITS USED: 3-7/8" Drag Bit															
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT						SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100					
-152.4		Continued from previous page													
-154.0	169.9	19	30	34								SS-38		NAVESINK FORMATION: Silty, Clayey SAND (SC-SM), dark bluish gray (5B 4/1), very dense, moist, fine to medium sand, trace shell fragments, weak HCl reaction, mostly glauconite (continued) 169.9ft: Greenish black (5BG 2.5/1), no HCl reaction	
-159.1	175.0	17	28	38								SS-40		175.0ft: Medium dense, weak HCl reaction	
-164.1	180.0	26	39	57								SS-41		180.0ft: No HCl reaction	
-169.0	184.9	20	30	38								SS-42A/B		184.9ft: Little coarse shell fragments	
-174.0	189.9	35	65/0.1									SS-43		MOUNT LAUREL FORMATION: Silty, Clayey SAND (SC-SM), dark gray (10YR 4/1), very dense, moist, fine to coarse subrounded sand, little shell fragments, weak to strong HCl reaction, little glauconite 189.9ft: Dark greenish gray (10Y 4/1), strong HCl reaction	
-179.1	195.0	100/0.3										SS-44		195.0ft: Fine to medium sand, weak HCl reaction	
-184.0	199.9	100/0.4										SS-45			
-194.1	210.0	21	36	42								SS-46		210.0ft: Trace shell fragments, few glauconite	
-203.9	219.8	26	40	60								SS-47		MOUNT LAUREL FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), very dense, moist, fine to medium sand, weak HCl reaction, trace glauconite	

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDI 7/10/09



PERMIT NO.: P200900125		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)				
BORING NO.: EB-1		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT					0 HR. ND			
GROUND SURFACE ELEV.: 15.9 US ft (NAVD88)		NORTHING: 232316.7 US ft (NAD83)			EASTING: 202774.1 US ft (NAD83)					24 HR. 3.1			
TOTAL DEPTH: 351.5 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 4"=38.5' / 6"=18.5'			HAMMER (ID): 140 lb Auto. (CBT-1)					
DATE STARTED: 1/9/09		COMPLETED: 1/21/09		HOLE DIA.: 4"-6"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-320.7					Continued from previous page								
-323.9	339.8	10	18	32								ENGLISHTOWN FORMATION: Sandy SILT (ML), very dark greenish gray (10Y 3/1), hard, moist, no HCl reaction, micaceous, trace shell fragments (continued) 339.8ft: No recovery-sample pulled out, catcher inverted	
-329.1	345.0	7	15	35									
-334.1	350.0	6	7	11									
												350.0ft: Black (N 2.5/), very stiff, no to weak HCl reaction, few shell fragments	
												351.5	
													Boring terminated at 351.5 feet.
													Boring terminated before proposed termination depth due to persistent problems with boring cave-in and loss of drill fluid circulation. Boring EB-3 proposed termination depth extended as replacement.
													Boring closed by tremie method with cement-bentonite grout on 1/22/09.

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MJB Date 7/10/09
 Checked By JOB Date 7/10/09
 SHEET 1 OF 4

PERMIT NO.: P200804329		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251							
BORING NO.: EB-2		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		FLUID LEVEL (ft)							
GROUND SURFACE ELEV.: 14.1 US ft (NAVD88)		NORTHING: 233264.7 US ft (NAD83)		EASTING: 202166.5 US ft (NAD83)		0 HR. ND							
TOTAL DEPTH: 200.7 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 14.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)							
DATE STARTED: 2/3/09		COMPLETED: 2/6/09		HOLE DIA.: 4"		ROD TYPE: NWJ							
						BITS USED: 3-7/8" Drag Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
14.1					Ground Surface							14.1	0.0
11.6	2.5	5	5	4	15					SS-1		12.1	2.0
9.1	5.0	5	5	4	9					SS-2		9.6	4.5
6.6	7.5	8	11	6	17					SS-3		7.1	7.0
4.1	10.0	4	1	2	3					SS-4			
1.6	12.5	WOH	1	1	2					SS-5			
-0.9	15.0	1	1	1	2					SS-6		2.1	12.0
-5.9	20.0	WOH	WOH	WOH	0					SS-7			
-11.2	25.3	WOH	WOH	WOH	0					SS-8			
-16.2	30.3	WOH	WOH	WOH	0					SS-9			
-21.1	35.2	WOH	WOH	WOH	0					SS-10			
-25.9	40.0	WOH	WOH	WOH	0					SS-11			
-31.7	45.8	4	6	10	16					SS-12		-24.9	39.0
-35.9	50.0	1	3	4	7					SS-13		-29.9	44.0
-40.9	55.0	WOH	2	3	5					SS-14		-33.9	48.0
		WOH	1	2	3					SS-15			
					3								

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP GDI 7/10/09



PERMIT NO.: P200804329		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-2		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND				
GROUND SURFACE ELEV.: 14.1 US ft (NAVD88)		NORTHING: 233264.7 US ft (NAD83)		EASTING: 202166.5 US ft (NAD83)			24 HR. 6.3					
TOTAL DEPTH: 200.7 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 14.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)				
DATE STARTED: 2/3/09		COMPLETED: 2/6/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-42.0					Continued from previous page							
-45.9	60.0	WOH	2	3	5						SS-16	60.0ft: Medium stiff, PP=1.5 tsf
-51.2	65.3	WOH	1	2	3						SS-17	48.9 KIRKWOOD FORMATION: Sandy LEAN CLAY (CL), very dark greenish gray (10Y 3/1), soft, moist, some fine to medium sand, trace shell fragments, no HCl reaction, PP=0.25 tsf
-55.9	70.0	1	1	1	2						SS-18	70.0ft: Very soft, trace organics, PP=1.0 tsf
-61.0	75.1	WOH	WOH	1	1						SS-19	58.9 KIRKWOOD FORMATION: FAT CLAY (CH), dark greenish gray (10Y 4/1), very soft, moist, no HCl reaction, trace organics, PP=1.0 tsf
-65.9	80.0	WOH	1	1	2						SS-20	80.0ft: PP=0.25 tsf
-70.9	85.0	1	2	1	3						SS-21	85.0ft: Soft, few organics, PP=0.25 tsf
-76.2	90.3	WOH	WOH	WOH	0						SS-22	90.3ft: Very soft, trace organics, PP=0.5 tsf
-80.9	95.0	WOH	WOH	WOH	0						SS-23	95.0ft: PP=0.5 tsf
-85.9	100.0	10	15	14	29						SS-24	83.9 KIRKWOOD FORMATION: Poorly graded SAND with silt and gravel (SP-SM), greenish gray (10Y 5/1), medium dense, wet, fine to coarse sand, little fine to coarse gravel, no HCl reaction
-90.9	105.0	10	14	14	28						SS-25	89.9 VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (5GY 5/1), medium dense, wet, fine to medium sand, few friable layers, strong HCl reaction, trace glauconite
-95.9	110.0	8	92/0.4		100/0.9						SS-26	110.0ft: Greenish gray (5GY 6/1), very dense, few moderately indurated layers

PSEG ESP BORE_PSEG ESP 7-07-09_GPI_PSEG ESP.GDT 7/10/09



PERMIT NO.: P200804329		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251							
BORING NO.: EB-2		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		FLUID LEVEL (ft)							
GROUND SURFACE ELEV.: 14.1 US ft (NAVD88)		NORTHING: 233264.7 US ft (NAD83)		EASTING: 202166.5 US ft (NAD83)		0 HR. ND							
TOTAL DEPTH: 200.7 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 14.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)							
DATE STARTED: 2/3/09		COMPLETED: 2/6/09		HOLE DIA.: 4"		ROD TYPE: NWJ							
BITS USED: 3-7/8" Drag Bit													
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT						SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100			
-154.2					Continued from previous page								
-155.9	170.0	11	18	30							SS-38		NAVESINK FORMATION: Clayey SAND (SC), greenish black (10GY 2.5/1), dense, wet, fine to medium sand, weak HCl reaction, mostly glauconite (continued)
-161.1	175.2	16	30	47							SS-39		NAVESINK FORMATION: Poorly graded SAND with silt (SP-SM), greenish black (10GY 2.5/1), very dense, wet, fine to medium sand, weak HCl reaction, mostly glauconite
-165.7	179.8	36	45	55/0.3						100/0.8	SS-40		
-170.9	185.0	20	80/0.5							100/1.0	SS-41		MOUNT LAUREL FORMATION: Sandy LEAN CLAY (CL), dark greenish gray (10Y 4/1), hard, dry to moist, fine to coarse subrounded sand, strong HCl reaction, little glauconite, trace mica, PP=>4.5 tsf
-175.8	189.9	100/0.3								100/0.3	SS-42		
-180.9	195.0	100/0.3								100/0.3	SS-43		195.0ft: Very dark greenish gray (10Y 3/1)
-185.9	200.0	70	30/0.2							100/0.7	SS-44		Boring terminated at 200.7 feet. Boring closed by tremie method with cement-bentonite grout on 2/07/09.

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



GEOTECHNICAL BORING LOG

Prepared By NBR Date 7/10/09

Checked By JA 2 Date 7/10/09

SHEET 1 OF 12

PERMIT NO.: P200900124		DRILLER: D. Osuch / R. Bartholomew			NJ LICENSE NO.: 0024289 / 0001383			GEOLOGIST: M. Lear							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)						
BORING NO.: EB-3		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND							
GROUND SURFACE ELEV.: 16.5 US ft (NAVD88)		NORTHING: 232349.0 US ft (NAD83)			EASTING: 202473.9 US ft (NAD83)			24 HR. 13.8							
TOTAL DEPTH: 631.5 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 53.7 ft			HAMMER (ID): 140 lb Auto. (CTB-3)							
DATE STARTED: 1/24/09		COMPLETED: 2/17/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag & Roller Cone Bits							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100		
16.5													16.5	0.0	
16.5	0.0	33	30	9											
14.0	2.5	5	5	4									14.5	2.0	ARTIFICIAL FILL: Silty GRAVEL with sand (GM), grayish brown (10YR 5/2), dense, dry to moist, fine to coarse gravel
11.5	5.0	WOH	2	2									12.0	4.5	ARTIFICIAL FILL: Poorly graded SAND with gravel (SP), dark gray (10YR 4/1), loose, wet, fine to medium sand, little fine gravel
9.0	7.5	2	1	2											HYDRAULIC FILL: SILT (ML), very dark gray (2.5Y 3/1), soft, moist to wet, trace fine sand, PP=0.5 tsf
6.5	10.0	2	4	3											7.5ft: Wet
4.0	12.5	2	1	1											10.0ft: Medium stiff
1.5	15.0	WOH	WOH	2											
-3.5	20.0	WOH	WOH	2											
-8.5	25.0	WOH	WOH	WOH											
-13.5	30.0	WOH	WOH	WOH											
-18.5	35.0	WOH	WOH	WOH											
-23.5	40.0	5	8	10											
-28.5	45.0	5	2	4											
-33.5	50.0	WOH	2	3											
-38.5	55.0	WOH	2	5											

PSEG ESP BORE, PSEG ESP, 7-07-09 GBJ PSEG ESP, GDT, 7/10/09



PERMIT NO.: P200900124	DRILLER: D. Osuch / R. Bartholomew	NJ LICENSE NO.: 0024289 / 0001383	GEOLOGIST: M. Lear
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: EB-3	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT	
GROUND SURFACE ELEV.: 16.5 US ft (NAVD88)		NORTHING: 232349.0 US ft (NAD83)	EASTING: 202473.9 US ft (NAD83)
TOTAL DEPTH: 631.5 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 53.7 ft	HAMMER (ID): 140 lb Auto. (CTB-3)
DATE STARTED: 1/24/09	COMPLETED: 2/17/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag & Roller Cone Bits			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-39.6		Continued from previous page										
-41.5	60.0	3	3	4							SS-16	KIRKWOOD FORMATION: Silty SAND (SM), very dark greenish gray (10Y 3/1), loose, wet, fine sand, few organics
-46.5	65.0	WOH	WOH	2							SS-17	KIRKWOOD FORMATION: FAT CLAY (CH), very dark greenish gray (10Y 3/1), very soft, moist to wet, trace fine sand, trace organics, trace shell fragments, PP=0.0 tsf
-53.5	70.0	WOH	3	4							SS-18	70.0ft: Medium stiff, moist, PP=1.25 tsf
-58.5	75.0	WOH	WOH	2							SS-19	75.0ft: Very soft, PP=1.25 tsf
-63.5	80.0	WOH	WOH	WOH							SS-20	80.0ft: Little fine to medium sand, PP=0.75 tsf
-68.5	85.0	WOH	WOH	WOH							SS-21	85.0ft: PP=0.75 tsf
-73.5	90.0	WOR	WOR	WOH							SS-22	90.0ft: Olive gray (5Y 4/2), PP=0.0 tsf
-78.5	95.0	4	9	14							SS-23	93.5ft: Harder drilling
-83.5	100.0	6	7	6							SS-24	KIRKWOOD FORMATION: Poorly graded SAND with silt (SP-SM), dark olive gray (5Y 3/2), medium dense, wet, fine to coarse sand, few fines, no HCl reaction
-88.5	105.0	24	27	18							SS-25	KIRKWOOD FORMATION: Poorly graded GRAVEL with sand (GP), dark gray (5Y 4/1), dense, wet, little fine to coarse sand, fine to coarse subrounded to subangular gravel, trace fines
-93.5	110.0	24	13	58							SS-26	VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (5GY 5/1), very dense, moist to wet, fine to medium sand, few friable to moderately indurated layers, strong HCl reaction, few glauconite

PSEG ESP BORE PSEG ESP 7-07-09 GPI PSEG ESP GDI 7/10/09



PERMIT NO.: P200900124	DRILLER: D. Osuch / R. Bartholomew	NJ LICENSE NO.: 0024289 / 0001383	GEOLOGIST: M. Lear
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: EB-3	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT	
GROUND SURFACE ELEV.: 16.5 US ft (NAVD88)		NORTHING: 232349.0 US ft (NAD83)	EASTING: 202473.9 US ft (NAD83)
TOTAL DEPTH: 631.5 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 53.7 ft	HAMMER (ID): 140 lb Auto. (CTB-3)
DATE STARTED: 1/24/09	COMPLETED: 2/17/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag & Roller Cone Bits			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-95.7		Continued from previous page										
-98.5	115.0	15	11	26							SS-27	VINCEN TOWN FORMATION: Silty SAND (SM), greenish gray (5GY 5/1), very dense, moist to wet, fine to medium sand, few friable to moderately indurated layers, strong HCl reaction, few glauconite (continued) 115.0ft: Dense, wet
-103.5	120.0	9	10	21							SS-28	120.0ft: Few friable layers, weak HCl reaction 122ft: Bit chatter to 124ft
-108.1	124.6	9	10	12							SS-29	124.6ft: Medium dense, trace glauconite
-113.1	129.6	12	13	19							SS-30	129.6ft: Greenish gray (10Y 5/1), dense, trace friable layers -Bit chatter drilling to 134.6ft
-118.1	134.6	50/0.5									SS-31	134.6ft: Very dense, moist, trace moderately indurated to indurated layers -Bit chatter from 135ft to 137ft and 138ft to 139ft
-123.1	139.6	7	8	92/0.2							SS-32	139.6ft: Trace moderately indurated layers -Bit chatter from 141ft to 143ft
-128.1	144.6	62	28	25							SS-33	-127.5 HORNERSTOWN FORMATION: Clayey SAND (SC), greenish gray (10Y 5/1), very dense, moist to wet, fine to medium sand, trace to few moderately indurated layers, weak to strong HCl reaction, trace glauconite -Slight bit chatter from 148ft to 149ft
-133.1	149.6	3	8	14							SS-34	149.6ft: Medium dense, weak HCl reaction, trace to few glauconite
-138.1	154.6	5	53	47/0.1							SS-35	154.6ft: Very dense, trace moderately indurated layers
-143.1	159.6	23	40	29							SS-36	159.6ft: Moist, trace friable layers, strong HCl reaction, few to little glauconite
-148.1	164.6	25	75/0.2								SS-37	-147.5 NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (5GY 3/1), very dense, moist, fine to medium sand, trace shell fragments, trace moderately indurated layers, weak HCl reaction, some to mostly glauconite

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900124		DRILLER: D. Osuch / R. Bartholomew			NJ LICENSE NO.: 0024289 / 0001383		GEOLOGIST: M. Lear					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)				
BORING NO.: EB-3		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND				
GROUND SURFACE ELEV.: 16.5 US ft (NAVD88)		NORTHING: 232349.0 US ft (NAD83)		EASTING: 202473.9 US ft (NAD83)		24 HR. 13.8						
TOTAL DEPTH: 631.5 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 53.7 ft		HAMMER (ID): 140 lb Auto. (CTB-3)					
DATE STARTED: 1/24/09		COMPLETED: 2/17/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag & Roller Cone Bits				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-151.8		Continued from previous page										
-153.1	169.6	30	25	35							SS-38	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (5GY 3/1), very dense, moist, fine to medium sand, trace shell fragments, trace moderately indurated layers, weak HCl reaction, some to mostly glauconite (continued) 169.6ft: Greenish black (10Y 2.5/1), moist to wet, trace to few shell fragments, no HCl reaction, mostly glauconite
-158.1	174.6	16	23	26							SS-39	
-163.1	179.6	20	38	48							SS-40	NAVESINK FORMATION: Clayey SAND (SC), greenish black (10Y 2.5/1), dense, moist, fine to medium sand, trace shell fragments, weak HCl reaction, mostly glauconite
-168.1	184.6	13	30	33							SS-41	NAVESINK FORMATION: Silty SAND (SM), greenish black (10Y 2.5/1), very dense, moist, fine to medium sand, trace shell fragments, weak HCl reaction, mostly glauconite
-173.1	189.6	25	39	61/0.1							SS-42	MOUNT LAUREL FORMATION: Clayey SAND (SC), dark olive gray (5Y 3/2), very dense, moist, fine to coarse subrounded sand, few to little shell fragments, weak HCl reaction, some glauconite
-178.1	194.6	100/0.4									SS-43	189.6ft: Trace shell fragments, little glauconite
-183.1	199.6	100/0.4									SS-44	194.6ft: Trace to few shell fragments, trace glauconite
-193.1	209.6	17	27	39							SS-45	MOUNT LAUREL FORMATION: Silty SAND (SM), olive gray (5Y 4/2), very dense, moist, fine to coarse subrounded to subangular sand, trace fine gravel, trace shell fragments, weak to no HCl reaction, trace glauconite
-203.1	219.6	25	40	60							SS-46	

PSEG ESP BORE PSEG ESP 7-07-09.CPI PSEG ESP.GDI 7/10/09



PERMIT NO.: P200900124		DRILLER: D. Osuch / R. Bartholomew		NJ LICENSE NO.: 0024289 / 0001383		GEOLOGIST: M. Lear							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION			COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)						
BORING NO.: EB-3		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		0 HR.	ND						
GROUND SURFACE ELEV.: 16.5 US ft (NAVD88)		NORTHING: 232349.0 US ft (NAD83)		EASTING: 202473.9 US ft (NAD83)		24 HR.	13.8						
TOTAL DEPTH: 631.5 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 53.7 ft		HAMMER (ID): 140 lb Auto. (CTB-3)							
DATE STARTED: 1/24/09		COMPLETED: 2/17/09		HOLE DIA.: 4"	ROD TYPE: NWJ	BITS USED: 3-7/8" Drag & Roller Cone Bits							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-376.3					Continued from previous page								
-383.1	399.6	2	7	16									WOODBURY FORMATION: FAT CLAY (CH), black (5Y 2.5/1), very stiff, dry to moist, trace shell fragments, weak HCl reaction, micaceous, PP=>4.5 tsf (continued)
-393.1	409.6	3	7	17									
-403.1	419.6	13	23	23									MERCHANTVILLE FORMATION: SILT (ML), greenish black (10Y 2.5/1), hard, moist, trace fine sand, trace friable layers, trace mica, weak HCl reaction, few to little glauconite, PP=3.5 tsf
-413.1	429.6	14	17	26									429.6ft: PP=4.0 tsf
-423.1	439.6	7	11	71									MERCHANTVILLE FORMATION: LEAN CLAY (CL), greenish black (10Y 2.5/1), hard, dry to moist, trace fine sand, trace friable to moderately indurated layers, no HCl reaction, few glauconite, PP=3.25 to 4.5 tsf
													MAGOTHY FORMATION: FAT CLAY (CH), gray (5YR 5/1) and very dark gray (2.5Y 3/1) mottled, hard, dry to moist, carbonaceous, trace lignite, no HCl reaction, PP=2.5 to >4.5 tsf

PSEG ESP BORE PSEG ESP. 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900124		DRILLER: D. Osuch / R. Bartholomew			NJ LICENSE NO.: 0024289 / 0001383			GEOLOGIST: M. Lear				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-3		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND				
GROUND SURFACE ELEV.: 16.5 US ft (NAVD88)		NORTHING: 232349.0 US ft (NAD83)		EASTING: 202473.9 US ft (NAD83)			24 HR. 13.8					
TOTAL DEPTH: 631.5 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 53.7 ft			HAMMER (ID): 140 lb Auto. (CTB-3)				
DATE STARTED: 1/24/09		COMPLETED: 2/17/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag & Roller Cone Bits				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-600.7					Continued from previous page							
-613.5	630.0	15	25	46						SS-70		POTOMAC FORMATION: LEAN CLAY (CL)-Interpreted from geophysical log (continued)
												POTOMAC FORMATION: LEAN CLAY (CL), gray (5YR 6/1) and reddish brown (5YR 4/4) mottled, hard, moist to dry, trace fine sand, no HCl reaction, PP=>4.5 tsf Boring terminated at 631.5 feet. Boring closed by tremie method with cement-bentonite grout on 2/18/09.

PSEG ESP BORE. PSEG ESP. 7-07-09 GFI PSEG ESP. GDI. 7/10/09



PERMIT NO.: P200901785		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)					
BORING NO.: EB-3UD		DRILL METHOD: Mud Rotary			SAMPLE METHODS: Shelby/Osterburg/Pitcher			0 HR. ND						
GROUND SURFACE ELEV.: 16.4 US ft (NAVD88)		NORTHING: 232350.2 US ft (NAD83)		EASTING: 202492.3 US ft (NAD83)			24 HR. 9.5							
TOTAL DEPTH: 226.2 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 24.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)						
DATE STARTED: 3/6/09		COMPLETED: 3/11/09		HOLE DIA.: 6"		ROD TYPE: NWJ		BITS USED: 5-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-95.8					Continued from previous page									
-97.4	113.8										UD-15	recovery=1.3ft VINCENTOWN FORMATION -Change sample method to Pitcher Barrel Sampler (continued) 113.8ft: Pitcher tube UD-15 advanced to 116.3ft in Silty SAND (SM), light gray (N 7/), wet, fine sand, strong HCl reaction; recovery=1.8ft		
-101.5	117.9										UD-16	117.9ft: Pitcher tube UD-16 advanced to 120.4ft in Silty SAND (SM), light gray (N 7/), wet, fine to medium sand, strong HCl reaction; recovery=1.8ft		
-105.6	122.0										UD-17	122.0ft: Pitcher tube UD-17 advanced to 124.5ft in Silty SAND (SM), light gray (N 7/), wet, fine sand, strong HCl reaction, with indurated layers; recovery=0.2ft		
-110.7	127.1										UD-18	127.1ft: Pitcher tube UD-18 advanced to 129.6ft in Silty SAND (SM), dark greenish gray (10Y 4/1), moist, fine sand, strong HCl reaction, with friable to moderately indurated layers; recovery=1.5ft		
-115.0	131.4										UD-19	131.4ft: Pitcher tube UD-19 advanced to 133.9ft in Silty SAND (SM), dark greenish gray (10Y 4/1), moist, fine to medium sand, strong HCl reaction, with moderately indurated to indurated layers; recovery=0.9ft		
-123.7	140.1										UD-20	140.1ft: Pitcher tube UD-20 advanced to 142.5ft in Clayey SAND (SC), greenish gray (5G 6/1), moist, fine sand, strong HCl reaction; recovery=0.4ft		
												-127.6	HORNERSTOWN FORMATION	144.0
-132.8	149.2										UD-21	149.2ft: Pitcher tube UD-21 advanced to 151.7ft in Silty SAND (SM), greenish gray (10Y 6/1), moist, fine to medium sand, strong HCl reaction, with indurated layers; recovery=2.3ft		
-135.1	151.5										UD-22	151.5ft: Pitcher tube UD-22 advanced to 154.0ft in Silty SAND (SM), greenish gray (10Y 6/1), moist, fine to medium sand, strong HCl reaction, with indurated layers; recovery=1.0ft		
-143.6	160.0										UD-23	160.0ft: Pitcher tube UD-23 advanced to 161.2ft in Silty SAND (SM), dark greenish gray (5GY 4/1), moist, fine to medium sand, strong HCl reaction, some glauconite; recovery=1.2ft		
												-147.6	NAVESINK FORMATION	164.0
-151.8	168.2													

PSEG ESP BORE PSEG ESP 7-07-09.GP1 PSEG ESP.GDI 7/10/09



PERMIT NO.: P200901785		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-3UD		DRILL METHOD: Mud Rotary			SAMPLE METHODS: Shelby/Osterburg/Pitcher			0 HR. ND				
GROUND SURFACE ELEV.: 16.4 US ft (NAVD88)		NORTHING: 232350.2 US ft (NAD83)		EASTING: 202492.3 US ft (NAD83)			24 HR. 9.5					
TOTAL DEPTH: 226.2 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 24.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)				
DATE STARTED: 3/6/09		COMPLETED: 3/11/09		HOLE DIA.: 6"		ROD TYPE: NWJ		BITS USED: 5-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-208.0					Continued from previous page							
										UD-33		224.2ft: Pitcher tube UD-33 advanced to 226.2ft in Silty SAND (SM), olive gray (5Y 4/2), moist, fine to medium sand, strong HCl reaction; recovery=0.0ft, tube destroyed in extraction, sample jarred MOUNT LAUREL FORMATION (continued) Boring terminated at 226.2 feet. Boring closed by tremie method with cement-bentonite grout on 3/11/09.
												226.2

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP.GDI 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MAN Date 7/16/09

Checked By Jos Date 7/16/09

SHEET 1 OF 4

PERMIT NO.: P200804330		DRILLER: G. McAneny		NJ LICENSE NO.: 0024058		GEOLOGIST: R. Clark										
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)								
BORING NO.: EB-4		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		0 HR.		ND								
GROUND SURFACE ELEV.: 20.3 US ft (NAVD88)		NORTHING: 231783.2 US ft (NAD83)		EASTING: 202017.5 US ft (NAD83)		24 HR.		3.5								
TOTAL DEPTH: 200.2 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 17.0 ft		HAMMER (ID): 140 lb Auto. (CTB-2)										
DATE STARTED: 1/8/09		COMPLETED: 1/13/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit								
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION				
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100			
20.3					Ground Surface								20.3	0.0		
20.3	0.0	29	48	17												
17.7	2.6	4	6	9												
15.3	5.0															
13.0	7.3	2	1	2												
		3	2	2												
10.3	10.0	1	1	1												
7.8	12.5	WOH	WOH	4												
5.3	15.0	3	9	12												
2.8	17.5	4	5	5												
0.5	19.8	3	4	6												
-2.2	22.5	4	2	3												
-4.7	25.0	3	4	5												
-7.2	27.5	2	2	4												
-9.7	30.0	2	2	6												
-12.2	32.5	WOH	1	WOH												
-14.7	35.0	WOH	1	1												
-17.2	37.5	WOH	WOH	WOH												
-19.7	40.0	WOH	WOH	WOH												
-22.2	42.5	WOH	4	4												
-24.7	45.0	WOH	3	5												
-27.2	47.5	WOH	3	2												
-29.7	50.0	8	11	10												
-32.2	52.5	9	9	10												
-34.7	55.0	7	8	7												

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/16/09



PERMIT NO.: P200804330		DRILLER: G. McAneny			NJ LICENSE NO.: 0024058			GEOLOGIST: R. Clark				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-4		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND				
GROUND SURFACE ELEV.: 20.3 US ft (NAVD88)		NORTHING: 231783.2 US ft (NAD83)		EASTING: 202017.5 US ft (NAD83)		24 HR. 3.5						
TOTAL DEPTH: 200.2 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 17.0 ft			HAMMER (ID): 140 lb Auto. (CTB-2)				
DATE STARTED: 1/8/09		COMPLETED: 1/13/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-35.8					Continued from previous page							
-37.2	57.5	9	11	13							SS-24	ALLUVIUM: Poorly graded SAND with silt (SP-SM), greenish gray (10Y 5/1), medium dense, wet, fine to medium sand, trace mica, no HCl reaction (continued)
-39.7	60.0	7	3	2							SS-25	
-42.2	62.5	WOH	WOH	WOH							SS-26	ALLUVIUM: FAT CLAY (CH), dark greenish gray (10Y 4/1), medium stiff, moist, no HCl reaction
-44.7	65.0	1	2	4							SS-27	62.5ft: Very soft, trace angular gravel
-47.2	67.5	WOH	2	3							SS-28	KIRKWOOD FORMATION: FAT CLAY (CH), dark gray (5Y 4/1), medium stiff, moist, trace organics, no HCl reaction
-49.7	70.0	WOH	3	4							SS-29	67.5ft: Greenish gray (10Y 5/1), trace fine sand
-52.2	72.5	7	9	13							SS-30	
-54.7	75.0	WOH	WOH	4							SS-31	KIRKWOOD FORMATION: Poorly graded SAND with silt (SP-SM), dark greenish gray (10Y 4/1), medium dense, wet, fine sand, no HCl reaction
-57.2	77.5	WOH	2	4							SS-32	77.5ft: Medium stiff, no HCl reaction
-59.7	80.0	WOH	1	3							SS-33	KIRKWOOD FORMATION: FAT CLAY (CH), dark greenish gray (10Y 4/1), soft, moist, trace fine sand, trace organics, weak HCl reaction
-62.2	82.5	1	1	1							SS-34	79.5ft: Medium stiff, no HCl reaction
-64.7	85.0	WOH	3	3							SS-35	KIRKWOOD FORMATION: LEAN CLAY (CL), dark greenish gray (10Y 4/1), soft, moist, trace to few fine sand, trace organics, no HCl reaction
-67.2	87.5	2	3	4							SS-36	82.0ft: Dark gray (10YR 4/1)
-69.7	90.0	WOH	WOH	WOH							SS-37	85.0ft: Medium stiff
-72.2	92.5	WOH	2	4							SS-38	87.5ft: Dark gray (10YR 4/1)
-74.7	95.0	WOH	WOH	WOH							SS-39	90.0ft: Dark gray (5Y 4/1), very soft
-77.2	97.5	WOH	WOH	3							SS-40	92.5ft: Dark gray (2.5Y 4/1), medium stiff
-79.7	100.0	WOH	WOH	WOH							SS-41	95.0ft: Very soft
-82.2	102.5	WOH	WOH	2							SS-42	97.5ft: Dark gray (2.5Y 4/1) mottled with olive yellow (2.5Y 6/6), soft
-84.7	105.0	WOR	WOH	3							SS-43	100.0ft: Dark gray (5Y 4/1), very soft
-87.2	107.5	50/0.4									SS-44	102.5ft: Trace laminations
-89.7	110.0	50/0.5									SS-45	105.0ft: Soft
												-Bit chatter/ harder drilling at 107ft
												KIRKWOOD FORMATION: Poorly graded SAND with silt and gravel (SP-SM), olive gray (5Y 4/2), very dense, wet, angular to subrounded gravel, few glauconite

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200804330		DRILLER: G. McAneny			NJ LICENSE NO.: 0024058			GEOLOGIST: R. Clark						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)					
BORING NO.: EB-4		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND						
GROUND SURFACE ELEV.: 20.3 US ft (NAVD88)		NORTHING: 231783.2 US ft (NAD83)		EASTING: 202017.5 US ft (NAD83)			24 HR. 3.5							
TOTAL DEPTH: 200.2 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 17.0 ft			HAMMER (ID): 140 lb Auto. (CTB-2)						
DATE STARTED: 1/8/09		COMPLETED: 1/13/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-91.9		Continued from previous page												
-92.2	112.5	7	6	9							SS-46		VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), olive gray (5Y 4/2), very dense, wet, fine sand, mostly moderately indurated, trace glauconite (continued)	
-94.7	115.0	5	41	31							SS-47		112.5ft: Olive gray (5Y 5/2), medium dense, trace shells, strong HCl reaction, no induration	
-97.2	117.5	11	8	10							SS-48		115.0ft: Greenish gray (10Y 7/1), very dense, few friable to moderately indurated layers, weak HCl reaction	
-99.7	120.0										SS-49		117.5ft: Medium dense	
-102.2	122.5	50/0.4									SS-50		120.0ft: Very dense, little indurated layers	
-104.7	125.0	50/0.4									SS-51		122.5ft: Mostly moderately indurated	
-107.2	127.5	6	50/0.2								SS-52		125.0ft: Greenish gray (10Y 6/1), some moderately indurated layers	
-109.7	130.0	9	10	42							SS-53		-106.2 VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 6/1), very dense, wet, fine sand, few friable to moderately indurated layers, weak HCl reaction, trace glauconite	
-109.7	130.0	50/0.2									SS-54		130.0ft: Moist, mostly moderately indurated	
-112.2	132.5	8	11	50/0.3							SS-55		132.5ft: Moist to wet	
-114.7	135.0	8	14	11							SS-56		-114.2 VINCENTOWN FORMATION: Clayey SAND (SC), greenish gray (10Y 6/1), medium dense, wet, fine sand, weak HCl reaction, trace glauconite	
-117.2	137.5	50/0.4									SS-57		137.5ft: Very dense, moist, mostly moderately indurated, strong HCl reaction	
-119.7	140.0	50/0.3									SS-58		140.0ft: Weak HCl reaction	
-122.2	142.5	3	10	19							SS-59		142.5ft: Medium dense, wet, strong HCl reaction, no induration	
-124.7	145.0	4	50/0.4								SS-60		145.0ft: Very dense	
-127.2	147.5	9	50/0.3								SS-61		-126.7 HORNERSTOWN FORMATION: Clayey SAND (SC), greenish gray (10Y 6/1), very dense, wet, fine sand, strong HCl reaction, trace glauconite	
-129.7	150.0	4	50/0.3								SS-62		150.0ft: Mostly moderately indurated	
-132.2	152.5	6	50/0.3								SS-63			
-134.7	155.0	50/0.3									SS-64			
-137.2	157.5	50/0.3									SS-65			
-139.7	160.0	35	18	25							SS-66		160.0ft: Dense, moist, few moderately indurated layers	
-142.2	162.5	7	39	25							SS-67		-141.7 HORNERSTOWN FORMATION: Silty SAND (SM), dark greenish gray (10Y 4/1), dense, moist to wet, fine sand, trace shell fragments, strong HCl reaction, few to little glauconite	
-144.7	165.0	7	13	25							SS-68		165.0ft: Very dense, moist, mostly indurated	
-147.2	167.5	50/0.3									SS-68			

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP GDT 7/10/09



PERMIT NO.: P200804330		DRILLER: G. McAney		NJ LICENSE NO.: 0024058		GEOLOGIST: R. Clark								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION			COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)							
BORING NO.: EB-4		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT				0 HR.	ND					
GROUND SURFACE ELEV.: 20.3 US ft (NAVD88)		NORTHING: 231783.2 US ft (NAD83)		EASTING: 202017.5 US ft (NAD83)				24 HR.	3.5					
TOTAL DEPTH: 200.2 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 17.0 ft		HAMMER (ID): 140 lb Auto. (CTB-2)								
DATE STARTED: 1/8/09		COMPLETED: 1/13/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100				
-148.0		Continued from previous page												
-149.7	170.0	21	40	50/0.3						SS-69		-148.7	169.0	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (10GY 3/1), very dense, wet, fine sand, trace shell fragments, trace moderately indurated layers, strong HCl reaction, mostly glauconite 172.5ft: Few shell fragments
-152.2	172.5	20	28	50						SS-70				
-154.7	175.0	22	32	45						SS-71				175.0ft: Greenish black (10GY 2.5/1), little shell fragments, weak HCl reaction
-157.2	177.5	22	33	45						SS-72				177.5ft: Very dark greenish gray (5GY 3/1)
-159.7	180.0	9	40	35						SS-73				180.0ft: Trace shell fragments
-162.2	182.5	25	39	46						SS-74				
-164.7	185.0	27	35	50/0.3						SS-75				185.0ft: Moist, strong organic/hydrocarbon odor
-167.2	187.5	34	35	50/0.4						SS-76				187.5ft: Trace shell fragments
-169.7	190.0	18	25	29						SS-77		-169.2	189.5	MOUNT LAUREL FORMATION: Clayey SAND (SC), dark gray (2.5Y 4/1), very dense, moist, fine to coarse rounded to subrounded sand, trace to little shell fragments, trace friable layers, strong HCl reaction, trace to little glauconite 192.5ft: Dark gray (5Y 4/1), fine sand, trace coarse subrounded sand, trace shells, trace friable zones
-172.2	192.5	18	35	50						SS-78				
-174.7	195.0	25	50/0.4							SS-79				
-177.2	197.5	50/0.3								SS-80				197.5ft: Trace to little coarse subrounded to subangular sand
-179.7	200.0	50/0.2								SS-81		-179.9	200.2	200.0ft: Trace coarse rounded to subrounded sand Boring terminated at 200.2 feet. Boring closed by tremie method with cement-bentonite grout on 1/13/09.

PSEG ESP BORE PSEG ESP_7-07-09.GPJ PSEG ESP.GDT 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MAC Date 7/10/09

Checked By JG2 Date 7/10/09

SHEET 1 OF 4

PERMIT NO.: P200804331		DRILLER: T. Samuelson / M. Adams		NJ LICENSE NO.: 0001238 / 0001350		GEOLOGIST: M. Lear									
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)							
BORING NO.: EB-5		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT				0 HR. ND							
GROUND SURFACE ELEV.: 13.8 US ft (NAVD88)		NORTHING: 233048.3 US ft (NAD83)		EASTING: 203016.4 US ft (NAD83)		24 HR. 5.4									
TOTAL DEPTH: 199.3 ft		DRILL MACHINE: CME-850 ATV		CASING DEPTH: 18.5 ft		HAMMER (ID): 140 lb Auto. (CTB-4)									
DATE STARTED: 1/10/09		COMPLETED: 1/14/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100		
13.8					Ground Surface							13.8	0.0		
11.3	2.5	2	4	6										SS-1	ARTIFICIAL FILL: LEAN CLAY (CL), dark brown (10YR 3/3), stiff, moist, few fine gravel, trace fine sand, trace organics
8.1	5.7	6	5	5										SS-2	2.5ft: Very dark grayish brown (10YR 3/2), trace fine gravel, trace to few organics
6.3	7.5	WOH	WOH	WOH										SS-3	HYDRAULIC FILL: FAT CLAY (CH), dark grayish brown (10YR 4/2), very soft, wet, trace fine sand, few organics
3.8	10.0	2	3	7										SS-4	HYDRAULIC FILL: Silty SAND (SM), very dark gray (10YR 3/1), loose, wet, fine to coarse sand, trace fine gravel, few organics
1.3	12.5	1	1	1										SS-5	HYDRAULIC FILL: Sandy SILT (ML), very dark gray (10YR 3/1), very soft, wet, some fine sand, trace organics
-1.2	15.0	WOH	WOH	WOH										SS-6	HYDRAULIC FILL: FAT CLAY (CH), very dark gray (10YR 3/1), very soft, wet, trace fine sand, few organics
-5.5	19.3	WOH	WOH	WOH										SS-7	
-10.8	24.6	WOH	WOH	WOH										SS-8	19.3ft: Trace organics
-15.5	29.3	WOH	WOH	WOH										SS-9	
-20.2	34.0	7	9	11										SS-10	
-25.2	39.0	9	9	8										SS-11	ALLUVIUM: Poorly graded SAND with silt (SP-SM), olive gray (5Y 4/2), medium dense, wet, fine to coarse sand, trace fine gravel
-30.2	44.0	7	6	7										SS-12	ALLUVIUM: Poorly graded SAND with silt and gravel (SP-SM), olive gray (5Y 4/2), medium dense, wet, fine to coarse sand, little fine to coarse gravel
-35.4	49.2	5	6	6										SS-13	49.2ft: Dark gray (5Y 4/1)
-40.2	54.0	3	4	5										SS-14	
														SS-15	KIRKWOOD FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), loose, wet, fine sand, trace fine gravel, no HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200804331		DRILLER: T. Samuelson / M. Adams		NJ LICENSE NO.: 0001238 / 0001350		GEOLOGIST: M. Lear						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251						
BORING NO.: EB-5		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		FLUID LEVEL (ft)						
GROUND SURFACE ELEV.: 13.8 US ft (NAVD88)		NORTHING: 233048.3 US ft (NAD83)		EASTING: 203016.4 US ft (NAD83)		0 HR. ND						
TOTAL DEPTH: 199.3 ft		DRILL MACHINE: CME-850 ATV		CASING DEPTH: 18.5 ft		HAMMER (ID): 140 lb Auto. (CTB-4)						
DATE STARTED: 1/10/09		COMPLETED: 1/14/09		HOLE DIA.: 4"		ROD TYPE: NWJ						
BITS USED: 3-7/8" Drag Bit												
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-42.3					Continued from previous page							
-45.2	59.0	3	4	6							SS-16	KIRKWOOD FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), loose, wet, fine sand, trace fine gravel, no HCl reaction (continued)
-50.2	64.0	6	6	8							SS-17	64.0ft: Medium dense, moist to wet
-55.2	69.0	9	11	13							SS-18	
-60.2	74.0	14	12	12							SS-19	
-65.2	79.0	12	16	17							SS-20	79.0ft: Dense, wet
-70.2	84.0	9	16	15							SS-21	84.0ft: Weak HCl reaction, orange iron staining at very end of sample
-73.2												-Bit chatter from 87ft to 89ft
-75.2	89.0	32	31	33							SS-22	KIRKWOOD FORMATION: Poorly graded GRAVEL with sand (GP), olive gray (5Y 4/2), very dense, moist to wet, fine to coarse subrounded gravel, fine to coarse subangular to subrounded sand -Bit chatter drilling to 94.0 feet
-80.2	94.0	41	35	31							SS-23	94.0ft: No recovery-sample catcher inverted/mangled-same as above based on drill response
-82.2												
-85.2	99.0	22	24	24							SS-24	VINCENTOWN FORMATION: Silty SAND (SM), brown (10YR 5/3), dense to very dense, moist to wet, fine to coarse sand, trace friable layers, trace shell fragments, weak to strong HCl reaction, trace glauconite, moderately oxidized
-90.2	104.0	12	25	28							SS-25	
-95.2	109.0	11	15	12							SS-26	-Bit chatter drilling to 109ft (indurated layers) 109.0ft: Medium dense, strong HCl reaction
												-Bit chatter from 111ft to 112ft

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200804331		DRILLER: T. Samuelson / M. Adams		NJ LICENSE NO.: 0001238 / 0001350		GEOLOGIST: M. Lear							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251							
BORING NO.: EB-5		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		FLUID LEVEL (ft)							
GROUND SURFACE ELEV.: 13.8 US ft (NAVD88)		NORTHING: 233048.3 US ft (NAD83)		EASTING: 203016.4 US ft (NAD83)		0 HR. ND							
TOTAL DEPTH: 199.3 ft		DRILL MACHINE: CME-850 ATV		CASING DEPTH: 18.5 ft		HAMMER (ID): 140 lb Auto. (CTB-4)							
DATE STARTED: 1/10/09		COMPLETED: 1/14/09		HOLE DIA.: 4"		ROD TYPE: NWJ							
BITS USED: 3-7/8" Drag Bit													
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-98.4		Continued from previous page											
-100.2	114.0	9	12	12								SS-27	VINCENTOWN FORMATION: Silty SAND (SM), brown (10YR 5/3), dense to very dense, moist to wet, fine to coarse sand, trace friable layers, trace shell fragments, weak to strong HCl reaction, trace glauconite, moderately oxidized (continued)
-105.2	119.0	17	12	14								SS-28	-Bit chatter from 116ft to 118ft
-110.2	124.0	50/0/0										SS-29	-Hard drilling/bit chatter to 124ft 124.0ft: Very dense, SPT refusal with no penetration at 124.0 feet; hard drilling/bit chatter to 123ft
-115.2	129.0	15	10	18								SS-30	129.0ft: Greenish gray (10Y 6/1), medium dense, trace friable to moderately indurated layers, no oxidation
-120.2	134.0	7	28	31								SS-31	134.0ft: Very dense, wet, trace friable layers
-125.2	139.0	8	22	36								SS-32	
-130.2	144.0	WOH		9	91/0.4							SS-33	144.0ft: Greenish gray (10Y 5/1), moist to wet, few friable to moderately indurated layers
-135.2	149.0	9	58	42/0.4								SS-34	HORNERSTOWN FORMATION: Clayey SAND (SC), greenish gray (10Y 5/1), dense, moist to wet, fine to medium sand, trace shell fragments, few friable layers, strong HCl reaction, few glauconite
-140.2	154.0	6	8	17								SS-35	154.0ft: Medium dense, moist to wet, fine sand, trace glauconite
-145.2	159.0	5	14	21								SS-36	159.0ft: Dark grayish green (10Y 4/1), dense, fine to medium sand, few shell fragments, few to little glauconite
-150.2	164.0	23	27	50								SS-37	NAVESINK FORMATION: Silty SAND (SM), greenish black (5GY 2.5/1), very dense, moist to wet, fine to medium sand, few to little shell fragments, strong HCl reaction, some to mostly glauconite

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200804331		DRILLER: T. Samuelson / M. Adams		NJ LICENSE NO.: 0001238 / 0001350		GEOLOGIST: M. Lear							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251							
BORING NO.: EB-5		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT									
GROUND SURFACE ELEV.: 13.8 US ft (NAVD88)		NORTHING: 233048.3 US ft (NAD83)		EASTING: 203016.4 US ft (NAD83)									
TOTAL DEPTH: 199.3 ft		DRILL MACHINE: CME-850 ATV		CASING DEPTH: 18.5 ft		HAMMER (ID): 140 lb Auto. (CTB-4)							
DATE STARTED: 1/10/09		COMPLETED: 1/14/09		HOLE DIA.: 4"		ROD TYPE: NWJ							
BITS USED: 3-7/8" Drag Bit													
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-154.5					Continued from previous page								
-155.2	169.0	23	32	48									NAVESINK FORMATION: Silty SAND (SM), greenish black (5GY 2.5/1), very dense, moist to wet, fine to medium sand, few to little shell fragments, strong HCl reaction, some to mostly glauconite (continued)
-160.2	174.0	21	28	38									NAVESINK FORMATION: Clayey SAND (SC), greenish black (5GY 2.5/1), very dense, moist, fine to medium sand, trace shell fragments, no to weak HCl reaction, mostly glauconite
-165.2	179.0	34	41	59									NAVESINK FORMATION: Silty SAND (SM), greenish black (5GY 2.5/1), very dense, moist, fine to medium sand, trace shell fragments, trace friable to moderately indurated layers, weak to strong HCl reaction, mostly glauconite
-170.2	184.0	34	43	57/0.4									MOUNT LAUREL FORMATION: Clayey SAND (SC), very dark gray (5Y 3/1), very dense, moist, fine to coarse subrounded sand, trace fine gravel, trace shell fragments, strong HCl reaction, trace glauconite
-175.2	189.0	100/0.4											
-180.2	194.0	100/0.2											
-185.2	199.0	100/0.3											
													Boring terminated at 199.3 feet.
													Boring closed by tremie method with cement-bentonite grout on 1/14/09.

PSEG ESP BORE 7-07-09.GPJ PSEG ESP.GDT 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MM Date 7/10/09

Checked By JDS Date 7/10/09

SHEET 1 OF 4

PERMIT NO.: P200804332		DRILLER: M. Adams			NJ LICENSE NO.: 0001350			GEOLOGIST: B. Deobald / R. Clark						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION					COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)				
BORING NO.: EB-6		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR.	ND					
GROUND SURFACE ELEV.: 13.7 US ft (NAVD88)		NORTHING: 232587.2 US ft (NAD83)		EASTING: 203262.4 US ft (NAD83)			24 HR.	0.0						
TOTAL DEPTH: 199.9 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 54.5 ft			HAMMER (ID): 140 lb Auto. (CTB-4)						
DATE STARTED: 1/26/09		COMPLETED: 2/4/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
13.7					Ground Surface							13.7	0.0	
11.2	2.5	4	8	16	● 24					SS-1		ARTIFICIAL FILL: Silty SAND with gravel (SM), very dark grayish brown (10YR 3/2), medium dense, moist to wet, fine to coarse sand, little angular gravel, trace organics		
9.4	4.3	11	7	7	● 14					SS-2		2.5ft: Few angular to rounded gravel		
6.1	7.6	3	2	2	● 4					SS-3		HYDRAULIC FILL: SILT (ML), very dark greenish gray (10Y 3/1), soft, wet, trace rounded gravel		
3.7	10.0	9	5	12	● 17					SS-4		7.6ft: Very stiff, few rounded gravel		
1.2	12.5	2	3	1	● 4					SS-5		4.2	HYDRAULIC FILL: Silty SAND (SM), very dark greenish gray (10Y 3/1), very loose, wet, fine sand	
-0.9	14.6	WOH	WOH	WOH	● 0					SS-6		1.7	HYDRAULIC FILL: SILT (ML), very dark greenish gray (10Y 3/1), very soft, wet	
-5.8	19.5	WOH	1	2	● 3					SS-7		-0.8	HYDRAULIC FILL: SILT with sand (ML), very dark greenish gray (10Y 3/1), soft, wet, little fine sand	
-10.8	24.5	WOH	1	1	● 2					SS-8		19.5ft: Very dark grayish brown (10YR 3/1), very soft, moist		
-15.8	29.5	WOH	WOH	WOH	● 0					SS-9		-9.3	HYDRAULIC FILL: FAT CLAY (CH), very dark grayish brown (10YR 3/1), very soft, moist	
-20.8	34.5	WOH	WOH	WOH	● 0					SS-10		29.5ft: Black (10YR 2/1)		
-25.8	39.5	5	16	22	● 38					SS-11		-19.3	ALLUVIUM: Poorly graded SAND (SP), dark greenish gray (10Y 4/1), dense, wet, fine to medium sand, trace organics, no HCl reaction	
-30.8	44.5	12	14	10	● 24					SS-12		39.5ft: Medium dense		
-35.8	49.5	15	14	17	● 31					SS-13		-29.3	ALLUVIUM: Silty SAND (SM), greenish gray (10GY 5/1), dense, wet, trace rounded gravel, no HCl reaction	
-40.8	54.5	10	8	9	● 17					SS-14		-34.3	ALLUVIUM: Well graded SAND (SW), dark gray (10YR 4/1), medium dense, wet, little subangular gravel, no HCl reaction	
		8	8	10	● 18					SS-15		-39.3	53.0	KIRKWOOD FORMATION: Poorly graded SAND with silt (SP-SM), greenish gray (5GY 6/1), medium dense, wet, trace subrounded gravel, no HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDI 7/10/09



PERMIT NO.: P200804332		DRILLER: M. Adams			NJ LICENSE NO.: 0001350			GEOLOGIST: B. Deobald / R. Clark				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-6		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND				
GROUND SURFACE ELEV.: 13.7 US ft (NAVD88)		NORTHING: 232587.2 US ft (NAD83)		EASTING: 203262.4 US ft (NAD83)			24 HR. 0.0					
TOTAL DEPTH: 199.9 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 54.5 ft			HAMMER (ID): 140 lb Auto. (CTB-4)				
DATE STARTED: 1/26/09		COMPLETED: 2/4/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-42.4					Continued from previous page							
-45.8	59.5	8	7	8							SS-16	KIRKWOOD FORMATION: Poorly graded SAND with silt (SP-SM), greenish gray (5GY 6/1), medium dense, wet, trace subrounded gravel, no HCl reaction (continued)
-50.8	64.5	3	5	8							SS-17	KIRKWOOD FORMATION: Sandy LEAN CLAY (CL), olive (5Y 5/3) and brownish yellow (10YR 6/8), stiff, moist, some fine sand, no HCl reaction
-55.8	69.5	19	18	15							SS-18	VINCENNTOWN FORMATION: Silty SAND (SM), light greenish gray (10Y 8/1) and brownish yellow (10YR 6/8), dense, moist, fine to coarse sand, few shell fragments, trace rounded gravel, weak HCl reaction 69.5ft: Strongly oxidized
-60.8	74.5	73	14	14							SS-19	74.5ft: Very dense, weak to strong HCl reaction
-65.8	79.5	10	10	13							SS-20	79.5ft: Light greenish gray (10Y 7/1) and brownish yellow (10YR 6/8), medium dense, wet, little shell fragments, moderately oxidized
-70.8	84.5	18	13	15							SS-21	84.5ft: Dense, few shell fragments, weakly oxidized
-75.8	89.5	36	20	13							SS-22	89.5ft: Greenish gray (10GY 6/1) and light greenish gray (10GY 7/1), dense, moist, no oxidation
-80.8	94.5										SS-23	94.5ft: Very dense, with indurated layers
-85.8	99.5										SS-24	99.5ft: Greenish gray (5GY 6/1), very dense, wet, fine to medium sand, weak HCl reaction, trace subrounded gravel, trace shell fragments
-90.8	104.5										SS-25	104.5ft: Dense, moist, weak to strong HCl reaction, trace friable layers
-95.8	109.5										SS-26	109.5ft: Moist to wet, strong HCl reaction -Bit chatter drilling to 114.5 feet

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDI 7/10/09



PERMIT NO.: P200804332		DRILLER: M. Adams		NJ LICENSE NO.: 0001350		GEOLOGIST: B. Deobald / R. Clark						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION			COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)					
BORING NO.: EB-6		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		0 HR. ND	24 HR. 0.0					
GROUND SURFACE ELEV.: 13.7 US ft (NAVD88)		NORTHING: 232587.2 US ft (NAD83)		EASTING: 203262.4 US ft (NAD83)								
TOTAL DEPTH: 199.9 ft		DRILL MACHINE: CME-850 ATV		CASING DEPTH: 54.5 ft		HAMMER (ID): 140 lb Auto. (CTB-4)						
DATE STARTED: 1/26/09		COMPLETED: 2/4/09		HOLE DIA.: 4"		ROD TYPE: NWJ						
						BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-98.5					Continued from previous page							
-100.8	114.5										SS-27	VINCENTOWN FORMATION: Silty SAND (SM), light greenish gray (10Y 8/1) and brownish yellow (10YR 6/8), dense, moist, fine to coarse sand, few shell fragments, trace rounded gravel, weak HCl reaction (continued) 114.5ft: Medium dense, wet, weak HCl reaction
-105.8	119.5										SS-28	119.5ft: Dense, moist -Bit chatter drilling to 124.5 feet
-110.8	124.5										SS-29	124.5ft: Medium dense
-115.8	129.5										SS-30	129.5ft: Very dense, indurated -Hard drilling/bit chatter to 133ft
-120.8	134.5										SS-31	VINCENTOWN FORMATION: Clayey SAND (SC), greenish gray (10Y 5/1), very dense, moist, fine sand, some moderately indurated layers, strong HCl reaction, few to little glauconite -Bit chatter 134.5ft to 135ft, 137ft to 139.5ft, and 139.5ft to 140ft
-125.8	139.5										SS-32	
-130.8	144.5										SS-33	HORNERSTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), dense, moist to wet, fine sand, few moderately indurated layers, strong HCl reaction, little glauconite
-135.8	149.5										SS-34	149.5ft: Very dense
-140.8	154.5										SS-35	154.5ft: Dense, wet
-145.8	159.5										SS-36	159.5ft: Very dense, trace shell fragments, some glauconite
-150.8	164.5										SS-37	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (5GY 3/1), very dense, wet, trace shell fragments, strong HCl reaction, mostly glauconite

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200804332		DRILLER: M. Adams			NJ LICENSE NO.: 0001350			GEOLOGIST: B. Deobald / R. Clark				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-6		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND				
GROUND SURFACE ELEV.: 13.7 US ft (NAVD88)		NORTHING: 232587.2 US ft (NAD83)		EASTING: 203262.4 US ft (NAD83)			24 HR. 0.0					
TOTAL DEPTH: 199.9 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 54.5 ft			HAMMER (ID): 140 lb Auto. (CTB-4)				
DATE STARTED: 1/26/09		COMPLETED: 2/4/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-154.6					Continued from previous page							
-155.8	169.5										SS-38	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (5GY 3/1), very dense, wet, trace shell fragments, strong HCl reaction, mostly glauconite (continued)
-160.8	174.5										SS-39	NAVESINK FORMATION: Clayey SAND (SC), very dark greenish gray (5GY 3/1), very dense, wet, weak HCl reaction, mostly glauconite
-165.8	179.5										SS-40	NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (5GY 3/1), very dense, wet, weak HCl reaction, mostly glauconite
-170.8	184.5										SS-41	MOUNT LAUREL FORMATION: Clayey SAND (SC), olive gray (5Y 4/2), very dense, moist, little coarse subrounded sand, strong HCl reaction, few to little glauconite
-175.8	189.5										SS-42	189.5ft: Dark greenish gray (10GY 4/1), trace glauconite
-180.8	194.5										SS-43	MOUNT LAUREL FORMATION: Silty SAND (SM), dark greenish gray (10GY 4/1), very dense, moist, fine to coarse subrounded sand, little shell fragments, strong HCl reaction, trace glauconite
-185.8	199.5										SS-44	199.5ft: Dark greenish gray (5GY 4/1), trace to little glauconite
												Boring terminated at 199.9 feet.
												Boring closed by tremie method with cement-bentonite grout on 2/04/09.
												NOTE: N-Values at 94.5ft and deeper not reported.

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MM Date 7/10/09

Checked By JAS Date 7/10/09

SHEET 1 OF 3

PERMIT NO.: P200804332		DRILLER: M. Adams / T. Ward			NJ LICENSE NO.: 0001350 / 0001105			GEOLOGIST: B. Deobald							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)						
BORING NO.: EB-6A		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND							
GROUND SURFACE ELEV.: 14.1 US ft (NAVD88)		NORTHING: 232587.0 US ft (NAD83)		EASTING: 203251.3 US ft (NAD83)			24 HR. 15.0								
TOTAL DEPTH: 151.1 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 34.0 ft			HAMMER (ID): 140 lb Auto. (CTB-4)							
DATE STARTED: 2/22/09		COMPLETED: 2/24/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100		
14.1					Ground Surface							14.1	0.0		
14.1	0.0														Driller advanced 4" casing to 34.0 ft and drilled without sampling to 94.6 feet. See EB-6 for information.
4.1	10.0														
-5.9	20.0														
-15.9	30.0														
-25.9	40.0														
-35.9	50.0														

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP GDI 7/10/09



PERMIT NO.: P200804332		DRILLER: M. Adams / T. Ward			NJ LICENSE NO.: 0001350 / 0001105			GEOLOGIST: B. Deobald					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)				
BORING NO.: EB-6A		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND					
GROUND SURFACE ELEV.: 14.1 US ft (NAVD88)		NORTHING: 232587.0 US ft (NAD83)		EASTING: 203251.3 US ft (NAD83)			24 HR. 15.0						
TOTAL DEPTH: 151.1 ft		DRILL MACHINE: CME-850 ATV			CASING DEPTH: 34.0 ft			HAMMER (ID): 140 lb Auto. (CTB-4)					
DATE STARTED: 2/22/09		COMPLETED: 2/24/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-42.0					Continued from previous page								
-45.9	60.0											Driller advanced 4" casing to 34.0 ft and drilled without sampling to 94.6 feet. See EB-6 for information. (continued)	
-55.9	70.0												
-65.9	80.0												
-75.9	90.0												
-80.5	94.6	17	11	43									SS-1
-85.5	99.6	9	8	12								SS-2	99.6ft: Greenish gray (10Y 5/1), medium dense, fine to coarse sand, trace shell fragments, weak HCl reaction
-90.5	104.6	36	20	22								SS-3	104.6ft: Dense, moist, fine to medium sand, trace friable to moderately indurated layers, weak to strong HCl reaction
-95.5	109.6	11	10	11								SS-4	109.6ft: Medium dense, moist to wet, weak HCl reaction -Bit chatter 113ft to 114ft

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200804332		DRILLER: M. Adams / T. Ward		NJ LICENSE NO.: 0001350 / 0001105		GEOLOGIST: B. Deobald						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251						
BORING NO.: EB-6A		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT		FLUID LEVEL (ft)						
GROUND SURFACE ELEV.: 14.1 US ft (NAVD88)		NORTHING: 232587.0 US ft (NAD83)		EASTING: 203251.3 US ft (NAD83)		0 HR. ND						
TOTAL DEPTH: 151.1 ft		DRILL MACHINE: CME-850 ATV		CASING DEPTH: 34.0 ft		HAMMER (ID): 140 lb Auto. (CTB-4)						
DATE STARTED: 2/22/09		COMPLETED: 2/24/09		HOLE DIA.: 4"		ROD TYPE: NWJ						
BITS USED: 3-7/8" Drag Bit												
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-98.1					Continued from previous page							
-100.5	114.6	20	17	13								VINCENTOWN FORMATION: Silty SAND (SM), dark greenish gray (10GY 4/1), very dense, wet, fine to medium sand, trace moderately indurated layers, strong HCl reaction, trace glauconite (continued)
-105.5	119.6	22	14	16								114.6ft: Greenish gray (10Y 6/1), trace friable to moderately indurated layers, weak to strong HCl reaction
-110.5	124.6	35	13	14								119.6ft: wet, trace moderately indurated layers
-115.5	129.6	50/0.2										124.6ft: Trace friable layers, weak HCl reaction
-120.5	134.6	17	50/0.1									129.6ft: Very dense, moist to wet, trace moderately indurated layers
-125.5	139.6	50/0.4										-Bit chatter from 133ft to 134ft
-130.5	144.6	50/0.1										139.6ft: Moist
-135.5	149.6	5	11	17								-Bit chatter 139.6ft to 141ft
												-128.9
												HORNERSTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 6/1), very dense, moist, fine to medium sand, friable to moderately indurated, weak HCl reaction, trace glauconite
												143.0
												149.6ft: Medium dense, wet
												-137.0
												151.1
												Boring terminated at 151.1 feet.
												Boring closed by tremie method with cement-bentonite grout on 2/24/09.

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDI 7/10/09



GEOTECHNICAL BORING LOG

Prepared By NMA Date 7/10/09

Checked By JWS Date 7/10/09

SHEET 1 OF 4

PERMIT NO.: P200900126		DRILLER: T. Ward / G. McAneny			NJ LICENSE NO.: 0001105 / 0024058			GEOLOGIST: M. Lear					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)				
BORING NO.: EB-7		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND					
GROUND SURFACE ELEV.: 17.0 US ft (NAVD88)		NORTHING: 232084.2 US ft (NAD83)		EASTING: 203023.1 US ft (NAD83)			24 HR. 4.2						
TOTAL DEPTH: 200.3 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 14.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)					
DATE STARTED: 12/19/08		COMPLETED: 1/6/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" & 4-7/8" Drag Bits					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
17.0	0.0	14	13	14	Ground Surface							17.0	0.0
14.5	2.5	6	3	3						SS-1		15.0	ARTIFICIAL FILL: Poorly graded GRAVEL with sand (GP), dark gray (2.5Y 4/1), medium dense, wet, trace roots/organics, fine to coarse angular gravel
12.0	5.0	WOH	WOH	WOH						SS-2A/B		14.0	ARTIFICIAL FILL: Poorly graded SAND (SP), grayish brown (2.5Y 5/2), loose, wet, fine to coarse sand, trace coarse gravel
9.8	7.2	5	4	2						SS-3		12.5	HYDRAULIC FILL: SILT (ML), dark gray (2.5Y 4/1), medium stiff, moist, few fine sand, trace organics
7.6	9.4	7	7	8						SS-4		10.0	HYDRAULIC FILL: FAT CLAY (CH), dark gray (N 4/), very soft, wet, trace organics
4.5	12.5	1	1	WOH						SS-5		8.0	HYDRAULIC FILL: Silty SAND (SM), dark gray (10YR 4/1), loose, moist, fine sand, trace mica, trace organics
1.6	15.4	WOH	1	1						SS-6		5.5	HYDRAULIC FILL: Sandy SILT (ML), dark gray (10YR 4/1), stiff, wet, fine to sand, trace organics
-3.0	20.0	1	1	1						SS-7		2.0	HYDRAULIC FILL: LEAN CLAY with sand (CL), dark gray (N 4/), very soft, moist, little fine sand, few organics
-8.0	25.0	WOH	WOH	WOH						SS-8		20.0ft:	Trace to few fine sand partings
-13.0	30.0	WOH	WOH	WOH						SS-9			
-18.0	35.0	WOH	1	1						SS-10		-15.5	HYDRAULIC FILL: FAT CLAY (CH), dark gray (10YR 4/1), very soft, moist, trace fine sand, trace organics
-23.0	40.0	9	6	6						SS-11		-21.0	ALLUVIUM: Poorly graded SAND with silt (SP-SM), olive gray (5Y 5/2), medium dense, wet, fine to coarse subangular sand, trace fine subangular to subrounded gravel
-28.0	45.0	5	4	5						SS-12		45.0ft:	Loose
-33.0	50.0	6	7	7						SS-13		50.0ft:	Medium dense, little fine to coarse subangular to subrounded gravel
-38.0	55.0	3	3	4						SS-14		-37.0	KIRKWOOD FORMATION: Silty SAND (SM), greenish gray (5GY 5/1), loose, wet, fine sand, few to little mica

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900126		DRILLER: T. Ward / G. McAneny			NJ LICENSE NO.: 0001105 / 0024058		GEOLOGIST: M. Lear					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)				
BORING NO.: EB-7		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR. ND				
GROUND SURFACE ELEV.: 17.0		US ft (NAVD88)		NORTHING: 232084.2		US ft (NAD83)		EASTING: 203023.1				
US ft (NAVD88)		NORTHING: 232084.2		US ft (NAD83)		EASTING: 203023.1		US ft (NAD83)				
TOTAL DEPTH: 200.3 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 14.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)					
DATE STARTED: 12/19/08		COMPLETED: 1/6/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" & 4-7/8" Drag Bits				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-39.1					Continued from previous page							
-43.0	60.0	3	8	8							SS-16	KIRKWOOD FORMATION: Silty SAND (SM), greenish gray (5GY 5/1), loose, wet, fine sand, few to little mica (continued) 60.0ft: Medium dense, few mica
-48.0	65.0	2	3	4							SS-17	KIRKWOOD FORMATION: Sandy SILT (ML), greenish gray (5GY 5/1), medium stiff, wet, fine sand, trace to few mica
-53.0	70.0	WOH	3	8							SS-18	KIRKWOOD FORMATION: LEAN CLAY with sand (CL), dark brown (7.5YR 3/2), stiff, moist to wet, little fine sand, few mica, few organics
-58.0	75.0	WOH	WOH	WOH							SS-19	KIRKWOOD FORMATION: Silty, Clayey SAND (SC-SM), dark brown (7.5YR 3/2), loose, moist, fine to medium sand, trace shells, trace organics
-63.0	80.0	2	3	8							SS-20A/B	KIRKWOOD FORMATION: Silty SAND (SM), dark grayish brown (2.5Y 4/2), medium dense, wet, fine sand, trace shells, little mica
-68.0	85.0	3	8	7							SS-21	KIRKWOOD FORMATION: GRAVEL-Not sampled interpreted from bit chatter from 83.0ft to 84.0ft VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 6/1), medium dense, wet, fine to medium sand, few friable to moderately indurated layers, strong HCl reaction
-73.0	90.0	48	23	15							SS-22	90.0ft: Brownish yellow (10YR 6/6), to greenish gray (10Y 6/1), dense, few shell fragments, little friable to moderately indurated layers, few glauconite, weakly oxidized
-78.0	95.0	18	14	16							SS-23	95.0ft: Medium dense, moist, fine to coarse sand, few friable to moderately indurated layers
-83.0	100.0	11	89/0.2								SS-24	VINCENTOWN FORMATION: LEAN CLAY with sand (CL), light greenish gray (10Y 7/1), hard, moist to wet, little fine to medium sand, trace moderately indurated layers, trace shell fragments, strong HCl reaction, trace glauconite
-88.0	105.0	11	11	12							SS-25	VINCENTOWN FORMATION: Silty SAND (SM), light greenish gray (10Y 7/1), medium dense, moist to wet, fine to medium sand, trace moderately indurated layers, few to little shell fragments, strong HCl reaction, trace glauconite
-93.0	110.0	7	17	14							SS-26	110.0ft: Dense

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDI 7/10/09



PERMIT NO.: P200900126		DRILLER: T. Ward / G. McAneny		NJ LICENSE NO.: 0001105 / 0024058		GEOLOGIST: M. Lear							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251							
BORING NO.: EB-7		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT									
GROUND SURFACE ELEV.: 17.0 US ft (NAVD88)		NORTHING: 232084.2 US ft (NAD83)		EASTING: 203023.1 US ft (NAD83)		FLUID LEVEL (ft) 0 HR. ND 24 HR. 4.2							
TOTAL DEPTH: 200.3 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 14.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)							
DATE STARTED: 12/19/08		COMPLETED: 1/6/09		HOLE DIA.: 4"		ROD TYPE: NWJ							
BITS USED: 3-7/8" & 4-7/8" Drag Bits													
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-95.2		Continued from previous page											
-98.0	115.0	8	19	39							SS-27		VINCENTOWN FORMATION: Silty SAND (SM), light greenish gray (10Y 7/1), medium dense, moist to wet, fine to medium sand, trace moderately indurated layers, few to little shell fragments, strong HCl reaction, trace glauconite (continued) 115.0ft: Very dense, few shell fragments, few moderately indurated layers -Bit chatter from 116ft to 117ft
-103.0	120.0	13	11	15							SS-28		120.0ft: Medium dense, trace friable layers
-108.0	125.0	9	91/0.2						100/0.7		SS-29		125.0ft: Very dense, few moderately indurated to indurated layers, trace shell fragments
-113.0	130.0	31	13	17							SS-30		130.0ft: Greenish gray (10Y 5/1), medium dense, moist, few friable to moderately indurated layers
-118.0	135.0	50/0.0							50/0.0		SS-31		135.0ft: No Recovery- SPT refusal with no penetration on indurated layers, very dense -Bit chatter from 138ft to 140ft
-123.0	140.0	7	26	74/0.1					100/0.6		SS-32		VINCENTOWN FORMATION: Clayey SAND (SC), greenish gray (10Y 5/1), very dense, moist, fine to medium sand, few moderately indurated to indurated layers, trace shell fragments, strong HCl reaction, trace glauconite
-128.0	145.0	6	9	14							SS-33		145.0ft: Medium dense -Bit chatter/hard drilling from 147ft to 148ft
-133.0	150.0	10	19	27							SS-34		HORNERSTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), dense, moist, fine sand, trace shell fragments, strong HCl reaction, few to little glauconite
-138.0	155.0	6	11	46							SS-35		155.0ft: Very dense, trace moderate indurated layers
-143.0	160.0	40	58	39							SS-36		160.0ft: Few to little friable to moderately indurated layers, few shell fragments, little glauconite
-148.0	165.0	4	13	26							SS-37		165.0ft: Very dark greenish gray (10Y 3/1), dense, trace shell fragments, some glauconite
													-151.0 168.0

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900126		DRILLER: T. Ward / G. McAneny			NJ LICENSE NO.: 0001105 / 0024058			GEOLOGIST: M. Lear										
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ			MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)								
BORING NO.: EB-7		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT			0 HR.		ND								
GROUND SURFACE ELEV.: 17.0		US ft (NAVD88)			NORTHING: 232084.2			US ft (NAD83)			EASTING: 203023.1		US ft (NAD83)		24 HR.		4.2	
TOTAL DEPTH: 200.3 ft			DRILL MACHINE: CME-75 Truck			CASING DEPTH: 14.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)									
DATE STARTED: 12/19/08		COMPLETED: 1/6/09			HOLE DIA.: 4"			ROD TYPE: NWJ			BITS USED: 3-7/8" & 4-7/8" Drag Bits							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT						SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION					
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100								
-151.3					Continued from previous page													
-153.0	170.0	10	15	26							SS-38		NAVESINK FORMATION: Silty, Clayey SAND (SC-SM), very dark greenish gray (10Y 3/1), dense, moist, fine to medium sand, few shell fragments, weak HCl reaction, mostly glauconite (continued) 170.0ft: N-Value for SS-38 invalid due to insufficient drop height of auto hammer (Hammer operation adjusted prior to drilling/sampling at 175.0ft)					
-158.0	175.0	19	28	44							SS-39		175.0ft: Very dense					
-163.0	180.0	16	23	39							SS-40		-161.0 NAVESINK FORMATION: Clayey SAND (SC), very dark greenish gray (10Y 3/1), very dense, moist, trace shell fragments, weak HCl reaction, mostly glauconite 178.0					
-168.0	185.0	23	37	63/0.3							SS-41		-166.0 NAVESINK FORMATION: Silty SAND (SM), very dark greenish gray (10Y 3/1), very dense, moist, trace shell fragments, trace moderately indurated layers, weak HCl reaction, mostly glauconite 183.0					
-173.0	190.0	37	63/0.4								SS-42		-171.0 MOUNT LAUREL FORMATION: Sandy LEAN CLAY (CL), dark gray (2.5Y 4/1), hard, dry to moist, fine to coarse subrounded sand, few fine subrounded gravel, trace shell fragments, strong HCl reaction, little glauconite 188.0					
-178.0	195.0	100/0.4									SS-43		-175.0 MOUNT LAUREL FORMATION: Silty SAND (SM), dark gray (2.5Y 4/1), very dense, dry to moist, fine to coarse subrounded sand, trace fine subrounded gravel, trace shell fragments, strong HCl reaction, little glauconite 192.0					
-183.0	200.0	100/0.3									SS-44		-183.3 Boring terminated at 200.3 feet. 200.3					
													Boring closed by tremie method with cement-bentonite grout on 1/09/09.					

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP GDT 7/10/09



GEOTECHNICAL BORING LOG

Prepared By MM Date 7/10/09

Checked By JH Date 7/10/09

SHEET 1 OF 6

PERMIT NO.: P200900127		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)						
BORING NO.: EB-8		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT/Shellby Tube				0 HR. ND						
GROUND SURFACE ELEV.: 15.3 US ft (NAVD88)		NORTHING: 231160.7 US ft (NAD83)		EASTING: 203499.7 US ft (NAD83)		24 HR. 4.2								
TOTAL DEPTH: 301.7 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 14.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)								
DATE STARTED: 2/7/09		COMPLETED: 2/19/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
15.3					Ground Surface							15.3	0.0	
15.3	0.0	3	6	8							SS-1		ARTIFICIAL FILL: Clayey SAND with gravel (SC), dark grayish brown (10YR 4/2), medium dense, moist, fine to coarse sand, no HCl reaction, subrounded gravel	2.0
12.8	2.5	5	2	2							SS-2		HYDRAULIC FILL: FAT CLAY (CH), black (N 2.5), soft, moist, no HCl reaction, PP=0.0 tsf	
10.3	5.0	WOH	WOH	WOH							SS-3		5.0ft: Very soft, trace mica	
7.8	7.5	WOH	WOH	WOH							SS-4		7.5ft: Dark gray (N 4/)	
5.3	10.0	WOH	1	WOH							SS-5		10.0ft: Trace organics	
3.0	12.3	WOH	WOH	WOH							SS-6		12.3ft: No recovery-Same as above	
0.5	14.8	WOH	3	2							SS-7A/B		14.0ft: Some fine to medium sand, PP=0.25 tsf	15.4
		WOH											HYDRAULIC FILL: Poorly graded SAND with silt (SP-SM), very dark gray (N 4/), wet, loose, fine to medium sand, no HCl reaction	
-4.8	20.1	WOH	WOH	WOH							SS-8		HYDRAULIC FILL: SILT (ML), very dark gray (N 3/), very soft, moist, no HCl reaction, trace mica, PP=0.0 tsf	19.0
-9.9	25.2	WOH	WOH	WOH							SS-9		25.2ft: Few to little fine sand	
-15.0	30.3	WOH	2	5							SS-10A/B		ALLUVIUM: Poorly graded SAND (SP), dark greenish gray (5GY 4/1), loose, wet, medium to coarse sand, no HCl reaction	31.4
-19.7	35.0	2	2	3							SS-11A/B		ALLUVIUM: PEAT (PT), dark brown (7.5YR 3/3), stiff, moist, no HCl reaction	33.0
-26.1	41.4	7	4	4							SS-12		ALLUVIUM: LEAN CLAY (CL), dark greenish gray (5GY 4/1), stiff, moist, no HCl reaction	36.0
-28.1	43.4										UD-1		ALLUVIUM: Clayey SAND (SC), greenish gray (10GY 6/1), to very dark greenish gray (5GY 3/1), loose, moist, fine to medium sand, no HCl reaction	41.0
-30.7	46.0	2	3	3							SS-13		ALLUVIUM: FAT CLAY (CH), very dark greenish gray (5GY 3/1), moist	43.0
-32.7	48.0										UD-2		43.4ft: Pushed shelby tube UD-1 to 45.4ft, recovery=1.8ft, PP=2.25 tsf	46.0
-35.5	50.8	4	3	1							SS-14		KIRKWOOD FORMATION: Clayey SAND (SC), dark yellowish brown (10YR 4/4), to brown (10YR 4/3), loose, moist, fine to medium sand, no HCl reaction	
-39.7	55.0	WOH	WOH	WOH							SS-15		48.0ft: Pushed shelby tube UD-2 to 50.0ft, recovery=1.8ft	
													50.8ft: Strong brown (7.5YR 4/6), very loose, wet, fine to coarse subrounded sand	
													55.0ft: Yellowish red (5YR 4/6)	

PSEG ESP BORE PSEG ESP 7-07-09 GFI PSEG ESP GDI 7/10/09



PERMIT NO.: P200900127		DRILLER: T. Ward		NJ LICENSE NO.: 0001105		GEOLOGIST: J. Howard								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION			COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)							
BORING NO.: EB-8		DRILL METHOD: Mud Rotary		SAMPLE METHODS: SPT/Shelby Tube		0 HR.	ND							
GROUND SURFACE ELEV.: 15.3 US ft (NAVD88)		NORTHING: 231160.7 US ft (NAD83)		EASTING: 203499.7 US ft (NAD83)		24 HR.	4.2							
TOTAL DEPTH: 301.7 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 14.0 ft		HAMMER (ID): 140 lb Auto. (CBT-1)								
DATE STARTED: 2/7/09		COMPLETED: 2/19/09		HOLE DIA.: 4"		ROD TYPE: NWJ								
						BITS USED: 3-7/8" Drag Bit								
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-40.8		Continued from previous page												
-42.3	57.6										UD-3	-41.7	57.0	KIRKWOOD FORMATION: Sandy SILT (ML), yellowish brown (10YR 5/6), wet, fine to medium sand, no HCl reaction
-44.7	60.0	3	4	6							SS-16	-44.7	60.0	57.6ft: Pushed shelby tube UD-3 to 59.6ft, recovery=1.7ft, PP=0.0 tsf
-49.5	64.8	19	16	9							SS-17	-47.7	63.0	VINCENOWN FORMATION: Sandy SILT (ML), brownish yellow (10YR 6/8), stiff, wet, fine to medium sand, strong HCl reaction, trace friable layers, trace glauconite, strongly oxidized
-51.6	66.9										UD-4			VINCENOWN FORMATION: Silty SAND (SM), brownish yellow (10YR 6/8), medium dense, wet, fine to medium sand, strong HCl reaction, trace friable to moderately indurated layers, trace glauconite, strongly oxidized
-54.2	69.5	7	7	9							SS-18			66.9ft: Pushed shelby tube UD-4 to 68.9ft, recovery=1.9ft
-59.5	74.8	9	8	13							SS-19			69.5ft: Yellowish brown (10YR 5/6)
-64.7	80.0	31	13	10							SS-20			74.8ft: Very pale brown (10YR 7/4), trace friable layers, trace glauconite, moderately oxidized
-66.6	81.9										UD-5			80.0ft: Brownish yellow (10YR 6/6), weakly oxidized
-67.9	83.2	12	22	21							SS-21			81.9ft: Pushed shelby tube UD-5 to 82.4ft, recovery=0.4ft
-74.7	90.0	9	12	12							SS-22			83.2ft: Dense, trace friable to moderately indurated layers
-76.6	91.9										UD-6			90.0ft: Medium dense, trace friable layers
-78.6	93.9	8	46	13							SS-23			91.9ft: Pushed shelby tube UD-6 to 93.7ft, recovery=1.3ft
-84.6	99.9	8	49	18							SS-24			93.9ft: Very dense
-89.7	105.0	9	7	9							SS-25			99.9ft: Yellow (2.5Y 7/6), moist, trace moderately indurated layers
-94.5	109.8	10	12	20							SS-26			105.0ft: Pale yellow (2.5Y 7/3), medium dense, trace shell fragments, very weakly oxidized
														109.8ft: Light brownish gray (2.5Y 6/2), dense, trace friable layers, no oxidation

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP GDT 7/10/09



PERMIT NO.: P200900127		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-8		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT/Shelby Tube					0 HR. ND		
GROUND SURFACE ELEV.: 15.3 US ft (NAVD88)		NORTHING: 231160.7 US ft (NAD83)		EASTING: 203499.7 US ft (NAD83)						24 HR. 4.2		
TOTAL DEPTH: 301.7 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 14.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)				
DATE STARTED: 2/7/09		COMPLETED: 2/19/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-96.9		Continued from previous page										
-99.7	115.0	21	13	11							SS-27	VINCENTOWN FORMATION: Silty SAND (SM), brownish yellow (10YR 6/8), medium dense, wet, fine to medium sand, strong HCl reaction, trace friable to moderately indurated layers, trace glauconite, strongly oxidized (continued) 115.0ft: Greenish gray (10Y 5/1), medium dense, wet
-104.7	120.0	9	12	12							SS-28	120.0ft: Greenish gray (10Y 6/1)
-109.8	125.1	11	9	12							SS-29	125.1ft: Greenish gray (10Y 5/1), moist
-114.5	129.8	8	8	8							SS-30	129.8ft: Greenish gray (10Y 6/1), wet
-119.5	134.8	18	7	16							SS-31	
-124.7	140.0	100/0.4								100/0.4	SS-32	140ft: Very dense, indurated
-129.7	145.0	15	9	19							SS-33	145.0ft: Medium dense
-134.5	149.8	100/0.3								100/0.3	SS-34	149.8ft: Very dense, moderately indurated
-137.2		HORNERSTOWN FORMATION: Clayey SAND (SC), greenish gray (10Y 5/1), very dense, moist, fine to medium sand, few friable layers, strong HCl reaction, trace to few glauconite										152.5
-139.7	155.0	44	15	39							SS-35	
-144.7	160.0	9	26	36							SS-36	160ft: Greenish gray (10Y 6/1), trace friable layers
-149.9	165.2	8	92/0.4							100/0.9	SS-37	165.2ft: Trace moderately indurated layers, few to little glauconite

PSEG ESP BORE PSEG ESP 7-07-09 GPI PSEG ESP GDI 7/10/09



PERMIT NO.: P200900127		DRILLER: T. Ward			NJ LICENSE NO.: 0001105			GEOLOGIST: J. Howard				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-8		DRILL METHOD: Mud Rotary			SAMPLE METHODS: SPT/Shelby Tube					0 HR. ND		
GROUND SURFACE ELEV.: 15.3 US ft (NAVD88)		NORTHING: 231160.7 US ft (NAD83)		EASTING: 203499.7 US ft (NAD83)			24 HR. 4.2					
TOTAL DEPTH: 301.7 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 14.0 ft			HAMMER (ID): 140 lb Auto. (CBT-1)				
DATE STARTED: 2/7/09		COMPLETED: 2/19/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-153.0					Continued from previous page							
-154.6	169.9	9	17	48							SS-38	169.9ft: Very dark greenish gray (5GY 3/1), weak HCl reaction, trace shell fragments, some glauconite
-159.7	175.0	25	39	59							SS-39	172.0ft: HORNERSTOWN FORMATION: Clayey SAND (SC), greenish gray (10Y 5/1), very dense, moist, fine to medium sand, few friable layers, strong HCl reaction, trace to few glauconite (continued)
-164.7	180.0	27	33	36							SS-40	180.0ft: NAVESINK FORMATION: Silty SAND (SM), black (N 2.5), very dense, moist, fine to medium sand, few shell fragments, strong HCl reaction, mostly glauconite
-169.7	185.0	41	38	51							SS-41	185.0ft: Weak HCl reaction, trace shell fragments
-174.7	190.0	27	33	52							SS-42	185.0ft: Very dark grayish green (5G 2.5/2)
-179.9	195.2	40	60/0.3								SS-43	190.0ft: Very dark grayish green (5G 2.5/2) to greenish black (10Y 2.5/1), few shell fragments
-184.5	199.8	100/0.4									SS-44	192.0ft: MOUNT LAUREL FORMATION: Clayey SAND (SC), very dark greenish gray (10Y 3/1), very dense, moist, fine to coarse subrounded sand, strong HCl reaction, little glauconite
-194.5	209.8	100/0.3									SS-45	199.8ft: Dry
-204.7	220.0	18	50	50/0.3							SS-46	209.8ft: Dark greenish gray (10Y 4/1), fine to medium sand, few glauconite
												215.0ft: MOUNT LAUREL FORMATION: Silty SAND (SM), dark greenish gray (10Y 4/1), very dense, wet, fine to medium sand, weak to strong HCl reaction, few glauconite

PSEG ESP BORE PSEG ESP 7-07-09.CPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900127	DRILLER: T. Ward	NJ LICENSE NO.: 0001105	GEOLOGIST: J. Howard
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: EB-8	DRILL METHOD: Mud Rotary	SAMPLE METHODS: SPT/Shelby Tube	
GROUND SURFACE ELEV.: 15.3 US ft (NAVD88)		NORTHING: 231160.7 US ft (NAD83)	EASTING: 203499.7 US ft (NAD83)
TOTAL DEPTH: 301.7 ft	DRILL MACHINE: CME-75 Truck	CASING DEPTH: 14.0 ft	HAMMER (ID): 140 lb Auto. (CBT-1)
DATE STARTED: 2/7/09	COMPLETED: 2/19/09	HOLE DIA.: 4"	ROD TYPE: NWJ
BITS USED: 3-7/8" Drag Bit			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-209.1					Continued from previous page							
-214.5	229.8	31	50	50/0.4						100/0.8	SS-47	229.8ft: Dark greenish gray (5GY 4/1), trace to few glauconite
-224.6	239.9	38	45	55/0.4						100/0.8	SS-48	239.9ft: No HCl reaction, trace shell fragments, trace glauconite
-234.7	250.0	63	37/0.3							100/0.8	SS-49	
-244.7	260.0	58	42/0.3							100/0.8	SS-50	
-254.5	269.8	43	57/0.4							100/0.8	SS-51	269.8ft: Wet
-264.7	280.0											280.0ft: Weak HCl reaction

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900127		DRILLER: D. Osuch			NJ LICENSE NO.: 0024289			GEOLOGIST: M. Lear				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-8G		DRILL METHOD: Mud Rotary			SAMPLE METHODS: NA					0 HR. ND		
GROUND SURFACE ELEV.: 15.7 US ft (NAVD88)			NORTHING: 231153.3 US ft (NAD83)		EASTING: 203528.3 US ft (NAD83)			24 HR. 3.2				
TOTAL DEPTH: 315.0 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 9.0 ft			HAMMER (ID): 140 lb Auto. (CTB-3)				
DATE STARTED: 1/22/09		COMPLETED: 1/23/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag & Roller Cone Bits				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-152.6					Continued from previous page							
												HORNERSTOWN FORMATION: SAND-Not sampled, intermittent bit chatter/hard drilling throughout, trace to some glauconite in drill fluid return, glauconite increases with depth. (continued)
												-156.3 172.0
												NAVESINK FORMATION: SAND-Not sampled, Some to mostly glauconite, few shell fragments in drill fluid return.
												-176.3 192.0
												MOUNT LAUREL FORMATION: SAND-Not sampled, hard drilling throughout, coarse sand, fine gravel, trace glauconite in drill fluid return.
												195.0ft: Boring choked off around drill bit overnight, pull rods and change bit from roller cone to drag bit, driller mixes fresh mud.

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900127		DRILLER: D. Osuch		NJ LICENSE NO.: 0024289		GEOLOGIST: M. Lear	
SITE DESCRIPTION: PSEG SITE ESP APPLICATION			COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)
BORING NO.: EB-8G		DRILL METHOD: Mud Rotary		SAMPLE METHODS: NA		0 HR. ND	24 HR. 3.2
GROUND SURFACE ELEV.: 15.7 US ft (NAVD88)		NORTHING: 231153.3 US ft (NAD83)		EASTING: 203528.3 US ft (NAD83)			
TOTAL DEPTH: 315.0 ft		DRILL MACHINE: CME-75 Truck		CASING DEPTH: 9.0 ft		HAMMER (ID): 140 lb Auto. (CTB-3)	
DATE STARTED: 1/22/09		COMPLETED: 1/23/09		HOLE DIA.: 4"		ROD TYPE: NWJ	
BITS USED: 3-7/8" Drag & Roller Cone Bits							

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-208.7													Continued from previous page
													MOUNT LAUREL FORMATION: SAND-Not sampled, hard drilling throughout, coarse sand, fine gravel, trace glauconite in drill fluid return. (continued)

PSEG ESP BORE PSEG ESP 7-07-09.GPJ PSEG ESP.GDT 7/10/09



PERMIT NO.: P200900127		DRILLER: D. Osuch			NJ LICENSE NO.: 0024289			GEOLOGIST: M. Lear				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EB-8G		DRILL METHOD: Mud Rotary			SAMPLE METHODS: NA			0 HR. ND				
GROUND SURFACE ELEV.: 15.7 US ft (NAVD88)		NORTHING: 231153.3 US ft (NAD83)		EASTING: 203528.3 US ft (NAD83)			24 HR. 3.2					
TOTAL DEPTH: 315.0 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: 9.0 ft			HAMMER (ID): 140 lb Auto. (CTB-3)				
DATE STARTED: 1/22/09		COMPLETED: 1/23/09		HOLE DIA.: 4"		ROD TYPE: NWJ		BITS USED: 3-7/8" Drag & Roller Cone Bits				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-264.8					Continued from previous page							
												MOUNT LAUREL FORMATION: SAND-Not sampled, hard drilling throughout, coarse sand, fine gravel, trace glauconite in drill fluid return. (continued)
												300.0ft: Driller mixes fresh mud
												-288.3 WENONAH FORMATION: SAND-Not sampled (Interpreted from geophysical log) 304.0
												315.0ft: Driller mixes fresh mud and flushes hole, pulls rods for geophysical testing
												-299.3 Boring terminated at 315.0 feet. 315.0
												Boring closed by tremie method with cement-bentonite grout on 1/24/09.

PSEG ESP BORE PSEG ESP 7-07-09.CPJ PSEG ESP.GDT 7/10/09

Observation Well Boring Logs



PERMIT NO.: P200900115		DRILLER: R. Tabor		NJ LICENSE NO.: 0001335		GEOLOGIST: R. Clark							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251							
BORING NO.: NOW-2L		DRILL METHOD: Rotosonic		SAMPLE METHODS: Rotosonic disturbed soil core									
GROUND SURFACE ELEV.: 8.3 US ft (NAVD88)		NORTHING: 235227.7 US ft (NAD83)		EASTING: 197752.8 US ft (NAD83)									
TOTAL DEPTH: 115.0 ft		DRILL MACHINE: Minisonic Track		CASING DEPTH: 115		HAMMER (ID): NA							
DATE STARTED: 1/22/09		COMPLETED: 1/22/09		HOLE DIA.: 6"		ROD TYPE: Sonic							
BITS USED: 4" Auger Core Bit													
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
8.3					Ground Surface							8.3	0.0
8.3	0.0										RUN 1		ARTIFICIAL FILL: Poorly graded SAND with silt and gravel (SP-SM), dark grayish brown (10YR 4/2), moist, angular gravel, trace organics
											S-1		HYDRAULIC FILL: FAT CLAY (CH), dark olive gray (5Y 3/2), moist, trace to little fine sand, some organics, no HCl reaction
-1.7	10.0										RUN 2		10.0ft: Dark gray (2.5Y 4/1), little organics
											S-2		
-11.7	20.0										RUN 3		
											S-3		
-21.7	30.0										RUN 4		30.0ft: Dark gray (5Y 4/1), to black (5Y 2.5/1), trace fine sand lenses
											S-3		
-31.7	40.0										RUN 5		
											S-4		
											S-5		ALLUVIUM: Clayey SAND (SC) and interbedded poorly graded SAND with silt (SP-SM), dark greenish gray (10Y 4/1), wet, fine sand, trace glauconite, no to weak HCl reaction
-41.7	50.0										RUN 6		ALLUVIUM: LEAN CLAY with sand (CL), dark olive gray (5Y 3/2), moist to wet, some organics, no HCl reaction
											S-6		
-51.7	60.0										RUN 7		ALLUVIUM: Poorly graded SAND with silt (SP-SM), grayish brown (2.5Y 5/2), wet, fine to coarse sand, trace subrounded to rounded gravel, no HCl reaction, trace mica
											S-7		
-61.7	70.0										RUN 8		68.0ft: FAT CLAY (CH) lense to 68.5ft VINCENTOWN FORMATION: Clayey SAND (SC), yellowish brown (10YR 5/4), wet, fine sand, no to weak HCl reaction, moderately oxidized
											S-8		
											S-9		
											RUN 8		
													68.5

PSEG ESP BORE PSEG ESP 6-15-09 GPT PSEG ESP GDT 6/16/09



PERMIT NO.: P200900117		DRILLER: R. Tabor			NJ LICENSE NO.: 0001335			GEOLOGIST: R. Clark				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: NOW-3L		DRILL METHOD: Rotasonic			SAMPLE METHODS: Rotasonic disturbed soil core			0 HR. ND				
GROUND SURFACE ELEV.: 7.4		US ft (NAVD88)		NORTHING: 234565.5 US ft (NAD83)		EASTING: 197897.9 US ft (NAD83)		24 HR. ND				
TOTAL DEPTH: 102.5 ft		DRILL MACHINE: Minisonic Track			CASING DEPTH: 102.5			HAMMER (ID): NA				
DATE STARTED: 1/20/09		COMPLETED: 1/21/09		HOLE DIA.: 6"		ROD TYPE: Sonic		BITS USED: 4" Auger Core Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-67.4					Continued from previous page							
-72.6	80.0									S-13		VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), greenish gray (10Y 5/1), wet, fine sand, trace shell fragments, strong HCl reaction, trace friable to moderately indurated layers, glauconitic (continued)
										RUN 9		
										S-14		
-82.6	90.0									RUN 10		
										S-15		
										RUN 11		
-92.6	100.0											
Boring terminated at 102.5 feet and observation well NOW-3L constructed. Boring logged to establish the general geologic conditions for the selection of observation well depths and well screen intervals. For complete strata and soil descriptions see geotechnical boring NB-3.												

PSEG ESP BORE PSEG ESP 6-15-09.GPJ PSEG ESP.GDT 6/16/09



GEOTECHNICAL BORING LOG

Prepared By mm Date 6/17/09

Checked By JG Date 6/17/09

SHEET 1 OF 2

PERMIT NO.: P200900119		DRILLER: R. Bartholomew			NJ LICENSE NO.: 0001383			GEOLOGIST: S. Johnson/J. Howard										
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)									
BORING NO.: NOW-4L		DRILL METHOD: Mud Rotary with Reverse Circulation			SAMPLE METHODS: SPT			0 HR. ND										
GROUND SURFACE ELEV.: 10.6 US ft (NAVD88)		NORTHING: 233972.7 US ft (NAD83)		EASTING: 198147.9 US ft (NAD83)			24 HR. ND											
TOTAL DEPTH: 85.0 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: NA			HAMMER (ID): 140 lb. Auto (CTB-5)										
DATE STARTED: 1/22/09		COMPLETED: 1/24/09		HOLE DIA.: 6"		ROD TYPE: NWJ		BITS USED: 3-7/8" & 5-7/8" Drag Bit										
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION						
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100					
10.6					Ground Surface							10.6	0.0					
															Drill without sampling to 18.0 feet. Boring advanced with a 4" drag bit during sampling, then reamed with a 6" drag bit for observation well installation.			
-7.4	18.0	WOH	WOH	WOH											-7.4	18.0	HYDRAULIC FILL: ELASTIC SILT (MH), dark greenish gray (5GY 4/1), very soft, moist, trace sand, trace mica, trace shells, no HCl reaction	
-12.7	23.3	WOH	WOH	WOH														
-17.4	28.0	5	4	4														HYDRAULIC FILL: Sandy ELASTIC SILT (MH), dark greenish gray (5GY 4/1), medium stiff, wet, little to some fine sand, few shell fragments, no HCl reaction
-22.4	33.0	WOH	2	1														33.0ft: Very dark greenish gray (5GY 3/1), soft, moist
-27.5	38.1	1	1	1														ALLUVIUM: Silty SAND (SM), very dark greenish gray (5GY 3/1), very loose, wet, fine to medium sand, no HCl reaction
-32.4	43.0	2	3	5														ALLUVIUM: Poorly graded SAND with silt (SP-SM), gray (N 5), loose, wet, fine to medium sand, no HCl reaction
-37.4	48.0	8	11	15														ALLUVIUM: Clayey SAND (SC), dark grayish brown (10YR 4/2), medium dense, moist, fine to medium sand, few fine gravel, no HCl reaction
-42.3	52.9	6	2	2														KIRKWOOD FORMATION: SILT (ML), brownish yellow (10YR 6/8), soft, moist, no HCl reaction
																		Drill without sampling to 62.9 feet.
-52.3	62.9	6	6	11														KIRKWOOD FORMATION: Sandy LEAN CLAY (CL), very dark gray (N 3), very stiff, moist, no HCl reaction
-57.2	67.8	8	11	23														VINCENTOWN FORMATION: Silty, clayey SAND (SC-SM), dark greenish gray (5GY 4/1), dense, moist, fine to medium sand, strong HCl reaction, glauconitic
-62.4	73.0	6	6	9														

PSEG ESP BORE PSEG ESP 6-15-09 GPI PSEG ESP.GDT. 6/17/09



PERMIT NO.: P200900119		DRILLER: R. Bartholomew			NJ LICENSE NO.: 0001383			GEOLOGIST: S. Johnson/J. Howard						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)					
BORING NO.: NOW-4L		DRILL METHOD: Mud Rotary with Reverse Circulation			SAMPLE METHODS: SPT					0 HR. ND				
GROUND SURFACE ELEV.: 10.6 US ft (NAVD88)			NORTHING: 233972.7 US ft (NAD83)		EASTING: 198147.9 US ft (NAD83)					24 HR. ND				
TOTAL DEPTH: 85.0 ft		DRILL MACHINE: CME-75 Truck			CASING DEPTH: NA			HAMMER (ID): 140 lb. Auto (CTB-5)						
DATE STARTED: 1/22/09		COMPLETED: 1/24/09		HOLE DIA.: 6"		ROD TYPE: NWJ		BITS USED: 3-7/8" & 5-7/8" Drag Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-64.2					Continued from previous page									
-67.4	78.0	15	12	14						SS-12		VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (5GY 6/1), medium dense, moist, fine to medium sand, strong HCl reaction (<i>continued</i>) 78.0ft: Greenish gray (5GY 5/1), trace shell fragments		
-72.4	83.0	11	19	72						SS-13		83.0ft: Very dense, weak to strong HCl reaction		
												-74.4	85.0	<p>Boring terminated at 85.0 feet and observation well NOW-4L constructed.</p> <p>Boring logged to establish the general geologic conditions for the selection of observation well depths and well screen intervals. For complete strata and soil descriptions see geotechnical boring NB-4.</p>

PSEG ESP BORE PSEG ESP 6-15-09.GPJ PSEG ESP.GDT 6/17/09



GEOTECHNICAL BORING LOG

Prepared By Max Date 6/17/09

Checked By JOS Date 6/17/09

SHEET 1 OF 2

PERMIT NO.: P200900123	DRILLER: R. Tabor	NJ LICENSE NO.: 0001335	GEOLOGIST: R. Clark
SITE DESCRIPTION: PSEG SITE ESP APPLICATION		COUNTY: Salem, NJ	MACTEC PROJECT NO.: 6468-08-2251
BORING NO.: NOW-5L	DRILL METHOD: Rotasonic	SAMPLE METHODS: Rotasonic disturbed soil core	
GROUND SURFACE ELEV.: 7.6 US ft (NAVD88)		NORTHING: 234927.5 US ft (NAD83)	EASTING: 198438.4 US ft (NAD83)
TOTAL DEPTH: 102.3 ft	DRILL MACHINE: Minisonic Track	CASING DEPTH: 102.3	HAMMER (ID): NA
DATE STARTED: 1/26/09	COMPLETED: 1/26/09	HOLE DIA.: 6"	ROD TYPE: Sonic
BITS USED: 4" Auger Core Bit			

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
7.6					Ground Surface							7.6	0.0
7.6	0.0										RUN 1		ARTIFICIAL FILL: LEAN CLAY with gravel (CL), very dark grayish brown (2.5Y 3/2), wet, trace organics, few sand, no HCL reaction
											S-1		HYDRAULIC FILL: FAT CLAY with gravel (CH), greenish black (10Y 3/1), moist to wet, no HCl reaction
-2.5	10.0										RUN 2		10.0ft: FAT CLAY (CH), very dark greenish gray (5GY 3/1), moist to wet, little fine sand, no HCl reaction
											S-2		
											RUN 3		20.0ft: Very dark gray (5Y 3/1), moist
											S-3		
-12.5	20.0										RUN 4		
											S-4		
											RUN 5		
											S-5		ALLUVIUM: Poorly graded SAND with clay (SP-SC), greenish gray (5GY 5/1), wet, no HCl reaction, trace glauconite
-22.5	30.0										RUN 6		ALLUVIUM: Poorly graded SAND with silt (SP-SM), greenish gray (5GY 5/1), wet, trace subrounded gravel, trace glauconite, no HCl reaction
											S-6		KIRKWOOD FORMATION: FAT CLAY (CH), dark olive gray (5Y 3/2), moist, no HCl reaction
											RUN 7		
											S-7		
											RUN 8		
											S-8		KIRKWOOD FORMATION: Clayey SAND (SC), dark gray (5Y 4/1), wet, fine sand, no HCl reaction
											S-9		KIRKWOOD FORMATION: Poorly graded GRAVEL with silt and sand (GP-GM), dark gray (5Y 4/1), wet, subrounded, no HCl reaction
-42.5	50.0										RUN 9		VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), olive gray (5Y 4/2), to reddish brown (5Y 4/3), wet, no HCl reaction, strongly oxidized
											S-10		70.0ft: Yellowish brown (10YR 5/4), strong HCl reaction
-52.5	60.0												
-62.5	70.0												

PSEG ESP BORE PSEG ESP 6-15-09.GPJ PSEG ESP.GDT 6/17/09



GEOTECHNICAL BORING LOG

Prepared By WAC Date 6/16/09

Checked By BJ Date 6/17/09

SHEET 1 OF 2

PERMIT NO.: P200900121		DRILLER: R. Tabor		NJ LICENSE NO.: 0001335		GEOLOGIST: R. Clark							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251							
BORING NO.: NOW-6L		DRILL METHOD: Rotasonic		SAMPLE METHODS: Rotasonic disturbed soil core									
GROUND SURFACE ELEV.: 7.8 US ft (NAVD88)		NORTHING: 235287.9 US ft (NAD83)		EASTING: 198312.8 US ft (NAD83)		FLUID LEVEL (ft) 0 HR. ND 24 HR. ND							
TOTAL DEPTH: 92.3 ft		DRILL MACHINE: Minisonic Track		CASING DEPTH: 92.3		HAMMER (ID): NA							
DATE STARTED: 1/25/09		COMPLETED: 1/25/09		HOLE DIA.: 6"		ROD TYPE: Sonic							
						BITS USED: 4" Auger Core Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
7.8					Ground Surface							7.8	0.0
7.8	0.0									RUN 1		ARTIFICIAL FILL: FAT CLAY (CH), very dark greenish gray (5GY 3/1), moist to wet, little angular gravel and sand	0.0
										S-1		HYDRAULIC FILL: FAT CLAY (CH), very dark greenish gray (5GY 3/1), moist to wet, few organics, no HCl reaction	5.0
-2.2	10.0									RUN 2		10.0ft: Wet, little sand, trace gravel	
										S-2			
										RUN 3		20.0ft: Very dark greenish gray (10Y 3/1), trace sand, trace organics	
										S-3			
-12.2	20.0									RUN 4			
										S-4			
										RUN 5			
										S-5		ALLUVIUM: poorly graded SAND with silt (SP-SM), greenish gray (10Y 5/1), wet, fine sand, little subangular to subrounded gravel, no HCl reaction	39.0
-22.2	30.0									RUN 6			
										S-6			
										RUN 7			
										S-7			
-32.2	40.0									RUN 8			
										S-8		KIRKWOOD FORMATION: FAT CLAY (CH), dark olive gray (5Y 3/2), moist, trace fine sand, no HCl reaction	44.5
										RUN 9			
										S-9			
-42.2	50.0									RUN 10			
										S-10		KIRKWOOD FORMATION: Clayey SAND (SC), olive gray (5Y 5/2), wet	63.0
										RUN 11		KIRKWOOD FORMATION: Silty SAND (SM), olive gray (5Y 5/2), wet, fine to coarse sand, trace subrounded gravel, no HCl reaction	64.0
										S-11			
										RUN 12		VINCEN TOWN FORMATION: Poorly graded SAND with clay (SP-SC), greenish gray (10Y 6/1), wet, fine sand, glauconitic, strong HCl reaction	67.0
										S-12			
-52.2	60.0									RUN 13			
										S-13			
										RUN 14			
										S-14			
-62.2	70.0									RUN 15			
										S-15			
										RUN 16			
										S-16			
										RUN 17			
										S-17			
										RUN 18			
										S-18			
										RUN 19			
										S-19			
										RUN 20			
										S-20			
										RUN 21			
										S-21			
										RUN 22			
										S-22			
										RUN 23			
										S-23			
										RUN 24			
										S-24			
										RUN 25			
										S-25			
										RUN 26			
										S-26			
										RUN 27			
										S-27			
										RUN 28			
										S-28			
										RUN 29			
										S-29			
										RUN 30			
										S-30			
										RUN 31			
										S-31			
										RUN 32			
										S-32			
										RUN 33			
										S-33			
										RUN 34			
										S-34			
										RUN 35			
										S-35			
										RUN 36			
										S-36			
										RUN 37			
										S-37			
										RUN 38			
										S-38			
										RUN 39			
										S-39			
										RUN 40			
										S-40			
										RUN 41			
										S-41			
										RUN 42			
										S-42			
										RUN 43			
										S-43			
										RUN 44			
										S-44			
										RUN 45			
										S-45			
										RUN 46			
										S-46			
										RUN 47			
										S-47			
										RUN 48			
										S-48			
										RUN 49			
										S-49			
										RUN 50			
										S-50			
										RUN 51			
										S-51			
										RUN 52			
										S-52			
										RUN 53			
										S-53			
										RUN 54			
										S-54			
										RUN 55			
										S-55			
										RUN 56			
										S-56			
										RUN 57			
										S-57			
										RUN 58			
										S-58			
										RUN 59			
										S-59			
										RUN 60			
										S-60			
										RUN 61			
										S-61			
										RUN 62			
										S-62			
										RUN 63			
										S-63			
										RUN 64			
										S-64			
										RUN 65			
										S-65			
										RUN 66			
										S-66			
										RUN 67			
										S-67			
										RUN 68			
										S-68			
										RUN 69			
										S-69			
										RUN 70			
										S-70			
										RUN 71			
										S-71			
										RUN 72			
										S-72			
										RUN 73			
										S-73			
										RUN 74			
										S-74			
										RUN 75			
										S-75			
										RUN 76			
										S-76			
										RUN 77			
										S-77			
										RUN 78			
										S-78			
										RUN 79			
										S-79			
										RUN 80			
										S-80			
										RUN 81			
										S-81			
										RUN 82			
										S-82			
										RUN 83			
										S-83			
										RUN 84			
										S-84			
										RUN 85			
			</										



PERMIT NO.: P200900121		DRILLER: R. Tabor			NJ LICENSE NO.: 0001335			GEOLOGIST: R. Clark						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)					
BORING NO.: NOW-6L		DRILL METHOD: Rotosonic			SAMPLE METHODS: Rotosonic disturbed soil core					0 HR. ND				
GROUND SURFACE ELEV.: 7.8 US ft (NAVD88)		NORTHING: 235287.9 US ft (NAD83)		EASTING: 198312.8 US ft (NAD83)						24 HR. ND				
TOTAL DEPTH: 92.3 ft		DRILL MACHINE: Minisonic Track			CASING DEPTH: 92.3			HAMMER (ID): NA						
DATE STARTED: 1/25/09		COMPLETED: 1/25/09		HOLE DIA.: 6"		ROD TYPE: Sonic		BITS USED: 4" Auger Core Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
-67.0					Continued from previous page									
-72.2	80.0									S-10		VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), strong brown (7.5YR 4/6), wet, fine to medium sand, strong HCl reaction, glauconitic, strongly oxidized (<i>continued</i>) 80.0ft: Greenish gray (10Y 6/1), no oxidation		
										RUN 9				
										S-11				
-82.2	90.0									RUN 10				
												-84.5	92.3	Boring terminated at 92.3 feet and observation well NOW-6L constructed. Boring logged to establish the general geologic conditions for the selection of observation well depths and well screen intervals. For complete strata and soil descriptions see geotechnical boring NB-6.

PSEG ESP BORE PSEG ESP 6-15-09.GPJ PSEG ESP.GDT 6/16/09



GEOTECHNICAL BORING LOG

Prepared By NR Date 6/16/09

Checked By JAJ Date 6/17/09

SHEET 1 OF 2

PERMIT NO.: P200900095		DRILLER: R. Tabor		NJ LICENSE NO.: 0001335		GEOLOGIST: R. Clark									
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)							
BORING NO.: NOW-7L		DRILL METHOD: Rotosonic		SAMPLE METHODS: Rotosonic disturbed soil core				0 HR. ND							
GROUND SURFACE ELEV.: 6.1 US ft (NAVD88)		NORTHING: 234973.4 US ft (NAD83)		EASTING: 199675.9 US ft (NAD83)				24 HR. ND							
TOTAL DEPTH: 97.0 ft		DRILL MACHINE: Minisonic Track		CASING DEPTH: 97.0		HAMMER (ID): NA									
DATE STARTED: 1/23/09		COMPLETED: 1/24/09		HOLE DIA.: 6"		ROD TYPE: Sonic		BITS USED: 4" Auger Core Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100		
6.1													6.1	0.0	Ground Surface
6.1	0.0										RUN 1		4.1	2.0	ARTIFICIAL FILL: FAT CLAY with gravel and sand (CH), very pale brown (10YR 7/3)
											S-1				HYDRAULIC FILL: FAT CLAY (CH), very dark greenish gray (10Y 3/1), wet, few organics, trace gravel and sand, no HCl reaction
-3.9	10.0										RUN 2				
											S-2				
-13.9	20.0										RUN 3		-13.9	20.0	ALLUVIUM: Clayey SAND (SC), dark greenish gray (10Y 4/1), wet, few shell fragments, little angular gravel
											S-3		-16.9	23.0	ALLUVIUM: FAT CLAY (CH), very dark greenish gray (10Y 3/1), wet, few fine sand, no HCl reaction
											S-4		-22.9	29.0	ALLUVIUM: Clayey SAND (SC), dark greenish gray (10Y 4/1), wet, trace angular gravel, no HCl reaction
-23.9	30.0										RUN 4		-26.4	32.5	KIRKWOOD FORMATION: LEAN CLAY with sand and gravel (CL), brown (10YR 5/3), moist, subangular to subrounded gravel and sand, no HCl reaction
											S-5				
-33.9	40.0										RUN 5		-33.9	40.0	VINCEN TOWN FORMATION: Clayey SAND (SC), yellowish brown (10YR 5/6), wet, fine sand, strong HCl reaction, strongly oxidized
											S-6				
-43.9	50.0										RUN 6		-42.4	48.5	VINCEN TOWN FORMATION: Poorly graded SAND with silt (SP-SM), yellowish brown (10YR 5/6), wet, fine sand, strong HCl reaction, strongly oxidized
											S-7				
-53.9	60.0										RUN 7		-57.4	63.5	VINCEN TOWN FORMATION: Poorly graded SAND with clay (SP-SC), light yellowish brown (10YR 6/4), wet, fine sand, strong HCl reaction, moderately oxidized
											S-8				
-63.9	70.0										RUN 8		-65.4	71.5	
											S-9				
											RUN 8				

PSEG ESP BORE PSEG ESP. 6-15-09 GFI PSEG ESP. GDT. 6/16/09



GEOTECHNICAL BORING LOG

Prepared By MM Date 6/16/09

Checked By JG Date 6/17/09

SHEET 1 OF 2

PERMIT NO.: P200900105		DRILLER: C. Marsh			NJ LICENSE NO.: 0001190			GEOLOGIST: T. Longley						
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)					
BORING NO.: EOW-2L		DRILL METHOD: Rotosonic			SAMPLE METHODS: Rotosonic disturbed soil core					0 HR. ND				
GROUND SURFACE ELEV.: 13.9 US ft (NAVD88)		NORTHING: 233271.5 US ft (NAD83)		EASTING: 202177.7 US ft (NAD83)			24 HR. ND							
TOTAL DEPTH: 111.0 ft		DRILL MACHINE: Prosonic Truck			CASING DEPTH: 111.0			HAMMER (ID): NA						
DATE STARTED: 1/26/09		COMPLETED: 1/26/09		HOLE DIA.: 6"		ROD TYPE: Sonic		BITS USED: 4" Auger Core Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
13.9					Ground Surface							13.9	0.0	
13.9	0.0									RUN 1		ARTIFICIAL FILL: SILT with sand (ML), very dark grayish brown (2.5Y 3/2), moist, trace rounded gravel	11.4	2.5
6.9	7.0									S-1		HYDRAULIC FILL: Silty SAND (SM), black (2.5Y 2.5/1), to greenish black (10GY 2.5/1), moist, trace fine to coarse rounded gravel; gravel and silt increase with depth		
										RUN 2				
										S-2		HYDRAULIC FILL: FAT CLAY (CH), dark greenish gray (10Y 3/1), moist, no HCl reaction, trace to few organics, few fine sand partings	1.6	12.3
-3.1	17.0									RUN 3				
										S-3				
-13.1	27.0									RUN 4		27.0ft: Greenish black (5GY 2.5/1)		
										S-4				
-23.1	37.0									RUN 5				
										S-5		ALLUVIUM: Well graded SAND (SW), light brownish gray (10YR 6/2), wet, few fine gravel	-25.1	39.0
										RUN 6				
-33.1	47.0									S-6		ALLUVIUM: Silty SAND (SM), dark gray (10YR 4/1), wet, fine to medium sand ALLUVIUM: FAT CLAY (CH), very dark gray (10YR 3/1), moist, no HCl reaction	-33.1	47.0
										RUN 7				
-43.1	57.0									S-7		KIRKWOOD FORMATION: FAT CLAY (CH), very dark grayish brown (2.5Y 3/2), moist, few to little shell fragments, no HCl reaction	-41.1	55.0
										RUN 8				
-53.1	67.0									S-8		67.0ft: Very dark gray (2.5Y 3/1) mottled with light yellowish brown (10YR 6/4), trace shell fragments		

PSEG ESP BORE PSEG ESP 6-15-09 GFI PSEG ESP GDI 6/16/09



GEOTECHNICAL BORING LOG

Prepared By nm Date 6/17/09

Checked By JGJ Date 6/17/09

SHEET 1 OF 2

PERMIT NO.: P200900109		DRILLER: M. Adams		NJ LICENSE NO.: 0001350		GEOLOGIST: B. Deobald										
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251										
BORING NO.: EOW-6L		DRILL METHOD: Mud Rotary with Reverse Circulation		SAMPLE METHODS: SPT		FLUID LEVEL (ft)										
GROUND SURFACE ELEV.: 13.3 US ft (NAVD88)		NORTHING: 232588.1 US ft (NAD83)		EASTING: 203300.7 US ft (NAD83)		0 HR. ND										
TOTAL DEPTH: 102.0 ft		DRILL MACHINE: CME-850 Track		CASING DEPTH: 9.3		HAMMER (ID): 140 lb. Auto (CTB-4)										
DATE STARTED: 1/22/09		COMPLETED: 1/23/09		HOLE DIA.: 6"		ROD TYPE: NWJ										
BITS USED: 3-7/8" & 5-7/8" Drag Bits																
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION				
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100			
13.3					Ground Surface							13.3	0.0			
															Drill without sampling to 19.6 feet, set 4" casing to 9.3 feet. Boring advanced with a 4" drag bit during sampling, then reamed with a 6" drag bit for observation well installation.	
-6.4	19.6	1	WOH	1											19.6	HYDRAULIC FILL: Sandy SILT (ML), very dark greenish gray (10Y 3/1), very soft, moist to wet, little sand, trace organics
-11.4	24.6	WOH	WOH	WOH											24.6	24.6ft: SILT (ML), soft, few sand
-16.4	29.6	WOH	WOH	WOH											28.0	HYDRAULIC FILL: FAT CLAY (CH), very dark greenish gray (10Y 3/1), very soft, moist, trace fine sand
-21.4	34.6	4	4	6											33.0	ALLUVIUM: Well graded SAND (SW), very dark gray (10YR 3/1), loose, wet, fine to coarse sand, trace angular gravel
-26.4	39.6	3	7	5											38.0	ALLUVIUM: LEAN CLAY (CL), light gray (10YR 7/1) mottled very pale brown (10YR 7/4), soft, moist
-31.4	44.6	4	2	4											43.0	ALLUVIUM: Silty SAND (SM), gray (10YR 6/1), loose, moist to wet, fine sand
-36.4	49.6	12	14	17											48.5	ALLUVIUM: Well graded SAND with gravel (SW), light olive gray (5Y 6/2), dense, wet, little sub-angular to rounded gravel
-41.3	54.5	10	5	16											53.0	ALLUVIUM: Poorly graded SAND (SP), light olive gray (5Y 6/2), medium dense, moist to wet, fine to medium sand, trace sub-angular to rounded gravel
															56.0	Drill without sampling to 84.5 feet. Continue SPT's at 84.5 feet

PSEG ESP BORE PSEG ESP 6-15-09 GFI PSEG ESP GDI 6/17/09



PERMIT NO.: P200900109		DRILLER: M. Adams			NJ LICENSE NO.: 0001350			GEOLOGIST: B. Deobald					
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)				
BORING NO.: EOW-6L		DRILL METHOD: Mud Rotary with Reverse Circulation			SAMPLE METHODS: SPT					0 HR. ND			
GROUND SURFACE ELEV.: 13.3 US ft (NAVD88)		NORTHING: 232588.1 US ft (NAD83)		EASTING: 203300.7 US ft (NAD83)						24 HR. ND			
TOTAL DEPTH: 102.0 ft		DRILL MACHINE: CME-850 Track			CASING DEPTH: 9.3			HAMMER (ID): 140 lb. Auto (CTB-4)					
DATE STARTED: 1/22/09		COMPLETED: 1/23/09		HOLE DIA.: 6"		ROD TYPE: NWJ		BITS USED: 3-7/8" & 5-7/8" Drag Bits					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100
-61.6					Continued from previous page								
-71.3	84.5	18	13	15							SS-9	-71.3	84.5
-76.3	89.5	20	13	15							SS-10	-74.8	88.0
-81.3	94.5	14	8	11							SS-11		
-86.3	99.5	40	16	14							SS-12		
												Drill without sampling to 84.5 feet. Continue SPT's at 84.5 feet (continued)	
												VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), very pale brown (10YR 7/2), mottled yellow (10YR 7/6), dense, moist, fine to medium sand, trace shell fragments, weak HCl reaction, weakly oxidized VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (5GY 6/1), medium dense, moist, fine to coarse sand, few shell fragments, trace friable layers, weak to strong HCl reaction, no oxidation 94.5ft: Moist to wet, fine to medium sand, trace shell fragments, trace rounded gravel, weak HCl reaction	
												99.5ft: Greenish gray (5GY 6/1), to dark greenish gray (5GY 4/1), very dense, glauconitic	
												Boring terminated at 102.0 feet and observation well EOW-6L constructed. Boring logged to establish the general geologic conditions for the selection of observation well depths and well screen intervals. For complete strata and soil descriptions see geotechnical boring EB-6.	

PSEG ESP BORE PSEG ESP 6-15-09.GPJ PSEG ESP.GDT 6/17/09



GEOTECHNICAL BORING LOG

Prepared By MM Date 6/16/09

Checked By JR Date 6/17/09

SHEET 1 OF 2

PERMIT NO.: P200900111		DRILLER: C. Marsh		NJ LICENSE NO.: 0001190		GEOLOGIST: T. Longley								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)						
BORING NO.: EOW-8L		DRILL METHOD: Rotosonic		SAMPLE METHODS: Rotosonic disturbed soil core				0 HR. ND						
GROUND SURFACE ELEV.: 15.4 US ft (NAVD88)		NORTHING: 231163.5 US ft (NAD83)		EASTING: 203516.0 US ft (NAD83)		24 HR. ND								
TOTAL DEPTH: 79.0 ft		DRILL MACHINE: Prosonic Truck		CASING DEPTH: 79.0		HAMMER (ID): NA								
DATE STARTED: 1/25/09		COMPLETED: 1/25/09		HOLE DIA.: 6"		ROD TYPE: Sonic		BITS USED: 4" Auger Core Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100				
15.4					Ground Surface							15.4	0.0	
15.4	0.0										RUN 1		ARTIFICIAL FILL: Poorly graded SAND with silt (SP-SM), brown (7.5YR 4/3), moist, trace gravel	
													11.9	3.5
8.4	7.0										S-1		HYDRAULIC FILL: FAT CLAY (CH), black (5Y 2.5/1), moist, trace organics, trace to few fine sand partings, no HCl reaction	
											RUN 2			
											S-2			
-1.6	17.0												-1.6	17.0
											RUN 3		HYDRAULIC FILL: Silty SAND (SM), black (5Y 2.5/1), wet, no HCl reaction	
											S-3			
													-4.6	20.0
											S-4		HYDRAULIC FILL: FAT CLAY (CH), black (5Y 2.5/1), moist, trace organics, few fine sand partings	
-11.6	27.0										RUN 4			
											S-5		ALLUVIUM: Poorly graded SAND (SP), gray (5Y 6/1), wet, no HCl reaction	
													-17.6	33.0
											S-6		ALLUVIUM: FAT CLAY (CH), black (5Y 2.5/1), moist, little organics, no HCl reaction	
											S-7		ALLUVIUM: PEAT (PT), dark reddish brown (5YR 3/2), moist, mostly organics, grades into SILT (ML), gray (N 5/), no HCl reaction	
-21.6	37.0										RUN 5		ALLUVIUM: Silty SAND (SM), greenish gray (10Y 5/1), moist, fine sand, trace to little gravel (increases with depth)	
											S-8			
											S-9		KIRKWOOD FORMATION: SILT (ML), brown (10YR 4/3), moist, no HCl reaction	
-31.6	47.0										RUN 6		47.0ft: Dark yellowish brown (10YR 4/4), moist to wet, few to little fine to coarse sand	
											S-10			
-41.6	57.0										RUN 7		VINCENTOWN FORMATION: Silty SAND (SM), reddish brown (5YR 4/4), wet, fine sand, no HCl reaction, strongly oxidized	
											S-11		57.0ft: Strong brown (7.5YR 5/6), no to strong HCl reaction, trace friable layers	
-51.6	67.0										RUN 8		VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), light yellowish brown (2.5Y 6/4), wet, strong HCl reaction, trace friable layers, moderately oxidized	
											S-12			
													-52.6	68.0

PSEG ESP BORE PSEG ESP 6-15-09 GFI PSEG ESP GDI 6/16/09



PERMIT NO.: P200900111		DRILLER: C. Marsh			NJ LICENSE NO.: 0001190			GEOLOGIST: T. Longley				
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)			
BORING NO.: EOW-8L		DRILL METHOD: Rotosonic			SAMPLE METHODS: Rotosonic disturbed soil core					0 HR. ND		
GROUND SURFACE ELEV.: 15.4 US ft (NAVD88)		NORTHING: 231163.5 US ft (NAD83)		EASTING: 203516.0 US ft (NAD83)						24 HR. ND		
TOTAL DEPTH: 79.0 ft		DRILL MACHINE: Prosonic Truck			CASING DEPTH: 79.0			HAMMER (ID): NA				
DATE STARTED: 1/25/09		COMPLETED: 1/25/09		HOLE DIA.: 6"		ROD TYPE: Sonic		BITS USED: 4" Auger Core Bit				
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft	0	20	40	60	80			
-59.4					Continued from previous page							
-61.6	77.0									RUN 9		VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), light yellowish brown (2.5Y 6/4), wet, strong HCl reaction, trace friable layers, moderately oxidized (continued) 76.0ft: Light gray (2.5Y 7/2), weakly oxidized Boring terminated at 79.0 feet and observation well EOW-8L constructed. Boring logged to establish the general geologic conditions for the selection of observation well depths and well screen intervals. For complete strata and soil descriptions see geotechnical boring EB-8.

PSEG ESP BORE PSEG ESP 6-15-09.GPJ PSEG ESP.GDT 6/16/09



PERMIT NO.: P200900100		DRILLER: C. Marsh			NJ LICENSE NO.: 0001190			GEOLOGIST: T. Longley							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)						
BORING NO.: EOW-9L		DRILL METHOD: Rotosonic			SAMPLE METHODS: Rotosonic disturbed soil core				0 HR.	ND					
GROUND SURFACE ELEV.: 17.9 US ft (NAVD88)		NORTHING: 230925.6 US ft (NAD83)		EASTING: 202844.6 US ft (NAD83)			24 HR.		ND						
TOTAL DEPTH: 129.0 ft		DRILL MACHINE: Prosonic Truck			CASING DEPTH: 129			HAMMER (ID): NA							
DATE STARTED: 1/20/09		COMPLETED: 1/20/09		HOLE DIA.: 6"		ROD TYPE: Sonic		BITS USED: 4" Auger Core Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100					
-56.9					Continued from previous page										
-59.1	77.0										S-12	KIRKWOOD FORMATION: FAT CLAY (CH), very dark greenish gray (10Y 3/1), moist, little shell fragments, no HCl reaction, trace fine sand, trace organics (continued) 77.0ft: Trace shell fragments			
											RUN 9				
											S-13				
-69.1	87.0										RUN 10	87.0ft: Sand increasing			
											S-14	-71.6	KIRKWOOD FORMATION: Poorly graded SAND (SP), greenish gray (10Y 5/1), to gray (5Y 5/1), wet, fine to coarse sand, no HCl reaction		
-79.1	97.0										RUN 11	97.0ft: Light gray (5Y 7/1)			
											S-15	-84.1	KIRKWOOD FORMATION: FAT CLAY (CH), very dark gray (5Y 3/1), moist, few organics		
											S-16	-87.1	VINCENTOWN FORMATION: Poorly graded SAND (SP), dark greenish gray (10Y 4/1), to light greenish gray (10Y 7/1), and greenish gray (10Y 6/1), wet, fine to medium sand, glauconitic, weak to strong HCl reaction, trace indurated layers		
-89.1	107.0										RUN 12				
											S-17				
-99.1	117.0										RUN 13	-99.1	VINCENTOWN FORMATION: Silty SAND (SM), greenish gray (10Y 5/1), to olive gray (5Y 5/1), wet, weak HCl reaction, few indurated layers		
											S-18				
												-111.1	117.0		
													129.0	Boring terminated at 129.0 feet and observation well EOW-9L constructed. Boring logged to establish the general geologic conditions for the selection of observation well depths and well screen intervals.	

PSEG ESP BORE PSEG ESP 6-15-09.GPJ PSEG ESP.GDT 6/16/09



GEOTECHNICAL BORING LOG

Prepared By MM Date 6/16/09

Checked By JAD Date 6/17/09

SHEET 1 OF 2

PERMIT NO.: P200900102		DRILLER: C. Marsh		NJ LICENSE NO.: 0001190		GEOLOGIST: T. Longley								
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251		FLUID LEVEL (ft)						
BORING NO.: EOW-10L		DRILL METHOD: Rotosonic		SAMPLE METHODS: Rotosonic disturbed soil core				0 HR. ND						
GROUND SURFACE ELEV.: 11.7 US ft (NAVD88)		NORTHING: 231706.7 US ft (NAD83)		EASTING: 203521.9 US ft (NAD83)		24 HR. ND								
TOTAL DEPTH: 97.0 ft		DRILL MACHINE: Prosonic Truck		CASING DEPTH: 97		HAMMER (ID): NA								
DATE STARTED: 1/22/09		COMPLETED: 1/22/09		HOLE DIA.: 6"		ROD TYPE: Sonic		BITS USED: 4" Auger Core Bit						
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100	
11.7					Ground Surface							11.7	0.0	
11.7	0.0										RUN 1			ARTIFICIAL FILL: SILT with sand and gravel (ML), dark reddish brown (5YR 3/4), dry
4.7	7.0										S-1		6.7	HYDRAULIC FILL: FAT CLAY (CH), black (5Y 2/5), wet, trace sand and gravel
											RUN 2			7.0ft: Very dark gray (N 3/), moist to wet, few fine sand partings, trace organics
-5.3	17.0										S-2			
											RUN 3			17.0ft: Black (5Y 2.5/1), moist, little organics
											S-3			
-15.3	27.0										RUN 4			
											S-4		-17.3	ALLUVIUM: Poorly graded SAND (SP), yellowish brown (10YR 5/4), to grayish brown (2.5Y 5/2), wet, trace fines, trace rounded gravel
											RUN 5		-22.3	
											S-5		-23.3	ALLUVIUM: Sandy SILT (SM), light olive brown (2.5Y 5/3), wet, trace gravel
-25.3	37.0										RUN 6		-25.3	KIRKWOOD FORMATION: FAT CLAY (CH), black (2.5Y 2.5/1), moist, trace organics
											S-6			KIRKWOOD FORMATION: SILT (ML), greenish black (10Y 2.5/1), moist, trace fine sand, trace organics, no HCl reaction
											RUN 7			
											S-7		-36.8	KIRKWOOD FORMATION: Poorly graded SAND (SP), very dark greenish gray (10Y 3/1), wet, trace fines, trace rounded gravel, no HCl reaction
											RUN 8		-39.6	VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), greenish gray (10Y 6/1), wet, trace gravel, strong HCl reaction, trace friable layers
											S-8			
											RUN 9			57.0ft: Moist to wet, few moderately indurated layers
											S-9			
											RUN 10			
											S-10			

PSEG ESP BORE PSEG ESP 6-15-09.GPJ PSEG ESP.GDI 6/16/09



PERMIT NO.: P200900102		DRILLER: C. Marsh			NJ LICENSE NO.: 0001190			GEOLOGIST: T. Longley							
SITE DESCRIPTION: PSEG SITE ESP APPLICATION				COUNTY: Salem, NJ		MACTEC PROJECT NO.: 6468-08-2251			FLUID LEVEL (ft)						
BORING NO.: EOW-10L		DRILL METHOD: Rotosonic			SAMPLE METHODS: Rotosonic disturbed soil core			0 HR. ND							
GROUND SURFACE ELEV.: 11.7 US ft (NAVD88)		NORTHING: 231706.7 US ft (NAD83)		EASTING: 203521.9 US ft (NAD83)			24 HR. ND								
TOTAL DEPTH: 97.0 ft		DRILL MACHINE: Prosonic Truck			CASING DEPTH: 97			HAMMER (ID): NA							
DATE STARTED: 1/22/09		COMPLETED: 1/22/09		HOLE DIA.: 6"		ROD TYPE: Sonic		BITS USED: 4" Auger Core Bit							
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT						SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
		0.5ft	0.5ft	0.5ft	0	20	40	60	80	100					
-63.1					Continued from previous page										
-65.3	77.0										RUN 9		VINCENTOWN FORMATION: Poorly graded SAND with silt (SP-SM), greenish gray (10Y 6/1), wet, trace gravel, strong HCl reaction, trace friable layers (continued) 77.0ft: Pale olive yellow (5Y 6/3)		
											S-11				
-75.3	87.0										RUN 10				
											S-12				
													-85.3	97.0	Boring terminated at 97.0 feet and observation well EOW-10L constructed. Boring logged to establish the general geologic conditions for the selection of observation well depths and well screen intervals.

PSEG ESP BORE PSEG ESP 6-15-09.GPJ PSEG ESP.GDT 6/16/09