

CHAPTER 6—ENGINEERED SAFETY FEATURES LIST OF TABLES

| | | |
|----------------|---|---------|
| Table 6.1-1 | Pressure-Retaining Material Specifications for Engineered Safety Features..... | 6.1-19 |
| Table 6.1-2 | Coatings Classifications and Uses..... | 6.1-27 |
| Table 6.2.1-1 | Loss of Coolant Accidents | 6.2-35 |
| Table 6.2.1-2 | Main Steam Line Breaks..... | 6.2-40 |
| Table 6.2.1-3 | LHSI Heat Exchanger Data..... | 6.2-42 |
| Table 6.2.1-4 | Containment Heat Sink Inventory | 6.2-43 |
| Table 6.2.1-5 | Containment Initial and Boundary Conditions..... | 6.2-69 |
| Table 6.2.1-6 | Containment Response to Hot Leg Breaks..... | 6.2-70 |
| Table 6.2.1-7 | Containment Response Cold Leg Pump Suction Breaks | 6.2-71 |
| Table 6.2.1-8 | Containment Response Cold Leg Pump Discharge Breaks | 6.2-73 |
| Table 6.2.1-9 | Peak Containment Pressure and Temperature for MSLB | 6.2-74 |
| Table 6.2.1-10 | Critical Rooms Containing HELBs | 6.2-77 |
| Table 6.2.1-11 | Evaluated Subcompartment HELBs | 6.2-81 |
| Table 6.2.1-12 | Mass and Energy Discharge Rates for Bounding High Energy Line Breaks | 6.2-87 |
| Table 6.2.1-13 | Safety Grade Doors Credited to Open in Subcompartment Analyses | 6.2-90 |
| Table 6.2.1-14 | Mass and Energy Discharge Rates for Feedwater Lines (LABn0BR005)..... | 6.2-91 |
| Table 6.2.1-15 | Mass and Energy Discharge Rates for Letdown and Charging Lines | 6.2-93 |
| Table 6.2.1-16 | Subcompartment Volumes (For Subcompartments Where the Pressure Increase is More Than 5 psi)..... | 6.2-96 |
| Table 6.2.1-17 | Subcompartment Vent Paths (For Subcompartments Where the Pressure Increase is More Than 5 psi)..... | 6.2-97 |
| Table 6.2.1-18 | Subcompartment Peak HELB Pressures..... | 6.2-101 |
| Table 6.2.1-19 | Mass and Energy Results for the Limiting Hot Leg Break | 6.2-102 |
| Table 6.2.1-20 | Mass and Energy Result for the Limiting Cold Leg Pump Suction Break..... | 6.2-121 |



| | | |
|----------------|---|---------|
| Table 6.2.1-21 | Mass and Energy Results for the Limiting Cold Leg Pump Discharge Break | 6.2-136 |
| Table 6.2.1-22 | Input Summary for Mass and Energy Release | 6.2-164 |
| Table 6.2.1-23 | Containment Energy Distribution for Cold Leg Pump Suction Break Energy (BTU)..... | 6.2-165 |
| Table 6.2.1-24 | MSLB Mass and Energy Release Data | 6.2-167 |
| Table 6.2.1-25 | MSLB Reactor Trip and Isolation Signal Summary..... | 6.2-177 |
| Table 6.2.3-1 | Design and Performance of Annulus Ventilation System | 6.2-250 |
| Table 6.2.3-2 | Secondary Containment Response Analysis..... | 6.2-251 |
| Table 6.2.3-3 | Instrumentation, Indication, and Alarm Features for AVS (Accident Filtration Trains)..... | 6.2-253 |
| Table 6.2.4-1 | Containment Penetration, Isolation Valve, and Actuator Data | 6.2-265 |
| Table 6.2.5-1 | CGCS Design and Performance Parameters | 6.2-307 |
| Table 6.2.5-2 | HMS Design and Performance Parameters..... | 6.2-308 |
| Table 6.2.5-3 | Combustible Gas Control System Failure Modes and Effects Analysis..... | 6.2-309 |
| Table 6.3-1 | Accumulators Design and Operating Parameters..... | 6.3-26 |
| Table 6.3-2 | Low Head Safety Injection Pumps Design and Operating Parameters | 6.3-27 |
| Table 6.3-3 | Medium Head Safety Injection Pumps Design and Operating Parameters | 6.3-28 |
| Table 6.3-4 | LHSI Heat Exchanger Design and Operating Parameters..... | 6.3-29 |
| Table 6.3-5 | Total Debris Source Term..... | 6.3-30 |
| Table 6.3-6 | Safety Injection System Failure Modes and Effects Analysis | 6.3-31 |
| Table 6.5-1 | Primary Containment Operations Following a Design Basis Accident | 6.5-11 |
| Table 6.8-1 | Extra Borating System Design and Operating Parameters..... | 6.8-6 |

Next File