

REGULATORY INFORMATION DISTRIBUTION SYSTEM (RIDS)

ACCESSION NBR:9412080137 DOC.DATE: 94/12/01 NOTARIZED: NO DOCKET # FACIL: 50-261 H.B. Robinson Plant, Unit 2, Carolina Power & Light C 05000261 AUTHOR AFFILIATION KRICH, R.M. Carolina Power & Light Co. RECIP. NAME RECIPIENT AFFILIATION Document Control Branch (Document Control Desk) SUBJECT: Provides info verbally requested by NRC re testing of installed spare safety injection pump at facility. $_{
m L}$ ENCL $\mathcal O$ DISTRIBUTION CODE: A001D COPIES RECEIVED:LTR TITLE: OR Submittal: General Distribution NOTES: COPIES RECIPIENT RECIPIENT COPIES ID CODE/NAME LTTR ENCL ID CODE/NAME LTTR ENCL PD2-1 LA PD2-1 PD MOZAFARI, B 1 INTERNAL: FILE_CENTER 1 NRR/DRCH/HICB NRR/DSSA/SCSB NRR/DSSA/SPLB 1 1 NRR/DSSA/SRXB 1 NUDOCS-ABSTRACT 1 OGC/HDS3 1

NRC PDR

1

NOTE TO ALL "RIDS" RECIPIENTS:

EXTERNAL: NOAC

PLEASE HELP US TO REDUCE WASTE! CONTACT THE DOCUMENT CONTROL DESK, ROOM P1-37 (EXT. 504-2083) TO ELIMINATE YOUR NAME FROM DISTRIBUTION LISTS FOR DOCUMENTS YOU DON'T NEED!

TOTAL NUMBER OF COPIES REQUIRED: LTTR 12 ENCL

1

mart

Ρ

R

D

С

Μ

E

Ν

T



Carolina Power & Light Company

Robinson Nuclear Plant PO Box 790 Hartsville SC 29551

Robinson File No.: 13510

Serial: RNP/94-1939

DEC 0 1 1994

United States Nuclear Regulatory Commission

Attention: Document Control Desk

Washington, DC 20555

H. B. ROBINSON STEAM ELECTRIC PLANT, UNIT NO. 2 DOCKET NO. 50-261/LICENSE NO. DPR-23 TESTING OF SAFETY INJECTION PUMPS

Gentlemen:

The purpose of this letter is to provide information verbally requested by the NRC Project Manager regarding testing of the installed spare safety injection pump at the H. B. Robinson Steam Electric Plant (HBRSEP), Unit No. 2.

The installed spare pump is tested in accordance with Operations Surveillance Test (OST)-151, "Safety Injection System Component Test (Quarterly)," to demonstrate operability prior to being used in place of either of the other two pumps. OST-155, "Safety Injection System Integrity Test (Refueling)," would also be completed on the installed spare pump if not performed at the last regularly scheduled interval. Performance of the quarterly testing required by this procedure at any other time is impractical in that it would be necessary to render one of the operable pumps inoperable to in order to rack in the spare pump breaker. During refueling outages, all three pumps are full-flow tested in accordance with OST-165, "Safety Injection System High Head Component Test (Cold Shutdown Greater Than 48 Hrs. Unless Tested In Previous 92 Days)." Copies of the OSTs are available at HBRSEP for your review.

Questions regarding this matter may be referred to Mr. K. R. Jury at (803) 383-1363.

Very truly yours,

090047

Manager - Regulatory Affairs

c: Mr. S. D. Ebneter, Regional Administrator, USNRC, Region II

Ms. B. L. Mozafari, USNRC Project Manager, HBRSEP

Mr. W. T. Orders, USNRC Senior Resident Inspector, HBRSEP

9412080137 941201 PDR ADDCK 05000261

Highway 151 and SC 23 Hartsville SC

4001 1/0