

## Carolina Power & Light Company

May 10, 1977

NG-3514 (R) FILE:

SERIAL: NG-77-565

Office of Nuclear Reactor Regulation Attn: Mr. Robert W. Reid, Chief Operating Reactor Branch No. 4 U. S. Nuclear Regulatory Commission Washington, D. C. 20555

H. B. ROBINSON STEAM ELECTRIC PLANT UN

DOCKET NO. 50-261 FACILITY OPERATING LICENSE NO. DPR-23

REQUEST FOR LICENSE AMENDMENT - REVISION OF TECHNICAL SPECIFICATIONS

Dear Mr. Reid:

In accordance with the Code of Federal Regulations, Title 10, Part 50.90 and Part 2.101, Carolina Power & Light Company (CP&L) hereby requests a revision to the Technical Specifications for its H. B. Robinson Steam Electric Plant, Unit No. 2.

This revision has been prepared to preclude conflicts between the inservice inspection and testing requirements set forth in Section XI of the ASME, Boiler and Pressure Vessel Code, and Addenda and the current Technical Specifications. For H. B. Robinson Steam Electric Plant, Unit No. 2 the effective ASME code is determined to be the 1974 edition of Section XI through Summer 1975 Addenda. The next regular 40-month inspection interval commences November 7, 1977.

Accordingly, it is requested that the entire section 4.2 (pages 4.2-1 through 4.2-24) of the H. B. Robinson Steam Electric Plant, Unit No. 2 Technical Specifications be deleted and replaced with the attached replacement page. Appropriate changes are indicated by a vertical line in the margin.

In consonance with the commencement of the next regular 40-month inspection interval, it is requested that this Technical Specification change be issued with an effective date of November 7, 1977.

Yours very truly,

E. E. Utley Senior Vice President

Power Supply

WH/gsm

Attachment

Sworn to and subscribed before me this  $10 \, \mathrm{th}$  day of May, 1977.

My commission expires July 4, 1980.

336 Fayetteville Street . P. O. Box 1551 . Raleigh, N. C. 27602

# 4.2 Primary System Surveillance

### Applicability

Applies to in-service structural surveillance of the reactor vessel and primary system boundary.

#### Objective

To assure the continued integrity of the primary system boundary.

### Specification

#### 4.2.1

- a. Inservice inspection of ASME Code Class 1, Class 2 and Class 3 components shall be performed in accordance with Section XI of the ASME Boiler and Presure Vessel Code and applicable Addenda as required by 10 CFR 50, Section 50.55a(g), except where specific written relief has been granted by the NRC pursuant to 10 CFR 50, Section 50.55a(g) (6) (i).
- b. Inservice testing of ASME Code Class 1, Class 2 and Class 3 pumps and valves shall be performed in accordance with Section XI of the ASME Boiler and Pressure Vessel Code and applicable Addenda as required by 10 CFR 50, Section 50.55a(g), except where specific written relief has been granted by the NRC pursuant to 10 CFR 50, Section 50.55a(g) (6) (i).