NRC FORM 374 (3-2000) U.S. NUCLEAR I			REGULATORY COMMISSION PAGE 1 OF 6 PAGES			PAGE 1 OF 6 PAGES		
MATERIALS LICENSE								
MATERIALS LICENSE SUPPLEMENTARY SHEET				License Number: SNM-33				
				Docket or Reference Number: 070-00036				
			Amendment No. 65					
Pur 438 34, lice byp the acc spe reg	Pursuant to the Atomic Energy Act of 1954, as amended, the Energy Reorganization Act of 1974 (Public Law 93- 438), and the applicable parts of Title 10, Code of Federal Regulations, Chapter I, Parts 19, 20, 30, 31, 32, 33, 34, 35, 36, 39, 40, 51, 70, and 71, and in reliance on statements and representations heretofore made by the licensee, a licensee is hereby issued authorizing the licensee to receive, acquire, possess, and transfer byproduct, source, and special nuclear material designated below; to use such material for the purpose(s) and at the place(s) designated below; to deliver or transfer such material to persons authorized to receive it in accordance with the regulations of the applicable Part(s). This license shall be deemed to contain the conditions specified in Section 183 of the Atomic Energy Act of 1954, as amended, and is subject to all applicable rules, regulations, and orders of the Nuclear Regulatory Commission now or hereafter in effect and to any conditions							
	Licensee							
1	Westinghouse Electric Company	LLC		3.	License Num	nber	SNM-00033	
2.	3300 State Road P Festus, Missouri 63028	SHUCLEAR	RE	GU 4.	Expiration Da	ate	License is continued until decommissioning is complete and the U.S. Nuclear Regulatory Commission notifies Westinghouse Electric Company LLC in writing that the license is terminated.	
-			Lonnon	5.	Reference N Maximum Ar	umber	at Licensee	
6.	Byproduct, Source, and/or Special Nuclear Material: 7. Ph	nemical and/or nysical Form:		8.	May Posses Under This L	s at Any icense:	One Time	
A.	 Uranium enriched to a maximum of less than 10 weight percent in the U-235 isotope A. Any (including o powders existing Hematite Site or 2001) 				A. 10,000 H	kilogram	s U-235	
В.	Uranium enriched greater than or equal 10 weight percent and less than 20 weight percent in the U-235 isotope	Any (including powders exist Hematite Site 2001)	i only m ing at tl on July	netal he / 1,	B. 9,999 gr	rams U-2	235	
C.	Uranium enriched greater C than or equal to 20 weight percent in the U-235 isotope	. Any (including powders exist Hematite Site 2001)) only m ing at ti on July	netal he / 1,	C. 4,999 gi	rams U-:	235 [*]	

NRC FORM 374 (3-2000) U.S. NUCL			U.S. NUCLEAR	REGULATORY C	OMMISSION	PAGE 2 OF 6 PAGES	
	MATERIALS LICENSE						
	MATERIALS LICENSE SUPPLEMENTARY SHEET			License Number: SNM-33			
				Docket or Reference Number: 070-00036			
				Amendment No. 65			
D.	Uranium (natural or depleted)	C.	Any (including powders exist Hematite Site 2001)	g only metal ing at the on July 1,	C. 2,000 ki	lograms	
E.	Co-60	E.	Sealed source	S	E. 40 millio	uries	
F.	Cs-137	F.	Sealed source	S	F. 500 milli	curies	
G.	Byproduct material, including Am-241	G.	Any		G. 400 micr	rocuries	
н.	Special, Source, and Byproduct Material as residual contamination	H.	Any (residual contamination) REGU/	H. Existing 2001	at the Hematite site On July 1,	
[*] L g	icense conditions for Category rams of U-235) are defined in th	III ⊢ ìe F	IEU (for less th undamental Nu	an 1000 gram Iclear Materia	ns U-235) an Il Control Pla	nd Category II HEU (1000 to 4999 In and the Physical Security Plan.	
9.	 Authorized Use: Items A through H. Uses as described in August 12, 2009 Decommissioning Plan and associated supporting documents noted in Hematite Decommissioning Plan SER (ADAMS Accession No. ML112101630) and July 5, 2011 License Application (ADAMS Accession No. ML111880290). 						
	S CONDITIONS						
10	10. The licensee is hereby granted the following special authorization from Chapter 1, Section 1.6.1 of the Jul 5, 2011, License Application.						
	Release of equipment and materials from restricted areas to controlled areas or offsite in accordance with the NRC's "Guidelines for Decontamination of Facilities and Equipment Prior to Release for Unrestricted Use or Termination of Licenses for Byproduct, Source, or Special Nuclear Material," dated April 1993.						
11	11. The licensee shall follow the revision dated February 18, 2011 of its Fundamental Nuclear Material Control Plan. This Plan may be further revised in accordance with, and pursuant to, the provisions of either 10 CFR Part 70.32(c) or 70.34.						
12	 The licensee shall follow the physical protection plans entitled, Physical Security Plan, dated September 11, 2013, Category I Contingency Safeguards Contingency Response Plan, dated July 28, 2011 and Category I Contingency Security Training and Qualification Plan, dated July 28, 2011. 						
13	13. Licensee is hereby granted permission to demolish or dismantle buildings including building slabs and foundations.						

3-2000	U.S. NUCLEAR	REGULATORY COMMISSION PAGE 3 OF 6 PAGES						
	MATERI							
		License Number: SNM-33						
	MATERIALS LICENSE SUPPLEMENTARY SHEET	Docket or Reference Number: 070-00036						
		Amendment No. 65						
14. Notwithstanding the requirement of 10 CFR 70.24, the licensee shall be exempted from the "monitoring system" requirements in the areas, and under the conditions specified below:								
	A. Low concentration materials (1.4 g U-235/L for solids, and 11.6 g U-235/L for liquids) that are safely subcritical by virtue of their low concentration, irrespective of any other physical conditions, including mass, geometry, moderation, reflection, etc.							
	B. Materials that are contained in authorized packages as defined in NRC/DOT regulations, including 10 CFR 71 and 49 CFR 173.							
	C. Materials within neutronically separate areas containing less than the following isotopic mass amount per separate area:							
	 700 g U-235 in uranium enriched to more than 5 wt.% U-235/U, and 1640 g U-235 in uranium enriched to no more than 5 wt.% U-235/U. 							
Notes: (1) Structure surfaces within the separate area that contain residual U-235 surface contamination below an areal density of 10 g U-235/ft ² are not included in the mass amount for the separate area.								
(2) Any U-235 in undisturbed subsurface areas is not included in the isotopic mass amount for the separate area.								
(3) Neutronically separated areas are to be considered effectively neutronically isolated from all other areas used to store fissile material when either of the following conditions are satisfied:								
	a. A minimum e maintained be	dge-to-edge separation distance of 12 feet is etween each area used to store fissile material; or						
	b. The configura conjunction w concrete bloc neutron trans isolation betw	ation of each area used to store fissile material, in <i>i</i> th any fixed shielding that may be present (e.g., k walls) between the areas, is demonstrated by port calculations to result in effective neutron ween each area.						

D. Residual materials on surfaces of the site buildings or installed equipment in those buildings including removal and transit of those SNM-bearing materials from the buildings. (Any SNM-bearing materials brought into site buildings must satisfy another provision in this Section 1.6.2 to meet the exemption.)

NRC FORM 374 (3-2000)	U.S.	NUCLEAR F	REGULATORY COMMISSION	PAGE 4 OF 6 PAGES				
	MATERIALS LICENSE							
			License Number: SNM-	33				
MATERI SUPPLEM	ALS LICENSE ENTARY SHEET	т	Docket or Reference Nu	mber: 070-00036				
			Amendment No. 65					

- E. A Contingency Hot Spot that is in secure storage, is neutronically isolated from other SNM, and is intrinsically safe due to two of its physical parameters (e.g., mass, volume, enrichment, geometry, moderation) being in a known state that is sufficient to render the item safely subcritical. The term 'Contingency Hot Spot' is defined in the *Nuclear Criticality Safety Contingency Plan for Remediating Contingency Hot Spots*. The term 'secure storage' is defined as an area in which dual controlled entry is required as well as tandem operations with oversight.
- F. NCS Exempt Materials not otherwise exempted by paragraph 14.A above. NCS Exempt Materials are defined as: "Unless otherwise defined and justified within a nuclear criticality safety evaluation, NCS Exempt Material is conservatively defined as material containing ²³⁵U with an average nuclide fissile concentration not exceeding 0.1 g ²³⁵U/L, or material that comprises no greater than 15 g²³⁵U and is enclosed within a container with a volume of at least 5 liters."

G. Non-NCS Exempt Materials in the process of exhumation from a burial area and characterization (e.g., in a Waste Evaluation Area and/or Material Assay Area), that have an unknown or indeterminate fissile material content (e.g., intact drums), provided the following criteria are met:

- 1. In-situ radiological survey equipment does not identify the item as a Contingency Hot Spot, and
- 2. The item is not consistent with the calibration basis of the radiological survey equipment used (e.g., dense shielded items, intact drums), and
- 3. A 12 foot separation distance (effective neutronic isolation) is maintained between the exhumed item and other exhumed items that are not exempt from Nuclear Criticality Safety (NCS) control (distance may be between 3 feet and 12 feet if effective neutronic isolation at the smaller distance is demonstrated by neutron transport calculations), and
- 4. The item is moved from exhumation to a Waste Evaluation Area and/or Material Assay Area without being placed in a storage area in-between, and
- 5. Only one container (or one item if it is too large for a collared drum) not exempt from NCS control is allowed at a time in a Waste Evaluation Area or Material Assay Area with minimum separation of 12 feet from other Non-NCS Exempt material (distance may be between 3 feet and 12 feet if effective neutronic isolation at the smaller distance is demonstrated by neutron transport calculations), and
- 6. Controls for a Contingency Hot Spot per Condition 16 are applied if the additional characterization (e.g., shielding removed) determines that a Contingency Hot Spot is present.

NRC FORM 374 (3-2000)	U.S. NUCLEAR	REGULATORY COMMISSION	PAGE 5 OF 6 PAGES					
	MATERIALS LICENSE							
			License Number: SNM-33					
MATERIALS LICENSE SUPPLEMENTARY SHE	Ē ET	Docket or Reference Nu	mber: 070-00036					
		Amendment No. 65						

- 15. Except as specifically provided otherwise in this license, the licensee shall conduct its program in accordance with the statements, representations, and procedures contained in the documents, including any enclosures, listed below. The U.S. Nuclear Regulatory Commission's regulations shall govern unless the statements, representations, and procedures in the licensee's application and the following correspondence are more restrictive than the regulations.
 - A. Westinghouse HEM-11-96, "Final Supplemental Response to NRC Request for Additional Information on the Hematite Decommissioning Plan and Related Revision to a Pending Licensing Action", July 5, 2011 except for Attachment 18. (ADAMS Accession Nos. ML111880290 and ML111880292)
 - B. Documents identified in Chapter 1 of NRC Decommissioning Plan SER ADAMS Accession No. (ML112101630).
 - C. Westinghouse HEM-11-56, "*Evaluation of Technetium-99 Under the Process Buildings*", May 5, 2011. (ADAMS Accession No. ML111260624).
 - D. Documents identified in the NRC's 10 CFR 20.2002 SERs associated with Amendment Nos. 58, 60, 63, and 65. (ADAMS Accession Nos. ML111441087, ML12158A401, ML13280A368, and ML15086A364)
 - E. Westinghouse HEM-12-101, "Special Nuclear Material License Application for the Hematite Decommissioning Project", August 16, 2012. (ADAMS Accession No. ML12233A362)
- 16. Notwithstanding the requirement of 10 CFR 70.22(a)(4), the licensee shall be exempted from the possession limit requirements of requirements of 6.C, 7.C and 8.C above with respect to the SNM covered by the Settlement Agreement, Consent Order and Final Judgment entered by the United States District Court for the Eastern District of Missouri Eastern Division in Westinghouse Electric Company, LLC v. the United States of America, et al, Case 4:03-cv-00861-CDP (ML112630111) subject to the conditions specified below:

If the licensee discovers any such SNM during decommissioning, the SNM shall be handled in accordance with the approved Physical Security Plan, Fundamental Nuclear Material Control Plan, and Nuclear Criticality Contingency Plan for Remediating Contingency Hot Spots.

17. Pursuant to 10 CFR 20.2002, the licensee may dispose of solid materials [consisting of a total of 126,306 m³ of soils, soil-like material (dewatered sanitary sludge) and associated debris and 28,451 m³ of concrete/asphalt, piping, soil and miscellaneous equipment] provided the total inventory of Tc-99 based on the average concentration and total mass shipped remains below 1.3 Ci or 2.05 Ci based upon the 95th upper confidence limit as waste at the US Ecology Idaho facility in Grand View, ID. Pursuant to 10 CFR 30.11 and 10 CFR 70.17, this material is exempt from the requirements in 10 CFR 30.3 and 10 CFR 70.3. Any waste material which will be chemically treated at the US Ecology Idaho facility in Grand View Idaho

NRC F((3-2000)	ORM 374 U.S. NUCLEAR I		REGULATORY COMMISSION	PAGE 6 OF 6 PAGES				
MATERIALS LICENSE								
			License Number: SNM-	33				
	MATERIALS LICENSE SUPPLEMENTARY SHEE	т	Docket or Reference Number: 070-00036					
			Amendment No. 65					
	will be shipped in a rail car and total U-235 content per rail car will be limited to 700 grams or less. In addition, Westinghouse will ensure that any chemical treatment which occurs at US Ecology Idaho is limited so that no treated batch contains more than the contents of one railcar.							
18.	18. The licensee SHALL evaluate the impact of any change to its methods or procedures for performing surveys or visual inspection of buried or exhumed waste and/or contaminated soil, whether in situ or ex situ, on its ability to comply with the applicable criticality safety mass and concentration limits and associated controls established in a nuclear criticality safety assessment/evaluation or in Condition 14. If, based upon this evaluation, the licensee determines that the change has the potential to increase or decrease the effectiveness or efficiency of the licensee's methods for complying with these limits, then the licensee SHALL provide the NRC a copy of the procedure and the evaluation within 48 hours after its approval.							
FOR			SION					
	FOR THE U.S. NUCLEAR REGULATORY COMMISSION GULA							
Date	e: April 29, 2015	Andre Divisi and Office and	/RA/ ew Persinko, Deputy Dire- ion of Decommissioning, I Waste Programs e of Nuclear Material Safe Safeguards	ctor Uranium Recovery, ety				