

RULES AND DIRECTIVES
BRANCH
E-REG

As of: 4/28/15 11:24 AM
Received: April 20, 2015
Status: Pending_Post
Tracking No. 1jz-8ien-meql
Comments Due: April 20, 2015
Submission Type: Web

PUBLIC SUBMISSION

2015 APR 28 AM 11: 34

Docket: NRC-2015-0047

Considerations in Licensing High Burnup Spent Fuel in Dry Storage and Transportation

Comment On: NRC-2015-0047-0001

Considerations in Licensing High Burnup Spent Fuel in Dry Storage and Transportation

Document: NRC-2015-0047-DRAFT-0004

Comment on FR Doc # 2015-05097

RECEIVED

3/5/2015

Submitter Information

80FR12041

Name: Donna Gilmore
Address: United States,
Email: dgilmore@cox.net

3

General Comment

Please consider modifying your guidelines based on the following comments and questions.

1. The determination to use a lead cask for high burnup fuel is not adequately addressed. Given the unpredictable nature and unknowns about high burnup fuel, which you have admitted is quite different than lower burnup fuel, how can just a lead cask be adequate? Also, the demonstration project is using a thick cask rather than a thin canister/thick concrete overpack. Different fuel assemblies, drying temperatures, containers and other variables do not appear to be accounted for with a demonstration cask or a lead cask.
2. What is your rationale for knowing which cask contains fuel that might be the most embrittled or otherwise damaged?
3. And by lead canister, do you mean a lead cask at each facility or just the demonstration project cask?
4. Since its impossible to know when a canister will crack and there is no current technology that can adequately inspect for cracks or repair cracks in canisters, it appears a more conservative approach should be taken and require canning of all high burnup fuel in damaged/failed fuel cans. I understand these cans are not sealed and have vent holes at both ends, so do not provide a true defense in depth radiation barrier. However, at minimum it provides fuel assembly retrievability and reduces other fuel storage risks.
5. What does the term examination mean and how could that possibly be done in other than the demonstration project? The demonstration project doesnt represent all the variations that currently exist in canisters and fuel assemblies and cladding.

SUNSE Review Complete
Template = ADM-013

E-REGS = ADM-03

Call = H. Akhavanik (hx2)

6. In the flowchart, a number of decision points and action boxes assume fuel can be examined. This would require unwelding the canister lids under water or in a hot cell. Since this is not practical or possible, it doesn't appear to be a feasible action.

7. Since the NRC is now approving burnup up to 68 GWd/MTU when it even has serious unknowns for fuel in the 40+ GWd/MTU range, it seems an even more conservative approach should be taken on storage and transportation guidelines. Or was that level of burnup address in the technical data available that you used to substantiate your high burnup guidelines? Please provide references.

8. Were these guidelines informed by any seismic data or analysis that might negatively impact cladding embrittlement (e.g., cause it to shatter under high seismic events). Given the new information from the USGS (in their Fukushima Lessons Learned) that one earthquake fault can jump nine feet to another fault, it would seem this should be considered, especially in high seismic areas such as San Onofre in San Diego county and Diablo Canyon in San Luis Obispo, California.

9. Please clarify specifically what the defense in depth is if high burnup fuel becomes damaged after dry storage. Particularly given the information in the following report.

the trend of the data generated in the current work clearly indicates that failure criteria for high-burnup cladding need to include the embrittling effects of radial-hydrides for drying-storage conditions that are likely to result in significant radial-hydride precipitation...A strong correlation was found between the extent of radial hydride formation across the cladding wall and the extent of wall cracking during RCT [ring-compression test] loading.

Ductile-to-Brittle Transition Temperature for High-Burnup Zircaloy-4 and ZIRLO Cladding Alloys Exposed to Simulated Drying-Storage Conditions M.C. Billone, et.al. September 28, 2012.
<http://pbadupws.nrc.gov/docs/ML1218/ML12181A238.pdf>

10. Would any of the information in this report regarding the explosive characteristics of hydrides cause you to consider reevaluating your guidelines?

Explosive Characteristics of Titanium, Zirconium, Thorium, Uranium and their Hydrides, Irving Hartmann, John Nagy, Murray Jacobsom, U.S. Dept of the Interior, Bureau of Mines, December 1951
<https://sanonofresafety.files.wordpress.com/2014/12/4410914explosivezirconiumdivofmines.pdf>

Zirconium Hydride Material Safety Data Sheet
<http://www.espimetals.com/index.php/msds/780-zirconium-hydride>

Additional references at <http://sanonofresafety.org/nuclear-waste/>

A copy of the above is attached in HighBurnupComments2015-04-20.pdf

Attachments

HighBurnupComments2015-04-20

To: Nuclear Regulatory Commission

April 20, 2015

Re: Considerations in Licensing High Burnup Spent Fuel in Dry Storage and Transportation
Docket ID NRC-2015-0047

Please consider modifying your guidelines based on the following comments and questions.

1. The determination to use a lead cask for high burnup fuel is not adequately addressed. Given the unpredictable nature and unknowns about high burnup fuel, which you have admitted is quite different than lower burnup fuel, how can just a lead cask be adequate? Also, the demonstration project is using a thick cask rather than a thin canister/thick concrete overpack. Different fuel assemblies, drying temperatures, containers and other variables do not appear to be accounted for with a demonstration cask or a lead cask.
2. What is your rationale for knowing which cask contains fuel that might be the most embrittled or otherwise damaged?
3. And by lead canister, do you mean a lead cask at each facility or just the demonstration project cask?
4. Since it's impossible to know when a canister will crack and there is no current technology that can adequately inspect for cracks or repair cracks in canisters, it appears a more conservative approach should be taken and require canning of all high burnup fuel in damaged/failed fuel cans. I understand these cans are not sealed and have vent holes at both ends, so do not provide a true defense in depth radiation barrier. However, at minimum it provides fuel assembly retrievability and reduces other fuel storage risks.
5. What does the term "examination mean" and how could that possibly be done in other than the demonstration project? The demonstration project doesn't represent all the variations that currently exist in canisters and fuel assemblies and cladding.
6. In the flowchart, a number of decision points and action boxes assume fuel can be examined. This would require unwelding the canister lids under water or in a hot cell. Since this is not practical or possible, it doesn't appear to be a feasible action.
7. Since the NRC is now approving burnup up to 68 GWd/MTU when it even has serious unknowns for fuel in the 40+ GWd/MTU range, it seems an even more conservative approach should be taken on storage and transportation guidelines. Or was that level of burnup address in the technical data available that you used to substantiate your high burnup guidelines? Please provide references.
8. Were these guidelines informed by any seismic data or analysis that might negatively impact cladding embrittlement (e.g., cause it to shatter under high seismic events). Given the new information from the USGS (in their Fukushima Lessons Learned) that one earthquake fault can jump nine feet to another fault, it would seem this should be

considered, especially in high seismic areas such as San Onofre in San Diego county and Diablo Canyon in San Luis Obispo, California.

9. Please clarify specifically what the defense in depth is if high burnup fuel becomes damaged after dry storage. Particularly given the information in the following report.

“...the trend of the data generated in the current work clearly indicates that failure criteria for high-burnup cladding need to include the embrittling effects of radial-hydrides for drying-storage conditions that are likely to result in significant radial-hydride precipitation...A strong correlation was found between the extent of radial hydride formation across the cladding wall and the extent of wall cracking during RCT [ring-compression test] loading.”

Ductile-to-Brittle Transition Temperature for High-Burnup Zircaloy-4 and ZIRLO™ Cladding Alloys Exposed to Simulated Drying-Storage Conditions M.C. Billone, et.al. September 28, 2012.

<http://pbadupws.nrc.gov/docs/ML1218/ML12181A238.pdf>

10. Would any of the information in this report regarding the explosive characteristics of hydrides cause you to consider reevaluating your guidelines?

Explosive Characteristics of Titanium, Zirconium, Thorium, Uranium and their Hydrides, Irving Hartmann, John Nagy, Murray Jacobsom, U.S. Dept of the Interior, Bureau of Mines, December 1951

<https://sanonofresafety.files.wordpress.com/2014/12/4410914explosivezirconiumdivofmines.pdf>

Zirconium Hydride Material Safety Data Sheet

<http://www.espimetals.com/index.php/msds/780-zirconium-hydride>

Additional references at <http://sanonofresafety.org/nuclear-waste/>

Thank you,

Donna Gilmore
SanOnofreSafety.org