June 3, 2015

MEMORANDUM TO:	Anthony H. Hsia, Deputy Director Division of Spent Fuel Management, NMSS
FROM:	Pierre Saverot, Project Manager <b>/RA/</b> Spent Fuel Licensing Branch Division of Spent Fuel Management, NMSS
SUBJECT:	SUMMARY OF MAY 20, 2015, MEETING WITH HOLTEC INTERNATIONAL

### Background

Holtec International (Holtec) is preparing an application for the Model No. HI-STAR 80 package. The meeting was noticed on March 4, 2015. The meeting attendance list and the presentation are provided as Enclosure Nos. 1 and 2, respectively.

#### Discussion

The Model No. HI-STAR 80 package is capable of transporting either (i) 12 PWR or 32 BWR fuel assemblies in a bare basket with a maximum heat load of 50 kW, or (ii) up to 5 metric tons of solid waste, e.g., fuel channels, core grids, control rods, burnable absorbers, in a non-fuel waste basket, or (iii) core component cassettes in a secondary packaging basket with a maximum heat load of 2 kW.

The closure system includes a double independently bolted closure lid as is the case for the Model Nos. HI-STAR 180 and 180D packages, and the closure lid seal joint remains leak-tight under both normal conditions of transport and hypothetical accident conditions.

Although most of the analyses will be "carried over" from the licensing approach for the Model Nos. HI-STAR 180 and 180 D, staff reminded Holtec that the application shall be "self-sufficient," complete, and include all the necessary information for a safety determination. The applicant confirmed that the 70,000 MWD/MTU burnup is an assembly average (thus, the peak burnup is higher) and that there is no change in the assembly pitch for the criticality analysis in line with what was done for the evaluation of the Model No. HI-STAR 180 package.

Regarding a potential deviation from a "typical" definition of package contents, staff stated that the 10 CFR 72.48 process by which licensees and certificate holders may make changes to their facilities, storage cask designs, and procedures without prior NRC approval does not exist in 10 CFR Part 71, and that entertaining this option for the Model No. HI-STAR 80 package may be very challenging.

The safety analysis considers all fresh fuel (both baskets), no burnup credit, and no more than 90% of the minimum  $B_4C$  content in Metamic-HT is credited. The applicant is only using CASMO-5 for sensitivity evaluations. This approach for moderator exclusion under accident

### A. Hsia

conditions, based on the double closure lid system, with a criticality analysis of hypothetical fuel reconfigurations has already been approved by staff. Staff asked if strain rate dependent foam properties had been considered in the structural crush evaluation, and also expressed concerns on the thermal analyses, as presented, with not enough margin for the maximum peak cladding temperatures.

Regarding non-fuel waste contents, staff asked the applicant to (i) quantify the source terms associated with those wastes, and (ii) justify the releasable contents. Staff recognized that no numerical analysis is required for the thermal evaluation due to the very low heat load (approximately 2 kW) but requested that the applicant selects one of the six provisions of 10 CFR 71.15 to demonstrate fissile exemption.

Staff made no regulatory commitments during the meeting.

Docket No. 71-9374 TAC No. L24996

Enclosure 1: Meeting Attendees Enclosure 2: Presentation A. Hsia

conditions, based on the double closure lid system, with a criticality analysis of hypothetical fuel reconfigurations has already been approved by staff. Staff asked if strain rate dependent foam properties had been considered in the structural crush evaluation, and also expressed concerns on the thermal analyses, as presented, with not enough margin for the maximum peak cladding temperatures.

Regarding non-fuel waste contents, staff asked the applicant to (i) quantify the source terms associated with those wastes, and (ii) justify the releasable contents. Staff recognized that no numerical analysis is required for the thermal evaluation due to the very low heat load (approximately 2 kW) but requested that the applicant selects one of the six provisions of 10 CFR 71.15 to demonstrate fissile exemption.

Staff made no regulatory commitments during the meeting.

Docket No. 71-9374 TAC No. L24996

Enclosure 1: Meeting Attendees Enclosure 2: Presentation

Distribution: Attendees, M. Lombard

G:\SFFT\Saverot\HI STAR 80\meeting summary May 20 2015.doc G:\SFST\Saverot\HI-STAR 80\HI-STAR 80 NRC Presentation

#### ADAMS Package No.: ML15155A546 Memo: ML15155A568 Presentation: ML15155A582

NAME PSaverot MDeBose MSampson   DATE 05/26/2015 05/28/2015 6/3/2015	<u>Distribution</u> : NRC	SFM	Е	SFM	С	SFM		
DATE 05/26/2015 05/28/2015 6/3/2015	NAME	PSave	rot	MDeBose		MSampsor	ı	
	DATE	05/26/2015		05/28/2015		6/3/2015		

C=Without attachment/enclosure

E=With attachment/enclosure

N=No copy

OFFICIAL RECORD COPY

# Meeting Between HOLTEC and the Nuclear Regulatory Commission May 20, 2015 Meeting Attendees

# NRC/NMSS/SFM

301-415-7505	pierre.saverot@nrc.gov
301-415-6878	david.tang@nrc.gov
301-415-	Antonio.rigato@nrc.gov
301-415-6941	andrew.barto@nrc.gov
301-415-7511	steven.everard@nrc.gov
301-415-6802	<u>meraj.rahimi@nrc.gov</u>
301-415-6950	joann.ireland@nrc.gov
301-415-7493	michele.sampson@nrc.gov
	301-415-7505 301-415-6878 301-415- 301-415-6941 301-415-7511 301-415-6802 301-415-6950 301-415-7493

## HOLTEC

Steve Horvath	856-298-6584	s.horvath@holtec.com
Stefan Anton	856-296-9219	s.anton@holtec.com
Luis Hinojosa	856-797-0900	I.hinojosa@holtec.com
Kevin Ecker	856-797-0900	k.ecker@holtec.com
Chuck Bullard	856-797-0900	<u>c.bullard@holtec.com</u>
Debu Majumdar	856-797-0900	d.majumdar@holtec.com

## SKB

Johan Rosenblad	46703200564	johan.rosenblad@skb.se
Henrik Algotsson	46701043154	henrik.algotsson.konsult@skb.se
Ulrika Broman	46703200497	ulrika.broman@skb.se
Markus Wilkman	46703690096	markus.wilkman@skb.se