NRC FORM 374		PAGE <u>1</u> OF <u>4</u> PAGES Amendment No. 05		
U.S. N		Amenument No. 05		
Pursuant to the Atomic Energy Act of 1954, as amer Federal Regulations, Chapter I, Parts 30, 31, 32, 33 made by the licensee, a license is hereby issued au special nuclear material designated below; to use su such material to persons authorized to receive it in a contain the conditions specified in Section 183 of regulations, and orders of the Nuclear Regulatory 0	, 34, 35, 36, 39, 40, and 70, and in relia thorizing the licensee to receive, acquir ich material for the purpose(s) and at t iccordance with the regulations of the the Atomic Energy Act of 1954, as	nce on statements and representations heretofore ire, possess, and transfer byproduct, source, and he place(s) designated below; to deliver or transfer applicable Part(s). This license shall be deemed to amended, and is subject to all applicable rules,		
Licensee	In accordar	ice with the letter dated		
	June 5, 20 <sup>2</sup>	June 5, 2015,		
1. Stantec Consulting Services, Inc.		mber 47-35105-01 is amended in o read as follows:		
2. 111 Elkins Street	4. Expiration	4. Expiration date February 28, 2023		
Fairmont, West Virginia 26554	5. Docket No.	030-38686		
S	Reference	Nos. 030-38602 and 030-35088		
6. Byproduct, source, and/or special 7. nuclear material	Chemical and/or physical form	<ol> <li>Maximum amount that licensee may possess at any one time under this license</li> </ol>		
A. Cesium 137	Sealed Sources (QSA Global Model CDCW556; Isotope Products Laboratories Model HEG-137)	A. 135 millicuries total and no single source to exceed the maximum activity specified in the certificate of registration issued by the U.S. Nuclear regulatory Commission or an Agreement State		
B. Americium 241	Sealed Sources (QSA Global Model AMNV.997; Isotope Products Laboratories Models Am1.N02, 3021, 3027)	B. 660 millicuries total and no single source to exceed the		
9. Authorized use:				
		411 portable gauging devices for		

NRC	FORM	3744	PAGE 2 OF 4 PAGES
			License Number 47-35105-01
		MATERIALS LICENSE	Docket or Reference Number
		SUPPLEMENTARY SHEET	030-38686 030-38602 and 030-35088
			Amendment No. 05
		CONDITIONS	
10.	Licensed material may be used or stored at the licensee's facilities located at 1574 Saltwell Road, Shinnston, West Virginia, and may be used at temporary job sites of the licensee anywhere in the Unite States where the U.S. Nuclear Regulatory Commission maintains jurisdiction for regulating the use of licensed material, including areas of exclusive Federal jurisdiction within Agreement States.		
	con site in A	e jurisdiction status of a Federal facility within an Ag tact the Federal agency controlling the job site in que is an area of exclusive Federal jurisdiction. Authoriz greement States not under exclusive Federal jurisdic ulatory agency.	estion to determine whether the proposed job zation for use of radioactive materials at job sites
11.	Licensed material shall be used by, or under the supervision of, individuals who have received the training described in application dated January 4, 2013, and have been designated, in writing, by the Radiation Safety Officer. The licensee shall maintain records of individuals designated as users for 3 years following the last use of licensed material by the individual.		
12.	The	Radiation Safety Officer for this license is Donavon	Cunningham.
13.		led sources or source rods containing licensed mate	
14.	A. Sealed sources shall be tested for leakage and/or contamination at intervals specified in the certificate of registration issued by the U.S. Nuclear Regulatory Commission under 10 CFR 32.210 or under equivalent regulations of an Agreement State.		
	В.	In the absence of a certificate from a transferor inc intervals specified in the certificate of registration is Commission under 10 CFR 32.210 or under equiva- the transfer, a sealed source received from another and the test results received.	ssued by the U.S. Nuclear Regulatory alent regulations of an Agreement State, prior to
	C.	Sealed sources need not be tested if they are in st they are removed from storage for use or transferr within the required leak test interval, they shall be shall be stored for a period of more than 10 years contamination.	ed to another person and have not been tested tested before use or transfer. No sealed source

<ul> <li>U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and under the license. Records of inventories shall be maintained for 5 years from the date of ea inventory and shall include the radionuclides, quantities, manufacturer's name and model nur the date of the inventory.</li> <li>16. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gaug container must be locked when in transport or storage, or when not under the direct surveillar authorized user.</li> </ul>	4 PAGES	
SUPPLEMENTARY SHEET         030-38686           030-38602 and 030-35088         Amendment No. 05           D. The leak test shall be capable of detecting the presence of 0.005 microcurie (185 becquerels) or more of removable contamination, a report shall be filed with the U Regulatory Commission in accordance with 10 CFR 30.50(c)(2), and the source shall be immediately from service and decontaminated, repaired, or disposed of in accordance with the U.S. Nuclear Regulatory Commission regulations.           E. Tests for leakage and/or contamination, limited to leak test sample collection, shall be p by the licensee or by other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. The licensee is not auth perform the analysis; analysis of leak test samples must be performed by persons specificensed by U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. The licensee is not auth perform the analysis; analysis of leak test samples must be performed by persons specificensed by U.S. Nuclear Regulatory Commission or an Agreement State to perform such services.           F. Records of leak test results shall be kept in units of microcuries and shall be maintained 5 years.           5. The licensee shall conduct a physical inventory every six months, or at other intervals approv U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and under the license. Records of inventories shall be maintained for 5 years from the date of ea inventory.           6. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gaug container must be locked when in transport or storage, or when not un		
D30-38602 and 030-35088     Amendment No. 05     D. The leak test shall be capable of detecting the presence of 0.005 microcurie (185 becquerels) or more of removable contamination, a report shall be filed with the U     Regulatory Commission in accordance with 10 CFR 30.50(c)(2), and the source shall b     immediately from service and decontaminated, repaired, or disposed of in accordance v     Commission regulations.     E. Tests for leakage and/or contamination, limited to leak test sample collection, shall be p     by the licensee or by other persons specifically licensed by the U.S. Nuclear Regulatory     Commission or an Agreement State to perform such services. The licensee is not auth     perform the analysis, analysis of leak test samples must be performed by persons specifically units of microcuries and shall be maintained     5 years.     The licensee shall conduct a physical inventory every six months, or at other intervals approv     U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and     under the license. Records of inventories shall be maintained for 5 years from the date of ea     inventory and shall include the radionuclides, quantities, manufacturer's name and model nur     the date of the inventory.     Each portable nuclear gauge shall have a lock or outer locked container designed to prevent     unauthorized or accidental removal of the sealed source from its shielded position. The gaug     container must be locked when in transport or storage, or when not under the direct surveilla     authorized user.		
<ul> <li>Amendment No. 05</li> <li>D. The leak test shall be capable of detecting the presence of 0.005 microcurie (185 becqueration of the test sample. If the test reveals the presence of 0.005 microc (185 becquerels) or more of removable contamination, a report shall be filed with the U Regulatory Commission in accordance with 10 CFR 30.50(c)(2), and the source shall be immediately from service and decontaminated, repaired, or disposed of in accordance with 10 CFR 30.50(c)(2), and the source shall be interdiately from service and decontaminated, repaired, or disposed of in accordance with 10 CFR 30.50(c)(2), and the source shall be interdiately from service and decontaminated, repaired, or disposed of in accordance with 10 commission regulations.</li> <li>E. Tests for leakage and/or contamination, limited to leak test sample collection, shall be p by the licensee or by other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. The licensee is not auth perform the analysis; analysis of leak test samples must be performed by persons specifically by U.S. Nuclear Regulatory Commission or an Agreement State to perform such services and shall be maintained 5 years.</li> <li>5. The licensee shall conduct a physical inventory every six months, or at other intervals approv U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and under the license. Records of inventories shall be maintained for 5 years from the date of ea inventory and shall include the radionuclides, quantities, manufacturer's name and model nur the date of the inventory.</li> <li>6. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gaug container must be locked when in transport or storage, or when not under the direct surveillar authorized user.</li> </ul>		
<ul> <li>D. The leak test shall be capable of detecting the presence of 0.005 microcurie (185 becquerels) or more of removable contamination, a report shall be filed with the U Regulatory Commission in accordance with 10 CFR 30.50(c)(2), and the source shall b immediately from service and decontaminated, repaired, or disposed of in accordance of Commission regulations.</li> <li>E. Tests for leakage and/or contamination, limited to leak test sample collection, shall be p by the licensee or by other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. The licensee is not auth perform the analysis; analysis of leak test samples must be performed by persons specificance of y U.S. Nuclear Regulatory Commission or an Agreement State to perform such services and shall be maintained by U.S. Nuclear Regulatory Commission or an Agreement State to perform such services and shall be maintained by U.S. Nuclear Regulatory Commission or an Agreement State to perform such services and shall be maintained by U.S. Nuclear Regulatory Commission or an Agreement State to perform such services and shall be maintained by U.S. Nuclear Regulatory Commission or an Agreement State to perform such services and shall be maintained by ears.</li> <li>5. The licensee shall conduct a physical inventory every six months, or at other intervals approv U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and under the license. Records of inventories shall be maintained for 5 years from the date of ea inventory and shall include the radionuclides, quantities, manufacturer's name and model nur the date of the inventory.</li> <li>6. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gaug container must be locked when in transport or storage, or when not under the direct surveilla authorized user.</li> </ul>		
<ul> <li>radioactive material on the test sample. If the test reveals the presence of 0.005 microi (185 becquerels) or more of removable contamination, a report shall be filed with the U Regulatory Commission in accordance with 10 CFR 30.50(c)(2), and the source shall b immediately from service and decontaminated, repaired, or disposed of in accordance or Commission regulations.</li> <li>E. Tests for leakage and/or contamination, limited to leak test sample collection, shall be p by the licensee or by other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. The licensee is not auth perform the analysis; analysis of leak test samples must be performed by persons specificensed by U.S. Nuclear Regulatory Commission or an Agreement State to perform such services and shall be maintained 5 years.</li> <li>5. The licensee shall conduct a physical inventory every six months, or at other intervals approv U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and under the license. Records of inventories shall be maintained for 5 years from the date of ea inventory.</li> <li>6. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gaug container must be locked when in transport or storage, or when not under the direct surveilla authorized user.</li> </ul>		
<ul> <li>by the licensee or by other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. The licensee is not auth perform the analysis; analysis of leak test samples must be performed by persons specilicensed by U.S. Nuclear Regulatory Commission or an Agreement State to perform such services. The licensee is not auth perform the analysis; analysis of leak test samples must be performed by persons specilicensed by U.S. Nuclear Regulatory Commission or an Agreement State to perform such systems.</li> <li>F. Records of leak test results shall be kept in units of microcuries and shall be maintained 5 years.</li> <li>The licensee shall conduct a physical inventory every six months, or at other intervals approved U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and under the license. Records of inventories shall be maintained for 5 years from the date of ea inventory and shall include the radionuclides, quantities, manufacturer's name and model nur the date of the inventory.</li> <li>Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gaug container must be locked when in transport or storage, or when not under the direct surveillar authorized user.</li> </ul>	curie .S. Nuclear e removed	
<ul> <li>5 years.</li> <li>15. The licensee shall conduct a physical inventory every six months, or at other intervals approved U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and under the license. Records of inventories shall be maintained for 5 years from the date of ear inventory and shall include the radionuclides, quantities, manufacturer's name and model nur the date of the inventory.</li> <li>16. Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gauge container must be locked when in transport or storage, or when not under the direct surveillar authorized user.</li> </ul>	/ orized to ifically	
<ul> <li>U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and under the license. Records of inventories shall be maintained for 5 years from the date of ea inventory and shall include the radionuclides, quantities, manufacturer's name and model nur the date of the inventory.</li> <li>Each portable nuclear gauge shall have a lock or outer locked container designed to prevent unauthorized or accidental removal of the sealed source from its shielded position. The gaug container must be locked when in transport or storage, or when not under the direct surveillar authorized user.</li> </ul>	l for	
unauthorized or accidental removal of the sealed source from its shielded position. The gaug container must be locked when in transport or storage, or when not under the direct surveillar authorized user.	The licensee shall conduct a physical inventory every six months, or at other intervals approved by the U.S. Nuclear Regulatory Commission, to account for all sources and/or devices received and possessed under the license. Records of inventories shall be maintained for 5 years from the date of each inventory and shall include the radionuclides, quantities, manufacturer's name and model numbers, and the date of the inventory.	
	e or its	
Any cleaning, maintenance, or repair of the gauges that requires detaching the source or source rod from the gauge shall be performed only by the manufacturer or by other persons specifically licensed by the U.S. Nuclear Regulatory Commission or an Agreement State to perform such services.		
<ol> <li>The licensee is authorized to transport licensed material in accordance with the provisions of 10 CFR Part 71, "Packaging and Transportation of Radioactive Material."</li> </ol>		

NRC FORM 374A	PAGE 4 OF 4 PAGE			
	License Number 47-35105-01			
MATERIALS LICENSE SUPPLEMENTARY SHEET	Docket or Reference Number 030-38686			
	030-38602 and 030-35088			
	Amendment No. 05			

- 19. Except as specifically provided otherwise in this license, the licensee shall conduct its program in accordance with the statements, representations, and procedures contained in the documents, including any enclosures, listed below. The U.S. Nuclear Regulatory Commission's regulations shall govern unless the statements, representations, and procedures in the licensee's application and correspondence are more restrictive than the regulations.
  - A. Application dated January 4, 2013 (ML13014A379)

ഗ

For the U.S. Nuclear Regulatory Commission

Date August 3, 2015

## Original signed by Sattar Lodhi

By

Sattar Lodhi Commercial, Industrial, R&D and Academic Branch Division of Nuclear Materials Safety Region I King of Prussia, Pennsylvania 19406