(STRIBUTION FOR PART 50 DOCK MATERIAL (TEMPORARY FORM)

dis-		•			•	•	CON	TROL NO	D: <u>4441</u>	
		· · · · · · · · · · · · · · · · · · ·		•			FILE	•		
					• .					
	Duke Power (DATE OF DOC	DAT	E REC'D	LTR	TWX	RPT	OTHER	
Charlot A.C. T		3201	4-16-75	4-2	3 - 75	XX				
TO:	<u> </u>		ORIG	CC	OTHER		NT AE	C PDR_	XX	
Mr. R.	A. Purple			37		SE	NT LO	CALPDF	XX XX	
CLASS	UNCLASS	PROP INFO	INPUT	NOC	YS REC'D	D(OCKET	NO:		
	XXX				37	<u> </u>		50- 269	X270/287	
DESCRI		re our 4-3-75	ltrfurn		OSURES:	Surve	illance		Required	
info re	refueling pe	eriod for Ocone	e Tech Specs &	•	During Rea	fuelin	g Outa	ge	nequired	
rans the	following:	Notarized 4-16	· - 75••••		(27					
			•	i '	(37 cys/er	icı re	c'a)			
					r			Do a	Vot Remove	
								Mercy	OWLEDGER	
DI ANT		onee 1-2-3						别句的的	ONTEROPE.	
PLANT	NAME: OCC	Mee 1-2-5								
:			FOR ACTION/	INFOR	MATION		DHL	4-25-75		
BUTLEF		SCHWENCER		•	REGAN					
W/ Co		W/ Copies	W/ Copies		W/ Co					
CLARK W/ Co		STOLZ (L) W/ Copies	DICKER (E. W/ Copies		LEAR (W/ Co					
PARRA		VASSALLO (I			SPEIS	•				
W/ Co		_W/ Copies	W/ Copies		W/ Co		•	•		
KNIEL (W/ Co		PURPLÉ (L) W Copies	YOUNGBLO W/ Copies) LPM W/ Co	voios		-		
	pies	vvecopies	INTERNAL D			phies	نفسفون سيدي ويرو			
REG FIL	H3D)	TECH REVIE		ISTALE	LIC ASS	ST.	· · · · · · · · · · · · · · · · · · ·	A/T IN	ID	
NRC PD	R (3)	SCHROEDER	GRIMES		R. DIGGS			BRAIT		
OGC, ROOM P-506A		MACCARY	GAMMILL	H. GEARIN (L)				SALTZ	ZMAN	
GOSSIC	K/STAFF	KNIGHT	KASTNER		E. GOULB	OURNI	E (L)	MELT	Z	
CASE GIAMBU	ISSO	PAWLICKI SHAO	BALLARD		P. KREUT		()	PLANS	, ". P	
BOYD	7330	STELLO	SPANGLER	LER J. LEE (L) M. MAIGRET (L)				MCDO		
MOORE		HOUSTON				S. REED (E)			C HAPMAN	
DEYOU		NOVAK	MULLER	M. SERVICE				DUBE		
SKOVHO		ROSS IPPOLITO	DICKER		S. SHEPPA)	E. COL		
			KNIGHTON	1111 0 411 1411				PETER		
	DEVICE				H. SMITH S. TEETS	MITH (L)			HARTFIELD (2) KLECKER	
	REGIOPR LAINAS					AMS (E) EISENH				
	REGION (2)	BENAROYA	M.AU		V. WILSON		-		INTON	
STEELE		VOLLMER	HARLESS	•	R. INGRA	M (L)			Ø	
OTELEE			EVTERNALD	1077 D 10	LITION			app		
4 40	041.000	7.71.77	EXTERNAL D	ISTRIB	·	•		(2))	
- - T !€	: (ABERNAT		– NATIONAL LA					SAN/LA		
	IC (BÜCHAN.	· · · · · · · · · · · · · · · · · · ·	 W. PENNINGTO 		E-201 GT				EN NAT LAB	
1 – AS 1 – Ne	us Anderso	n 1	 CONSULTANT NEWMARK/BL 		CRARIAN	_		ERIKSON PED (RUT	N, OMNE TH GUSSMAÑ	
			ASST. SHEPPARD	4-25-	75		Rm	B-127 GT		
-				-/	. /	1	J. D.	RUNKL	ES, Rm E-201	

- GT

DUKE POWER COMPANY

Regulatory Docket File

Power Building

422 SOUTH CHURCH STREET, CHARLOTTE, N. C. 28201

A. C. THIES
SENIOR VICE PRESIDENT
PRODUCTION AND TRANSMISSION

April 16, 1975

Mr. R. A. Purple, Chief
Operating Reactors Branch 1
Division of Reactor Licensing
U. S. Nuclear Regulatory Commission
Washington, D. C. 20555

Re: Oconee Nuclear Station
Docket Nos. 0-269 -270, -287

Dear Mr. Purple:

Your letter of April 3, 1975 requested additional information necessary to complete your review of my March 12, 1975 request to delete the definition of refueling period (Section 1.2.8) for Oconee Nuclear Station Technical Specifications. Attached is the listing of all Oconee Nuclear Station surveillance requirements which are specified for performance prior to, during, or after a refueling shutdown with an explanation of why they can only be/or should be performed at this time.

The one-hour discharge test of the 125 volt DC batteries required by Technical Specification 4.6.6.c, currently required during a refueling outage, does not require a refueling outage for its completion. A change to Oconee Nuclear Station Technical Specifications is hereby requested which will make this an annual surveillance item.

Very truly yours,

s/A. C. Thies A. C. Thies

ACT: vr

Attachment

P. O. Box 2178

Mr. R. A. Purple Page 2 April 16, 1975

A. C. THIES, being duly sworn, states that he is Senior Vice President of Duke Power Company; that he is authorized on the part of said Company to sign and file with the Atomic Energy Commission this request for amendment of the Oconee Nuclear Station Technical Specifications, Appendix A to Facility Operating Licenses DPR-38, DPR-47, and DPR-55; and that all statements and matters set forth therein are true and correct to the best of his knowledge.

s/A. C. Thies

A. C. Thies, Senior Vice President

ATTEST

s/John C. Goodman, Jr.
John C. Goodman, Jr.
Assistant Secretary

Subscribed and sworn to before me this 16th day of April, 1975

s/Edna B. Farmer Notary Public

My Commission Expires:

October 24, 1977

Regulatory lituret File

SURVEILLANCE ITEMS REQUIRED DURING REFUELING OUTAGE

Technical Specification 4.1.2

1. Functional Tests and Refueling System Interlocks

2. Functional Test of Spent Fuel Cooling System

Assert 1/4 16:75

RESPONSE

These two items are scheduled prior to refueling. The intention is to test these systems immediately prior to their use.

Technical Specification 4.6.3

During each refueling outage for the affected unit, a simulated emergency transfer from the 4160 volt main feeder buses to the startup transformer (i.e., CT1, CT2, or CT3) to the 4160 volt standby buses shall be made to verify proper operation.

RESPONSE

The performance of this test requires a complete unit blackout for approximately four hours. Therefore, in order to ensure adequate decay heat removal, the test must be performed at the end of a refueling interval when decay heat generation is a minimum. During the test, the reactor vessel head is removed and the fuel transfer canal is filled to provide heat transfer. It is concluded that this test is not feasible at times other than a refueling outage.

Technical Specification 4.7.1

The control rod trip insertion time shall be measured for each control rod at either full flow or no flow conditions following each refueling outage prior to return to power.

RESPONSE

This test is performed following refueling to assure the proper installation of control rods after the installation of the reactor vessel head.