

Crew A: SRO-I: Pelletier; RO: Paul; RO: Felske

Facility: Byron			Date of Exam: 3/14/2016			Operating Test No.: Byron 2016301											
A P P L I C A N T	E V E N T  T Y P E	Scenarios												T O T A L	M I N I M U M(*)		
		16-1			16-2			16-4			C R E W P O S I T I O N				R	I	U
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P				
Pelletier	Paul	Felske	Surrogate	Pelletier	Felske	Pelletier	Felske	Paul	SRO	ATC	BOP						
RO <input type="checkbox"/> SRO-I Pelletier <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX	3			4		2						3	1	1	0	
	NOR	1			-		1						2	1	1	1	
	I/C	2,4,5,6			2,5		4,5,6,7						10	4	4	2	
	MAJ	7,8,9			6,7		8,9						7	2	2	1	
	TS	3,4			-		3,4,5						5	0	2	2	
RO Paul <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX		3					-					1	1	1	0	
	NOR		-					1					1	1	1	1	
	I/C		2,5					4,6					4	4	4	2	
	MAJ		8,9					8,9					4	2	2	1	
	TS		-					-					0	0	2	2	
RO Felske <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX			-		-	2						1	1	1	0	
	NOR			1		1	-						2	1	1	1	
	I/C			4,6		3,4	5,7						6	4	4	2	
	MAJ			8,9		6,7	8,9						6	2	2	1	
	TS			-		-	-						0	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX				4									1	1	0	
	NOR				1									1	1	1	
	I/C				2,3,4,5									4	4	2	
	MAJ				6,7									2	2	1	
	TS				2,3,4									0	2	2	

Instructions:

1. Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the “at-the-controls (ATC)” and “balance-of-plant (BOP)” positions; Instant SROs must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an Instant SRO *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
2. Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (\*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
3. Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant’s competence count toward the minimum requirements specified for the applicant’s license level in the right-hand columns.

Crew B: SRO-I: Martinez; RO: Richards

Facility: Byron			Date of Exam: 3/14/2016						Operating Test No.: Byron 2016301								
A P P L I C A N T	E V E N T  T Y P E	Scenarios												T O T A L	M I N I M U M (*)		
		16-1			16-3										R	I	U
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P				
Martinez	Richards	Surr ogate	Surr ogate	Martinez	Richards												
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> Martinez <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX	3			1								2	1	1	0	
	NOR	1			-								1	1	1	1	
	I/C	2,4,5,6			3,5								6	4	4	2	
	MAJ	7,8,9			7,8,9								6	2	2	1	
	TS	3,4			-								2	0	2	2	
RO Richards <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX		3			-							1	1	1	0	
	NOR		-			2							1	1	1	1	
	I/C		2,5			4,6							4	4	4	2	
	MAJ		8,9			7,8,9							5	2	2	1	
	TS		-			-							0	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX			-	1									1	1	0	
	NOR			1	2									1	1	1	
	I/C			4,6	3,4,5,6									4	4	2	
	MAJ			8,9	7,8,9									2	2	1	
	TS			-	3,5									0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX													1	1	0	
	NOR													1	1	1	
	I/C													4	4	2	
	MAJ													2	2	1	
	TS													0	2	2	

Instructions:

1. Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the “at-the-controls (ATC)” and “balance-of-plant (BOP)” positions; Instant SROs must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an Instant SRO *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
2. Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (\*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
3. Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant’s competence count toward the minimum requirements specified for the applicant’s license level in the right-hand columns.

Crew C: SRO-I: Hamblin; SRO-I: Mickelson; RO: Egeland

Facility: Byron		Date of Exam: 3/14/2016									Operating Test No.: Byron 2016301						
A P P L I C A N T	E V E N T  T Y P E	Scenarios												T O T A L	M I N I M U M(*)		
		16-1			16-2			16-3			C R E W P O S I T I O N				R	I	U
		C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N			C R E W P O S I T I O N						
		S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P	S R O	A T C	B O P				
Hamblin	Egeland	Mickelson	Mickelson	Hamblin	Egeland	Hamblin	Mickelson	Egeland									
RO <input type="checkbox"/> SRO-I Hamblin <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX	3			4		1						3	1	1	0	
	NOR	1			-		2						2	1	1	1	
	I/C	2,4,5,6			2,5		3,4,5,6						8	4	4	2	
	MAJ	7,8,9			6,7		7,8,9						8	2	2	1	
	TS	3,4			-		3,5						4	0	2	2	
RO <input type="checkbox"/> SRO-I Mickelson <input checked="" type="checkbox"/> SRO-U <input type="checkbox"/>	RX			- 4			1						2	1	1	0	
	NOR			1 1			-						2	1	1	1	
	I/C			4,6	2,3,4,5		3,5						8	4	4	2	
	MAJ			8,9	6,7		7,8,9						7	2	2	1	
	TS			- 2,3,4			-						3	0	2	2	
RO Egeland <input checked="" type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX		3										2	1	1	0	
	NOR		-			1				2			2	1	1	1	
	I/C		2,5			3,4				4,6			6	4	4	2	
	MAJ		8,9			6,7				7,8,9			7	2	2	1	
	TS		-			-				-			0	0	2	2	
RO <input type="checkbox"/> SRO-I <input type="checkbox"/> SRO-U <input type="checkbox"/>	RX													1	1	0	
	NOR													1	1	1	
	I/C													4	4	2	
	MAJ													2	2	1	
	TS													0	2	2	

Instructions:

1. Check the applicant level and enter the operating test number and Form ES-D-1 event numbers for each event type; TS are not applicable for RO applicants. ROs must serve in both the “at-the-controls (ATC)” and “balance-of-plant (BOP)” positions; Instant SROs must serve in both the SRO and the ATC positions, including at least two instrument or component (I/C) malfunctions and one major transient, in the ATC position. If an Instant SRO *additionally* serves in the BOP position, one I/C malfunction can be credited toward the two I/C malfunctions required for the ATC position.
2. Reactivity manipulations may be conducted under normal or *controlled* abnormal conditions (refer to Section D.5.d) but must be significant per Section C.2.a of Appendix D. (\*) Reactivity and normal evolutions may be replaced with additional instrument or component malfunctions on a 1-for-1 basis.
3. Whenever practical, both instrument and component malfunctions should be included; only those that require verifiable actions that provide insight to the applicant’s competence count toward the minimum requirements specified for the applicant’s license level in the right-hand columns.