

Project Name: Clinch River SMR Project Number: 6468-13-1072


Tested By: Mike Hamilton | M | |
Test Date: 1/27/2014 | 1/31 | 1/4 |
Reviewed By: Allen Cottingham | MAC |
Review Date: 1/30/2014 | (-30-14)


Sample No.: L3-5 BH Boring No.: MP-105 Run. No.: N/A Sample Depth (ft): 82.7-83.3

Page 2 of 2

Specimen Prior to Testing ("MP-105 L3-5-BH before test.jpg"):

Specimen After Testing ("MP-105 L3-5-BH after test.jpg"):





Comments:	
	i



Project Name: Clinch River SMR

Sample No.: L3-7 BH Boring No.: MP-105

Project Number: 6468-13-1072

Run. No.: N/A Sample Depth (ft): 138.1-138.9


Tested By: Mike Hamilton Test Date: 1/27/2014

Reviewed By: Allen Cottingham

Review Date: 1/30/2014

Page 1 of 2

Rock Type	(See boring log)
Moisture Condition	Laboratory Air-Dry
Specimen Diameter, (in)	1.77
Specimen Length, (in)	4.16
Length/Diameter Ratio	2.4
Specimen Conforms with Dimensional Requirements?	No <sup>(1)</sup>
As-Tested Unit Weight, (pcf)	-168.9-169 /cz 8/6/1
Loading Rate (lb/sec)	90
Test Duration to Failure, (min)	4
Uniaxial Compressive Strength, (psi)	6,800
Type of Break	Shear
Young's Modulus, (psi)	8,230,000
Poisson's Ratio	0.19



#### Comments:

Young's Modulus and Poisson's Ratio determined using linear least-squares of stress-strain data from 40% to 60% of the uniaxial compressive strength (data points used are indicated on the figure above).

Axial Strain is negative; Lateral Strain is positive. Load direction with respect to lithology: Vertical

(1) Specimen did not meet Side Strightness and End Flatness requirements of ASTM D4543-08. Authorization to proceed with test received from John Damm.




Project Name: Clinch River SMR Project Number: 6468-13-1072


 Sample No.: L3-7 BH
Boring No.: MP-105
Run. No.: N/A
Sample Depth (ft): 138.1-138.9

Page 2 of 2

Specimen Prior to Testing ("MP-105 L3-7-BH before test.jpg"):

Specimen After Testing ("MP-105 L3-7-BH after test.jpg"):





Comments.



Project Name: Clinch River SMR

Project Number: 6468-13-1072

Sample No.: L3-9 BH

Boring No.: MP-105

Run. No.: N/A


Tested By: Mike Hamilton

Test Date: 1/27/2014 1/31/14 Sample Depth (ft): 186.6-187.2

Reviewed By: Allen Cottingham Review Date: 1/30/2014 1-31-14

Page 1 of 2

Rock Type	(See boring log)
Moisture Condition	Laboratory Air-Dry
Specimen Diameter, (in)	1.77
Specimen Length, (in)	3.85
Length/Diameter Ratio	2.2
Specimen Conforms with Dimensional Requirements?	No <sup>(1)</sup>
As-Tested Unit Weight, (pcf)	166.4_166 H1
Loading Rate (lb/sec)	90
Test Duration to Failure, (min)	7
Uniaxial Compressive Strength, (psi)	13,100
Type of Break	Shear
Young's Modulus, (psi)	9,880,000
Poisson's Ratio	0.25



#### Comments:

Young's Modulus and Poisson's Ratio determined using linear least-squares of stress-strain data from 40% to 60% of the uniaxial compressive strength (data points used are indicated on the figure above)

Axial Strain is negative; Lateral Strain is positive. Load direction with respect to lithology: Vertical (1) Specimen did not meet End Flatness requirements of ASTM D4543-08. Authorization to proceed with test received from John Damm.



Project Name: Clinch River SMR Project Number: 6468-13-1072

Tested By: Mike Hamilton MH Test Date: 1/27/2014 1/31 H4
Reviewed By: Allen Cottingham MAC No. 1/30 1/4
Review Date: 1/30/2014 1/30 1/4


Sample No.: L3-9 BH Boring No.: MP-105 Run. No.: N/A Sample Depth (ft): 186.6-187.2

Page 2 of 2

Specimen Prior to Testing ("MP-105 L3-9-BH before test.jpg"):

Specimen After Testing ("MP-105 L3-9-BH after test.jpg"):





Comments.	



Project Name: Clinch River SMR Project Number: 6468-13-1072

Sample No.: L3-19 BH Boring No.: MP-111

Run. No.: N/A

Tested By: Mike Hamilton

Sample Depth (ft): 118.9-119.5


Test Date: 1/26/2014

Reviewed By: Allen Cottingham

Review Date: 1/30/2014

Page 1 of 2

Rock Type	(See boring log)	
Moisture Condition	Laboratory Air-Dry	
Specimen Diameter, (in)	2.39	
Specimen Length, (in)	5.47	
Length/Diameter Ratio	2.3	
Specimen Conforms with Dimensional Requirements?	No <sup>(1)</sup>	
As-Tested Unit Weight, (pcf)	-167.4 167 9CL	3/
Loading Rate (lb/sec)	160	
Test Duration to Failure, (min)	4.7	
Uniaxial Compressive Strength, (psi)	5,690	
Type of Break	Shear	
Young's Modulus, (psi)	6,240,000	
Poisson's Ratio	0.19	



#### Comments:

Young's Modulus and Poisson's Ratio determined using linear least-squares of stress-strain data from 40% to 60% of the uniaxial compressive strength (data points used are indicated on the figure above).

Axial Strain is negative; Lateral Strain is positive. Load direction with respect to lithology: Vertical

(1) Specimen did not meet Side Straightness, End Perpendicularity, End Flatness and End Parallelism requirements of ASTM D4543-08. Authorization to proceed with test received from John Damm.




Project Name: Clinch River SMR Project Number: 6468-13-1072

Tested By: Mike Hamilton M.H.
Test Date: 1/26/2014 1/31/14
Reviewed By: Allen Cottingham
Review Date: 1/30/2014 1-30-


Sample No.: L3-19 BH Boring No.: MP-111 Run. No.: N/A Sample Depth (ft): 118.9-119.5

Page 2 of 2

Specimen Prior to Testing ("MP-111 L3-19 BH before test.jpg"):



Specimen After Testing ("MP-111 L3-19 BH after test.jpg"):



C	O	1	Υ	1	r	Υ	1	e	r	١	t	S	×



Project Name: Clinch River SMR Project Number: 6468-13-1072 Sample No.: L3-24 BH

Boring No.: MP-115

Run. No.: N/A

Sample Depth (ft): 69.4-70.6

Tested By: Mike Hamilton

Test Date: 1/26/2014 1/3


131/14

Reviewed By: Allen Cottingham

Review Date: 1/30/2014 1.31-1

Page 1 of 2

Rock Type	(See boring log)
Moisture Condition	Laboratory Air-Dry
Specimen Diameter, (in)	2.40
Specimen Length, (in)	5.33
Length/Diameter Ratio	2.2
Specimen Conforms with Dimensional Requirements?	No <sup>(1)</sup>
As-Tested Unit Weight, (pcf)	167.9-168 for
Loading Rate (lb/sec)	160
Test Duration to Failure, (min)	3.3
Uniaxial Compressive Strength, (psi)	4,210
Type of Break	Shear
Young's Modulus, (psi)	5,270,000
Poisson's Ratio	0.18



#### Comments:

Young's Modulus and Poisson's Ratio determined using linear least-squares of stress-strain data from 40% to 60% of the uniaxial compressive strength (data points used are indicated on the figure above).

Axial Strain is negative; Lateral Strain is positive. Load direction with respect to lithology: Vertical

(1) Specimen did not meet End Flatness requirements of ASTM D4543-08. Authorization to

proceed with test received from John Damm.



Project Name: Clinch River SMR Project Number: 6468-13-1072


Tested By: Mike Hamilton | MH |
Test Date: 1/26/2014 | 1/31/14 |
Reviewed By: Allen Cottingham | NAC |
Review Date: 1/30/2014 | 1-30-14


Sample No.: L3-24 BH Boring No.: MP-115 Run. No.: N/A Sample Depth (ft): 69.4-70.6

Page 2 of 2

Specimen Prior to Testing ("MP-115 L3-24 BH before test.jpg"):

Specimen After Testing ("MP-115 L3-24 BH after test.jpg"):





Comments:	