

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9316	6	71-9316	USA/9316/B(U)-96	1 OF	7

2. PREAMBLE

- a. This certificate is issued to certify that the package (packaging and contents) described in Item 5 below meets the applicable safety standards set forth in Title 10, Code of Federal Regulations, Part 71, "Packaging and Transportation of Radioactive Material."
- b. This certificate does not relieve the consignor from compliance with any requirement of the regulations of the U.S. Department of Transportation or other applicable regulatory agencies, including the government of any country through or into which the package will be transported.

3. THIS CERTIFICATE IS ISSUED ON THE BASIS OF A SAFETY ANALYSIS REPORT OF THE PACKAGE DESIGN OR APPLICATION

- |  |  |
|--|--|
| a. ISSUED TO ( <i>Name and Address</i> )<br>Alpha-Omega Services, Inc.<br>9156 Rose Street<br>P.O. Box 789<br>Bellflower, CA 90706 | b. TITLE AND IDENTIFICATION OF REPORT OR APPLICATION<br>AOS application, Revision H-1, dated March 11, 2016,<br>as supplemented by Revision H-2 dated June 27, 2016. |
|--|--|

4. CONDITIONS

This certificate is conditional upon fulfilling the requirements of 10 CFR Part 71, as applicable, and the conditions specified below.

5.

(a) Packaging

(1) Model Nos.: AOS-025A, AOS-050A, AOS-100A, AOS-100B, and AOS-100A-S

(2) Description

A cylindrical stainless steel packaging, designed to transport Type B quantities of encapsulated solid materials or solid metals meeting Normal or Special Form criteria. The packaging is available in three model sizes – AOS-025, AOS-050, and AOS-100. Tungsten alloy is used as shielding material in model numbers with the suffix A, while carbon steel is the shielding material for model numbers with the suffix B. The Model No. AOS-100A-S has a double-ended opening configuration to be either loaded or unloaded from either end of the package. All models use a double O-ring arrangement seal in the lid joint.

The packaging includes an outer shell, a cavity, a shielding cylinder and shielding plugs, a bottom plate, a lid and lid plug. The outer shell and the cavity cylinder interlock to encase the shielding cylinder, made of either tungsten or carbon steel. A weldment attaches the upper portion of the cavity to its lower portion encasing the shielding. At the cavity's closed end, the shielding plug is encased between the cavity bottom wall and the packaging bottom plate. The shielding plug encased on the lid plug is of the same size and material (tungsten or carbon steel) as the one encased at the bottom of the packaging. The lid consists of a flat disk, with recessed areas concentric with the bolt holes on the top surface, to protect the bolts from impact loads.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGE
	9316	6	71-9316	USA/9316/B(U)-96	2	OF 7

5.(a)(2) Description (Continued)

The packaging may use either elastomeric or metallic lid seals: the Model Nos. AOS-025A and AOS-050A elastomeric seal has two O-rings and one flat metal retainer ring, while the Model No. AOS-100 has two O-rings and two SS300 series flat retainer rings. The metallic seal for all models is a double "C" cross section seal.

The packaging may require the use of a liner, axial shielding plates, and/or cavity spacer plates, depending on the model, for shipment of some contents, as stated in Tables 3 and 4 of this certificate. Additional packaging components include lid bolts and port plugs with their threaded pipe plugs, O-ring seals, port plug covers, and a pair of trunnions with their attachment bolts.

The impact limiters consist of a thin-walled stainless steel cylindrical shell, filled with polyurethane foam, with a dish head at one end and a flat disk at the other end. At the dish-head end, another recess is provided to reduce the area available for impact during a head-on drop event. Twelve (12) squared ribs are attached to the inner wall of the cylindrical recess section of the flat disk end. Eight (8) of these ribs extend beyond the flat disk plate and are used as turnbuckle attachment points. The turnbuckles join the impact limiters and partially enclose the packaging. For the Model No. AOS-025 package, the turnbuckles are replaced with "J" hooks. The package is transported in the upright position, using a shipping cage and a pallet. The Model Nos. AOS-50 and AOS-100 may include a lifting bar with the shipping cage; the lifting points are disabled during transport when the shipping cage lifting bar is included.

The maximum weights of the package shall not exceed the values listed in Table 1 below:

Table 1: Package Dimensions and Weights

Model	Width in a transport configuration (in.)	Height in a transport configuration (in.)	Packaging OD (in.)	Packaging Height (in.)	Cavity OD (in.)	Cavity Height (in.)	Maximum Package Weight (lbs.)
AOS-025A	18.00	21.38	7.00	9.00	1.62	5.00	220
AOS-050A	35.75	38.63 <sup>a</sup>	14.00	18.00	3.25	10.00	1,500
AOS-100A	61.02	75.40 <sup>a</sup>	28.00	36.00	6.50	20.00	12,500
AOS-100B	61.02	75.40 <sup>a</sup>	28.00	36.00	6.50	20.00	11,000
AOS-100A-S	61.02	75.40 <sup>a</sup>	28.00	36.00	6.50	20.00	12,500

a: the height specified in a transport configuration includes the optional lifting bar on the shipping cage.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9316	6	71-9316	USA/9316/B(U)-96	3 OF	7

5(a)(3) Drawings

The packaging is constructed and assembled in accordance with the following drawings:

Table 2: Packaging Drawings

Model	Assembly	Rev	Impact Limiter	Rev	Packaging	Rev	Liner/Axial Shielding Plates	Rev	Cavity Spacer Plates	Rev
AOS-025A	166D8142	I	105E9722	I	166D8143	H	183C8485	H	-	-
AOS-050A	105E9718	I	166D8138	I	166D8137	H	183C8519	A	-	-
AOS-100A	105E9711	I	105E9713	J	105E9712 G001	J	183C8491	I	183C8518	A
AOS-100B	105E9711	I	105E9713	J	105E9712 G002	J	-	-	-	-
AOS-100A-S	105E9711	I	105E9713	J	105E9719	J	183C8491	I	183C8518	A

5.(b) Contents

(1) Type and form of material

Activation product radioactive materials as Normal or Special Form. Special Form materials shall have a current certificate. Normal Form materials shall be enclosed in an inner container. The inner container is considered to be a "shoring device."

Any material with a melting point less than 900°F shall be in Special Form.

(2) Maximum quantity of material per package

- (i) Maximum decay heat: 10 watts for Model No. AOS-025A; 100 watts for Model No. AOS-050A; 400 watts for Model Nos. AOS-100A, AOS-100A-S, and AOS-100B.
- (ii) Maximum weight of contents: 10 lbs for Model No. AOS-025A; 60 lbs. for Model No. AOS-050A; 500 lbs. for Model Nos. AOS-100A, AOS-100A-S, and AOS-100B. Maximum weight includes any shoring devices and any additional shielding plates.
- (iii) Fissile materials and irradiated fissile materials containing fission products are prohibited. Free-standing liquid is not authorized.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGE
9316	6	71-9316	USA/9316/B(U)-96	4	OF 7

Table 3- Activity Limits All Isotopes except Ir-192 and Ir-194 (TBq)

Isotope	Decay Heat Ci/Watt	AOS-025	AOS-050	AOS-100A AOS-100A-S	AOS-100B
Co-60	64.5	4.92 E-03	2.78 E-02	10.1	0.403
Co-60-B	64.5	-	-	30.5	-
Co-60-C <sup>(1)</sup>	64.5	-	-	748	-
Cs-137	200	0.370	0.713	1320	21.5
Hf-181	231	-	3.41	3420	162
Zr/Nb-95	61.7	-	0.107	134	2.70
Ho-166	233	0.487	2.81	-	-
Yb-169	392	145	349	-	-
Shipping Configuration		Use of Liner Required. Drawing 183C8485 Rev. H	No additional shielding required	Co-60-B quantities require axial shielding plates per drawing 183C8491, Rev. I.  Co-60-C quantities require both axial shielding plates and cavity spacer plates per drawing 183C8491, Rev. I and 183C8518, Rev. A.	No additional shielding required

(1): For Co-60-C quantities, the maximum allowable specific activity is 350 Ci/g.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1. a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
9316	6	71-9316	USA/9316/B(U)-96	5 OF	7

Table 4 – Activity Limits for Ir-192 and Ir-194 (TBq)

Model	Decay Heat Ci/Watt	Ir-192 limit (TBq)	Ir-194 impurity limit (TBq)	Shipping Configuration
AOS-025A	0.44	2.62	0.0185	Use of Liner Required. Drawing 183C8485 Rev. H
	0.40	2.33	0.0740	
	0.37	2.10	0.1110	
AOS-050A	6.90	41.32	0.37	Use of Axial Shielding Plates Required. Drawing 183C8519, Rev. A
	6.71	39.84	0.74	
	6.33	36.88	1.48	
	5.94	33.92	2.22	
	5.56	30.96	2.96	
AOS-100A	400	2,286.37	148.00	No Additional Shielding Required
	400	2,094.42	370.00	
AOS-100B	15.33	89.31	3.70	No Additional Shielding Required.
	13.85	76.22	8.51	

6. In addition to the requirements of Subpart G of 10 CFR Part 71:
- (a) The package must be prepared for shipment and operated in accordance with the Operating Procedures of Chapter No. 7 of the application, and
  - (b) Each packaging must meet the Acceptance Tests and Maintenance Program of Chapter No. 8 of the application.
7. For transport by air, quantities are limited to the lesser of Tables 3 or 4 of this certificate or 3,000 A<sub>2</sub>.
8. For contents meeting Normal Form requirements, the package must be leak-tested to 10<sup>-7</sup> std cm<sup>3</sup>/sec prior to the first use of the package, and prior to each subsequent use.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGE
	9316	6	71-9316	USA/9316/B(U)-96	6 OF	7

9. When contents are loaded under water, or if water is introduced in the cavity of the package, the package must be vacuum dried prior to shipment and the cavity of the package filled with helium for such shipments.
10. The sealing surfaces of the package must be inspected. The metallic seal shall be replaced prior to each shipment. The elastomeric seal can be used only for shipment of Special Form material.
11. Shoring must be placed between the inner container and the package cavity's walls to secure and immobilize the containers, and prevent both radial and axial movements during normal conditions of transport. Shoring devices must be comprised of materials compatible with the radioactive contents and the cask cavity material. All shoring materials within the cavity must have a melting point greater than (i) 600°F for Co-60 in metallic form and Cs-137 in the form of cesium chloride and (ii) 900°F for all other contents.
12. Torque values for the lid bolts and the connectors of the impact limiters must be as follows:

Model	Lid Bolt (ft-lb), lubricated	Impact limiter connector (ft-lb), lubricated
AOS-025A	35	10
AOS-050A	62.5	3
AOS-100A	500	70
AOS-100B	500	70
AOS-100A-S	500	70

13. The weight of the foam in each impact limiter must be measured and its average density calculated based on the known volume of foam fill.
14. The package authorized by this certificate is hereby approved for use under the general license provisions of 10 CFR 71.17.
15. The package is shipped by exclusive use for contents utilizing axial shielding and spacer plates.
16. Expiration date: July 31, 2021.

**CERTIFICATE OF COMPLIANCE  
FOR RADIOACTIVE MATERIAL PACKAGES**

1.	a. CERTIFICATE NUMBER	b. REVISION NUMBER	c. DOCKET NUMBER	d. PACKAGE IDENTIFICATION NUMBER	PAGE	PAGES
	9316	6	71-9316	USA/9316/B(U)-96	7 OF	7

REFERENCES

Radioactive Material Transport Packaging System Safety Analysis Report for Model AOS-025, AOS-050, and AOS-100 Transport Packages, Rev. H-1, dated March 11, 2016, as supplemented by Rev. H-2, dated June 27, 2016.

FOR THE U.S. NUCLEAR REGULATORY COMMISSION

/IRA/

John McKirgan, Chief  
Spent Fuel Licensing Branch  
Division of Spent Fuel Management  
Office of Nuclear Material Safety  
and Safeguards

Date: July 12, 2016

