



INDIANA AND MICHIGAN POWER
D. C. COOK NUCLEAR PLANT
UPDATED FINAL SAFETY ANALYSIS REPORT

Revision: 27.0
 Table: 14.1-1
 Page: 1 of 2

Unit 1 Design Power Capability Parameters Used in Non-LOCA Safety Analyses

Parameter	(MUR Power Uprate) ^{1,2}		(Reduced Temperature and Pressure) ^{1,2}		(Rerating) ²		(Return to RCS NOP/NOT) ¹	
	Case 1	Case 2	Case 3	Case 4	Case 5	Case 6	Case 7	Case 8
NSSS Power, MWt	3,327	3,327	3,262	3,262	3,425	3,425	3,327	3,327
Core Power, MWt	3,315	3,315	3,250	3,250	3,413	3,413	3,315	3,315
RCS Flow, gpm/loop	83,200	83,200	83,200	83,200	88,500	88,500	83,200	83,200
Minimum Measured Flow, gpm/loop	84775	84775	84775	84775	91600	91600	84,775	84,775
RCS Temperatures, °F								
Core Outlet	593.1	613.6	589.7	611.9	583.6	614.0	593.1	613.6
Vessel Outlet	588.2	609.1	586.8	609.1	580.7	611.2	588.2	609.1

¹ The non-LOCA analyses are based on a Thermal Design Flow (TDF) of 83,200 gpm / loop and a Minimum Measured Flow (MMF) of 84,775 gpm / loop. However, subsequent evaluations were performed to show that the following higher flows are also supported: 88,500 gpm / loop (TDF) and 90,725 gpm / loop (MMF).

² Cook Unit 1 is not licensed to operate at the rerated conditions specified by Cases 5 and 6 with 30% steam generator tube plugging (SGTP) levels. However, several events that were previously performed using these conditions were subsequently evaluated to support the 30% SGTP program. Hence, the rerated conditions are also specified in this table for completeness.



INDIANA AND MICHIGAN POWER
D. C. COOK NUCLEAR PLANT
UPDATED FINAL SAFETY ANALYSIS REPORT

Revision: 27.0
 Table: 14.1-1
 Page: 2 of 2

Unit 1 Design Power Capability Parameters Used in Non-LOCA Safety Analyses

Parameter	(MUR Power Uprate) ^{1,2}		(Reduced Temperature and Pressure) ^{1,2}		(Rerating) ²		(Return to RCS NOP/NOT) ¹	
	Case 1	Case 2	Case 3	Case 4	Case 5	Case 6	Case 7	Case 8
Core Average	557.6	579.5	555.8	579.4	549.7	581.8	557.6	579.5
Vessel Average	553.7	575.4	553.0	576.3	547.0	578.7	553.7	575.4
Vessel/Core Inlet	519.2	471.7	519.2	543.5	513.3	546.2	519.2	541.7
Steam Generator Outlet	518.9	541.5	518.9	543.2	513.1	546.0	518.9	541.5
Zero Load	547.0	547.0	547.0	547.0	547.0	547.0	547.0	547.0
RCS Pressure, psia	2,250 or 2,100	2,250 or 2,100	2,250 or 2,100	2,250 or 2,100	2,250 or 2,100	2,250 or 2,100	2,250	2,250
Steam Pressure, psia	618	765	595	749	603	820	618	765
Steam Flow (10 ⁶ lb/hr total)	14.44	14.50	14.12	14.17	14.98	15.07	14.44	14.50
Feedwater Temp., °F	437.4	437.4	434.8	434.8	442	442	437.4	437.4
SG Tube Plugging, %	30	30	30	30	10	10	30	30