



NOTES:  
 1. ALL EQUIPMENT LOCATED AS NOTED.  
 2. LOGIC DIAG LSK-33-2.  
 3. □ - DENOTES DW PENETRATION.

LIMIT SWITCH DEVELOPMENT		FUNCTION		
33	VALVE POSN	2CMS*SOV60B	2CMS*SOV63B	2CMS*SOV61B
	FULL OPEN			
	FULL CLOSE			
1	— —	RED LT	RED LT	RED LT
2	— —	GRN LT	GRN LT	GRN LT
3	— —	ESK-7SCI41	ESK-7SCI41	ESK-7SCI41
4	— —	SPARE	SPARE	SPARE

PRC APERTURE CARD

CS	DETAIL	ESK	SPARES	USED ON
IV-	"H5"	3B	1B, 2T	
IW-	"H5"	3B	1B, 2T	
IX-	"H5"	3B	1B, 2T	

NUCLEAR SAFETY RELATED  
 QA CAT I  
 AC ELEM DIAG-120VAC MISC CKT  
 CONTAINMENT ATMOSPHERE MONITORING  
 NINE MILE POINT NUCLEAR STATION-UNIT 2  
 NIAGARA MOHAWK POWER CORPORATION  
 STONE & WEBSTER ENGINEERING CORPORATION  
 12177-ESK-7CMS22

GE-NEED  
 GE-LS1TG

D