

ATTACHMENT A

NIAGARA MOHAWK POWER CORPORATION

LICENSE NO. DPR-63

DOCKET NO. 50-220

Proposed Changes to Technical Specifications (Appendix A)

Existing page 47 will be replaced with the attached revised page. This page has been retyped in its entirety with marginal markings to indicate changes to the text.



LIMITING CONDITION FOR OPERATION

3.1.3 EMERGENCY COOLING SYSTEM

Applicability:

Applies to the operating status of the emergency cooling system.

Objective:

To assure the capability of the emergency cooling system to cool the reactor coolant in the event the normal reactor heat sink is not available.

Specification:

- a. During power operating conditions and whenever the reactor coolant temperature is greater than 212°F except for hydrostatic testing with the reactor not critical, both emergency cooling systems shall be operable except as specified in 3.1.3.b and c.
- b. During the remainder of Cycle 8 with one emergency cooling system inoperable, Specification 3.1.3a shall be considered fulfilled, provided the additional surveillance required in 4.1.3.f is performed.
- c. During Cycle 9 and subsequent cycles, if one emergency cooling system becomes inoperable, Specification 3.1.3.a shall be considered fulfilled, provided that the inoperable system is returned to an operable condition within 7 days and the additional surveillance required in 4.1.3.f is performed.

SURVEILLANCE REQUIREMENT

4.1.3 EMERGENCY COOLING SYSTEM

Applicability:

Applies to periodic testing requirements for the emergency cooling system.

Objective:

To assure the capability of the emergency cooling system for cooling of the reactor coolant.

Specification:

The emergency cooling system surveillance shall be performed as indicated below:

- a. At least once every five years -  
The system heat removal capability shall be determined.
- b. At least once daily -  
The shell side water level and makeup tank water level shall be checked.
- c. At least once per month -  
The makeup tank level control valve shall be manually opened and closed.



10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

10-10-10

ATTACHMENT B

NIAGARA MOHAWK POWER CORPORATION

LICENSE DPR-63

DOCKET NO. 50-220

Supporting Information

Hydrostatic test temperatures and pressures are governed by the requirements of Technical Specification 3.2.2. The pressure temperature limits set forth therein are periodically revised based on measured nil-ductility temperature shifts of irradiated vessel material samples. Recent revisions to these pressure/temperature limits will result in minimum temperatures for pressurization in excess of 212°F. The Emergency Cooling System is normally an integral part of the hydrostatic test performed at Nine Mile Point Unit 1. During the test the Emergency Cooling System steam supply piping and emergency condenser tube bundles are filled with water. In this condition, the Emergency Cooling System is not available to perform its intended function. Therefore, the requirements for Emergency Cooling System operability when the reactor coolant is greater than 212°F is requested to be modified to exempt this requirement during hydrostatic testing with the reactor not critical.

10CFR50.91 requires that at the time a licensee requests an amendment, it must provide to the Commission its analysis, using the standards in Section 50.92, about the issue of no significant hazards consideration. Therefore, in accordance with 10CFR50.91 and 10CFR50.92, the following analysis has been performed:


The proposed amendment in accordance with the operation of Nine Mile Point Unit 1 will not involve a significant increase in the probability or consequences of an accident previously evaluated.

The Emergency Cooling System is a standby high pressure system designed to act as a redundant backup to the main station condenser for receiving reactor core decay heat following reactor vessel isolation and scram.

In addition, for small line breaks, the Emergency Cooling System assists the Automatic Depressurization System (ADS) in depressurizing the reactor vessel.

The Emergency Cooling System is not intended to mitigate the affects of initial pressure peaks resulting from various transients such as turbine trip, or main steam line isolation valve closure, but rather longer term decay heat removal.

The Emergency Cooling System consists of two independent loops each designed to remove decay heat at a rate of approximately three percent of maximum reactor steam flow. This capacity is sufficient to handle the decay heat production at 100 seconds following SCRAM. Each loop consists of a 12-inch steam supply header, two parallel condensers, a 10-inch condensate return line, two steam supply isolation valves and one condensate return isolation valve, separate shell steam vents and separate instrumentation and control.



• • • • •

.

.

.

.

.

.

.

.

.

.

.

ATTACHMENT B (cont'd)

The Emergency Cooling System is designed such that operation is maintained by natural circulation. Steam flows from the reactor vessel to the condensers where it is condensed. The condensate returns by gravity to the suction side of a reactor recirculation loop where it is returned to the reactor vessel.

The configuration of Nine Mile Point Unit 1 for the hydrostatic test conditions differs from normal operation. Control rods are fully inserted and water level is outside its normal band. Pressurization is controlled utilizing the control rod drive system and/or hydrostatic test pump while temperature changes are affected utilizing the reactor recirculation system and/or other supplemental heat sources. Also, the reactor coolant system, with the exception of the Emergency Cooling System, is isolated. In this configuration, the capability of the Emergency Condenser System to remove decay heat following reactor isolation or to assist in reactor depressurization for small line break is not required.

Therefore, the proposed amendment will not invoke a significant increase in the probability of consequences of an accident previously evaluated.

The proposed amendment in accordance with the operation of Nine Mile Point Unit 1 will not create the possibility of a new or different kind of accident from any accident previously evaluated.

The proposed amendment eliminates the requirement for Emergency Condenser System operability with reactor coolant temperature greater than 212°F during hydrostatic testing with the reactor not critical. The Emergency Cooling System is normally included in hydrostatic testing of the reactor coolant system. With its steam supply lines full of water, the system is not available nor necessary to perform its designed function. A break in the Emergency Condenser System under hydrostatic conditions is enveloped by a similar break under normal operating conditions. Also, transients, which operation of the Emergency Cooling System would mitigate, are not feasible to occur due to the plant configuration existing during hydrostatic testing. The proposed change will not create the possibility of a new or different kind of accident from any accident previously evaluated.

The proposed amendment in accordance with the operation of Nine Mile Point Unit 1 will not involve a significant reduction in a margin of safety.

Implementation of the proposed change will have no effect on the availability of the Emergency Cooling System for those plant operating conditions where it is required to mitigate the effects of operational transients. Excluding the operability of the Emergency Cooling System during hydrostatic testing of the reactor coolant system with the reactor not critical will not result in a reduction in the margin of safety.

As determined by the analysis above, this proposed amendment involves no significant hazards consideration.



10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100

101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200

201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300