

UNITED STATES NUCLEAR REGULATORY COMMISSION

WASHINGTON, D.C. 20555

NIAGARA MOHAWK POWER CORPORATION

DOCKET NO. 50-220


NINE MILE POINT NUCLEAR STATION UNIT NO. 1

AMENDMENT TO FACILITY OPERATING LICENSE

Amendment No. 134 License No. DPR-63

- 1. The Nuclear Regulatory Commission (the Commission) has found that:
 - A. The application for amendment by Niagara Mohawk Power Corporation (the licensee) dated November 20, 1990, as superseded February 7, 1992, complies with the standards and requirements of the Atomic Energy Act of 1954, as amended (the Act) and the Commission's rules and regulations set forth in 10 CFR Chapter I;
 - B. The facility will operate in conformity with the application, the provisions of the Act, and the rules and regulations of the Commission;
 - C. There is reasonable assurance (i) that the activities authorized by this amendment can be conducted without endangering the health and safety of the public, and (ii) that such activities will be conducted in compliance with the Commission's regulations;
 - D. The issuance of this amendment will not be inimical to the common defense and security or to the health and safety of the public: and
 - E. The issuance of this amendment is in accordance with 10 CFR Part 51 of the Commission's regulations and all applicable requirements have been satisfied.
- 2. Accordingly, the license is amended by changes to the Technical Specifications as indicated in the attachment to this license amendment, and paragraph 2.C.(2) of Facility Operating License No. DPR-63 is hereby amended to read as follows:

9212150126 921203 PDR ADOCK 05000220



(2) Technical Specifications

The Technical Specifications contained in Appendices A and B, as revised through Amendment No. 134, are hereby incorporated in the license. The licensee shall operate the facility in accordance with the Technical Specifications.

3. This license amendment is effective as of the date of its issuance to be implemented within 30 days.

FOR THE NUCLEAR REGULATORY COMMISSION


Robert A. Capral
Robert A. Capra, Director

Project Directorate I-1
Division of Reactor Projects - I/II
Office of Nuclear Reactor Regulation

Attachment: Changes to the Technical Specifications

Date of Issuance: December 3, 1992


4



ATTACHMENT TO LICENSE AMENDMENT AMENDMENT NO. 134 TO FACILITY OPERATING LICENSE NO. DPR-63 DOCKET NO. 50-220

Revise Appendix A as follows:

Remove Page 146 Insert Page 146



LIMITING CONDITION FOR OPERATION

Table 3.3.4 "

PRIMARY CONTAINMENT ISOLATION VALVES LINES ENTERING FREE SPACE OF THE CONTAINMENT

Line or System	No. of Valves (Each Line)	Location Relative to Primary Containment	Normal Position	Hotive Power	Haximum Oper. Time (Sec)	Action on Initiating Signal	Initiating Signal (All Valves Have · · Remote Kanual Backup)
Drywell Yent & Purge			3				*
N ₂ Connection	1	Outside	Closed (a)	Air/D.C. Sol.	60	Close	Reactor water level low-low or high drywell pressure or high radiation at stack monitoring.
(One Line)	. 1	Outside	Closed (a)	A.C. Hotor	60	Close	
Air Connection (One Line)	} .	Outside Outside	Closed (a) Closed (a)	Air/D.C. Sol. A.C. Motor	60 60	Close Close	
Suppression Chamber Vent & Purge							
N ₂ Connection (One Line)	1	Outside Outside	Closed (a) Closed (a)	Air/D.C. Sol. A.C. Motor	60 60	Close Close	Reactor water level low-low or high drywell pressure or high radiation at stack monitoring.
Air Connection (One Line)	1	Outside Outside	Closed (a) Closed (a)	Air/D.C. Sol. A.C. Kotor	60 60	Close Close	
Ormell No Hakeup (One Line)	2	Outside	Closed (b)	Air/D.C. Sol.	60	Close	Reactor water level low-low or drywell high pressure
Suppression Chamber lig Hakeup (One Line)	2	Outside	Closed (b)	Air/D.C. Sol.	60	Close	Reactor water level low-low or drywell high pressure
Ore Line)	1	Inside Outside	Open Open	A.C. Motor Air/D.C. Sol.	60 60	Close Close	Reactor water level low-low or drywell high pressure
Floor Drain Line (One Line)	1	Inside Outside	Open Open	A.C. Hotor Air/D.C. Sol.	60 60	Close Close	
Suppression Charber Water Hakeup (One Line)	1	Outside Outside	Closed (b)	A.C. Hotor Sclf Act. Ck.	60 	-	Remote manual
Yacuum Relief Atmusphere to Pressure Suppression System (Three Lines)	1	Outside Outside	Closed	A.C. Hotor Self Act. Ck.	5	Open -	Negative pressure rel- ative to atmosphere
Reactor Cleanup System Relief Valve Discharg (One Line to Suppression Chamber)	<u>e</u> 2	Outside '	•	Self Act. Ck.	, ,	•,	<u>.</u>

