



GENERAL ELECTRIC 117C4739
 TITLE ELEM DIAGRAM POSITION INDICATOR PROBE
 FIRST MADE FOR CONTROL ROD DRIVE
 UNLESS OTHERWISE SPECIFIED USE THE FOLLOWING:
 APPLIED PRACTICES SURFACES TOLERANCES ON MACHINED DIMENSIONS
 FRACTIONS DECIMALS ANGLES
 ✓ + + +
 FCF: 922D223

FOR INFORMATION ONLY

NINE MILE PT. 2
 MPL B13
 PT/GRP
 DWG 117C4739

REV	DATE	BY	DESCRIPTION	PRINTS TO
1	12-72	W	PRE-PRODUCTION ISSUE	DE-C
2	11-17-70	W	PRODUCTION ISSUE	A B14
CHGD. ALL PIN NOS # 1 & 2 WAS 12 & 13 TO 15 WAS # 1 TO 11. PDL 11/13/70 WCS 11-13-70				

MADE BY: [Signature] AUG 25, 1970
 APPROVED: [Signature] 9-10-70
 APED SAN JOSE
 DWG NO. 117C4739
 5-CHK'D BY: [Signature] 8-28-70

STONE & WEBSTER ENGINEERING CORPORATION
 NINE MILE POINT NUCLEAR STATION - UNIT 2
 NIAGARA MOHAWK POWER CORPORATION
 J. O. 12177

INSTRUCTIONS TO SUPPLIER (E2)
 APPROVED AS DEFINED IN SPECIFICATION
 APPROVED AS REVISED SPECIFICATION
 RELEASED FOR FABRICATION
 RELEASED FOR MATERIAL PURCHASE

SUPPLIER TO RESUBMIT FOR REVIEW FOR RECORD NONE REQUIRED

NOTES:
 (E1) FOR INFORMATION ONLY RETURN TO SUPPLIER NOT REQUIRED

DESIGN ENGINEER'S DATE STAMP (D)
 OUT:
 INITIALS OF SELECTED REVIEWERS

RESPONSIBLE ENGINEER'S DATE STAMP (E2)
 NOTED OCT 16 1986

REMARKS (C) (LIMIT TO 24 CHARACTERS & BLANKS) (33-74)
 117C4739 REV 1

DATE MONTH DAY (1-12) YEAR (13-33) DWG TYPE (E1) MAX DAYS (32-33)
 11 01 16 86 C 21

FUNCTIONAL TITLE (E1) (LIMIT TO 4 CHARACTERS & BLANKS) (37-80)
 CONTROL ROD DRIVE POSITION INDICATOR PROBE

S & W FILE NO. (E1) (11-80) (21-24)
 117C4739

JOB ORDER NO. 12177 00

9305060174
 9305060174 D