



HIGHEST REF. DESIGNATION USED				
D5	TP7	S1	R35	U58
REF. DESIGNATION NOT USED				
U38,39,52,27				

\* FOR REF. ONLY  
 78 XX OUTPUT COMMON INPUT  
 79 XX OUTPUT INPUT COMMON

**NOTES:**  
 S1-7 OPEN, S1-8 CLOSED, 50HZ  
 S1-7 OPEN, S1-8 OPEN, 60HZ  
 S1-1 (USB) TO S1-5 (MSB) CHARGER CURRENT BALANCE  
 RESISTORS ARE 1/4W 5% & CAPS IN MFD, UNLESS OTHERWISE NOTED  
 GATE SIGNAL (FOUR LEG RECTIFIER)  
 DESIGNATION (SINGLE LEG RECTIFIER)  
 (DOUBLE LEG RECTIFIER)

5,35 1,31 6,36  
 +20V GND -20V  
 INTERLOCK  
 21  
 ANALOG COMMAND (FROM A2)

S/D A13A3 CHG DIGI MK2U		EA	
<b>EXIDE ELECTRONICS</b>			
S CN 60-012		SCHAEMATIK A13A3	
A CN 8321		CHG. SYNC & DIGITAL CONTROL	
REV. 1/19/82		REF. 101 072 372	
D 110 071 308			

9305070017  
 50-410  
 911070103  
 10/31/91  
 09 586 91