

23 pages withheld in their entirety
exemption 4

vapor pressure depressant in aerosol.

SALES SPECIFICATION	
APPEARANCE	Clear liquid free from suspended substance
CONTENT	96.0% min
SPECIFIC GRAVITY	1.318 - 1.324
FREE HALOGEN	Passes test
ACIDITY (HCl)	10ppm max
NONVOLATILES	10ppm max
HALOGENATED IMPURITY	1.0% max
DISTILLATION RANGE	72 - 88 C
WATER	100ppm max
COLOR (APHA)	15 max
TRANSPORTATION	
PACKING	260kgs in Drum
HAZARD CLASS	6.1
UN NO.	2831
OTHER INFORMATION	
European Hazard Symbols: XN N, Risk Phrases: 20/59, Safety Phrases: 24/25/59/61	

NFPA RATINGS	Health: 2; Flammability: 0 ; Reactivity: 1
FLASH POINT	practically not flammable
STABILITY	Stable under ordinary conditions
APPLICATIONS	
Hydrochlorofluorocarbon refrigerants; Fluorocarbon plastics and compounds; Solvents; Extaction of oil; Antiseptics;	
SALES SPECIFICATION	
APPEARANCE	clear volatile liquid
PURITY	99.9% min
COLOR, AHHA	10 max
ACIDITY	10ppm max
MOISTURE	100ppm max
TRANSPORTATION	
PACKING	250kgs in drum, Iso-Tank
HAZARD CLASS	6.1 (Packing group : III)
UN NO.	1888
OTHER INFORMATION	
European Hazard Symbols: XN, Risk Phrases: 22-38-40-48/20/22. Safety Phrases: 36/37	

<http://www.jtbaker.com/msds/englishhtml/T4914.htm>

MSDS Number: T4914 * * * * * Effective Date: 09/14/00 * * * * * Supercedes: 07/15/99



From: Mallinckrodt Baker, Inc.
222 Red School Lane
Phillipsburg, NJ 08865



24 Hour Emergency Telephone: 908-859-2151
CHEMTREC: 1-800-424-9300

National Response in Canada
CANUTEC: 613-996-6666

Outside U.S. And Canada
Chemtrec: 703-527-3887

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All non-emergency questions should be directed to Customer Service (1-800-582-2537) for assistance.

1,1,1-TRICHLOROETHANE

1. Product Identification

Synonyms: Methyl chloroform; trichloroethane; chloroetene

CAS No.: 71-55-6

Molecular Weight: 133.40

Chemical Formula: CH₃CCl₃

Product Codes: 5381, 9435, 9437, W509, W510

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Methyl Chloroform	71-55-6	96 - 100%	Yes
Dioxane	123-91-1	< 3%	Yes

1,2-Epoxybutane 106-88-7 < 0.5% Yes
Actual concentrations proprietary

3. Hazards Identification

Emergency Overview

WARNING! HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM, LIVER, KIDNEYS, AND CARDIOVASCULAR SYSTEM. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. POSSIBLE CANCER HAZARD. CONTAINS DIOXANE WHICH MAY CAUSE CANCER BASED ON ANIMAL DATA. Risk of cancer depends on duration and level of exposure.

J.T. Baker SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 3 - Severe (Cancer Causing)

Flammability Rating: 1 - Slight

Reactivity Rating: 1 - Slight

Contact Rating: 2 - Moderate

Lab Protective Equip: GOGGLES; LAB COAT; VENT HOOD; PROPER GLOVES

Storage Color Code: Blue (Health)

Potential Health Effects

Inhalation:

Inhalation of vapors will irritate the respiratory tract. Affects the central nervous system. Symptoms include headache, dizziness, weakness, nausea. Higher levels of exposure (> 5000 ppm) can cause irregular heart beat, kidney and liver damage, fall in blood pressure, unconsciousness and even death.

Ingestion:

Harmful if swallowed. Symptoms similar to inhalation will occur along with nausea, vomiting. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. If aspirated, may be rapidly

absorbed through the lungs and result in injury to other body systems.

Skin Contact:

Causes mild irritation and redness, especially on prolonged contact. Repeated contact may cause drying or flaking of the skin.

Eye Contact:

Liquids and vapors cause irritation. Symptoms include tearing, redness, stinging, swelling.

Chronic Exposure:

Prolonged or repeated skin contact may cause dermatitis. Chronic exposure may affect the kidneys and liver. Dioxane is a suspected human carcinogen based on animal data.

Aggravation of Pre-existing Conditions:

Personnel with CNS, kidney, liver or heart disease may be more susceptible to the effects of this substance. Use of alcoholic beverages may aggravate symptoms.

4. First Aid Measures

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion:

If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Call a physician.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Autoignition temperature: 500C (932F)

Flammable limits in air % by volume:

lcl: 7.0; ucl: 16.0

Vapors in containers can explode if subjected to high energy source.

11. Toxicological Information

Oral rat LD50: 9600 mg/kg; inhalation rat LC50: 18000 ppm/4H;
investigated as a mutagen, tumorigen, reproductive effector; irritation eye
rabbit, Standard Draize; 2mg/24H severe.

-----\Cancer Lists\-----

---NTP Carcinogen---

Ingredient	Known	Anticipated	IARC Category
Methyl Chloroform (71-55-6)	No	No	3
Dioxane (123-91-1)	No	Yes	2B
1,2-Epoxybutane (106-88-7)	No	No	2B

12. Ecological Information

Environmental Fate:

When released into the soil, this material is not expected to biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material is expected to quickly evaporate. When released to water, this material is expected to quickly evaporate. This material is not expected to significantly bioaccumulate. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition. When released to the atmosphere, this material has an average global half-life of 6.0 - 6.9 years. When released into the air, this material may adversely affect the ozone layer.

Environmental Toxicity:

This material is expected to be slightly toxic to aquatic life. The LC50/96-hour values for fish are between 10 and 100 mg/l.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local

disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: 1,1,1-TRICHLOROETHANE

Hazard Class: 6.1

UN/NA: UN2831

Packing Group: III

Information reported for product/size: 20L

15. Regulatory Information

-----\Chemical Inventory Status - Part 1\-----

Ingredient	TSCA	EC	Japan	Australia
Methyl Chloroform (71-55-6)	Yes	Yes	Yes	Yes
Dioxane (123-91-1)	Yes	Yes	Yes	Yes
1,2-Epoxybutane (106-88-7)	Yes	Yes	Yes	Yes

-----\Chemical Inventory Status - Part 2\-----

Ingredient	--Canada--			
	Korea	DSL	NDSL	Phil.
Methyl Chloroform (71-55-6)	Yes	Yes	No	Yes
Dioxane (123-91-1)	Yes	Yes	No	Yes
1,2-Epoxybutane (106-88-7)	Yes	Yes	No	Yes

-----\Federal, State & International Regulations - Part 1\-----

Ingredient	-SARA 302-		-----SARA 313-----	
	RQ	TPQ	List	Chemical Catg.

Keep in a tightly closed light-resistant container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Wear special protective equipment (Sec. 8) for maintenance break-in or where exposures may exceed established exposure levels. Wash hands, face, forearms and neck when exiting restricted areas. Shower, dispose of outer clothing, change to clean garments at the end of the day. Avoid cross-contamination of street clothes. Wash hands before eating and do not eat, drink, or smoke in workplace. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Chloroform odor threshold: 250 mg/m³. The odor threshold only serves as a warning of exposure; not smelling it does not mean you are not being exposed.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

Chloroform:

-OSHA Permissible Exposure Limit (PEL):

50 ppm (TWA) Ceiling

-ACGIH Threshold Limit Value (TLV):

10 ppm (TWA), Listed as A3 animal carcinogen

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, wear a supplied air, full-facepiece respirator, airlined hood, or full-facepiece self-contained breathing apparatus. Breathing air quality must meet the requirements of the OSHA respiratory protection standard (29CFR1910.134). This substance has poor warning properties.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Appearance:

Clear, colorless liquid.

Odor:

Characteristic ethereal odor.

Solubility:

0.8g/100g water @ 20C (68F).

Specific Gravity:

1.48 @ 20C/4C

pH:

No information found.

% Volatiles by volume @ 21C (70F):

100

Boiling Point:

62C (144F)

Melting Point:

-63.5C (-83F)

Vapor Density (Air=1):

4.1

Vapor Pressure (mm Hg):

160 @ 20C (68F)

Evaporation Rate (BuAc=1):

11.6

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage. pH decreases on prolonged exposure to light and air due to formation of HCl.

Hazardous Decomposition Products:

May produce carbon monoxide, carbon dioxide, hydrogen chloride and phosgene when heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Strong caustics and chemically active metals such as aluminum, magnesium powder, sodium, or potassium; acetone, fluorine, methanol, sodium methoxide, dinitrogen tetroxide, tert-butoxide, triisopropylphosphine.

Australian Hazchem Code: 2Z

Poison Schedule: S6

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: 2 Flammability: 0 Reactivity: 0

Label Hazard Warning:

DANGER! MAY BE FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY AFFECT CENTRAL NERVOUS SYSTEM, CARDIOVASCULAR SYSTEM, LIVER AND KIDNEYS. SUSPECT CANCER HAZARD. MAY CAUSE CANCER.

Risk of cancer depends on level and duration of exposure.

Label Precautions:

Do not breathe vapor.

Do not get in eyes, on skin, or on clothing.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Label First Aid:

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. In all cases get medical attention immediately.

Product Use:

Laboratory Reagent.

Revision Information:

MSDS Section(s) changed since last revision of document include: 8, 16.

Disclaimer:

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly

trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: Environmental Health & Safety
Phone Number: (314) 654-1600 (U.S.A.)