Docket No. 50-237

Mr. Thomas J. Kovach Nuclear Licensing Manager Commonwealth Edison Company-Suite 300 OPUS West III 1400 OPUS Place Downers Grove, Illinois 60515 DISTRIBUTION: Docket File
NRC & Local PDRs PDIII-2 r/f
J. Roe J. Zwolinski
J. Dyer C. Moore
B. Siegel OGC
B. Elliott ACRS(10)
PDIII-2 p/f B. Clayton RIII

Dear Mr. Kovach:

SUBJECT: DRESDEN NUCLEAR POWER STATION, UNIT 2, FRACTURE TOUGHNESS EVALUATION OF THE SHELL MATERIAL ON THE SECONDARY SIDE OF THE LOW PRESSURE COOLANT INJECTION HEAT EXCHANGERS (TAC NO. M77614)

In a letter dated February 4, 1991, the Commonwealth Edison Company provided a fracture toughness evaluation of the low pressure coolant injection heat exchangers (LPCI-HX) in Dresden Nuclear Power Station, Unit 2. Enclosed is our Safety Evaluation in which the staff has concluded that the A-212, Grade B material on the secondary side of the LPCI-HX has adequate fracture toughness. Our review of the fracture toughness of Dresden, Unit 2, materials as part of SEP Topic III-1 is completed.

Sincerely,

Original Signed By:

Byron L. Siegel, Project Manager Project Directorate III-2 Division of Reactor Projects - III/IV/V Office of Nuclear Reactor Regulation

Enclosure: Safety Evaluation

cc w/enclosure:
See next page

WE THE OFFICE COMP

	^				
OFC	LA PDI I I - 2	PM:PDIII-2	D:PDIII-2		1 4
NAME	CMOORE	BSIEGEL: ja	JDYER M		1
DATE	1/ 1/0/93	1 /14/93	1/19/93	1	

9301270256 930119 PDR ADOCK 05000237 PDR PDR



· wkali

DISTRIBUTION:

J. Roe

J. Dver

B. Siegel

B. Elliott

PDIII-2 p/f

NRC & Local PDRs

Docket File

PDIII-2 r/f

C. Moore

ACRS(10)

OGC

J. Zwolinski

B. Clayton RIII

Docket No. 50-237

Mr. Thomas J. Kovach Nuclear Licensing Manager Commonwealth Edison Company-Suite 300 OPUS West III 1400 OPUS Place

Downers Grove, Illinois 60515

Dear Mr. Kovach:

DRESDEN NUCLEAR POWER STATION, UNIT 2, FRACTURE TOUGHNESS EVALUATION SUBJECT:

OF THE SHELL MATERIAL ON THE SECONDARY SIDE OF THE LOW PRESSURE

COOLANT INJECTION HEAT EXCHANGERS (TAC NO. M77614)

In a letter dated February 4, 1991, the Commonwealth Edison Company provided a fracture toughness evaluation of the low pressure coolant injection heat exchangers (LPCI-HX) in Dresden Nuclear Power Station, Unit 2. Enclosed is our Safety Evaluation in which the staff has concluded that the A-212, Grade B material on the secondary side of the LPCI-HX has adequate fracture toughness. Our review of the fracture toughness of Dresden, Unit 2, materials as part of SEP Topic III-1 is completed.

Sincerely,

Original Signed By:

Byron L. Siegel, Project Manager Project Directorate III-2 Division of Reactor Projects - III/IV/V Office of Nuclear Reactor Regulation

Enclosure: Safety Evaluation

cc w/enclosure: See next page

OFC	IA PDIII-2	PM:PDIII-2	D:PDIII-2		1 .
NAME	; CMOORE	BSIEGEL: ja	JDYER M	!	1
DATE	1 10/93	1 /14/93	///4/93	<u> </u>	

Mr. Thomas J. Kovach Commonwealth Edison Company Dresden Nuclear Power Station Unit Nos. 2 and 3

cc:

Michael I. Miller, Esquire Sidley and Austin One First National Plaza Chicago, Illinois 60690

Mr. C. Schroeder Plant Manager Dresden Nuclear Power Station 6500 North Dresden Road Morris, Illinois 60450-9765

U. S. Nuclear Regulatory Commission Resident Inspectors Office Dresden Station 6500 North Dresden Road Morris, Illinois 60450-9766

Chairman
Board of Supervisors of
Grundy County
Grundy County Courthouse
Morris, Illinois 60450

Regional Administrator Nuclear Regulatory Commission, Region III 799 Roosevelt Road, Bldg. #4 Glen Ellyn, Illinois 60137

Illinois Department of Nuclear Safety Office of Nuclear Facility Safety 1035 Outer Park Drive Springfield, Illinois 62704

Robert Neumann Office of Public Counsel State of Illinois Center 100 W. Randolph Suite 11-300 Chicago, Illinois 60601